

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-025-02903
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No. B-1839
7. Lease Name or Unit Agreement Name EVGSAU 2738
8. Well Number 001
9. OGRID Number 217817
10. Pool name or Wildcat Vacuum GB/SA
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3946' GL

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-100) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator
ConocoPhillips Company

3. Address of Operator
P.O. Box 51810 Midland, TX 79710

4. Well Location
Unit Letter **D** : **660** feet from the **North** line and **660** feet from the **West** line
Section **27** Township **17-S** Range **35-E** NMPM County **Lea**

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3946' GL

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
CLOSED-LOOP SYSTEM ☐
OTHER: ☐

SUBSEQUENT

REMEDIAL WORK
COMMENCE DRILLING OPNS
CASING/CEMENT JOB

INT TO PA ☒
P&A NR
P&A R

OTHER:

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

--MIRU. ND WH, NU BOP. POOH w/ Prod Equip
--RIH WL Set CIBP @ 4,153'. Circ hole w/ MLF. Cap BP w/ 55sx cmt to 3,650'
--Spot 45sx cmt @ 3,100' - 2,700'. WOC-Tag
--Spot 30sx cmt @ 1,800' - 1,541'. WOC-Tag
--Spot 40sx cmt @ 324' to surface
--POOH. Fill wellbore. Verify cmt @ surface in all annuli

NOTIFY OCD 24 HOURS PRIOR TO BEGINNING
PLUGGING OPERATIONS

A closed-loop system will be used for all fluids from this wellbore and disposed of required by OCD Rule 19.15.17

Spud Date:

9/26/38

Rig Release Date:

11/4/38

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Greg Bryant TITLE P&A Tech - Basic Energy Services DATE 3/16/16

Type or print name Greg Bryant E-mail address: _____ PHONE: 432-563-3355

For State Use Only

APPROVED BY: Mahesh Patel TITLE Petroleum Engr. Specialist DATE 03/21/2016

Conditions of Approval (if any):

MAR 22 2016

WELLBORE SKETCH
ConocoPhillips Company - Lower 48 - Mid-Continent BU / Permian Operations

Date: March 14, 2016

RKB @ 3963'
DF @
GF @ 3946'

Subarea : Buckeye
Lease & Well No. : East Vacuum GB/SA Unit, Tract 2738 001
Legal Description : 660 FNL & 660 FWL, Sec. 27, T-17S, R-35E
County : Lea State : New Mexico
Field : Vacuum (Grayburg-San Andres)
Date Spudded : 9/26/1938 Rig Released: 11/4/1938
API Number : 30-025-02903
Status: Producing
Drilled as: State 5 #27 State Lease No. B-1839
OGRID No. 017643

Stimulation History:

Interval	Date	Type	Gals	Lbs. Sand	Max Press	ISIP	Max Rate	Down
4530-4654	11/6/1938	Dowell XX	3500					
4530-4654	10/11/1945	Dowell XX	5000					
	5/14/1951	Set CIBP @ 4270' w/ gravel to 4265' & cmt to 4250'						
	5/16/1951	DO to 4654'						
4253-4644	10/10/1951	Gel Acid	6000					
4555-4632	7/30/1952	XF26M38	3500					
4230-4644	12/7/1957	Crude Oil	20,000	10,000				
	7/28/1980	Perf 1640 w/ 4 JHPF & sqz'd w/ 550 sxs cmt						
	8/1/1980	CO to 4634'						
	10/27/1985	Perf 4448-4458, 4505-4530 & 4571-4589 w/ 1 SPF						
4448-4589	10/27/1985	15% NEFE	10,000					
4448-4589	4/5/2002	15% NEFE	4500					
4448-4589	8/2/2010	Xylene	1000					

17 1/2" Hole
TOC 9 5/8" @ 33'

13 3/8" 48# H-40 @ 274'
Cmt'd w/ 260 sxs, circ
TOC @ Surface

12 1/2" Hole
9 5/8" 33# H-40 @ 1591'
Cmt'd w/ 615 sxs, circ
TOC @ 33'

Perf 1640 w/ 4 JHPF & sqz'd w/ 550 sxs cmt

Top Salt @ 1750'

Base Salt @

8 3/4" Hole
7" 24# J-55 @ 4230'
Cmt'd w/ 330 sxs, Circ
TOC @ Surface

6 3/4" Hole
5 1/2" 15.5# J-55 @ 4253'
Cmt'd w/ 250 sxs, Circ 30 sxs
TOC @ Surface

6 3/4" Open Hole
4253-4654

4448-4458'

4505-4530'

4571-4589'

Formation Tops:

Rustler
Salado
Yates
Seven Rivers
Queen
Grayburg
San Andres
Glorieta

PBTD @ 4634'
TD @ 4654'

WELLBORE SKETCH
ConocoPhillips Company - Lower 48 - Mid-Continent BU / Permian Operations

Date: March 14, 2016

RKB @ 3963'
DF @
GF @ 3946'

Subarea : Buckeye
Lease & Well No. : East Vacuum GB/SA Unit, Tract 2738 001
Legal Description : 660 FNL & 660 FWL, Sec. 27, T-17S, R-35E
County : Lea State : New Mexico
Field : Vacuum (Grayburg-San Andres)
Date Spudded : 9/26/1938 Rig Released: 11/4/1938
API Number : 30-025-02903
Status: Producing
Drilled as: State 5 #27 State Lease No. B-1839
OGRID No. 017643

Stimulation History:

Interval	Date	Type	Gals	Lbs. Sand	Max Press	ISIP	Max Rate	Max Down
4530-4654	11/6/1938	Dowell XX	3500					
4530-4654	10/11/1945	Dowell XX	5000					
	5/14/1951	Set CIBP @ 4270' w/ gravel to 4265' & cmt to 4250'						
	5/16/1951	DO to 4654'						
4253-4644	10/10/1951	Gel Acid	6000					
4555-4632	7/30/1952	XF26M38	3500					
4230-4644	12/7/1957	Crude Oil	20,000	10,000				
	7/28/1980	Perf 1640 w/ 4 JHPF & sqz'd w/ 550 sxs cmt						
	8/1/1980	CO to 4634'						
	10/27/1985	Perf 4448-4458, 4505-4530 & 4571-4589 w/ 1 SPF						
4448-4589	10/27/1985	15% NEFE	10,000					
4448-4589	4/5/2002	15% NEFE	4500					
4448-4589	8/2/2010	Xylene	1000					

17 1/2" Hole

TOC 9 5/8" @ 33'

Spot 40sx cmt @ 324'-3'

13 3/8" 48# H-40 @ 274'

Cmt'd w/ 260 sxs, circ

TOC @ Surface

12 1/2" Hole

9 5/8" 33# H-40 @ 1591'

Cmt'd w/ 615 sxs, circ

TOC @ 33'

Spot 30sx cmt @ 1800'-1541' - Tag

Perf 1640 w/ 4 JHPF & sqz'd w/ 550 sxs cmt

Top Salt @ 1750'

Base Salt @

Spot 45sx cmt @ 3100'-2700' - Tag

8 3/4" Hole

7" 24# J-55 @ 4230'

Cmt'd w/ 330 sxs, Circ

TOC @ Surface

Set CIBP @ 4153' - 55sx cmt @ 4153'-3650'

6 3/4" Hole

5 1/2" 15.5# J-55 @ 4253'

Cmt'd w/ 250 sxs, Circ 30 sxs

TOC @ Surface

6 3/4" Open Hole

4253-4654

4448-4458'

4505-4530'

4571-4589'

Formation Tops:

Rustler
Salado
Yates
Seven Rivers
Queen
Grayburg
San Andres
Glorieta

PBTD @ 4634'
TD @ 4654'