

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.	30-025-20717	✓
5. Indicate Type of Lease	STATE ☒ FEE ☐	✓
6. State Oil & Gas Lease No.		
7. Lease Name or Unit Agreement Name	Vacuum Glorieta East Unit	✓
8. Well Number	9	✓
9. OGRID Number	217817	✓
10. Pool name or Wildcat	Vacuum Glorieta	
11. Elevation (Show whether DR, RKB, RT, GR, etc.)	3948' GL	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator
ConocoPhillips Company ✓

3. Address of Operator
P.O. Box 51810 Midland, TX 79710

4. Well Location
Unit Letter N: 330 feet from the South line and 1980 feet from the West line
Section 28 Township 17-S Range 35-E NMPM County Lea

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3948' GL

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT	
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☒	REMEDIAL WORK	INT TO PA ☒
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS.	P&A NR ☐
PULL OR ALTER CASING ☐	MULTIPLE COMPL ☐	CASING/CEMENT JOB	P&A R ☐
DOWNHOLE COMMINGLE ☐			
CLOSED-LOOP SYSTEM ☐			
OTHER: ☐		OTHER: ☐	

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

--MIRU. ND WH, NU BOP.
--RIH Tbg Tag BP @ 5,985'. Circ hole w/ MLF. Cap BP w/ 25sx cmt
--Spot 60sx cmt @ 4,417' - 3,642'. WOC-Tag
--Perf @ 3,050' - Sqz 60sx cmt to 2,670'. WOC-Tag
--Perf @ 1,638' - Sqz 40sx cmt to 1,500'. WOC-Tag
--Perf @ 300' - Circ 70sx cmt to surface
--POOH. Fill wellbore. Verify cmt @ surface in all annuli

NOTIFY OCD 24 HOURS PRIOR TO BEGINNING
PLUGGING OPERATIONS

A closed-loop system will be used for all fluids from this wellbore and disposed of required by OCD Rule 19.15.17

Spud Date:

5/11/64

Rig Release Date:

5/31/64

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE [Signature] TITLE P&A Tech - Basic Energy Services DATE 3/16/16

Type or print name Greg Bryant E-mail address: _____ PHONE: 432-563-3355

For State Use Only

APPROVED BY: [Signature] TITLE Petroleum Engr. Specialist DATE 03/21/2016

Conditions of Approval (if any):

MAR 22 2016

WELLBORE SKETCH
ConocoPhillips Company - Lower 48 - Mid-Continent BU / Permian Operations

Date: 2/22/2016

RKB @
 DF @ 3956'
 GL @ 3948'

Subarea : Buckeye
 Lease & Well No. : Vacuum Glorieta East Unit, Well 01-09
 Legal Description : 330 FSL & 1980 FWL, Sec. 28, T17S, R35E,
 County : Lea State : New Mexico
 Field : Vacuum Glorieta
 Date Spudded : 5/11/1964 Rig Released: 5/31/1964
 API Number : 30-025-20717
 Status: Drilled as State K #27 OGRID # 017643

Stimulation History:

Interval	Date	Type	Gals	Lbs. Sand	Max Press	ISIP	Max Rate	Max Down
	6/1/1964	Perf 6052-6062 w/ 1 SPF						
6052-6062	6/1/1964	15% NEA	500					
6052-6062	1/6/1969	15% NEA	5000					
	6/22/1976	Sqz 6052-6062 w/ 150 sxs cmt						
	6/24/1976	Perf 6082-6086, 6096-6104, 6114-6120						
6082-6120	6/24/1976	15% HCL	3500					
	9/7/1984	Perf 6035-6069 w/ 1 SPF						
6035-6069	9/7/1984	15% HCL	4100					
	2/16/2016	Set CIBP @ 5985'						

9 7/8" Hole

7-5/8" 24 H-40 @ 1587'
 Cmt'd w/ 600 sx, circ
 TOC @ Surface
 Top Salt @ 1588'

Base Salt @ 2720'

TOC 4 1/2" @ 3010' (TS)

CIBP @ 5985'

6035-6069'

Sqz'd 6052-6062 w/ 150 sxs cmt

6082-6086'

6096-6104'

6114-6120'

6 3/4" Hole
 4-1/2" 9.5 J-55 @ 6200'
 Cmt'd w/ 850 sx,
 TOC @ 3010' (TS)

Formation Tops:

Rustler	1550'
Base Salt	
Tansill	2723'
Yates	2814'
Seven Rivers	3044'
Queen	3692'
Grayburg	4021'
San Andres	4367'
Glorieta	5928'
Paddock	6031'

PBTD: 6181'
 TD: 6200'

WELLBORE SKETCH
ConocoPhillips Company - Lower 48 - Mid-Continent BU / Permian Operations


Date: 2/22/2016

RKB @
DF @ 3956'
GL @ 3948'

Subarea : Buckeye
Lease & Well No. : Vacuum Glorieta East Unit, Well 01-09
Legal Description : 330 FSL & 1980 FWL, Sec. 28, T17S, R35E,
County : Lea State : New Mexico
Field : Vacuum Glorieta
Date Spudded : 5/11/1964 Rig Released: 5/31/1964
API Number : 30-025-20717
Status:
Drilled as State K #27 OGRID # 017643

Stimulation History:

Interval	Date	Type	Gals	Lbs. Sand	Max Press	ISIP	Max Rate	Down
6052-6062	6/1/1964	Perf 6052-6062 w/ 1 SPF						
6052-6062	6/1/1964	15% NEA	500					
6052-6062	1/6/1969	15% NEA	5000					
	6/22/1976	Sqz 6052-6062 w/ 150 sxs cmt						
	6/24/1976	Perf 6082-6086, 6096-6104, 6114-6120						
6082-6120	6/24/1976	15% HCL	3500					
	9/7/1984	Perf 6035-6069 w/ 1 SPF						
6035-6069	9/7/1984	15% HCL	4100					
	2/16/2016	Set CIBP @ 5985'						



9 7/8" Hole

P&S 70sx cmt @ 300'-3'

7 5/8" 24 H-40 @ 1587'

Cmt'd w/ 600 sx, circ

TOC @ Surface

Top Salt @ 1588'

P&S 40sx cmt @ 1638'-1500' - Tag

Base Salt @ 2720'

P&S 60sx cmt @ 3050'-2670' - Tag

TOC 4 1/2" @ 3010' (TS)

Spot 60sx cmt @ 4417'-3642' - Tag

Spot 25sx cmt @ 5985'-5700'

CIBP @ 5985'

6035-6069'

Sqz'd 6052-6062 w/ 150 sxs cmt

6082-6086'

6096-6104'

6114-6120'

6 3/4" Hole

4-1/2" 9.5 J-55 @ 6200'

Cmt'd w/ 850 sx,

TOC @ 3010' (TS)

Formation Tops:

Rustler	1550'
Base Salt	
Tansill	2723'
Yates	2814'
Seven Rivers	3044'
Queen	3692'
Grayburg	4021'
San Andres	4367'
Glorieta	5928'
Paddock	6031'

PBTD: 6181'
TD: 6200'