

**R-111-POTASH**

OCD Hobbs  
**HOBBS OCD**

ATS-15-661

FORM APPROVED  
OMB No. 1004-0137  
Expires October 31, 2014

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**MAR 21 2016**

5. Lease Serial No. **Fee Lease E**  
NMNM077054, State LO66910002, BO148 20012

**APPLICATION FOR PERMIT TO DRILL OR REENTER**

**RECEIVED  
UNORTHODOX  
LOCATION**

6. If Indian, Allottee or Tribe Name

7. If Unit or CA Agreement, Name and No.

**<H>**

1a. Type of work:  DRILL  REENTER  
1b. Type of Well:  Oil Well  Gas Well  Other  Single Zone  Multiple Zone

8. Lease Name and Well No.  
Gay Nineties Federal Com #2H

**(317452)**

2. Name of Operator BC Operating, Inc. **(160825)**

9. APJ Well No.  
**30-025-47132**

3a. Address P.O. Box 50820  
Midland, Texas 79710

3b. Phone No. (include area code)  
432-684-9696

10. Field and Pool, or Exploratory  
Gem; Bone Spring **(27220)**

4. Location of Well (Report location clearly and in accordance with any State requirements.)  
At surface 1780' FNL & 342' FEL of Unit Letter 'H', Section 36, T-19S R-32E  
At proposed prod. zone 240' FSL & 510' FEL of Unit Letter 'P', Section 1, T-20S, R-32E

11. Sec., T. R. M. or Blk and Survey or Area  
Section 36, T-19S, R-32E  
Section 1, T-20S, R-32E

14. Distance in miles and direction from nearest town or post office\*  
30 miles East of Carlsbad

12. County or Parish  
Lea

13. State  
NM

15. Distance from proposed\* location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any)  
240'

16. No. of acres in lease  
Fee: 320  
State: 558.21  
**Fed: 798.8**  
Total: 1677.01

17. Spacing Unit dedicated to this well  
239.77

18. Distance from proposed location\* to nearest well, drilling, completed, applied for, on this lease, ft.  
376'

19. Proposed Depth  
18,132' MD / 9900 TVD

20. BLM/BIA Bond No. on file  
NM2572

21. Elevations (Show whether DF, KDB, RT, GL, etc.)  
3573' GL

22. Approximate date work will start\*  
01/01/2015

23. Estimated duration  
45 days

24. Attachments

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No.1, must be attached to this form:

- Well plat certified by a registered surveyor.
- A Drilling Plan.
- A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office).
- Bond to cover the operations unless covered by an existing bond on file (see Item 20 above).
- Operator certification
- Such other site specific information and/or plans as may be required by the BLM.

25. Signature **Pam Stevens**

Name (Printed/Typed)  
Pam Stevens

Date  
08/22/2014

Title  
Regulatory Analyst

Approved by (Signature) **/s/George MacDoneli**

Name (Printed/Typed)

Date **MAR 18 2016**

Title **FIELD MANAGER**

Office **CARLSBAD FIELD OFFICE**

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.  
Conditions of approval, if any, are attached.

**APPROVAL FOR TWO YEARS**

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Continued on page 2)

\*(Instructions on page 2)

**Kz**  
**03/22/16**

**Capitan Controlled Water Basin**

**Approval Subject to General Requirements & Special Stipulations Attached**

**SEE ATTACHED FOR  
CONDITIONS OF APPROVAL**


**MAR 22 2016**

## BC Operating, Inc. Gay Nineties Federal Com #2H

### Regarding Blowout Preventers

1. Drilling nipple will be constructed so it can be removed mechanically without the use of a welder. The minimum internal diameter will equal BOP bore.
2. Wear ring will be properly installed in head.
3. Blowout preventer and all associated fittings will be in operable condition to withstand a minimum 3000 psi working pressure.
4. All fittings will be flanged.
5. A full bore safety valve tested to a minimum 3000 psi working pressure with proper connection will be available on the rig floor at all times.
6. All choke lines will be anchored to prevent movement.
7. All BOP equipment will be equal to or larger in bore opening than the internal diameter of the last casing.
8. A Kelly cock will be maintained attached to Kelly.
9. Hand wheels and wrenches will be properly installed and tested for safe operation.
10. Hydraulic control for blowout preventer will be located as near in proximity to driller's controls as possible.
11. All BOP equipment will meet API standards and include a minimum 40 gallon accumulator having two independent means of power to initiate closure.

### 3M Choke Manifold Equipment





**BC Operating, Inc. Gay Nineties Federal Com #2H**

Must have table for contingency casing

	Y or N
Is casing new? If used, attach certification as required in Onshore Order #1	Y
Does casing meet API specifications? If no, attach casing specification sheet.	Y
Is premium or uncommon casing planned? If yes attach casing specification sheet.	N
Does the above casing design meet or exceed BLM's minimum standards? If not provide justification (loading assumptions, casing design criteria).	Y
Will the intermediate pipe be kept at a minimum 1/3 fluid filled to avoid approaching the collapse pressure rating of the casing?	Y
Is well located within Capitan Reef?	Y
If yes, does production casing cement tie back a minimum of 50' above the Reef?	Y
Is well within the designated 4 string boundary.	Y
Is well located in SOPA but not in R-111-P?	N
If yes, are the first 2 strings cemented to surface and 3 <sup>rd</sup> string cement tied back 500' into previous casing?	
Is well located in R-111-P and SOPA?	Y
If yes, are the first three strings cemented to surface?	Y
Is 2 <sup>nd</sup> string set 100' to 600' below the base of salt?	Y
Is well located in high Cave/Karst?	N
If yes, are there two strings cemented to surface?	
(For 2 string wells) If yes, is there a contingency casing if lost circulation occurs?	
Is well located in critical Cave/Karst?	N
If yes, are there three strings cemented to surface?	

**BC Operating, Inc. Gay Nineties Federal Com #2H**

**3. Cementing Program**

Casing	# Sks	Wt. lb/gal	Yld ft <sup>3</sup> /sack	H <sub>2</sub> O gal/sk	500# Comp. Strength (hours)	Slurry Description
Surf.	1620	13.7	1.66	8.7	10	Lead: Class C + 4.0% Bentonite + 1% CaCl <sub>2</sub> + 0.5% Cello-Flake
	680	14.8	1.329	6.4	8	Tail: Class C + 0.2% FLO-1 + 1% CaCl <sub>2</sub> + 0.1% TWR-2
Inter. 1 <i>See COA</i>	730	12.8	1.84	9.8	15	Lead: 35:65 C Blend + 6% Bentonite + 0.25% Cello-Flake + 0.2% FLO-1 + 5% sodium Chloride
	560	14.8	1.352	6.4	11	Tail: Class C + 0.1% MTR-150 + 0.1% TWR-2 + 1% CaCl <sub>2</sub>
Inter. 2	1100	12.8	1.84	9.8	15	Lead: 35:65 C Blend + 6% Bentonite + 0.25% Cello-Flake + 0.2% FLO-1 + 5% sodium Chloride
	590	14.8	1.352	8	11	Tail: Class C + 0.1% MTR-150 + 0.1% TWR-2 + 1% CaCl <sub>2</sub>
Prod.	890	11.8	2.31	12.84	24	Lead: 50:50 C Blend + 0.3% Cello-flake + 10% Bentonite + 5% PSE-2 + 0.3% CFR-13 + 0.2% CFL-20 + 0.65% MTR-150 + 0.15% TWR-2
	1390	12.6	1.93	10.46	11	Tail: THS 12.6 + 0.6% CFL-6 + 0.2% MTR-150 + 0.1% TWR-2 + 0.3% CFR-13

Optional DV tool depth(s) will be adjusted based on hole conditions and cement volumes will be adjusted proportionally. If used, DV tool will be set a minimum of 50 feet below previous casing and a minimum of 200 feet above current shoe. Lab reports with the 500 psi compressive strength time for the cement will be onsite for review.

Casing String	TOC	% Excess
Surface	0'	100%
1 <sup>st</sup> Intermediate	0'	50%
2 <sup>nd</sup> Intermediate	0'	100%
Production	2275'	30%

Include Pilot Hole Cementing specs:

**Pilot hole depth 10000**

**KOP 9184**

*See COA*

Plug top	Plug Bottom	% Excess	No. Sacks	Wt. lb/gal	Yld ft <sup>3</sup> /sack	Water gal/sk	Slurry Description and Cement Type
9184	9684	10	205	16.4	1.06	4.3	Class H
9800	10000	10	85	16.4	1.06	4.3	Class H

**BC Operating, Inc. Gay Nineties Federal Com #2H**

**4. Pressure Control Equipment**

A variance is requested for the use of a diverter on the surface casing. See attached for schematic.
--

See COA

BOP installed and tested before drilling which hole?	Size?	Min. Required WP	Type	✓	Tested to:
16" <del>17-1/2"</del>	20"	2M	Annular	x	50% of working pressure  2M
			Blind Ram		
			Pipe Ram		
			Double Ram		
			Other*		
12-1/4"	13-5/8"	2M	Annular	x	50% of working pressure must test BOP to 2,000 psi  2M
			Blind Ram		
			Pipe Ram		
			Double Ram		
			Other*		
8 1/2" <del>8-3/4"</del>	11"	3M	Annular	x	50% testing pressure  3M
			Blind Ram	x	
			Pipe Ram	x	
			Double Ram		
			Other*		

\*Specify if additional ram is utilized.

BOP/BOPE will be tested by an independent service company to 250 psi low and the high pressure indicated above per Onshore Order 2 requirements. The System may be upgraded to a higher pressure but still tested to the working pressure listed in the table above. If the system is upgraded all the components installed will be functional and tested.

Pipe rams will be operationally checked each 24 hour period. Blind rams will be operationally checked on each trip out of the hole. These checks will be noted on the daily tour sheets. Other accessories to the BOP equipment will include a Kelly cock and floor safety valve (inside BOP) and choke lines and choke manifold. See attached schematics.

Y	Formation integrity test will be performed per Onshore Order #2. On Exploratory wells or on that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.i.
---	--

**BC Operating, Inc. Gay Nineties Federal Com #2H**

See  
COA

Y	A variance is requested for the use of a flexible choke line from the BOP to Choke Manifold. See attached for specs and hydrostatic test chart.	
	Y/N	Are anchors required by manufacturer?
N	<p>A multibowl wellhead is being used. The BOP will be tested per Onshore Order #2 after installation on the surface casing which will cover testing requirements for a maximum of 30 days. If any seal subject to test pressure is broken the system must be tested.</p> <ul style="list-style-type: none"> <li>• Provide description here</li> </ul> <p>See attached schematic.</p>	

**5. Mud Program**

Depth		Type	Weight (ppg)	Viscosity	Water Loss
From	To				
0	Surf. shoe	FW Gel	8.5-8.6	28-32	N/C
Surf csg	Int 1 shoe	Saturated Brine	10.0-10.2	28-29	N/C
Int 1 csg	Int 2 shoe	Cut Brine	8.5-9.3	28-34	N/C
Int 2 csg	9800	FW gel then	8.4-8.5	28-29	N/C
9800	TD Pilot	Xan PX to log	8.4-8.6	34-36	<12
KOP	TD Hz	Cut Brine	8.6-8.9	46-50	<10

Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept on location at all times.

What will be used to monitor the loss or gain of fluid?	PVT/Pason/Visual Monitoring
---	-----------------------------

**6. Logging and Testing Procedures**

Logging, Coring and Testing	
Y	Will run GR/CNL from TD to surface (horizontal well – vertical portion of hole). Stated logs run will be in the Completion Report and submitted to the BLM.
	No Logs are planned based on well control or offset log information.
N	Drill stem test? If yes, explain
N	Coring? If yes, explain

Additional logs planned	Interval
Y	Resistivity
Y	Density
Y	CBL
Y	Mud log
	PEX

**7. Drilling Conditions**

Condition	Specify what type and where?
BH Pressure at deepest TVD	3400 psi
Abnormal Temperature	No

Mitigation measure for abnormal conditions. Describe. Lost circulation material/sweeps/mud scavengers.

See COA

Hydrogen Sulfide (H<sub>2</sub>S) monitors will be installed prior to drilling out the surface shoe. If H<sub>2</sub>S is detected in concentrations greater than 100 ppm, the operator will comply with the provisions of Onshore Oil and Gas Order #6. If Hydrogen Sulfide is encountered, measured values and formations will be provided to the BLM.

	H <sub>2</sub> S is present
Y	H <sub>2</sub> S Plan attached

**8. Other facets of operation**

Is this a walking operation? No. If yes, describe.  
 Will be pre-setting casing? No. If yes, describe.

Attachments

- Directional Plan
- Specification sheet for TTRS1 connection
- Other, describe