

OCD Hobbs

Revised 11/26/14

Form 3160-3  
(March 2012)FORM APPROVED  
OMB No. 1004-0137  
Expires October 31, 2014UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

Split Estate

## APPLICATION FOR PERMIT TO DRILL OR REENTER

5. Lease Serial No.  
LC 031621B6. If Indian, Allottee or Tribe Name  
N/A7. If Unit or CA Agreement, Name and No.  
N/A8. Lease Name and Well No.  
Britt B 53 (31365)9. API Well No.  
30-025-4315510. Field and Pool, or Exploratory  
Blindery; Tubb MONUMENT; TUBB11. Sec., T. R. M. or Blk. and Survey or Area  
Sec. 15, T20S, R37E (47090) Kc12. County or Parish  
Lea County13. State  
NM1a. Type of work: ☒ DRILL ☐ REENTER1b. Type of Well: ☒ Oil Well ☐ Gas Well ☐ Other ☐ Single Zone ☒ Multiple Zone

2. Name of Operator ConocoPhillips Company (217817) HC

3a. Address 600 N. Dairy Ashford Rd.; P10-3096  
Houston, TX 77079-11753b. Phone No. (include area code)  
281-206-5281 MAR 28 2016

4. Location of Well (Report location clearly and in accordance with any State requirements.)\*

At surface 330' FNL &amp; 2340' FWL; UL C, Sec. 15, T20S, R37E

At proposed prod. zone 660' FNL &amp; 1980' FWL; UL C, Sec. 15, T20S, R37E

14. Distance in miles and direction from nearest town or post office\*  
Approximately 5 miles NW of Monument, NM15. Distance from proposed\* location to nearest property or lease line, ft.  
(Also to nearest drig. unit line, if any) 330'16. No. of acres in lease  
175717. Spacing Unit dedicated to this well  
40.00

18. Distance from proposed location\* to nearest well, drilling, completed, applied for, on this lease, ft. ~500'

19. Proposed Depth  
7170' TVD/7193' MD20. BLM/BIA Bond No. on file  
ES008521. Elevations (Show whether DF, KDB, RT, GL, etc.)  
3566' GL22. Approximate date work will start\*  
03/01/201523. Estimated duration  
7 days

## 24. Attachments

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No.1, must be attached to this form:

- Well plat certified by a registered surveyor.
- A Drilling Plan.
- A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office).
- Bond to cover the operations unless covered by an existing bond on file (see Item 20 above).
- Operator certification
- Such other site specific information and/or plans as may be required by the BLM.

25. Signature Susan B. Maunders

Name (Printed/Typed)  
Susan B. Maunders

Date 11/26/14

Title  
Senior Regulatory Specialist

Approved by (Signature) Steve Caffey

Name (Printed/Typed)

Date MAR 23 2016

Title  
FIELD MANAGEROffice  
CARLSBAD FIELD OFFICE

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Conditions of approval, if any, are attached.

APPROVAL FOR TWO YEARS

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Continued on page 2)

\*(Instructions on page 2)

Lea County Controlled Water Basin

Approval Subject to General Requirements  
& Special Stipulations AttachedSEE ATTACHED FOR  
CONDITIONS OF APPROVAL

APR 14 2016

Drilling Plan  
ConocoPhillips Company  
Britt B; Blinebry -Tubb - Drinkard

Britt B#53

Lea County, New Mexico

**1. Estimated tops of geological markers and estimated depths to water, oil, or gas formations:.**

The datum for these depths is RKB (which is 13' above Ground Level).

Formations	Top Depth FT MD	Top Depths FT TVD	Contents
Quaternary	Surface	Surface	Fresh Water
Rustler	1307	1307	Anhydrite
Salado (top of salt)	1398	1398	Salt
Tansill (base of salt)	2549	2548	Gas, Oil and Water
Yates	2695	2693	Gas, Oil and Water
Seven Rivers	2954	2951	Gas, Oil and Water
Queen	3492	3486	Gas, Oil and Water
Penrose	3603	3597	Gas, Oil and Water
Grayburg	3773	3766	Gas, Oil and Water
San Andres	4019	4011	Gas, Oil and Water
Glorieta	5222	5208	Gas, Oil and Water
Paddock	5355	5341	Gas, Oil and Water
Blinebry	5678	5662	Gas, Oil and Water
Tubb	6391	6372	Gas, Oil and Water
Drinkard	6699	6678	Gas, Oil and Water
Abo	6992	6970	Gas, Oil and Water
Deepest estimated perforation	6992	6970	Deepest estimated perf. is Top of Abo
Total Depth (maximum)	7193	7170	200' below deepest estimated perforation

All of the water bearing formations identified above will be protected by setting of the 8-5/8" surface casing 25' - 70' into the Rustler formation and circulating of cement from casing shoe to surface in accordance with the provisions of Onshore Oil and Gas Order No. 2 and New Mexico Oil Conservation Division Title 19.

The targeted oil and gas bearing formations identified above will be protected by setting of the 5-1/2" production casing 10' off bottom of TD and circulating of cement from casing shoe to surface in accordance with the provisions of Onshore Oil and Gas Order No. 2 and New Mexico Oil Conservation Division Title 19.

## 2. Proposed casing program:

Type	Hole Size	Interval MD RKB (ft)		OD	Wt	Gr	Conn	MIY	Col	Jt Str	Safety Factors Calculated per ConocoPhillips Corporate Criteria		
		From	To								Burst DF	Collapse DF	Jt Str DF (Tension) Dry/Buoyant
Cond	20	0	40' - 85' (30' - 75' BGL)	16	0.5" wall	B	Line Pipe	N/A	N/A	N/A	NA	NA	NA
Alt. Cond	20	0	40' - 85' (30' - 75' BGL)	13-3/8	48#	H-40	PE	1730	740	N/A	NA	NA	NA
Surf	12-1/4	0	<del>1337</del> <sup>1340</sup> - 1367'	8-5/8	24#	J-55	STC	2950	1370	244	1.38	2.15	3.05
Prod	7-7/8	0	7153' - 7183'	5-1/2	17#	L-80	LTC	7740	6290	338	3.47	4.89	2.68

The casing will be suitable for H<sub>2</sub>S Service. All casing will be new.

The surface and production casing will be set approximately 10' off bottom and we will drill the hole with a 45' range uncertainty for casing set depth to fit the casing string so that the cementing head is positioned at the floor for the cement job.

The production casing will be set 155' to 200' below the deepest estimated perforation to provide rathole for the pumping completion and for the logs to get deep enough to log the interval of interest.

### Casing Safety Factors - BLM Criteria:

Type	Depth	Wt	MIY	Col	Jt Str	Drill Fluid	Burst	Collapse	Tensile-Dry	Tens-Bouy
Surface Casing	1337	24	2950	1370	244000	8.5	4.99	2.32	7.6	8.7
Production Casing	7183	17	7740	6290	338000	10	2.07	1.68	2.77	3.27

### Casing Safety Factors - Additional ConocoPhillips Criteria:

ConocoPhillips casing design policy establishes Corporate Minimum Design Factors (see table below) and requires that service life load cases be considered and provided for in the casing design.

ConocoPhillips Corporate Criteria for Minimum Design Factors

	Burst	Collapse	Axial
Casing Design Factors	1.15	1.05	1.4

Type  
Conductor  
Surface Casing (8-5/8" 24# J-55 STC)  
Production Casing (5-1/2" 17# L-80 LTC)

Depth	Wt	MIY	Col	Jt Str	Pipe Yield MW	Burst Col.	Ten
85	65	35000	-	-	432966	-	-
1337	24	2950	1370	244000	381000	8.5	1.41
7183	17	7740	6290	338000	397000	10	2.07
						2.48	1.95

#### Burst - ConocoPhillips Required Load Cases

The maximum internal (burst) load on the Surface Casing occurs when the surface casing is tested to 1500 psi (as per BLM Onshore Order 2 - 18 Requirements).

The maximum internal (burst) load on the Production Casing occurs during the fracture stimulation where the maximum allowable working pressure (MAWP) is the pressure that would fit ConocoPhillips Corporate Criteria for Minimum Factors.

(MAWP) is the pressure that would fit ConocoPhillips Corporate Criteria for Minimum Factors.

Surface Casing Test Pressure =	1500 psi	Predicted Pore Pressure at TD (PPTD) =	8.55 ppg
Surface Rated Working Pressure (BOPF) =	3000 psi	Predicted Frac Gradient at Shoe (CSFG) =	19.23 ppg
Field SW =	10 ppg		

Surface Casing Burst Safety Factor = API Burst Rating / Maximum Predicted Surface Pressure (MPSP) OR Maximum Allowable Surface Pressure (MASP)

Production Casing MAWP for the Fracture Stimulation = API Burst Rating / Corporate Minimum Burst Design Factor

#### Surface Casing Burst Safety Factor:

Case #1. MPSP (MWhyd next section) =	1337	x	0.052	x	10	=	695			
Case #2. MPSP (Field SW @ Bullhead CSFG + 200 psi) =	1337	x	0.052	x	19.23	=	695	+	200	= 842
Case #3. MPSP (Kick Vol @ next section TD) =	7183	x	0.052	x	8.55	=	584.6	-	591	= 2018
Case #4. MPSP (PPTD - GG) =	7183	x	0.052	x	8.55	=	718.3	=		2475
Case #3 & #4 Limited to MPSP (CSFG + 0.2 ppg) =	1337	x	0.052	x	( 19.23 + 0.2 )	=				1351
MASP (MWhyd + Test Pressure) =	1337	x	0.052	x	8.5	+	1500	=		2091
Burst Safety Factor (Max. MPSP or MASP) =	2950	/	2091	=	1.41					

#### Production Casing Burst Safety Factor:

Case #1. MPSP (MWhyd TD) =	7183	x	0.052	x	10	=	3735.16			
Case #4. MPSP (PPTD - GG) =	7183	x	0.052	x	8.55	=	718.3	=		2475
Burst Safety Factor (Max. MPSP) =	7740	/	3735	=	2.07					
MAWP for the Fracture Stimulation (Corporate Criteria) =	7740	/	1.15	=	6730					

#### Collapse - ConocoPhillips Required Load Cases

The maximum collapse load on the Surface Casing occurs when cementing to surface, 1/3 evacuation to the next casing setting depth, or deepest depth of exposure (full evacuation).

The maximum collapse load on the Production Casing occurs when cementing to surface, or 1/3 evacuation to the deepest depth of exposure; and

therefore, the external pressure profile for the evacuation cases should be equal to the pore pressure of the horizons on the outside of the casing which we assumed to be PPTD.

Surface Casing Collapse Safety Factor = API Collapse Rating / Full Evacuation OR Cement Displacement during Cementing to Surface

Production Casing Collapse Safety Factor = API Collapse Rating / Maximum Predicted Surface Pressure OR Cement Displacement during Cementing to Surface

Cement Displacement Fluid (FW) =	8.34 ppg	Top of Cement =	Cement to Surface
Surface Cement Lead =	13.6 ppg	Prod Cement Lead =	11.8 ppg
Surface Cement Tail =	14.8 ppg	Prod Cement Tail =	16.4 ppg
Top of Surface Tail Cement =	300 ft	Top of Prod Tail Cement =	5200 ft

#### Surface Casing Collapse Safety Factor:

Full Evacuation Diff Pressure =	1337	x	0.052	x	8.55	=	594			
Cementing Diff Lift Pressure =	(( 1037	x	0.052	x	13.6	) + (	300	x	0.052	x 14.8 ) = 580
Collapse Safety Factor =	1370	/	594	=	2.30					384

#### Production Casing Collapse Safety Factor:

1/3 Evacuation Diff Pressure =	(( 7183	x	0.052	x	8.55	) + (	7183	/	3	x 0.052 x 8.34 ) = 2155
Cementing Diff Lift Pressure =	(( 1983	x	0.052	x	11.8	) + (	5200	x	0.052	x 16.4 ) = 3115
Collapse Safety Factor =	6290	/	2536	=	2.48					2536

#### Tensile Strength - ConocoPhillips Required Load Cases

The maximum axial (tension) load occurs if casing were to get stuck and pulled on to try to get it unstuck.

Maximum Allowable Axial Load for Pipe Yield = API Pipe Yield Strength Rating / Corporate Minimum Axial Design Factor

Maximum Allowable Axial Load for Joint = API Joint Strength Rating / Corporate Minimum Axial Design Factor

Maximum Allowable Hook Load (Limited to 75% of Rig Max Load) = Maximum Allowable Axial Load

Maximum Allowable Overpull Margin = Maximum Allowable Hook Load - Bouyant Wt of the String

Tensile Safety Factor = API Pipe Yield OR API Joint Strength OR Rig Max Load Rating / ( Bouyant Wt of String + Minimum Overpull Required )

Rig Max Load (300,000 lbs) x 75% =	225000 lbs
Minimum Overpull Required =	50000 lbs

#### Surface Casing Tensile Strength Safety Factor:

Air Wt =	32088									
Bouyant Wt =	32088	x	0.870	=	27924					
Max. Allowable Axial Load (Pipe Yield) =	381000	/	1.40	=	272143					
Max. Allowable Axial Load (Joint) =	244000	/	1.40	=	174286					
Max. Allowable Hook Load (Limited to 75% of Rig Max Load) =	174286									
Max. Allowable Overpull Margin =	174286	-	( 32088	x	0.870	) =	146362			
Tensile Safety Factor =	244000	/	( 27924	+	50000	) =	3.13			

#### Production Casing Tensile Strength Safety Factor:

Air Wt =	122111									
Bouyant Wt =	122111	x	0.847	=	103468					
Max. Allowable Axial Load (Pipe Yield) =	397000	/	1.40	=	283571					
Max. Allowable Axial Load (Joint) =	338000	/	1.40	=	241429					
Max. Allowable Hook Load (Limited to 75% of Rig Max Load) =	225000									
Max. Allowable Overpull Margin =	225000	-	( 122111	x	0.847	) =	121532			
Tensile Safety Factor =	300000	/	( 103468	+	50000	) =	1.95			

#### Compression Strength - ConocoPhillips Required Load Cases

The maximum axial (compression) load for the well is where the surface casing is landed on the conductor

with a support of a plate or landing ring. The surface casing is also calculated to bear 60% of the load

but not limited. Any other axial loads such as a snubbing unit or other would need to be added to the load.

Compression Safety Factor = API Axial Joint Strength Rating OR API Axial Pipe Yield Rating / Maximum Predicted Load

Wellhead Load = 3000 lbs

#### Conductor & Surface Compression Safety Factor

Surf Casing Wt (Bouyant) =	( 32088	x	0.870	) =	27924					
Prod Casing Wt (Bouyant) =	( 122111	x	0.847	) =	103468					
Tubing Wt (Air Wt) =	7183	x	6.5	=	46690					
Tubing Fluid Wt =	7183	x	0.052	x	6.55	x	0.7854	x	2.441	= 11449
Load on Conductor =	3000	+	27924	+	103468	+	46689.5	+	11449	= 192531
Conductor Compression Safety Factor =	432966	/	192531	=	2.25					
Load on Surface Casing =	192531	x	60%	=	115518					
Surface Casing Compression Safety Factor =	244000	/	115518	=	2.11					

### 3. Proposed cementing program:

#### 16" or 13-3/8" Conductor:

Cement to surface with rathole mix, ready mix or Class C Neat cement.  
(Note: The gravel used in the cement is not to exceed 3/8" diameter)  
TOC at surface.

#### 8-5/8" Surface Casing Cementing Program:

The intention for the cementing program for the Surface Casing is to:

- Place the Tail Slurry from the casing shoe to 350' above the casing shoe,
- Bring the Lead Slurry to surface.

Spacer: 20 bbls Fresh Water

Slurry		Intervals Ft MD		Weight ppg	Sx	Vol Cuft	Additives	Yield ft <sup>3</sup> /sx
Lead	Class C	Surface	1037' – 1067'	13.6	450	765	+ 2% Extender + 2% CaCl <sub>2</sub> + 0.125 lb/sx Lost Circulation Control Agent + 0.2% Defoamer  Excess = 200% based on gauge hole volume	1.70
Tail	Class C	1037' – 1067'	1337' – 1367'	14.8	300	402	1% CaCl <sub>2</sub>  Excess = 100% based on gauge hole volume	1.34

Displacement: Fresh Water.

**Note:** In accordance with the Pecos District Conditions of Approval, we will Wait on Cement (WOC) for a period of not less than 18 hrs after placement or until at least 500 psi compressive strength has been reached in both the Lead Slurry and Tail Slurry cements on the Surface Casing, whichever is greater.

#### 5-1/2" Production Casing Cementing Program – Single Stage Cementing Option:

The intention for the cementing program for the Production Casing – Single Stage Cementing Option is to:

- Place the Tail Slurry from the casing shoe to above the top of the Grayburg,
- Bring the Lead Slurry to surface.

Spacer: 20 bbls Fresh Water

Slurry		Intervals Ft MD		Weight ppg	Sx	Vol Cuft	Additives	Yield ft <sup>3</sup> /sx
Lead	C Gas Tight Slurry	Surface	3000'	11.5	500	1300	Class C 94 lb/sx 6% Extender 10% Gas Migration Control 2% Sodium Metasilicate (dry) 1% Cement Bonding Agent 3% Aluminum Silicate 0.125 lb/sx Cello Flake 3 lb/sx LCM-1	2.6
Tail	Poz/C Gas Tight Slurry	3000'	7153' – 7183'	14.0	800	1120	(35:65) Poz:C 33 lb/sx 1% Sodium Metasilicate (dry) 1.5% Fluid Loss Control,	1.40

Displacement: Fresh Water with approximately 250 ppm glutaraldehyde biocide.

### 5-1/2" Production Casing Cementing Program – Two-Stage Cementing Option (Shallow Flow):

ConocoPhillips Company respectfully requests the options to our cementing program. The intention for the cementing program for the Production Casing – Two-Stage Cementing Option is to:

- Provide a contingency plan for using a Stage Tool and Annulus Casing Packer(s) to isolate shallow saltwater or gas flow if either of these events occurs while drilling the well.
- Place the Stage 1 Cement from the casing shoe to surface.
- Proceed with Stage 2 Cement only if cement returns are contaminated or flow was observed after pumping 1<sup>st</sup> stage.

Spacer: 20 bbls Fresh Water

Stage 1 - Slurry		Intervals Ft MD		Weight ppg	Sx	Vol Cuft	Additives	Yield ft <sup>3</sup> /sx
See CBA Lead	C Gas Tight Slurry	Surface	3000'	11.5	500	1300	Class C 94 lb/sx 6% Extender 10% Gas Migration Control 2% Sodium Metasilicate (dry) 1% Cement Bonding Agent 3% Aluminum Silicate 0.125 lb/sx Cello Flake 3 lb/sx LCM-1	2.6
Tail	Poz/C Gas Tight Slurry	3000'	7153' – 7183'	14.0	800	1120	(35:65) Poz:C 33 lb/sx 1% Sodium Metasilicate (dry) 1.5% Fluid Loss Control,	1.40

1<sup>st</sup> stage displacement: FW followed by Weighted Spacer

Spacer: Remaining Weighted Spacer in cementing lines from the 1<sup>st</sup> stage displacement

Stage 2 - Slurry		Intervals Ft MD		Weight ppg	Sx	Vol Cuft	Additives	Yield ft <sup>3</sup> /sx
Lead	Class C	Surface	Stage Tool ~1450'	11.5	250	620	1% CaCl <sub>2</sub> Excess = 100% based on gauge hole volume	2.6

2<sup>nd</sup> stage displacement: Fresh Water

### 5-1/2" Production Casing Cementing Program – Two-Stage Cementing Option (Lower Zone Losses or Waterflow):

ConocoPhillips Company respectfully requests the options to our cementing program. The intention for the cementing program for the Production Casing – Two-Stage Cementing Option is to:

- Provide a contingency plan for using a Stage Tool and Annulus Casing Packer(s) to isolate losses or waterflow if either of these events occurs while drilling the well.
- Place the Stage 1 Cement from the casing shoe to the stage tool,
- Bring Stage 2 Cement from the stage tool to surface.

Spacer: 20 bbls Fresh Water

Stage 1 – Slurry		Intervals Ft MD		Weight ppg	Sx	Vol Cuft	Additives	Yield ft <sup>3</sup> /sx
Tail	Poz/C Gas Tight Slurry	Stage Tool ~2900'	7153' – 7183'	14.0	800	1120	(35:65) Poz:C 33 lb/sx 1% Sodium Metasilicate (dry) 1.5% Fluid Loss Control,	2.6

1<sup>st</sup> stage displacement: FW followed by Brine

Spacer: 20 bbls Fresh Water

Stage 2 - Slurry		Intervals Ft MD		Weight ppg	Sx	Vol Cuft	Additives	Yield ft <sup>3</sup> /sx
Lead	C <sup>-</sup> Gas Tight Slurry	Surface	Stage Tool ~2900'	11.5	500	1300	Class C 94 lb/sx 6% Extender 10% Gas Migration Control 2% Sodium Metasilicate (dry) 1% Cement Bonding Agent 3% Aluminum Silicate 0.125 lb/sx Cello Flake 3 lb/sx LCM-1	2.6

Displacement: Fresh Water

**Proposal for Option to Adjust Production Casing Cement Volumes:**

The production casing cement volumes for the proposed single stage and two-stage option presented above are estimates based on gauge hole. We will adjust these volumes based on the caliper log data for each well and our trends for amount of cement returns to surface. Also, if no caliper log is available for any particular well, we would propose an option to possibly increase the production casing cement volume to account for any uncertainty in regard to the hole volume.

#### 4. Pressure Control Equipment:

A 11" 3M system will be installed, used, maintained, and tested accordingly as described in Onshore Oil and Gas Order No. 2.

Our BOP equipment will be:

- o Rotating Head
- o Annular BOP, 11" 3M
- o Blind Ram, 11" 3M
- o Pipe Ram, 11" 3M

After nipping up, and every 30 days thereafter or whenever any seal subject to test pressure is broken followed by related repairs, blowout preventors will be pressure tested. BOP will be inspected and operated at least daily to insure good working order. All pressure and operating tests will be done by an independent service company and recorded on the daily drilling reports. BOP will be tested using a test plug to isolate BOP stack from casing. BOP test will include a low pressure test from 250 to 300 psi for a minimum of 10 minutes or until requirements of test are met, whichever is longer. Ram type preventers and associated equipment will be tested to the approved stack working pressure of 3000 psi isolated by test plug. Annular type preventers will be tested to 50 percent of rated working pressure, and therefore will be tested to 1500 psi. Pressure will be held for at least 10 minutes or until provisions of test are met, whichever is longer. Valve on casing head below test plug will be open during testing of BOP stack. BOP will comply with all provisions of Onshore Oil and Gas Order No. 2 as specified. **See Attached BOPE Schematic.** A variance is respectfully requested to allow for the use of flexible hose. The variance request is included as a separate enclosure with attachments.

#### 5. Proposed Mud System:

The mud systems that are proposed for use are as follows:

DEPTH	TYPE	Density ppg	FV sec/qt	API Fluid Loss cc/30 min	pH	Vol bbl
0 – Surface Casing Point	Fresh Water or Fresh Water Native Mud in Steel Pits	8.5 – 9.0	28 – 40	N.C.	N.C.	150 – 300
Surface Casing Point to TD	Brine (Saturated NaCl <sub>2</sub> ) in Steel Pits	10	29	N.C.	10 – 11	300 – 1000
Conversion to Mud at TD	Brine Based Mud (NaCl <sub>2</sub> ) in Steel Pits	10	33 – 40	5 – 10	10 – 11	0 – 1000

Gas detection equipment and pit level flow monitoring equipment will be on location. A flow paddle will be installed in the flow line to monitor relative amount of mud flowing in the non-pressurized return line. Mud probes will be installed in the individual tanks to monitor pit volumes of the drilling fluid with a pit volume totalizer. Gas detecting equipment and H2S monitor alarm will be installed in the mud return system and will be monitored. A mud gas separator will be installed and operable before drilling out from the Surface Casing. The gases shall be piped into the flare system. Drilling mud containing H2S shall be degassed in accordance with API RP-49, item 5.14.

In the event that the well is flowing from a waterflow, then we would discharge excess drilling fluids from the steel mud pits through a fas-line into steel frac tanks at an offset location for containment. Depending on the rate of waterflow, excess fluids will be hauled to an approved disposal facility, or if in suitable condition, may be reused on the next well.

No reserve pit will be built.

#### **Proposal for Option to Not Mud Up at TD:**

FW, Brine, and Mud volume presented above are estimates based on gauge 12-1/4" or 7-7/8" holes. We will adjust these volume based on hole conditions. We do not plan to keep any weighting material at the wellsite. Also, we propose an option to not mud up leaving only brine in the hole if we have good hole stability.



#### 6. Logging, Coring, and Testing Program:

- a. No drill stem tests will be done
- b. Remote gas monitoring planned for the production hole section (optional).
- c. No whole cores are planned
- d. The open hole electrical logging program is planned to be as follows:
  - Total Depth to 1700' MD: Spectral Gamma Ray, PE, Resistivity (laterologs), Bulk Density, and Sonic
  - Total Depth to surface Casing Shoe: Caliper
  - Total Depth to surface, Total Gamma Ray and Neutron
  - Total Depth to 2350' MD ; Mud Log (optional)
  - Total Depth to 2350' MD ; Dielectric Scanner (optional)
  - Formation pressure data (XPT) on electric line if needed (optional)
  - Rotary Sidewall Cores on electric line if needed (optional)
  - FMI (Formation MicroImager) if needed (optional)
  - UBI (Ultrasonic Borehole Imager) if needed (optional)
- e. Cement Bond Log (optional).

#### 7. Abnormal Pressures and Temperatures:

- No abnormal pressures are expected to be encountered.
- Loss of circulation is a possibility in the horizons below the Top of Grayburg. We expect that normal Loss of Circulation Material will be successful in healing any such loss of circulation events.
  - The bottom hole pressure is expected to be 7.8 ppg gradient.
  - The expected Bottom Hole Temperature is 100 degrees F.
- The estimated H<sub>2</sub>S concentrations and ROE calculations for the gas in the zones to be penetrated are presented in the table below for the various producing horizons in this area:

FORMATION / ZONE	H2S (PPM)	Gas Rate (MCFD)	ROE 100 PPM	ROE 500 PPM
Seven Rivers	6	50 - 100 MCFD	0	0
Grayburg / San Andres	18360	20 - 50 MCFD	95	43

ConocoPhillips will comply with the provisions of Oil and Gas Order # 6, Hydrogen Sulfide Operations. Also, ConocoPhillips will provide an H<sub>2</sub>S Contingency Plan (please see copy attached) and will keep this plan updated and posted at the wellsite during the drilling operation.

#### 8. Anticipated starting date and duration of operations:

Well pad and road constructions will begin as soon as all agency approvals are obtained. Anticipated date to drill this well is in March 2015 after receiving approval of the APD.

#### Attachments:

- Attachment # 1 ..... Two-stage Cementing Schematic
- Attachment # 2 ..... BOP and Choke Manifold Schematic – 3M System
- Attachment # 3 ..... Diagram of Choke Manifold Equipment

#### Contact Information:

Proposed 26 November 2014 by:  
Steven Herrin  
Drilling Engineer, ConocoPhillips Company  
Phone (281) 206-5115  
Cell (432) 209-7558  
Britt B #53


(Date: 11/26/2014)

Page 8 of 11

## Attachment # 1


### Two-Stage Cementing (Alternative for Shallow Gas / Salt Water / Gas & Water Flow)

Provide contingency plan for using two-stage cementing for the production casing cement job if gas flow occurs during the drilling operations. See APD Drill Plan Section 3. Proposed cementing program.




### Two-Stage Cementing (Alternative for Oil / Water / Gas & Water Flow)

Provide contingency plan for using two-stage cementing for the production casing cement job if oil or water flow occurs during the drilling operations. See APD Drill Plan Section 3. Proposed cementing program.



**BLOWOUT PREVENTER ARRANGEMENT**


3M System per Onshore Oil and Gas Order No. 2 utilizing 3M and 5M Rated Equipment



Item	Description
1	Rotating Head, 11"
2A	Fill up Line and Valve
2B	Flow Line (10")
2C	Shale Shakers and Solids Settling Tank
2D	Cuttings Bins for Zero Discharge
2E	Rental Mud Gas Separator with vent line to flare and return line to mud system
3	Annular BOP (11", 3M)
4	Double Ram (11", 3M, equipped with Blind Rams and Pipe Rams)
5	Kill Line (2" flexible hose, 3000 psi WP)
6	Kill Line Valve, Inner (3-1/8", 3000 psi WP)
7	Kill Line Valve, Outer (3-1/8", 3000 psi WP)
8	Kill Line Check Valve (2-1/16", 3000 psi WP)
9	Choke Line (5M Stainless Steel Collex Line, 3-1/8" 3M API Type 6B, 3000 psi WP)
10	Choke Line Valve, Inner (3-1/8", 3000 psi WP)
11	Choke Line Valve, Outer, (Hydraulically operated, 3-1/8", 3000 psi WP)
12	Adapter Flange (11" 5M to 11" 3M)
13	Spacer Spool (11", 5M)
14	Casing Head (11" 5M)
15	Ball Valve and Threaded Nipple on Casing Head Outlet, 2" 5M
16	Surface Casing

Submitted by: Steven Herrin, Drilling Engineer, Mid-Continent Business Unit, ConocoPhillips Company, 03-Jan-2014

**CHOKE MANIFOLD ARRANGEMENT**  
**3M System per Onshore Oil and Gas Order No. 2 utilizing 3M and 5M Equipment**



Item	Description
1	Manual Adjustable Choke, 2-1/16", 3M
2	Remote Controlled Hydraulically Operated Adjustable Choke, 2-1/16", 3M
3	Gate Valve, 2-1/16" 5M
4	Gate Valve, 2-1/16" 5M
5	Gate Valve, 2-1/16" 5M
6	Gate Valve, 2-1/16" 5M
7	Gate Valve, 3-1/8" 3M
8	Gate Valve, 2-1/16" 5M
9	Gate Valve, 2-1/16" 5M
10	Gate Valve, 2-1/16" 5M
11	Gate Valve, 3-1/8" 3M
12	Gate Valve, 2-1/16" 5M
13	Pressure Gauge
14	2" hammer union tie-in point for BOP Tester

We will test each valve to 3000 psi from the upstream side.

Submitted by:



Steven Hemin

Drilling Engineer, Mid-Continent Business Unit, ConocoPhillips Company

Date: 3-January-2014

# ConocoPhillips

**ConocoPhillips**  
**Well: Britt B Well No. 53**  
**Site: Britt B**  
**Project: Lea County, New Mexico**  
**Design: rev0**  
**Date:**



Section Details										
Sec	MD	Inc	Azi	TVD	+N-S	+E-W	Dleg	TFace	Vsect	Annotation
1	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
2	2000.00	0.00	0.00	2000.00	0.00	0.00	0.00	0.00	0.00	KOP Begin 2°/100' build
3	2276.72	5.53	226.88	2276.29	-9.13	-9.75	2.00	226.88	13.35	Begin 5.53° tangent
4	7193.35	5.53	226.88	7170.00	-333.26	-355.84	0.00	0.00	487.52	PBHL/TD

Surf Loc: RKB=3566+13 @ 3579.00usft ( )  
 US State Plane 1927 (Exact solution)  
 New Mexico East 3001  
 Northing: 576203.98 Easting: 836941.94 Latitude: 32° 34' 45.597455 N Longitude: 103° 14' 23.368414 W  
 Total Corr: Magnetic to Grid North (M->G) : To convert a Magnetic Direction to a Grid Direction, Add 6.62°



Azimuths to Grid North  
 True North: -0.59°  
 Magnetic North: 6.62°

Magnetic Field  
 Strength: 48550.0snT  
 Dip Angle: 60.48°  
 Date: 10/9/2014  
 Model: USER DEFINED BGGM



**PRODIRECTIONAL**