

HOBBS OCD

APR 18 2016

RECEIVED

Mewbourne Oil Company

Lea County, New Mexico

Pepper Ridge 15 B2CN Fed Com #3H

Sec 15, T26S, R33E

SL: 185' FNL & 2200' FWL

BHL: 330' FSL & 2200' FWL

Plan: Design #1

Standard Planning Report

04 January, 2016

APR 22 2016

Planning Report

Database:	Hobbs	Local Co-ordinate Reference:	Site Pepper Ridge 15 B2CN Fed Com #3H
Company:	Mewbourne Oil Company	TVD Reference:	WELL @ 3329.0usft (Original Well Elev)
Project:	Lea County, New Mexico	MD Reference:	WELL @ 3329.0usft (Original Well Elev)
Site:	Pepper Ridge 15 B2CN Fed Com #3H	North Reference:	Grid
Well:	Sec 15, T26S, R33E	Survey Calculation Method:	Minimum Curvature
Wellbore:	BHL: 330' FSL & 2200' FWL		
Design:	Design #1		

Project	Lea County, New Mexico		
Map System:	US State Plane 1927 (Exact solution)	System Datum:	Mean Sea Level
Geo Datum:	NAD 1927 (NADCON CONUS)		
Map Zone:	New Mexico East 3001		

Site	Pepper Ridge 15 B2CN Fed Com #3H		
Site Position:		Northing:	382,808.00 usft
From:	Map	Easting:	739,242.00 usft
Position Uncertainty:	0.0 usft	Slot Radius:	13-3/16"
		Latitude:	32° 3' 0.368 N
		Longitude:	103° 33' 40.183 W
		Grid Convergence:	0.41 °

Well	Sec 15, T26S, R33E		
Well Position	+N/-S	0.0 usft	Northing: 382,808.00 usft
	+E/-W	0.0 usft	Easting: 739,242.00 usft
Position Uncertainty	0.0 usft	Wellhead Elevation:	3,329.0 usft
		Latitude:	32° 3' 0.368 N
		Longitude:	103° 33' 40.183 W
		Ground Level:	3,302.0 usft

Wellbore	BHL: 330' FSL & 2200' FWL		
Magnetics	Model Name	Sample Date	Declination
	IGRF2010	1/4/2016	7.01
			Dip Angle
			59.91
			Field Strength
			48,058

Design	Design #1		
Audit Notes:			
Version:	Phase:	PROTOTYPE	Tie On Depth: 0.0
Vertical Section:	Depth From (TVD)	+N/-S	+E/-W
	(usft)	(usft)	(usft)
	0.0	0.0	0.0
			Direction
			179.54

Plan Sections										
Measured	Inclination	Azimuth	Vertical	+N/-S	+E/-W	Dogleg	Build	Turn	TFO	Target
Depth	(°)	(°)	Depth	(usft)	(usft)	Rate	Rate	Rate	(°)	
(usft)			(usft)			(°/100usft)	(°/100usft)	(°/100usft)		
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.00	0.00	
10,346.5	0.00	0.00	10,346.5	0.0	0.0	0.00	0.00	0.00	0.00	
11,091.4	89.37	179.54	10,824.0	-472.2	3.8	12.00	12.00	0.00	179.54	
15,387.5	89.37	179.54	10,871.0	-4,768.0	38.0	0.00	0.00	0.00	0.00	BHL: 330' FSL & 2200'

Planning Report

Database:	Hobbs	Local Co-ordinate Reference:	Site Pepper Ridge 15 B2CN Fed Com #3H
Company:	Mewbourne Oil Company	TVD Reference:	WELL @ 3329.0usft (Original Well Elev)
Project:	Lea County, New Mexico	MD Reference:	WELL @ 3329.0usft (Original Well Elev)
Site:	Pepper Ridge 15 B2CN Fed Com #3H	North Reference:	Grid
Well:	Sec 15, T26S, R33E	Survey Calculation Method:	Minimum Curvature
Wellbore:	BHL: 330' FSL & 2200' FWL		
Design:	Design #1		

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
0.0	0.00	0.00	0.0	0.0	0.0	0.0	0.00	0.00	0.00
SL: 185' FNL & 2200' FWL									
100.0	0.00	0.00	100.0	0.0	0.0	0.0	0.00	0.00	0.00
200.0	0.00	0.00	200.0	0.0	0.0	0.0	0.00	0.00	0.00
300.0	0.00	0.00	300.0	0.0	0.0	0.0	0.00	0.00	0.00
400.0	0.00	0.00	400.0	0.0	0.0	0.0	0.00	0.00	0.00
500.0	0.00	0.00	500.0	0.0	0.0	0.0	0.00	0.00	0.00
600.0	0.00	0.00	600.0	0.0	0.0	0.0	0.00	0.00	0.00
700.0	0.00	0.00	700.0	0.0	0.0	0.0	0.00	0.00	0.00
800.0	0.00	0.00	800.0	0.0	0.0	0.0	0.00	0.00	0.00
900.0	0.00	0.00	900.0	0.0	0.0	0.0	0.00	0.00	0.00
1,000.0	0.00	0.00	1,000.0	0.0	0.0	0.0	0.00	0.00	0.00
1,100.0	0.00	0.00	1,100.0	0.0	0.0	0.0	0.00	0.00	0.00
1,200.0	0.00	0.00	1,200.0	0.0	0.0	0.0	0.00	0.00	0.00
1,300.0	0.00	0.00	1,300.0	0.0	0.0	0.0	0.00	0.00	0.00
1,400.0	0.00	0.00	1,400.0	0.0	0.0	0.0	0.00	0.00	0.00
1,500.0	0.00	0.00	1,500.0	0.0	0.0	0.0	0.00	0.00	0.00
1,600.0	0.00	0.00	1,600.0	0.0	0.0	0.0	0.00	0.00	0.00
1,700.0	0.00	0.00	1,700.0	0.0	0.0	0.0	0.00	0.00	0.00
1,800.0	0.00	0.00	1,800.0	0.0	0.0	0.0	0.00	0.00	0.00
1,900.0	0.00	0.00	1,900.0	0.0	0.0	0.0	0.00	0.00	0.00
2,000.0	0.00	0.00	2,000.0	0.0	0.0	0.0	0.00	0.00	0.00
2,100.0	0.00	0.00	2,100.0	0.0	0.0	0.0	0.00	0.00	0.00
2,200.0	0.00	0.00	2,200.0	0.0	0.0	0.0	0.00	0.00	0.00
2,300.0	0.00	0.00	2,300.0	0.0	0.0	0.0	0.00	0.00	0.00
2,400.0	0.00	0.00	2,400.0	0.0	0.0	0.0	0.00	0.00	0.00
2,500.0	0.00	0.00	2,500.0	0.0	0.0	0.0	0.00	0.00	0.00
2,600.0	0.00	0.00	2,600.0	0.0	0.0	0.0	0.00	0.00	0.00
2,700.0	0.00	0.00	2,700.0	0.0	0.0	0.0	0.00	0.00	0.00
2,800.0	0.00	0.00	2,800.0	0.0	0.0	0.0	0.00	0.00	0.00
2,900.0	0.00	0.00	2,900.0	0.0	0.0	0.0	0.00	0.00	0.00
3,000.0	0.00	0.00	3,000.0	0.0	0.0	0.0	0.00	0.00	0.00
3,100.0	0.00	0.00	3,100.0	0.0	0.0	0.0	0.00	0.00	0.00
3,200.0	0.00	0.00	3,200.0	0.0	0.0	0.0	0.00	0.00	0.00
3,300.0	0.00	0.00	3,300.0	0.0	0.0	0.0	0.00	0.00	0.00
3,400.0	0.00	0.00	3,400.0	0.0	0.0	0.0	0.00	0.00	0.00
3,500.0	0.00	0.00	3,500.0	0.0	0.0	0.0	0.00	0.00	0.00
3,600.0	0.00	0.00	3,600.0	0.0	0.0	0.0	0.00	0.00	0.00
3,700.0	0.00	0.00	3,700.0	0.0	0.0	0.0	0.00	0.00	0.00
3,800.0	0.00	0.00	3,800.0	0.0	0.0	0.0	0.00	0.00	0.00
3,900.0	0.00	0.00	3,900.0	0.0	0.0	0.0	0.00	0.00	0.00
4,000.0	0.00	0.00	4,000.0	0.0	0.0	0.0	0.00	0.00	0.00
4,100.0	0.00	0.00	4,100.0	0.0	0.0	0.0	0.00	0.00	0.00
4,200.0	0.00	0.00	4,200.0	0.0	0.0	0.0	0.00	0.00	0.00
4,300.0	0.00	0.00	4,300.0	0.0	0.0	0.0	0.00	0.00	0.00
4,400.0	0.00	0.00	4,400.0	0.0	0.0	0.0	0.00	0.00	0.00
4,500.0	0.00	0.00	4,500.0	0.0	0.0	0.0	0.00	0.00	0.00
4,600.0	0.00	0.00	4,600.0	0.0	0.0	0.0	0.00	0.00	0.00
4,700.0	0.00	0.00	4,700.0	0.0	0.0	0.0	0.00	0.00	0.00
4,800.0	0.00	0.00	4,800.0	0.0	0.0	0.0	0.00	0.00	0.00
4,900.0	0.00	0.00	4,900.0	0.0	0.0	0.0	0.00	0.00	0.00
5,000.0	0.00	0.00	5,000.0	0.0	0.0	0.0	0.00	0.00	0.00
5,100.0	0.00	0.00	5,100.0	0.0	0.0	0.0	0.00	0.00	0.00
5,200.0	0.00	0.00	5,200.0	0.0	0.0	0.0	0.00	0.00	0.00

Planning Report

Database:	Hobbs	Local Co-ordinate Reference:	Site Pepper Ridge 15 B2CN Fed Com #3H
Company:	Mewbourne Oil Company	TVD Reference:	WELL @ 3329.0usft (Original Well Elev)
Project:	Lea County, New Mexico	MD Reference:	WELL @ 3329.0usft (Original Well Elev)
Site:	Pepper Ridge 15 B2CN Fed Com #3H	North Reference:	Grid
Well:	Sec 15, T26S, R33E	Survey Calculation Method:	Minimum Curvature
Wellbore:	BHL: 330' FSL & 2200' FWL		
Design:	Design #1		

Planned Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
5,300.0	0.00	0.00	5,300.0	0.0	0.0	0.0	0.00	0.00	0.00	
5,400.0	0.00	0.00	5,400.0	0.0	0.0	0.0	0.00	0.00	0.00	
5,500.0	0.00	0.00	5,500.0	0.0	0.0	0.0	0.00	0.00	0.00	
5,600.0	0.00	0.00	5,600.0	0.0	0.0	0.0	0.00	0.00	0.00	
5,700.0	0.00	0.00	5,700.0	0.0	0.0	0.0	0.00	0.00	0.00	
5,800.0	0.00	0.00	5,800.0	0.0	0.0	0.0	0.00	0.00	0.00	
5,900.0	0.00	0.00	5,900.0	0.0	0.0	0.0	0.00	0.00	0.00	
6,000.0	0.00	0.00	6,000.0	0.0	0.0	0.0	0.00	0.00	0.00	
6,100.0	0.00	0.00	6,100.0	0.0	0.0	0.0	0.00	0.00	0.00	
6,200.0	0.00	0.00	6,200.0	0.0	0.0	0.0	0.00	0.00	0.00	
6,300.0	0.00	0.00	6,300.0	0.0	0.0	0.0	0.00	0.00	0.00	
6,400.0	0.00	0.00	6,400.0	0.0	0.0	0.0	0.00	0.00	0.00	
6,500.0	0.00	0.00	6,500.0	0.0	0.0	0.0	0.00	0.00	0.00	
6,600.0	0.00	0.00	6,600.0	0.0	0.0	0.0	0.00	0.00	0.00	
6,700.0	0.00	0.00	6,700.0	0.0	0.0	0.0	0.00	0.00	0.00	
6,800.0	0.00	0.00	6,800.0	0.0	0.0	0.0	0.00	0.00	0.00	
6,900.0	0.00	0.00	6,900.0	0.0	0.0	0.0	0.00	0.00	0.00	
7,000.0	0.00	0.00	7,000.0	0.0	0.0	0.0	0.00	0.00	0.00	
7,100.0	0.00	0.00	7,100.0	0.0	0.0	0.0	0.00	0.00	0.00	
7,200.0	0.00	0.00	7,200.0	0.0	0.0	0.0	0.00	0.00	0.00	
7,300.0	0.00	0.00	7,300.0	0.0	0.0	0.0	0.00	0.00	0.00	
7,400.0	0.00	0.00	7,400.0	0.0	0.0	0.0	0.00	0.00	0.00	
7,500.0	0.00	0.00	7,500.0	0.0	0.0	0.0	0.00	0.00	0.00	
7,600.0	0.00	0.00	7,600.0	0.0	0.0	0.0	0.00	0.00	0.00	
7,700.0	0.00	0.00	7,700.0	0.0	0.0	0.0	0.00	0.00	0.00	
7,800.0	0.00	0.00	7,800.0	0.0	0.0	0.0	0.00	0.00	0.00	
7,900.0	0.00	0.00	7,900.0	0.0	0.0	0.0	0.00	0.00	0.00	
8,000.0	0.00	0.00	8,000.0	0.0	0.0	0.0	0.00	0.00	0.00	
8,100.0	0.00	0.00	8,100.0	0.0	0.0	0.0	0.00	0.00	0.00	
8,200.0	0.00	0.00	8,200.0	0.0	0.0	0.0	0.00	0.00	0.00	
8,300.0	0.00	0.00	8,300.0	0.0	0.0	0.0	0.00	0.00	0.00	
8,400.0	0.00	0.00	8,400.0	0.0	0.0	0.0	0.00	0.00	0.00	
8,500.0	0.00	0.00	8,500.0	0.0	0.0	0.0	0.00	0.00	0.00	
8,600.0	0.00	0.00	8,600.0	0.0	0.0	0.0	0.00	0.00	0.00	
8,700.0	0.00	0.00	8,700.0	0.0	0.0	0.0	0.00	0.00	0.00	
8,800.0	0.00	0.00	8,800.0	0.0	0.0	0.0	0.00	0.00	0.00	
8,900.0	0.00	0.00	8,900.0	0.0	0.0	0.0	0.00	0.00	0.00	
9,000.0	0.00	0.00	9,000.0	0.0	0.0	0.0	0.00	0.00	0.00	
9,100.0	0.00	0.00	9,100.0	0.0	0.0	0.0	0.00	0.00	0.00	
9,200.0	0.00	0.00	9,200.0	0.0	0.0	0.0	0.00	0.00	0.00	
9,300.0	0.00	0.00	9,300.0	0.0	0.0	0.0	0.00	0.00	0.00	
9,400.0	0.00	0.00	9,400.0	0.0	0.0	0.0	0.00	0.00	0.00	
9,500.0	0.00	0.00	9,500.0	0.0	0.0	0.0	0.00	0.00	0.00	
9,600.0	0.00	0.00	9,600.0	0.0	0.0	0.0	0.00	0.00	0.00	
9,700.0	0.00	0.00	9,700.0	0.0	0.0	0.0	0.00	0.00	0.00	
9,800.0	0.00	0.00	9,800.0	0.0	0.0	0.0	0.00	0.00	0.00	
9,900.0	0.00	0.00	9,900.0	0.0	0.0	0.0	0.00	0.00	0.00	
10,000.0	0.00	0.00	10,000.0	0.0	0.0	0.0	0.00	0.00	0.00	
10,100.0	0.00	0.00	10,100.0	0.0	0.0	0.0	0.00	0.00	0.00	
10,200.0	0.00	0.00	10,200.0	0.0	0.0	0.0	0.00	0.00	0.00	
10,300.0	0.00	0.00	10,300.0	0.0	0.0	0.0	0.00	0.00	0.00	
10,346.5	0.00	0.00	10,346.5	0.0	0.0	0.0	0.00	0.00	0.00	
KOP @ 10347'										

Planning Report

Database:	Hobbs	Local Co-ordinate Reference:	Site Pepper Ridge 15 B2CN Fed Com #3H
Company:	Mewbourne Oil Company	TVD Reference:	WELL @ 3329.0usft (Original Well Elev)
Project:	Lea County, New Mexico	MD Reference:	WELL @ 3329.0usft (Original Well Elev)
Site:	Pepper Ridge 15 B2CN Fed Com #3H	North Reference:	Grid
Well:	Sec 15, T26S, R33E	Survey Calculation Method:	Minimum Curvature
Wellbore:	BHL: 330' FSL & 2200' FWL		
Design:	Design #1		

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
10,400.0	6.41	179.54	10,399.9	-3.0	0.0	3.0	12.00	12.00	0.00
10,500.0	18.41	179.54	10,497.4	-24.4	0.2	24.4	12.00	12.00	0.00
10,600.0	30.41	179.54	10,588.3	-65.7	0.5	65.7	12.00	12.00	0.00
10,700.0	42.41	179.54	10,668.6	-125.0	1.0	125.0	12.00	12.00	0.00
10,728.8	45.86	179.54	10,689.2	-145.0	1.2	145.0	12.00	12.00	0.00
First Take Point: 330' FNL & 2200' FWL									
10,800.0	54.41	179.54	10,734.8	-199.6	1.6	199.6	12.00	12.00	0.00
10,900.0	66.41	179.54	10,784.1	-286.4	2.3	286.4	12.00	12.00	0.00
11,000.0	78.41	179.54	10,814.3	-381.6	3.0	381.6	12.00	12.00	0.00
11,091.3	89.37	179.54	10,824.0	-472.2	3.8	472.2	12.00	12.00	0.00
LP: 657' FNL & 2200' FWL									
11,100.0	89.37	179.54	10,824.1	-480.9	3.8	480.9	0.07	0.07	0.00
11,200.0	89.37	179.54	10,825.2	-580.9	4.6	580.9	0.00	0.00	0.00
11,300.0	89.37	179.54	10,826.3	-680.9	5.4	680.9	0.00	0.00	0.00
11,400.0	89.37	179.54	10,827.4	-780.9	6.2	780.9	0.00	0.00	0.00
11,500.0	89.37	179.54	10,828.5	-880.9	7.0	880.9	0.00	0.00	0.00
11,600.0	89.37	179.54	10,829.6	-980.8	7.8	980.9	0.00	0.00	0.00
11,700.0	89.37	179.54	10,830.7	-1,080.8	8.6	1,080.9	0.00	0.00	0.00
11,800.0	89.37	179.54	10,831.8	-1,180.8	9.4	1,180.9	0.00	0.00	0.00
11,900.0	89.37	179.54	10,832.8	-1,280.8	10.2	1,280.9	0.00	0.00	0.00
12,000.0	89.37	179.54	10,833.9	-1,380.8	11.0	1,380.9	0.00	0.00	0.00
12,100.0	89.37	179.54	10,835.0	-1,480.8	11.8	1,480.9	0.00	0.00	0.00
12,200.0	89.37	179.54	10,836.1	-1,580.8	12.6	1,580.8	0.00	0.00	0.00
12,300.0	89.37	179.54	10,837.2	-1,680.8	13.4	1,680.8	0.00	0.00	0.00
12,400.0	89.37	179.54	10,838.3	-1,780.8	14.2	1,780.8	0.00	0.00	0.00
12,500.0	89.37	179.54	10,839.4	-1,880.8	15.0	1,880.8	0.00	0.00	0.00
12,600.0	89.37	179.54	10,840.5	-1,980.8	15.8	1,980.8	0.00	0.00	0.00
12,700.0	89.37	179.54	10,841.6	-2,080.7	16.6	2,080.8	0.00	0.00	0.00
12,800.0	89.37	179.54	10,842.7	-2,180.7	17.4	2,180.8	0.00	0.00	0.00
12,900.0	89.37	179.54	10,843.8	-2,280.7	18.2	2,280.8	0.00	0.00	0.00
13,000.0	89.37	179.54	10,844.9	-2,380.7	19.0	2,380.8	0.00	0.00	0.00
13,100.0	89.37	179.54	10,846.0	-2,480.7	19.8	2,480.8	0.00	0.00	0.00
13,200.0	89.37	179.54	10,847.1	-2,580.7	20.6	2,580.8	0.00	0.00	0.00
13,300.0	89.37	179.54	10,848.2	-2,680.7	21.4	2,680.8	0.00	0.00	0.00
13,400.0	89.37	179.54	10,849.3	-2,780.7	22.2	2,780.8	0.00	0.00	0.00
13,500.0	89.37	179.54	10,850.4	-2,880.7	23.0	2,880.8	0.00	0.00	0.00
13,600.0	89.37	179.54	10,851.4	-2,980.7	23.8	2,980.8	0.00	0.00	0.00
13,700.0	89.37	179.54	10,852.5	-3,080.7	24.6	3,080.8	0.00	0.00	0.00
13,800.0	89.37	179.54	10,853.6	-3,180.6	25.3	3,180.7	0.00	0.00	0.00
13,900.0	89.37	179.54	10,854.7	-3,280.6	26.1	3,280.7	0.00	0.00	0.00
14,000.0	89.37	179.54	10,855.8	-3,380.6	26.9	3,380.7	0.00	0.00	0.00
14,100.0	89.37	179.54	10,856.9	-3,480.6	27.7	3,480.7	0.00	0.00	0.00
14,200.0	89.37	179.54	10,858.0	-3,580.6	28.5	3,580.7	0.00	0.00	0.00
14,300.0	89.37	179.54	10,859.1	-3,680.6	29.3	3,680.7	0.00	0.00	0.00
14,400.0	89.37	179.54	10,860.2	-3,780.6	30.1	3,780.7	0.00	0.00	0.00
14,500.0	89.37	179.54	10,861.3	-3,880.6	30.9	3,880.7	0.00	0.00	0.00
14,600.0	89.37	179.54	10,862.4	-3,980.6	31.7	3,980.7	0.00	0.00	0.00
14,700.0	89.37	179.54	10,863.5	-4,080.6	32.5	4,080.7	0.00	0.00	0.00
14,800.0	89.37	179.54	10,864.6	-4,180.6	33.3	4,180.7	0.00	0.00	0.00
14,900.0	89.37	179.54	10,865.7	-4,280.5	34.1	4,280.7	0.00	0.00	0.00
15,000.0	89.37	179.54	10,866.8	-4,380.5	34.9	4,380.7	0.00	0.00	0.00
15,100.0	89.37	179.54	10,867.9	-4,480.5	35.7	4,480.7	0.00	0.00	0.00
15,200.0	89.37	179.54	10,868.9	-4,580.5	36.5	4,580.7	0.00	0.00	0.00
15,300.0	89.37	179.54	10,870.0	-4,680.5	37.3	4,680.7	0.00	0.00	0.00

Planning Report

Database:	Hobbs	Local Co-ordinate Reference:	Site Pepper Ridge 15 B2CN Fed Com #3H
Company:	Mewbourne Oil Company	TVD Reference:	WELL @ 3329.0usft (Original Well Elev)
Project:	Lea County, New Mexico	MD Reference:	WELL @ 3329.0usft (Original Well Elev)
Site:	Pepper Ridge 15 B2CN Fed Com #3H	North Reference:	Grid
Well:	Sec 15, T26S, R33E	Survey Calculation Method:	Minimum Curvature
Wellbore:	BHL: 330' FSL & 2200' FWL		
Design:	Design #1		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
15,387.5	89.37	179.54	10,871.0	-4,768.0	38.0	4,768.2	0.00	0.00	0.00
BHL: 330' FSL & 2200' FWL									

Design Targets									
Target Name	hit/miss target	Dip Angle (°)	Dip Dir. (°)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude Longitude
SL: 185' FNL & 2200' FV	- plan hits target center	0.00	0.00	0.0	0.0	0.0	382,808.00	739,242.00	32° 3' 0.368 N 103° 33' 40.183 W
- Point									
KOP @ 10347'	- plan hits target center	0.00	0.00	10,346.5	0.0	0.0	382,808.00	739,242.00	32° 3' 0.368 N 103° 33' 40.183 W
- Point									
First Take Point: 330' FN	- plan hits target center	0.00	0.00	10,689.2	-145.0	1.2	382,663.00	739,243.15	32° 2' 58.933 N 103° 33' 40.181 W
- Point									
LP: 657' FNL & 2200' FV	- plan hits target center	0.00	0.00	10,824.0	-472.2	3.8	382,335.80	739,245.80	32° 2' 55.695 N 103° 33' 40.178 W
- Point									
BHL: 330' FSL & 2200' F	- plan hits target center	0.00	0.00	10,871.0	-4,768.0	38.0	378,040.00	739,280.00	32° 2' 13.183 N 103° 33' 40.137 W
- Point									