

15-856

OCD Hobbs

# HOBBS OCD

APR 25 2016

Form 3160-3  
(March 2012)

**RECEIVED** UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
OMB No. 1004-0137  
Expires October 31, 2014

## APPLICATION FOR PERMIT TO DRILL OR REENTER

1a. Type of work: <input checked="" type="checkbox"/> DRILL <input type="checkbox"/> REENTER		5. Lease Serial No. NMNM63994	
1b. Type of Well: <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other <input checked="" type="checkbox"/> Single Zone <input type="checkbox"/> Multiple Zone		6. If Indian, Allottee or Tribe Name	
2. Name of Operator Devon Energy Production Company, L.P. (6137)		7. If Unit or CA Agreement, Name and No. (313306)	
3a. Address 333 West Sheridan Avenue Oklahoma City, OK 73102-5010		8. Lease Name and Well No. Boundary Raider 6 Fed 1H	
3b. Phone No. (include area code) 405.228.7203		9. API Well No. 30-025-48182	
4. Location of Well (Report location clearly and in accordance with any State requirements) At surface 200 FNL & 1650 FEL, Unit B Sec. 7 At proposed prod. zone 330 FNL & 1980 FEL, Lot 2 Sec. 6 PP: 354 FSL & 1980 FEL		10. Field and Pool, or Exploratory SAND DUNES; BS (3800) Sec. T. R. M. or Blk. and Survey or Area Sec. 7 T23S 32E	
14. Distance in miles and direction from nearest town or post office* Approximately 20 miles NE of Malaga, NM		12. County or Parish Lea County	
15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any) See attached map		13. State NM	
16. No. of acres in lease NMNM63994 - 1,020.63 ac		17. Spacing Unit dedicated to this well 159.71 ac	
18. Distance from proposed location* to nearest well, drilling, completed, applied for, on this lease, ft. See attached map		19. Proposed Depth TVD - 10,396' MD - 15,300'	
20. BLM/BIA Bond No. on file CO-1104; NBM-000801		21. Elevations (Show whether DF, KDB, RT, GL, etc.) 3534.1' GL	
22. Approximate date work will start* 4/10/2014		23. Estimated duration 45 days	

**NORTH DUNE LOCATION**

### 24. Attachments

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, must be attached to this form:

- 1. Well plat certified by a registered surveyor.
- 2. A Drilling Plan.
- 3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office).
- 4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above).
- 5. Operator certification
- 6. Such other site specific information and/or plans as may be required by the BLM.

25. Signature 	Name (Printed/Typed) Trina C. Couch	Date 11/25/2014
-------------------	--	--------------------

Approved by (Signature)/s/ George MacDoneli	Name (Printed/Typed)	Date APR 19 2016
Title FIELD MANAGER	Office CARLSBAD FIELD OFFICE	

The NMOCD Gas Capture Plan notice has been posted on the web site under Announcements/Notice to Operators. A copy of the GCP form is included with the notice and is also in the Forms section under Unnumbered forms. Please submit accordingly in a timely manner.

or equitable title to those rights in the subject lease which would entitle the applicant to **APPROVAL FOR TWO YEARS**

for any person knowingly and willfully to make to any department or agency of the United matter within its jurisdiction.

\*(Instructions on page 2)

Carlsbad Controlled Water Basin

Ka  
08/25/16

Approval Subject to General Requirements & Special Stipulations Attached

SEE ATTACHED FOR CONDITIONS OF APPROVAL

APR 25 2016

## Devon Energy, Boundary Raider 6 Fed 1H

### 1. Geologic Formations

TVD of target	10,396'	Pilot hole depth	N/A
MD at TD:	15,300'	Deepest expected fresh water:	

### Basin

Formation	Depth (TVD) from KB	Water/Mineral Bearing/Target Zone?	Hazards*
RUSTLER	837	Barren	
TOP SALT	970	Barren	
BASE SALT	4,280	Barren	
DELAWARE	4,580	Oil	
CHERRY CANYON	5,658	Oil	
BRUSHY CANYON	7,065	Oil	
BONE SPRING	8,435	Oil	
1ST BONE SPRING SAND	9,560	Oil	
KOP	9,818	Oil	
2ND BONE SPRING SAND	10,210	Oil	
2nd Bone Spring A sand Target ( 0 feet Vertical section)	10,390	Oil	
LANDING POINT (END OF CURVE)	10,396	Oil	
TD HORIZONTAL HOLE (END OF WELL)	10,350	Oil	

\*H2S, water flows, loss of circulation, abnormal pressures, etc.

## Devon Energy, Boundary Raider 6 Fed 1H

### 2. Casing Program

Hole Size	Casing Interval		Csg. Size	Weight (lbs)	Grade	Conn	SF Collapse	SF Burst	SF Tension
	From	To							
17.5"	0	1,000'	13.375"	48	H-40	STC	1.67	2.66	2.76
12.25"	0	4,600'	9.625"	40	J-55	LTC	1.22	1.83	2.26
8.75"	0	15,300'	5.5"	17	P-110	BTC	4.76	1.20	1.40
BLM Minimum Safety Factor							1.125	1.00	1.6 Dry 1.8 Wet

All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.h

Must have table for contingency casing

	Y or N
Is casing new? If used, attach certification as required in Onshore Order #1	Y
Does casing meet API specifications? If no, attach casing specification sheet.	Y
Is premium or uncommon casing planned? If yes attach casing specification sheet.	N
Does the above casing design meet or exceed BLM's minimum standards? If not provide justification (loading assumptions, casing design criteria).	Y
Will the intermediate pipe be kept at a minimum 1/3 fluid filled to avoid approaching the collapse pressure rating of the casing?	Y
<b>Is well located within Capitan Reef?</b>	
If yes, does production casing cement tie back a minimum of 50' above the Reef?	N
Is well within the designated 4 string boundary.	
<b>Is well located in SOPA but not in R-111-P?</b>	
If yes, are the first 2 strings cemented to surface and 3 <sup>rd</sup> string cement tied back 500' into previous casing?	N
<b>Is well located in R-111-P and SOPA?</b>	
If yes, are the first three strings cemented to surface?	N
Is 2 <sup>nd</sup> string set 100' to 600' below the base of salt?	
<b>Is well located in high Cave/Karst?</b>	
If yes, are there two strings cemented to surface?	N
(For 2 string wells) If yes, is there a contingency casing if lost circulation occurs?	
<b>Is well located in critical Cave/Karst?</b>	
If yes, are there three strings cemented to surface?	N

## Devon Energy, Boundary Raider 6 Fed 1H

### 3. Cementing Program

Casing	# Sks	Wt. lb/gal	H:O gal/sk	Yld ft/sack	500# Comp. Strength (hours)	Slurry Description
Surf.	410	13.5	9.07	1.72	12	Lead: Class C Cement + 4% Bentonite Gel + 0.125 lbs/sack Poly-E-Flake
	560	14.8	6.32	1.33	7	Tail: Class C Cement + 0.125 lbs/sack Poly-E-Flake
Inter.	980	12.9	9.81	1.85	17	Lead: (65:35) Class C Cement: Poz (Fly Ash): 6% BWOC Bentonite + 5% BWOW Sodium Chloride + 0.125 lbs/sack Poly-E-Flake
	430	14.8	6.32	1.33	6	Tail: Class C Cement + 0.125 lbs/sack Poly-E-Flake
Prod.	780	12.5	10.86	1.96	30	1 <sup>st</sup> Lead: (65:35) Class H Cement: Poz (Fly Ash) + 6% BWOC Bentonite + 0.25% BWOC HR-601 + 0.125 lbs/sack Poly-E-Flake
	1420	14.5	5.31	1.2	25	1 <sup>st</sup> Tail: (50:50) Class H Cement: Poz (Fly Ash) + 0.5% bwoc HALAD-344 + 0.4% bwoc CFR-3 + 0.2% BWOC HR-601 + 2% bwoc Bentonite
	DV/ECP Tool 5000'					
	100	11	14.81	2.55	22	2 <sup>nd</sup> stage Lead: Tuned Light® Cement + 0.125 lb/sk Pol-E-Flake
	120	14.8	6.32	1.33	6	2 <sup>nd</sup> stage Tail: Class C Cement + 0.125 lbs/sack Poly-E-Flake

See COA

DV tool depth(s) will be adjusted based on hole conditions and cement volumes will be adjusted proportionally. DV tool will be set a minimum of 50 feet below previous casing and a minimum of 200 feet above current shoe. Lab reports with the 500 psi compressive strength time for the cement will be onsite for review.

Casing String	TOC	% Excess
Surface	0'	100%
Intermediate	0'	75%
Production	1 <sup>st</sup> Stage = 5000' / 2 <sup>nd</sup> Stage = 3600'	25%

**Devon Energy, Boundary Raider 6 Fed 1H**

**4. Pressure Control Equipment**

N	A variance is requested for the use of a diverter on the surface casing. See attached for schematic.
---	--

BOP installed and tested before drilling which hole?	Size?	Min. Required WP	Type	✓	Tested to:
12-1/4"	13-5/8"	3M	Annular	x	50% of working pressure
			Blind Ram		
			Pipe Ram		
			Double Ram	x	
			Other*		
8-3/4"	13-5/8"	3M	Annular	x	50% testing pressure
			Blind Ram		
			Pipe Ram		
			Double Ram	x	
			Other*		
			Annular		
			Blind Ram		
			Pipe Ram		
			Double Ram		
			Other*		

\*Specify if additional ram is utilized.

BOP/BOPE will be tested by an independent service company to 250 psi low and the high pressure indicated above per Onshore Order 2 requirements. The System may be upgraded to a higher pressure but still tested to the working pressure listed in the table above. If the system is upgraded all the components installed will be functional and tested.

Pipe rams will be operationally checked each 24 hour period. Blind rams will be operationally checked on each trip out of the hole. These checks will be noted on the daily tour sheets. Other accessories to the BOP equipment will include a Kelly cock and floor safety valve (inside BOP) and choke lines and choke manifold. See attached schematics.

Y	Formation integrity test will be performed per Onshore Order #2. On Exploratory wells or on that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.i.
---	--

**Devon Energy, Boundary Raider 6 Fed 1H**

*See COA*

Y	A variance is requested for the use of a flexible choke line from the BOP to Choke Manifold. See attached for specs and hydrostatic test chart.
Y	Are anchors required by manufacturer?
Y	<p>A multibowl wellhead is being used. The BOP will be tested per Onshore Order #2 after installation on the surface casing which will cover testing requirements for a maximum of 30 days. If any seal subject to test pressure is broken the system must be tested.</p> <p>Devon proposes using a multi-bowl wellhead assembly (FMC Uni-head). This assembly will only be tested when installed on the surface casing. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be 3000 (3M) psi.</p> <ul style="list-style-type: none"> <li>• Wellhead will be installed by FMC's representatives.</li> <li>• If the welding is performed by a third party, the FMC's representative will monitor the temperature to verify that it does not exceed the maximum temperature of the seal.</li> <li>• FMC representative will install the test plug for the initial BOP test.</li> <li>• FMC will install a solid steel body pack-off to completely isolate the lower head after cementing intermediate casing. After installation of the pack-off, the pack-off and the lower flange will be tested to 5M, as shown on the attached schematic. Everything above the pack-off will not have been altered whatsoever from the initial nipple up. Therefore the BOP components will not be retested at that time.</li> <li>• If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head will be cut and top out operations will be conducted.</li> <li>• Devon will pressure test all seals above and below the mandrel (but still above the casing) to full working pressure rating.</li> <li>• Devon will test the casing to 0.22 psi/ft or 1500 psi, whichever is greater, as per Onshore Order #2.</li> </ul> <p>After running the 13-3/8" surface casing, a 13-5/8" BOP/BOPE system with a minimum rating of 3M will be installed on the FMC Uni-head wellhead system and will undergo a 250 psi low pressure test followed by a 3,000 psi high pressure test. The 3,000 psi high and 250 psi low test will cover testing requirements a maximum of 30 days, as per Onshore Order #2. If the well is not complete within 30 days of this BOP test, another full BOP test will be conducted, as per Onshore Order #2.</p> <p>After running the 9-5/8' intermediate casing with a mandrel hanger, the 13-5/8" BOP/BOPE system with a minimum rating of 3M will already be installed on the FMC Uni-head.</p> <p>The pipe rams will be operated and checked each 24 hour period and each time the drill pipe is out of the hole. These tests will be logged in the daily driller's log. A 2" kill line and 3" choke line will be incorporated into the drilling spool below the ram BOP. In addition to the rams and annular preventer, additional BOP accessories include a kelly cock, floor safety valve, choke lines, and choke manifold rated at 3,000 psi WP.</p>

*See COA*

**Devon Energy, Boundary Raider 6 Fed 1H**

	Devon requests a variance to use a flexible line with flanged ends between the BOP and the choke manifold (choke line). The line will be kept as straight as possible with minimal turns
	See attached schematic.

**5. Mud Program**

Depth		Type	Weight (ppg)	Viscosity	Water Loss
From	To				
0	1,000'	FW Gel	8.6-8.8	28-34	N/C
1,000'	4,600'	Saturated Brine	10.0-10.2	28-34	N/C
4,600'	15,300'	Cut Brine	8.5-9.3	28-34	N/C

Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept on location at all times.

What will be used to monitor the loss or gain of fluid?	PVT/Pason/Visual Monitoring
---	-----------------------------

**6. Logging and Testing Procedures**

Logging, Coring and Testing	
x	Will run GR/CNL from TD to surface (horizontal well – vertical portion of hole). Stated logs run will be in the Completion Report and submitted to the BLM.
	No Logs are planned based on well control or offset log information.
	Drill stem test? If yes, explain
	Coring? If yes, explain

Additional logs planned	Interval
Resistivity	Int. shoe to KOP
Density	Int. shoe to KOP
X CBL	Production casing
X Mud log	Intermediate shoe to TD
PEX	

Devon Energy, Boundary Raider 6 Fed 1H

7. Drilling Conditions

Condition	Specify what type and where?
BH Pressure at deepest TVD	4678 psi
Abnormal Temperature	No

Mitigation measure for abnormal conditions. Describe. Lost circulation material/sweeps/mud scavengers.

See  
COA

Hydrogen Sulfide (H2S) monitors will be installed prior to drilling out the surface shoe. If H2S is detected in concentrations greater than 100 ppm, the operator will comply with the provisions of Onshore Oil and Gas Order #6. If Hydrogen Sulfide is encountered, measured values and formations will be provided to the BLM.	
N	H2S is present
Y	H2S Plan attached

8. Other facets of operation


Is this a walking operation? No.

Will be pre-setting casing? No.

Attachments

Directional Plan

Other, describe



PRIMARY MODE

**DEVON ENERGY**  
 ARTESIA  
 S.E.N.M  
 13 3/8 X 9 5/8

QUOTE LAYOUT  
 F18648  
 REF: DM100161737  
 DM100151315

**PRIVATE AND CONFIDENTIAL**  
 THIS DOCUMENT AND ALL THE INFORMATION CONTAINED HEREIN ARE THE CONFIDENTIAL AND EXCLUSIVE PROPERTY OF FMC TECHNOLOGIES AND MAY NOT BE REPRODUCED, COPIED, DISCLOSED OR MADE PUBLIC IN ANY MANNER PRIOR TO EXPRESS WRITTEN AUTHORIZATION BY FMC TECHNOLOGIES. THIS DOCUMENT IS ACCEPTED BY RECIPIENT PURSUANT TO AGREEMENT TO THE FOREGOING AND MUST BE RETURNED UPON DEMAND.  
 MANUFACTURER AGREES THAT ARTICLES MADE IN ACCORDANCE WITH THIS DOCUMENT SHALL BE CONSIDERED FMC TECHNOLOGIES DESIGN AND THAT IDENTICAL ARTICLES OR PARTS THEREOF SHALL NOT BE MANUFACTURED FOR THE USE OR SALE BY MANUFACTURER OR ANY OTHER PERSON WITHOUT THE PRIOR EXPRESS WRITTEN AUTHORIZATION BY FMC TECHNOLOGIES


REVISIONS	DESCRIPTION
A 05-08-13	
B 1-22-14	
C 5-13-14	

SURFACE WELLHEAD LAYOUT  
 UNIHEAD, UH-1,SOW,  
 DEVON ENERGY, ODESSA

DRAWN BY	K. VLI	05-08-13
DRAFTING REVIEW	Z. MARQUEZ	05-08-13
DESIGN REVIEW	K. TAHA	05-08-13
APPROVED BY	R. HAMILTON	05-08-13

**FMC Technologies**

DRAWING NUMBER  
**DM100161771-2A**



CONTINGENCY MODE

DEVON ENERGY

ARTESIA


S.E.N.M

13 3/8 X 9 5/8

QUOTE LAYOUT  
F18648  
REF: DM100161737  
DM100151315

<p><b>PRIVATE AND CONFIDENTIAL</b></p> <p>THIS DOCUMENT AND ALL THE INFORMATION CONTAINED HEREIN ARE THE CONFIDENTIAL AND EXCLUSIVE PROPERTY OF FMC TECHNOLOGIES AND MAY NOT BE REPRODUCED, USED, DISCLOSED, OR MADE PUBLIC IN ANY MANNER PRIOR TO EXPRESS WRITTEN AUTHORIZATION BY FMC TECHNOLOGIES. THIS DOCUMENT IS ACCEPTED BY RECIPIENT PURSUANT TO AGREEMENT TO THE FOREGOING, AND MUST BE RETURNED UPON DEMAND.</p> <p>MANUFACTURER AGREES THAT ARTICLES MADE IN ACCORDANCE WITH THIS DOCUMENT SHALL BE CONSIDERED FMC TECHNOLOGIES' DESIGN AND THAT IDENTICAL ARTICLES OR PARTS THEREOF SHALL NOT BE MANUFACTURED FOR THE USE OR SALE BY MANUFACTURER OR ANY OTHER PERSON WITHOUT THE PRIOR EXPRESS WRITTEN AUTHORIZATION BY FMC TECHNOLOGIES.</p>	<p>REVISIONS</p> <p>A 05-08-13</p> <p>B 1-22-14</p> <p>C 5-13-14</p>	<p>DESCRIPTION</p> <p>SURFACE WELLHEAD LAYOUT UNIHEAD, UH-1, SOW, DEVON ENERGY, ODESSA</p>	<p>DRAWN BY</p> <p>K. VU 05-08-13</p> <p>DRAFTING REVIEW</p> <p>Z. MARQUEZ 05-08-13</p> <p>DESIGN REVIEW</p> <p>K. TAHA 05-08-13</p> <p>APPROVED BY</p> <p>R. HAMILTON 05-08-13</p>	<p><b>FMC Technologies</b></p> <p>DRAWING NUMBER</p> <p>DM100161771-2B</p>

**DEVON ENERGY**  
 Project: Lea County, NM (NAD-83)  
 Site: Boundary Raider 6 Fed  
 Well: 1H  
 Wellbore: OH  
 Design: Plan #1



Azimuths to Grid North  
 True North: -0.33°  
 Magnetic North: 7.08°  
 Magnetic Field  
 Strength: 48288.8snT  
 Dip Angle: 60.17°  
 Date: 10/6/2014  
 Model: BSGM2014

PROJECT DETAILS: Lea County, NM (NAD-83)  
 Geodetic System: US State Plane 1983  
 Datum: North American Datum 1983  
 Ellipsoid: GRS 1980  
 Zone: New Mexico Eastern Zone

**DESIGN TARGET DETAILS**


Name	TVD	+N/-S	+E/-W	Northing	Easting	Latitude	Longitude
SHL (BR6F 1H)	0.00	5138.10	-376.67	482786.34	733702.00	32° 19' 32.574 N	103° 42' 38.061 W
PBHL (BR6F 1H)	10350.00	5138.10	-376.67	487922.44	733325.33	32° 20' 23.419 N	103° 42' 42.103 W

**SECTION DETAILS**

Sec	MD	Intc	Azi	TVD	+N/-S	+E/-W	Dleg	TFace	VFace	Annotation
1	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	KOP 10° DLS
2	9823.07	0.00	0.00	9823.07	0.00	0.00	0.00	0.00	0.00	LP
3	10728.84	90.58	355.81	10396.00	-42.33	10.00	355.81	578.72	578.72	TD
4	15300.24	90.58	355.81	10350.00	5136.10	-376.67	0.00	0.00	5149.89	TD

**FORMATION TOP DETAILS**

TVDPPath	MDPath	Formation	DipAngle	DipDir
837.00	837.00	Rustler	0.00	
970.00	970.00	Top Salt	0.00	
4280.00	4280.00	Base Salt	0.00	
4580.00	4580.00	Delaware	0.00	
5658.00	5658.00	Cherry Canyon	0.00	
7065.00	7065.00	Brushy Canyon	0.00	
8435.00	8435.00	1st BS SS	0.00	
9560.00	9560.00	2nd BS SS	0.00	
10251.00	10306.28		0.00	



Vertical Section at 355.81° (600 usf/in)



**LEAM DRILLING SYSTEMS LLC**  
 2010 East Davis, Conroe, Texas 77301  
 Phone: 936/756-7577, Fax 936/756-7595

Plan: Plan #1 (H/OH)  
 Boundary Raider 6 Fed  
 Created By: Brady Deaver  
 Date: 13:38, October 06 2014  
 Approved: \_\_\_\_\_  
 Date: \_\_\_\_\_