

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-025-08470
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator V-F PETROLEUM INC.		6. State Oil & Gas Lease No. VB-1913-0001
3. Address of Operator P.O. Box 1889, Midland, Texas 79702		7. Lease Name or Unit Agreement Name State BU
4. Well Location Unit Letter N : 660 feet from the South line and 1,980 feet from the West line Section 2 Township 22-S Range 34-E NMPM Lea County		8. Well Number 1
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3,585' GR		9. OGRID Number 24010
		10. Pool name or Wildcat SAN SIMON; YATES, WEST

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ **INT TO PA**
TEMPORARILY ABANDON ☐ **P&A NR**
PULL OR ALTER CASING ☐ **P&A R**
DOWNHOLE COMMINGLE ☐
OTHER: _____

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS ☐ P AND A ☒
CASING/CEMENT JOB ☐
OTHER: _____

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

04/13/16 Set CIBP @ 3,575'. Pump 25 sx CMT on top of CIBP. Circulate hole w/ 10 lb mud. Pressure test CSG to 500#. Pump 25 sx CMT plug from 2,000' - 1,625'. Pull out of hole w/tbg. Run in hole w/3.62 jet cutter. Shot at 1,400'. Tried to pull CSG. Could not. Pump 25 sx CMT plug from 1,450' to 1,076'. Perf @ 378'. Pump 98 sx CMT, circulate to surface.

04/14/16 CMT in 4 1/2" CSG @ 90'. CMT between 4 1/2' & 8 5/8" @ surface. Spot 10 sx CMT to fill 4 1/2" CSG to surface. Cut WH off. Install dry hole marker.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE *Eric Sprinkle* TITLE Petroleum Engineer DATE 04/19/2016

Type or print name Eric Sprinkle E-mail address: eric@vfpetroleum.com PHONE: 432-683-3344

For State Use Only

APPROVED BY: *Mark Whitman* TITLE Petroleum Engr. Specialist DATE 4-25-2016

Conditions of Approval (if any):

APR 26 2016