

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. Oil Cons. Division
1625 N. French Dr.
Hobbs, NM 88240

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Pogo Producing Company

3. Address and Telephone No.

P. O. Box 10340, Midland, TX 79702-7340 432-685-8100

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1650' FSL & 330' FWL, Section 18, T22S, R32E

5. Lease Designation and Serial No.

NM-90587

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Livingston Ridge 18 Fed #6

9. API Well No.

30-025-36295

10. Field and Pool, or Exploratory Area

Livingston Ridge Delaware

11. County or Parish, State

Lea County, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Spud

☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spud & Set Surface Csg - MIRU Patterson #54. Spud well @ 20:00 hrs 07/04/03. Drld 17-1/2" hole to 842'. TD reached @ 19:15 hrs 07/05/03. Ran 19 jts 13-3/8" 48# H-40 LT&C csg. TPGS @ 842'. Cmt'd w/ 740 sks 65:35:6 @ 12.4 ppg followed by 200 sks Cl "C" + 2% CaCl2 @ 14.8 ppg. Circ 160 sks to surface. WOC 18 hrs. Make cut-off. Weld on WH. NU BOP's and test ok.

ACCEPTED FOR RECORD

JUL 18 2003

GARY GOURLEY
PETROLEUM ENGINEER

14. I hereby certify that the foregoing is true and correct

Signed Cathy Timberlin Title Sr. Operation Tech Date 07/16/03

(This space for Federal or State office use)

Approved by _____ Title _____ Date _____
Conditions of approval, if any: K

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side