

Submit 1 Copy To Appropriate District Office
 District I – (575) 393-6161
 1625 N. French Dr., Hobbs, NM 88240
 District II – (575) 748-1283
 811 S. First St., Artesia, NM 88210
 District III – (505) 334-6178
 1000 Rio Brazos Rd., Aztec, NM 87410
 District IV – (505) 476-3460
 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
 Energy, Minerals and Natural Resources
HOBBS OCD
 OIL CONSERVATION DIVISION
 1220 South St. Francis Dr.
 Santa Fe, NM 87505

Form C-103
 Revised July 18, 2013

MAY 18 2016
 RECEIVED

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-025-32855
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>		5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
2. Name of Operator LEGACY RESERVES OPERATING LP		6. State Oil & Gas Lease No. 306443
3. Address of Operator PO BOX 10848, MIDLAND, TX 79702		7. Lease Name or Unit Agreement Name COOPER JAL UNIT
4. Well Location Unit Letter <u>D</u> : <u>825</u> feet from the <u>NORTH</u> line and <u>330</u> feet from the <u>WEST</u> line Section <u>25</u> Township <u>24S</u> Range <u>36E</u> NMPM County <u>LEA</u>		8. Well Number 415
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3307' GL		9. OGRID Number 240974
10. Pool name or Wildcat Jalmat; T-Y-7R/Langlie Mattix;7R-Q-G		

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK <input type="checkbox"/> PLUG AND ABANDON <input type="checkbox"/> TEMPORARILY ABANDON <input checked="" type="checkbox"/> CHANGE PLANS <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> MULTIPLE COMPL <input type="checkbox"/> DOWNHOLE COMMINGLE <input type="checkbox"/> CLOSED-LOOP SYSTEM <input type="checkbox"/> OTHER: <input type="checkbox"/>		SUBSEQUENT REPORT OF: REMEDIAL WORK <input type="checkbox"/> ALTERING CASING <input type="checkbox"/> COMMENCE DRILLING OPNS. <input type="checkbox"/> P AND A <input type="checkbox"/> CASING/CEMENT JOB <input type="checkbox"/> OTHER: <input type="checkbox"/>	
---	--	---	--

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

The well is uneconomic to produce at this time. Because of the current economic conditions at this time all future development plans for the field are on hold. When we increase our injection well density this well will benefit greatly from the increased movement of fluids. We are requesting to be granted a 5yr TA status for this well.

3 YEARS / 35'

Procedure:

Pull out and lay down production equipment. Set CIBP @ 2925' and cap with 10' cement. Pressure test.

Condition of Approval: notify

OCD Hobbs office 24 hours

prior of running MIT Test & Chart

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE [Signature] TITLE OPERATIONS ENGINEER DATE 05/16/2016

Type or print name JOHN SAENZ E-mail address: jsaenz@legacylp.com PHONE: 432-689-5200

For State Use Only

APPROVED BY: [Signature] TITLE Dist. Supervisor DATE 5/20/2016

Conditions of Approval (if any):

Legacy Reserves
DAILY OPERATIONS REPORT

COOPER JAL UNIT # 415

Printed May 9, 2016 Page 1 of 1

COOPER JAL UNIT # 415

LEA Co., NM

BOLO ID: 300658.19.10

Zone:

Rod part - will not fix due to economics. TA well.

Dec 11, 2015 Friday (Day 1)

Anchors tested.

Daily Cost: \$1,134

Cum. Cost: \$1,134

Feb 10, 2016 Wednesday (Day 2)

MIRU. Unhung well, POOH, laying down rods. Laid down pol rod and liner. 48 - 1", 36 - 7/8. 7/8 pin break.

Daily Cost: \$1,050

Cum. Cost: \$2,184

Feb 11, 2016 Thursday (Day 3)

Opened well up, unflanged wellhead. NU BOP. Swabbed tubing. Pulled 52 jts of tubing to rod part. Latched on to rods, unset pump. POOH and laid down 34 - 7/8 rods, 24 - 1 1/2 kbars and pump. Pulled the rest of tbg out, laid down TAC. RU wireline, RIH with gauge ring. POOH then RIH and set CIBP at 2925' with 10' of cmt. RIH with 55 jts opened ended. Laid down 60 jts. Secured well, shut down.

Daily Cost: \$6,608

Cum. Cost: \$8,792

Feb 12, 2016 Friday (Day 4)

Drove to location, open well up. Rigged up pump truck on tubing. Circulated 110bbls of packer fluid up the casing. Then tied truck to casing and pressured up to 550 psi. Ran a chart for thirty minutes. Held good. RD pump truck, opened well up. Pulled and laid down 48 jts of tubing. Flanged up wellhead with 8 x 2 7/8 sub. Rigged down, cleaned location. Shut down until Tuesday.

Daily Cost: \$4,782

Cum. Cost: \$13,574

WELLBORE SCHEMATIC AND HISTORY

CURRENT COMPLETION SCHEMATIC	LEASE NAME Cooper Jal Unit	WELL NO. 415
	STATUS: Active Oil	API# 30-025-32855
	LOCATION: 625 FNL & 330 FWL, Sec 25, T - 24S, R - 36E; Lee County, New Mexico	
	SPUD DATE: 05/31/95 TD 3825	KB 3,322 DF
	INT. COMP. DATE: 07/30/95 PBDT 3784	GL 3,307
	ELECTRIC LOGS:	GEOLOGICAL DATA
	Temperature Survey (6-6-95 Halliburton)	CORES, DST'S or MUD LOGS:
	SDL - DSN - CSNG from 3830 - 400' (6-5-95 Halliburton)	
	DDL - MSFL - Sonic from 3830 - 2700' (6-5-95 Halliburton)	
	HYDROCARBON BEARING ZONE DEPTH TOPS:	
	Yates @ 3032'	7-Rivers @ 3241'
		Queen @ 3640'
	CASING PROFILE	
	SURF. 8 5/8" - 24#, WC-50, ST&C set@ 420'. Cmt'd w/250 sxs - circ cmt to surface.	
	PROD. 5 1/2" - 15.5#, WC-50, LT&C set@ 3825'. Cmt'd w/7250 sxs - TOC @ 1150' from surface by Temperature Survey.	
	LINER: None	
	CURRENT PERFORATION DATA	
	CSG. PERFS:	OPEN HOLE :
	12-Jun-95 Perf'd Langlie Mattix 1/3540 - 43', 3556 - 62', 3640 - 46', 3706 - 10' w/ 4 spt	
	12-Jun-95 Perf'd Jalmat 1/ 3078 - 3090' w/ 4 spt (56 holes total)	
	30-Jul-96 Perf'd Jalmat 1/ 3038 - 48', 3054 - 58', 3111 - 20', 3154 - 58', 3302 - 04', & 3374 - 78' w/ 4 spt (156 holes total).	
	11-Apr-07 Perf'd Queen 1/ 3774 - 78', 3752 - 55', 3736 - 40', 3724 - 27', 3714 - 16' & 3700 - 03'; Perf'd U-7-R 1/ 3508 - 15'; Perf'd Yates 1/ 3302 - 05', 3334 - 40', 3222 - 26', 3173 - 77', 3164 - 67' & 3136 - 40', 50 feet.	
	TUBING DETAIL	
	9/13/11	ROD DETAIL
	9/14/11	
	Length (ft)	Detail
	2800	89 2 7/8", 6.5# Super Max tbg
	3	1 2 7/8" x 5 1/2" TAC
	940	30 2 7/8", 6.5# Super Max tbg
	1	1 2 7/8" SN
	4	1 4" Perf Sub w/ Bull Plug
	31	1 2 7/8" OEMA
	3779	
	Length (ft)	Detail
	20	1 26' x 1 1/4" polish rod w/ 7/8" Pin
	0	1 1 1/4" x 1 1/2" x 14' liner
	12	3 2', 4', 6' - 1" pony rods
	1225	49 1" steel rods
	1850	74 7/8" K bars w/ On/Off Tool
	600	24 1 1/2" K bars w/ On/Off Tool
	20	1 2 1/2" x 2" X 20' RHBC - HVR w/ 6' GA
	0	1 1 1/4" x 1' Strainer Nipple
	3727	btm
	WELL HISTORY SUMMARY	
	12-Jun-95 Perf'd L. M. (Queen) 1/ 3540 - 3710'. Acid'd w/ 2,000 gals 7 1/2% NEFE HCL & Frac'd w/ 43,600 gals 35# XL 2% KCl carrying 150,000#s 16/30 brady sand. Perf'd Yates 1/ 3076 - 90'. Acid'd w/ 3,000 gals 7 1/2% NEFE HCL & Frac'd w/ 43,000 gals 35# XL 2% KCl carrying 220,000#s sand. IP=46 bopd, 42 bwpd, & 40 Mcfgpd (pumping)	
	30-Jul-96 Perf'd Jalmat (Yates) 1/ 3038 - 48', 3054 - 58', 3111 - 20', 3154 - 58', 3302 - 04', & 3374 - 78' w/ 4 spt (156 holes). Acid'd perfs 3111 - 3378' w/ 1,800 gals 15% NEFE HCL dropping 130 7/8" RCN Ball Sealers. AIR= 10 bpm @ 1900 psig. ISIP= vacuum. Acid'd perfs 3038 - 3058' with 1,200 gals 15% NEFE HCL dropping 90 7/8" RCN Ball Sealers. AIR= 10 bpm at 1950 psig. ISIP= 570 psi. P5min= vacuum. Commingle all perfs 3038 - 3710'. Before WO: 8 bopd, 50 bwpd, & 20 mcfcpd. After WO: 14 bopd, 52 bwpd & 29 Mcfgpd.	
	11-Mar-97 Replaced 67 rods. Returned well to production.	
	24-Apr-97 Replaced 67 rods. Returned well to production.	
	24-Apr-97 Replaced PC pump with conventional rod pump. Returned well to production.	
	12-Apr-99 C/O fill from 3711 - 3720' (9'). Replaced 50 jts tbg & 40 3/4" rod boxes. Returned well to production.	
	27-Sep-01 Replaced rod pump. Returned to production.	
	11-Apr-07 POOH w/ rods, pump & rods. RIH w/ 4 3/4" Mill Tooth bit, on 2 7/8" work string. Tagged at 3673'. C/O to 3730'. Circ'd formation sa scale, iron sulfite & metal. C/O 1/ 3725' to 3784'. recovered formation sand, scale iron sulfite, BS & metal. RIH with 5 1/2" AST PKI set at 2994', test casing to 500# - okay. Perf'd Queen 1/ 3774 - 78', 3752 - 55', 3736 - 40', 3724 - 27', 14 - 16' & 3700 - 03'; Perf'd Upp 7-Rivers 1/ 3508 - 15', Perf'd Yates 1/ 3302 - 05', 34 - 40', 3222 - 26', 3173 - 77', 64 - 67' & 36 - 40', 50 feet, 150 holes. CO2 Foam Acid Frac the Langlie Mattix (3508 - 3778') w/ 160 bbls 15% NEFE acid + 44 Tons CO2 diverted w/ 6000# rock salt. AIR= 13.6 BPM. Pmax= 5001#, Pavg= 3438'. ISIP= 471#. CO2 Foam Acid Frac Jalmat (3302 - 3378') w/ 262 bbls 15% NEFE acid + 131 Tons CO2 diverting w/ 9000# RS. AIR= 18.3 bpm. Pmax= 5090#, Pavg= 4151#. ISIP= 823#. Next day SITP= 700 psig. Flow test for 9 hours: 29 bbls, show of oil and gas. FTP= 525#. SION. Next day SITP= 700#. Flow test for 9 hours: 38 bbls fluid w/ 5% oil cut z77 gas show. Ending FTP= 100#. SION. Next day, killed well. POOH w/ frac tubing & PKR. RIH Prod string. PWOP.	
	05-Jun-09 POOH w/ rods, pump & tubing. RIH w/ Gray Wireline Tag Bar. Tagged @ 3784'. RIH with Pressure Gradient Tool, took reading ev 500'. Hydrotest tubing in hole to 7000#. RIH with pump and rods. Pressure @ 3,000' = 316 psig. PWOP.	
	19-Aug-10 POOH with fods, pump and tubing. Hydrotest tubing to 7,000 psig - found hole on joint above SN and collar leak on 10th joint. RIH with pump and rods. Load tubing with 13 bbls water and test pump to 500 psig - good pump action. PWOP.	
	25-Jul-11 POOH with rods and pump. Replaced pump. RIH with pump and rods. PWOP.	
	12-Sep-11 POOH w/ rods, pump & tubing. Ran Press Gradient Survey. Tagged @ 3784'. Hydrotest tubing to 7,000#. RIH w/ plunger & rods. F	
	11-Sep-12 POOH with parted 107th - 7/8" (uncrewed pin). Replaced bad pin. PWOP.	

Surface Csg

Hole Size: 8 5/8 in

Csg. Size: 8 5/8 in

Set @: 420 ft

Sxs Cmt: 250

Circ: Yes

TOC @: surf

TOC by: circ

Production Csg

Hole Size: 7 7/8 in

Csg. Size: 5 1/2 in

Set @: 3825 ft

Sxs Cmt: 725

Circ: Yes

TOC @: 1150 ft surf.

TOC by: TS

New Perfs

3038'-48'

3054'-58'

3076'-90'

3111'-20'

3136'-40'

3173'-77'

3222'-26'

2234'-40'

3302'-05'

3508'-15'

3540'-43'

3556'-62'

Queen @ 3640'

3640'-46'

3700'-03'

3714'-16'

3724'-27'

3736'-40'

3752'-55'

3774'-78'

PBDT: 3784 ft

TD: 3825 ft