

Submit To Appropriate District Office Two Copies District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505		State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505			Form C-105 Revised August 1, 2011		
1. WELL API NO. 30-025-42904							
2. Type of Lease ☒ STATE ☐ FEE ☐ FED/INDIAN							
3. State Oil & Gas Lease No.							
WELL COMPLETION OR RECOMPLETION REPORT AND LOG							
4. Reason for filing: ☒ COMPLETION REPORT (Fill in boxes #1 through #31 for State and Fee wells only) ☐ C-144 CLOSURE ATTACHMENT (Fill in boxes #1 through #9, #15 Date Rig Released and #32 and/or #33; attach this and the plat to the C-144 closure report in accordance with 19.15.17.13.K NMAC)				5. Lease Name or Unit Agreement Name Warbler State Com 6. Well Number: 2Y			
7. Type of Completion: ☒ NEW WELL ☐ WORKOVER ☐ DEEPENING ☐ PLUGBACK ☐ DIFFERENT RESERVOIR ☐ OTHER							
8. Name of Operator COG Operating LLC				9. OGRID 229137			
10. Address of Operator 2208 W. Main Street Artesia, NM 88210				11. Pool name or Wildcat WC-025 G-06 S213323D; Bone Spring			
12. Location	Unit Ltr	Section	Township	Range	Lot	Feet from the	
Surface:	C	28	21S	33E		195	
BH:	N	28	21S	33E		340	
13. Date Spudded	14. Date T.D. Reached	15. Date Rig Released		16. Date Completed (Ready to Produce)		17. Elevations (DF and RKB, RT, GR, etc.)	
10/31/15	11/29/15	11/30/15		4/29/16		3698' GR	
18. Total Measured Depth of Well		19. Plug Back Measured Depth		20. Was Directional Survey Made?		21. Type Electric and Other Logs Run	
15362'		15265'		Yes		None	
22. Producing Interval(s), of this completion - Top, Bottom, Name 11082-15225' Bone Spring							
CASING RECORD (Report all strings set in well)							
CASING SIZE	WEIGHT LB./FT.	DEPTH SET		HOLE SIZE		CEMENTING RECORD	
16"	65#	1748'		20"		1350 sx	
11 3/4"	47#	3510'		14 3/4"		1575 sx	
8 5/8"	32#	5330'		10 5/8"		2035 sx (TOC @ 3186')	
5 1/2"	17#	15315'		7 7/8"		2150 sx	
LINER RECORD				TUBING RECORD			
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET	
					2 7/8"	10337'	
						10319'	
26. Perforation record (interval, size, and number) 11082-15165' (1224) 15215-15225' (60)				27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC. DEPTH INTERVAL AMOUNT AND KIND MATERIAL USED 11082-15165' Acdz w/106596 gal 7 1/2%; Frac w/8022190# sand & 11,424,966 gal fluid			
PRODUCTION							
Date First Production		Production Method (Flowing, gas lift, pumping - Size and type pump)			Well Status (Prod. or Shut-in)		
5/3/16		Flowing			Producing		
Date of Test	Hours Tested	Choke Size	Prod'n For Test Period	Oil - Bbl	Gas - MCF	Water - Bbl.	
5/16/16	24			578	660	2701	
Flow Tubing Press.	Casing Pressure	Calculated 24-Hour Rate	Oil - Bbl.	Gas - MCF	Water - Bbl.	Oil Gravity - API - (Corr.)	
550#			578	660	2701		
29. Disposition of Gas (Sold, used for fuel, vented, etc.)					30. Test Witnessed By		
Sold					Tyler Deans		
31. List Attachments							
Surveys							
32. If a temporary pit was used at the well, attach a plat with the location of the temporary pit.							
33. If an on-site burial was used at the well, report the exact location of the on-site burial:							
Latitude			Longitude		NAD 1927 1983		
I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief							
Signature		Printed Name:		Title		Date:	
Stormi Davis		Stormi Davis		Regulatory Analyst		5/20/16	
E-mail Address: sdavis@concho.com							

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well and not later than 60 days after completion of closure. When submitted as a completion report, this shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 11, 12 and 26-31 shall be reported for each zone.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico			Northwestern New Mexico	
T. Anhy		T. Canyon	T. Ojo Alamo	T. Penn A"
T. Salt	1757'	T. Strawn	T. Kirtland	T. Penn. "B"
B. Salt	3365'	T. Atoka	T. Fruitland	T. Penn. "C"
T. Yates	3418'	T. Miss	T. Pictured Cliffs	T. Penn. "D"
T. 7 Rivers	3450'	T. Devonian	T. Cliff House	T. Leadville
T. Queen	4305'	T. Silurian	T. Menefee	T. Madison
T. Grayburg		T. Montoya	T. Point Lookout	T. Elbert
T. San Andres		T. Simpson	T. Mancos	T. McCracken
T. Glorieta		T. Rustler 1669'	T. Gallup	T. Ignacio Otzte
T. Paddock		T. Capitan 3514'	Base Greenhorn	T. Granite
T. Blinebry		T. Delaware 5260'	T. Dakota	
T. Tubb		T. Bell Canyon 5269'	T. Morrison	
T. Drinkard		T. Cherry Canyon 5689'	T. Todilto	
T. Abo		T. Brushy Canyon 7487'	T. Entrada	
T. Wolfcamp		T. Bone Springs Lm 8769'	T. Wingate	
T. Penn		T. 1 st Bone Spring 10008'	T. Chinle	
T. Cisco (Bough C)		T. 2 nd Bone Spring 10621'	T. Permian	

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....
No. 2, from.....to.....
No. 3, from.....to.....
No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology