

UNITED STATES
DEPARTMENT OF THE INTERIOR **OCD Hobbs**
BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB NO. 1004-0135
Expires: July 31, 2010

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.

5. Lease Serial No.
NMNM19858

6. If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or No.

SUBMIT IN TRIPLICATE - Other instructions on reverse side.

1. Type of Well
 Oil Well Gas Well Other

2. Name of Operator **EOG RESOURCES INCORPORATED** Contact: **STAN WAGNER**
E-Mail: stan_wagner@eogresources.com

3a. Address **MIDLAND, TX 79702**

3b. Phone No. (include area code)
Ph: 432-686-3689

8. Well Name and No.
HAWK 26 FED 708H ✓

9. API Well No.
30-025-42401-00-X1 ✓

10. Field and Pool, or Exploratory
WOLFCAMP

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
Sec 26 T24S R33E SWSE 0500FSL 1679FEL
32.182588 N Lat, 103.539533 W Lon ✓

11. County or Parish, and State
LEA COUNTY, NM

HOBBS OCD

MAY 27 2016

RECEIVED

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

| TYPE OF SUBMISSION | TYPE OF ACTION | | | |
|---|---|---|--|---|
| <input type="checkbox"/> Notice of Intent | <input type="checkbox"/> Acidize | <input type="checkbox"/> Deepen | <input type="checkbox"/> Production (Start/Resume) | <input type="checkbox"/> Water Shut-Off |
| <input checked="" type="checkbox"/> Subsequent Report | <input type="checkbox"/> Alter Casing | <input type="checkbox"/> Fracture Treat | <input type="checkbox"/> Reclamation | <input type="checkbox"/> Well Integrity |
| <input type="checkbox"/> Final Abandonment Notice | <input type="checkbox"/> Casing Repair | <input type="checkbox"/> New Construction | <input type="checkbox"/> Recomplete | <input checked="" type="checkbox"/> Other |
| | <input type="checkbox"/> Change Plans | <input type="checkbox"/> Plug and Abandon | <input type="checkbox"/> Temporarily Abandon | Change to Original APD |
| | <input type="checkbox"/> Convert to Injection | <input type="checkbox"/> Plug Back | <input type="checkbox"/> Water Disposal | |

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleate horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleation in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

EOG Resources requests and amendment to our approved APD for this well to reflect a change in casing design and our intention to use a multi-bowl wellhead system in the drilling of the well.

Detailed information regarding the changes is attached.

14. I hereby certify that the foregoing is true and correct.

**Electronic Submission #338369 verified by the BLM Well Information System
For EOG RESOURCES INCORPORATED, sent to the Hobbs
Committed to AFMSS for processing by PRISCILLA PEREZ on 05/18/2016 (16KGR0007SE)**

Name (Printed/Typed) **STAN WAGNER** Title **REGULATORY ANALYST**

Signature (Electronic Submission) Date **05/04/2016**

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved By _____ Title _____ Date _____

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office _____

Accepted for Record Only

Accepted for Record Only

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

**** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED ****

KB

KE

EOG RESOURCES, INC.
HAWK 26 FED NO. 708H

1. GEOLOGIC NAME OF SURFACE FORMATION:

Permian

2. ESTIMATED TOPS OF IMPORTANT GEOLOGICAL MARKERS:

| | |
|----------------------------------|---------|
| Rustler | 1,218' |
| Top of Salt | 1,710' |
| Base of Salt / Top Anhydrite | 5,000' |
| Base Anhydrite | 5,248' |
| Lamar | 5,248' |
| Bell Canyon | 5,279' |
| Cherry Canyon | 6,273' |
| Brushy Canyon | 7,725' |
| Bone Spring Lime | 9,250' |
| 1 st Bone Spring Sand | 10,220' |
| 2 nd Bone Spring Lime | 10,670' |
| 2 nd Bone Spring Sand | 10,940' |
| 3 rd Bone Spring Lime | 11,360' |
| 3 rd Bone Spring Sand | 11,960' |
| Wolfcamp | 12,300' |
| TD | 12,500' |

3. ESTIMATED DEPTHS OF ANTICIPATED FRESH WATER, OIL OR GAS:

| | | |
|----------------------------------|---------|-------------|
| Upper Permian Sands | 0- 400' | Fresh Water |
| Cherry Canyon | 6,273' | Oil |
| Brushy Canyon | 7,725' | Oil |
| Bone Spring Lime | 9,250' | Oil |
| 1 st Bone Spring Sand | 10,220' | Oil |
| 2 nd Bone Spring Lime | 10,670' | Oil |
| 2 nd Bone Spring Sand | 10,940' | Oil |
| 3 rd Bone Spring Lime | 11,360' | Oil |
| 3 rd Bone Spring Sand | 11,960' | Oil |
| Wolfcamp | 12,300' | Oil |

No other Formations are expected to give up oil, gas or fresh water in measurable quantities. Surface fresh water sands will be protected by setting 10.75" casing at 1,300' and circulating cement back to surface.

**EOG RESOURCES, INC.
HAWK 26 FED NO. 708H**

4. CASING PROGRAM - NEW

| Hole Size | Interval | Csg OD | Weight | Grade | Conn | DF _{min} Collapse | DF _{min} Burst | DF _{min} Tension |
|-----------|------------------|--------|--------|---------|----------|----------------------------|-------------------------|---------------------------|
| 14.75" | 0 – 1,300' | 10.75" | 40.5# | J55 | STC | 1.125 | 1.25 | 1.60 |
| 9.875" | 0-8,000' | 7.625" | 29.7# | HCP-110 | LTC | 1.125 | 1.25 | 1.60 |
| 8.75" | 8,000' – 11,400' | 7.625" | 29.7# | HCP-110 | Ultra FJ | 1.125 | 1.25 | 1.60 |
| 6.75" | 0'-17,818' | 5.5" | 23# | HCP-110 | ULT SFII | 1.125 | 1.25 | 1.60 |

Variance is requested to wave the centralizer requirements for the 7-5/8" FJ casing in the 8-3/4" hole size. An expansion additive will be utilized, in the cement slurry, for the entire length of the 8-3/4" hole interval to maximize cement bond and zonal isolation. Centralizers will be placed in the 9-7/8" hole interval at least one every third joint.

Variance is also requested to wave any centralizer requirements for the 5-1/2" FJ casing in the 6-3/4" hole size. An expansion additive will be utilized, in the cement slurry, for the entire length of the 6-3/4" hole interval to maximize cement bond and zonal isolation.

Cementing Program:

| Depth | No. Sacks | Wt. ppg | Yld Ft ³ /ft | Mix Water Gal/sk | Slurry Description |
|-------------------|-----------|---------|-------------------------|------------------|---|
| 10-3/4" 1,300' | 700 | 13.5 | 1.73 | 9.13 | Class C + 4.0% Bentonite + 0.6% CD-32 + 0.5% CaCl ₂ + 0.25 lb/sk Cello-Flake (TOC @ Surface) |
| | 300 | 14.8 | 1.34 | 6.34 | Class C + 0.6% FL-62 + 0.25 lb/sk Cello-Flake + 0.2% Sodium Metasilicate |
| 7-5/8" 11,400' | 780 | 9.0 | 2.86 | 11.14 | D195 LiteFill (Beads) + 0.50% Retarder + D046 Antifoam |
| | 525 | 13.5 | 1.55 | 7.47 | 50:50 Class H:Poz + 0.10% D065 + 0.20% D112 + 10% D154 + 2.0% D174 + 0.40% D800 |
| 5-1/2" 17,818' | 575 | 14.1 | 1.26 | 5.80 | Class H + 0.1% C-20 + 0.05% CSA-1000 + 0.20% C-49 + 0.40% C-17 |

Note: Cement volumes based on bit size plus at least 25% excess in the open hole plus 10% excess in the cased-hole overlap section.

**EOG RESOURCES, INC.
HAWK 26 FED NO. 708H**

5. MINIMUM SPECIFICATIONS FOR PRESSURE CONTROL:

Variance is requested to use a co-flex line between the BOP and choke manifold (instead of using a 4" OD steel line).

The minimum blowout preventer equipment (BOPE) shown in Exhibit #1 will consist of a single ram, mud cross and double ram-type (10,000 psi WP) preventer and an annular preventer (5000-psi WP). Both units will be hydraulically operated and the ram-type will be equipped with blind rams on bottom and drill pipe rams on top. All BOPE will be tested in accordance with Onshore Oil & Gas order No. 2.

Before drilling out of the surface casing, the ram-type BOP and accessory equipment will be tested to 5000/ 250 psig and the annular preventer to 5000/ 250 psig. The surface casing will be tested to 1500 psi for 30 minutes.

Before drilling out of the intermediate casing, the ram-type BOP and accessory equipment will be tested to 5000/ 250 psig and the annular preventer to 5000/ 250 psig. The intermediate casing will be tested to 2000 psi for 30 minutes.

Pipe rams will be operationally checked each 24-hour period. Blind rams will be operationally checked on each trip out of the hole. These checks will be noted on the daily tour sheets.

A hydraulically operated choke will be installed prior to drilling out of the intermediate casing shoe.

6. TYPES AND CHARACTERISTICS OF THE PROPOSED MUD SYSTEM:

During this procedure we plan to use a Closed-Loop System and haul contents to the required disposal.

The applicable depths and properties of the drilling fluid systems are as follows.

| Depth | Type | Weight (ppg) | Viscosity | Water Loss |
|------------------------------|-------------|---------------------|------------------|-------------------|
| 0 - 1,300' | Fresh - Gel | 8.6-8.8 | 28-34 | N/c |
| 1,300' - 11,400' | Brine | 8.8-10.0 | 28-34 | N/c |
| 11,400' - 17,818' Lateral | Oil Base | 10.0-11.5 | 58-68 | 3 - 6 |

An electronic pit volume totalizer (PVT) will be utilized on the circulating system, to monitor pit volume, flow rate, pump pressure and stroke rate.

Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept at the wellsite at all times.

**EOG RESOURCES, INC.
HAWK 26 FED NO. 708H**

7. AUXILIARY WELL CONTROL AND MONITORING EQUIPMENT:

- (A) A kelly cock will be kept in the drill string at all times.
- (B) A full opening drill pipe-stabbing valve (inside BOP) with proper drill pipe connections will be on the rig floor at all times.
- (C) H₂S monitoring and detection equipment will be utilized from surface casing point to TD.

8. LOGGING, TESTING AND CORING PROGRAM:

Open-hole logs are not planned for this well.

GR-CCL Will be run in cased hole during completions phase of operations.

9. ABNORMAL CONDITIONS, PRESSURES, TEMPERATURES AND POTENTIAL HAZARDS:

The estimated bottom-hole temperature (BHT) at TD is 170 degrees F with an estimated maximum bottom-hole pressure (BHP) at TD of 7475 psig. No hydrogen sulfide or other hazardous gases or fluids have been encountered, reported or are known to exist at this depth in this area. No major loss circulation zones have been reported in offsetting wells.

10. ANTICIPATED STARTING DATE AND DURATION OF OPERATIONS:

The drilling operation should be finished in approximately one month. If the well is productive, an additional 60-90 days will be required for completion and testing before a decision is made to install permanent facilities.

11. WELLHEAD:

A multi-bowl wellhead system will be utilized.

After running the 10-3/4" surface casing, a 13-5/8" BOP/BOPE system with a minimum working pressure of 5000 psi will be installed on the wellhead system and will be pressure tested to 250 psi low followed by a 5000 psi pressure test. This pressure test will be repeated at least every 30 days, as per Onshore Order No. 2

EOG RESOURCES, INC.
HAWK 26 FED NO. 708H

The minimum working pressure of the BOP and related BOPE required for drilling below the surface casing shoe shall be 5000 psi.

The multi-bowl wellhead will be installed by vendor's representative(s). A copy of the installation instructions for the Stream Flo FBD100 Multi-Bowl WH system has been sent to the NM BLM office in Carlsbad, NM.

The wellhead will be installed by a third party welder while being monitored by WH vendor's representative.

All BOP equipment will be tested utilizing a conventional test plug. Not a cup or J-packer type.

A solid steel body pack-off will be utilized after running and cementing the intermediate casing. After installation the pack-off and lower flange will be pressure tested to 5000 psi. Prior to running the intermediate casing, the rams will be changed out to accommodate the 7-5/8" casing. The bonnet seals will be tested to 1500 psi. After installing the intermediate casing the casing rams will be removed and replaced with variable bore rams. The remaining BOPE will not be retested after installing the intermediate casing.

Both the surface and intermediate casing strings will be tested as per Onshore Order No. 2 to at least 0.22 psi/ft or 1500 psi, whichever is greater.


Wellhead drawing Attached.

Hawk 26 Fed #708H


Lea County, New Mexico
Proposed Wellbore
Revised 5/4/16
API: 30-025-42401

500' FSL
1679' FEL
Section 26
T-24-S, R-33-E

KB: 3,558'
GL: 3,528'



Lateral:
17,818' MD, 12,500' TVD
Upper Most Perf:
10' FNL & 1388' FEL
Lower Most Perf:
330' FSL & 1394' FEL
BH Location: 230' FSL & 1394' FEL
Section 35
T-24-S, R-33-E



*CONCEPT QUOTE DRAWING

EOG RESOURCES

10-3/4" X 7-5/8" X 5-1/2"
 FBD-100 WELLHEAD SYSTEM
 QUOTE # - 93482

| | | |
|-----|------|---------|
| DWN | BAY | 1/28/16 |
| CHK | | |
| APP | | |
| BY | DATE | |



Worldwide Expertise - Global Strength

DRAWING NO
 WH-15848