

Form 3160-3  
(March 2012)

**CONFIDENTIAL**

AMENDED

**UNORTHODOX  
LOCATION**

FORM APPROVED  
OMB No. 1004-0137  
Expires October 31, 2014

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**APPLICATION FOR PERMIT TO DRILL OR REENTER**

5. Lease Serial No. NMNM92781	
6. If Indian, Allottee or Tribe Name	
7. If Unit or CA Agreement, Name and No. NMNM094480X	
8. Lease Name and Well No. GAUCHO UNIT 29H (30863)	
9. API Well No. 30-025-47335	
10. Field and Pool, or Exploratory WC-025 G-06 S223421L; Bone Spring (97922)	
11. Sec., T. R. M. or Blk. and Survey or Area Sec 20, T22S, R34E	
12. County or Parish LEA	13. State NM
14. Distance in miles and direction from nearest town or post office* Approximately 20 miles SW of Eunice, NM	
15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any) See attached map	16. No. of acres in lease 960 ac
17. Spacing Unit dedicated to this well 160 ac	19. Proposed Depth TVD: 11,382'; MD: 16,576'
18. Distance from proposed location* to nearest well, drilling, completed, applied for, on this lease, ft. See attached map	
21. Elevations (Show whether DF, KDB, RT, GL, etc.) 3,463.8' GL	22. Approximate date work will start* 09/17/2016
23. Estimated duration 45 Days	

**HOBBS OCD**

JUN 30 2016

**RECEIVED**

24. Attachments To Be Pad Drilled With Gaucho Unit 30H

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No.1, must be attached to this form:

- 1. Well plat certified by a registered surveyor.
- 2. A Drilling Plan.
- 3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office).
- 4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above).
- 5. Operator certification
- 6. Such other site specific information and/or plans as may be required by the BLM.

25. Signature 	Name (Printed/Typed) David H. Cook	Date 12/14/2015
-------------------	---------------------------------------	--------------------

Title  
Regulatory Compliance Professional

Approved by (Signature) <b>James A. Amos</b>	Name (Printed/Typed)	Date JUN 24 2016
---	----------------------	---------------------

Title  
**FIELD MANAGER** Office  
**CARLSBAD FIELD OFFICE**

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.  
Conditions of approval, if any, are attached.

**APPROVAL FOR TWO YEARS**

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section States any false, fictitious or fraudulent statements or

take to any department or agency of the United

(Continued on page 2)

See attached NMOCD  
Conditions of Approval

\*(Instructions on page 2)

**APPROVAL SUBJECT TO  
GENERAL REQUIREMENTS  
AND SPECIAL STIPULATIONS  
ATTACHED**

**SEE ATTACHED FOR  
CONDITIONS OF APPROVAL**

*KZ 06/30/16*

Witness Surface Casing

Capitan Controlled Water Basin

## Devon Energy, Gaucho Unit 29H

### Geologic Formations

TVD of target	11,382'	Pilot hole depth	N/A
MD at TD:	16,576'	Deepest expected fresh water:	

### Basin

Formation	Depth (TVD) from KB	Water/Mineral Bearing/Target Zone?	Hazards*
Rustler	1,616	110'	
Salt	1,925	Barren	
Base of Salt	3,700	Barren	
Yates	3,930	Barren	
Delaware	5,244	Oil	
Brushy Canyon	7,400	Oil	
1 <sup>st</sup> Bone Spring Lime	8,524	Oil	
1 <sup>st</sup> Bone Spring Sand	9,539	Oil	
2 <sup>nd</sup> Bone Spring Sand	10,119	Oil	
3 <sup>rd</sup> Bone Spring Sand	11,106	Oil	
Top WCMP	11,408	Oil	

\*H2S, water flows, loss of circulation, abnormal pressures, etc.

Devon Energy, Gaucho Unit 29H

2. Casing Program SEE COA

Hole Size	Casing Interval		Csg. Size	Weight (lbs)	Grade	Conn	SF Collapse	SF Burst	SF Tension
	From	To							
17.5"	0	1,675'	13.375"	54.5	J-55	BTC	1.44	3.48	9.96
12.25"	0	3,400'	9.625"	36	J-55	LTC	1.27	1.99	3.70
5000 12.25"	3,400'	<del>3,850'</del>	9.625"	40	J-55	LTC	1.43	1.97	3.38
8.75"	0	11,000'	7"	29	P-110	BTC	1.87	2.29	3.14
6.125"	10,500'	16,576'	4.5"	13.5	P-110	BTC	2.17	1.48	2.04
BLM Minimum Safety Factor							1.125	1.00	1.6 Dry 1.8 Wet

All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.h

Must have table for contingency casing

	Y or N
Is casing new? If used, attach certification as required in Onshore Order #1	Y
Does casing meet API specifications? If no, attach casing specification sheet.	Y
Is premium or uncommon casing planned? If yes attach casing specification sheet.	N
Does the above casing design meet or exceed BLM's minimum standards? If not provide justification (loading assumptions, casing design criteria).	Y
Will the <u>intermediate pipe be kept at a minimum 1/3 fluid filled to avoid approaching the collapse pressure rating of the casing?</u>	Y
Is well located within Capitan Reef?	<del>Y</del> N
If yes, does <u>production casing cement tie back a minimum of 50' above the Reef?</u>	Y
Is well within the designated 4 string boundary.	
Is well located in SOPA but not in R-111-P?	N
If yes, are the first 2 strings cemented to surface and 3 <sup>rd</sup> string cement tied back 500' into previous casing?	
Is well located in R-111-P and SOPA?	N
If yes, are the first three strings cemented to surface?	
Is 2 <sup>nd</sup> string set 100' to 600' below the base of salt?	
Is well located in high Cave/Karst?	N
If yes, are there two strings cemented to surface?	
(For 2 string wells) If yes, is there a contingency casing if lost circulation occurs?	
Is well located in critical Cave/Karst?	N
If yes, are there three strings cemented to surface?	

Devon Energy, Gaucho Unit 29H

3. Cementing Program

SEE COP

Casing	# Sks	Wt. lb/gal	H <sub>2</sub> O gal/sk	Yld ft <sup>3</sup> /sack	500# Comp. Strength (hours)	Slurry Description
13-3/8" Surface	950	13.5	9.07	1.72	12	Lead: Class C Cement + 4% Bentonite Gel + 0.125 lbs/sack Poly-E-Flake
	550	14.8	6.32	1.33	6	Tail: Class C Cement + 0.125 lbs/sack Poly-E-Flake
9-5/8" Inter.	<u>660</u>	12.9	9.81	<u>1.85</u>	17	Lead: (65:35) Class C Cement: Poz (Fly Ash): 6% BWOC Bentonite + 5% BWOW Sodium Chloride + 0.125 lbs/sack Poly-E-Flake
	<u>430</u>	14.8	6.32	<u>1.33</u>	6	Tail: Class C Cement + 0.125 lbs/sack Poly-E-Flake
7" Int	<u>380</u>	11	14.81	<u>2.55</u>	14	Lead: Tuned Light <sup>®</sup> Cement + 0.125 lb/sk Pol-E-Flake
	<u>400</u>	14.5	5.31	<u>1.2</u>	25	Tail: (50:50) Class H Cement: Poz (Fly Ash) + 0.5% bwoc HALAD-344 + 0.4% bwoc CFR-3 + 0.2% BWOC HR-601 + 2% bwoc Bentonite
4-1/2" Liner	670	14.5	5.31	1.2	25	Tail: (50:50) Class H Cement: Poz (Fly Ash) + 0.5% bwoc HALAD-344 + 0.4% bwoc CFR-3 + 0.2% BWOC HR-601 + 2% bwoc Bentonite

Cement Low!!

Casing String	TOC	% Excess
13-3/8" Surface	0'	100%
9-5/8" Intermediate	0'	75%
7" Intermediate	3350'	25%
4-1/2" Production Liner	10500'	25%

**Devon Energy, Gaucho Unit 29H**

**4. Pressure Control Equipment**

N	A variance is requested for the use of a diverter on the surface casing. See attached for schematic.
---	--

BOP installed and tested before drilling which hole?	Size?	Min. Required WP	Type	✓	Tested to:
12-1/4"	13-5/8"	5M	Annular	x	5M
			Blind Ram		
			Pipe Ram		
			Double Ram	x	
			Other*		
8-3/4"	13-5/8"	5M	Annular	x	5M
			Blind Ram		
			Pipe Ram		
			Double Ram	x	
			Other*		
6-1/8"	13-5/8"	5M	Annular	x	5M
			Blind Ram		
			Pipe Ram		
			Double Ram	x	
			Other*		

\*Specify if additional ram is utilized.

BOP/BOPE will be tested by an independent service company to 250 psi low and the high pressure indicated above per Onshore Order 2 requirements. The System may be upgraded to a higher pressure but still tested to the working pressure listed in the table above. If the system is upgraded all the components installed will be functional and tested.

Pipe rams will be operationally checked each 24 hour period. Blind rams will be operationally checked on each trip out of the hole. These checks will be noted on the daily tour sheets. Other accessories to the BOP equipment will include a Kelly cock and floor safety valve (inside BOP) and choke lines and choke manifold. See attached schematics.

Y	Formation integrity test will be performed per Onshore Order #2. On Exploratory wells or on that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.i.
---	--

Devon Energy, Gaucho Unit 29H

SEE COA

Y	<p><u>A variance is requested for the use of a flexible choke line from the BOP to Choke Manifold. See attached for specs and hydrostatic test chart.</u></p>
Y	<p>Are anchors required by manufacturer?</p>
Y	<p><u>A multibowl wellhead is being used.</u> The BOP will be tested per Onshore Order #2 after installation on the surface casing which will cover testing requirements for a maximum of 30 days. If any seal subject to test pressure is broken the system must be tested.</p> <p>Devon proposes using a multi-bowl wellhead assembly (FMC Uni-head). This assembly will only be tested when installed on the surface casing. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be 5000 (5M) psi.</p> <ul style="list-style-type: none"> <li>• Wellhead will be installed by FMC's representatives.</li> <li>• If the welding is performed by a third party, the FMC's representative will monitor the temperature to verify that it does not exceed the maximum temperature of the seal.</li> <li>• FMC representative will install the test plug for the initial BOP test.</li> <li>• FMC will install a solid steel body pack-off to completely isolate the lower head after cementing intermediate casing. After installation of the pack-off, the pack-off and the lower flange will be tested to 5M, as shown on the attached schematic. Everything above the pack-off will not have been altered whatsoever from the initial nipple up. Therefore the BOP components will not be retested at that time.</li> <li>• If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head will be cut and top out operations will be conducted.</li> <li>• Devon will pressure test all seals above and below the mandrel (but still above the casing) to full working pressure rating.</li> <li>• Devon will test the casing to 0.22 psi/ft or 1500 psi, whichever is greater, as per Onshore Order #2.</li> </ul> <p>After running the 13-3/8" surface casing, a 13-5/8" BOP/BOPE system with a minimum rating of 5M will be installed on the FMC Uni-head wellhead system and will undergo a 250 psi low pressure test followed by a 5,000 psi high pressure test. The 5,000 psi high and 250 psi low test will cover testing requirements a maximum of 30 days, as per Onshore Order #2. If the well is not complete within 30 days of this BOP test, another full BOP test will be conducted, as per Onshore Order #2.</p> <p>After running the 9-5/8' intermediate casing with a mandrel hanger, the 13-5/8" BOP/BOPE system with a minimum rating of 5M will already be installed on the FMC Uni-head.</p> <p>The pipe rams will be operated and checked each 24 hour period and each time the drill pipe is out of the hole. These tests will be logged in the daily driller's log. A 2" kill line and 3" choke line will be incorporated into the drilling spool below the ram BOP. In addition to the rams and annular preventer, additional BOP accessories include a kelly cock, floor safety valve, choke lines, and choke manifold rated at 5,000 psi WP.</p>

SEE  
COA

**Devon Energy, Gaucho Unit 29H**

<p>Devon requests a variance to use a flexible line with flanged ends between the BOP and the choke manifold (choke line). The line will be kept as straight as possible with minimal turns</p> <p>See attached schematic.</p>
--

**5. Mud Program**

Depth		Type	Weight (ppg)	Viscosity	Water Loss
From	To				
0	1,675'	FW Gel	8.6-8.8	28-34	N/C
1,675'	<del>3,850'</del>	Saturated Brine	10.0-10.2	28-34	N/C
<del>3,850'</del>	16,576'	Cut Brine	8.5-9.3	28-34	N/C

5000

Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept on location at all times.

What will be used to monitor the loss or gain of fluid?	PVT/Pason/Visual Monitoring
---	-----------------------------

**6. Logging and Testing Procedures**

Logging, Coring and Testing.	
x	Will run GR/CNL from TD to surface (horizontal well – vertical portion of hole). Stated logs run will be in the Completion Report and submitted to the BLM.
	No Logs are planned based on well control or offset log information.
	Drill stem test? If yes, explain
	Coring? If yes, explain

Additional logs planned	Interval
Resistivity	Int. shoe to KOP
Density	Int. shoe to KOP
X	CBL
X	Mud log
	PEX

Devon Energy, Gaucho Unit 29H

7. Drilling Conditions

SEE COA

Condition	Specify what type and where?
BH Pressure at deepest TVD	3000 psi
Abnormal Temperature	No

Mitigation measure for abnormal conditions. Describe. Lost circulation material/sweeps/mud scavengers.

Hydrogen Sulfide (H2S) monitors will be installed prior to drilling out the surface shoe. If H2S is detected in concentrations greater than 100 ppm, the operator will comply with the provisions of Onshore Oil and Gas Order #6. If Hydrogen Sulfide is encountered, measured values and formations will be provided to the BLM.	
N	H2S is present
Y	H2S Plan attached

**8. Other facets of operation**

Is this a walking operation? No.

Will be pre-setting casing? No.

Attachments

Directional Plan

Other, describe