

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB NO. 1004-0135
Expires: July 31, 2010

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.

Carlsbad Field Office
OCD Hobbs

5. Lease Serial No.
NMNM122621

6. If Unit or CA/Agreement, Name and/or No.

SUBMIT IN TRIPLICATE - Other instructions on reverse side.

7. If Unit or CA/Agreement, Name and/or No.

1. Type of Well
 Oil Well Gas Well Other

8. Well Name and No.
WHIRLING WIND 14 FED COM 701H

2. Name of Operator
EOG RESOURCES INCORPORATED
Contact: STAN WAGNER
E-Mail: stan_wagner@eogresources.com

9. API Well No.
30-025-42886-00-X1

3a. Address
MIDLAND, TX 79702

3b. Phone No. (include area code)
Ph: 432-686-3689

10. Field and Pool, or Exploratory
WC-025 G09 S253336D

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
Sec 14 T26S R33E NENE 4FNL 556FEL

11. County or Parish, and State
LEA COUNTY, NM

HOBBS OCD

JUN 28 2016

RECEIVED

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input checked="" type="checkbox"/> Other
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	Change to Original APD
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

EOG Resources requests an amendment to our approved APD for this well to reflect a change in wellbore configuration.

A pilot hole is planned for this well. The well will be logged and plugged back to kick-off point. Details attached.

**SEE ATTACHED FOR
CONDITIONS OF APPROVAL**

14. I hereby certify that the foregoing is true and correct.

**Electronic Submission #341976 verified by the BLM Well Information System
For EOG RESOURCES INCORPORATED, sent to the Hobbs
Committed to AFMSS for processing by PRISCILLA PEREZ on 06/14/2016 (16PP0782SE)**

Name (Printed/Typed) STAN WAGNER

Title REGULATORY ANALYST

Signature (Electronic Submission)

Date 06/14/2016

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved By (BLM Approver Not Specified) Mustafa Hague

Title **PETROLEUM ENGINEER**

Date 06/21/2016

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office Hobbs

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

**Whirling Wind 14 Fed Com 701H
30-025-42886
EOG Resources, Inc
Surface Location: Sec. 14, T. 26S, R. 33E
Conditions of Approval**

A. CASING

All previous COAs still apply, except for the following :

Changes to the approved APD casing program need prior approval if the items substituted are of lesser grade or different casing size or are Non-API. The Operator can exchange the components of the proposal with that of superior strength (i.e. changing from J-55 to N-80, or from 36# to 40#). Changes to the approved cement program need prior approval if the altered cement plan has less volume or strength or if the changes are substantial (i.e. Multistage tool, ECP, etc.).

The initial wellhead installed on the well will remain on the well with spools used as needed.

Centralizers required on surface casing per Onshore Order 2.III.B.1.f.

Wait on cement (WOC) for Water Basin:

After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi at the shoe, 2) until cement has been in place at least 8 hours. WOC time will be recorded in the driller's log. See individual casing strings for details regarding lead cement slurry requirements. **DURING THIS WOC TIME, NO DRILL PIPE, ETC. SHALL BE RUN IN THE HOLE.**

Provide compressive strengths including hours to reach required 500 pounds compressive strength prior to cementing each casing string. Have well specific cement details onsite prior to pumping the cement for each casing string.

No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.

Risks:

Possibility of Water Flows in the Castile and in the Salado

Possibility of Lost Circulation in the Rustler, in the Red Beds and in the Delaware
Abnormal pressures may be encountered upon penetrating the 3rd Bone Spring Sandstones and all subsequent formations.

1. The 10 3/4 inch surface casing shall be set at approximately 990 feet (**in a competent bed below the Magenta Dolomite, which is a Member of the Rustler, and if salt is encountered, set casing at least 25 feet above the salt**) and cemented to the surface.
 - a. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with surface log readout will be used or a cement bond log shall be run to verify the top of the cement. Temperature survey will be run a minimum of six hours after pumping cement and ideally between 8-10 hours after completing the cement job.
 - b. **Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry.**
 - c. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength, whichever is greater.
 - d. If cement falls back, remedial cementing will be done prior to drilling out that string.

Formation below the 10 3/4 inch shoe to be tested according to Onshore Order 2.III.B.1.i. Test to be done as a mud equivalency test using the mud weight necessary for the pore pressure of the formation below the shoe (not the mud weight required to prevent dissolving the salt formation) and the mud weight for the bottom of the hole. Report results to BLM office.

2. The minimum required fill of cement behind the 7 5/8 inch intermediate casing is:

Cement to surface. If cement does not circulate see A.1.a, c-d above.

Formation below the 7 5/8 inch shoe to be tested according to Onshore Order 2.III.B.1.i. Test to be done as a mud equivalency test using the mud weight necessary for the pore pressure of the formation below the shoe (not the mud weight required to prevent dissolving the salt formation) and the mud weight for the bottom of the hole. Report results to BLM office.

Pilot hole is required to have a plug at the bottom of the hole. If two plugs are set, the BLM is to be contacted (575-393-3612) prior to tag of bottom plug, which must be a minimum of 200 feet in length. Operator can set one plug from bottom of pilot hole to kick-off point and save the WOC time for tagging the first plug. Top of Wolfcamp plug is required, tagged and witness. Proposed plug is approved as written.

Variance is granted for centralizers in the production interval per the drilling program.

3. The minimum required fill of cement behind the **5 1/2** inch production casing is:

Cement should tie-back at least **500** feet into previous casing string. Operator shall provide method of verification. **Additional cement may be required since excess was calculated to be 13%.**

4. If hardband drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.

MHH 06212016

**UNITED STATES DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

Pecos District
Carlsbad Field Office
620 E Greene Street
Carlsbad, NM 88220

Finding of No Significant Impact

**[Thistle Unit 1H]
NEPA No. DOI-BLM- NM-P020-2016-1322-EA**

FINDING OF NO SIGNIFICANT IMPACT:

I have determined that the proposed action, as described in the EA will not have any significant impact, individually or cumulatively, on the quality of the human environment. Because there would not be any significant impact, an environmental impact statement is not required.

In making this determination, I considered the following factors:

1. The activities described in the proposed action do not include any significant beneficial or adverse impacts (40 CFR 1508.27(b)(1)). The EA includes a description of the expected environmental consequences of Devon Energy Production Company, L.P. (Devon) has applied for a permit to drill one horizontal oil well from a new well pad that adjoins the Thistle Unit 65H well pad and buried pipelines to be constructed on state surface approximately 24.19 miles northwest of Jal, NM.
2. The activities included in the proposed action would not significantly affect public health or safety (40 CFR 1508.27(b)(2)).
3. The proposed activities would not significantly affect any unique characteristics (40 CFR 1508.27(b)(3)) of the geographic area such as prime and unique farmlands, caves, wild and scenic rivers, designated wilderness areas, wilderness study areas, or areas of critical concern.
4. The activities described in the proposed action do not involve effects on the human environment that are likely to be highly controversial (40 CFR 1508.27(b)(4)).
5. The activities described in the proposed action do not involve effects that are highly uncertain or involve unique or unknown risks (40 CFR 1508.27(b)(5)).
6. My decision to implement these activities does not establish a precedent for future actions with significant effects or represent a decision in principle about a future consideration (40 CFR 1508.27(b)(6)).
7. The effects of [*Devon Energy Production Company, L.P. (Devon) has applied for a permit to drill one horizontal oil well from a new well pad that adjoins the Thistle Unit 65H well pad and buried pipelines to be constructed on state surface approximately 24.19 miles northwest of Jal, NM.*] would not be significant, individually or cumulatively, when considered with the effects of other actions (40 CFR 1508.27(b)(7)). The EA discloses that there are no other connected or cumulative actions that would cause significant cumulative impacts.
8. I have determined that the activities described in the proposed action will not adversely affect or cause loss or destruction of scientific, cultural, or historical resources, including those listed in or eligible for listing in the National Register of Historic Places (40 CFR 1508.27(b)(8)). Cultural resource surveys

a) *Pages 21-22*

9. The proposed activities are not likely to adversely affect any endangered or threatened species or its habitat that has been determined to be critical under the Endangered Species Act (40 CFR 1508.27(b)(9)).

a) *Pages 19-20*

10. The proposed activities will not knowingly threaten any violation of Federal, State, or local law or requirements imposed for the protection of the environment (40 CFR 1508.27(b)(10)).

Pages 3-5

APPROVED:

George MacDonell
Field Manager
Carlsbad Field Office

Date

EOG RESOURCES, INC.
WHIRLING WIND 14 FED COM NO. 701H

1. GEOLOGIC NAME OF SURFACE FORMATION:

Permian

2. ESTIMATED TOPS OF IMPORTANT GEOLOGICAL MARKERS:

Rustler	900'
Top of Salt	1,255'
Base of Salt / Top Anhydrite	4,920'
Base Anhydrite	5,160'
Lamar	5,160'
Bell Canyon	5,187'
Cherry Canyon	6,250'
Brushy Canyon	7,898'
Bone Spring Lime	9,360'
1 st Bone Spring Sand	10,275'
2 nd Bone Spring Lime	10,470'
2 nd Bone Spring Sand	10,805'
3 rd Bone Spring Carb	11,155'
3 rd Bone Spring Sand	11,905'
Wolfcamp	12,330'
TD	13,500'

3. ESTIMATED DEPTHS OF ANTICIPATED FRESH WATER, OIL OR GAS:

Upper Permian Sands	0- 400'	Fresh Water
Cherry Canyon	6,250'	Oil
Brushy Canyon	7,898'	Oil
1 st Bone Spring Sand	10,275'	Oil
2 nd Bone Spring Lime	10,470'	Oil
2 nd Bone Spring Sand	11,805'	Oil
3 rd Bone Spring Carb	11,155'	Oil
3 rd Bone Spring Sand	11,905'	Oil
Wolfcamp	12,330'	Oil

No other Formations are expected to give up oil, gas or fresh water in measurable quantities. Surface fresh water sands will be protected by setting 10.75" casing at 925' and circulating cement back to surface.

EOG RESOURCES, INC.
WHIRLING WIND 14 FED COM NO. 701H

4. CASING PROGRAM - NEW

Hole Size	Interval	Csg OD	Weight	Grade	Conn	DF _{min} Collapse	DF _{min} Burst	DF _{min} Tension
14.75"	0 – 925'	10.75"	40.5#	J55	STC	1.125	1.25	1.60
9.875"	0-8,000'	7.625"	29.7#	HCP-110	LTC	1.125	1.25	1.60
8.75"	8,000' – 10,900'	7.625"	29.7#	HCP-110	FlushMax III	1.125	1.25	1.60
6.75"	0'-19,962'	5.5"	23#	HCP-110	ULT SFII	1.125	1.25	1.60

Variance is requested to wave the centralizer requirements for the 7-5/8" FJ casing in the 8-3/4" hole size. An expansion additive will be utilized, in the cement slurry, for the entire length of the 8-3/4" hole interval to maximize cement bond and zonal isolation. Centralizers will be placed in the 9-7/8" hole interval at least one every third joint.

Variance is also requested to wave any centralizer requirements for the 5-1/2" FJ casing in the 6-3/4" hole size. An expansion additive will be utilized, in the cement slurry, for the entire length of the 6-3/4" hole interval to maximize cement bond and zonal isolation.

Cementing Program:

Depth	No. Sacks	Wt. ppg	Yld Ft ³ /ft	Mix Water Gal/sk	Slurry Description
10-3/4" 925	325	13.5	1.73	9.13	Class C + 4.0% Bentonite + 0.6% CD-32 + 0.5% CaCl ₂ + 0.25 lb/sk Cello-Flake (TOC @ Surface)
	200	14.8	1.34	6.34	Class C + 0.6% FL-62 + 0.25 lb/sk Cello-Flake + 0.2% Sodium Metasilicate
7-5/8" 10,900'	750	9.0	2.50	9.06	Class C + 0.6% ASM-3 + 0.15% CDF-4P + 0.6% LTR + 0.5% SCA-6 + 0.13 pps LCL-11 + 0.13 pps LDP-c-0215
	500	12.5	1.71	9.06	Class C + 0.6% LTR + 0.5% SCA-6 + 0.6% ASM-3 + 0.15% CDF-4P + 0.13% LCL-11 + 0.13% LCF-7
	250	15.6	1.19	5.20	Class H + 0.2% ASM-3 + 0.3% SCA-6 + 0.65% LTR + 0.3% SPC-2
13,500	110	17.8	0.91	11.56	230' Btm Hole Plug - Class 'H' + 1.20% CD-31 + 0.20% R-3 + 5.00% Salt (1.252 lb/sk)
11,700' – 12,000'	350	17.8	0.91	11.56	600' Sidetrack Plug - Class 'H' + 1.20% CD-31 + 0.20% R-3 + 5.00% Salt (1.252 lb/sk)
5-1/2" 19,962'	725	14.1	1.26	5.80	Class H + 0.1% C-20 + 0.05% CSA-1000 + 0.20% C-49 + 0.40% C-17

Note: Cement volumes based on bit size plus at least 25% excess in the open hole plus 10% excess in the cased-hole overlap section.

**EOG RESOURCES, INC.
WHIRLING WIND 14 FED COM NO. 701H**

5. MINIMUM SPECIFICATIONS FOR PRESSURE CONTROL:

Variance is requested to use a co-flex line between the BOP and choke manifold (instead of using a 4" OD steel line).

The minimum blowout preventer equipment (BOPE) shown in Exhibit #1 will consist of a single ram, mud cross and double ram-type (10,000 psi WP) preventer and an annular preventer (5000-psi WP). Both units will be hydraulically operated and the ram-type will be equipped with blind rams on bottom and drill pipe rams on top. All BOPE will be tested in accordance with Onshore Oil & Gas order No. 2.

Before drilling out of the surface casing, the ram-type BOP and accessory equipment will be tested to 5000/ 250 psig and the annular preventer to 5000/ 250 psig. The surface casing will be tested to 1500 psi for 30 minutes.

Before drilling out of the intermediate casing, the ram-type BOP and accessory equipment will be tested to 5000/ 250 psig and the annular preventer to 5000/ 250 psig. The intermediate casing will be tested to 2000 psi for 30 minutes.

Pipe rams will be operationally checked each 24-hour period. Blind rams will be operationally checked on each trip out of the hole. These checks will be noted on the daily tour sheets.

A hydraulically operated choke will be installed prior to drilling out of the intermediate casing shoe.

6. TYPES AND CHARACTERISTICS OF THE PROPOSED MUD SYSTEM:

During this procedure we plan to use a Closed-Loop System and haul contents to the required disposal.

The applicable depths and properties of the drilling fluid systems are as follows.

Depth	Type	Weight (ppg)	Viscosity	Water Loss
0 - 925' 990'	Fresh - Gel	8.6-8.8	28-34	N/c
925' - 10,900'	Brine	8.8-10.0	28-34	N/c
10,900' - 13,500' Pilot Hole	Oil Base	8.7-10.5	58-68	3-6
10,900' - 19,962' Lateral	Oil Base	10.0-11.5	58-68	3 - 6

An electronic pit volume totalizer (PVT) will be utilized on the circulating system, to monitor pit volume, flow rate, pump pressure and stroke rate.

Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept at the wellsite at all times.

EOG RESOURCES, INC.
WHIRLING WIND 14 FED COM NO. 701H

7. AUXILIARY WELL CONTROL AND MONITORING EQUIPMENT:

- (A) A kelly cock will be kept in the drill string at all times.
- (B) A full opening drill pipe-stabbing valve (inside BOP) with proper drill pipe connections will be on the rig floor at all times.
- (C) H₂S monitoring and detection equipment will be utilized from surface casing point to TD.

8. LOGGING, TESTING AND CORING PROGRAM:

Triple Combo Open-hole logs are planned for this well.

GR-CCL Will be run in cased hole during completions phase of operations.

9. ABNORMAL CONDITIONS, PRESSURES, TEMPERATURES AND POTENTIAL HAZARDS:

The estimated bottom-hole temperature (BHT) at TD is 182 degrees F with an estimated maximum bottom-hole pressure (BHP) at TD of 7504 psig. No hydrogen sulfide or other hazardous gases or fluids have been encountered, reported or are known to exist at this depth in this area. Severe loss circulation is expected from 7,300' to Intermediate casing point.

10. ANTICIPATED STARTING DATE AND DURATION OF OPERATIONS:


The drilling operation should be finished in approximately one month. If the well is productive, an additional 60-90 days will be required for completion and testing before a decision is made to install permanent facilities.

Whirling Wind 14 Fed Com #701H

4' FNL
556' FEL
Section 14
T-26-S, R-33-E


Lea County, New Mexico
Proposed Wellbore
Revised 6/14/16
API: 30-025-42886

KB: 3,370'
GL: 3,340'



Lateral: 19,962' MD, 12,550' TVD
Upper Most Perf:
330' FSL & 350' FEL Sec. 11
Lower Most Perf:
2308' FSL & 330' FEL Sec 2
BH Location: 2408' FSL & 330' FEL
Section 2
T-26-S, R-33-E

FLUSHMAX-III
Connection Data Sheet



Pipe Body	Imperial		S.I.	
	P110	P110	P110	P110
Grade	7 5/8	in	193.68	mm
Pipe OD (D)	29.7	lb/ft	44.25	kg/m
Weight	29.0	lb/ft	43.26	kg/m
Actual weight	0.375	in	9.53	mm
Wall thickness (t)	6.875	in	174.63	mm
Pipe ID (d)	8.537	in	5.508	mm ²
Pipe body cross section	6.750	in	171.45	mm
Drift Dia.				

Connection	
Box OD (W)	7.625 in 193.68 mm
PIN ID	6.875 in 174.63 mm
Pin critical area	4.420 in ² 2.852 mm ²
Box critical area	4.424 in ² 2.854 mm ²
Joint load efficiency	60 %
Make up loss	3.040 in 77.22 mm
Thread taper	1/16 (3/4 in per ft)
Number of threads	5 thread per in.

Connection Performance Properties			
Tensile Yield load	563.4	kips	2.506 kN
M.I.Y.P.	7.574	psi	52.2 MPa
Collapse strength	5.350	psi	36.9 MPa

Note
M.I.Y.P. = Minimum Internal Yield Pressure of the connection

Torque Recommended			
Min.	8,700	ft-lb	11,700 N-m
Opt.	9,700	ft-lb	13,100 N-m
Max.	10,700	ft-lb	14,500 N-m
Operational Max.	23,600	ft-lb	32,000 N-m

Note : Operational Max. torque can be applied for high torque application