

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources
OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised July 18, 2013

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-025-33927
1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐		5. Indicate Type of Lease STATE ☐ FEE ☒
2. Name of Operator CHEVRON USA INC		6. State Oil & Gas Lease No. N/A
3. Address of Operator 1400 SMITH ST, HOUSTON, TX 77002		7. Lease Name or Unit Agreement Name KYTE
4. Well Location Unit Letter <u>G</u> : <u>1980</u> feet from the <u>NORTH</u> line and <u>1980</u> feet from the <u>EAST</u> line Section <u>23</u> Township <u>20S</u> Range <u>38E</u> NMPM LEA County		8. Well Number <u>5</u>
11. Elevation (Show whether DR, RKB, RT, GR, etc.)		9. OGRID Number 4323
		10. Pool name or Wildcat DK ABO

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT	
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☒	REMEDIAL WORK	INT TO PA <u>Am</u> ✓
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPN	P&A NR
PULL OR ALTER CASING ☐	MULTIPLE COMPL ☐	CASING/CEMENT JOB	P&A R
DOWNHOLE COMMINGLE ☐			
CLOSED-LOOP SYSTEM ☐			
OTHER: ☐		OTHER:	

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

WELL INFO
TD: 7799'
PERFORATIONS: 7385' - 6030'
SURFACE CASING: 8-5/8" 24# @ 1630' w/ CEMENT TO SURFACE
PRODUCTION CASING: 5-1/2" 17# @ 7790' w/ TOC 3000'
CIBP SET @ 7582'

Set CIBP at 7185'. Dump bail
4 sx cmt or spot 25 sx cmt.
Set CIBP at 6700'. Dump bail
4 sx cmt or spot 25 sx cmt
Pressure test
CSG

1. SET CIBP AT 6000'. MIX AND PUMP CEMENT PLUG FROM 6000' - 5700' W/ 35 SXS OF CLASS "C" CEMENT
2. MIX AND PUMP CEMENT PLUG FROM 4500' - 4000' W/ 55 SXS OF CLASS "C" CEMENT. (SAN ANDRES)
3. PERFORATE & SQUEEZE WITH CLASS "C" CEMENT AT 2930' W/ 150 SXS. TOC AT 2450'. (YATES/BSALT)
4. PERFORATE & SQUEEZE WITH CLASS "C" CEMENT AT 1700' W/ 155 SXS. TOC AT 1150'. ((TSALT/SHOE)
5. PERFORATE & SQUEEZE WITH CLASS "C" CEMENT AT 400' W/ 120 SXS. TOC AT SURFACE'. (FRWR/SURFACE0)

CUT off wellhead 3' below ground level. Verify cement to surface all strings. Install dry hole marker.

Spud Date:

4/24/1997

Rig I

NOTIFY OCD 24 HOURS PRIOR TO BEGINNING PLUGGING OPERATIONS

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Abhishek Roy TITLE P&A PROJECT MANAGER DATE 07/07/16

Type or print name ABHISHEK ROY E-mail address: BULQ@CHEVRON.COM PHONE: 713-396-6915
For State Use Only

APPROVED BY: Mark W. [Signature] TITLE Petroleum Engr Specialist DATE 7/19/2016
Conditions of Approval (if any):

Vertical schematic (actual)

PROPOSED

Eunice Area/Blinberry Feild
Kyte 5-23
Lea County New Mexico
API# 30-025-33927

8-5/8" CSG set @ 1630'
CMT Cir. to surface

Perf 5-1/2"x 8-5/8" CSG @ 400, Cir. a
400', 120 sxs cmt plug to surface

Perf 5-1/2" CSG @ 1700, Squeeze a
550', 155 sxs cmt plug, TOC @ 1150'

Perf 5-1/2" CSG @ 2950, Squeeze a
500', 150 sxs cmt plug, TOC @ 2450'

5-1/2" CSG set @ 7790'
CMT Cir. to 3000'

TOC @ 3000'

Mix and pump a cmt plug from 4500' –
4000' W/ 55 sxs of class "C" Cmt

Set a CIBP @ 6000' w/300' 35 sxs cmt
plug on top

Perforations: 7460' – 6030'

CIBP set @ 7582'

Perforations: 7675' – 7593'

Current Wellbore Schematic

WELL (PN): KYTE 5-23 (CVX) (890133)
 FIELD OFFICE: HOBBS
 FIELD: Blinbry
 STATE / COUNTY: NEW MEXICO / LEA
 LOCATION: SEC 23-20S-38E, 1980 FNL & 1980 FEL
 ROUTE: HOB-NM-ROUTE 09- JUSTIN HOBBS
 ELEVATION: GL: 3,570.0 KB: 3,581.5 KB Height: 11.5
 DEPTHS: TD: 7,800.0

API #: 3002533927
 Serial #:
 SPUD DATE: 4/24/1997
 RIG RELEASE: 2/1/2000
 1ST SALES GAS:
 1ST SALES OIL: 2/6/2000
 Current Status: PRODUCING

