

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised August 1, 2011

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.
30-025-09134 ✓
5. Indicate Type of Lease
STATE FEE X ✓
6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well X Gas Well Other

2. Name of Operator
CIMAREX ENERGY CO. OF COLORADO

3. Address of Operator
600 N. MARIENFELD, SUITE 600, MIDLAND, TEXAS 79701

4. Well Location

Unit Letter P : 990 feet from the SOUTH line and 990 feet from the EAST line ✓
Section 34 Township 22S Range 36E NMPM LEA County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3.505' - GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON X
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUEN

REMEDIAL WORK
COMMENCE DRILLING OPN
CASING/CEMENT JOB

INT TO PA PM X
P&A NR _____
P&A R _____

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

- 1) SET 5-1/2" CIBP @ 2900'; PUMP 25 SXS. CMT. @ 2,900'-2,750'; CIRC. WELL W/ PXA MUD. Pressure test csg.
2) PUMP 25 SXS. CMT. @ 1,772'-1,622' (DV TOOL); WOC X TAG CMT. PLUG. > combine plugs
3) PUMP 25 SXS. CMT. @ 1,493'-1,383' (T/SALT, T/ANHY.); WOC X TAG CMT. PLUG.
4) PERF. X CIRC. TO SURF., FILLING ALL ANNULI, 125 SXS. CMT. @ 368'-3' (8-5/8" CSG.SHOE).
5) DIG OUT X CUT OFF WELLHEAD 3' B.G.L.; WELD ON STEEL PLATE TO CSGS. X INSTALL DRY HOLE MARKER. Verify cement to surface all strings.

DURING THIS PROCEDURE WE PLAN TO USE THE CLOSED-LOOP SYSTEM W/ A STEEL TANK AND HAUL CONTENTS TO THE REQUIRED DISPOSAL, PER OCD RULE 19.15.17.

Spud Date:

NOTIFY OCD 24 HOURS PRIOR TO BEGINNING
PLUGGING OPERATIONS

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE David A. Eyer TITLE: AGENT

DATE: 07/25/16

Type or print name: DAVID A. EYLER

E-mail address: DEYLER@MILAGRO-RES.COM PHONE: 432.687.3033

For State Use Only

APPROVED BY: Mah Whitaker TITLE: Petroleum Engr. Specialist DATE: 8/1/2016

Conditions of Approval (if any):

MW



7/7/2016

8-5/8" 24# @ 318' cmt w/200 sx "C" Circulated

No Record

DV Tool @ 1702'
TOC NR

5-1/2" 17# J-55 csg @ 2999'
Cmt 1st stage w/200 sx
Cmt 2nd stage w/200 sx

Baker Model "R" @ 2635' (GLM) 3/31/73

PBTD: 3450'
TD: 3512'

Tagged Fill 3/31/73

CIMAREX

Spudded 5/12/1950
Original Operator:
Dalport Oil Corp.

Cimarex Energy Co. of Colorado
JONES, OTIS L #1
API 30-025-09134, Property #309529-039
990' FSL & 990' FEL, Sec 34, T22S R36E
Lea County, NM
GL:3505', KB:3512'

J PIWETZ

7/7/2016

8-5/8" 24# @ 318' cmt w/200 sx "C" Circulated

PERF. X CIRC. 125 SXS. @ 368'-3'

T/SALT/ANHY ~ 1,438'

R/SALT/ANHY ~ 2,991'

PXA
MUD

Pump 25 SXS. @ 1493'-1383'-TAG

PXA
MUD

Pump 25 SXS. @ 1772'-1622'-TAG

PXA
MUD

Pump 25 SXS. @ 2900'-2750'

Baker Model "R" @ 2635' (GLM) 3/31/73

SET 5 1/2" CNBP @ 2900'

DV Tool @ 1702'
TOC NR

5-1/2" 17# J-55 csg @ 2999'
Cmt 1st stage w/200 sx
Cmt 2nd stage w/200 sx

PBTD: 3450'
TD: 3512'

Tagged Fill 3/31/73

DAZ 07/25/16