



OCCIDENTAL PERMIAN LTD

**NORTH HOBBS UNIT
SEC. 24, T18S, R37E
NHU 24-680**

HOBBS OCD

NHU 24-680

AUG 04 2016

RECEIVED

Survey: MWD SURVEYS

Standard Survey Report

25 March, 2016





GEOGUIDANCE DRILLING

Survey Report



Company:	OCCIDENTAL PERMIAN LTD	Local Co-ordinate Reference:	Well NHU 24-680
Project:	NORTH HOBBS UNIT	TVD Reference:	NHU 24-680 @ 3685.5usft (H&P 340)
Site:	SEC. 24, T18S, R37E	MD Reference:	NHU 24-680 @ 3685.5usft (H&P 340)
Well:	NHU 24-680	North Reference:	Grid
Wellbore:	NHU 24-680	Survey Calculation Method:	Minimum Curvature
Design:	NHU 24-680	Database:	EDM 5000.1 Single User Db

Project	NORTH HOBBS UNIT		
Map System:	US State Plane 1927 (Exact solution)	System Datum:	Mean Sea Level
Geo Datum:	NAD 1927 (NADCON CONUS)		
Map Zone:	New Mexico East 3001		

Site	SEC. 24, T18S, R37E		
Site Position:		Northing:	632,000.00 usft
From:	Map	Easting:	847,000.00 usft
Position Uncertainty:	0.0 usft	Slot Radius:	13-3/16 "
		Latitude:	32° 43' 56.582 N
		Longitude:	103° 12' 17.743 W
		Grid Convergence:	0.61 °


Well	NHU 24-680, SUR. N 632675.21 E 849279.93		
Well Position	+N/-S	0.0 usft	Northing:
	+E/-W	0.0 usft	Easting:
Position Uncertainty	0.0 usft	Wellhead Elevation:	3,685.5 usft
		Latitude:	32° 44' 3.022 N
		Longitude:	103° 11' 50.972 W
		Ground Level:	3,669.0 usft

Wellbore	NHU 24-680		
Magnetics	Model Name	Sample Date	Declination (°)
	IGRF2015	2/29/2016	6.95
			Dip Angle (°)
			60.61
			Field Strength (nT)
			48,413

Design	NHU 24-680		
Audit Notes:			
Version:	1.0	Phase:	ACTUAL
		Tie On Depth:	0.0
Vertical Section:	Depth From (TVD) (usft)	+N/-S (usft)	+E/-W (usft)
	0.0	0.0	0.0
			Direction (°)
			138.87

Survey Program	Date 3/25/2016		
From (usft)	To (usft)	Survey (Wellbore)	Tool Name
194.0	4,690.0	MWD SURVEYS (NHU 24-680)	MWD+IGRF
			Description
			OWSG MWD + IGRF or WMM

Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
0.0	0.00	0.00	0.0	0.0	0.0	0.0	0.00	0.00	0.00
194.0	1.00	5.55	194.0	1.7	0.2	-1.2	0.52	0.52	0.00
376.0	1.45	25.90	375.9	5.3	1.3	-3.1	0.34	0.25	11.18
558.0	2.70	142.70	557.9	4.0	4.9	0.2	1.98	0.69	64.18
743.0	7.50	141.60	742.1	-8.9	15.1	16.6	2.60	2.59	-0.59
907.0	10.20	140.40	904.1	-28.5	31.0	41.9	1.65	1.65	-0.73
1,087.0	14.10	139.50	1,080.1	-57.5	55.4	79.7	2.17	2.17	-0.50
1,266.0	14.41	138.97	1,253.5	-90.9	84.2	123.8	0.19	0.17	-0.30
1,446.0	13.45	141.08	1,428.3	-124.0	112.0	167.1	0.60	-0.53	1.17
1,616.0	11.64	138.53	1,594.2	-152.3	135.8	204.0	1.11	-1.06	-1.50



GEOGUIDANCE DRILLING

Survey Report



Company:	OCCIDENTAL PERMIAN LTD	Local Co-ordinate Reference:	Well NHU 24-680
Project:	NORTH HOBBS UNIT	TVD Reference:	NHU 24-680 @ 3685.5usft (H&P 340)
Site:	SEC. 24, T18S, R37E	MD Reference:	NHU 24-680 @ 3685.5usft (H&P 340)
Well:	NHU 24-680	North Reference:	Grid
Wellbore:	NHU 24-680	Survey Calculation Method:	Minimum Curvature
Design:	NHU 24-680	Database:	EDM 5000.1 Single User Db

Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
1,796.0	14.10	143.32	1,769.7	-183.5	160.9	244.1	1.49	1.37	2.66
1,975.0	14.63	144.90	1,943.1	-219.5	187.0	288.3	0.37	0.30	0.88
2,152.0	13.88	144.39	2,114.6	-255.0	212.2	331.6	0.43	-0.42	-0.29
2,332.0	13.93	141.60	2,289.3	-289.5	238.2	374.8	0.37	0.03	-1.55
2,512.0	13.75	140.99	2,464.1	-323.1	265.1	417.8	0.13	-0.10	-0.34
2,690.0	12.88	140.15	2,637.3	-354.8	291.2	458.8	0.50	-0.49	-0.47
2,869.0	11.88	138.57	2,812.2	-383.9	316.1	497.1	0.59	-0.56	-0.88
3,049.0	9.10	137.56	2,989.1	-408.3	338.0	529.9	1.55	-1.54	-0.56
3,235.0	8.92	141.87	3,172.8	-430.5	356.8	559.0	0.38	-0.10	2.32
3,415.0	8.10	142.41	3,350.9	-451.6	373.2	585.6	0.46	-0.46	0.30
3,595.0	6.10	143.10	3,529.5	-469.3	386.7	607.8	1.11	-1.11	0.38
3,775.0	6.46	141.08	3,708.4	-484.8	398.8	627.4	0.23	0.20	-1.12
3,955.0	6.10	136.91	3,887.3	-499.7	411.7	647.1	0.32	-0.20	-2.32
4,135.0	6.10	135.34	4,066.3	-513.4	424.9	666.2	0.09	0.00	-0.87
4,315.0	5.32	129.78	4,245.4	-525.6	438.0	684.0	0.53	-0.43	-3.09
4,495.0	5.23	126.62	4,424.6	-535.8	451.0	700.3	0.17	-0.05	-1.76
4,612.0	5.63	126.62	4,541.1	-542.4	459.9	711.1	0.34	0.34	0.00
4,690.0	5.63	126.62	4,618.7	-547.0	466.1	718.6	0.00	0.00	0.00

Survey Projected to TD

Formations

Measured Depth (usft)	Vertical Depth (usft)	Name	Lithology	Dip (°)	Dip Direction (°)
220.6	220.6	Top Red Beds			
1,505.9	1,486.6	Rustler (Base Red Beds)			
1,657.9	1,635.2	Top Salt			
2,763.0	2,708.5	Base Salt			
3,531.6	3,466.5	Queen			
3,841.4	3,774.4	Grayburg			
4,009.0	3,941.0	Basal Grayburg			
4,103.6	4,035.1	San Andres			

Survey Annotations

Measured Depth (usft)	Vertical Depth (usft)	Local Coordinates		Comment
		+N/-S (usft)	+E/-W (usft)	
4,690.0	4,618.7	-547.0	466.1	Survey Projected to TD

Checked By: _____ Approved By: _____ Date: _____






OCCIDENTAL PERMIAN LTD

Project: NORTH HOBBS UNIT
Site: SEC. 24, T18S, R37E
Well: NHU 24-680
Wellpath: NHU 24-680
Design: NHU 24-680



Azimuths to Grid North
True North: -0.61°
Magnetic North: 6.34°

Magnetic Field
Strength: 48413.2nT
Dip Angle: 60.61°
Date: 2/29/2016
Model: IGRF2015



LEGEND

- NHU 24-680, NHU 24-680, 022916 V2 V0
- NHU 24-422, NHU 24-422, NHU 24-422 V0
- NHU 24-680
- MWD SURVEYS

SECTION DETAILS

No plan data is available