

District I
1625 N. French Dr., Hobbs, NM 88240

District II
811 A. First St., Artesia, NM 88210

District III
1000 Rio Brazos Rd. Aztec, NM 87410

District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-025-06003
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease NO.
7. Lease Name or Unit Agreement Name T. Anderson
8. Well Number 3
9. OGRID Numer 873
10. Pool Name Monument Blinebry

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR DEEPEN OR PLUG BACK TO A DIFFERENT RESERVIOR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>	
2. Name of Operator Apache Corporation	
3. Address of Operator 303 Veterans Airpark Lane, Ste. 3000, Midland, TX 79705	
4. Well Location Unit Letter K : 2310 feet from the S line and 1650 feet from th W line Section 8 Township 20S Range 37E NMPM County Lea	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3547' GL	

12. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK	<input type="checkbox"/>	PLUG AND ABANDON	<input checked="" type="checkbox"/>
TEMPORARILY ABANDON	<input type="checkbox"/>	CHANGE PLANS	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	MULTIPLE COMPL	<input type="checkbox"/>
DOWNHOLE COMMINGLE	<input type="checkbox"/>		

OTHER: ☐

SUBSEQUENT

REMEDIAL WORK	INT TO P&A P&A NR P&A R
COMMENCE DRILLING OPN	
CASING/CEMENT JOB	
ALTERING CASING	
P AND A	
OTHER:	

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work.) SEE RULE 1103. For Multiple Completions: Attach wellbore diagram or proposed completion or recompletion.

Apache Corporation proposes to P&A the above mentioned well by the attached procedure. A closed loop system will be used for all fluids from this wellbore and disposed of required by OCD Rule 19.15.17.

Spud Date:

NOTIFY OCD 24 HOURS PRIOR TO BEGINNING PLUGGING OPERATIONS

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Guinn Burks TITLE Sr. Reclamation Foreman DATE 8/9/16Type or print name Guinn Burks E-mail add. guinn.burks@apachecorp.com PHONE: 432-556-9143APPROVED BY: Maah White TITLE Petroleum Engr. Specialist DATE 8-16-2016

Conditions of Approval (if any):



COUNTY

3

30-025-06003

Lea, NM

PROPOSED PROCEDURE

Verify cmt to surface
all strings

0

17 1/2" Hole
13 3/8" 36# @ 295'
w/ 300 sx to surf

573

TOC @ 1032' by TS

1146

1719

2292

2865

11" Hole
8 5/8" 32# @ 2900'
w/ 1500 sx to 1032' (TS)

TOC Cal @ 2683'

3438

4011

4584

5157

Set CIBP @ 5510' w/ 35' cmt

5730

7 7/8" Hole
5 1/2" 17# @ 5730'
w/ 500 sx

6. PUH & perf @ 350' & sqz 235 sx Class "C" cmt from 350' to surf. Attempt to CIRC 5 1/2" & 8 5/8" to surf. (Surf Shoe & Water Board)

5. PUH & perf @ 1215' & sqz 50 sx Class "C" cmt from 1215' - 1115' WOC/TAG (Top of Salt)

4. PUH & perf @ 2243' & sqz 50 sx Class "C" cmt from 2243'-2143' WOC/TAG (Base of Salt)

3. PUH to 2950' & spot 25 sx Class "C" cmt from 2950' - 2700' WOC/TAG (Intermediate Shoe)

2. PUH to 3746' & spot 25 sx Class "C" cmt from 3746'-3496' WOC/TAG (San Andres)

1. MIRU P&A rig, RIH w/ tbg & verify CIBP @ 5510' & CIRC w/MLF & spot 40 sx Class "C" cmt from 5475'-5118' WOC/TAG (Sqzd perms @ 5168'-5220')

Sqzd perfs @ 5168'-5220'

Blinebry perfs @ 5592'-5717'

PBTD @ 5475'
TD @ 5730'



T. Anderson

3

30-025-06003

Lea, NM

0

17 1/2" Hole
13 3/8" 36# @ 295'
w/ 300 sx to surf

573

TOC @ 1032' by TS

1146

1719

2292

TOC Cal @ 2683'

2865

11" Hole
8 5/8" 32# @ 2900'
w/ 1500 sx to 1032' (TS)

3438

4011

4584

5157

Set CIBP @ 5510' w/ 35' cmt

Sqzd perfs @ 5168'-5220'

Blinebry perfs @ 5592'-5717'

5730

7 7/8" Hole
5 1/2" 17# @ 5730'
w/ 500 sx

PBTD @ 5475'
TD @ 5730'