

Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

HOBBS
AUG 29 2016
RECEIVED

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-005-20558
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. K-3259
7. Lease Name or Unit Agreement Name Sun State
8. Well Number 1
9. OGRID Number 258867
10. Pool name or Wildcat SWD;SAN ANDRES
11. Elevation (Show whether DR, RKB, RT, GR, etc.)

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well Gas Well **XX Other** SWD-1039-A

2. Name of Operator STEVENSON OIL CO., INC.

3. Address of Operator
1709 N. 9TH STREET, LOVINGTON, NM 88260

4. Well Location
Unit Letter M : 660 feet from the South line and 660 feet from the West line
Section 36 Township 7S Range 30E NMPM Chaves County

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

- PERFORM REMEDIAL WORK
- TEMPORARILY ABANDON
- PULL OR ALTER CASING
- DOWNHOLE COMMINGLE
- CLOSED-LOOP SYSTEM
- OTHER:

- PLUG AND ABANDON
- CHANGE PLANS
- MULTIPLE COMPL

SUBSEQUENT REPORT OF:

- REMEDIAL WORK
- COMMENCE DRILLING OPNS.
- CASING/CEMENT JOB
- OTHER:

- ALTERING CASING
- P AND A

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

REQUEST PERMISSION TO PULL WELL TO LOCATE LEAK AND TEST:

1. Notify OCD 24 hrs. prior to starting work.
2. POOH with tubing and pkr.
3. RIH with plug and test.
4. Locate leak.
5. Space out and set cement plug, and drill out cement
6. Displace annulus with pkr. fluid and set pkr. within 100' of top perf.
7. Notify OCD 24-hrs. prior to testing.
8. Pressure test well.
9. Return to injection.

SWD-1039A

**Condition of Approval: notify
OCD Hobbs office 24 hours
prior of running MIT Test & Chart**

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Debbie McKelvey TITLE AGENT DATE 8/29/16

Type or print name Debbie McKelvey E-mail address: debmkelvey@earthlink.net PHONE: 575-392-3575

For State Use Only
APPROVED BY: Marys Brown TITLE Dist Supervisor DATE 8/31/2016
Conditions of Approval (if any):