

Submit To Appropriate District Office State Lease - 6 copies Fee Lease - 5 copies <u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 <u>District II</u> 1301 W. Grand Avenue, Artesia, NM 88210 <u>District III</u> 1000 Rio Brazos Rd., Aztec, NM 87410 <u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM 87505		State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505		Form C-105 Revised June 10, 2003 WELL API NO. 30-025-37618 5. Indicate Type of Lease STATE ☐ FEE ☒ State Oil & Gas Lease No.	
WELL COMPLETION OR RECOMPLETION REPORT AND LOG					
1a. Type of Well: OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER _____ b. Type of Completion: NEW ☒ WORK ☐ DEEPEN ☐ PLUG ☐ DIFF. _____ WELL OVER BACK RESVR. ☐ OTHER _____				7. Lease Name or Unit Agreement Name NORTHEAST DRINKARD UNIT	
2. Name of Operator Apache Corporation				8. Well No. 146	
3. Address of Operator 6120 South Yale, Suite 1500 Tulsa, OK 74136-4224				9. Pool name or Wildcat Eunice; Blinebry-Tubb-Drinkard, North	
4. Well Location Unit Letter H 2366 Feet From The North Line and 990 Feet From The East Line Section 4 23 Township 21S Range 37E NMPM Lea County					
10. Date Spudded 01/15/2006		11. Date T.D. Reached 01/26/2006		12. Date Compl. (Ready to Prod.) 02/16/2006	
13. Elevations (DF& RKB, RT, GR, etc.) 3462' GR		14. Elev. Casinghead			
15. Total Depth 6924'		16. Plug Back T.D. 6906'		17. If Multiple Compl. How Many Zones? 3	
18. Intervals Drilled By Rotary Tools X Cable Tools				19. Producing Interval(s), of this completion - Top, Bottom, Name Blinebry, Tubb & Drinkard	
20. Was Directional Survey Made No				21. Type Electric and Other Logs Run SD/DSN & DLL/MS	
23. CASING RECORD (Report all strings set in well)					
CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8-5/8"	24#	1207'	12-1/4"	550 sx / circ 148 sx	
5-1/2"	17#	6924'	7-7/8"	1150 sx / TOC 340' CBL	
24. LINER RECORD			25. TUBING RECORD		
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE
					2-7/8"
					6803'
26. Perforation record (interval, size, and number) BLINEBRY 5706-10,5800-04,90-94 & 5980-84' 2 JSPF TUBB 6224-28,86-90 & 6342-46' 2 JSPF DRINKARD 6548-52,6603-06,69-73,97-6700 & 6759-62' 2 JSPF			27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC. DEPTH INTERVAL AMOUNT AND KIND MATERIAL USED 5706 - 5984' 2000gals 15%HCl-36kgals gel+82k# 20/40 sd 6224 - 6346' 2000gals 15%HCl-36kgals gel+82k# 20/40 sd 6548 - 6762' 2000gals 15%HCl-43kgals gel+62k# 20/40 sd		
28. PRODUCTION					
Date First Production 02/16/2006		Production Method (Flowing, gas lift, pumping - Size and type pump) Pumping		Well Status (Prod. or Shut-in) Producing	
Date of Test 03/06/2006	Hours Tested 24 hrs	Choke Size	Prod'n For Test Period	Oil - Bbl 59	Gas - MCF 226
Water - Bbl. 220	Gas - Oil Ratio 3831				
Flow Tubing Press.	Casing Pressure	Calculated 24-Hour Rate	Oil - Bbl.	Gas - MCF	Water - Bbl.
Oil Gravity - API - (Corr.)					
29. Disposition of Gas (Sold, used for fuel, vented, etc.) Sold					Test Witnessed By Apache Corporation
30. List Attachments Deviation Report, Logs, C-102 & C104					
31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief					
Signature		Printed Name Elaine Linton		Title Engineering Technician Date 03/21/2006	
E-mail Address elaine.linton@apachecorp.com					

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn "B"
T. Salt	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates 2648'	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers 2871'	T. Devonian	T. Menefee	T. Madison
T. Queen 3438'	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg 3777'	T. Montoya	T. Mancos	T. McCracken
T. San Andres 4013'	T. Simpson	T. Gallup	T. Ignacio Otzte
T. Glorieta 5256'	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T.
T. Blinebry 5721'	T. Gr. Wash	T. Morrison	T.
T. Tubb 6251'	T. Delaware Sand	T. Todilto	T.
T. Drinkard 6563'	T. Bone Springs	T. Entrada	T.
T. Abo 6826'	T. Rustler 1290'	T. Wingate	T.
T. Wolfcamp	T.	T. Chinle	T.
T. Penn	T.	T. Permian	T.
T. Cisco (Bough C)	T.	T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....

No. 2, from.....to.....

No. 3, from.....to.....

No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology