Office State of No	ew Mexico Form C-103
Office District I – (575) 393-6161 1625 N. French Dr., Hobbs, NM 88240 District II – (575) 748-1283	d Natural Resources Revised July 18, 2013 WELL API NO.
District II - (575) 748-1283	30-025-20212
District II – (575) 748-1283 811 S. First St., Artesia, NM 88210 1 2 20160IL CONSERVA District III – (505) 334-6178	5. Indicate Type of Lease
1220 Douth b	STATE FEE X
1000 Rio Brazos Rd., Aztec, NM 87410 <u>District IV</u> – (505) 476-3460 1220 S. St. Francis Dr., Santa Fe, RECEIVED 87505 Santa Fe, 1	NM 87505 6. State Oil & Gas Lease No.
SUNDRY NOTICES AND REPORTS ON V	WELLS 7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM OPROPOSALS.)	N OR PLUG BACK TO A
	ATER INJECTOR 8. Well Number
2. Name of Operator	9. OGRID Number
CHEVRON U.S.A.INC.	4323
3. Address of Operator	10. Pool name or Wildcat
6301 DEAUVILLE BLVD RM 3002, MIDLAND, TX. 79706	The state of the s
	G -103.50756
	UTH line and790 feet from theEAST line
Section 25 Township 17-S	Range 34-E NMPM County LEA her DR, RKB, RT, GR, etc.)
3,989° GL	ner DR, RRB, RI, GR, etc.)
12. Check Appropriate Box to Indi	cate Nature of Notice, Report or Other Data
NOTICE OF INT	CURCEOUENT REPORT OF
NOTICE OF INT PERFORM REMEDIAL WORK ☐ INT TO PA	SUBSEQUENT REPORT OF:
	REMEDIAL WORK ALTERING CASING
TEMPORARILY ABANDON P&A NR R. X	COMMENCE DRILLING OPNS. P AND A X CASING/CEMENT JOB
PULL OR ALTER CASING P&A R DOWNHOLE COMMINGLE	CASING/CEMENT JOB
CLOSED-LOOP SYSTEM OTHER:	OTHER:
	tate all pertinent details, and give pertinent dates, including estimated date
	NMAC. For Multiple Completions: Attach wellbore diagram of
10/06/16 MOVE IN & RU, ND WH, NU & TEST BOP, POOH	W/ TBG. NOTIFIED MARK WHITAKER W/ NM OCD.
10/07/16 PIH TAG CIRP @5 700' CIR MI F & TEST CSG 500	0 PSI, MIX & SPOT 25 SX CL "C" CMT FROM 5,785'- 5,533',
	X & SPOT 25 SX CL "C" CMT. FROM 2,873'- 2,621'. UPDATED OCD.
10/08/16 RIH TAG PLUG @ 2,600', MIX & SPOT 40 SX CL " 40 SX CL "C" CMT FROM 401'- SURFACE.	C" CMT FROM 1,812'- 1,408', WOC & TAG @ 1,385', MIX & SPOT
10/09/16 VERIFIED CEMENT BACK TO SURFACE CUT AI	LL CASING & ANCHORS & REMOVED 3' BELOW GRADE. WELD
ON DRY HOLE MARKER AS PER RULE 19.15.7.14. OF NM	
ALL CEMENT PLUGS CLASS "C", W/ CLOSED LOOP S	YSTEM.
BOND COVERAGE: CA 0329	
	oved for Plugging of wellbore only. Liability under
bond	d is retained pending restoration and completion
of the	e C-103, Specific for Subsequent Report of
Spud Date: Well	Plugging, which may be found on the OCD
web	page under forms.
I hereby certify that the information above is true and complete t	to the best of my knowledge and belief.
	Agent for Chevron DATE 10 / 10 / 16
Type or print name Monty L. McCarver E-mail address:	monty.mccarver@cjes.com PHONE: _713-325-6288
APPROVED BY: Waller TITLE	P.E.S. DATE 10/12/2016
Conditions of Approval (if any):	Dillo
Conditions of rippioral (II ally).	