	EPARTMENT OF THE I UREAU OF LAND MANA	GEMENT	OCD	Expires	IO. 1004-0135 : July 31, 2010
(August 2007) UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT SUNDRY NOTICES AND REPORTS ON WELLS SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.			5. Lease Serial No. NMNM116166		
2 20 abandoned well	is form for proposals to II. Use form 3160-3 (AP	drill or to re-enter an D) for such proposals.		6. If Indian, Allottee	or Tribe Name
CENSUBMIT IN TRI	PLICATE - Other instruc	ctions on reverse side.		7. If Unit or CA/Agre	ement, Name and/or No
1. Trace Well 8 Oil Well Gas Well Other				8. Well Name and No. EK 29 BS2 FEDERAL COM 3H	
2. Name of Operator MCELVAIN OIL & GAS PROF	TONY G COOPER er@mcelvain.com		9. API Well No. 30-025-42699-00-X1		
 Address 1050 17TH STREET SUITE 1 DENVER, CO 80265-1801 	3b. Phone No. (include area code Ph: 303-893-0933 Ext; 337			10. Field and Pool, or Exploratory E K	
4. Location of Well (Footage, Sec., T.)			11. County or Parish, and State	
Sec 29 T18S R34E SESW 30		LEA COUNTY, NM			
12. CHECK APPF	ROPRIATE BOX(ES) TO	O INDICATE NATURE OF	NOTICE, RI	EPORT, OR OTHE	R DATA
TYPE OF SUBMISSION	TYPE OF ACTION				
□ Notice of Intent	Acidize	Deepen	Product	ion (Start/Resume)	□ Water Shut-Of
	Alter Casing	Fracture Treat	Reclama	ation	U Well Integrity
Subsequent Report	Casing Repair	New Construction	Recomp	lete	Other
Final Abandonment Notice	Change Plans	Plug and Abandon	Tempor	arily Abandon	Well Spud
	Convert to Injection	Plug Back	U Water D	lisposal	
following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi Spudded 17.5" surface hole w	andonment Notices shall be fil nal inspection.)		ompletion in a n	ew interval, a Form 316	0-4 shall be filed once
testing has been completed. Final Ab determined that the site is ready for fi	andonment Notices shall be fil nal inspection.) ith Spudder Rig on 7/19/ it pe ,2 joints casing ,float courface 46 total e of both shoe joints and tom from 1704' to 1820' vel	sults in a multiple completion or rec ed only after all requirements, includ 16 ollar and circulate same then every third joint to surface ce casing set @ 1813' from grou	ompletion in a n ding reclamation 44 joints of ement basket nd level float	ew interval, a Form 316 , have been completed,	0-4 shall be filed once
testing has been completed. Final Ab determined that the site is ready for fi Spudded 17.5" surface hole w 7/23/16 Surface casing cemen 12:30 20:30 8.00 Make up sho 13 3/8" 54.5# STC casing to su 11:30 12:30 centralizers middl at 72'joints wash casing to bott collar @ 1734' from ground lev 21:30 23:59 2.50 12 rig up Hal water ahead with red dye follow	andonment Notices shall be fil inal inspection.) ith Spudder Rig on 7/19/ ith Spudder Rig on 7/1	sults in a multiple completion or rec ed only after all requirements, includ 16 ollar and circulate same then every third joint to surface ce casing set @ 1813' from grou	44 joints of ement basket nd level float om 20 bbls of	ew interval, a Form 316 , have been completed, System	0-4 shall be filed once
testing has been completed. Final Ab determined that the site is ready for fi Spudded 17.5" surface hole w 7/23/16 Surface casing cemen 12:30 20:30 8.00 Make up sho 13 3/8" 54.5# STC casing to su 11:30 12:30 centralizers middl at 72'joints wash casing to bott collar @ 1734' from ground lev 21:30 23:59 2.50 12 rig up Hal water ahead with red dye follow	andonment Notices shall be fil inal inspection.) ith Spudder Rig on 7/19/ ith Spudder Rig on 7/1	sults in a multiple completion or rec ed only after all requirements, inclue 16 ollar and circulate same then every third joint to surface ce casing set @ 1813' from grou it lines to 3000 psi test ok pup 350175 verified by the BLM We OIL & GAS PROP INC, sent to essing by PRISCILLA PEREZ o	44 joints of ement basket nd level float om 20 bbls of Il Information o the Hobbs / n 09/08/2016	ew interval, a Form 316 , have been completed, System	0-4 shall be filed once
testing has been completed. Final Ab determined that the site is ready for fi Spudded 17.5" surface hole w 7/23/16 Surface casing cemen 12:30 20:30 8.00 Make up sho 13 3/8" 54.5# STC casing to su 11:30 12:30 centralizers middl at 72'joints wash casing to bott collar @ 1734' from ground lev 21:30 23:59 2.50 12 rig up Hal water ahead with red dye follow	andonment Notices shall be fil nal inspection.) ith Spudder Rig on 7/19/ ith Spudder Rig on 7/19/ it pe ,2 joints casing ,float ca urface 46 total e of both shoe joints and tom from 1704' to 1820' //el liburton cement head tes wed by 303 bbls of true and correct. Electronic Submission # For MCELVAIN imitted to AFMSS for proce APLIS	sults in a multiple completion or rec ed only after all requirements, inclue 16 ollar and circulate same then every third joint to surface ce casing set @ 1813' from grou it lines to 3000 psi test ok pup 350175 verified by the BLM We OIL & GAS PROP INC, sent to essing by PRISCILLA PEREZ o Title VP DR	44 joints of 44 joints of ment basket nd level float om 20 bbls of 11 Information o the Hobbs n 09/08/2015 ILLING AND 016	System System COMPLETION	0-4 shall be filed once
testing has been completed. Final Ab determined that the site is ready for fi Spudded 17.5" surface hole w 7/23/16 Surface casing cemen 12:30 20:30 8.00 Make up sho 13 3/8" 54.5# STC casing to su 11:30 12:30 centralizers middl at 72'joints wash casing to bott collar @ 1734' from ground lev 21:30 23:59 2.50 12 rig up Hal water ahead with red dye follow 14. I hereby certify that the foregoing is Com Name (<i>Printed/Typed</i>) CHRIS C/	andonment Notices shall be fil nal inspection.) ith Spudder Rig on 7/19/ ith Spudder Rig on 7/19/ it pe ,2 joints casing ,float ca urface 46 total e of both shoe joints and tom from 1704' to 1820' //el liburton cement head tes wed by 303 bbls of true and correct. Electronic Submission # For MCELVAIN imitted to AFMSS for proce APLIS	sults in a multiple completion or rec ed only after all requirements, inclue 16 ollar and circulate same then every third joint to surface ce casing set @ 1813' from grou it lines to 3000 psi test ok pup 350175 verified by the BLM We OIL & GAS PROP INC, sent to essing by PRISCILLA PEREZ o Title VP DR	44 joints of 44 joints of ment basket nd level float om 20 bbls of 11 Information o the Hobbs n 09/08/2015 ILLING AND 016	System System COMPLETION	0-4 shall be filed once
testing has been completed. Final Ab determined that the site is ready for fi Spudded 17.5" surface hole w 7/23/16 Surface casing cemen 12:30 20:30 8.00 Make up sho 13 3/8" 54.5# STC casing to su 11:30 12:30 centralizers middl at 72'joints wash casing to bott collar @ 1734' from ground lev 21:30 23:59 2.50 12 rig up Hal water ahead with red dye follow 14. I hereby certify that the foregoing is Com Name (<i>Printed/Typed</i>) CHRIS C/	andonment Notices shall be fil nal inspection.) ith Spudder Rig on 7/19/ ith Spudder Rig on 7/19/ it pe ,2 joints casing ,float ca urface 46 total e of both shoe joints and tom from 1704' to 1820' //el liburton cement head tes wed by 303 bbls of true and correct. Electronic Submission # For MCELVAIN imitted to AFMSS for proce APLIS	sults in a multiple completion or rec ed only after all requirements, inclue 16 ollar and circulate same then every third joint to surface ce casing set @ 1813' from grou it lines to 3000 psi test ok pup 350175 verified by the BLM We OIL & GAS PROP INC, sent to essing by PRISCILLA PEREZ o Title VP DR	44 joints of 44 joints of ment basket nd level float om 20 bbls of 11 Information the Hobbs/ n 09/08/2016 11 LING AND 016 OFFICE US	System System COMPLETION	0-4 shall be filed once
testing has been completed. Final Ab determined that the site is ready for fi Spudded 17.5" surface hole w 7/23/16 Surface casing cemen 12:30 20:30 8.00 Make up sho 13 3/8" 54.5# STC casing to so 11:30 12:30 centralizers middl at 72'joints wash casing to bott collar @ 1734' from ground lev 21:30 23:59 2.50 12 rig up Hal water ahead with red dye follow 14. I hereby certify that the foregoing is Com Name (<i>Printed/Typed</i>) CHRIS C/ Signature (Electronic S	andonment Notices shall be fil nal inspection.) ith Spudder Rig on 7/19/ it pe ,2 joints casing ,float ca urface 46 total e of both shoe joints and tom from 1704' to 1820' vel liburton cement head tes wed by 303 bbls of true and correct. Electronic Submission # For MCELVAIN imitted to AFMSS for proce APLIS ubmission) THIS SPACE FC	sults in a multiple completion or rec ed only after all requirements, inclue 16 ollar and circulate same then every third joint to surface ce casing set @ 1813' from grou it lines to 3000 psi test ok pup 350175 verified by the BLM We OIL & GAS PROP INC, sent to essing by PRISCILLA PEREZ o Title VP DR Date 09/06/2 DR FEDERAL OR STATE	44 joints of 44 joints of ment basket nd level float om 20 bbls of 11 Information the Hobbs/ n 09/08/2016 11 LING AND 016 OFFICE US	System System GOMPLETION COMPLETION SE U OF LAND/MAN CC	0-4 shall be filed once and the operator has
testing has been completed. Final Ab determined that the site is ready for fi Spudded 17.5" surface hole w 7/23/16 Surface casing cemen 12:30 20:30 8.00 Make up sho 13 3/8" 54.5# STC casing to so 11:30 12:30 centralizers middl at 72'joints wash casing to bot collar @ 1734' from ground lew 21:30 23:59 2.50 12 rig up Hal water ahead with red dye follow 14. I hereby certify that the foregoing is Com Name (<i>Printed/Typed</i>) CHRIS C/ Signature (Electronic S Approved By	andonment Notices shall be fil nal inspection.) ith Spudder Rig on 7/19/ ith pe ,2 joints casing ,float courface 46 total e of both shoe joints and, tom from 1704' to 1820' vel liburton cement head tes wed by 303 bbls of true and correct. Electronic Submission # For MCELVAIN initted to AFMSS for proce APLIS Dubmission) THIS SPACE FC	sults in a multiple completion or rec ed only after all requirements, inclue 16 16 ollar and circulate same then every third joint to surface ce casing set @ 1813' from grou it lines to 3000 psi test ok pup 350175 verified by the BLM We OIL & GAS PROP INC, sent to essing by PRISCILLA PEREZ o Title VP DRI Date 09/06/2 DR FEDERAL OR STATE	44 joints of 44 joints of ement basket nd level float om 20 bbls of 11 Information the Hobbs/ n 09/08/2016 11 LLING AND 1016 OFFICE US	System System 16PP1086SE COMPLETION SE UOV 4/2015 SE UOF LAND/MANCE RISBAD //ELD OF H	0-4 shall be filed once and the operator has

Additional data for EC transaction #350175 that would not fit on the form

32. Additional remarks, continued

1

1

20:30 21:30 1.00 5 Rig down casing crew while circulating with rig pump 2x casing capacity of displacement to 2 BPM bump plug @655PSI took to 1176 Psi floats held 1.5 bbls back 69 bbls cement to surface

7/24/16 6:00 8:00 2.00 21 Cut off 13 3/8" casing at 07:00 hours at ground level and weld cap on same , Release rig @08:00 hour 7/24/2016

Halliburton Surface Casing / Cement Pump Procedure:

20 bbls Fresh Water w/Red Dye, 8.33 ppg 1030 sks ExtendaCem, 13.7 ppg 615 sks HalCem, 14.8 ppg 270 bbls Displacement

The job was started at 21:20 7/23. The lines were tested to 3000 psi. The spacer was mixed and pumped at 6 bpm. The 1030 sks of lead were mixed and pumped at 7 bpm, and the 615 sks of tail cement were mixed and pumped at 6 bpm. The cement was displaced at 6 bpm. The plug bumped at 676 psi and was taken to 1176 psi. Checked the floats and 1.5 bbls returned to the truck. Approximately 69 bbls of cement were circulated to surface.