

30.025-43549

Permit Information:

Well Name: Convoy 28 State Com No. 501H

Location:

SL: 598' FNL & 1275' FEL, Section 28, T-24-S, R-33-E, Lea Co., N.M.

BHL: 230' FSL & 1275' FEL, Section 33, T-24-S, R-33-E, Lea Co., N.M.

Casing Program:

Hole Size	Interval	Csg OD	Weight	Grade	Conn	DF _{min} Collapse	DF _{min} Burst	DF _{min} Tension
14.75"	0 - 1,200'	10.75"	40.5#	J55	STC	1.125	1.25	1.60
9.875"	0 - 5,150'	7.625"	29.7#	HCP-110	LTC	1.125	1.25	1.60
6.75"	0' - 21,192	5.5"	17#	HCP-110	LTC	1.125	1.25	1.60

Cement Program:

Depth	No. Sacks	Wt. ppg	Yld Ft ³ /ft	Slurry Description
1,200'	400	13.5	1.75	Class C + 2% CaCl ₂ + 4% Gel + 0.25 pps Celloflake
	300	14.8	1.34	Class C + 2% CaCl ₂
5,150'	700	12.7	1.90	35:65 Poz:Class C + 6% Gel + 3% CaCl ₂ + 0.5% CPT-45 + 0.45% CPT-20
	250	14.8	1.33	Class C + 0.20% CPT-19
21,192'	750	11.0	3.21	50:50 Poz:Class H + 0.4% CPT-503P + 3.0% CPT-45 + 5.0% Gypsum + 5.0% Salt + 0.15% Citric Acid + 0.15% CPT-20A + 1.0% CPT-19
	1400	14.4	1.20	50:50 Poz:Class H + 0.25% CPT-503P + 0.80% CPT-16A + 0.20% CPT-35 + 0.40% CPT-49 + 0.25% CPT-20A

Mud Program:

Depth	Type	Weight (ppg)	Viscosity	Water Loss
0 - 1,200'	Fresh - Gel	8.6-8.8	28-34	N/c
1,200' - 5,150'	Brine	8.8-10.0	28-34	N/c
5,150' - 21,192' Lateral	Brine	8.8-10.0	28-34	N/c