

Submit 1 Copy To Appropriate District Office
 District I - (575) 393-6161
 1625 N. French Dr., Hobbs, NM 88240
 District II - (575) 748-1283
 811 S. First St., Artesia, NM 88210
 District III - (505) 334-6178
 1000 Rio Brazos Rd., Aztec, NM 87410
 District IV - (505) 476-3460
 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
 Energy, Minerals and Natural Resources

Form C-103
 Revised July 18, 2013

OIL CONSERVATION DIVISION
 1220 South St. Francis Dr.
 Santa Fe, NM 87505

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-025-11970
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>		5. Indicate Type of Lease FEDERAL STATE <input type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator BLM for Patterson Operating & Pumping Inc. DBA/Penergy		6. State Oil & Gas Lease No.
3. Address of Operator NMOCD 1625 N. French Drive Hobbs, NM 88240		7. Lease Name or Unit Agreement Name Glenn Ryan
4. Well Location Unit Letter <u>J</u> : <u>1650</u> feet from the <u>South</u> line and <u>2310</u> feet from the <u>East</u> line Section <u>11</u> Township <u>26S</u> Range <u>37E</u> NMPM County <u>LEA</u>		8. Well Number <u>2</u>
11. Elevation (Show whether DR, RKB, RT, GR, etc.)		9. OGRID Number
10. Pool name or Wildcat Leonard:Queen, South		

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK <input type="checkbox"/> PLUG AND ABANDON <input checked="" type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> MULTIPLE COMPL <input type="checkbox"/> DOWNHOLE COMMINGLE <input type="checkbox"/> CLOSED-LOOP SYSTEM <input type="checkbox"/> OTHER: <input type="checkbox"/>		SUBSEQUENT REMEDIAL WORK [<input type="checkbox"/>] COMMENCE DRILLING OPNS. [<input type="checkbox"/>] CASING/CEMENT JOB [<input type="checkbox"/>] OTHER: _____	INT TO PA <input checked="" type="checkbox"/> P&A NR _____ P&A R _____
--	--	--	--

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

SEE ATTACHED PROCEDURE AND SCHEMATIC

CONTACT NMOCD 24 HOURS PRIOR TO BEGINNING PLUGGING OPERATIONS

HOBBS OCD

JAN 25 2017

Spud Date:

Rig Release Date:

RECEIVED

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Mark Whitaker TITLE Petroleum Engineering Specialist DATE 1/25/2017

Type or print name Mark Whitaker E-mail address: marka.whitaker@state.nm.us PHONE: 575-393-6161

For State Use Only
 APPROVED BY: Markus Brown TITLE AO/II DATE 1/25/2017
 Conditions of Approval (if any): _____

Patterson Operating & Pumping Inc DBA as Penergy
Glenn Ryan No. 2
30-025-11970
UL – J, Sec. 11, T26S, R37E

10 3/4" @ 169' w/ 75 sx cmt
5 1/2" @ 2891' w/ 350 sx cmt
OH completion

1. MIRU. POOH w/ production equipment.
2. Run gauge ring. Set CIBP at 2800'.
3. Circulate hole with mud laden fluid. Spot 70 sx cement on CIBP. WOC and tag. Pressure test casing to 500 psi.
4. Perforate at 1150'. Squeeze w/ 50 sx cement. WOC and tag.
5. Perforate at 220'. Pump sufficient cement to circulate to surface inside/outside 5 1/2" casing.
6. Cut off wellhead 3' below ground level and verify cement to surface all strings.
7. Install below ground P&A marker. Photos should be taken prior to and after welding on plate. OCD should be notified prior to cut off so it can be witnessed.

NOTES: Mud laden fluid consists of 9.5 ppg brine with 25 sx salt gel per 100 bbls of fluid. If casing will not hold pressure, contact the OCD for instructions prior to proceeding with P&A.

