

Carlsbad Field Office OCD Hobbs

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

HOBBS OCD

FEB 06 2017

RECEIVED

FORM APPROVED
OMB No. 1004-0137
Expires October 31, 2014

APPLICATION FOR PERMIT TO DRILL OR REENTER

1a. Type of Work: <input checked="" type="checkbox"/> DRILL <input type="checkbox"/> REENTER		5. Lease Serial No. NMNM120908	
1b. Type of Well: <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other <input checked="" type="checkbox"/> Single Zone <input type="checkbox"/> Multiple Zone		6. If Indian, Allottee or Tribe Name	
2. Name of Operator COG Production LLC. (217955)		7. If Unit or CA Agreement, Name and No.	
3a. Address 2208 West Main Street Artesia, NM 88210		8. Lease Name and Well No. (40143) Windward Federal #9H	
3b. Phone No. (include area code) 575-748-6940		9. API Well No. 30-025-43566	
4. Location of Well (Report location clearly and in accordance with any State requirements.*) At surface 210' FNL & 2000' FEL Unit Letter B (NWNE) SHL Sec. 30 - T24S - R32E At proposed prod. Zone 200' FSL & 2405' FEL Unit Letter O (SWSE) BHL Sec. 31 - T24S - R32E		10. Field and Pool, or Exploratory (97899) WC-025 G-06 S253206M; Bone Spring	
14. Distance in miles and direction from nearest town or post office* Approximately 20 miles East from Malaga		11. Sec., T.R.M. or Blk and Survey or Area Sec. 30 - T24S - R32E	
15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig. Unit line, if any) 200'		12. County or Parish Lea County	
16. No. of acres in lease 1891.72		13. State NM	
17. Spacing Unit dedicated to this well 320		18. Distance from location* to nearest well, drilling, completed, applied for, on this lease, ft. SHL: 50' (Prop. Windward 10H) BHL: 5109'	
19. Proposed Depth TVD: 9,195' MD: 19,245'		20. BLM/BIA Bond No. on file NMB000845 & NMB000860	
21. Elevations (Show whether DF, KDB, RT, GL, etc.) 3551.0'		22. Approximate date work will start* 11/1/2016	
		23. Estimated duration 30 days	

24. Attachments

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, shall be attached to this form:

- Well plat certified by a registered surveyor.
- A Drilling Plan
- A Surface Use Plan (if the location is on National Forest System Lands, the SUPO shall be filed with the appropriate Forest Service Office).
- Bond to cover the operations unless covered by an existing bond on file (see Item 20 above).
- Operator certification
- Such other site specific information and/or plans as may be required by the authorized officer.

25. Signature <i>Mayte Reyes</i>	Name (Printed/Typed) Mayte Reyes	Date 9-6-2016
Title		

Regulatory Analyst Approved by (Signature) <i>Cody Layton</i>	Name (Printed/Typed) Cody Layton	Date 1/27/17
Title FIELD MANAGER		
Office BLM-CARLSBAD FIELD OFFICE		

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Continued on page 2)

APPROVAL FOR TWO YEARS *(Instructions on page 2)

SEE ATTACHED FOR
CONDITIONS OF APPROVAL

KZ
02/06/17

COG Production, LLC - Windward Federal #9H

1. Geologic Formations

TVD of target	9,195' EOL	Pilot hole depth	NA
MD at TD:	19,245'	Deepest expected fresh water:	550'

Formation	Depth (TVD) from KB	Water/Mineral Bearing/ Target Zone?	Hazards*
Quaternary Fill	Surface	Water	
Rustler	712	Water	
Top of Salt	940	Salt	
Base of Salt	4350	Salt	
Lamar	4576	Salt Water	
Bell Canyon	4603	Salt Water	
Cherry Canyon	5509	Oil/Gas	
Brushy Canyon	6893	Oil/Gas	
Bone Spring Lime	8532	Oil/Gas	
U. Avalon Shale	8577	Oil/Gas	
L. Avalon Shale	9038	Oil/Gas	
1st Bone Spring Sand	9624	Oil/Gas	
2nd Bone Spring Sand	X	Oil/Gas	
3rd Bone Spring Sand	X	Oil/Gas	
Wolfcamp	X	Oil/Gas	

2. Casing Program

Hole Size	Casing Interval		Csg. Size	Weight (lbs)	Grade	Conn.	SF Collapse	SF Burst	SF Tension
	From	To							
17.5"	0	740	13.375"	54.5	J55	STC	3.34	1.38	12.74
12.25"	0	4605	9.625"	40	J55	LTC	1.05	1.10	2.82
8.75"	0	19,245	5.5"	17	P110	LTC	1.66	2.98	2.85
BLM Minimum Safety Factor							1.125	1	1.6 Dry 1.8 Wet

Intermediate casing will be kept at least 1/3 full while running casing to mitigate collapse. Intermediate burst based on 0.7 frac gradient at the shoe with Gas Gradient 0.1 psi/ft to surface.

All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.h

COG Production, LLC - Windward Federal #9H

	Y or N
Is casing new? If used, attach certification as required in Onshore Order #1	Y
Does casing meet API specifications? If no, attach casing specification sheet.	Y
Is premium or uncommon casing planned? If yes attach casing specification sheet.	N
Does the above casing design meet or exceed BLM's minimum standards? If not provide justification (loading assumptions, casing design criteria).	Y
Will the intermediate pipe be kept at a minimum 1/3 fluid filled to avoid approaching the collapse pressure rating of the casing?	Y
Is well located within Capitan Reef?	
If yes, does production casing cement tie back a minimum of 50' above the Reef?	N
Is well within the designated 4 string boundary?	
Is well located in SOPA but not in R-111-P?	
If yes, are the first 2 strings cemented to surface and 3 rd string cement tied back 500' into previous casing?	N
Is well located in R-111-P and SOPA?	
If yes, are the first three strings cemented to surface?	N
Is 2 nd string set 100' to 600' below the base of salt?	
Is well located in high Cave/Karst?	
If yes, are there two strings cemented to surface?	N
(For 2 string wells) If yes, is there a contingency casing if lost circulation occurs?	
Is well located in critical Cave/Karst?	
If yes, are there three strings cemented to surface?	N

3. Cementing Program

Casing	# Sks	Wt. lb/ gal	Yld ft3/ sack	H ₂ O gal/sk	500# Comp. Strength (hours)	Slurry Description
Surf.	250	13.5	1.75	9	12	Lead: Class C + 4% Gel + 1% CaCl ₂
	250	14.8	1.34	6.34	8	Tail: Class C + 2% CaCl ₂
Inter.	880	12.7	2.0	9.6	16	Lead: 35:65:6 C Blend
	250	14.8	1.34	6.34	8	Tail: Class C + 2% CaCl
5.5 Prod	640	11.9	2.5	19	72	Lead: 50:50:10 H Blend
	2690	14.4	1.24	5.7	19	Tail: 50:50:2 Class H Blend

Volumes Subject to Observed Hole Conditions and/or Fluid Caliper Results
 Lab reports with the 500 psi compressive strength time for the cement will be onsite for review.

Casing String	TOC	% Excess
Surface	0'	50%
1 st Intermediate	0'	50%
Production	4,105'	25% OH in Lateral (KOP to EOL) – 40% OH in Vertical

4. Pressure Control Equipment

N	A variance is requested for the use of a diverter on the surface casing. See attached for schematic.
---	--

BOP installed and tested before drilling which hole?	Size?	Min. Required WP	Type	x	Tested to:
12-1/4"	13-5/8"	2M	Annular	x	2000 psi
			Blind Ram		
			Pipe Ram		
			Double Ram		
			Other*		
8-3/4"	13-5/8"	3M	Annular	x	50% testing pressure
			Blind Ram	x	
			Pipe Ram	x	
			Double Ram		
			Other*		

BOP/BOPE will be tested by an independent service company to 250 psi low and the high pressure indicated above per Onshore Order 2 requirements. The System may be upgraded to a higher pressure but still tested to the working pressure listed in the table above. If the system is upgraded all the components installed will be functional and tested.

Pipe rams will be operationally checked each 24 hour period. Blind rams will be operationally checked on each trip out of the hole. These checks will be noted on the daily tour sheets. Other accessories to the BOP equipment will include a Kelly cock and floor safety valve (inside BOP) and choke lines and choke manifold. See attached schematics.

X	Formation integrity test will be performed per Onshore Order #2. On Exploratory wells or on that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.i.
Y	A variance is requested for the use of a flexible choke line from the BOP to Choke Manifold. See attached for specs and hydrostatic test chart.
N	Are anchors required by manufacturer?
N	A multibowl wellhead is being used. The BOP will be tested per Onshore Order #2 after installation on the surface casing which will cover testing requirements for a maximum of 30 days. If any seal subject to test pressure is broken the system must be tested.

5. Mud Program

Depth		Type	Weight (ppg)	Viscosity	Water Loss
From	To				
0	Surf. Shoe	FW Gel	8.6 - 8.8	28-34	N/C
Surf csg	9-5/8" Int shoe	Saturated Brine	10 - 10.2	28-34	N/C
9-5/8" Int shoe	Lateral TD	Cut Brine	8.6 - 9.4	28-34	N/C

Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept on location at all times.

What will be used to monitor the loss or gain of fluid?	PVT/Pason/Visual Monitoring
---	-----------------------------

6. Logging and Testing Procedures

Logging, Coring and Testing.	
Y	Will run GR/CNL from TD to surface (horizontal well – vertical portion of hole). Stated logs run will be in the Completion Report and submitted to the BLM.
Y	No Logs are planned based on well control or offset log information.
N	Drill stem test? If yes, explain.
N	Coring? If yes, explain.

Additional logs planned	Interval
N Resistivity	Pilot Hole TD to ICP
N Density	Pilot Hole TD to ICP
Y CBL	Production casing (If cement not circulated to surface)
Y Mud log	Intermediate shoe to TD
N PEX	

7. Drilling Conditions

Condition	Specify what type and where?
BH Pressure at deepest TVD	4495 psi at 9195' TVD
Abnormal Temperature	NO 150 Deg. F.

No abnormal pressure or temperature conditions are anticipated. Sufficient mud materials to maintain mud properties and weight increase requirements will be kept on location at all times.

Sufficient supplies of Paper/LCM for periodic sweeps to control seepage and losses will be maintained on location.

Hydrogen Sulfide (H₂S) monitors will be installed prior to drilling out the surface shoe. If H₂S is detected in concentrations greater than 100 ppm, the operator will comply with the provisions of Onshore Oil and Gas Order #6. If Hydrogen Sulfide is encountered, measured values and formations will be provided to the BLM.

N H₂S is present


Y H₂S Plan attached

8. Other Facets of Operation


N	Is it a walking operation?
N	Is casing pre-set?

x	H ₂ S Plan.
x	BOP & Choke Schematics.
x	Directional Plan


2,000 psi BOP Schematic




3,000 psi BOP Schematic



2M Choke Manifold Equipment (WITH MGS + CLOSED LOOP)




3M Choke Manifold Equipment (WITH MGS + CLOSED LOOP)



COG Production LLC
Rig Plat & Closed Loop Equipment Diagram

Well pad will be 400' X 400' with
cellar in center of pad



Flare Lines will be from both Choke
Manifold & Separator to edge of
location.

"I further certify that COG will comply with Rule 19.15.17
NMAC by using a Closed Loop System."



Midwest Hose
& Specialty, Inc.

Internal Hydrostatic Test Certificate

General Information		Hose Specifications	
Customer	Hobbs	Hose Assembly Type	Rotary/Vibrator
MWH Sales Representative	Ryan Rynolds	Certification	API 7K/FSL Level 2
Date Assembled	11/19/2015	Hose Grade	D
Location Assembled	OKC	Hose Working Pressure	5000
Sales Order #	271739	Hose Lot # and Date Code	11834 11/14
Customer Purchase Order #	302337	Hose I.D. (Inches)	3.5"
Assembly Serial # (Pick Ticket #)	326000	Hose O.D. (Inches)	4.89"
Hose Assembly Length	25'	Armor (yes/no)	No
Fittings			
End A		End B	
Stem (Part and Revision #)	R3.5X64WB	Stem (Part and Revision #)	R3.5X64WB
Stem (Heat #)	A144783	Stem (Heat #)	A144783
Ferrule (Part and Revision #)	RF3.5	Ferrule (Part and Revision #)	RF3.5
Ferrule (Heat #)	J1628	Ferrule (Heat #)	J1628
Connection . Flange Hammer Union Part	4-1/16 5000	Connection (Part #)	4-1/16 5000
Connection (Heat #)	14032501	Connection (Heat #)	1404H321
Nut (Part #)	N/A	Nut (Part #)	N/A
Nut (Heat #)	N/A	Nut (Heat #)	N/A
Dies Used	5.49"	Dies Used	5.49"
Hydrostatic Test Requirements			
Test Pressure (psi)	10,000	Hose assembly was tested with ambient water temperature.	
Test Pressure Hold Time (minutes)	11 1/2		
Date Tested		Tested By	Approved By
11/19/2015			



Midwest Hose
& Specialty, Inc.

Certificate of Conformity

<i>Customer:</i> Hobbs	<i>Customer P.O.#</i> 302337
<i>Sales Order #</i> 271739	<i>Date Assembled:</i> 11/19/2015

Specifications

<i>Hose Assembly Type:</i> Rotary/Vibrator	
<i>Assembly Serial #</i> 326000	<i>Hose Lot # and Date Code</i> 11834 11/14
<i>Hose Working Pressure (psi)</i> 5000	<i>Test Pressure (psi)</i> 10000

We hereby certify that the above material supplied for the referenced purchase order to be true according to the requirements of the purchase order and current industry standards.

Supplier:

Midwest Hose & Specialty, Inc.
3312 S I-35 Service Rd
Oklahoma City, OK 73129

Comments:

<i>Approved By</i>	<i>Date</i>
<i>Kim Thomas</i>	11/19/2015



Midwest Hose
& Specialty, Inc.

Internal Hydrostatic Test Graph

November 19, 2015

Customer: Hobbs


Pick Ticket #: 326000

Hose Specifications

<u>Hose Type</u>	<u>Length</u>
D	25'
<u>I.D.</u>	<u>O.D.</u>
3.5"	4.89"
<u>Working Pressure</u>	<u>Burst Pressure</u>
5000 PSI	Standard Safety Multiplier Applies

Verification

<u>Type of Fitting</u>	<u>Coupling Method</u>
4 1/16 5K	Swage
<u>Die Size</u>	<u>Final O.D.</u>
5.49"	5.50"
<u>Hose Serial #</u>	<u>Hose Assembly Serial #</u>
11834	326000



Test Pressure
10000 PSI

Time Held at Test Pressure
11 2/4 Minutes

Actual Burst Pressure

Peak Pressure
10473 PSI

Comments: Hose assembly pressure tested with water at ambient temperature.

Tested By: James Hawkins

Approved By: Kim Thomas

X _____

X _____

Hose Assembly & Test Report

General Information		Hose Specifications		
Customer	Hobbs	Hose Assembly Type	chose + k11	
Date Assembled	6-26-14	Certification	API 7K	
Location Assembled	Dick	Hose Grade	D	
Sales Order #	216297	Hose Working Pressure	5,000	
Customer Purchase Order #	237512	Hose Lot #	B309	
Hose Assembly Serial #	26022	Hose Date Code	04/12	
Pick Ticket Line Item	0010	Hose I.D. (Inches)	3.5 inches	
Hose Assembly Length (Feet and Inches)	50 feet	Hose O.D. (Inches)	5.49	
Contact Information Phone #		Armor (yes/no)	yes	
Fittings				
End A		End B		
Stem (Part and Revision #)	R3.5 x 64 WD	Stem (Part and Revision #)	R3.5 x 64 WB	
Stem (Heat #)	1314050225	Stem (Heat #)	1314050225	
Stem (Rockwell Hardness HRB #)	—	Stem (Rockwell Hardness HRB #)	—	
Ferrule (Part and Revision #)	RF 3.5	Ferrule (Part and Revision #)	RF 3.5	
Ferrule (Heat #)	126151	Ferrule (Heat #)	372114	
Ferrule (Rockwell Hardness HRB #)	—	Ferrule (Rockwell Hardness HRB #)	—	
Connection (Part #)	4 1/16 SK	Connection (Part #)	4 1/16 SK	
Connection (Heat #)	U3360	Connection (Heat #)	U3360	
Connection (Brinell Hardness HB #)	—	Connection (Brinell Hardness HB #)	—	
Stress Relief #	17614	Stress Relief #	17614	
Welding #	MKR	Welding #	MKR	
X-ray #	—	X-ray #	—	
Assembly Information				
End A		End B		
Skive O.D. (Inches)	5.04	Skive O.D. (Inches)	4.92	
Swager Dies (1st pass)	5.62	Swager Dies (1st pass)	5.53	
Swager Dies (2nd pass)	—	Swager Dies (2nd pass)	—	
Final Swage O.D. (Inches)	5.14	Final Swage O.D. (Inches)	4.98	
Compression % (See Crimp Calculator)	24%	Compression % (See Crimp Calculator)	22%	
Swaged By	Charles Ash			
Hydrostatic Test Requirements				
Test Pressure (psi)	10,000	Hold Time (minutes)	13 1/4	
Tested By	Charles Ash		Date Tested	6-26-14
This is to certify that the above Hose Assembly has been satisfactorily tested in accordance with MHSI procedure 8.2.4.2				
Final Verification				
<input checked="" type="checkbox"/> No	Hammer Unions	Yes	<input checked="" type="checkbox"/> No	
<input checked="" type="checkbox"/> No	Safety Clamps	Yes	<input checked="" type="checkbox"/> No	
Third Party Witness	Customer or Third Party Witnessed By:			

COG Production LLC
 H₂S Equipment Schematic
 Terrain: Shinnery sand hills.

Well pad will be 400' X 400'
 with cellar in center of pad

