

District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30- 025-22550
5. Indicate Type of Lease STATE ☐ FEE ☒
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Livingston Trust
8. Well Number 1
9. OGRID Number 16696
10. Pool name or Wildcat Bagley Permian Penn, North

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐
2. Name of Operator OXY USA Inc.
3. Address of Operator P.O. Box 50250 Midland, TX 79710
4. Well Location Unit Letter: D : 660 feet from the north line and 660 feet from the west line Section 28 Township 11S Range 33E NMPM County Lea
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 4280'

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT F	
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☒	REMEDIAL WORK ☐	INT TO PA ☒
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	P&A NR ☐
PULL OR ALTER CASING ☐	MULTIPLE COMPL ☐	CASING/CEMENT JOB ☐	P&A R ☐
DOWNHOLE COMMINGLE ☐			
CLOSED-LOOP SYSTEM ☐			
OTHER: ☐		OTHER: ☐	

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

NOTIFY OCD 24 HOURS PRIOR TO
BEGINNING PLUGGING OPERATIONS

See Attached

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE David Stewart TITLE Sr. Regulatory Advisor DATE 3/16/17

Type or print name David Stewart E-mail address: david_stewart@oxy.com PHONE: 432-685-5717

For State Use Only

APPROVED BY: Michael Whitaker TITLE Petroleum Engr. Specialist DATE 03/22/2017

Conditions of Approval (if any):

Attachment C-103
OXY USA Inc.
Lovington Trust #1 – 30-025-22550

TD-10200' PBTD-9390' Perfs-9241-9365' CIBP-9400'

12-3/4" 34# csg @ 370' w/ 375sx, 17" hole, TOC-Surf-Circ
8-5/8" 24-32# csg @ 3800' w/ 350sx, 11" hole, TOC-2422'-Calc
4-1/2" 11.6# csg @ 10198' w/ 450sx, 7-7/8" hole, TOC-8152'-Calc

1. RIH & set CIBP @ 9191', M&P 25sx cmt to 8941' *Pressure test casing.*
2. M&P 25sx cmt @ 8565-8315' WOC-Tag
3. Perf 4-1/2" @ 7325', sqz 35sx cmt to 7225' WOC-Tag
4. Perf 4-1/2" @ 6560', sqz 35sx cmt to 6460' WOC-Tag
5. Perf 4-1/2" @ 5160', sqz 35sx cmt to 5060' WOC-Tag
6. Perf 4-1/2" @ 3850', sqz 65sx cmt to 3660' WOC-Tag
7. Perf 4-1/2" @ 2475', sqz 35sx cmt to 2375' WOC-Tag
8. Perf 4-1/2" & 8-5/8" @ 1740', sqz 60sx cmt to 1640' WOC-Tag
9. Perf 4-1/2" & 8-5/8" @ 420', sqz 300sx cmt to surface

10# MLF between plugs

Above ground steel tanks will be utilized

*cut off wellhead 3' below ground level,
verify cmt to surface all strings,
install above ground P&A marker
(upright)*

*T. ANHY 1690'
T. VATES 2425'*

ÖXY USA Inc. - Current
Lovington Trust #1
API No. 30-025-22550

17" hole @ 370'
12-3/4" csg @ 370'
w/ 375sx-TOC-Surf-Circ

11" hole @ 3800'
8-5/8" csg @ 3800'
w/ 350sx-TOC-2422'-Calc

7-7/8" hole @ 10200'
4-1/2" csg @ 10198'
w/ 450sx-TOC-8152'-Calc

CIBP @ 9400' w/ 1sx

Perfs @ 9241-9365'

Perfs @ 9909-10079'

PB-10131'

TD-10200'

OXY USA Inc. - Proposed
 Lovington Trust #1
 API No. 30-025-22550

300sx @ 420'-Surface

60sx @ 1740-1640' WOC-Tag

35sx @ 2475-2375' WOC-Tag

65sx @ 3850-3660' WOC-Tag

35sx @ 5160-5060' WOC-Tag

35sx @ 6560-6460' WOC-Tag

35sx @ 7325-7225' WOC-Tag

25sx @ 8565-8315' WOC-Tag

CIBP @ 9191' w/ 25sx to 8941'

CIBP @ 9400' w/ 1sx

PB-10131'



Perf @ 420'

17" hole @ 370'
 12-3/4" csg @ 370'
 w/ 375sx-TOC-Surf-Circ

Perf @ 1740'

Perf @ 2475'

Perf @ 3850'

11" hole @ 3800'
 8-5/8" csg @ 3800'
 w/ 350sx-TOC-2422'-Calc

Perf @ 5160'

Perf @ 6560'

Perf @ 7325'

Perfs @ 9241-9365'

Perfs @ 9909-10079'

7-7/8" hole @ 10200'
 4-1/2" csg @ 10198'
 w/ 450sx-TOC-8152'-Calc

TD-10200'