

Submit 1 Copy To Appropriate District
Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-025-21080
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name EVGSAU Tr 2864
8. Well Number 400E
9. OGRID Number 217817
10. Pool name or Wildcat Vacuum; Glorieta/SA

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator
ConocoPhillips Company

3. Address of Operator
600 N. Dairy Ashford Rd. Houston, TX 77079

4. Well Location
Unit Letter **E** : **2322** feet from the **North** line and **660** feet from the **West** line
Section **28** Township **17-S** Range **35-E** NMPM County **Lea**

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3944' GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT F	
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☒	REMEDIAL WORK ☐	INT TO PA Pm X P&A NR _____ P&A R _____
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	
PULL OR ALTER CASING ☐	MULTIPLE COMPL ☐	CASING/CEMENT JOB ☐	
DOWNHOLE COMMINGLE ☐			
CLOSED-LOOP SYSTEM ☐			
OTHER: ☐		OTHER: _____	

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

--MIRU. ND WH, NU BOP. Release & POOH RBP @ 1498'
--Tag RBP @ 4000' - Circ hole w/ MLF. Spot 25sx cmt @ 4000' - 3700'. WOC-Tag
--Spot 25sx cmt @ 3200' - 3000'. WOC-Tag
--Perf @ **1750'** - Sqz 55sx cmt - disp TOC to 1650'. WOC-Tag
--Perf @ 250' - Circ 80sx cmt to surface
--POOH. Fill wellbore. Verify cmt @ surface in all annuli

ISOLATE HOLES IN CASING PRIOR TO PERFORATING

NOTIFY OCD 24 HOURS PRIOR TO
BEGINNING PLUGGING OPERATIONS

... from this wellbore and disposed of required by OCD Rule 19.15.17**

Spud Date: **9/22/64**

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE **[Signature]** TITLE **P&A A.M. - Basic Energy Services** DATE **5/1/17**

Type or print name **Greg Bryant** E-mail address: PHONE: **432-563-3355**

For State Use Only

APPROVED BY: **[Signature]** TITLE **Petroleum Engr. Specialist** DATE **05/04/2017**


Conditions of Approval (if any):

WELLBORE SKETCH
ConocoPhillips Company -- Permian Basin Business Unit

Date: 4/5/2017

RKB @ 3533'
 DF @ 3533'
 GL @ 3522'

Subarea :	Buckeye	
Lease & Well No. :	EVGSAU	No. 2864-400
Legal Description :	2322' FNL & 660' FWL., Sec. 28, T-17-S, R-35-E	
County :	Lea	State : New Mexico
Field :	Vaccum	
Date Spudded :	9/22/1964	
API Number :	30-025-21080	



8-5/8" 24# J-55 @ 1700'
 Cmt'd w/ 640 sx
 TOC @ Surface

RBP @ 1498'

There is a casing leak somewhere in this area

RBP @ 4000'

Fish @ 4,523'

Glorietta Perfs: 4518' - 4603'

CIBP w/ 35' cement @ 7040'
 Abo Perfs: 7060' - 7106'

CIBP w/ 13' fill @ 4687'

Drillable BP w/ cement @ 6031'
 Glorietta Perfs: 6126' - 6159'

4-1/2" 9.5# J-55 @ 6250'
 Cmt'd w/ 800 sx
 TOC @ 2600'

T.S.


PBTD @ 6199'
 TD @ 6250'

WELLBORE SKETCH
ConocoPhillips Company -- Permian Basin Business Unit

Date: 4/5/2017

RKB @ 3533'
 DF @ 3533'
 GL @ 3522'

Subarea : Buckeye
 Lease & Well No. : EVGSAU No. 2864-400
 Legal Description : 2322' FNL & 660' FWL,, Sec. 28, T-17-S, R-35-E
 County : Lea State : New Mexico
 Field : Vaccum
 Date Spudded : 9/22/1964
 API Number : 30-025-21080



P&S 80sx cmt @ 250'-3'

8-5/8" 24# J-55 @ 1700'
 Cmt'd w/ 640 sx
 TOC @ Surface

RBP @ 1498' (POOH)

P&S 55sx cmt @ 1800'-1650' - Tag

There is a casing leak somewhere in this area

Spot 25sx cmt @ 3200'-3000' - Tag

Spot 25sx cmt @ 4000'-3700' - Tag

RBP @ 4000'

Fish @ 4,523'

Glorietta Perfs: 4518' - 4603'

CIBP w/ 35' cement @ 7040'
 Abo Perfs: 7000' - 7100'

CIBP w/ 13' fill @ 4687'

Drillable BP w/ cement @ 6031'
 Glorietta Perfs: 6126' - 6159'

4-1/2" 9.5# J-55 @ 6250'
 Cmt'd w/ 800 sx
 TOC @ 2600'

PBTD @ 6199'
 TD @ 6250'