

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised August 1, 2011

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-025-35990
5. Indicate Type of Lease STATE ☒ FEE ☒
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name COOPER 5
8. Well Number 009
9. OGRID Number 162683
10. Pool name or Wildcat MONUMENT; TUBB

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other

2. Name of Operator
CIMAREX ENERGY CO. OF COLORADO

3. Address of Operator
600 N. MARIENFELD, SUITE 600, MIDLAND, TEXAS 79701

4. Well Location

Unit Letter: B : 924 feet from the NORTH line and 1936 feet from the EAST line
Section 05 Township 20S Range 37E NMPM LEA County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3,557' - GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT RE

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING/CEMENT JOB ☐

INT TO PA ☒
P&A NR
P&A R

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

- Pressure test cs.g.
- 1) SET 4-1/2" CIBP @ 6,450'; CIRC. WELL W/ PXA FLUID; PUMP 25 SXS. CMT. @ 6,450'-6,290' (T/TUBB).
 - 2) PUMP 25 SXS. CMT. @ 5,303'-5,153' (T/GLOR). 3880'
 - 3) PUMP 50 SXS. CMT. @ 3,850'-3,490' (DV TOOL, T/GRBG.); WOC X TAG CMT. PLUG.
 - 4) PUMP 25 SXS. CMT. @ 2,542'-2,422' (T/YATES, B/SALT); WOC X TAG CMT. PLUG.
 - 5) PUMP 25 SXS. CMT. @ 1,295'-1,095' (8-5/8" CSG.SHOE, T/SALT); WOC X TAG CMT. PLUG.
 - 6) MIX X CIRC. TO SURF. 25 SXS. CMT. @ 200'-3'. 250'
 - 7) DIG OUT X CUT OFF WELLHEAD 3' B.G.L.; WELD ON STEEL PLATE TO CSGS. X INSTALL DRY HOLE MARKER.

Verify cmt to surface all strings

Spud Date:

R

NOTIFY OCD 24 HOURS PRIOR TO
BEGINNING PLUGGING OPERATIONS

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE David A. Eyler TITLE: AGENT

DATE: 05/04/17

Type or print name: DAVID A. EYLER

E-mail address: DEYLER@MILGRO-RES.COM PHONE: 432.687.3033

For State Use Only

APPROVED BY: Mark W. Pataki TITLE: Petroleum Engr. Specialist DATE: 05/11/2017

Conditions of Approval (if any):



KB: 17' above GL

Cimarex Energy Co. of Colorado

Cooper 5-9 (Monument Field)

924' FNL & 1936' FEL

Sec. 5, T-20S, R-37E, Lea Co., NM

H. Eads

6/7/2012

12-1/4" Hole

8-5/8" 24# J-55 csg @ 1245' - 29 jts
cmtd w/ 580 sx, 111 sx cmt circ

DV Tool @ 3830'

Rods : 172 - 3/4" D rods
85 - 7/8" D rods

Pump: 2" X 1-1/4" X 20' RHBC

204 jts 2-3/8" 4.7# 8rd J-55 Tbg

Tubb perms: (6485' - 6491')

7-7/8" Hole

4-1/2", 11.6# P-110 csg @ 6800' - 185 jts
cmt w/ 1510 sx (Stg 1: 560, circ 80 & Stg 2: 950, circ 20)

PBTD @ 6745'

TD @ 6800'

CIMAREX

KB: 17' above GL

Cimarex Energy Co. of Colorado

Cooper 5-9 (Monument Field)

924' FNL & 1936' FEL

Sec. 5, T-20S, R-37E, Lea Co., NM

H. Eads

6/7/2012

12-1/4" Hole

18-5/8" 24# J-55 csg @ 1245' - 29 jts

cmtd w/ 580 sx, 111 sx cmt circ

CIRC. 25 SXS. CMT. @ 200' - 3'

PXA
MUD

Pump 25 SXS. CMT. @ 1295' - 1095' TAG

PXA
MUD

Pump 25 SXS. CMT. @ 2542' - 2422' TAG

PXA
MUD

DV Tool @ 3830'

Pump 50 SXS. CMT. @ 3850' - 3490' TAG

PXA
MUD

Pump. 25 SXS. CMT. @ 5303' - 5153'

PXA
MUD

Pump 25 SXS. CMT. @ 6450' - 6290'

SET 4 1/2" CD3P @ 6450'

Tubb perms: (6485' - 6491')

7-7/8" Hole

4-1/2", 11.6# P-110 csg @ 6800' - 185 jts

cmt w/ 1510 sx (Stg 1: 560, circ 80 & Stg 2: 950, circ 20)

PBTD @ 6745'

TD @ 6800'

DAE 03/31/14