

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources
OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised August 1, 2011

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-025-33876
1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐		5. Indicate Type of Lease STATE ☐ FEE ☒
2. Name of Operator Chevron USA INC		6. State Oil & Gas Lease No.
3. Address of Operator 6301 DEAUVILLE BLVD., MIDLAND, TX 79706		7. Lease Name or Unit Agreement Name Chambers Strawn Unit
4. Well Location Unit Letter L : 2,281 feet from the South line and 531 feet from the West line Section 8 Township 16S Range 36E NMPM County Lea		8. Well Number: 2
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3,938' GL		9. OGRID Number 14179 4323
		10. Pool name or Wildcat Shoe Bar, Strawn NE

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:
PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT
REMEDIAL WORK
COMMENCE DRILLING OPNS
CASING/CEMENT JOB

INT TO P&A ☒
P&A NR
P&A R

OTHER: ☐

OTHER: TEMPOF. ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 13-3/8" @ 454' TOC Surface, 8-5/8" @ 4,100' TOC Surface, 5-1/2" @ 11,831' TOC @ 2,575', Perforations 11,444'-11,464', DV tool @ 8,212'.

Chevron USA INC respectfully request to abandon this well as follows:

1. Call and notify NMOCD 24 hrs before operations begin.
2. MIRU, NDWH, NU BOPE, POOH w/ packer & tbq.
3. Set CIBP @ 11,400', circ MLF, spot 30 sx of CL "H" cement on top of CIBP, WOC/Tag/Test.
4. Spot 25 sx Class "H" cement plug at 9,675' - 9,475' (Wolfcamp).
5. Spot 25 sx Class "H" cement plug at 8,265' - 8,065', WOC & tag (DV tool, Abo).
6. Spot 25 sx Class "C" cement plug at 6,400' - 6,200' (Glorieta).
7. Spot 25 sx Class "C" cement plug at 4,795' - 4,595', WOC & tag (San Andres).
8. Spot 25 sx Class "C" cement plug at 4,150' - 3,950', WOC & tag (Shoe).
9. Spot 25 sx Class "C" cement plug at 3,200' - 3,000', WOC & tag (B.Salt, Yates).
10. Perf @ 2,000' and sqz 60 sx Class "C" cement f/ 1,800' t/ 2,000', WOC & tag (T.Salt).
11. Perf @ 505' and sqz 145 sx Class "C" cement f/ Surface t/ 505' (Shoe, FW, Surf).
12. Cut all casings & anchors & remove 3' below grade. Verify cement to surface & weld on dry hole marker. Clean location.

Note: All cement plugs class "C" or "H" with closed loop system used.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE [Signature] TITLE Engineer DATE 8/8/17

Type or print name Howie Lucas E-mail address: howie.lucas@chevron.com PHONE: (832)-588-4044

For State Use Only

APPROVED BY: [Signature] TITLE Petroleum Engr. Specialist DATE 08/10/2017

Conditions of Approval (if any):

Current WBD - Chambers Strawn Unit 2

Southeastern New Mexico

Created: 07/27/17 By: M. Stewart
 Updated: 08/09/17 By: H. Lucas
 Lease: Chambers Strawn Unit
 Field: Shoe Bar NE
 Surf. Loc.: 2281' FSL & 531' FWL
 Bot. Loc.:
 County: Lea St.: NM
 Status: Production Well

Well #: 2 St. Lse:
 API: 30 025 33876
 Unit Ltr.: L Section: 8
 TSHP/Rng: 16S / 36E
 Unit Ltr.: Section:
 TSHP/Rng:
 Directions: Buckeye, NM

T. Anhy
 T. Salt
 B. Salt
 T. Yates
 T. 7 Rivers
 T. Queen
 T. Grayburg
 T. San Andres 4744'
 T. Glorieta 6348'
 T. Paddock 6906'
 T. Binebry
 T. Tubbs 7514'
 T. Drinkard 7772'
 T. Abo 8194'
 T. Wolfcamp 9624'
 T. Perm 10940'
 T. Cisco (Bough C)
 T. Canyon
 T. Strawn 11434'
 T. Azoka 11624'
 T. Miss
 T. Devonian
 T. Silurian
 T. Montoya
 T. Simpson
 T. McKee
 T. Ellenburger
 T. Gr. Wash
 T. Delaware Sand
 T. Bone Springs
 T.
 T.
 T.

Surface Casing

Size: 13 3/8"
 Wt., Grd.: 54.5 #, K-55
 Depth: 454'
 Cmt: 450 sxs
 Circulate: Yes
 TOC: Surface
 Hole Size: 17 1/2"

Intermediate Casing

Size: 8 5/8"
 Wt., Grd.: 32#; S-80
 Depth: 4100'
 Cmt: 1155 sxs
 Circulate: Yes
 TOC: Surface
 Hole Size: 11"

Production Casing

Size: 5 1/2"
 Wt., Grd.: 17#; N-80
 Depth: 11,831'
 Cmt: 1535 sxs
 Circulate: No
 TOC: 2575' WBD
 Hole Size: 7 7/8"

DV Tool
 8212

ROD DETAILS

Item Des	OD (in)	Grade	Len (ft)	Jts	Top (FWS)	Bot (FWS)
Packer Rod	1.00		25.00	1	25.00	20.00
Rod Sub	1.00		8.00	1	48.00	33.00
Rod Sub	1.00		4.00	1	52.00	34.00
Bucker Rod	1.00		1,050.00	42	53.00	1,103.00
Bucker Rod	1.00		4,425.00	177	1,108.00	5,513.00
Bucker Rod	1.00		5,725.00	229	5,531.00	11,256.00
Bucker Sp	1.13		205.00	8	11,256.00	11,461.00
Work Pump	1.34		24.00		11,480.00	11,480.00

2 7/8" 6.5# L-80 Tubing

TAC set at 11383' in 15,000 lbs tension
 SN: 11479
 History notes significant paraffin issues

Perforations: Strawn
 11,444-11454'

PBTD: 11,739
 TD: 11,831

Proposed WBD - Chambers Strawn Unit 2

Southeastern New Mexico

Created: 07/27/17 By: M. Stewart
 Updated: 08/08/17 By: H. Lucas
 Updated: By:
 Lease: Chambers Strawn Unit
 Field: Shoe Bar NE
 Surf. Loc.: 2281' FSL & 531' FWL
 Bot. Loc.:
 County: Lea St.: NM
 Status: Production Well

Well #: 2 St. Lse
 API: 30-025-33876
 Unit Ltr.: L Section: 8
 TSHR/Rng: 16S / 36E
 Unit Ltr.: Section:
 TSHR/Rng:
 Directions: Buckeye, NM

T. Anby
 T. Salt
 B. Salt
 T. Yates
 T. 7 Rivers
 T. Queen
 T. Grayburg
 T. San Andres
 T. Glorieta
 T. Padlock
 T. Blinberry
 T. Tubbs
 T. Drinkard
 T. Abo
 T. Wolfcamp
 T. Perm
 T. Cisco (Bough C)
 T. Canyon
 T. Strawn 11434'
 T. Atoka 11624'
 T. Miss
 T. Devonian
 T. Silurian
 T. Montoya
 T. Simpson
 T. McKee
 T. Ellenburger
 T. Gr. Wash
 T. Delaware Sand
 T. Bone Springs
 T.
 T.
 T.
 T.

Surface Casing
 Size: 13 3/8"
 Wt., Grd.: 54.5 #, K-55
 Depth: 454'
 Cmt: 450 sxs
 Circulate: Yes
 TOC: Surface
 Hole Size: 17 1/2"

Intermediate Casing
 Size: 8 5/8"
 Wt., Grd.: 32#, S-80
 Depth: 4100'
 Cmt: 1155 sxs
 Circulate: Yes
 TOC: Surface
 Hole Size: 11"

Production Casing
 Size: 5 1/2"
 Wt., Grd.: 17#, N-80
 Depth: 11,831'
 Cmt: 1535 sxs
 Circulate: No
 TOC: 2575' WBD
 Hole Size: 7 7/8"

Perforations: Strawn
 11,444-11464'

