

Submit 1 Copy To Appropriate District Office

District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

HOBBS OCD

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.
Santa Fe, NM 87505

AUG 21 2017

RECEIVED

WELL API NO. 30-025-40170
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Good Chief State
8. Well Number 1
9. OGRID Number 281085
10. Pool name or Wildcat Comanche Stateline Tansil-Yates

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator
RMR Operating, LLC

3. Address of Operator
14282 Gillis Rd. Farmers Branch, Texas 75244-3715

4. Well Location
Unit Letter A : 330 feet from the North line and 330 feet from the South line
Section 28 Township 26S Range 36E NMPM County Lea

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
2943' GL

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
CLOSED-LOOP SYSTEM ☐
OTHER: ☐

SUBSEQUENT

REMEDIAL WORK
COMMENCE DRILLING OPNS
CASING/CEMENT JOB

INT TO PA Pm
P&A NR _____
P&A R _____

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

② Circulate hole with 9.5# Brine w/ 12.5# gel/BB1 Pressure test csg to 500psi

① Set CIBP at 3165'. (Top Perf @3215')

Spot 25 sx on top CIBP.

Spot 25 sxs cmt at 2950'. 1477' WOC & TAG (Shoe plug)

Spot 100' cmt plug from 400' to 300' (Fresh Water Plug)

Spot 25 sx cmt 250' to surface

Spot 10 sxs cmt surface plug.

Cut-off wellhead. Install marker. Clean Location

Spud Date:

Verify cement to
surface all strings

Rig Release Date:

NOTIFY OCD 24 HOURS PRIOR TO
BEGINNING PLUGGING OPERATIONS

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Ross Pearson TITLE V.P. Operations DATE 8/18/17

Type or print name Ross Pearson E-mail address: ross@redmountainresources.com PHONE: 469-995-0425

For State Use Only

APPROVED BY: Maureen L. Stetson TITLE Petroleum Engr. Specialist DATE 08/21/2017

Conditions of Approval (if any):

**Good Chief State #1
330' FNL, 330' FEL
Section 28, T-26-S, R-36-E
Lea County, New Mexico**

SPUD: 07/31/2011
COMP: 08/13/2011
DATUM: G.L. 2907'
K.B. 2920'

WELLBORE DIAGRAM - NOT TO SCALE

OPEN HOLE LOGS:

Halliburton

DSN/SG
dated 07-26-11 (7-7/8" hole)

DLL/MG
dated 07-26-11 (7-7/8" hole)

BSAT
dated 07-26-11 (7-7/8" hole)

REFERENCE LOG:

Halliburton

DSN/SG
dated 07-26-11 (7-7/8" hole)

7-7/8"
HOLE

← TOC @ Surface

8-5/8" 32# J-55 STC
csg @ 1427'

← 2-7/8" 6.5# J-55 8rd EUE
TBG @ ?'

TAC @ 3028'

SN @ 3095'

Perf Sub @ 3099'

Collar & Bullplug @ 3132

KB 3142'

5-1/2" 17# L-80 LTC csg @ 3,873'

TOC @ Surface

Tansill PERFS.:
3,215' - 3,222.5'

Yates 1 PERFS.:
3409' - 3419'

Yates 2 PERFS.:
3565' - 3575'

PBTD: 3,828'

TD: 3,874'