

*Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources
OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised July 18, 2013

WELL API NO. 30-025-30798	
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>	
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name VACUUM GRAYBURG SAN ANDRES UNIT	
8. Well Number 147	
9. OGRID Number 4323	
10. Pool name or Wildcat VACUUM GRAYBURG SAN ANDRES	
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other <u>INJECTOR</u>	
2. Name of Operator CHEVRON U.S.A. INC.	
3. Address of Operator 6301 DEAUVILLE BLVD, MIDLAND, TX 79706	
4. Well Location Unit Letter <u>H</u> : <u>1360</u> feet from the <u>NORTH</u> line and <u>660</u> feet from the <u>EAST</u> line Section <u>2</u> Township <u>18-S</u> Range <u>34-E</u> NMPM County <u>LEA</u>	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 4,004' (GL)	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	P AND A <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	MULTIPLE COMPL <input type="checkbox"/>	CASING/CEMENT JOB <input type="checkbox"/>	
DOWNHOLE COMMINGLE <input type="checkbox"/>			
CLOSED-LOOP SYSTEM <input type="checkbox"/>			
OTHER: <input type="checkbox"/>	REPLACE PACKER <input type="checkbox"/>	OTHER: <input type="checkbox"/>	REPLACE PACKER <input checked="" type="checkbox"/>

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Completed operations:

MIRU, set plug and NU BOP. Pull plug and kill well, TOO H w/ tbg and pkr. RIH w/ RBP to test casing, set @ 4215' and tested good. RIH w/ bit to C/O to PBTD @ 4824'. RIH w/ treating packer to 4,188' and pump 6000 gal 15% HCl. RIH w/ new packer and set @ 4210'. RDMO and perform MIT to return to injection.

Updated WBD below.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE [Signature] TITLE Production Engineer DATE 9/21/17

Type or print name Michael Stewart E-mail address: michael.stewart@chevron.com PHONE: 432-687-7431

For State Use Only

APPROVED BY: [Signature] TITLE Petroleum Engineer DATE 09/22/17
Conditions of Approval (if any):

VGSAU #147 Wellbore Diagram

Created: 11/05/03 By: SMG
 Updated: 04/01/08 By: BSPT
 Updated: 08/31/09 By: NC
 Updated: 05/01/17 By: MAS
 Lease: Vacuum Grayburg San Andres Unit
 Field: Vacuum Grayburg San Andres Unit
 Surf. Loc.: 1,360' FNL & 660' FEL
 Bot. Loc.:
 County: Lea St.: NM
 Status: Active Injection Well

Well #: 147 St. Lse: 857948
 API: 30-025-30798
 Unit Ltr.: H Section: 2
 TSHP/Rng: S-18 E-34
 Unit Ltr.: Section:
 TSHP/Rng:
 Directions: Buckeye, NM
 Chevno: QU2458

Surface Casing

Size: 8 5/8"
 Wt., Grd.: 24# WC-50
 Depth: 1,530'
 Sxs Cmt: 650
 Circulate: 180 sx
 TOC: Surface
 Hole Size: 11"

KB: 4,018
 DF: 4,017
 GL: 4,004
 Ini. Spud: 08/21/93
 Ini. Comp.: 09/19/93

Production Casing

Size: 5 1/2"
 Wt., Grd.: 15.5# WC-50
 Depth: 4,900'
 Sxs Cmt: 1,400
 Circulate: 124 sx
 TOC: Surface
 Hole Size: 7 7/8"

