

# CURRENT WELLBORE DIAGRAM

Configured for SWD Service

Nemo Fund I, LLC

Lewis Fee SWD #1

API # 30-025-34236

1230' FSL x 2544' FWL, UL 'L' Sec 31, T9S, R37E, Lea County, NM

Per SWD-1651; max 2492 psi

SWD; Devonian (96101)

MIT 4/07/17 - 565 psi/ 30 mins. - Pass

All Depths KB

KB 4005'

GL 3989'

17-1/2" Hole

13-3/8" 48# J-55

**Set @ 475'**

Cement to surface: yes

T. Yates 2875'

12-1/4" Hole

8-5/8" 28/32# K55

**Set @ 4172'**

Cement to surface: yes

T. San Andres 4215'

T. Glorieta 5610'

T. Wolfcamp 9020'

T. Penn 9785'

T. Strawn 10645'

T. Atoka 11230'

T. Miss 11860'

T. Devonian 12420'

7-7/8" Hole

5-1/2" 17# J55

**Set @ 12460'**

Cement to surface: no

TOC @ 4190' (TS)

2-7/8" 6.5# IPC Tbg

TOC @ 4190' (TS)

Pkr Fluid in Annulus

Inj Pkr set below 12,360'

7-7/8" Open Hole  
12460' - 12505'

4-3/4" Open Hole  
12505' - 12705'

PBTD 12700'

TD @ 12705'

Drawing Not to Scale

Existing WBD Updated by:

Ben Stone 9/22/2017

(Original by: DJH)