

Submit 1 Copy To Appropriate District Office
 District I - (575) 393-6161
 1625 N. French Dr., Hobbs, NM 88240
 District II - (575) 748-1283
 811 S. First St., Artesia, NM 88210
 District III - (505) 334-6178
 1000 Rio Brazos Rd., Aztec, NM 87410
 District IV - (505) 476-3460
 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
 Energy, Minerals and Natural Resources

Form C-103
 Revised August 1, 2011

OIL CONSERVATION DIVISION
 1220 South St. Francis Dr.
 Santa Fe, NM 87505

HOBBS
 OCT 13 2017
 RECEIVED

WELL API NO. 30-025-34587
5. Indicate Type of Lease STATE X FEE
6. State Oil & Gas Lease No. V-4362
7. Lease Name or Unit Agreement Name Rancho Verde 10 State
8. Well Number 001
9. OGRID Number 212929
10. Pool name or Wildcat Wolf Camp
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 4319 GL

SUNDRY NOTICES AND REPORTS ON WELLS
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well X Gas Well Other

2. Name of Operator
Everquest Energy Corp

3. Address of Operator
10 Desta Drive, Suite 300, Midland, TX 79705

4. Well Location
 Unit Letter L : 2310 feet from the South line and 930 feet from the West line
 Section 10 Township 16S Range 32E NMPM Lea County

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF II PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> DOWNHOLE COMMINGLE <input type="checkbox"/> OTHER: <input type="checkbox"/>	SUBSEQUENT REPORT OF: REMEDIAL WORK <input type="checkbox"/> ALTERING CASING <input type="checkbox"/> COMMENCE DRILLING OPNS. <input type="checkbox"/> P AND A XX CASING/CEMENT JOB <input type="checkbox"/> OTHER: <input type="checkbox"/>
--	---

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Approved for Plugging of wellbore only. Liability under bond is retained pending restoration and completion of the C-103, Specific for Subsequent Report of Well Plugging, which may be found on the OCD web page under forms.
 Restoration Due By 10-09-2018

ATTACHED

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Denise Jones TITLE Regulatory Analyst DATE 10-12-17
 Type or print name Denise Jones E-mail address: djones@Cambrianmgmt.com PHONE: 432-620-9181
For State Use Only
 APPROVED BY: Martha Whitaker TITLE P.E.S. DATE 10/16/2017
 Conditions of Approval (if any):

Plugging Report
Rancho Verde 10 State #1
API: 30-025-34587

10/3/2017 Move in rig and plugging equipment. Installed BOP. Rigged up and tallied out of hole with tubing.

10/4/2017 RIH with packer to 4387'. Left unset and circulated 5 1/2" casing full. Set packer and tested 5 1/2" casing to 500#. Good. Opened 5 1/2" X 8 5/8" annulus to the tank. Pumped 100 bbls brine down the tubing, under the packer to the bad casing at 4862' and up the intermediate annulus to surface until the returns cleaned up. Mixed 50 sx Class C cement with CaCl and displaced below the packer. WOC 3 hrs. Unset packer and tagged cement at 4736'. 126' above the bad casing at 4862'. POOH with the packer and started taking the bolts off of the top spool to expose the 5 1/2" casing stub. SION.

10/5/2017 Finished removing top spool and exposed 5 1/2" casing. Welded on 5 1/2" pull stub and pulled casing off of the slips. Cut casing at 4287'. Picked up foster casing tongs and laid down 104 full joints of casing and the top and bottom cut offs. Reassembled wellhead, installed BOP and SION.

10/6/2017 RIH to 4352' with tubing and circulated MLF. Spotted 50 sx Class C cement with CaCl. Stood back 15 stands and closed in well. WOC. Opened tubing. It was on a strong vacuum. RIH to tag. No tag. Spotted another 50 sx Class C cement with CaCl at 4352'. Stood back 15 stands and shut down.

10/9/2017 RIH and tagged at 4285'. Spotted 50 sx Class C cement with CaCl at 4285'. WOC and tagged at 4146'. POOH to 2510' and spotted 40 sx Class C cement. ETOC at 2359'. POOH to 1270' and spotted 40 sx Class C cement. ETOC at 1119'. POOH to 476' and spotted 40 sx Class C cement. SION. Will tag in the morning.

10/10/2017 Tagged cement at 317'. POOH to 63' and circulated cement to surface with 20 sx. Rigged down. Dug out cellar and cut off well head. Cement was to surface inside 13 3/8" and 8 5/8" casing. Installed marker and cut off anchors.