

F/F

Form 3160-3
(March 2012)

HOBBS OCD
NOV 29 2017
RECEIVED
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

APPLICATION FOR PERMIT TO DRILL OR REENTER

FORM APPROVED
OMB No. 1004-0137
Expires: October 31, 2014

5. Lease Serial No.
NMNM97153

6. If Indian, Allottee or Tribe Name

7. If Unit or CA Agreement, Name and No.

8. Lease Name and Well No.
VACA DRAW 9418 10 FED 8H

9. API Well No.
30-025-44250

10. Field and Pool, or Exploratory
RED HILLS / UPPER BONE SPRING SH

11. Sec., T. R. M. or Blk. and Survey or Area
SEC 10 / T25S / R33E / NMP

12. County or Parish
LEA

13. State
NM

1a. Type of work: ☒ DRILL ☐ REENTER

1b. Type of Well: ☒ Oil Well ☐ Gas Well ☐ Other ☒ Single Zone ☐ Multiple Zone

2. Name of Operator
BTA OIL PRODUCERS LLC (260297)

3a. Address
104 S. Pecos Midland TX 79701

3b. Phone No. (include area code)
(432)682-3753

4. Location of Well (Report location clearly and in accordance with any State requirements.)*

At surface NWNW / 200 FNL / 520 FWL / LAT 32.151786 / LONG -103.567083

At proposed prod. zone SWSW / 50 FSL / 330 FWL / LAT 32.137955 / LONG -103.567713

14. Distance in miles and direction from nearest town or post office*
22 miles

15. Distance from proposed*
location to nearest 50 feet
property or lease line, ft.
(Also to nearest drig. unit line, if any)

16. No. of acres in lease
640

17. Spacing Unit dedicated to this well
160

18. Distance from proposed location*
to nearest well, drilling, completed, 200 feet
applied for, on this lease, ft.

19. Proposed Depth
10100 feet / 15126 feet

20. BLM/BIA Bond No. on file
FED: NM1195

21. Elevations (Show whether DF, KDB, RT, GL, etc.)
3418 feet

22. Approximate date work will start*
03/01/2018

23. Estimated duration
45 days

24. Attachments

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No.1, must be attached to this form:

1. Well plat certified by a registered surveyor.
2. A Drilling Plan.
3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office).
4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above).
5. Operator certification
6. Such other site specific information and/or plans as may be required by the BLM.

25. Signature
(Electronic Submission)

Name (Printed/Typed)
Kayla McConnell / Ph: (432)682-3753

Date
06/01/2017

Title
Regulatory Analyst

Approved by (Signature)
(Electronic Submission)

Name (Printed/Typed)
Cody Layton / Ph: (575)234-5959

Date
11/17/2017

Title
Supervisor Multiple Resources

Office
CARLSBAD

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.
Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Continued on page 2)

*(Instructions on page 2)

APPROVED WITH CONDITIONS
Approval Date: 11/17/2017

K2
12/04/17

Additional Operator Remarks

Location of Well

1. SHL: NWNW / 200 FNL / 520 FWL / TWSP: 25S / RANGE: 33E / SECTION: 10 / LAT: 32.151786 / LONG: -103.567083 (TVD: 0 feet, MD: 0 feet)
PPP: NWNW / 330 FNL / 515 FWL / TWSP: 25S / RANGE: 33E / SECTION: 10 / LAT: 32.151429 / LONG: -103.567083 (TVD: 10100 feet, MD: 10379 feet)
BHL: SWSW / 50 FSL / 330 FWL / TWSP: 25S / RANGE: 33E / SECTION: 10 / LAT: 32.137955 / LONG: -103.567713 (TVD: 10100 feet, MD: 15126 feet)

BLM Point of Contact

Name: Tenille Ortiz
Title: Legal Instruments Examiner
Phone: 5752342224
Email: tortiz@blm.gov

INSTRUCTIONS

GENERAL: This form is designed for submitting proposals to perform certain well operations, as indicated on Federal and Indian lands and leases for action by appropriate Federal agencies, pursuant to applicable Federal laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from local Federal offices.

ITEM 1: If the proposal is to redrill to the same reservoir at a different subsurface location or to a new reservoir, use this form with appropriate notations. Consult applicable Federal regulations concerning subsequent work proposals or reports on the well.

ITEM 4: Locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local Federal offices for specific instructions.

ITEM 14: Needed only when location of well cannot readily be found by road from the land or lease description. A plat or plats, separate or on the reverse side, showing the roads to, and the surveyed location of, the well, and any other required information, should be furnished when required by Federal agency offices.

ITEMS 15 AND 18: If well is to be, or has been directionally drilled, give distances for subsurface location of hole in any present or objective productive zone.

ITEM 22: Consult applicable Federal regulations, or appropriate officials, concerning approval of the proposal before operations are started.

NOTICES

The Privacy Act of 1974 and regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et seq., 25 U.S.C. 396; 43 CFR 3160

PRINCIPAL PURPOSES: The information will be used to: (1) process and evaluate your application for a permit to drill a new oil, gas, or service well or to reenter a plugged and abandoned well; and (2) document, for administrative use, information for the management, disposal and use of National Resource Lands and resources including (a) analyzing your proposal to discover and extract the Federal or Indian resources encountered; (b) reviewing procedures and equipment and the projected impact on the land involved; and (c) evaluating the effects of the proposed operation on the surface and subsurface water and other environmental impacts.

ROUTINE USE: Information from the record and/or the record will be transferred to appropriate Federal, State, and local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecution, in connection with congressional inquiries and for regulatory responsibilities.

EFFECT OF NOT PROVIDING INFORMATION: Filing of this application and disclosure of the information is mandatory only if you elect to initiate a drilling or reentry operation on an oil and gas lease.

The Paperwork Reduction Act of 1995 requires us to inform you that:

The BLM collects this information to allow evaluation of the technical, safety, and environmental factors involved with drilling for oil and/or gas on Federal and Indian oil and gas leases. This information will be used to analyze and approve applications.

Response to this request is mandatory only if the operator elects to initiate drilling or reentry operations on an oil and gas lease.

The BLM would like you to know that you do not have to respond to this or any other Federal agency-sponsored information collection unless it displays a currently valid OMB control number.

BURDEN HOURS STATEMENT: Public reporting burden for this form is estimated to average 8 hours per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management (1004-0137), Bureau Information Collection Clearance Officer (WO-630), 1849 C Street, N.W., Mail Stop 401 LS, Washington, D.C. 20240.



OCD Hobbs

U.S. Department of the Interior
Bureau of Land Management

Application for Permit to Drill

APD Package Report

Date Printed: 11/20/2017 09:17 AM

APD ID: 10400014586

Well Status: AAPD

APD Received Date: 06/01/2017 01:18 PM 260297

Well Name: VACA DRAW 9418 10 FED 317432

Operator: BTA OIL PRODUCERS LLC

Well Number: 8H

APD Package Report Contents

Permit 97900

- Form 3160-3
- Operator Certification Report
- Application Report
- Application Attachments
 - Well Plat: 1 file(s)
- Drilling Plan Report
- Drilling Plan Attachments
 - Blowout Prevention Choke Diagram Attachment: 2 file(s)
 - Blowout Prevention BOP Diagram Attachment: 1 file(s)
 - Casing Design Assumptions and Worksheet(s): 3 file(s)
 - Proposed horizontal/directional/multi-lateral plan submission: 1 file(s)
 - Other Facets: 2 file(s)
 - Other Variances: 2 file(s)
- SUPO Report
- SUPO Attachments
 - Existing Road Map: 2 file(s)
 - Attach Well map: 1 file(s)
 - Production Facilities map: 1 file(s)
 - Water source and transportation map: 1 file(s)
 - Well Site Layout Diagram: 1 file(s)
- PWD Report
- PWD Attachments
 - None
- Bond Report
- Bond Attachments
 - None

HOBBS OCD
NOV 29 2017
RECEIVED

INSTRUCTIONS

GENERAL: This form is designed for submitting proposals to perform certain well operations, as indicated on Federal and Indian lands and leases for action by appropriate Federal agencies, pursuant to applicable Federal laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from local Federal offices.

ITEM 1: If the proposal is to redrill to the same reservoir at a different subsurface location or to a new reservoir, use this form with appropriate notations. Consult applicable Federal regulations concerning subsequent work proposals or reports on the well.

ITEM 4: Locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local Federal offices for specific instructions.

ITEM 14: Needed only when location of well cannot readily be found by road from the land or lease description. A plat, or plats, separate or on the reverse side, showing the roads to, and the surveyed location of, the well, and any other required information, should be furnished when required by Federal agency offices.

ITEMS 15 AND 18: If well is to be, or has been directionally drilled, give distances for subsurface location of hole in any present or objective productive zone.

ITEM 22: Consult applicable Federal regulations, or appropriate officials, concerning approval of the proposal before operations are started.

NOTICES

The Privacy Act of 1974 and regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et seq., 25 U.S.C. 396; 43 CFR 3160

PRINCIPAL PURPOSES: The information will be used to: (1) process and evaluate your application for a permit to drill a new oil, gas, or service well or to reenter a plugged and abandoned well; and (2) document, for administrative use, information for the management, disposal and use of National Resource Lands and resources including (a) analyzing your proposal to discover and extract the Federal or Indian resources encountered; (b) reviewing procedures and equipment and the projected impact on the land involved; and (c) evaluating the effects of the proposed operation on the surface and subsurface water and other environmental impacts.

ROUTINE USE: Information from the record and/or the record will be transferred to appropriate Federal, State, and local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecution, in connection with congressional inquiries and for regulatory responsibilities.

EFFECT OF NOT PROVIDING INFORMATION: Filing of this application and disclosure of the information is mandatory only if you elect to initiate a drilling or reentry operation on an oil and gas lease.

The Paperwork Reduction Act of 1995 requires us to inform you that:

The BLM collects this information to allow evaluation of the technical, safety, and environmental factors involved with drilling for oil and/or gas on Federal and Indian oil and gas leases. This information will be used to analyze and approve applications.

Response to this request is mandatory only if the operator elects to initiate drilling or reentry operations on an oil and gas lease.

The BLM would like you to know that you do not have to respond to this or any other Federal agency-sponsored information collection unless it displays a currently valid OMB control number.

BURDEN HOURS STATEMENT: Public reporting burden for this form is estimated to average 8 hours per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management (1004-0137), Bureau Information Collection Clearance Officer (WO-630), 1849 C Street, N.W., Mail Stop 401 LS, Washington, D.C. 20240.

Engineer Worksheet

Carlsbad Field Office

620 E. Greene St.

Carlsbad, NM 88220-6292

| | | | | | |
|------------------------|-------------------------------------|-----------------------|------------------------------------|-------------------|----|
| Tracking Number: | ATS-17-813 | County: | Lea | | |
| Company: | BTA Oil Producers | Well Name and Number: | VACA DRAW 9418 10 FED -8H | | |
| Surface Hole Location: | 200°N. & 520°W. SEC010 T025S, R033E | Bottom Hole Location: | 50°S. & 330°W. SEC010 T025S, R033E | | |
| Lease Number: | NMNM97153 | Prod Status: | | Effective: | |
| Bond: | Statewide | Bond #: | NM1195 | Potash: | No |
| NOS Received: | NO | APD Received: | 6-1-2017 | 10-Day LTR Sent: | |
| Acreage: | | Orthodox: | Yes | COM Agr Required: | No |

Deficiencies Noted:

☒ Form 3160-3 ☒ Survey Plat ☒ Drilling Plan ☒ Surface Plan ☒ Bonding ☒ Original Signature ☒ Operator Cert Statement

Other Deficiencies: ☐

Adjudication

Comments:

GEO Report Completed 9-29-2017

Technical Checklist

| | | | | | |
|---|---|------------|---------------------------------|-------|---------|
| Plat: | ok | Elevation: | 3418 | | |
| Proposed Depth: | TVD: 10100 | MD: 15126 | Targeted Formation: Bone Spring | | |
| Anticipated Water-Oil, Gas, Etc.: | Expected fresh water above 1141 ft/ Oil-Gas: Delaware and Bone Spring | | | | |
| Casing/Cement Program: | See COA for depth changes / See COA for cement deficiency. | | | | |
| Bottom Hole Mud Weight | 9.2 | BHP: | 4831.84 | MASP: | 2609.84 |
| <input checked="" type="checkbox"/> Horizontal <input type="checkbox"/> Directional <input type="checkbox"/> Vertical <input type="checkbox"/> Re-entry | | | | | |
| Well Control Prog(BOP, ETC) | 3M BOP after surface casing. Variance: 3M Multibowl BOP | | Mud Program: | Ok | |
| Test-Log-Cores Program: | Required: See COA. Proposed: GR | | | | |
| H2S or Other Hazards: | H2S no. Possibility of water flows in the Salado and Castile. Possibility of lost circulation in Red Beds, Rustler, and Delaware. | | | | |
| Water Basin: | Carlsbad | | | | |
| Casings to Witness: | <input checked="" type="checkbox"/> Surface <input type="checkbox"/> Intermediate <input type="checkbox"/> Production <input type="checkbox"/> CIT Required | | | | |
| | <input type="checkbox"/> Other Witness | | | | |
| Comments: | Witness surface casing. | | | | |

Mustafa Haque 11-7-2017

Engineer Date Signature Adjudication Date Adjudicator Initials



U.S. Department of the Interior
BUREAU OF LAND MANAGEMENT

PWD Data Report

11/20/2017

Section 1 - General

Would you like to address long-term produced water disposal? NO

Section 2 - Lined Pits

Would you like to utilize Lined Pit PWD options? NO

Produced Water Disposal (PWD) Location:

PWD surface owner:

PWD disturbance (acres):

Lined pit PWD on or off channel:

Lined pit PWD discharge volume (bbl/day):

Lined pit specifications:

Pit liner description:

Pit liner manufacturers information:

Precipitated solids disposal:

Describe precipitated solids disposal:

Precipitated solids disposal permit:

Lined pit precipitated solids disposal schedule:

Lined pit precipitated solids disposal schedule attachment:

Lined pit reclamation description:

Lined pit reclamation attachment:

Leak detection system description:

Leak detection system attachment:

Lined pit Monitor description:

Lined pit Monitor attachment:

Lined pit: do you have a reclamation bond for the pit?

Is the reclamation bond a rider under the BLM bond?

Lined pit bond number:

Lined pit bond amount:

Additional bond information attachment:

Section 3 - Unlined Pits

Would you like to utilize Unlined Pit PWD options? NO

Produced Water Disposal (PWD) Location:

PWD surface owner:

PWD disturbance (acres):

Unlined pit PWD on or off channel:

Unlined pit PWD discharge volume (bbl/day):

Unlined pit specifications:

Precipitated solids disposal:

Describe precipitated solids disposal:

Precipitated solids disposal permit:

Unlined pit precipitated solids disposal schedule:

Unlined pit precipitated solids disposal schedule attachment:

Unlined pit reclamation description:

Unlined pit reclamation attachment:

Unlined pit Monitor description:

Unlined pit Monitor attachment:

Do you propose to put the produced water to beneficial use?

Beneficial use user confirmation:

Estimated depth of the shallowest aquifer (feet):

Does the produced water have an annual average Total Dissolved Solids (TDS) concentration equal to or less than that of the existing water to be protected?

TDS lab results:

Geologic and hydrologic evidence:

State authorization:

Unlined Produced Water Pit Estimated percolation:

Unlined pit: do you have a reclamation bond for the pit?

Is the reclamation bond a rider under the BLM bond?

Unlined pit bond number:

Unlined pit bond amount:

Additional bond information attachment:

Section 4 - Injection

Would you like to utilize Injection PWD options? NO

Produced Water Disposal (PWD) Location:

PWD surface owner:

PWD disturbance (acres):

Injection PWD discharge volume (bbl/day):

Injection well mineral owner:

Injection well type:

Injection well number:

Injection well name:

Assigned injection well API number?

Injection well API number:

Injection well new surface disturbance (acres):

Minerals protection information:

Mineral protection attachment:

Underground Injection Control (UIC) Permit?

UIC Permit attachment:

Section 5 - Surface Discharge

Would you like to utilize Surface Discharge PWD options? NO

Produced Water Disposal (PWD) Location:

PWD surface owner:

PWD disturbance (acres):

Surface discharge PWD discharge volume (bbl/day):

Surface Discharge NPDES Permit?

Surface Discharge NPDES Permit attachment:

Surface Discharge site facilities information:

Surface discharge site facilities map:

Section 6 - Other

Would you like to utilize Other PWD options? NO

Produced Water Disposal (PWD) Location:

PWD surface owner:

PWD disturbance (acres):

Other PWD discharge volume (bbl/day):

Other PWD type description:

Other PWD type attachment:

Have other regulatory requirements been met?

Other regulatory requirements attachment:



U.S. Department of the Interior
BUREAU OF LAND MANAGEMENT

Bond Info Data Report

11/20/2017

Bond Information

Federal/Indian APD: FED

BLM Bond number: NM1195

BIA Bond number:

Do you have a reclamation bond? NO

Is the reclamation bond a rider under the BLM bond?

Is the reclamation bond BLM or Forest Service?

BLM reclamation bond number:

Forest Service reclamation bond number:

Forest Service reclamation bond attachment:

Reclamation bond number:

Reclamation bond amount:

Reclamation bond rider amount:

Additional reclamation bond information attachment:



U.S. Department of the Interior
BUREAU OF LAND MANAGEMENT

Operator Certification Data Report

11/20/2017

Operator Certification

I hereby certify that I, or someone under my direct supervision, have inspected the drill site and access route proposed herein; that I am familiar with the conditions which currently exist; that I have full knowledge of state and Federal laws applicable to this operation; that the statements made in this APD package are, to the best of my knowledge, true and correct; and that the work associated with the operations proposed herein will be performed in conformity with this APD package and the terms and conditions under which it is approved. I also certify that I, or the company I represent, am responsible for the operations conducted under this application. These statements are subject to the provisions of 18 U.S.C. 1001 for the filing of false statements.

NAME: Kayla McConnell

Signed on: 06/01/2017

Title: Regulatory Analyst

Street Address: 104 S. Pecos

City: Midland

State: TX

Zip: 79701

Phone: (432)682-3753

Email address: kmccconnell@btaoil.com

Field Representative

Representative Name: Nick Eaton

Street Address: 104 South Pecos

City: Midland

State: TX

Zip: 79701

Phone: (432)682-3753

Email address: neaton@btaoil.com



U.S. Department of the Interior
BUREAU OF LAND MANAGEMENT

Application Data Report

11/20/2017

APD ID: 10400014586

Submission Date: 06/01/2017

Highlighted data
reflects the most
recent changes

Operator Name: BTA OIL PRODUCERS LLC

Well Name: VACA DRAW 9418 10 FED

Well Number: 8H

[Show Final Text](#)

Well Type: OIL WELL

Well Work Type: Drill

Section 1 - General

APD ID: 10400014586

Tie to previous NOS? 10400010933

Submission Date: 06/01/2017

BLM Office: CARLSBAD

User: Kayla McConnell

Title: Regulatory Analyst

Federal/Indian APD: FED

Is the first lease penetrated for production Federal or Indian? FED

Lease number: NMNM97153

Lease Acres: 640

Surface access agreement in place?

Allotted?

Reservation:

Agreement in place? NO

Federal or Indian agreement:

Agreement number:

Agreement name:

Keep application confidential? YES

Permitting Agent? NO

APD Operator: BTA OIL PRODUCERS LLC

Operator letter of designation:

Operator Info

Operator Organization Name: BTA OIL PRODUCERS LLC

Operator Address: 104 S. Pecos

Zip: 79701

Operator PO Box:

Operator City: Midland

State: TX

Operator Phone: (432)682-3753

Operator Internet Address: pinskeep@btaoil.com

Section 2 - Well Information

Well in Master Development Plan? NO

Master Development Plan name:

Well in Master SUPO? NO

Master SUPO name:

Well in Master Drilling Plan? NO

Master Drilling Plan name:

Well Name: VACA DRAW 9418 10 FED

Well Number: 8H

Well API Number:

Field/Pool or Exploratory? Field and Pool

Field Name: RED HILLS

Pool Name: UPPER BONE
SPRING SHALE

Is the proposed well in an area containing other mineral resources? NATURAL GAS,OIL

Operator Name: BTA OIL PRODUCERS LLC

Well Name: VACA DRAW 9418 10 FED

Well Number: 8H

Describe other minerals:

Is the proposed well in a Helium production area? N Use Existing Well Pad? YES New surface disturbance? Y

Type of Well Pad: MULTIPLE WELL

Multiple Well Pad Name: VACA Number: 1
DRAW 9418 10 FED

Well Class: HORIZONTAL

Number of Legs:

Well Work Type: Drill

Well Type: OIL WELL

Describe Well Type:

Well sub-Type: EXPLORATORY (WILDCAT)

Describe sub-type:

Distance to town: 22 Miles

Distance to nearest well: 200 FT

Distance to lease line: 50 FT

Reservoir well spacing assigned acres Measurement: 160 Acres

Well plat: Vaca_Draw_9418_10_Fed_8H__C102_06-01-2017.pdf

Well work start Date: 03/01/2018

Duration: 45 DAYS

Section 3 - Well Location Table

Survey Type: RECTANGULAR

Describe Survey Type:

Datum: NAD83

Vertical Datum: NGVD29

Survey number:

| | NS-Foot | NS Indicator | EW-Foot | EW Indicator | Twsp | Range | Section | Aliquot/Lot/Tract | Latitude | Longitude | County | State | Meridian | Lease Type | Lease Number | Elevation | MD | TVD |
|------------------|---------|--------------|---------|--------------|------|-------|---------|---------------------|---------------|---------------------|--------|-------------------|-------------------|------------|---------------|---------------|-----------|-----------|
| SHL Leg #1 | 200 | FNL | 520 | FWL | 25S | 33E | 10 | Aliquot NWN W | 32.15178 6 | - 103.5670 83 | LEA | NEW MEXI CO | NEW MEXI CO | F | NMNM 97153 | 341 8 | 0 | 0 |
| KOP Leg #1 | 200 | FNL | 520 | FWL | 25S | 33E | 10 | Aliquot NWN W | 32.15178 6 | - 103.5670 83 | LEA | NEW MEXI CO | NEW MEXI CO | F | NMNM 97153 | - 291 1 | 632 9 | 632 9 |
| PPP Leg #1 | 330 | FNL | 515 | FWL | 25S | 33E | 10 | Aliquot NWN W | 32.15142 9 | - 103.5670 83 | LEA | NEW MEXI CO | NEW MEXI CO | F | NMNM 97153 | - 668 2 | 103 79 | 101 00 |

Operator Name: BTA OIL PRODUCERS LLC

Well Name: VACA DRAW 9418 10 FED

Well Number: 8H

| | NS-Foot | NS Indicator | EW-Foot | EW Indicator | Twsp | Range | Section | Aliquot/Lot/Tract | Latitude | Longitude | County | State | Meridian | Lease Type | Lease Number | Elevation | MD | TVD |
|-------------------|---------|--------------|---------|--------------|------|-------|---------|---------------------|---------------|---------------------|--------|-------------------|-------------------|------------|---------------|---------------|-----------|-----------|
| EXIT Leg #1 | 330 | FSL | 340 | FWL | 25S | 33E | 10 | Aliquot SWS W | 32.13872 5 | - 103.5676 78 | LEA | NEW MEXI CO | NEW MEXI CO | F | NMNM 97153 | - 668 2 | 148 45 | 101 00 |
| BHL Leg #1 | 50 | FSL | 330 | FWL | 25S | 33E | 10 | Aliquot SWS W | 32.13795 5 | - 103.5677 13 | LEA | NEW MEXI CO | NEW MEXI CO | F | NMNM 97153 | - 668 2 | 151 26 | 101 00 |



U.S. Department of the Interior
BUREAU OF LAND MANAGEMENT

Drilling Plan Data Report

11/20/2017

APD ID: 10400014586

Submission Date: 06/01/2017

Highlighted data
reflects the most
recent changes

Operator Name: BTA OIL PRODUCERS/LLC

Well Name: VACA DRAW 9418 10 FED

Well Number: 8H

[Show Final Text](#)

Well Type: OIL WELL

Well Work Type: Drill

Section 1 - Geologic Formations

| Formation ID | Formation Name | Elevation | True Vertical Depth | Measured Depth | Lithologies | Mineral Resources | Producing Formation |
|--------------|------------------|-----------|---------------------|----------------|-------------|-------------------|---------------------|
| 1 | QUATERNARY | 3237 | 0 | 0 | ALLUVIUM | NONE | No |
| 2 | RUSTLER | 2146 | 1091 | 1091 | | NONE | No |
| 3 | TOP SALT | 1742 | 1495 | 1495 | SALT | NONE | No |
| 4 | BASE OF SALT | -1257 | 4494 | 4494 | SALT | NONE | No |
| 5 | DELAWARE | -1837 | 5074 | 5074 | | NATURAL GAS,OIL | No |
| 6 | BONE SPRING LIME | -6006 | 9243 | 9243 | | NATURAL GAS,OIL | No |

Section 2 - Blowout Prevention

Pressure Rating (PSI): 3M

Rating Depth: 11100

Equipment: The 13-5/8" blowout preventer equipment (BOP) shown in Exhibit A will consist of a (3M system) double ram type (3000 psi WP) preventer and a bag-type (Hydril) preventer (3000 psi WP). Both units will be hydraulically operated and the ram type preventer will be equipped with blind rams on top and 4-1/2" drill pipe rams on bottom. The BOP's will be installed on the 13 3/8" surface casing and utilized continuously until total depth is reached. All BOP's and associated equipment will be tested as per BLM drilling Operations Order No. 2. A 2" kill line and 3" choke line will be incorporated in the drilling spool below the ram-type BOP. Other accessory BOP equipment will include a Kelly cock, floor safety valve, choke lines, and choke manifold having a 3000 psi WP rating.

Requesting Variance? YES

Variance request: A choke hose variance is requested. See attached test chart and spec.

Testing Procedure: Pipe rams will be operated and checked each 24-hour period and each time the drill pipe is out of the hole. These functional tests will be documented on the daily driller's log.

Choke Diagram Attachment:

Choke Hose - Test Chart and Specs_12-08-2016.pdf

Vaca_Draw_9418_10_Fed___3k_Choke_05-31-2017.pdf

BOP Diagram Attachment:

Vaca_Draw_9418_10_Fed___3k_BOP_05-31-2017.pdf

DISTRICT I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720

DISTRICT II
811 S. First St., Artesia, NM 88210
Phone: (575) 748-1283 Fax: (575) 748-9720

DISTRICT III
1000 Rio Brazos Road, Aztec, NM 87410
Phone: (505) 334-6178 Fax: (505) 334-6170

DISTRICT IV
1220 S. St. Francis Dr., Santa Fe, NM 87505
Phone: (505) 476-3460 Fax: (505) 476-3462

State of New Mexico
Energy, Minerals & Natural Resources Department
OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, New Mexico 87505

HOBBS OCD
NOV 29 2017

Form C-102
Revised August 1, 2011
Submit one copy to appropriate
District Office

AMENDED REPORT


WELL LOCATION AND ACREAGE DEDICATION PLAT

| | | |
|---------------------------------------|---|--|
| API Number 30-025-44250 | Pool Code 97900 | Pool Name Red Hills Upper; Bone Spring Shale |
| Property Code 305274 317432 | Property Name VACA DRAW 9418 10 FEDERAL | Well Number 8H |
| OGRID No. 260297 | Operator Name BTA OIL PRODUCERS, LLC | Elevation 3418' |

| Surface Location | | | | | | | | | |
|------------------|-----------|-------------|-------------|---------|---------------|------------------|---------------|----------------|------------|
| UL or lot No. | Section | Township | Range | Lot Idn | Feet from the | North/South line | Feet from the | East/West line | County |
| D | 10 | 25-S | 33-E | | 200 | NORTH | 520 | WEST | LEA |

| Bottom Hole Location If Different From Surface | | | | | | | | | |
|--|-----------------|--------------------|-------------|---------|---------------|------------------|---------------|----------------|------------|
| UL or lot No. | Section | Township | Range | Lot Idn | Feet from the | North/South line | Feet from the | East/West line | County |
| M | 10 | 25-S | 33-E | | 50 | SOUTH | 330 | WEST | LEA |
| Dedicated Acres 160 | Joint or Infill | Consolidation Code | Order No. | | | | | | |

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION



| OPERATOR CERTIFICATION | |
|---|---|
| I hereby certify that the information herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division. | |
| Signature <i>Kayla McConnell</i> | Date 6/1/17 |
| Printed Name Kayla McConnell | |
| E-mail Address kmccconnell@btaoil.com | |
| SURVEYOR CERTIFICATION | |
| I hereby certify that the well location shown on this plat was plotted from field notes and/or surveys made by me or under my supervision, and that the same is true and correct to the best of my belief. | |
| Date of Survey FEBRUARY 11, 2017 | |
| Signature <i>Ronald J. Edson</i> | Professional Engineer 2/24/2017 |
| Certificate Number Gary G. Edson 12641 | Ronald J. Edson 3239 |
| ACK REL W.D.:1611030 | JWSC W.D.:17.11.0114 |

Operator Name: BTA OIL PRODUCERS LLC

Well Name: VACA DRAW 9418 10 FED

Well Number: 8H

Section 3 - Casing

| Casing ID | String Type | Hole Size | Csg Size | Condition | Standard | Tapered String | Top Set MD | Bottom Set MD | Top Set TVD | Bottom Set TVD | Top Set MSL | Bottom Set MSL | Calculated casing length MD | Grade | Weight | Joint Type | Collapse SF | Burst SF | Joint SF Type | Joint SF | Body SF Type | Body SF |
|-----------|--------------|-----------|----------|-----------|----------|----------------|------------|---------------|-------------|----------------|-------------|----------------|-----------------------------|-------|--------|------------|-------------|----------|---------------|----------|--------------|---------|
| 1 | SURFACE | 17.5 | 13.375 | NEW | API | N | 0 | 1100 | 0 | 1100 | -6682 | -7782 | 1100 | J-55 | 54.5 | STC | 1.6 | 3.86 | DRY | 5.7 | DRY | 9.5 |
| 2 | INTERMEDIATE | 12.25 | 9.625 | NEW | API | N | 0 | 5070 | 0 | 5070 | -6682 | -11752 | 5070 | J-55 | 40 | LTC | 1.6 | 1.4 | DRY | 2.1 | DRY | 2.9 |
| 3 | PRODUCTION | 8.75 | 7.0 | NEW | API | N | 0 | 15126 | 0 | 10100 | -6682 | -16782 | 15126 | P-110 | 17 | LTC | 1.5 | 2.1 | DRY | 2.5 | DRY | 3.1 |

Casing Attachments

Casing ID: 1 String Type: SURFACE

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

Vaca_Draw_9418_10_Fed_8H__Casing_Assumptions_05-31-2017.pdf

Operator Name: BTA OIL PRODUCERS LLC

Well Name: VACA DRAW 9418 10 FED

Well Number: 8H

Casing Attachments

Casing ID: 2 String Type: INTERMEDIATE

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

Vaca_Draw_9418_10_Fed_8H___Casing_Assumptions_05-31-2017.pdf

Casing ID: 3 String Type: PRODUCTION

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

Vaca_Draw_9418_10_Fed_8H___Casing_Assumptions_05-31-2017.pdf

Section 4 - Cement

| String Type | Lead/Tail | Stage Tool Depth | Top MD | Bottom MD | Quantity(sx) | Yield | Density | Cu Ft | Excess% | Cement type | Additives |
|--------------|-----------|------------------|--------|-----------|--------------|-------|---------|-------|---------|-------------|------------------|
| SURFACE | Lead | | 0 | 890 | 640 | 1.75 | 13.5 | 1811 | 81 | Class C | 4% Gel |
| SURFACE | Tail | | 890 | 1100 | 200 | 1.34 | 14.8 | 268 | 81 | Class C | 2% CaCl2 |
| INTERMEDIATE | Lead | | 0 | 4420 | 1085 | 2.18 | 12.7 | 2365 | 61 | Class C | 6% Gel |
| INTERMEDIATE | Tail | | 4420 | 5070 | 425 | 1.22 | 14.4 | 332 | 61 | Class C | 0.004 GPS cf-41L |
| PRODUCTION | Lead | | 4000 | 9200 | 425 | 4.43 | 10.5 | 1838 | 42 | 50:50 H | 0.004 GPS cf-41L |

Operator Name: BTA OIL PRODUCERS LLC

Well Name: VACA DRAW 9418 10 FED

Well Number: 8H

| String Type | Lead/Tail | Stage Tool Depth | Top MD | Bottom MD | Quantity(sx) | Yield | Density | Cu Ft | Excess% | Cement type | Additives |
|-------------|-----------|------------------|--------|-----------|--------------|-------|---------|-------|---------|-------------|-----------|
| PRODUCTION | Tail | | 9200 | 1512 6 | 2100 | 1.22 | 14.4 | 3324 | 15 | 50:50 H | 2% Gel |

Section 5 - Circulating Medium

Mud System Type: Closed

Will an air or gas system be Used? NO

Description of the equipment for the circulating system in accordance with Onshore Order #2:

Diagram of the equipment for the circulating system in accordance with Onshore Order #2:

Describe what will be on location to control well or mitigate other conditions: Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept on location at all times.

Describe the mud monitoring system utilized: PVT/Pason/Visual Monitoring

Circulating Medium Table

| Top Depth | Bottom Depth | Mud Type | Min Weight (lbs/gal) | Max Weight (lbs/gal) | Density (lbs/cu ft) | Gel Strength (lbs/100 sqft) | PH | Viscosity (CP) | Salinity (ppm) | Filtration (cc) | Additional Characteristics |
|-----------|--------------|-------------------|----------------------|----------------------|---------------------|-----------------------------|----|----------------|----------------|-----------------|----------------------------|
| 0 | 1100 | SPUD MUD | 8.3 | 8.4 | | | | | | | |
| 1100 | 5070 | SALT SATURATED | 10 | 10.2 | | | | | | | |
| 5070 | 10100 | OTHER : Cut Brine | 8.6 | 9.2 | | | | | | | |

Operator Name: BTA OIL PRODUCERS LLC

Well Name: VACA DRAW 9418 10 FED

Well Number: 8H

Section 6 - Test, Logging, Coring

List of production tests including testing procedures, equipment and safety measures:

No DST Planned

List of open and cased hole logs run in the well:

GR

Coring operation description for the well:

No cores are currently planned

Section 7 - Pressure

Anticipated Bottom Hole Pressure: 4831

Anticipated Surface Pressure: 2609

Anticipated Bottom Hole Temperature(F): 161

Anticipated abnormal pressures, temperatures, or potential geologic hazards? NO

Describe:

Contingency Plans geohazards description:

Contingency Plans geohazards attachment:

Hydrogen Sulfide drilling operations plan required? NO

Hydrogen sulfide drilling operations plan:

Section 8 - Other Information

Proposed horizontal/directional/multi-lateral plan submission:

Vaca_Draw_9418_10_Fed_8H___Directional_Plan_05-31-2017.pdf

Other proposed operations facets description:

A variance is requested for a Multi Bowl Wellhead. See the attached schematic and running procedure.

Other proposed operations facets attachment:


H2S Plan m_12-08-2016.pdf

H2S_Equipment_Schematic___Well_Pad_05-23-2017.pdf

Other Variance attachment:

Multi Bowl Wellhead Schematic_12-08-2016.pdf

Wellhead System and Testing_12-08-2016.pdf



ContiTech

CONTITECH RUBBER
Industrial Kfl.

No: QC-DB- 590/ 2014

Page: 16 / 176

Rig 94

Asset 24455

| QUALITY CONTROL INSPECTION AND TEST CERTIFICATE | | | | CERT. N°: 1592 | |
|--|--|--------------------------|--|---|--|
| PURCHASER: ContiTech Oil & Marine Corp. | | | | P.O. N°: 4500401753 | |
| CONTITECH ORDER N°: 539225 | | HOSE TYPE: 3" ID | | Choke & Kill Hose | |
| HOSE SERIAL N°: [REDACTED] | | NOMINAL / ACTUAL LENGTH: | | 7,62 m / 7,66 m | |
| W.P. 68,9 MPa 10000 psi | | T.P. 103,4 MPa 15000 psi | | Duration: 60 min. | |
| Pressure test with water at ambient temperature | | | | | |
| See attachment. (1 page) | | | | | |
| → 10 Min. ↑ 50 MPa | | | | | |
| COUPLINGS Type | | Serial N° | | Quality | |
| 3" coupling with 4 1/16" 10K API Swivel Flange end Hub | | 2574 5533 | | AISI 4130 AISI 4130 AISI 4130 | |
| | | | | Heat N° A1582N H8572 58855 A1199N A1423N | |
| Not Designed For Well Testing | | | | API Spec 16 C | |
| Fire Rated | | | | Temperature rate: "B" | |
| All metal parts are flawless | | | | | |
| WE CERTIFY THAT THE ABOVE HOSE HAS BEEN MANUFACTURED IN ACCORDANCE WITH THE TERMS OF THE ORDER INSPECTED AND PRESSURE TESTED AS ABOVE WITH SATISFACTORY RESULT. | | | | | |
| STATEMENT OF CONFORMITY: We hereby certify that the above items/equipment supplied by us are in conformity with the terms, conditions and specifications of the above Purchaser Order and that these items/equipment were fabricated inspected and tested in accordance with the referenced standards, codes and specifications and meet the relevant acceptance criteria and design requirements. | | | | | |
| Date: | | Inspector | | Quality Control | |
| 04. September 2014. | | | | [Signature] ContiTech Rubber Industrial Kfl. Quality Control Dept. | |

File Name
File Message
Device Type
Serial No.
Data Count

000720 63543.68545-547 GEV 000236 00043568545-547 GEV

63543.68545.50547

CX10

SPP000309

0046

Press: Comp

2014/09/01 01:33:54.000 - 2014/09/01 04:39:39.000


Print Group


Print Range

Comment

1.000 sec
Sampling Int.
Start Time
Stop Time

| Data No | Cursor A | Cursor B | Difference |
|---------|--------------|--------------|--------------|
| 001 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 002 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 003 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 004 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 005 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 006 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 007 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 008 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 009 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 010 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 011 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 012 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 013 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 014 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 015 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 016 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 017 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 018 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 019 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 020 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 021 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 022 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 023 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 024 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 025 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 026 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 027 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 028 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 029 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 030 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 031 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 032 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 033 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 034 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 035 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 036 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 037 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 038 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 039 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 040 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 041 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 042 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 043 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 044 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 045 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 046 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 047 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 048 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 049 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 050 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 051 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 052 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 053 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 054 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 055 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 056 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 057 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 058 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 059 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 060 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 061 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 062 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 063 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 064 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 065 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 066 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 067 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 068 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 069 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 070 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 071 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 072 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 073 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 074 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 075 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 076 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 077 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 078 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 079 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 080 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 081 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 082 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 083 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 084 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 085 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 086 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 087 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 088 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 089 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 090 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 091 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 092 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 093 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 094 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 095 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 096 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 097 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 098 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 099 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |
| 100 | 01:33:54.000 | 01:33:54.000 | 00:00:00.000 |





3M choke manifold design

3,000 psi BOP Schematic




Exhibit A



BTA Oil Producers, LLC

Well: Vaca Draw 9418 10 Fed #8H

Casing Assumption

| Hole Size | Csg. Size | From (MD) | To (MD) | From (TVD) | To (TVD) | Tapered String | Weight (lbs) | Grade | Conn. | Collapse | Burst | Body Tension | Joint Tension | Dry/Buoyant | Mud Weight (ppg) |
|-----------|-----------|-----------|---------|------------|----------|----------------|--------------|-------|-------|----------|-------|--------------|---------------|-------------|------------------|
| 17.50 | 13.375 | 0 | 1100 | 0 | 1100 | No | 54.5 | J-55 | STC | 1.60 | 3.86 | 9.50 | 5.70 | Dry | 8.4 |
| 12.25 | 9.625 | 0 | 5070 | 0 | 5070 | No | 40.0 | J-55 | LTC | 1.60 | 1.40 | 2.90 | 2.10 | Dry | 10.0 |
| 8.75 | 5.500 | 0 | 15126 | 0 | 10100 | No | 17.0 | P-110 | LTC | 1.50 | 2.10 | 3.10 | 2.50 | Dry | 9.2 |



BTA Oil Producers, LLC

Well: Vaca Draw 9418 10 Fed #8H

Casing Assumption

| Hole Size | Csg.Size | From (MD) | To (MD) | From (TVD) | To (TVD) | Tapered String | Weight (lbs) | Grade | Conn. | Collapse | Burst | Body Tension | Joint Tension | Dry/ Buoyant | Mud Weight (ppg) |
|-----------|----------|-----------|---------|------------|----------|----------------|--------------|-------|-------|----------|-------|--------------|---------------|--------------|------------------|
| 17.50 | 13.375 | 0 | 1100 | 0 | 1100 | No | 54.5 | J-55 | STC | 1.60 | 3.86 | 9.50 | 5.70 | Dry | 8.4 |
| 12.25 | 9.625 | 0 | 5070 | 0 | 5070 | No | 40.0 | J-55 | LTC | 1.60 | 1.40 | 2.90 | 2.10 | Dry | 10.0 |
| 8.75 | 5.500 | 0 | 15126 | 0 | 10100 | No | 17.0 | P-110 | LTC | 1.50 | 2.10 | 3.10 | 2.50 | Dry | 9.2 |



BTA Oil Producers, LLC

Well: Vaca Draw 9418 10 Fed #8H

Casing Assumption

| Hole Size | Csg.Size | From (MD) | To (MD) | From (TVD) | To (TVD) | Tapered String | Weight (lbs) | Grade | Conn. | Collapse | Burst | Body Tension | Joint Tension | Dry/Buoyant | Mud Weight (ppg) |
|-----------|----------|-----------|---------|------------|----------|----------------|--------------|-------|-------|----------|-------|--------------|---------------|-------------|------------------|
| 17.50 | 13.375 | 0 | 1100 | 0 | 1100 | No | 54.5 | J-55 | STC | 1.60 | 3.86 | 9.50 | 5.70 | Dry | 8.4 |
| 12.25 | 9.625 | 0 | 5070 | 0 | 5070 | No | 40.0 | J-55 | LTC | 1.60 | 1.40 | 2.90 | 2.10 | Dry | 10.0 |
| 8.75 | 5.500 | 0 | 15126 | 0 | 10100 | No | 17.0 | P-110 | LTC | 1.50 | 2.10 | 3.10 | 2.50 | Dry | 9.2 |

HOBBS OCD
NOV 29 2017
RECEIVED




Weatherford®

Wellhead Field Service Manual

WFT-SB Wellhead System Running Procedure


Publication: SM-11-1

Release Date: December 2014




RP104114

©2014 Weatherford International Ltd. All Rights Reserved

| | | | | | |
|--|---------------------------------|------------------------------|------------------------|-----------------------------|----------------|
|  Weatherford 5-3-GL-GL-WES-00XXX | Field Service Manual | Prepared By: | Reviewed By: | Approved By: | SM-11-1 |
| | | <i>Marion Robertson</i> | <i>Bruce Ross</i> | <i>Manuel Zaragoza</i> | Rev WIP |
| | | Marion Robertson Dec 2014 | Bruce Ross Dec 2014 | Manuel Zaragoza Dec 2014 | Page 1 of 24 |

NOTE: THIS DRAWING IS NOT TO SCALE. THE DIMENSIONS REFLECTED ON THIS DRAWING ARE ESTIMATED DIMENSIONS AND ARE FOR REFERENCE ONLY.



Weatherford

© 2016 Weatherford All rights reserved

| | | |
|-----------------------------|---------------------|----------------------|
| Customer: BTA OIL PRODUCERS | Project No.: 146245 | Quote No.: 291545 v2 |
| Project Name: WEST TEXAS | Date: 07/06/16 | Drawn By: JL |


Table of Content

WFT-Split Bowl (SB) Wellhead System

| | |
|--|---|
| Wellhead System Assembly Drawing | 3 |
|--|---|


Running Procedure

| | |
|--|----|
| Casing Head/Spool Assembly Rig-Up and Installation | 4 |
| Testing the BOP | 5 |
| Running and Retrieving the Long Bowl Protector..... | 3 |
| Running the Bowl Protector Prior to Drilling | 6 |
| Retrieving the Bowl Protector After Drilling | 7 |
| Hanging Off the Intermediate Casing..... | 7 |
| Hanging Off the Intermediate Casing- Contingency Completion..... | 9 |
| Installation of the Pack-Off Bushing and Energizing the Seals | 10 |
| Installation | 10 |
| Energizing the Seal | 12 |
| Retesting the BOP Stack | 14 |
| Running and Retrieving the Short Bowl Protector | 15 |
| Running Short Bowl Protector | 15 |
| Retrieving the Short Bowl Protector | 16 |
| Running the Production Casing | 16 |
| Installation of the Slip-Type Casing Hanger Under the BOP Stack | 16 |
| Installation of the Slip-Type Casing Hanger Through the BOP Stack..... | 17 |
| Hanging Off the Production Casing | 18 |
| Installation and Testing the Tubing Spool Assembly | 20 |
| Installation | 20 |
| Testing the Secondary Seal and Flange Connection | 20 |
| Testing the BOP | 21 |
| Hanging Off the Production Tubing String..... | 22 |
| Installing and Testing of the Production Tree..... | 23 |
| Installation | 23 |
| Testing | 24 |


| | | | | | |
|--|----------------------------------|-------------------------|--------------|-----------------|----------------|
|  Weatherford 5-3-GL-GL-WES-00XXX | Field Services Manual | Prepared By: | Reviewed By: | Approved By: | SM-13-1 |
| | | <i>Marion Robertson</i> | Brad Franks | Manual Zaragoza | Rev WIP |
| | | Marion Robertson | Brad Franks | Manual Zaragoza | Page 2 of 24 |
| | | Dec 2014 | Dec 2014 | Dec 2014 | |

WFT Split Bowl (SB) Wellhead System

WFT-SB Split Multi-Bowl/ Conventional Wellhead System



RP104091

| | | | | | |
|--|---------------------------------|-------------------------|---------------|-----------------|----------------|
|  Weatherford 5-3-GL-GL-WES-00XXX | Field Service Manual | Prepared By: | Reviewed By: | Approved By: | SM-13-1 |
| | | <i>Marion Robertson</i> | Brad Franks | Manual Zaragoza | Rev WIP |
| | | Marion Robertson | Brad Franks | Manual Zaragoza | Page 3 of 24 |
| | | December 2014 | December 2014 | December 2014 | |

WFT Split Bowl (SB) Multi-Bowl/Conventional Wellhead System (Continued)

WFT-SB Casing Head/Spool Assembly Rig Up and Installation

1. Determine the correct elevation for the wellhead system, and cut the conductor pipe at a comfortable elevation, below the surface casing final cut.


NOTE

Ensure that the cut on the conductor is level, as this will determine the orientation of all remaining wellhead equipment.

2. Remove any excess conductor pipe and set aside.
3. Grind the conductor pipe and remove any sharp edges, ensuring that the conductor pipe cut is level.
4. Run the surface casing to the required depth and cement casing in place. Allow the cement to set.
5. Lift the blow-out preventer (BOP) or diverter and prepare to cut off the surface casing at a sufficient height above the cellar deck to facilitate the installation of the WFT-SB Casing Head/Spool Assembly with Base Plate.
6. Once the surface casing is released from the rig floor, cut it approximately 12 inches (or more) above the final cut location.
7. Remove the excess surface casing, and the BOP or diverter, and set aside.
8. Bevel the surface casing outer diameter (3/16" x 3/8") and inner diameter (1/8" x 45 degrees). Remove any sharp edges.

9. Examine the Casing Head with Slip-On Weld (SOW) bottom prep. Verify the following:

- O-ring seal, bore, ports and exposed ring grooves are clean and in good condition.
- Test fittings, studs and nuts, valves, flanges and bull plugs are intact and in good condition.




10. Determine the correct elevation for the wellhead assembly. Measure depth of the surface casing socket in SOW with O-ring bottom prep.
11. Lightly lubricate the casing stub with an oil or light grease.

WARNING

Excessive oil or grease will prevent a positive seal from forming.

12. Align and level the WFT-SB Casing Head/Spool Assembly over the casing stub, orienting the outlets to drilling equipment, per the drilling supervisor's direction.

| | | | | | |
|--|-----------------------------|-------------------------|---------------|-----------------|----------------|
|  Weatherford 5-3-GL-GL-WES-00XXX | Field Service Manual | Prepared By: | Reviewed By: | Approved By: | SM-13-1 |
| | | <i>Marion Robertson</i> | Brad Franks | Manual Zaragoza | Rev WIP |
| | | Marion Robertson | Brad Franks | Manual Zaragoza | Page 4 of 24 |
| | | December 2014 | December 2014 | December 2014 | |

WFT Split Bowl (SB) Wellhead System (Continued)

14. Slowly and carefully lower the assembly over the casing stub until the stub bottoms in the casing socket.
15. Remove the test fitting from the casing head test port, and set aside.
16. Ensure that the WFT-SB Casing Head/Spool Assembly is plumb and level.
17. Weld and test the surface casing using the recommended welding procedure located in the Appendices Section of this manual.

Testing the BOP Stack

1. Examine the Test Plug/Running & Retrieval Tool. Verify the following:
 - Elastomer seals, threads and plugs are intact and in good condition.
 - Drill pipe threads are correct size, clean and in good condition.
2. Install a new, appropriately sized ring gasket in the ring groove of the WFT-SB Spool and make up the BOP stack.

NOTE

Immediately after make-up of the BOP stack and periodically during drilling of hole for the casing string, the BOP stack (flanged connections and rams) must be tested.

3. Orient the test plug with elastomer down/ACME threads up, and make up a joint of drill pipe to the test plug.


NOTE

If pressure is to be supplied through the drill pipe, remove the pipe plug from the weep port.

CAUTION

Ensure that the test plug elastomer is down and Acme threads are up when testing.

4. Fully retract all lockscrews in the entire WFT-SB casing head/spool assembly.
5. Lubricate the test plug elastomer seal with a light oil or grease.
6. Lower the test plug through the BOP stack into the WFT-SB assembly, until it lands on the casing head load shoulder.



Weatherford

5-3-GL-GL-WES-00XXX

**Field Service
Manual**

Prepared By:

Marion Robertson

Marion Robertson

December 2014

Reviewed By:

Brad Franks

Brad Franks

December 2014

Approved By:

Manual Zaragoza

Manual Zaragoza

December 2014

SM-13-1

Rev WIP

Page 5 of 24

WFT Split Bowl (SB) Wellhead System (Continued)

7. Open lower casing head side outlet valve. Monitor any leakage past the test plug seal.
 8. Close the BOP rams on the drill pipe, and test to **5,000 psi or as required by the drilling supervisor**.
 9. After a satisfactory test is achieved, release pressure and open the rams.
 10. Remove as much fluid from the BOP stack as possible.
 11. Retrieve the test plug assembly slowly to avoid damage to the seal.
 12. Close all outlet valves on WFT-SB Casing Head/Spool Assembly.
 13. Repeat Steps 1 thru 12, as required during drilling of the hole.
2. Examine the Bowl Protector Running/Retrieval Tool. Verify the following:
 - Threads are clean, undamaged and free of debris
 - Ports are clean and unobstructed.
 - Drill Pipe threads are correct size, clean and in good condition.
 3. Orient the Bowl Protector Running Tool with Acme threads down.

⚠ CAUTION ⚠

Ensure that the left hand (LH) Acme threads are down prior to engaging Bowl Protector Running Tool into Long Bowl Protector.


Running and Retrieval of the Long Bowl Protector


NOTE

Always use a bowl protector while drilling to protect wellhead load shoulders from damage by drill bit or rotating drill pipe. The bowl protector must be retrieved prior to running the casing string.

Running in the Bowl Protector prior to Drilling

1. Examine the Long Bowl Protector. Verify the following:
 - Bore drift is correct size, clean, in good condition, and free of debris
 - Threads are clean and undamaged
 - O-ring seals are properly installed, clean, and undamaged.



| | | | | | |
|--|-----------------------------|-------------------------|---------------|-----------------|----------------|
|  Weatherford 5-3-GL-GL-WES-00XXX | Field Service Manual | Prepared By: | Reviewed By: | Approved By: | SM-13-1 |
| | | <i>Marion Robertson</i> | Brad Franks | Manual Zaragoza | Rev WIP |
| | | Marion Robertson | Brad Franks | Manual Zaragoza | Page 6 of 24 |
| | | December 2014 | December 2014 | December 2014 | |

WFT Split Bowl (SB) Wellhead System (Continued)

4. Make-up a drill pipe joint to the Running Tool.
5. Thread Running Tool into the Long Bowl Protector, rotating two turns counterclockwise.
6. Verify that all lockscrews in the WFT-SB Casing Head/Spool Assembly are fully retracted.
7. Slowly lower the Running Tool/Bowl Protector Assembly through the BOP stack and into the WFT-SB Casing Head/Spool Assembly, until it lands securely on the casing head load shoulder.
8. On WFT-SB Casing Spool, run in two Lockscrews ("snug" tight **ONLY**), 180 degrees apart, to hold Bowl Protector in place.

WARNING

Do NOT over tighten the lockscrews, as this will cause damage to the Bowl Protector and the lockscrews.

9. Remove the running tool from the bowl protector, by rotating the drill pipe clockwise two turns while lifting straight up.
10. Drill out and prepare to run the casing string per the drilling supervisor's instruction.

Retrieving the Bowl Protector after Drilling

1. Make-up the retrieval tool to the drill pipe, with Acme threads down.
2. Slowly lower the retrieval tool through the BOP Stack into the Bowl Protector.
3. Rotate the retrieval Tool counterclockwise, two turns, to engage with bowl protector Acme threads.

4. Fully retract both lockscrews on the WFT-SB casing spool, and retrieve the bowl protector.

NOTE

Ensure that all lockscrews in both the upper flange (casing spool) and lower flange (casing head) of the wellhead Assembly are fully retracted from well bore.

5. Remove the bowl protector and the running and retrieval tool from the drill floor.

Hanging off the Intermediate Casing

1. Run the intermediate casing as required and space out appropriately for the mandrel casing hanger.



NOTE

If the intermediate casing becomes stuck and the mandrel casing hanger cannot be landed, refer to STAGE 4B.

2. Examine the WFT-SBD-SN Mandrel Casing Hanger. Verify the following:
 - Bore drift is correct size, clean and free of debris
 - All threads are clean and undamaged.
 - Flow-By flutes are clear and unobstructed.
 - Slick Neck seal area is clean and undamaged.
3. Examine the Mandrel Casing Hanger Running Tool. Verify the following:
 - Threads are clean and in good condition.
 - O-ring seals are clean and undamaged.
4. Thread the mandrel hanger onto the last joint of casing to be run. Torque the connection thread to manufacturer's optimum "make-up" torque value.
5. Make up a landing joint to the top of the running tool. Torque the connection to thread manufacturer's maximum "make-up" torque valve.

CAUTION

If Steps 4 and 5 were performed prior to being shipped to location, the hanger running tool should be backed off and made back up to ensure it will back off freely.

| | | | | | |
|--|-----------------------------|---|---------------|-----------------|----------------|
|  Weatherford 5-3-GL-GL-WES-00XXX | Field Service Manual | Prepared By: | Reviewed By: | Approved By: | SM-13-1 |
| | |  | Brad Franks | Manual Zaragoza | Rev WIP |
| | | Marion Robertson | Brad Franks | Manual Zaragoza | Page 7 of 24 |
| | | December 2014 | December 2014 | December 2014 | |

WFT Split Bowl (SB) Wellhead System (Continued)

6. Liberally lubricate the outer diameter of the hanger neck and inner diameter of the running tool O-ring seals with a light oil or grease.



Do NOT use pipe dope or other metal based compounds. This will cause galling.


7. Maintaining a neutral weight, rotate the hanger running tool with chain tongs, first clockwise until a thread "jump" can be felt, then counterclockwise, approximately eight turns, to a positive stop, and then back off (clockwise) one quarter (1/4) turn.




Do NOT torque the running tool to the casing hanger connection. Do NOT back off more than one quarter (1/4) turn.

8. Remove the flush fitting hex head pipe plug from the outer diameter of the running tool and attach a test pump.
9. Apply hydraulic test pressure to **5,000 psi and hold for 15 minutes or as required by the drilling supervisor.**
10. Upon completion of a successful test, bleed off test pressure through the test pump and remove the pump. Replace the pipe plug.
11. Locate indicator groove machined in outer diameter of Running Tool, coat with white paint.

12. Verify that all lockscrews in the WFT-SB casing head/casing spool assembly are fully retracted.
13. Slowly and carefully lower the mandrel hanger through the BOP stack, and land the hanger onto the casing head load shoulder.
14. Slack off weight on the casing.
15. Check that the well is stable and no pressure buildup or mud flow is occurring.



| | | | | | |
|--|-----------------------------|-------------------------|---------------|-----------------|----------------|
|  Weatherford 5-3-GL-GL-WES-00XXX | Field Service Manual | Prepared By: | Reviewed By: | Approved By: | SM-13-1 |
| | | <i>Marion Robertson</i> | Brad Franks | Manual Zaragoza | Rev WIP |
| | | Marion Robertson | Brad Franks | Manual Zaragoza | Page 8 of 24 |
| | | December 2014 | December 2014 | December 2014 | |

WFT Split Bowl (SB) Wellhead System (Continued)

16. Drain the BOP stack through the casing head side outlet valves.
17. Remove the pipe plug from the casing head flange port marked "Inspection Port."
18. Visually verify that the running tool groove is in the center of the inspection port, and that the mandrel hanger has landed properly.
19. Reinstall the pipe plug and tighten securely.
20. Place a paint mark on the landing joint level with the rig floor, and cement casing as required.

NOTE

If the casing is to be reciprocated during cementing, it is advisable to pick up the mandrel hanger a minimum of eight feet above the landing point. Place a mark on the landing joint, level with the rig floor, and then reciprocate above that point. If at any time resistance is felt, land the mandrel casing hanger immediately.



21. Retrieve the hanger running tool and landing joint by rotating landing joint clockwise (to the right), fourteen full turns.

Hanging off Intermediate Casing – Contingency Completion

NOTE

The following procedure should **ONLY** be followed if the intermediate casing should become stuck in the hole. If the casing did **NOT** get stuck and is successfully hung off with the mandrel casing hanger, skip this stage.

1. Cement the intermediate casing in accordance with the program, taking returns through the flow-by flutes of the mandrel casing hanger as required.
2. Drain the casing head bowl through the side outlet.
3. Separate the WFT-SB casing spool from the casing head.
4. Pull up on WFT-SB casing spool and suspend it above casing head, high enough to install a WFT-21 Slip Type Casing Hanger.
5. Wash out as required.
6. Examine the WFT-21 slip type casing hanger. Verify the following:
 - Hanger is correct size, clean and undamaged.
 - Slip segments are sharp and in proper position.
 - All screws are in place.
7. Remove the latch screw to open the slip type hanger.
8. Place two boards on the casing head flange, against the casing, to support the hanger.
9. Wrap the hanger around the casing and replace the latch screw.
10. Prepare to lower the hanger into the casing head bowl.
11. Grease the WFT-21 slip type casing hanger body and remove the slip retaining cap screws.
12. Remove the boards and allow the hanger to slide down into the casing head.

| | | | | | |
|--|-----------------------------|---|---------------|-----------------|----------------|
|  Weatherford 5-3-GL-GL-WES-00XXX | Field Service Manual | Prepared By: | Reviewed By: | Approved By: | SM-13-1 |
| | |  | Brad Franks | Manual Zaragoza | Rev WIP |
| | | Marion Robertson | Brad Franks | Manual Zaragoza | Page 9 of 24 |
| | | December 2014 | December 2014 | December 2014 | |

WFT Split Bowl (SB) Wellhead System (Continued)

13. Once the hanger has landed securely on the casing head bowl load shoulder, pull tension on the casing to the desired hanging weight, and then slack off.

NOTE

A sharp decrease on weight indicator will signify that the hanger has taken weight. If this does not occur, pull tension again and slack once more.

14. Rough cut the casing approximately eight inches, or more, above the top of the casing head flange. Remove the excess casing.
15. Final cut the casing at $2\frac{1}{2}" \pm 1/8"$ above casing head flange.
16. Bevel the casing outer diameter ($1/4" \times 30$ degrees) and inner diameter ($1/8" \times 30$ degrees).
17. Remove and discard the used gasket ring from the casing head.
18. Clean the mating ring grooves on the WFT-SB casing spool and casing head. Lightly wipe with oil or grease.


WARNING

Excessive oil or grease will prevent a positive seal from forming.

19. Install a new appropriately sized ring gasket into the casing head groove.
20. Loosely reconnect or make up the WFT-SB casing spool to the casing head.

NOTE

The casing spool to casing head connection will be fully tightened after the pack-off bushing is run and proper setting is verified.




Installation of the Pack-Off Bushing and Energizing the P-Seals

WFT-SB Pack-Off Bushing Installation

NOTE

Installation procedure is identical for both Standard and Emergency WFT-SB Pack-Off Bushings.

- Determine which pack-off bushing to use:
 - If casing has been run normally and is hung off with a mandrel casing hanger, use a standard packoff bushing.
- Examine the appropriate pack-off bushing. Verify the following:
 - All elastomer seals are in place and undamaged.
 - Bore, ports and alignment lugs are clean and in good condition.
 - Coat the lockscrew relief groove with white paint.
- Liberal lubricate the inner diameter of the double P-seal grooves and outer diameter of dovetail seals with a light oil or grease.

| | | | | | |
|--|-----------------------------|-------------------------|---------------|-----------------|----------------|
|  Weatherford 5-3-GL-GL-WES-00XXX | Field Service Manual | Prepared By: | Reviewed By: | Approved By: | SM-13-1 |
| | | <i>Marion Robertson</i> | Brad Franks | Manual Zaragoza | Rev WIP |
| | | Marion Robertson | Brad Franks | Manual Zaragoza | Page 10 of 24 |
| | | December 2014 | December 2014 | December 2014 | |

WFT Split Bowl (SB) Wellhead System (Continued)

4. Examine the pack-off bushing running tool. Verify the following:
 - All elastomer seals are properly installed, clean and undamaged
 - Threads are clean, undamaged and free of debris
 - Bore and ports are clean and unobstructed.
5. Make-up a landing joint to the running tool and rack back assembly.
6. Run two or three stands of heavy weight drill pipe or collars in the hole and set floor slips.
10. Lower the assembly through the BOP Stack and the WFT-SB spool assembly until the pack-off bushing lands on the casing hanger.


NOTE


Use heavy weight drill pipe or drill collars. Weight required to push Pack-Off Bushing into Casing Head, over Mandrel Hanger slick neck, is approximately 14,000 lbs.

WARNING

When lowering the drill pipe into the well, extreme caution must be taken to not damage the top of the mandrel hanger with the end of the drill pipe. It is recommended that the drill pipe be centralized to the hanger inner diameter, as closely as possible, when entering the hanger.

7. Carefully lower the bushing over the drill pipe and set it on top of floor slips.
8. Make up the landing joint/running tool assembly to the drill pipe suspended in floor slips.
9. Carefully pick up the pack-off bushing, thread the bushing into the running tool, then rotate the bushing approximately two turns counterclockwise (to the left), coming to a positive stop.
11. Verify, through inspection port that the pack-off bushing has landed properly after:
 - ensuring well is stable and no pressure buildup or mud flow is occurring.
 - drain BOP Stack through Casing Head side outlet valves.
 - remove Pipe Plug (1"-NPT) from Casing Head flange port marked "Inspection Port".
 - Check, to ensure, bottom of Lockscrew relief groove (painted white) on Support Bushing is at bottom of inspection port.
 - Reinstall Pipe Plug and tighten securely.
12. Fully run in all Casing Head Lockscrews (lower flange), in an alternating cross pattern.
13. Using two chain tongs, 180° apart, rotate Landing Joint/Running Tool approximately 2 turns clockwise (to the



| | | | | | |
|--|-----------------------------|-------------------------|---------------|-----------------|----------------|
|  Weatherford 5-3-GL-GL-WES-00XXX | Field Service Manual | Prepared By: | Reviewed By: | Approved By: | SM-13-1 |
| | | <i>Marion Robertson</i> | Brad Franks | Manual Zaragoza | Rev WIP |
| | | Marion Robertson | Brad Franks | Manual Zaragoza | Page 11 of 24 |
| | | December 2014 | December 2014 | December 2014 | |


right), coming to a stop and carefully lift tool to Drill Floor, set aside.

NOTE

If the Contingency Pack-Off Bushing is being installed, it is now necessary to make up the Speed Head Casing Head/Casing Spool connection. Tighten all studs in an alternating cross pattern until the flange bolting is fully made up.

Energizing the P-Seals


1. Locate the two lower injection fittings ("INJ"), located 180 degrees apart on the casing head. Remove the dust cap from one fitting and remove the second fitting entirely.
2. Attach a bleeder tool to the injection fitting without the dust cap, in the casing head. Open the bleeder tool.
3. Attach a plastic injection tool to the open port and inject plastic packing into the port until a continuous stream flows from the bleeder tool. Close the bleeder tool.
4. Remove the injection tool. Reinstall the injection fitting into the open port and remove the dust cap. Reattach the injection tool.
5. Continue injecting plastic packing to **5,000 psi. or to 80% of casing collapse pressure, whichever is less.**



NOTE

The strength of a mandrel casing hanger slick neck is equivalent to P110 Grade casing with the same weight as run in the casing string.

6. Hold and monitor pressure for 15 minutes or as required by the drilling supervisor.
7. If pressure drops, the plastic packing has not filled the seal area completely. Open the bleeder tool, bleed off the pressure and repeat Steps 5 and 6, until pressure is stabilized.
8. Remove the plastic injection tool and bleeder tool. Reinstall the dust caps on both injection fittings.
9. Repeat Steps 1 thru 8 to pack off and energize the upper P-Seal.

| | | | | | |
|--|-----------------------------|-------------------------|---------------|-----------------|----------------|
|  Weatherford 5-3-GL-GL-WES-00XXX | Field Service Manual | Prepared By: | Reviewed By: | Approved By: | SM-13-1 |
| | | <i>Marion Robertson</i> | Brad Franks | Manual Zaragoza | Rev WIP |
| | | Marion Robertson | Brad Franks | Manual Zaragoza | Page 12 of 24 |
| | | December 2014 | December 2014 | December 2014 | |

WFT Split Bowl (SB) Wellhead System (Continued)

10. Locate the "SEAL TEST" fitting, slightly below and 90 degrees from the injection fittings. Remove the dust cap from this fitting.
11. Attach a test pump to the fitting.
12. Pump clean test fluid between the P-Seals until a test pressure of **5,000 psi or 80% of casing collapse pressure is attained, whichever is lower.**

WARNING

Do NOT exceed 80% of casing collapse pressure when a slip type casing hanger and contingency pack-off bushing are utilized.

13. Hold test pressure for **15 minutes or as required by the drilling supervisor.**
14. If pressure drops, a leak has developed. Take the appropriate action per the following table:


| Leak Location | Cause | Action |
|----------------------------------|----------------------|--|
| Into the bore of the casing head | Upper P-seal leaking | Bleed off pressure and re-inject plastic packing into leaking upper P-seal port. |
| Around the casing | Lower P-Seal leaking | Bleed off pressure and re-inject plastic packing into lower P-seal port. |

15. Repeat Steps 12 thru 14 until a satisfactory test is achieved.
16. Once a satisfactory test is achieved, carefully bleed off pressure and remove Test Pump.
17. Attach the bleeder tool to the test port fitting and open the tool to vent any remaining trapped pressure.

CAUTION

Always direct the bleeder tool port away from people and property.

18. Remove the bleeder tool and reinstall dust cap in Test Port Fitting.



Weatherford

5-3-GL-GL-WES-00XXX

Field Service Manual

Prepared By:

Marion Robertson

Marion Robertson

December 2014

Reviewed By:

Brad Franks

Brad Franks

December 2014

Approved By:

Manual Zaragoza

Manual Zaragoza

December 2014

SM-13-1

Rev WIP

Page 13 of 24

WFT Split Bowl (SB) Wellhead System (Continued)

Retesting the BOP Stack

1. Examine the Test Plug/Running Tool. Verify the following:

- Elastomer seals are intact and in good condition.
- Drill pipe threads are clean and in good condition.

NOTE

Immediately after testing the support bushing seals and periodically during conditioning of the hole prior to running tubing, the BOP stack (flanged connections and rams) must be tested.

2. Orient the test plug with elastomer down/ACME threads up. Make up a joint of drill pipe to the test plug.

NOTE

Remove the pipe plug from the weep port if pressure is to be supplied through the drill pipe.

CAUTION


Make sure the elastomer is down and ACME threads are up when testing.

3. Fully retract all lockscrews in the upper WFT-SB Spool Assembly.


WARNING

Do NOT retract the lockscrews located in the casing head (lower flange). Doing so could allow the pack-off support bushing to rise out of position.

4. Lubricate the test plug elastomer seal with light oil or grease.



5. Lower the test plug through the BOP stack into the WFT-SB spool assembly until it lands on top of the pack-off bushing.
6. Open the upper WFT-SB casing spool side outlet valves. Monitor for any leakage past the test plug seal.
7. Close the BOP rams on the drill pipe and test to **10,000 psi or as required by the drilling supervisor**.
8. After a satisfactory test is achieved, release all pressure and open the rams.
9. Remove as much fluid from the BOP stack as possible.
10. Retrieve the test plug assembly slowly to avoid damage to the seal.
11. Close all outlet valves on the WFT-SB casing head/spool assembly.

| | | | | | |
|--|-----------------------------|-------------------------|---------------|-----------------|----------------|
|  Weatherford 5-3-GL-GL-WES-00XXX | Field Service Manual | Prepared By: | Reviewed By: | Approved By: | SM-13-1 |
| | | <i>Marion Robertson</i> | Brad Franks | Manual Zaragoza | Rev WIP |
| | | Marion Robertson | Brad Franks | Manual Zaragoza | Page 14 of 24 |
| | | December 2014 | December 2014 | December 2014 | |

WFT Split Bowl (SB) Wellhead System (Continued)

Running and Retrieving the Short Bowl Protector

NOTE

Always use a bowl protector while drilling to protect the wellhead load shoulders from damage by the drill bit or rotating drill pipe. The bowl protector must be retrieved prior to running the casing string!

Running the Bowl Protector Prior to Drilling

1. Examine the short bowl protector. Verify the following:
 - Bore drift is correct size, is clean, in good condition, and free of debris.
 - Threads are correct size and type.
 - Threads are clean and in good condition.
2. Orient the bowl protector running tool with ACME threads down.

NOTE

The running tool is the same tool used for handling the long bowl protector.

CAUTION

Make sure that the left hand (LH) ACME threads are down prior to engaging the bowl protector running tool into the short bowl protector.

3. Make-up a drill pipe joint to the running tool.
4. Thread the running tool into the short bowl protector, rotating two turns counterclockwise (to the left).
5. Verify that all upper lockscrews in the WFT-SB spool assembly are fully retracted. Slowly lower the running

tool/bowl protector assembly through the BOP stack into the WFT-SB spool assembly until it lands on top of the pack-off bushing.

WARNING


Do NOT retract the lower lockscrews located in the WFT-SB casing head, as this could allow the pack-off bushing to rise out of position.


6. On the upper WFT-SB spool assembly, run in two lockscrews ("snug" tight ONLY), 180 degrees apart, to hold the bowl protector in place.

WARNING

Do NOT over tighten the lockscrews, as this will cause damage to both the bowl protector and lockscrews.

7. Remove the running tool from the bowl protector, by rotating the drill pipe clockwise two turns while lifting straight up.
8. Drill out and prepare to the production casing string per the drilling supervisor's instructions.



| | | | | | |
|--|-----------------------------|-------------------------|---------------|-----------------|----------------|
|  Weatherford 5-3-GL-GL-WES-00XXX | Field Service Manual | Prepared By: | Reviewed By: | Approved By: | SM-13-1 |
| | | <i>Marion Robertson</i> | Brad Franks | Manual Zaragoza | Rev WIP |
| | | Marion Robertson | Brad Franks | Manual Zaragoza | Page 15 of 24 |
| | | December 2014 | December 2014 | December 2014 | |

WFT Split Bowl (SB) Wellhead System (Continued)

Retrieval of the Short Bowl Protector After Drilling

1. Make up the retrieval tool to the drill pipe with ACME threads down.
2. Slowly lower the retrieval tool into the bowl protector.
3. Rotate the retrieval tool counterclockwise, two turns, to engage with the bowl protector ACME threads.
4. Fully retract both lockscrews on the casing spool (upper flange), and retrieve the bowl protector.
5. Remove the bowl protector and retrieval tool from the drill string.

Running the Production Casing

1. Run the production casing to necessary depth and cement as required.

NOTE

There are two methods for installing WFT-22 Slip Type Casing Hangers:

- Under the BOP stack.
- Through the BOP stack.

Installation of the Slip-Type Casing Hanger Under the BOP Stack

1. Drain the casing head through the uppermost side outlet valve.
2. Lift and suspend the BOP stack above the WFT-SB spool assembly to a minimum of 18 inches.
3. Wash out the WFT-SB casing head/spool assembly as required.
4. Confirm that ONLY the lockscrews in the casing spool (upper flange) are fully retracted.

5. Examine the WFT-22 slip-type casing hanger. Verify the following:

- Slip segments are clean and undamaged.
- All screws are in place.
- Packing element is clean and undamaged.


CAUTION


The packing element should not protrude past the casing hanger outer diameter. If the packing element does extend past the outer diameter, loosen the cap screws in the bottom of the hanger.

6. Place two boards across the casing spool face, against the casing, to support the hanger.
7. Disengage the spring loaded latch, open the hanger and wrap the hanger around the casing, allowing the support boards to carry weight.
8. Re-engage the casing hanger spring loaded latch.
9. Remove the slip retaining cap screws from the outer diameter of the hanger body, allowing the slip segments to settle around the casing.
10. Supporting the weight of the casing hanger, remove the support boards and lower the hanger into the WFT-SB casing head/spool assembly until it lands on the pack-off bushing load shoulder.

CAUTION

Do NOT drop the hanger; lower it carefully.



| | | | | | |
|--|-----------------------------|-------------------------|---------------|-----------------|----------------|
|  Weatherford 5-3-GL-GL-WES-00XXX | Field Service Manual | Prepared By: | Reviewed By: | Approved By: | SM-13-1 |
| | | <i>Marion Robertson</i> | Brad Franks | Manual Zaragoza | Rev WIP |
| | | Marion Robertson | Brad Franks | Manual Zaragoza | Page 16 of 24 |
| | | December 2014 | December 2014 | December 2014 | |

WFT Split Bowl (SB) Wellhead System (Continued)

Installation of the Slip-Type Casing Hanger through the BOP Stack

1. Drain the WFT-SB casing head/spool assembly and BOP stack through the side outlet valves on the spool assembly.
2. Wash out the wellhead assembly until clean returns are seen.
3. Examine the slip type casing hanger. Verify the following:
 - slip segments are clean and undamaged
 - all screws are in place
 - Packing Element is clean and undamaged.

CAUTION

The packing element should not protrude past the casing hanger outer diameter. If the packing element does extend past the outer diameter, loosen the cap screws in the bottom of the hanger.


4. Place two boards across the rotary table, against the casing, to support the hanger.
5. Disengage the spring loaded latch, open the hanger and wrap it around the casing, allowing the support boards to carry the weight.
6. Re-engage the casing hanger's spring loaded latch.
7. Measure the distance from the top flange of the WFT-SB casing spool to the drilling rig floor (RKB).
8. Measure out two lengths of soft-line cord (rope) to the same length as the


RKB measurement, and adding an additional 10 feet to each line.

9. Mark the soft line cord at the required length.
10. Install two eyebolts into the tapped holes in the top of the casing hanger slip segments, 180 degrees apart.
11. Securely tie the soft-line cord to the eyebolts.

NOTE

Measuring the soft-line cord and installing the eyebolts into the hanger segments should be done offline.



| | | | | | |
|--|-----------------------------|-------------------------|---------------|-----------------|----------------|
|  Weatherford 5-3-GL-GL-WES-00XXX | Field Service Manual | Prepared By: | Reviewed By: | Approved By: | SM-13-1 |
| | | <i>Marion Robertson</i> | Brad Franks | Manual Zaragoza | Rev WIP |
| | | Marion Robertson | Brad Franks | Manual Zaragoza | Page 17 of 24 |
| | | December 2014 | December 2014 | December 2014 | |

WFT Split Bowl (SB) Wellhead System (Continued)

12. Remove the slip retaining cap screws from the outer diameter of the hanger body, allowing the slip segments to settle around the casing.
13. Supporting the weight of the casing hanger, remove the support boards and carefully lower the hanger through the BOP stack into the WFT-SB casing head/spool assembly, until it securely lands on the pack-off bushing load shoulder.



Do NOT drop hanger; lower it carefully.



Hanging off the Production Casing


1. With the casing hanger now landed onto the pack-off bushing load shoulder, pull tension on the casing to the desired hanging weight, and then slack off.

NOTE

A sharp decrease on the weight indicator will signify that the hanger has taken weight. If this does not occur, pull tension again and slack off once more.

2. Rough cut casing approximately 16" above top of WFT-SB Spool top flange. Remove excess casing.
3. Carefully remove BOP stack, set aside.
4. Final cut the casing at about $12\frac{7}{8}" \pm \frac{1}{8}"$ above the face of the WFT-SB spool, which will allow room for the double studded adapter flange.
5. Grind the casing stub level and bevel the casing outer diameter ($\frac{1}{4}" \times \frac{1}{8}"$) and inner diameter ($\frac{1}{8}" \times 45$ degrees).



| | | | | | |
|--|-----------------------------|-------------------------|---------------|-----------------|----------------|
|  Weatherford 5-3-GL-GL-WES-00XXX | Field Service Manual | Prepared By: | Reviewed By: | Approved By: | SM-13-1 |
| | | <i>Marion Robertson</i> | Brad Franks | Manual Zaragoza | Rev WIP |
| | | Marion Robertson | Brad Franks | Manual Zaragoza | Page 18 of 24 |
| | | December 2014 | December 2014 | December 2014 | |

WFT Split Bowl (SB) Wellhead System (Continued)

Installation of the Double-Studded Adapter (DSA) Flange

1. Examine the double studded adapter (DSA) Flange. Verify the following:
 - Ring grooves are clean and undamaged.
 - Stud threads are clean and undamaged.
2. Orient the DSA flange with the 10M side down.
3. Thoroughly clean the mating grooves of the DSA flange and the WFT-SB spool assembly. Wipe lightly with oil or grease.


WARNING

Excessive oil or grease will prevent a positive seal from forming.

4. Install a new appropriately sized ring gasket into the WFT-SB spool assembly groove.
5. Lift, while holding level, and carefully lower the DSA over the production casing stub until it lands on the ring gasket.
6. Make-up the flange connection with appropriate nuts, tightening in alternate cross pattern, as required by API 6A.
7. Fill the void area in the DSA around the production casing with a light weight oil.
8. Continue filling with a light weight oil to the top of the DSA.

WARNING

Do NOT allow oil to run into the ring groove. This may prevent a positive seal from forming.



RP104104



Weatherford

5-3-GL-GL-WES-00XXX

**Field Service
Manual**

Prepared By:

Marion Robertson
Marion Robertson

December 2014

Reviewed By:

Brad Franks

Brad Franks

December 2014

Approved By:

Manual Zaragoza

Manual Zaragoza

December 2014

SM-13-1

Rev WIP

Page 19 of
24

WFT Split Bowl (SB) Wellhead System (Continued)

Installation and Testing of the Tubing Spool Assembly

Installation of the TCM Tubing Spool Assembly

1. Examine the tubing spool assembly. Verify the following:
 - bore is clean and free of debris
 - ring grooves and seals are clean and undamaged
 - PE-seal assembly is properly installed, clean and undamaged.
2. Thoroughly clean the mating ring grooves of the WFT-TCM Tubing Spool and WFT-SB Casing Spool.
3. Lightly lubricate the inner diameter of the PE-seal and outer diameter of the casing stub with oil or grease.

WARNING

Excessive oil or grease will prevent a positive seal from forming.

4. Install a new appropriately sized ring gasket into the WFT-SB casing spool assembly groove.
5. Orient the tubing spool assembly as required and carefully lower it over the casing stub, until it lands on the ring gasket.
6. Make up the flange connection with the appropriate studs and nuts, tightening in an alternating cross pattern, as required by API 6A.

Testing the Secondary Seal and Flange Connection Test


1. Locate the test port fitting on the OD of the tubing spool lower flange. Remove the dust cap from the fitting.
2. Attach a test pump to the test port fitting.


3. Pump clean test fluid into the void area between the flanges until a test pressure of **10,000 psi or 80% of casing collapse pressure is attained**, whichever is lower.
4. Hold and monitor pressure for 15 minutes or as required by the drilling supervisor.
5. Once a satisfactory test is achieved, carefully bleed off pressure and remove the test pump
6. Attach a bleeder tool to the test port fitting and open the tool to vent any remaining trapped pressure.

CAUTION

Always direct the bleeder tool port away from people and property.

7. Remove the bleeder tool and reinstall the dust cap on the test port fitting.
8. Install a new appropriately sized ring gasket into the tubing spool groove.



| | | | | | |
|--|-----------------------------|-------------------------|---------------|-----------------|----------------|
|  Weatherford 5-3-GL-GL-WES-00XXX | Field Service Manual | Prepared By: | Reviewed By: | Approved By: | SM-13-1 |
| | | <i>Marion Robertson</i> | Brad Franks | Manual Zaragoza | Rev WIP |
| | | Marion Robertson | Brad Franks | Manual Zaragoza | Page 20 of 24 |
| | | December 2014 | December 2014 | December 2014 | |

WFT Split Bowl (SB) Wellhead System (Continued)

Testing the BOP

NOTE

Immediately after the make-up of the BOP Stack and periodically during drilling of hole for the next string, the BOP stack (flanged connections and rams) must be tested.


1. Examine the test plug. Verify that:
 - O-ring seals and plugs are properly installed, clean and undamaged.
 - All threads are clean and undamaged.
2. Orient the test plug with O-ring seals up and drill pipe pin connection down.
3. Make up a joint of drill pipe to the top of the test plug.


NOTE

If pressure is to be supplied through the drill pipe, the pipe plug should be removed from the weep port.

4. Fully retract all lockscrews on the WFT-TCM tubing spool assembly.
5. Open the side outlet valves on the tubing spool.
6. Wipe the test plug O-ring seals with a light oil or grease.
7. Lower the test plug through the BOP until it lands on the tubing spool load shoulder.
8. Close the BOP rams on the drill pipe and test to **10,000 psi maximum**.
9. Monitor the open outlets for signs of leakage past the test plug.

10. Once a satisfactory test is achieved, release pressure and open the rams.
11. Close the side outlet valves.
12. Remove as much fluid from the BOP stack as possible.
13. Slowly retrieve the test plug, avoiding damage to the seals.
14. Repeat this procedure, as required, during drilling or conditioning of the hole.



| | | | | | |
|--|-----------------------------|-------------------------|---------------|-----------------|----------------|
|  Weatherford 5-3-GL-GL-WES-00XXX | Field Service Manual | Prepared By: | Reviewed By: | Approved By: | SM-13-1 |
| | | <i>Marion Robertson</i> | Brad Franks | Manual Zaragoza | Rev WIP |
| | | Marion Robertson | Brad Franks | Manual Zaragoza | Page 21 of 24 |
| | | December 2014 | December 2014 | December 2014 | |


WFT Split Bowl (SB) Wellhead System (Continued)


Hanging off the Production Tubing String

1. Run the production tubing and space out appropriately for the tubing hanger.
2. Examine the TC1AEN Tubing Hanger. Verify the following:
 - Packing element is clean and undamaged.
 - S-seals are properly installed.
 - S-seals are clean and undamaged.
 - All threads are clean and undamaged.
3. Make-up a short handling joint to the top of the tubing hanger.
4. Pick up the tubing hanger and make it up to the tubing string, tightening the connection to the thread manufacturer's recommended optimum torque value.
5. Remove the short handling joint from the top of the hanger. Make up the landing joint to the top of the tubing hanger, tightening the connection to the thread manufacturer's recommended minimum torque values.
6. Ensure that all tubing spool lockscrews are fully retracted from the bore and open side outlet valves. Drain the BOP stack.
7. Calculate the distance from the tubing spool load shoulder to the rig floor. Measure from the face of the tubing spool.
8. Carefully lower the tubing hanger into the well, tallying the tubing every five feet, until the tubing hanger lands securely on the tubing spool load shoulder.
9. Run in all tubing spool lockscrews, in an alternating cross pattern, to 300 ft-lbs, in 75 ft-lb increments.
10. Remove the landing joint from the tubing hanger, and set it aside.

NOTE

The side outlet valves should remain open while landing the tubing hanger.



| | | | | | |
|--|-----------------------------|-------------------------|---------------|-----------------|----------------|
|  Weatherford 5-3-GL-GL-WES-00XXX | Field Service Manual | Prepared By: | Reviewed By: | Approved By: | SM-13-1 |
| | | <i>Marion Robertson</i> | Brad Franks | Manual Zaragoza | Rev WIP |
| | | Marion Robertson | Brad Franks | Manual Zaragoza | Page 22 of 24 |
| | | December 2014 | December 2014 | December 2014 | |

WFT Split Bowl (SB) Wellhead System (Continued)

11. Install the Type H Back Pressure Valve, carefully lowering the BPV through the BOP stack into the tubing hanger. Rotate the BPV counterclockwise (to the left) until it bottoms out in the tubing hanger BPV prep. Continue rotating counterclockwise, approximately 7 turns, to retrieve the running tool.
12. With the well safe and under control, the BOP stack may be removed.

Installation and Testing of the Production Tree

Installation

1. Examine the production tree assembly. Verify the following;
 - Bore is clean and free of debris.
 - All valves are in the fully open position.
 - All threads and seal areas are clean and undamaged.
 - All fittings, nuts and handwheels are intact and undamaged.
2. Thoroughly clean all exposed portions of the tubing hanger, tubing head adapter flange and bottom prep of the tubing head adapter.
3. Thoroughly clean mating ring grooves of the tubing head adapter flange and WFT-TCM tubing spool.
4. Lightly lubricate the tubing hanger neck outer diameter and tubing head adapter flange bottom prep with oil or grease.

WARNING



Excessive oil or grease will prevent a positive seal from forming.

5. Install a new appropriately sized ring gasket into the WFT-TCM tubing spool groove.

6. Fill the void area around the hanger with hydraulic fluid, to the top of the tubing spool assembly.

WARNING

Do NOT overfill the void area, allowing oil to run into the ring groove. This may prevent a positive seal from forming.



Weatherford

5-3-GL-GL-WES-00XXX

Field Service Manual

Prepared By:

Marion Robertson
Marion Robertson

December 2014

Reviewed By:

Brad Franks
Brad Franks

December 2014

Approved By:

Manual Zaragoza
Manual Zaragoza

December 2014

SM-13-1

Rev WIP

Page 23 of 24

WFT Split Bowl (SB) Wellhead System (Continued)

- Align and level the production tree above the tubing hanger and carefully lower it over the tubing hanger neck, landing it on the ring gasket.

WARNING

Do NOT damage the hanger neck seals, as this will impair their sealing ability.

- Make up the connection using the appropriate studs and nuts, and tightening in an alternating cross pattern, as required by API 6A.

Testing the Production Tree Connection


- Locate the test port fitting on the outer diameter of the tubing head adapter flange. Remove the dust cap from the fitting.
- Attach a test pump to test port fitting, and open the pump.
- Pump clean test fluid into void area between flanges, test to 10,000 psi maximum.
- Hold and monitor pressure for **15 minutes or as required by the production supervisor**.
- Once a satisfactory test is achieved, carefully bleed off test pressure and remove the test pump.
- Attach a bleeder tool to the test port fitting, and open the tool to vent any remaining trapped pressure.


CAUTION

Always direct the bleeder tool away from people and property.

- Remove the bleeder tool and reinstall the dust cap on the test port fitting.

- Remove the type 'H' back pressure valve (BPV) through the production tree.
- Ensure that the well is safe and secure by closing all gate valves.



| | | | | | |
|--|-----------------------------|-------------------------|---------------|-----------------|----------------|
|  Weatherford 5-3-GL-GL-WES-00XXX | Field Service Manual | Prepared By: | Reviewed By: | Approved By: | SM-13-1 |
| | | <i>Marion Robertson</i> | Brad Franks | Manual Zaragoza | Rev WIP |
| | | Marion Robertson | Brad Franks | Manual Zaragoza | Page 24 of 24 |
| | | December 2014 | December 2014 | December 2014 | |