

FEB 15 2018**RECEIVED**

**PECOS DISTRICT
DRILLING OPERATIONS
CONDITIONS OF APPROVAL**

OPERATOR'S NAME:	Matador Production Company
LEASE NO.:	NMNM-136226
WELL NAME & NO.:	Biggers Federal Com 24H
SURFACE HOLE FOOTAGE:	0090' FSL & 1226' FEL
BOTTOM HOLE FOOTAGE	0240' FNL & 0994' FEL
LOCATION:	Section 18, T. 25 S., R 35 E., NMPM
COUNTY:	County, New Mexico

The BLM is to be notified in advance for a representative to witness:

- a. Spudding well (minimum of 24 hours)
- b. Setting and/or Cementing of all casing strings (minimum of 4 hours)
- c. BOPE tests (minimum of 4 hours)

☐ **Lea County**

Call the Hobbs Field Station, 414 West Taylor, Hobbs NM 88240,
(575) 3933612

Communitization Agreement

The operator will submit a Communitization Agreement to the Carlsbad Field Office, 620 E Greene St. Carlsbad, New Mexico 88220, at least 90 days before the anticipated date of first production from a well subject to a spacing order issued by the New Mexico Oil Conservation Division. The Communitization Agreement will include the signatures of all working interest owners in all Federal and Indian leases subject to the Communitization Agreement (i.e., operating rights owners and lessees of record), or certification that the operator has obtained the written signatures of all such owners and will make those signatures available to the BLM immediately upon request.

If the operator does not comply with this condition of approval, the BLM may take enforcement actions that include, but are not limited to, those specified in 43 CFR 3163.1.

In addition, the well sign shall include the surface and bottom hole lease numbers. When the Communitization Agreement number is known, it shall also be on the sign.

Provide NMOCD Gas Capture Plan (GCP) Form:

Well(s)/Facility information:

1. Name of facility

2. Wells that will be located (new and future) at this facility

- a. Well name and number
- b. Well API number
- c. Well location, Sect, T, R, Footages, county, state
- d. Expected IP gas rate, Mcfpd of each well
- e. First planned production date for well(s) that are developed from this facility

A. Hydrogen Sulfide

1. **Although Hydrogen Sulfide has not been reported in the area, it is always a potential hazard. If Hydrogen Sulfide is encountered, report measured amounts and formations to the BLM.**
2. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval. **If the drilling rig is removed without approval – an Incident of Non-Compliance will be written and will be a “Major” violation.**
3. Floor controls are required for 3M or Greater systems. These controls will be on the rig floor, unobstructed, readily accessible to the driller and will be operational at all times during drilling and/or completion activities. Rig floor is defined as the area immediately around the rotary table; the area immediately above the substructure on which the draw works is located, this does not include the dog house or stairway area.
4. **The record of the drilling rate along with the GR/N well log run from TD to surface (horizontal well – vertical portion of hole) shall be submitted to the BLM office as well as all other logs run on the borehole 30 days from completion. If available, a digital copy of the logs is to be submitted in addition to the paper copies. The Rustler top and top and bottom of Salt are to be recorded on the Completion Report.**

A. CASING

Changes to the approved APD casing program need prior approval if the items substituted are of lesser grade or different casing size or are Non-API. The Operator can exchange the components of the proposal with that of superior strength (i.e. changing from J-55 to N-80, or from 36# to 40#). Changes to the approved cement program need prior approval if the altered cement plan has less volume or strength or if the changes are substantial (i.e. Multistage tool, ECP, etc.).

The initial wellhead installed on the well will remain on the well with spools used as needed.

Centralizers required on surface casing per Onshore Order 2.III.B.1.f.

Wait on cement (WOC) for Water Basin:

After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi at the shoe, 2) until cement has been in place at least **8 hours**. WOC time will be recorded in the driller's log. See individual casing strings for details regarding lead cement slurry requirements.

Provide compressive strengths including hours to reach required 500 pounds compressive strength prior to cementing each casing string. Have well specific cement details onsite prior to pumping the cement for each casing string.

No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.

Possibility of water flows in the Castile and Salado formations

Possibility of lost circulation in the Rustler, Red Beds, and Delaware formations

1. The 13-3/8 inch surface casing shall be set at approximately 1000 feet and cemented to the surface. **If salt is encountered, set casing at least 25 feet above the salt.**
 - a. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with surface log readout will be used or a cement bond log shall be run to verify the top of the cement. Temperature survey will be run a minimum of six hours after pumping cement and ideally between 8-10 hours after completing the cement job.
 - b. **Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry.**
 - c. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength, whichever is greater.
 - d. If cement falls back, remedial cementing will be done prior to drilling out that string.

Intermediate casing shall be kept fluid filled while running into hole to meet BLM minimum collapse requirements.

2. The minimum required fill of cement behind the 9-5/8 inch intermediate casing is:

- ☐ Cement to surface. If cement does not circulate see B.1.a, c-d above.

Centralizers required on horizontal leg, must be type for horizontal service and a minimum of one every other joint.

3. The minimum required fill of cement behind the 5-1/2 inch production casing is:

- ☐ Cement as proposed by operator. Operator shall provide method of verification.

4. If hardband drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.

B. PRESSURE CONTROL

1. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in Onshore Oil and Gas Order No. 2 and API 53.
2. Variance approved to use flex line from BOP to choke manifold. Check condition of flexible line from BOP to choke manifold, replace if exterior is damaged or if line fails test. Line to be as straight as possible with no hard bends and is to be anchored according to Manufacturer's requirements. The flexible hose can be exchanged with a hose of equal size and equal or greater pressure rating. **Anchor requirements, specification sheet and hydrostatic pressure test certification matching the hose in service, to be onsite for review. These documents shall be posted in the company man's trailer and on the rig floor.** If the BLM inspector questions the straightness of the hose, a BLM engineer will be contacted and will review in the field or via picture supplied by inspector to determine if changes are required (operator shall expect delays if this occurs).
3. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be psi (**Operator will have a 5M, testing to 2,000 psi**).
 - a. **For surface casing only:** If the BOP/BOPE is to be tested against casing, the wait on cement (WOC) time for that casing is to be met (see WOC statement at start of casing section). Independent service company required.
4. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the 9-5/8 intermediate casing shoe shall be psi (**Operator will have a 5M, testing to 3,000 psi**).

5. The appropriate BLM office shall be notified a minimum of hours in advance for a representative to witness the tests.
- a. In a water basin, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. The casing cut-off and BOP installation can be initiated four hours after installing the slips, which will be approximately six hours after bumping the plug. For those casing strings not using slips, the minimum wait time before cut-off is eight hours after bumping the plug. BOP/BOPE testing can begin after cut-off or once cement reaches 500 psi compressive strength (including lead when specified), whichever is greater. However, if the float does not hold, cut-off cannot be initiated until cement reaches 500 psi compressive strength (including lead when specified).
 - a. The tests shall be done by an independent service company utilizing a test plug **not a cup or J-packer**. The operator also has the option of utilizing an independent tester to test without a plug (i.e. against the casing) pursuant to Onshore Order 2 with the pressure not to exceed 70% of the burst rating for the casing. Any test against the casing must meet the WOC time for water basin (8 hours) or potash (24 hours) or 500 pounds compressive strength, whichever is greater, prior to initiating the test (see casing segment as lead cement may be critical item).
 - b. The test shall be run on a 5000 psi chart for a 2-3M BOP/BOP, on a 10000 psi chart for a 5M BOP/BOPE and on a 15000 psi chart for a 10M BOP/BOPE. If a linear chart is used, it shall be a one hour chart. A circular chart shall have a maximum 2 hour clock. If a twelve hour or twenty-four hour chart is used, tester shall make a notation that it is run with a two hour clock.
 - c. The results of the test shall be reported to the appropriate BLM office.
 - d. All tests are required to be recorded on a calibrated test chart. **A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.**
 - e. The BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes if test is done with a test plug and 30 minutes without a test plug. This test shall be performed prior to the test at full stack pressure.

C. DRILL STEM TEST

If drill stem tests are performed, Onshore Order 2.III.D shall be followed.

D. WASTE MATERIAL AND FLUIDS

All waste (i.e. drilling fluids, trash, salts, chemicals, sewage, gray water, etc.) created as a result of drilling operations and completion operations shall be safely contained and disposed of properly at a waste disposal facility. No waste material or fluid shall be disposed of on the well location or surrounding area.

Porto-johns and trash containers will be on-location during fracturing operations or any other crew-intensive operations.

JAM 012318

FEB 15 2018**RECEIVED**

**PECOS DISTRICT
SURFACE USE
CONDITIONS OF APPROVAL**

OPERATOR'S NAME:	Matador Prod Co
LEASE NO.:	NM136226
WELL NAME & NO.:	24H – Biggers Fed Com
SURFACE HOLE FOOTAGE:	90'/S & 1226'/E
BOTTOM HOLE FOOTAGE:	240'/N & 994'/E
LOCATION:	Section 18, T. 25 S., R. 35 E., NMPM
COUNTY:	Lea County, New Mexico

TABLE OF CONTENTS

Standard Conditions of Approval (COA) apply to this APD. If any deviations to these standards exist or special COAs are required, the section with the deviation or requirement will be checked below.

- ☐ **General Provisions**
- ☐ **Permit Expiration**
- ☐ **Archaeology, Paleontology, and Historical Sites**
- ☐ **Noxious Weeds**
- ☒ **Special Requirements**
 - Lesser Prairie-Chicken Timing Stipulations
 - Below Ground-level Abandoned Well Marker
 - Hydrology
- ☐ **Construction**
 - Notification
 - Topsoil
 - Closed Loop System
 - Federal Mineral Material Pits
 - Well Pads
 - Roads
- ☐ **Road Section Diagram**
- ☐ **Production (Post Drilling)**
 - Well Structures & Facilities
- ☐ **Interim Reclamation**
- ☐ **Final Abandonment & Reclamation**

I. GENERAL PROVISIONS

The approval of the Application For Permit To Drill (APD) is in compliance with all applicable laws and regulations: 43 Code of Federal Regulations 3160, the lease terms, Onshore Oil and Gas Orders, Notices To Lessees, New Mexico Oil Conservation Division (NMOCD) Rules, National Historical Preservation Act As Amended, and instructions and orders of the Authorized Officer. Any request for a variance shall be submitted to the Authorized Officer on Form 3160-5, Sundry Notices and Report on Wells.

II. PERMIT EXPIRATION

If the permit terminates prior to drilling and drilling cannot be commenced within 60 days after expiration, an operator is required to submit Form 3160-5, Sundry Notices and Reports on Wells, requesting surface reclamation requirements for any surface disturbance. However, if the operator will be able to initiate drilling within 60 days after the expiration of the permit, the operator must have set the conductor pipe in order to allow for an extension of 60 days beyond the expiration date of the APD. (Filing of a Sundry Notice is required for this 60 day extension.)

III. ARCHAEOLOGICAL, PALEONTOLOGY & HISTORICAL SITES

Any cultural and/or paleontological resource discovered by the operator or by any person working on the operator's behalf shall immediately report such findings to the Authorized Officer. The operator is fully accountable for the actions of their contractors and subcontractors. The operator shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery shall be made by the Authorized Officer to determine the appropriate actions that shall be required to prevent the loss of significant cultural or scientific values of the discovery. The operator shall be held responsible for the cost of the proper mitigation measures that the Authorized Officer assesses after consultation with the operator on the evaluation and decisions of the discovery. Any unauthorized collection or disturbance of cultural or paleontological resources may result in a shutdown order by the Authorized Officer.

IV. NOXIOUS WEEDS

The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes the roads, pads, associated pipeline corridor, and adjacent land affected by the establishment of weeds due to this action. The operator shall consult with the Authorized Officer for acceptable weed control methods, which include following EPA and BLM requirements and policies.

V. SPECIAL REQUIREMENT(S)

Timing Limitation Stipulation / Condition of Approval for lesser prairie-chicken:

Oil and gas activities including 3-D geophysical exploration, and drilling will not be allowed in lesser prairie-chicken habitat during the period from March 1st through June 15th annually. During that period, other activities that produce noise or involve human activity, such as the maintenance of oil and gas facilities, pipeline, road, and well pad construction, will be allowed except between 3:00 am and 9:00 am. The 3:00 am to 9:00 am restriction will not apply to normal, around-the-clock operations, such as venting, flaring, or pumping, which do not require a human presence during this period. Additionally, no new drilling will be allowed within up to 200 meters of leks known at the time of permitting. Normal vehicle use on existing roads will not be restricted. Exhaust noise from pump jack engines must be muffled or otherwise controlled so as not to exceed 75 db measured at 30 feet from the source of the noise.

Below Ground-level Abandoned Well Marker to avoid raptor perching: Upon the plugging and subsequent abandonment of the well, the well marker will be installed at ground level on a plate containing the pertinent information for the plugged well. For more installation details, contact the Carlsbad Field Office at 575-234-5972.

Watershed/Water Quality:

The entire perimeter of the well pad will be bermed to prevent oil, salt, and other chemical contaminants from leaving the well pad.

- The compacted berm shall be constructed at a minimum of 12 inches high with impermeable mineral material (e.g. caliche).
- No water flow from the uphill side(s) of the pad shall be allowed to enter the well pad.
- The topsoil stockpile shall be located outside the bermed well pad.
- Topsoil, either from the well pad or surrounding area, shall not be used to construct the berm.
- No storm drains, tubing or openings shall be placed in the berm.
- If fluid collects within the bermed area, the fluid must be vacuumed into a safe container and disposed of properly at a state approved facility.
- The integrity of the berm shall be maintained around the surfaced pad throughout the life of the well and around the downsized pad after interim reclamation has been completed.
- Any access road entering the well pad shall be constructed so that the integrity of the berm height surrounding the well pad is not compromised. (Any access road crossing the berm cannot be lower than the berm height.)

VI. CONSTRUCTION

A. NOTIFICATION

The BLM shall administer compliance and monitor construction of the access road and well pad. Notify the Carlsbad Field Office at (575) 234-5909 at least 3 working days prior to commencing construction of the access road and/or well pad.

When construction operations are being conducted on this well, the operator shall have the approved APD and Conditions of Approval (COA) on the well site and they shall be made available upon request by the Authorized Officer.

B. TOPSOIL

The operator shall strip the top portion of the soil (root zone) from the entire well pad area and stockpile the topsoil along the edge of the well pad as depicted in the APD. The root zone is typically six (6) inches in depth. All the stockpiled topsoil will be redistributed over the interim reclamation areas. Topsoil shall not be used for berming the pad or facilities. For final reclamation, the topsoil shall be spread over the entire pad area for seeding preparation.

Other subsoil (below six inches) stockpiles must be completely segregated from the topsoil stockpile. Large rocks or subsoil clods (not evident in the surrounding terrain) must be buried within the approved area for interim and final reclamation.

C. CLOSED LOOP SYSTEM

Tanks are required for drilling operations: No Pits.

The operator shall properly dispose of drilling contents at an authorized disposal site.

D. FEDERAL MINERAL MATERIALS PIT

Payment shall be made to the BLM prior to removal of any federal mineral materials. Call the Carlsbad Field Office at (575) 234-5972.

E. WELL PAD SURFACING

Surfacing of the well pad is not required.

If the operator elects to surface the well pad, the surfacing material may be required to be removed at the time of reclamation. The well pad shall be constructed in a manner which creates the smallest possible surface disturbance, consistent with safety and operational needs.

F. EXCLOSURE FENCING (CELLARS & PITS)

Exclosure Fencing

The operator will install and maintain exclosure fencing for all open well cellars to prevent access to public, livestock, and large forms of wildlife before and after drilling operations until the pit is free of fluids and the operator initiates backfilling. (For examples of exclosure fencing design, refer to BLM's Oil and Gas Gold Book, Exclosure Fence Illustrations, Figure 1, Page 18.)

G. ON LEASE ACCESS ROADS**Road Width**

The access road shall have a driving surface that creates the smallest possible surface disturbance and does not exceed fourteen (14) feet in width. The maximum width of surface disturbance, when constructing the access road, shall not exceed twenty-five (25) feet.

Surfacing

Surfacing material is not required on the new access road driving surface. If the operator elects to surface the new access road or pad, the surfacing material may be required to be removed at the time of reclamation.

Where possible, no improvements should be made on the unsurfaced access road other than to remove vegetation as necessary, road irregularities, safety issues, or to fill low areas that may sustain standing water.

The Authorized Officer reserves the right to require surfacing of any portion of the access road at any time deemed necessary. Surfacing may be required in the event the road deteriorates, erodes, road traffic increases, or it is determined to be beneficial for future field development. The surfacing depth and type of material will be determined at the time of notification.

Crowning

Crowning shall be done on the access road driving surface. The road crown shall have a grade of approximately 2% (i.e., a 1" crown on a 14' wide road). The road shall conform to Figure 1; cross section and plans for typical road construction.

Ditching

Ditching shall be required on both sides of the road.

Turnouts


Vehicle turnouts shall be constructed on the road. Turnouts shall be intervisible with interval spacing distance less than 1000 feet. Turnouts shall conform to Figure 1; cross section and plans for typical road construction.

Drainage

Drainage control systems shall be constructed on the entire length of road (e.g. ditches, sidehill outslowing and insloping, lead-off ditches, culvert installation, and low water crossings).

A typical lead-off ditch has a minimum depth of 1 foot below and a berm of 6 inches above natural ground level. The berm shall be on the down-slope side of the lead-off ditch.

Cross Section of a Typical Lead-off Ditch



All lead-off ditches shall be graded to drain water with a 1 percent minimum to 3 percent maximum ditch slope. The spacing interval are variable for lead-off ditches and shall be determined according to the formula for spacing intervals of lead-off ditches, but may be amended depending upon existing soil types and centerline road slope (in %);

Formula for Spacing Interval of Lead-off Ditches

Example - On a 4% road slope that is 400 feet long, the water flow shall drain water into a lead-off ditch. Spacing interval shall be determined by the following formula:

$$400 \text{ foot road with } 4\% \text{ road slope: } \frac{400'}{4\%} + 100' = 200' \text{ lead-off ditch interval}$$

Cattle guards

An appropriately sized cattle guard sufficient to carry out the project shall be installed and maintained at fence/road crossings. Any existing cattle guards on the access road route shall be repaired or replaced if they are damaged or have deteriorated beyond practical use. The operator shall be responsible for the condition of the existing cattle guards that are in place and are utilized during lease operations.

Fence Requirement

Where entry is granted across a fence line, the fence shall be braced and tied off on both sides of the passageway prior to cutting. The operator shall notify the private surface landowner or the grazing allotment holder prior to crossing any fences.

Public Access

Public access on this road shall not be restricted by the operator without specific written approval granted by the Authorized Officer.

Construction Steps

1. Salvage topsoil
2. Construct road

3. Redistribute topsoil
4. Revegetate slopes




Figure 1. Cross-sections and plans for typical road sections representative of BLM resource or FS local and higher-class roads.

VII. PRODUCTION (POST DRILLING)

A. WELL STRUCTURES & FACILITIES

Placement of Production Facilities

Production facilities should be placed on the well pad to allow for maximum interim recontouring and revegetation of the well location.

Exclosure Netting (Open-top Tanks)

Immediately following active drilling or completion operations, the operator will take actions necessary to prevent wildlife and livestock access, including avian wildlife, to all open-topped tanks that contain or have the potential to contain salinity sufficient to cause harm to wildlife or livestock, hydrocarbons, or Resource Conservation and Recovery Act of 1976-exempt hazardous substances. At a minimum, the operator will net, screen, or cover open-topped tanks to exclude wildlife and livestock and prevent mortality. If the operator uses netting, the operator will cover and secure the open portion of the tank to prevent wildlife entry. The operator will net, screen, or cover the tanks until the operator removes the tanks from the location or the tanks no longer contain substances that could be harmful to wildlife or livestock. Use a maximum netting mesh size of 1 ½ inches. The netting must not be in contact with fluids and must not have holes or gaps.

Chemical and Fuel Secondary Containment and Exclosure Screening

The operator will prevent all hazardous, poisonous, flammable, and toxic substances from coming into contact with soil and water. At a minimum, the operator will install and maintain an impervious secondary containment system for any tank or barrel containing hazardous, poisonous, flammable, or toxic substances sufficient to contain the contents of the tank or barrel and any drips, leaks, and anticipated precipitation. The operator will dispose of fluids within the containment system that do not meet applicable state or U. S. Environmental Protection Agency livestock water standards in accordance with state law; the operator must not drain the fluids to the soil or ground. The operator will design, construct, and maintain all secondary containment systems to prevent wildlife and livestock exposure to harmful substances. At a minimum, the operator will install effective wildlife and livestock exclosure systems such as fencing, netting, expanded metal mesh, lids, and grate covers. Use a maximum netting mesh size of 1 ½ inches.

Open-Vent Exhaust Stack Exclosures

The operator will construct, modify, equip, and maintain all open-vent exhaust stacks on production equipment to prevent birds and bats from entering, and to discourage perching, roosting, and nesting. (*Recommended exclosure structures on open-vent exhaust stacks are in the shape of a cone.*) Production equipment includes, but may not be limited to, tanks, heater-treaters, separators, dehydrators, flare stacks, in-line units, and compressor mufflers.

Containment Structures

Proposed production facilities such as storage tanks and other vessels will have a secondary containment structure that is constructed to hold the capacity of 1.5 times the largest tank, plus freeboard to account for precipitation, unless more stringent protective requirements are deemed necessary.

Painting Requirement

All above-ground structures including meter housing that are not subject to safety requirements shall be painted a flat non-reflective paint color, **Shale Green** from the BLM Standard Environmental Color Chart (CC-001: June 2008).

VIII. INTERIM RECLAMATION

During the life of the development, all disturbed areas not needed for active support of production operations should undergo interim reclamation in order to minimize the environmental impacts of development on other resources and uses.

Within six (6) months of well completion, operators should work with BLM surface management specialists (Jim Amos: 575-234-5909) to devise the best strategies to reduce the size of the location. Interim reclamation should allow for remedial well operations, as well as safe and efficient removal of oil and gas.

During reclamation, the removal of caliche is important to increasing the success of revegetating the site. Removed caliche that is free of contaminants may be used for road repairs, fire walls or for building other roads and locations. In order to operate the well or complete workover operations, it may be necessary to drive, park and operate on restored interim vegetation within the previously disturbed area. Disturbing revegetated areas for production or workover operations will be allowed. If there is significant disturbance and loss of vegetation, the area will need to be revegetated. Communicate with the appropriate BLM office for any exceptions/exemptions if needed.

All disturbed areas after they have been satisfactorily prepared need to be reseeded with the seed mixture provided below.

Upon completion of interim reclamation, the operator shall submit a Sundry Notices and Reports on Wells, Subsequent Report of Reclamation (Form 3160-5).

IX. FINAL ABANDONMENT & RECLAMATION

At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land are restored.

Earthwork for final reclamation must be completed within six (6) months of well plugging. All pads, pits, facility locations and roads must be reclaimed to a satisfactory revegetated, safe, and stable condition, unless an agreement is made with the landowner or BLM to keep the road and/or pad intact.

After all disturbed areas have been satisfactorily prepared, these areas need to be revegetated with the seed mixture provided below. Seeding should be accomplished by drilling on the contour whenever practical or by other approved methods. Seeding may need to be repeated until revegetation is successful, as determined by the BLM.

Operators shall contact a BLM surface protection specialist prior to surface abandonment operations for site specific objectives (Jim Amos: 575-234-5909).

Below Ground-level Abandoned Well Marker to avoid raptor perching: Upon the plugging and subsequent abandonment of the well, the well marker will be installed at ground level on a plate containing the pertinent information for the plugged well.

Seed Mixture for LPC Sand/Shinnery Sites

Holder shall seed all disturbed areas with the seed mixture listed below. The seed mixture shall be planted in the amounts specified in pounds of pure live seed (PLS)* per acre. There shall be no primary or secondary noxious weeds in the seed mixture. Seed will be tested and the viability testing of seed shall be done in accordance with State law(s) and within nine (9) months prior to purchase. Commercial seed shall be either certified or registered seed. The seed container shall be tagged in accordance with State law(s) and available for inspection by the Authorized Officer.

Seed will be planted using a drill equipped with a depth regulator to ensure proper depth of planting where drilling is possible. The seed mixture will be evenly and uniformly planted over the disturbed area (smaller/heavier seeds have a tendency to drop the bottom of the drill and are planted first). Holder shall take appropriate measures to ensure this does not occur. Where drilling is not possible, seed will be broadcast and the area shall be raked or chained to cover the seed. When broadcasting the seed, the pounds per acre are to be doubled. Seeding shall be repeated until a satisfactory stand is established as determined by the Authorized Officer. Evaluation of growth may not be made before completion of at least one full growing season after seeding.

Species to be planted in pounds of pure live seed* per acre:

<u>Species</u>	<u>lb/acre</u>
Plains Bristlegrass	5lbs/A
Sand Bluestem	5lbs/A
Little Bluestem	3lbs/A
Big Bluestem	6lbs/A
Plains Coreopsis	2lbs/A
Sand Dropseed	1lbs/A

*Pounds of pure live seed:

Pounds of seed x percent purity x percent germination = pounds pure live seed



Hydrogen Sulfide Drilling

Operations Plan

1 H2S safety instructions to the following:

- Characteristics of H2S
- Physical effects and hazards
- Principal and operation of H2S detectors, warning system, and briefing areas
- Evacuation procedures, routes, and first aid
- Proper use of safety equipment & life support systems
- Essential personnel meeting medical evaluation criteria will receive additional training on the proper use of 30-minute pressure demand air packs

2 H2S Detection and Alarm Systems:

- H2S sensor/detectors will be located on the drilling rig floor, in the base of the sub structure / cellar area, on the mud pits in the shale shaker area. Additional H2S detectors may be placed as deemed necessary
- An audio alarm system will be installed on the derrick floor and in the doghouse.

3 Windssocks and / Wind Streamers:

- Windssocks at mud pit area should be high enough to be visible.
- Windssock on the rig floor and / top of doghouse should be high enough to be visible.

4 Condition Flags and Signs:

- Warning sign on access road to location
- Flags to be displayed on sign at entrance to location
 - Green Flag – Normal Safe Operation Condition
 - Yellow Flag – Potential Pressure and Danger
 - Red Flag – Danger (H2S present in dangerous concentrations) Only H2S trained personnel admitted on location

5 Well Control Equipment:

- See attachments

6 Communication:

- While working under masks, chalkboards will be used for communications.
- Hand signals will be used where chalkboard is inappropriate.
- Two-way radio will be used to communicate off location in case of emergency help is required. In most cases cellular telephones will be available at drilling foreman's trailer or living quarters.
-

Casing Design Criteria and Load Case Assumptions

Production Casing

Collapse: $DF_c=1.125$

- Full Internal Evacuation: Collapse force equal to the mud gradient in which the casing will be run (0.47 psi/ft). The effects of axial load on collapse will be considered.
- Cementing: Collapse force equal to the gradient of planned cement slurries to planned depths and mud gradient in which the casing will be run above that (0.47 psi/ft) and an internal force equal to mud gradient of displacement fluid (0.43 psi/ft).

Burst: $DF_b=1.125$

- Pressure Test: 8000 psi casing test with an external force equal to the mud gradient in which the casing will be run (0.47 psi/ft), which is a more conservative backup force than pore pressure.
- Injection Down Casing: 9500 psi surface injection pressure plus an internal pressure gradient of 0.65 psi/ft with an external force equal to the mud gradient in which the casing will be run (0.47 psi/ft), which is a more conservative backup force than pore pressure.

Tensile: $DF_t=1.8$

- Overpull: A downward force of 100,000 lbs is applied at the shoe along with the weight of the casing string utilizing the effects of buoyancy (9.0 ppg).



7 Drilling Stem Testing:

- No DSTs or cores are planned at this time.

8 Drilling contractor supervisor will be required to be familiar with the effects H₂S has on tubulars good and other mechanical equipment.

9 If H₂S is encountered, mud system will be altered if necessary to maintain control of formation. A mud gas separator will be brought into service along with H₂S scavengers if necessary.

11 Emergency Contacts

- See following page

H2S Contingency Plan Emergency Contacts
Biggers Fed Com wells
Matador Production Company
Sec. 18, T25S, R35E Lea County, NM

<u>Company Office</u>			
Matador Production Company		(972)-371-5200	
<u>Key Personnel</u>			
Name	Title	Office	Mobile
Billy Goodwin	Vice President Drilling	972-371-5210	817-522-2928
Gary Martin	Drilling Superintendent		601-669-1774
Dee Smith	Drilling Superintendent	972-371-5447	972-822-1010
Patrick Walsh	Drilling Engineer	972-371-5291	626-318-5808
Greg Deevers	Construction Superintendent		405-431-9527
Jimmy Benefield	Construction Superintendent		318-548-6659
<u>Lea County</u>			575-390-3186
Ambulance		911	
Nor Lea General Hospital (Hobbs)		575-397-0560	
State Police (Hobbs)		575-392-5580	
City Police (Hobbs)		575-397-9625	
Sheriff's Office (Lovington)		575-396-3611	
Fire Marshall (Lovington)		575-391-2983	
Volunteer Fire Dept. (Jal)		575-395-2221	
Emergency Management (Lovington)		575-391-2983	
New Mexico Oil Conservation Division (Hobbs)		575-393-6161	
BLM (Hobbs)		575-393-3612	
Hobbs Animal Clinic		575-392-5563	
Dal Paso Animal Hospital (Hobbs)		575-397-2286	
Mountain States Equine (Hobbs)		575-392-7488	
<u>Carlsbad</u>			
BLM		575-234-5972	
<u>Santa Fe</u>			
New Mexico Emergency Response Commission (Santa Fe)		505-476-9600	
New Mexico Emergency Response Commission (Santa Fe) 24 hrs		505-827-9126	
New Mexico State Emergency Operations Center		505-476-9635	
<u>National</u>			
National Emergency Response Center (Washington, D.C.)		800-424-8802	
<u>Medical</u>			
Flight for Life- 4000 24th St.; Lubbock, TX		806-743-9911	
Aerocare- R3, Box 49F; Lubbock, TX		806-747-8923	
Med Flight Air Amb- 2301 Yale Blvd SE, D3; Albuquerque, NM		505-842-4433	
SB Air Med Service- 2505 Clark Carr Loop SE; Albuquerque, NM		505-842-4949	
<u>Other</u>			
Boots & Coots IWC		800-256-9688	or 281-931-8884
Cudd Pressure Control		432-699-0139	or 432-563-3356
Halliburton		575-746-2757	
B.J. Services		575-746-3569	
NM Dept. of Transportation (Roswell)		575-637-7200	


H2S Rig Diagram

Biggers Fed Com 24H
SHL 90' FSL & 1226' FEL
18-25S-35E Lea County, NM

Wind Direction Indicator

H2S Monitors

Briefing Areas



NORTH


Prevailing Winds Out of the South

Matador Production Company

Biggers Fed Com #024H
H₂S Contingency Plan:
1 Mile Radius Map

Section 18, Township 25S, Range 35E
Lea County, New Mexico



 Surface Hole Location



NAD 1983 New Mexico State Plane East
FIPS 3001 Feet

PERMITS WEST


Prepared by Permits West, Inc., June 6, 2017
for Matador Production Company





Matador Resources
Lea County, NM
Biggers Fed Com
024H
Prelim Plan A
GL:3333*KB:29'

US State Plane 1927 (E-Wad solution)
NAD 1927 (NADCOM CONUS) Clarke 1866
New Mexico East 3301
Mean Sea Level




RKB Elevation: RIG @ 3382.00usft (GL 3333*KB:29')




+N-S	+E-W	Northing	Easting	Latitude	Longitude	Spot
0.00	0.00	409818.00	788455.00	32° 7' 23.799 N	103° 24' 5' 712 W	

SECTION DETAILS- Lateral

Sec	MD	Inc	Azi	TVD	+N-S	+E-W	Dleg	Vsect
1	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
2	1400.00	0.00	0.00	1400.00	0.00	0.00	0.00	0.00
3	1733.33	5.00	99.87	1732.91	-2.49	14.32	1.50	-2.60
4	4078.35	5.00	99.87	4069.01	-37.51	215.68	0.00	-39.20
5	4411.69	0.00	0.00	4401.92	-40.00	230.00	1.50	-41.81
6	8652.77	0.00	0.00	8643.00	-40.00	230.00	0.00	-41.81
7	9452.77	80.00	359.75	9207.25	433.46	227.93	10.00	431.66
8	9477.77	80.00	359.75	9211.59	458.08	227.83	0.00	458.28
9	9644.49	90.00	359.55	9228.10	623.95	226.81	6.00	622.15
10	13971.67	90.00	359.55	9226.00	4951.00	193.00	0.00	4949.33



Azimuth Corrections
Total Magnetic Cor. (M to G) 6.30°
Declination (M to T) 6.80° East



Matador Production Company

Biggers Fed Com #024H
H₂S Contingency Plan:
2 Mile Radius Map

Section 18, Township 25S, Range 35E
Lea County, New Mexico

⊙ Surface Hole Location



1:27,000
0 0.25 0.5 1
Miles



NAD 1983 New Mexico State Plane East
FIPS 3001 Feet

PERMITS WEST

Prepared by Permis West, Inc., June 8, 2017
for Matador Production Company



**Pro Directional
Survey Report**

Company: Matador Resources
Project: Lea County, NM
Site: Biggers Fed Com
Well: 024H
Wellbore: OH
Design: Prelim Plan A

HOBBS OCD
FEB 15 2018
RECEIVED

Local Co-ordinate Reference: Well 024H
TVD Reference: RIG @ 3362.00usft (GL:3333'+KB:29')
MD Reference: RIG @ 3362.00usft (GL:3333'+KB:29')
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Database: WellPlanner1

Project	Lea County, NM		
Map System:	US State Plane 1927 (Exact solution)	System Datum:	Mean Sea Level
Geo Datum:	NAD 1927 (NADCON CONUS)		
Map Zone:	New Mexico East 3001		

Site	Biggers Fed Com			
Site Position:		Northing:	409,817.00 usft	Latitude: 32° 7' 23.792 N
From:	Map	Easting:	788,425.00 usft	Longitude: 103° 24' 6.061 W
Position Uncertainty:	0.00 usft	Slot Radius:	13-3/16 "	Grid Convergence: 0.50 °

Well	024H			
Well Position	+N/-S	0.00 usft	Northing:	409,818.00 usft
	+E/-W	0.00 usft	Easting:	788,455.00 usft
Position Uncertainty	0.00 usft	Wellhead Elevation:	usft	Ground Level: 3,333.00 usft

Wellbore	OH				
Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	HDGM	3/21/2017	6.80	59.87	48,036.10

Design	Prelim Plan A			
Audit Notes:				
Version:	Phase:	PLAN	Tie On Depth:	0.00
Vertical Section:	Depth From (TVD) (usft)	+N/-S (usft)	+E/-W (usft)	Direction (°)
	0.00	0.00	0.00	359.55

Survey Tool Program	Date 3/21/2017			
From (usft)	To (usft)	Survey (Wellbore)	Tool Name	Description
0.00	13,971.67	Prelim Plan A (OH)	MWD - OWSG	MWD - OWSG

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
100.00	0.00	0.00	100.00	0.00	0.00	0.00	0.00	0.00	0.00
200.00	0.00	0.00	200.00	0.00	0.00	0.00	0.00	0.00	0.00
300.00	0.00	0.00	300.00	0.00	0.00	0.00	0.00	0.00	0.00
400.00	0.00	0.00	400.00	0.00	0.00	0.00	0.00	0.00	0.00
500.00	0.00	0.00	500.00	0.00	0.00	0.00	0.00	0.00	0.00
600.00	0.00	0.00	600.00	0.00	0.00	0.00	0.00	0.00	0.00
700.00	0.00	0.00	700.00	0.00	0.00	0.00	0.00	0.00	0.00
800.00	0.00	0.00	800.00	0.00	0.00	0.00	0.00	0.00	0.00
900.00	0.00	0.00	900.00	0.00	0.00	0.00	0.00	0.00	0.00

Pro Directional Survey Report

Company: Matador Resources
Project: Lea County, NM
Site: Biggers Fed Com
Well: 024H
Wellbore: OH
Design: Prelim Plan A

Local Co-ordinate Reference: Well 024H
TVD Reference: RIG @ 3362.00usft (GL:3333'+KB:29')
MD Reference: RIG @ 3362.00usft (GL:3333'+KB:29')
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Database: WellPlanner1

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
1,000.00	0.00	0.00	1,000.00	0.00	0.00	0.00	0.00	0.00	0.00
1,100.00	0.00	0.00	1,100.00	0.00	0.00	0.00	0.00	0.00	0.00
1,200.00	0.00	0.00	1,200.00	0.00	0.00	0.00	0.00	0.00	0.00
1,300.00	0.00	0.00	1,300.00	0.00	0.00	0.00	0.00	0.00	0.00
1,400.00	0.00	0.00	1,400.00	0.00	0.00	0.00	0.00	0.00	0.00
1,500.00	1.50	99.87	1,499.99	-0.22	1.29	-0.23	1.50	1.50	0.00
1,600.00	3.00	99.87	1,599.91	-0.90	5.16	-0.94	1.50	1.50	0.00
1,700.00	4.50	99.87	1,699.69	-2.02	11.60	-2.11	1.50	1.50	0.00
1,733.33	5.00	99.87	1,732.91	-2.49	14.32	-2.60	1.50	1.50	0.00
1,800.00	5.00	99.87	1,799.32	-3.49	20.04	-3.64	0.00	0.00	0.00
1,900.00	5.00	99.87	1,898.94	-4.98	28.63	-5.20	0.00	0.00	0.00
2,000.00	5.00	99.87	1,998.56	-6.47	37.22	-6.76	0.00	0.00	0.00
2,100.00	5.00	99.87	2,098.18	-7.97	45.80	-8.33	0.00	0.00	0.00
2,200.00	5.00	99.87	2,197.80	-9.46	54.39	-9.89	0.00	0.00	0.00
2,300.00	5.00	99.87	2,297.42	-10.95	62.98	-11.45	0.00	0.00	0.00
2,400.00	5.00	99.87	2,397.04	-12.45	71.56	-13.01	0.00	0.00	0.00
2,500.00	5.00	99.87	2,496.66	-13.94	80.15	-14.57	0.00	0.00	0.00
2,600.00	5.00	99.87	2,596.28	-15.43	88.74	-16.13	0.00	0.00	0.00
2,700.00	5.00	99.87	2,695.90	-16.93	97.32	-17.69	0.00	0.00	0.00
2,800.00	5.00	99.87	2,795.52	-18.42	105.91	-19.25	0.00	0.00	0.00
2,900.00	5.00	99.87	2,895.14	-19.91	114.50	-20.81	0.00	0.00	0.00
3,000.00	5.00	99.87	2,994.76	-21.41	123.08	-22.37	0.00	0.00	0.00
3,100.00	5.00	99.87	3,094.38	-22.90	131.67	-23.93	0.00	0.00	0.00
3,200.00	5.00	99.87	3,194.00	-24.39	140.26	-25.49	0.00	0.00	0.00
3,300.00	5.00	99.87	3,293.62	-25.89	148.84	-27.05	0.00	0.00	0.00
3,400.00	5.00	99.87	3,393.23	-27.38	157.43	-28.62	0.00	0.00	0.00
3,500.00	5.00	99.87	3,492.85	-28.87	166.02	-30.18	0.00	0.00	0.00
3,600.00	5.00	99.87	3,592.47	-30.37	174.61	-31.74	0.00	0.00	0.00
3,700.00	5.00	99.87	3,692.09	-31.86	183.19	-33.30	0.00	0.00	0.00
3,800.00	5.00	99.87	3,791.71	-33.35	191.78	-34.86	0.00	0.00	0.00
3,900.00	5.00	99.87	3,891.33	-34.85	200.37	-36.42	0.00	0.00	0.00
4,000.00	5.00	99.87	3,990.95	-36.34	208.95	-37.98	0.00	0.00	0.00
4,078.35	5.00	99.87	4,069.01	-37.51	215.68	-39.20	0.00	0.00	0.00
4,100.00	4.68	99.87	4,090.58	-37.82	217.48	-39.53	1.50	-1.50	0.00
4,200.00	3.18	99.87	4,190.34	-39.00	224.22	-40.76	1.50	-1.50	0.00
4,300.00	1.68	99.87	4,290.25	-39.72	228.39	-41.51	1.50	-1.50	0.00
4,400.00	0.18	99.87	4,390.23	-40.00	229.98	-41.80	1.50	-1.50	0.00
4,411.69	0.00	0.00	4,401.92	-40.00	230.00	-41.81	1.50	-1.50	0.00
4,500.00	0.00	0.00	4,490.23	-40.00	230.00	-41.81	0.00	0.00	0.00
4,600.00	0.00	0.00	4,590.23	-40.00	230.00	-41.81	0.00	0.00	0.00
4,700.00	0.00	0.00	4,690.23	-40.00	230.00	-41.81	0.00	0.00	0.00
4,800.00	0.00	0.00	4,790.23	-40.00	230.00	-41.81	0.00	0.00	0.00
4,900.00	0.00	0.00	4,890.23	-40.00	230.00	-41.81	0.00	0.00	0.00
5,000.00	0.00	0.00	4,990.23	-40.00	230.00	-41.81	0.00	0.00	0.00

Pro Directional Survey Report

Company: Malador Resources
Project: Lea County, NM
Site: Biggers Fed Com
Well: 024H
Wellbore: OH
Design: Prelim Plan A

Local Co-ordinate Reference: Well 024H
TVD Reference: RIG @ 3362.00usft (GL:3333'+KB:29')
MD Reference: RIG @ 3362.00usft (GL:3333'+KB:29')
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Database: WellPlanner1

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
5,100.00	0.00	0.00	5,090.23	-40.00	230.00	-41.81	0.00	0.00	0.00
5,200.00	0.00	0.00	5,190.23	-40.00	230.00	-41.81	0.00	0.00	0.00
5,300.00	0.00	0.00	5,290.23	-40.00	230.00	-41.81	0.00	0.00	0.00
5,400.00	0.00	0.00	5,390.23	-40.00	230.00	-41.81	0.00	0.00	0.00
5,500.00	0.00	0.00	5,490.23	-40.00	230.00	-41.81	0.00	0.00	0.00
5,600.00	0.00	0.00	5,590.23	-40.00	230.00	-41.81	0.00	0.00	0.00
5,700.00	0.00	0.00	5,690.23	-40.00	230.00	-41.81	0.00	0.00	0.00
5,800.00	0.00	0.00	5,790.23	-40.00	230.00	-41.81	0.00	0.00	0.00
5,900.00	0.00	0.00	5,890.23	-40.00	230.00	-41.81	0.00	0.00	0.00
6,000.00	0.00	0.00	5,990.23	-40.00	230.00	-41.81	0.00	0.00	0.00
6,100.00	0.00	0.00	6,090.23	-40.00	230.00	-41.81	0.00	0.00	0.00
6,200.00	0.00	0.00	6,190.23	-40.00	230.00	-41.81	0.00	0.00	0.00
6,300.00	0.00	0.00	6,290.23	-40.00	230.00	-41.81	0.00	0.00	0.00
6,400.00	0.00	0.00	6,390.23	-40.00	230.00	-41.81	0.00	0.00	0.00
6,500.00	0.00	0.00	6,490.23	-40.00	230.00	-41.81	0.00	0.00	0.00
6,600.00	0.00	0.00	6,590.23	-40.00	230.00	-41.81	0.00	0.00	0.00
6,700.00	0.00	0.00	6,690.23	-40.00	230.00	-41.81	0.00	0.00	0.00
6,800.00	0.00	0.00	6,790.23	-40.00	230.00	-41.81	0.00	0.00	0.00
6,900.00	0.00	0.00	6,890.23	-40.00	230.00	-41.81	0.00	0.00	0.00
7,000.00	0.00	0.00	6,990.23	-40.00	230.00	-41.81	0.00	0.00	0.00
7,100.00	0.00	0.00	7,090.23	-40.00	230.00	-41.81	0.00	0.00	0.00
7,200.00	0.00	0.00	7,190.23	-40.00	230.00	-41.81	0.00	0.00	0.00
7,300.00	0.00	0.00	7,290.23	-40.00	230.00	-41.81	0.00	0.00	0.00
7,400.00	0.00	0.00	7,390.23	-40.00	230.00	-41.81	0.00	0.00	0.00
7,500.00	0.00	0.00	7,490.23	-40.00	230.00	-41.81	0.00	0.00	0.00
7,600.00	0.00	0.00	7,590.23	-40.00	230.00	-41.81	0.00	0.00	0.00
7,700.00	0.00	0.00	7,690.23	-40.00	230.00	-41.81	0.00	0.00	0.00
7,800.00	0.00	0.00	7,790.23	-40.00	230.00	-41.81	0.00	0.00	0.00
7,900.00	0.00	0.00	7,890.23	-40.00	230.00	-41.81	0.00	0.00	0.00
8,000.00	0.00	0.00	7,990.23	-40.00	230.00	-41.81	0.00	0.00	0.00
8,100.00	0.00	0.00	8,090.23	-40.00	230.00	-41.81	0.00	0.00	0.00
8,200.00	0.00	0.00	8,190.23	-40.00	230.00	-41.81	0.00	0.00	0.00
8,300.00	0.00	0.00	8,290.23	-40.00	230.00	-41.81	0.00	0.00	0.00
8,400.00	0.00	0.00	8,390.23	-40.00	230.00	-41.81	0.00	0.00	0.00
8,500.00	0.00	0.00	8,490.23	-40.00	230.00	-41.81	0.00	0.00	0.00
8,600.00	0.00	0.00	8,590.23	-40.00	230.00	-41.81	0.00	0.00	0.00
8,652.77	0.00	0.00	8,643.00	-40.00	230.00	-41.81	0.00	0.00	0.00
8,700.00	4.72	359.75	8,690.18	-38.05	229.99	-39.86	10.00	10.00	0.00
8,750.00	9.72	359.75	8,739.76	-31.77	229.96	-33.57	10.00	10.00	0.00
8,800.00	14.72	359.75	8,788.62	-21.19	229.92	-22.99	10.00	10.00	0.00
8,850.00	19.72	359.75	8,836.36	-6.39	229.85	-8.19	10.00	10.00	0.00
8,900.00	24.72	359.75	8,882.63	12.52	229.77	10.71	10.00	10.00	0.00
8,950.00	29.72	359.75	8,927.08	35.38	229.67	33.58	10.00	10.00	0.00

Pro Directional Survey Report

Company: Matador Resources
Project: Lea County, NM
Site: Biggers Fed Com
Well: 024H
Wellbore: OH
Design: Prelim Plan A

Local Co-ordinate Reference: Well 024H
TVD Reference: RIG @ 3362.00usft (GL:3333'+KB:29')
MD Reference: RIG @ 3362.00usft (GL:3333'+KB:29')
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Database: WellPlanner1

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
9,000.00	34.72	359.75	8,969.36	62.03	229.55	60.23	10.00	10.00	0.00
9,050.00	39.72	359.75	9,009.16	92.27	229.42	90.47	10.00	10.00	0.00
9,100.00	44.72	359.75	9,046.18	125.86	229.28	124.06	10.00	10.00	0.00
9,150.00	49.72	359.75	9,080.13	162.55	229.12	160.74	10.00	10.00	0.00
9,200.00	54.72	359.75	9,110.75	202.06	228.94	200.25	10.00	10.00	0.00
9,250.00	59.72	359.75	9,137.81	244.08	228.76	242.28	10.00	10.00	0.00
9,300.00	64.72	359.75	9,161.10	288.31	228.57	286.50	10.00	10.00	0.00
9,350.00	69.72	359.75	9,180.45	334.39	228.37	332.59	10.00	10.00	0.00
9,400.00	74.72	359.75	9,195.71	381.99	228.16	380.18	10.00	10.00	0.00
9,452.77	80.00	359.75	9,207.25	433.46	227.93	431.66	10.00	10.00	0.00
9,477.77	80.00	359.75	9,211.59	458.08	227.83	456.28	0.00	0.00	0.00
9,500.00	81.33	359.72	9,215.20	480.02	227.73	478.21	6.00	6.00	-0.12
9,550.00	84.33	359.66	9,221.44	529.62	227.46	527.82	6.00	6.00	-0.12
9,600.00	87.33	359.60	9,225.07	579.48	227.14	577.68	6.00	6.00	-0.12
9,644.49	90.00	359.55	9,226.11	623.95	226.81	622.15	6.00	6.00	-0.12
9,700.00	90.00	359.55	9,226.10	679.46	226.38	677.66	0.00	0.00	0.00
9,800.00	90.00	359.55	9,226.10	779.46	225.60	777.66	0.00	0.00	0.00
9,900.00	90.00	359.55	9,226.10	879.45	224.82	877.66	0.00	0.00	0.00
10,000.00	90.00	359.55	9,226.10	979.45	224.04	977.66	0.00	0.00	0.00
10,100.00	90.00	359.55	9,226.09	1,079.45	223.25	1,077.66	0.00	0.00	0.00
10,200.00	90.00	359.55	9,226.09	1,179.45	222.47	1,177.66	0.00	0.00	0.00
10,300.00	90.00	359.55	9,226.09	1,279.44	221.69	1,277.66	0.00	0.00	0.00
10,400.00	90.00	359.55	9,226.09	1,379.44	220.91	1,377.66	0.00	0.00	0.00
10,500.00	90.00	359.55	9,226.08	1,479.44	220.13	1,477.66	0.00	0.00	0.00
10,600.00	90.00	359.55	9,226.08	1,579.43	219.35	1,577.66	0.00	0.00	0.00
10,700.00	90.00	359.55	9,226.08	1,679.43	218.57	1,677.66	0.00	0.00	0.00
10,800.00	90.00	359.55	9,226.08	1,779.43	217.78	1,777.66	0.00	0.00	0.00
10,900.00	90.00	359.55	9,226.07	1,879.42	217.00	1,877.66	0.00	0.00	0.00
11,000.00	90.00	359.55	9,226.07	1,979.42	216.22	1,977.66	0.00	0.00	0.00
11,100.00	90.00	359.55	9,226.07	2,079.42	215.44	2,077.66	0.00	0.00	0.00
11,200.00	90.00	359.55	9,226.07	2,179.42	214.66	2,177.66	0.00	0.00	0.00
11,300.00	90.00	359.55	9,226.06	2,279.41	213.88	2,277.66	0.00	0.00	0.00
11,400.00	90.00	359.55	9,226.06	2,379.41	213.10	2,377.66	0.00	0.00	0.00
11,500.00	90.00	359.55	9,226.06	2,479.41	212.31	2,477.66	0.00	0.00	0.00
11,600.00	90.00	359.55	9,226.06	2,579.40	211.53	2,577.66	0.00	0.00	0.00
11,700.00	90.00	359.55	9,226.06	2,679.40	210.75	2,677.66	0.00	0.00	0.00
11,800.00	90.00	359.55	9,226.05	2,779.40	209.97	2,777.66	0.00	0.00	0.00
11,900.00	90.00	359.55	9,226.05	2,879.39	209.19	2,877.66	0.00	0.00	0.00
12,000.00	90.00	359.55	9,226.05	2,979.39	208.41	2,977.66	0.00	0.00	0.00
12,100.00	90.00	359.55	9,226.05	3,079.39	207.63	3,077.66	0.00	0.00	0.00
12,200.00	90.00	359.55	9,226.04	3,179.38	206.84	3,177.66	0.00	0.00	0.00
12,300.00	90.00	359.55	9,226.04	3,279.38	206.06	3,277.66	0.00	0.00	0.00
12,400.00	90.00	359.55	9,226.04	3,379.38	205.28	3,377.66	0.00	0.00	0.00

Pro Directional Survey Report

Company: Matador Resources
Project: Lea County, NM
Site: Biggers Fed Com
Well: 024H
Wellbore: OH
Design: Prelim Plan A

Local Co-ordinate Reference: Well 024H
TVD Reference: RIG @ 3362.00usft (GL:3333'+KB:29')
MD Reference: RIG @ 3362.00usft (GL:3333'+KB:29')
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Database: WellPlanner1

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
12,500.00	90.00	359.55	9,226.04	3,479.38	204.50	3,477.66	0.00	0.00	0.00
12,600.00	90.00	359.55	9,226.03	3,579.37	203.72	3,577.66	0.00	0.00	0.00
12,700.00	90.00	359.55	9,226.03	3,679.37	202.94	3,677.66	0.00	0.00	0.00
12,800.00	90.00	359.55	9,226.03	3,779.37	202.16	3,777.66	0.00	0.00	0.00
12,900.00	90.00	359.55	9,226.03	3,879.36	201.37	3,877.66	0.00	0.00	0.00
13,000.00	90.00	359.55	9,226.02	3,979.36	200.59	3,977.66	0.00	0.00	0.00
13,100.00	90.00	359.55	9,226.02	4,079.36	199.81	4,077.66	0.00	0.00	0.00
13,200.00	90.00	359.55	9,226.02	4,179.35	199.03	4,177.66	0.00	0.00	0.00
13,300.00	90.00	359.55	9,226.02	4,279.35	198.25	4,277.66	0.00	0.00	0.00
13,400.00	90.00	359.55	9,226.01	4,379.35	197.47	4,377.66	0.00	0.00	0.00
13,500.00	90.00	359.55	9,226.01	4,479.34	196.69	4,477.66	0.00	0.00	0.00
13,600.00	90.00	359.55	9,226.01	4,579.34	195.90	4,577.66	0.00	0.00	0.00
13,700.00	90.00	359.55	9,226.01	4,679.34	195.12	4,677.66	0.00	0.00	0.00
13,800.00	90.00	359.55	9,226.00	4,779.34	194.34	4,777.66	0.00	0.00	0.00
13,900.00	90.00	359.55	9,226.00	4,879.33	193.56	4,877.66	0.00	0.00	0.00
13,971.67	90.00	359.55	9,226.00	4,951.00	193.00	4,949.33	0.00	0.00	0.00

Design Targets

Target Name	Dip Angle (°)	Dip Dir. (°)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude
- hit/miss target									
- Shape									
[BigFedCom024H]LPP	0.00	0.00	0.00	4,861.00	193.00	414,679.00	788,648.00	32° 8' 11.883 N	103° 24' 2.978 W
- plan misses target center by 4864.83usft at 0.00usft MD (0.00 TVD, 0.00 N, 0.00 E)									
- Point									
[BigFedCom024H]FPP	0.00	0.00	0.00	241.00	230.00	410,059.00	788,685.00	32° 7' 26.164 N	103° 24' 3.013 W
- plan misses target center by 333.14usft at 0.00usft MD (0.00 TVD, 0.00 N, 0.00 E)									
- Point									
[BigFedCom024H]PBHL	0.00	0.00	9,226.00	4,951.00	193.00	414,769.00	788,648.00	32° 8' 12.774 N	103° 24' 2.969 W
- plan hits target center									
- Point									

Plan Annotations

Measured Depth (usft)	Vertical Depth (usft)	Local Coordinates		Comment
		+N/-S (usft)	+E/-W (usft)	
1400	1400	0	0	Start Build 1.50
1733	1733	-2	14	Start 2345.02 hold
4078	4069	-38	216	Start Drop -1.50
4412	4402	-40	230	Start 4241.08 hold
8653	8643	-40	230	Start Build 10.00
9453	9207	433	228	Start 25.00 hold
9478	9212	458	228	Start DLS 6.00
9644	9226	624	227	EOC: 9644.49 MD
13,970	9226	4949	193	PBHL - X:788648 Y:414769
13,972	9226	4951	193	TD at 13971.67

Pro Directional Anticollision Report

Company: Matador Research
Project: Lea County
Reference Site: Biggers Fed Com
Site Error: 0.00 usft
Reference Well: 024H
Well Error: 0.00 usft
Reference Wellbore: OH
Reference Design: Prelim Plan A

Local Co-ordinate Reference: Well 024H
TVD Reference: RIG @ 3362.00usft (GL:3333'+KB:29')
MD Reference: RIG @ 3362.00usft (GL:3333'+KB:29')
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Output errors are at: 2.00 sigma
Database: WellPlanner1
Offset TVD Reference: Offset Datum

Reference	Prelim Plan A		
Filter type:	NO GLOBAL FILTER: Using user defined selection & filtering criteria		
Interpolation Method:	Stations	Error Model:	ISCWSA
Depth Range:	Unlimited	Scan Method:	Closest Approach 3D
Results Limited by:	Maximum center-center distance of 9,999.98 usft	Error Surface:	Pedal Curve
Warning Levels Evaluated at:	2.00 Sigma	Casing Method:	Not applied

Survey Tool Program Date 3/21/2017

From (usft)	To (usft)	Survey (Wellbore)	Tool Name	Description
0.00	13,971.67	Prelim Plan A (OH)	MWD - OWSG	MWD - OWSG

Summary		Reference Measured Depth (usft)	Offset Measured Depth (usft)	Distance Between Centres (usft)	Distance Between Ellipses (usft)	Separation Factor	Warning
Site Name							
Offset Well - Wellbore - Design							
Biggers Fed Com							
203H - OH - Prelim Plan A		1,400.00	1,401.00	30.02	20.44	3.134	CC, ES
203H - OH - Prelim Plan A		1,500.00	1,501.01	31.30	21.01	3.043	SF
214H - OH - Prelim Plan A		1,055.27	1,054.27	30.00	22.90	4.228	CC
214H - OH - Prelim Plan A		1,200.00	1,198.84	30.38	22.26	3.744	ES
214H - OH - Prelim Plan A		4,100.00	4,103.90	86.51	57.66	2.998	SF
217H - OH - Prelim Plan A		600.00	599.00	43.14	39.30	11.247	CC, ES
217H - OH - Prelim Plan A		900.00	896.10	51.81	45.86	8.719	SF

Offset Design Biggers Fed Com - 203H - OH - Prelim Plan A												Offset Site Error:	0.00 usft
Survey Program: 0-MWD - OWSG, 5500-MWD - OWSG, 12809-MWD - OWSG												Offset Well Error:	0.00 usft
Reference	Offset	Semi Major Axis		Distance		Minimum Separation		Separation Factor		Warning			
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	Offset Wellbore Centre +N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning
0.00	0.00	1.00	-1.00	0.00	0.00	-91.91	-1.00	-30.00	30.02				
100.00	100.00	101.00	99.00	0.13	0.13	-91.91	-1.00	-30.00	30.02	29.76	0.26	116.299	
200.00	200.00	201.00	199.00	0.49	0.49	-91.91	-1.00	-30.00	30.02	29.04	0.98	30.785	
300.00	300.00	301.00	299.00	0.84	0.85	-91.91	-1.00	-30.00	30.02	28.32	1.69	17.740	
400.00	400.00	401.00	399.00	1.20	1.21	-91.91	-1.00	-30.00	30.02	27.61	2.41	12.461	
500.00	500.00	501.00	499.00	1.56	1.56	-91.91	-1.00	-30.00	30.02	26.89	3.13	9.603	
600.00	600.00	601.00	599.00	1.92	1.92	-91.91	-1.00	-30.00	30.02	26.17	3.84	7.811	
700.00	700.00	701.00	699.00	2.28	2.28	-91.91	-1.00	-30.00	30.02	25.46	4.56	6.583	
800.00	800.00	801.00	799.00	2.64	2.64	-91.91	-1.00	-30.00	30.02	24.74	5.28	5.689	
900.00	900.00	901.00	899.00	3.00	3.00	-91.91	-1.00	-30.00	30.02	24.02	5.99	5.008	
1,000.00	1,000.00	1,001.00	999.00	3.35	3.36	-91.91	-1.00	-30.00	30.02	23.31	6.71	4.473	
1,100.00	1,100.00	1,101.00	1,099.00	3.71	3.72	-91.91	-1.00	-30.00	30.02	22.59	7.43	4.041	
1,200.00	1,200.00	1,201.00	1,199.00	4.07	4.07	-91.91	-1.00	-30.00	30.02	21.87	8.14	3.686	
1,300.00	1,300.00	1,301.00	1,299.00	4.43	4.43	-91.91	-1.00	-30.00	30.02	21.16	8.86	3.387	
1,400.00	1,400.00	1,401.00	1,399.00	4.79	4.79	-91.91	-1.00	-30.00	30.02	20.44	9.58	3.134	CC, ES
1,500.00	1,499.99	1,501.01	1,498.99	5.14	5.15	168.71	-1.00	-30.00	31.30	21.01	10.28	3.043	SF
1,600.00	1,599.91	1,601.09	1,598.91	5.48	5.51	169.95	-1.00	-30.00	35.16	24.17	10.98	3.201	
1,700.00	1,699.69	1,701.31	1,698.69	5.82	5.87	171.51	-1.00	-30.00	41.61	29.93	11.69	3.561	
1,733.33	1,732.91	1,731.91	1,731.91	5.94	5.98	172.03	-1.00	-30.00	44.35	32.44	11.91	3.723	
1,800.00	1,799.32	1,801.68	1,798.32	6.17	6.23	172.95	-1.00	-30.00	50.11	37.72	12.39	4.044	
1,900.00	1,898.94	1,902.06	1,897.94	6.53	6.59	173.99	-1.00	-30.00	58.77	45.67	13.09	4.488	

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

Pro Directional Anticollision Report

Company: Matador Resources
Project: Lea County, NM
Reference Site: Biggers Fed Com
Site Error: 0.00 usft
Reference Well: 024H
Well Error: 0.00 usft
Reference Wellbore: OH
Reference Design: Prelim Plan A

Local Co-ordinate Reference: Well 024H
TVD Reference: RIG @ 3362.00usft (GL:3333'+KB:29')
MD Reference: RIG @ 3362.00usft (GL:3333'+KB:29')
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Output errors are at: 2.00 sigma
Database: WellPlanner1
Offset TVD Reference: Offset Datum

Offset Design Biggers Fed Com - 203H - OH - Prelim Plan A													Offset Site Error: 0.00 usft
Survey Program: 0-MWD - QWSG, 5500-MWD - QWSG, 12809-MWD - QWSG													Offset Well Error: 0.00 usft
Reference		Offset		Semi Major Axis		Distance							
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	Offset Wellbore Centre +N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning
2,000.00	1,998.56	2,002.44	1,997.56	6.88	6.95	174.77	-1.00	-30.00	67.44	53.64	13.80	4.887	
2,100.00	2,098.18	2,102.82	2,097.18	7.24	7.31	175.37	-1.00	-30.00	76.12	61.62	14.51	5.247	
2,200.00	2,197.80	2,203.20	2,196.80	7.61	7.67	175.84	-1.00	-30.00	84.81	69.60	15.22	5.574	
2,300.00	2,297.42	2,303.58	2,296.42	7.97	8.03	176.23	-1.00	-30.00	93.51	77.58	15.93	5.871	
2,400.00	2,397.04	2,403.96	2,396.04	8.34	8.39	176.55	-1.00	-30.00	102.21	85.57	16.64	6.143	
2,500.00	2,496.66	2,504.34	2,495.66	8.70	8.75	176.82	-1.00	-30.00	110.91	93.56	17.35	6.392	
2,600.00	2,596.28	2,604.72	2,595.28	9.07	9.11	177.05	-1.00	-30.00	119.61	101.55	18.06	6.622	
2,700.00	2,695.90	2,705.10	2,694.90	9.44	9.47	177.25	-1.00	-30.00	128.32	109.54	18.78	6.833	
2,800.00	2,795.52	2,805.48	2,794.52	9.82	9.83	177.43	-1.00	-30.00	137.02	117.53	19.49	7.030	
2,900.00	2,895.14	2,905.86	2,894.14	10.19	10.19	177.58	-1.00	-30.00	145.73	125.52	20.21	7.212	
3,000.00	2,994.76	3,006.24	2,993.76	10.56	10.55	177.72	-1.00	-30.00	154.44	133.52	20.92	7.381	
3,100.00	3,094.38	3,106.62	3,093.38	10.94	10.91	177.84	-1.00	-30.00	163.15	141.51	21.64	7.540	
3,200.00	3,194.00	3,207.00	3,193.00	11.31	11.26	177.95	-1.00	-30.00	171.86	149.50	22.36	7.688	
3,300.00	3,293.62	3,307.38	3,292.62	11.69	11.62	178.05	-1.00	-30.00	180.57	157.50	23.07	7.826	
3,400.00	3,393.23	3,407.77	3,392.23	12.06	11.98	178.14	-1.00	-30.00	189.28	165.49	23.79	7.956	
3,500.00	3,492.85	3,508.15	3,491.85	12.44	12.34	178.22	-1.00	-30.00	197.99	173.48	24.51	8.079	
3,600.00	3,592.47	3,608.53	3,591.47	12.82	12.70	178.30	-1.00	-30.00	206.70	181.48	25.22	8.194	
3,700.00	3,692.09	3,708.91	3,691.09	13.19	13.06	178.36	-1.00	-30.00	215.41	189.47	25.94	8.303	
3,800.00	3,791.71	3,809.29	3,790.71	13.57	13.42	178.43	-1.00	-30.00	224.13	197.46	26.66	8.406	
3,900.00	3,891.33	3,909.67	3,890.33	13.95	13.78	178.49	-1.00	-30.00	232.84	205.46	27.38	8.504	
4,000.00	3,990.95	3,989.95	3,989.95	14.33	14.07	178.54	-1.00	-30.00	241.55	213.52	28.03	8.619	
4,078.35	4,069.01	4,068.01	4,068.01	14.63	14.35	178.58	-1.00	-30.00	248.38	219.79	28.59	8.688	
4,100.00	4,090.58	4,089.58	4,089.58	14.71	14.43	178.59	-1.00	-30.00	250.20	221.46	28.74	8.705	
4,200.00	4,190.34	4,189.34	4,189.34	15.08	14.79	178.63	-1.00	-30.00	257.05	227.59	29.46	8.726	
4,300.00	4,290.25	4,289.25	4,289.25	15.44	15.14	178.66	-1.00	-30.00	261.28	231.10	30.17	8.659	
4,400.00	4,390.23	4,389.23	4,389.23	15.79	15.50	178.66	-1.00	-30.00	262.89	232.01	30.89	8.512	
4,411.69	4,401.92	4,400.92	4,400.92	15.83	15.54	-81.47	-1.00	-30.00	262.91	231.94	30.97	8.490	
4,500.00	4,490.23	4,489.23	4,489.23	16.13	15.86	-81.47	-1.00	-30.00	262.91	231.32	31.59	8.322	
4,600.00	4,590.23	4,589.23	4,589.23	16.47	16.22	-81.47	-1.00	-30.00	262.91	230.61	32.30	8.141	
4,700.00	4,690.23	4,689.23	4,689.23	16.81	16.58	-81.47	-1.00	-30.00	262.91	229.91	33.00	7.967	
4,800.00	4,790.23	4,789.23	4,789.23	17.16	16.94	-81.47	-1.00	-30.00	262.91	229.20	33.71	7.800	
4,900.00	4,890.23	4,889.23	4,889.23	17.50	17.30	-81.47	-1.00	-30.00	262.91	228.50	34.41	7.640	
5,000.00	4,990.23	4,989.23	4,989.23	17.84	17.65	-81.47	-1.00	-30.00	262.91	227.79	35.12	7.486	
5,100.00	5,090.23	5,089.23	5,089.23	18.19	18.01	-81.47	-1.00	-30.00	262.91	227.08	35.83	7.338	
5,200.00	5,190.23	5,189.23	5,189.23	18.53	18.37	-81.47	-1.00	-30.00	262.91	226.37	36.53	7.196	
5,300.00	5,290.23	5,289.23	5,289.23	18.87	18.73	-81.47	-1.00	-30.00	262.91	225.67	37.24	7.059	
5,400.00	5,390.23	5,389.23	5,389.23	19.22	19.09	-81.47	-1.00	-30.00	262.91	224.96	37.95	6.928	
5,500.00	5,490.23	5,489.23	5,489.23	19.57	19.29	-81.47	-1.00	-30.00	262.91	224.41	38.50	6.829	
5,600.00	5,590.23	5,589.23	5,589.23	19.91	19.31	-81.47	-1.00	-30.00	262.91	224.03	38.88	6.763	
5,700.00	5,690.23	5,689.23	5,689.23	20.26	19.32	-81.47	-1.00	-30.00	262.91	223.67	39.24	6.700	
5,800.00	5,790.23	5,789.23	5,789.23	20.60	19.34	-81.47	-1.00	-30.00	262.91	223.30	39.61	6.637	
5,900.00	5,890.23	5,889.23	5,889.23	20.95	19.37	-81.47	-1.00	-30.00	262.91	222.92	39.99	6.575	
6,000.00	5,990.23	5,989.23	5,989.23	21.30	19.40	-81.47	-1.00	-30.00	262.91	222.54	40.37	6.512	
6,100.00	6,090.23	6,089.23	6,089.23	21.65	19.44	-81.47	-1.00	-30.00	262.91	222.15	40.76	6.450	
6,200.00	6,190.23	6,189.23	6,189.23	22.00	19.49	-81.47	-1.00	-30.00	262.91	221.75	41.16	6.388	
6,300.00	6,290.23	6,289.23	6,289.23	22.35	19.54	-81.47	-1.00	-30.00	262.91	221.35	41.56	6.325	
6,400.00	6,390.23	6,389.23	6,389.23	22.69	19.60	-81.47	-1.00	-30.00	262.91	220.93	41.97	6.264	
6,500.00	6,490.23	6,489.23	6,489.23	23.04	19.66	-81.47	-1.00	-30.00	262.91	220.52	42.39	6.202	
6,600.00	6,590.23	6,589.23	6,589.23	23.39	19.73	-81.47	-1.00	-30.00	262.91	220.09	42.82	6.141	
6,700.00	6,690.23	6,689.23	6,689.23	23.74	19.81	-81.47	-1.00	-30.00	262.91	219.65	43.25	6.079	
6,800.00	6,790.23	6,789.23	6,789.23	24.09	19.89	-81.47	-1.00	-30.00	262.91	219.23	43.68	6.019	
6,900.00	6,890.23	6,889.23	6,889.23	24.44	19.98	-81.47	-1.00	-30.00	262.91	218.78	44.12	5.958	

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

Pro Directional Anticollision Report

Company: Matador Resources
Project: Lea County, NM
Reference Site: Biggers Fed Com
Site Error: 0.00 usft
Reference Well: 024H
Well Error: 0.00 usft
Reference Wellbore: OH
Reference Design: Prelim Plan A

Local Co-ordinate Reference: Well 024H
TVD Reference: RIG @ 3362.00usft (GL:3333'+KB:29')
MD Reference: RIG @ 3362.00usft (GL:3333'+KB:29')
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Output errors are at: 2.00 sigma
Database: WellPlanner1
Offset TVD Reference: Offset Datum

Offset Design Biggers Fed Com - 203H - OH - Prelim Plan A													Offset Site Error:	0.00 usft
Survey Program: 0-MWD - OWSG, 5500-MWD - OWSG, 12808-MWD - OWSG													Offset Well Error:	0.00 usft
Reference		Offset		Semi Major Axis			Distance							Warning
Measured Depth	Vertical Depth	Measured Depth	Vertical Depth	Reference	Offset	Highside Toolface	Offset Wellbore Centre		Between Centres	Between Ellipses	Minimum Separation	Separation Factor		
(usft)	(usft)	(usft)	(usft)	(usft)	(usft)	(°)	+N/-S (usft)	+E/-W (usft)	(usft)	(usft)	(usft)			
7,000.00	6,990.23	6,989.23	6,989.23	24.79	20.08	-81.47	-1.00	-30.00	262.91	218.34	44.57	5.898		
7,100.00	7,090.23	7,089.23	7,089.23	25.14	20.18	-81.47	-1.00	-30.00	262.91	217.88	45.03	5.839		
7,200.00	7,190.23	7,189.23	7,189.23	25.50	20.29	-81.47	-1.00	-30.00	262.91	217.42	45.49	5.780		
7,300.00	7,290.23	7,283.82	7,283.82	25.85	20.39	-81.54	-1.20	-30.90	263.82	217.90	45.93	5.745		
7,400.00	7,390.23	7,377.66	7,377.60	26.20	20.50	-81.78	-1.88	-34.04	267.03	220.68	46.34	5.762		
7,500.00	7,490.23	7,471.29	7,471.06	26.55	20.61	-82.19	-3.05	-39.41	272.54	225.79	46.75	5.830		
7,600.00	7,590.23	7,566.75	7,566.20	26.90	20.72	-82.74	-4.71	-47.05	280.24	233.07	47.17	5.941		
7,700.00	7,690.23	7,666.37	7,665.44	27.25	20.85	-83.32	-6.55	-55.53	288.47	240.82	47.65	6.054		
7,800.00	7,790.23	7,765.99	7,764.68	27.61	20.99	-83.86	-8.40	-64.02	296.73	248.60	48.13	6.165		
7,900.00	7,890.23	7,865.61	7,863.92	27.96	21.13	-84.38	-10.24	-72.50	305.01	256.39	48.62	6.273		
8,000.00	7,990.23	7,965.23	7,963.16	28.31	21.28	-84.87	-12.08	-80.99	313.32	264.20	49.12	6.379		
8,100.00	8,090.23	8,064.85	8,062.40	28.66	21.43	-85.33	-13.93	-89.47	321.65	272.03	49.62	6.482		
8,200.00	8,190.23	8,164.47	8,161.64	29.02	21.59	-85.78	-15.77	-97.95	330.00	279.87	50.13	6.583		
8,300.00	8,290.23	8,264.09	8,260.88	29.37	21.75	-86.19	-17.62	-106.44	338.37	287.73	50.64	6.681		
8,400.00	8,390.23	8,371.71	8,368.18	29.72	21.94	-86.57	-19.38	-114.53	345.79	294.54	51.25	6.747		
8,500.00	8,490.23	8,481.21	8,477.54	30.08	22.13	-86.81	-20.51	-119.77	350.50	298.65	51.85	6.780		
8,600.00	8,590.23	8,590.92	8,587.23	30.43	22.32	-86.91	-20.99	-121.94	352.45	300.02	52.43	6.722		
8,652.77	8,643.00	8,645.69	8,642.00	30.62	22.41	-86.91	-21.00	-122.00	352.51	299.79	52.72	6.686		
8,700.00	8,690.18	8,707.14	8,689.18	30.78	22.52	-86.99	-21.00	-122.00	352.40	299.41	53.00	6.649		
8,750.00	8,739.76	8,742.45	8,738.76	30.95	22.59	-88.03	-21.00	-122.00	352.13	298.89	53.24	6.614		
8,800.00	8,788.62	8,808.70	8,787.62	31.12	22.71	-89.73	-21.00	-122.00	351.92	298.39	53.53	6.574		
8,806.63	8,795.02	8,802.29	8,794.02	31.15	22.70	-90.00	-21.00	-122.00	351.91	298.37	53.54	6.573		
8,850.00	8,836.36	8,839.05	8,835.36	31.29	22.77	-92.00	-21.00	-122.00	352.16	298.40	53.76	6.551		
8,900.00	8,882.63	8,885.32	8,881.63	31.44	22.85	-94.72	-21.00	-122.00	353.36	299.36	54.01	6.543		
8,950.00	8,927.08	8,929.76	8,926.08	31.59	22.94	-97.71	-21.00	-122.00	356.16	301.91	54.25	6.565		
9,000.00	8,969.36	8,972.05	8,968.36	31.72	23.02	-100.78	-21.00	-122.00	361.23	306.74	54.49	6.629		
9,050.00	9,009.16	9,011.85	9,008.16	31.85	23.10	-103.72	-21.00	-122.00	369.23	314.51	54.72	6.747		
9,100.00	9,046.18	9,048.87	9,045.18	31.96	23.17	-106.35	-21.00	-122.00	380.74	325.80	54.94	6.930		
9,150.00	9,080.13	9,082.81	9,079.13	32.08	23.23	-108.49	-21.00	-122.00	396.20	341.06	55.14	7.185		
9,200.00	9,110.75	9,113.43	9,109.75	32.22	23.29	-109.98	-21.00	-122.00	415.83	360.51	55.32	7.517		
9,250.00	9,137.81	9,140.49	9,136.81	32.37	23.35	-110.69	-21.00	-122.00	439.66	384.18	55.48	7.925		
9,300.00	9,161.10	9,163.79	9,160.10	32.54	23.40	-110.48	-21.00	-122.00	467.51	411.90	55.61	8.406		
9,350.00	9,180.45	9,183.14	9,179.45	32.72	23.43	-109.21	-21.00	-122.00	499.06	443.34	55.72	8.957		
9,400.00	9,195.71	9,201.60	9,194.71	32.91	23.47	-106.73	-21.00	-122.00	533.86	478.06	55.81	9.566		
9,452.77	9,207.25	9,209.94	9,206.25	33.11	23.49	-102.60	-21.00	-122.00	573.57	517.72	55.86	10.268		
9,477.77	9,211.59	9,214.28	9,210.59	33.22	23.50	-103.26	-21.00	-122.00	593.21	537.33	55.88	10.616		
9,500.00	9,215.20	9,217.89	9,214.20	33.31	23.50	-102.06	-21.00	-122.00	611.00	555.11	55.90	10.931		
9,550.00	9,221.44	9,224.12	9,220.44	33.53	23.52	-98.73	-21.00	-122.00	652.15	596.23	55.92	11.661		
9,600.00	9,225.07	9,227.76	9,224.07	33.76	23.52	-94.50	-21.00	-122.00	694.60	638.66	55.94	12.417		
9,644.49	9,226.11	9,228.79	9,225.11	33.97	23.53	-90.00	-21.00	-122.00	733.24	677.29	55.95	13.106		
9,700.00	9,226.10	9,228.79	9,225.10	34.25	23.53	-90.00	-21.00	-122.00	782.31	726.36	55.95	13.982		
9,800.00	9,226.10	9,228.79	9,225.10	34.82	23.53	-90.00	-21.00	-122.00	872.67	816.72	55.96	15.595		
9,900.00	9,226.10	9,228.79	9,225.10	35.45	23.53	-90.00	-21.00	-122.00	964.94	908.97	55.97	17.242		
10,000.00	9,226.10	9,228.78	9,225.10	36.14	23.53	-90.00	-21.00	-122.00	1,058.61	1,002.63	55.98	18.912		
10,100.00	9,226.09	9,228.78	9,225.09	36.90	23.53	-90.00	-21.00	-122.00	1,153.34	1,097.35	55.99	20.600		
10,200.00	9,226.09	9,228.78	9,225.09	37.71	23.53	-90.00	-21.00	-122.00	1,248.89	1,192.89	56.00	22.302		
10,300.00	9,226.09	9,228.78	9,225.09	38.58	23.53	-89.99	-21.00	-122.00	1,345.09	1,289.08	56.01	24.015		
10,400.00	9,226.09	9,228.77	9,225.09	39.48	23.53	-89.99	-21.00	-122.00	1,441.81	1,385.79	56.03	25.735		
10,500.00	9,226.08	9,228.77	9,225.08	40.46	23.53	-89.99	-21.00	-122.00	1,538.95	1,482.91	56.04	27.461		
10,600.00	9,226.08	9,228.77	9,225.08	41.47	23.53	-89.99	-21.00	-122.00	1,636.43	1,580.37	56.06	29.192		
10,700.00	9,226.08	9,228.77	9,225.08	42.52	23.53	-89.99	-21.00	-122.00	1,734.20	1,678.13	56.07	30.927		
10,800.00	9,226.08	9,228.76	9,225.08	43.60	23.53	-89.99	-21.00	-122.00	1,832.21	1,776.12	56.09	32.664		

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

Pro Directional Anticollision Report

Company: Matador Resources
Project: Lea County, NM
Reference Site: Biggers Fed Com
Site Error: 0.00 usft
Reference Well: 024H
Well Error: 0.00 usft
Reference Wellbore: OH
Reference Design: Prelim Plan A

Local Co-ordinate Reference: Well 024H
TVD Reference: RIG @ 3362.00usft (GL:3333'+KB:29')
MD Reference: RIG @ 3362.00usft (GL:3333'+KB:29')
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Output errors are at: 2.00 sigma
Database: WellPlanner1
Offset TVD Reference: Offset Datum

Offset Design Biggers Fed Com - 203H - OH - Prelim Plan A												Offset Site Error:	0.00 usft
Survey Program: 0-MWD - OWSG, 5500-MWD - OWSG, 12808-MWD - OWSG												Offset Well Error:	0.00 usft
Reference		Offset		Semi Major Axis			Distance						
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	Offset Wellbore Centre +N-S (usft)	+E-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning
10,900.00	9,226.07	9,228.76	9,225.07	44.73	23.53	-89.99	-21.00	-122.00	1,930.42	1,874.31	56.11	34.403	
11,000.00	9,226.07	9,228.76	9,225.07	45.88	23.53	-89.99	-21.00	-122.00	2,028.81	1,972.68	56.13	36.143	
11,100.00	9,226.07	9,228.76	9,225.07	47.06	23.53	-89.99	-21.00	-122.00	2,127.35	2,071.20	56.15	37.884	
11,200.00	9,226.07	9,228.75	9,225.07	48.28	23.53	-89.99	-21.00	-122.00	2,226.02	2,169.84	56.18	39.625	
11,300.00	9,226.06	9,228.75	9,225.06	49.52	23.53	-89.99	-21.00	-122.00	2,324.80	2,268.60	56.20	41.366	
11,400.00	9,226.06	9,228.75	9,225.06	50.78	23.53	-89.99	-21.00	-122.00	2,423.69	2,367.46	56.23	43.107	
11,500.00	9,226.06	9,228.75	9,225.06	52.06	23.53	-89.99	-21.00	-122.00	2,522.66	2,466.41	56.25	44.847	
11,600.00	9,226.06	9,228.74	9,225.06	53.37	23.53	-89.99	-21.00	-122.00	2,621.71	2,565.43	56.28	46.586	
11,700.00	9,226.06	9,228.74	9,225.06	54.69	23.53	-89.99	-21.00	-122.00	2,720.82	2,664.52	56.30	48.323	
11,800.00	9,226.05	9,228.74	9,225.05	56.03	23.53	-89.99	-21.00	-122.00	2,820.00	2,763.67	56.33	50.059	
11,900.00	9,226.05	9,228.74	9,225.05	57.39	23.53	-89.99	-21.00	-122.00	2,919.24	2,862.88	56.36	51.794	
12,000.00	9,226.05	9,228.74	9,225.05	58.77	23.53	-89.99	-21.00	-122.00	3,018.53	2,962.14	56.39	53.527	
12,100.00	9,226.05	9,228.73	9,225.05	60.15	23.53	-89.99	-21.00	-122.00	3,117.86	3,061.44	56.42	55.257	
12,200.00	9,226.04	9,228.73	9,225.04	61.56	23.53	-89.99	-21.00	-122.00	3,217.23	3,160.78	56.46	56.986	
12,300.00	9,226.04	9,228.73	9,225.04	62.97	23.53	-89.99	-21.00	-122.00	3,316.65	3,260.16	56.49	58.712	
12,400.00	9,226.04	15,733.95	12,588.04	64.40	63.05	-173.98	3,376.39	-149.40	3,381.65	3,314.32	67.33	50.224	
12,500.00	9,226.04	15,833.95	12,588.04	65.83	64.48	-173.98	3,476.39	-150.26	3,381.66	3,313.12	68.54	49.336	
12,600.00	9,226.03	15,933.95	12,588.03	67.28	65.92	-173.98	3,576.39	-151.13	3,381.67	3,311.90	69.77	48.469	
12,700.00	9,226.03	16,033.95	12,588.03	68.74	67.38	-173.98	3,676.38	-151.99	3,381.68	3,310.67	71.01	47.622	
12,800.00	9,226.03	16,133.95	12,588.03	70.20	68.84	-173.97	3,776.38	-152.86	3,381.69	3,309.42	72.26	46.796	
12,900.00	9,226.03	16,233.95	12,588.03	71.68	70.31	-173.97	3,876.37	-153.72	3,381.70	3,308.16	73.53	45.989	
13,000.00	9,226.02	16,333.95	12,588.02	73.16	71.79	-173.97	3,976.37	-154.59	3,381.71	3,306.89	74.81	45.203	
13,100.00	9,226.02	16,433.95	12,588.02	74.65	73.28	-173.97	4,076.37	-155.45	3,381.71	3,305.61	76.10	44.436	
13,200.00	9,226.02	16,533.95	12,588.02	76.14	74.78	-173.97	4,176.36	-156.32	3,381.72	3,304.32	77.41	43.688	
13,300.00	9,226.02	16,633.95	12,588.02	77.65	76.28	-173.97	4,276.36	-157.18	3,381.73	3,303.01	78.72	42.959	
13,400.00	9,226.01	16,733.95	12,588.01	79.16	77.79	-173.97	4,376.36	-158.05	3,381.74	3,301.70	80.04	42.248	
13,500.00	9,226.01	16,833.95	12,588.01	80.67	79.30	-173.96	4,476.35	-158.91	3,381.75	3,300.37	81.38	41.556	
13,600.00	9,226.01	16,933.95	12,588.01	82.19	80.82	-173.96	4,576.35	-159.78	3,381.76	3,299.04	82.72	40.882	
13,700.00	9,226.01	17,033.95	12,588.01	83.72	82.35	-173.96	4,676.34	-160.64	3,381.77	3,297.70	84.07	40.225	
13,800.00	9,226.00	17,133.95	12,588.00	85.25	83.88	-173.96	4,776.34	-161.51	3,381.78	3,296.34	85.43	39.584	
13,900.00	9,226.00	17,233.95	12,588.00	86.78	85.41	-173.96	4,876.34	-162.37	3,381.78	3,294.98	86.80	38.981	
13,971.67	9,226.00	17,305.62	12,588.00	87.89	86.52	-173.96	4,948.00	-162.99	3,381.79	3,294.01	87.78	38.524	

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

Pro Directional Anticollision Report

Company: Matador Resources
Project: Lea County, NM
Reference Site: Biggers Fed Com
Site Error: 0.00 usft
Reference Well: 024H
Well Error: 0.00 usft
Reference Wellbore: OH
Reference Design: Prelim Plan A

Local Co-ordinate Reference: Well 024H
TVD Reference: RIG @ 3362.00usft (GL:3333'+KB:29')
MD Reference: RIG @ 3362.00usft (GL:3333'+KB:29')
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Output errors are at: 2.00 sigma
Database: WellPlanner1
Offset TVD Reference: Offset Datum

Offset Design Biggers Fed Com - 214H - OH - Prelim Plan A														Offset Site Error: 0.00 usft
Survey Program: 0-MWD - OWSG, 5500-MWD - OWSG, 12981-MWD - OWSG														Offset Well Error: 0.00 usft
Reference		Offset		Semi Major Axis		Distance		Offset Wellbore Centre		Between Centres		Between Ellipses		Warning
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)		+N/-S (usft)	+E/-W (usft)	usft	usft	usft	usft	
0.00	0.00	1.00	-1.00	0.00	0.00	180.00		-30.00	0.00	30.00				
100.00	100.00	101.00	99.00	0.13	0.13	180.00		-30.00	0.00	30.00	29.74	0.26	116.234	
200.00	200.00	201.00	199.00	0.49	0.49	180.00		-30.00	0.00	30.00	29.02	0.98	30.768	
300.00	300.00	301.00	299.00	0.84	0.85	180.00		-30.00	0.00	30.00	28.31	1.69	17.731	
400.00	400.00	401.00	399.00	1.20	1.21	180.00		-30.00	0.00	30.00	27.59	2.41	12.454	
500.00	500.00	501.00	499.00	1.56	1.56	180.00		-30.00	0.00	30.00	26.87	3.13	9.597	
600.00	600.00	601.00	599.00	1.92	1.92	180.00		-30.00	0.00	30.00	26.16	3.84	7.807	
700.00	700.00	701.00	699.00	2.28	2.28	180.00		-30.00	0.00	30.00	25.44	4.56	6.579	
800.00	800.00	801.00	799.00	2.64	2.64	180.00		-30.00	0.00	30.00	24.72	5.28	5.685	
900.00	900.00	901.00	899.00	3.00	3.00	180.00		-30.00	0.00	30.00	24.01	5.99	5.005	
1,000.00	1,000.00	999.00	999.00	3.35	3.35	180.00		-30.00	0.00	30.00	23.30	6.70	4.475	
1,055.27	1,055.27	1,054.27	1,054.27	3.55	3.54	179.26		-30.00	0.39	30.00	22.90	7.10	4.228 CC	
1,100.00	1,100.00	1,098.99	1,098.98	3.71	3.70	177.55		-29.98	1.28	30.01	22.60	7.41	4.049	
1,200.00	1,200.00	1,198.84	1,198.75	4.07	4.04	170.19		-29.93	5.17	30.38	22.26	8.11	3.744 ES	
1,300.00	1,300.00	1,298.42	1,298.12	4.43	4.39	158.68		-29.85	11.65	32.06	23.24	8.82	3.635	
1,400.00	1,400.00	1,402.41	1,396.87	4.79	4.76	145.19		-29.73	20.67	36.28	26.74	9.53	3.805	
1,500.00	1,499.99	1,502.84	1,495.90	5.14	5.13	34.68		-29.60	31.08	41.95	31.72	10.23	4.101	
1,600.00	1,599.91	1,603.06	1,595.13	5.48	5.49	28.22		-29.47	41.51	46.39	35.47	10.92	4.249	
1,700.00	1,699.69	1,703.16	1,694.49	5.82	5.87	24.14		-29.33	51.95	48.91	37.29	11.61	4.212	
1,733.33	1,732.91	1,730.17	1,727.63	5.94	5.97	23.14		-29.29	55.43	49.26	37.44	11.82	4.157	
1,800.00	1,799.32	1,803.19	1,793.91	6.17	6.24	21.31		-29.20	62.40	49.74	37.43	12.31	4.041	
1,900.00	1,898.94	1,903.22	1,893.33	6.53	6.62	18.63		-29.06	72.85	50.56	37.55	13.01	3.885	
2,000.00	1,998.56	2,003.25	1,992.75	6.88	6.99	16.05		-28.93	83.30	51.48	37.77	13.72	3.753	
2,100.00	2,098.18	2,103.28	2,092.17	7.24	7.37	13.56		-28.80	93.74	52.51	38.09	14.42	3.641	
2,200.00	2,197.80	2,203.31	2,191.59	7.61	7.76	11.17		-28.66	104.19	53.63	38.50	15.13	3.545	
2,300.00	2,297.42	2,303.34	2,291.01	7.97	8.14	8.88		-28.53	114.64	54.84	39.00	15.84	3.463	
2,400.00	2,397.04	2,403.37	2,390.44	8.34	8.52	6.69		-28.39	125.09	56.13	39.58	16.55	3.392	
2,500.00	2,496.66	2,503.40	2,489.86	8.70	8.91	4.61		-28.26	135.54	57.50	40.24	17.26	3.332	
2,600.00	2,596.28	2,603.43	2,589.28	9.07	9.29	2.62		-28.12	145.99	58.95	40.98	17.97	3.280	
2,700.00	2,695.90	2,703.47	2,688.70	9.44	9.68	0.73		-27.99	156.44	60.46	41.77	18.68	3.236	
2,800.00	2,795.52	2,803.50	2,788.12	9.82	10.07	-1.06		-27.85	166.89	62.03	42.63	19.40	3.197	
2,900.00	2,895.14	2,903.53	2,887.54	10.19	10.46	-2.77		-27.72	177.33	63.66	43.54	20.12	3.164	
3,000.00	2,994.76	3,003.56	2,986.97	10.56	10.85	-4.39		-27.59	187.78	65.35	44.51	20.84	3.136	
3,100.00	3,094.38	3,103.59	3,086.39	10.94	11.23	-5.92		-27.45	198.23	67.08	45.52	21.56	3.112	
3,200.00	3,194.00	3,203.62	3,185.81	11.31	11.62	-7.38		-27.32	208.68	68.86	46.58	22.28	3.090	
3,300.00	3,293.62	3,303.65	3,285.23	11.69	12.01	-8.76		-27.18	219.13	70.68	47.68	23.01	3.072	
3,400.00	3,393.23	3,403.68	3,384.65	12.06	12.40	-10.07		-27.05	229.58	72.54	48.81	23.73	3.057	
3,500.00	3,492.85	3,503.71	3,484.07	12.44	12.79	-11.32		-26.91	240.03	74.44	49.98	24.46	3.044	
3,600.00	3,592.47	3,603.74	3,583.50	12.82	13.18	-12.50		-26.78	250.48	76.37	51.19	25.19	3.032	
3,700.00	3,692.09	3,703.77	3,682.92	13.19	13.58	-13.63		-26.65	260.92	78.34	52.42	25.92	3.022	
3,800.00	3,791.71	3,803.80	3,782.34	13.57	13.97	-14.70		-26.51	271.37	80.33	53.68	26.65	3.014	
3,900.00	3,891.33	3,903.84	3,881.76	13.95	14.36	-15.72		-26.38	281.82	82.34	54.96	27.38	3.007	
4,000.00	3,990.95	4,003.87	3,981.18	14.33	14.75	-16.69		-26.24	292.27	84.39	56.27	28.12	3.001	
4,078.35	4,069.01	4,074.46	4,059.08	14.63	15.03	-17.41		-26.14	300.46	86.00	57.34	28.66	3.000	
4,100.00	4,090.58	4,103.90	4,080.60	14.71	15.14	-17.60		-26.11	302.72	86.51	57.66	28.85	2.998 SF	
4,200.00	4,190.34	4,203.98	4,179.97	15.08	15.53	-18.12		-25.97	313.16	90.37	60.79	29.58	3.055	
4,300.00	4,290.25	4,304.18	4,279.22	15.44	15.93	-18.11		-25.84	323.59	96.73	66.42	30.31	3.192	
4,400.00	4,390.23	4,404.58	4,378.28	15.79	16.32	-17.68		-25.71	334.00	105.57	74.54	31.02	3.403	
4,411.69	4,401.92	4,407.04	4,389.84	15.83	16.33	-82.26		-25.69	335.22	106.76	75.69	31.07	3.436	
4,500.00	4,490.23	4,505.13	4,477.19	16.13	16.72	82.81		-25.57	344.40	115.93	84.20	31.73	3.654	
4,600.00	4,590.23	4,605.67	4,576.10	16.47	17.11	83.35		-25.44	354.79	126.32	93.89	32.44	3.895	
4,700.00	4,690.23	4,693.78	4,675.00	16.81	17.46	83.80		-25.31	365.19	136.73	103.63	33.10	4.131	

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

Pro Directional Anticollision Report

Company: Matador Resources
Project: Lea County, NM
Reference Site: Biggers Fed Com
Site Error: 0.00 usft
Reference Well: 024H
Well Error: 0.00 usft
Reference Wellbore: OH
Reference Design: Prelim Plan A

Local Co-ordinate Reference: Well 024H
TVD Reference: RIG @ 3362.00usft (GL:3333'+KB:29')
MD Reference: RIG @ 3362.00usft (GL:3333'+KB:29')
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Output errors are at: 2.00 sigma
Database: WellPlanner1
Offset TVD Reference: Offset Datum

Offset Design Biggers Fed Com - 214H - OH - Prelim Plan A													Offset Site Error: 0.00 usft
Survey Program: 0-MWD - OWSG, 5500-MWD - OWSG, 12981-MWD - OWSG													Offset Well Error: 0.00 usft
Reference		Offset		Semi Major Axis		Distance							
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	Offset Wellbore Centre +N-S (usft)	+E-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning
4,800.00	4,790.23	4,793.23	4,773.91	17.16	17.85	84.18	-25.17	375.58	147.14	113.33	33.80	4.353	
4,900.00	4,890.23	4,892.68	4,872.82	17.50	18.24	84.52	-25.04	385.98	157.55	123.04	34.51	4.565	
5,000.00	4,990.23	5,007.87	4,971.73	17.84	18.69	84.82	-24.91	396.37	167.97	132.70	35.27	4.762	
5,100.00	5,090.23	5,108.41	5,070.63	18.19	19.08	85.08	-24.77	406.77	178.39	142.41	35.99	4.957	
5,200.00	5,190.23	5,191.04	5,169.54	18.53	19.41	85.31	-24.64	417.16	188.82	152.19	36.63	5.154	
5,300.00	5,290.23	5,309.51	5,268.45	18.87	19.88	85.52	-24.50	427.56	199.25	161.84	37.41	5.326	
5,400.00	5,390.23	5,389.94	5,367.35	19.22	20.19	85.70	-24.37	437.95	209.68	171.63	38.05	5.510	
5,500.00	5,490.23	5,489.40	5,466.26	19.57	20.43	85.87	-24.24	448.35	220.12	181.52	38.60	5.703	
5,600.00	5,590.23	5,588.85	5,565.17	19.91	20.50	86.02	-24.10	458.74	230.55	191.58	38.97	5.916	
5,700.00	5,690.23	5,688.30	5,664.08	20.26	20.56	86.17	-23.97	469.14	240.99	201.66	39.33	6.127	
5,800.00	5,790.23	5,787.75	5,762.98	20.60	20.63	86.29	-23.84	479.53	251.43	211.73	39.70	6.333	
5,900.00	5,890.23	5,887.20	5,861.89	20.95	20.71	86.41	-23.70	489.92	261.87	221.79	40.08	6.534	
6,000.00	5,990.23	5,986.66	5,960.80	21.30	20.79	86.52	-23.57	500.32	272.31	231.85	40.46	6.730	
6,100.00	6,090.23	6,086.11	6,059.71	21.65	20.88	86.62	-23.44	510.71	282.75	241.90	40.85	6.922	
6,200.00	6,190.23	6,185.56	6,158.61	22.00	20.98	86.72	-23.30	521.11	293.19	251.95	41.24	7.109	
6,300.00	6,290.23	6,285.01	6,257.52	22.35	21.08	86.80	-23.17	531.50	303.63	261.99	41.65	7.291	
6,400.00	6,390.23	6,384.46	6,356.43	22.69	21.19	86.89	-23.03	541.90	314.08	272.02	42.06	7.468	
6,500.00	6,490.23	6,483.92	6,455.34	23.04	21.31	86.96	-22.90	552.29	324.52	282.05	42.47	7.640	
6,600.00	6,590.23	6,583.37	6,554.24	23.39	21.44	87.03	-22.77	562.69	334.97	292.07	42.90	7.808	
6,700.00	6,690.23	6,682.82	6,653.15	23.74	21.57	87.10	-22.63	573.08	345.41	302.08	43.33	7.972	
6,800.00	6,790.23	6,782.27	6,752.06	24.09	21.70	87.17	-22.50	583.48	355.86	312.09	43.77	8.131	
6,900.00	6,890.23	6,881.73	6,850.97	24.44	21.85	87.23	-22.37	593.87	366.30	322.09	44.21	8.286	
7,000.00	6,990.23	6,981.18	6,949.87	24.79	22.00	87.28	-22.23	604.27	376.75	332.09	44.66	8.436	
7,100.00	7,090.23	7,080.63	7,048.78	25.14	22.15	87.34	-22.10	614.66	387.20	342.08	45.11	8.583	
7,200.00	7,190.23	7,180.08	7,147.69	25.50	22.31	87.39	-21.97	625.06	397.64	352.07	45.58	8.725	
7,300.00	7,290.23	7,279.53	7,246.60	25.85	22.48	87.43	-21.83	635.45	408.09	362.05	46.04	8.863	
7,400.00	7,390.23	7,378.99	7,345.50	26.20	22.65	87.48	-21.70	645.85	418.54	372.02	46.52	8.997	
7,500.00	7,490.23	7,478.44	7,444.41	26.55	22.83	87.52	-21.57	656.24	428.99	381.99	47.00	9.128	
7,600.00	7,590.23	7,577.89	7,543.32	26.90	23.01	87.56	-21.43	666.64	439.44	391.95	47.48	9.254	
7,700.00	7,690.23	7,677.34	7,642.22	27.25	23.20	87.60	-21.30	677.03	449.88	401.91	47.97	9.377	
7,800.00	7,790.23	7,776.80	7,741.13	27.61	23.39	87.64	-21.16	687.42	460.33	411.86	48.47	9.497	
7,900.00	7,890.23	7,876.25	7,840.04	27.96	23.59	87.68	-21.03	697.82	470.78	421.81	48.97	9.613	
8,000.00	7,990.23	7,975.70	7,938.95	28.31	23.79	87.71	-20.90	708.21	481.23	431.75	49.48	9.726	
8,100.00	8,090.23	8,075.15	8,037.85	28.66	24.00	87.75	-20.76	718.61	491.68	441.69	49.99	9.835	
8,200.00	8,190.23	8,174.60	8,136.76	29.02	24.22	87.78	-20.63	729.00	502.13	451.62	50.51	9.941	
8,300.00	8,290.23	8,274.06	8,235.67	29.37	24.43	87.81	-20.50	739.40	512.58	461.54	51.03	10.044	
8,400.00	8,390.23	8,373.51	8,334.58	29.72	24.65	87.84	-20.36	749.79	523.03	471.47	51.56	10.144	
8,500.00	8,490.23	8,477.79	8,438.30	30.08	24.89	87.87	-20.22	760.54	533.34	481.22	52.12	10.233	
8,600.00	8,590.23	8,573.78	8,533.92	30.43	25.14	87.89	-20.10	769.86	541.38	488.66	52.72	10.269	
8,652.77	8,643.00	8,655.19	8,615.22	30.62	25.26	87.90	-20.06	773.37	544.40	491.37	53.03	10.266	
8,700.00	8,690.18	8,710.18	8,670.16	30.78	25.37	88.20	-20.03	775.68	546.32	493.03	53.29	10.252	
8,750.00	8,739.76	8,768.03	8,727.99	30.95	25.47	88.84	-20.01	777.26	547.53	493.97	53.56	10.223	
8,800.00	8,788.62	8,825.06	8,785.01	31.12	25.57	90.05	-20.00	777.96	548.05	494.24	53.81	10.185	
8,850.00	8,836.36	8,875.40	8,835.36	31.29	25.66	91.57	-20.00	778.00	548.32	494.26	54.06	10.143	
8,900.00	8,882.63	8,921.67	8,881.63	31.44	25.73	93.31	-20.00	778.00	549.19	494.88	54.31	10.112	
8,950.00	8,927.08	8,966.12	8,926.08	31.59	25.81	95.23	-20.00	778.00	551.12	496.55	54.57	10.100	
9,000.00	8,969.36	9,008.41	8,968.36	31.72	25.88	97.22	-20.00	778.00	554.55	499.71	54.83	10.113	
9,050.00	9,009.16	9,048.21	9,008.16	31.85	25.95	99.14	-20.00	778.00	559.95	504.83	55.12	10.159	
9,100.00	9,046.18	9,085.22	9,045.18	31.96	26.01	100.88	-20.00	778.00	567.78	512.36	55.42	10.244	
9,150.00	9,080.13	9,119.17	9,079.13	32.08	26.07	102.31	-20.00	778.00	578.44	522.70	55.75	10.376	
9,200.00	9,110.75	9,149.79	9,109.75	32.22	26.12	103.31	-20.00	778.00	592.26	536.18	56.08	10.560	
9,250.00	9,137.81	9,176.85	9,136.81	32.37	26.17	103.77	-20.00	778.00	609.43	553.00	56.43	10.800	

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

Pro Directional Anticollision Report

Company: Matador Resources
Project: Lea County, NM
Reference Site: Biggers Fed Com
Site Error: 0.00 usft
Reference Well: 024H
Well Error: 0.00 usft
Reference Wellbore: OH
Reference Design: Prelim Plan A

Local Co-ordinate Reference: Well 024H
TVD Reference: RIG @ 3362.00usft (GL:3333'+KB:29')
MD Reference: RIG @ 3362.00usft (GL:3333'+KB:29')
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Output errors are at: 2.00 sigma
Database: WellPlanner1
Offset TVD Reference: Offset Datum

Offset Design Biggers Fed Com - 214H - OH - Prelim Plan A													Offset Site Error: 0.00 usft
Survey Program: 0-MWD - CWSG, 5500-MWD - CWSG, 12981-MWD - CWSG													Offset Well Error: 0.00 usft
Reference		Offset		Semi Major Axis		Distance		Minimum Separation		Separation Factor		Warning	
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	Offset Wellbore Centre +N/-S (usft)	Offset Wellbore Centre +E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)		
9,300.00	9,161.10	9,200.14	9,160.10	32.54	26.21	103.61	-20.00	778.00	630.02	573.25	56.77	11.097	
9,350.00	9,180.45	9,219.50	9,179.45	32.72	26.24	102.71	-20.00	778.00	653.98	596.87	57.11	11.451	
9,400.00	9,195.71	9,234.76	9,194.71	32.91	26.27	101.00	-20.00	778.00	681.12	623.69	57.43	11.861	
9,452.77	9,207.25	9,246.30	9,206.25	33.11	26.29	98.22	-20.00	778.00	712.88	655.15	57.73	12.348	
9,477.77	9,211.59	9,250.64	9,210.59	33.22	26.30	98.66	-20.00	778.00	728.87	671.01	57.86	12.596	
9,500.00	9,215.20	9,254.24	9,214.20	33.31	26.30	97.87	-20.00	778.00	743.52	685.54	57.98	12.824	
9,550.00	9,221.44	9,260.48	9,220.44	33.53	26.32	95.70	-20.00	778.00	777.93	719.71	58.22	13.363	
9,600.00	9,225.07	9,264.11	9,224.07	33.76	26.32	92.94	-20.00	778.00	814.14	755.71	58.43	13.934	
9,644.49	9,226.11	9,265.15	9,225.11	33.97	26.32	90.00	-20.00	778.00	847.63	789.04	58.59	14.466	
9,700.00	9,226.10	9,265.15	9,225.10	34.25	26.32	90.00	-20.00	778.00	890.80	832.03	58.78	15.156	
9,800.00	9,226.10	9,265.15	9,225.10	34.82	26.32	90.00	-20.00	778.00	971.74	912.68	59.06	16.453	
9,900.00	9,226.10	9,265.14	9,225.10	35.45	26.32	90.00	-20.00	778.00	1,055.95	996.65	59.30	17.808	
10,000.00	9,226.10	9,265.14	9,225.10	36.14	26.32	90.00	-20.00	778.00	1,142.71	1,083.22	59.49	19.208	
10,100.00	9,226.09	9,265.14	9,225.09	36.90	26.32	90.00	-20.00	778.00	1,231.47	1,171.82	59.65	20.644	
10,200.00	9,226.09	9,265.14	9,225.09	37.71	26.32	90.00	-20.00	778.00	1,321.85	1,262.06	59.79	22.108	
10,300.00	9,226.09	9,265.13	9,225.09	38.58	26.32	90.00	-20.00	778.00	1,413.52	1,353.61	59.91	23.594	
10,400.00	9,226.09	9,265.13	9,225.09	39.49	26.32	90.00	-20.00	778.00	1,506.25	1,446.24	60.01	25.099	
10,500.00	9,226.08	9,265.13	9,225.08	40.46	26.32	90.00	-20.00	778.00	1,599.85	1,539.75	60.10	26.619	
10,600.00	9,226.08	9,265.13	9,225.08	41.47	26.32	90.00	-20.00	778.00	1,694.19	1,634.01	60.18	28.152	
10,700.00	9,226.08	9,265.12	9,225.08	42.52	26.32	90.00	-20.00	778.00	1,789.14	1,728.89	60.25	29.694	
10,800.00	9,226.08	9,265.12	9,225.08	43.60	26.32	90.00	-20.00	778.00	1,884.62	1,824.30	60.32	31.245	
10,900.00	9,226.07	9,265.12	9,225.07	44.73	26.32	90.00	-20.00	778.00	1,980.54	1,920.16	60.38	32.803	
11,000.00	9,226.07	9,265.12	9,225.07	45.88	26.32	89.99	-20.00	778.00	2,076.84	2,016.41	60.43	34.366	
11,100.00	9,226.07	9,265.11	9,225.07	47.06	26.32	89.99	-20.00	778.00	2,173.48	2,113.00	60.49	35.934	
11,200.00	9,226.07	9,265.11	9,225.07	48.28	26.32	89.99	-20.00	778.00	2,270.41	2,209.88	60.54	37.505	
11,300.00	9,226.06	9,265.11	9,225.06	49.52	26.32	89.99	-20.00	778.00	2,367.60	2,307.02	60.58	39.080	
11,400.00	9,226.06	9,265.11	9,225.06	50.78	26.32	89.99	-20.00	778.00	2,465.01	2,404.38	60.63	40.657	
11,500.00	9,226.06	9,265.10	9,225.06	52.06	26.32	89.99	-20.00	778.00	2,562.62	2,501.95	60.67	42.236	
11,600.00	9,226.06	9,265.10	9,225.06	53.37	26.32	89.99	-20.00	778.00	2,660.41	2,599.69	60.72	43.816	
11,700.00	9,226.06	9,265.10	9,225.06	54.69	26.32	89.99	-20.00	778.00	2,758.36	2,697.60	60.76	45.397	
11,800.00	9,226.05	9,265.10	9,225.05	56.03	26.32	89.99	-20.00	778.00	2,856.45	2,795.64	60.80	46.979	
11,900.00	9,226.05	9,265.10	9,225.05	57.39	26.32	89.99	-20.00	778.00	2,954.66	2,893.82	60.84	48.561	
12,000.00	9,226.05	9,265.09	9,225.05	58.77	26.32	89.99	-20.00	778.00	3,053.00	2,992.11	60.89	50.143	
12,100.00	9,226.05	9,265.09	9,225.05	60.15	26.32	89.99	-20.00	778.00	3,151.43	3,090.51	60.93	51.725	
12,200.00	9,226.04	9,265.09	9,225.04	61.56	26.32	89.99	-20.00	778.00	3,249.97	3,189.00	60.97	53.306	
12,300.00	9,226.04	9,265.09	9,225.04	62.97	26.32	89.99	-20.00	778.00	3,348.59	3,287.58	61.01	54.886	
12,400.00	9,226.04	9,265.08	9,225.04	64.40	26.32	89.99	-20.00	778.00	3,447.29	3,386.23	61.05	56.465	
12,500.00	9,226.04	16,007.16	12,718.04	65.83	65.97	171.13	3,484.24	749.87	3,535.32	3,465.86	69.46	50.895	
12,600.00	9,226.03	16,107.16	12,718.03	67.28	67.38	171.13	3,584.23	749.00	3,535.31	3,464.59	70.72	49.994	
12,700.00	9,226.03	16,207.16	12,718.03	68.74	68.81	171.13	3,684.23	748.12	3,535.29	3,463.31	71.98	49.113	
12,800.00	9,226.03	16,307.16	12,718.03	70.20	70.24	171.13	3,784.22	747.25	3,535.28	3,462.02	73.26	48.254	
12,900.00	9,226.03	16,407.16	12,718.03	71.68	71.68	171.13	3,884.22	746.37	3,535.27	3,460.71	74.56	47.417	
13,000.00	9,226.02	16,507.16	12,718.02	73.16	73.14	171.13	3,984.22	745.50	3,535.25	3,459.39	75.86	46.600	
13,100.00	9,226.02	16,607.16	12,718.02	74.65	74.60	171.13	4,084.21	744.62	3,535.24	3,458.05	77.18	45.803	
13,200.00	9,226.02	16,707.16	12,718.02	76.14	76.07	171.14	4,184.21	743.75	3,535.22	3,456.71	78.51	45.027	
13,300.00	9,226.02	16,807.16	12,718.02	77.65	77.55	171.14	4,284.20	742.87	3,535.21	3,455.35	79.85	44.271	
13,400.00	9,226.01	16,907.16	12,718.01	79.16	79.04	171.14	4,384.20	742.00	3,535.19	3,453.99	81.21	43.534	
13,500.00	9,226.01	17,007.16	12,718.01	80.67	80.53	171.14	4,484.20	741.12	3,535.18	3,452.61	82.57	42.816	
13,600.00	9,226.01	17,107.16	12,718.01	82.19	82.03	171.14	4,584.19	740.25	3,535.16	3,451.23	83.94	42.117	
13,700.00	9,226.01	17,207.16	12,718.01	83.72	83.54	171.14	4,684.19	739.37	3,535.15	3,449.83	85.32	41.436	
13,800.00	9,226.00	17,307.16	12,718.00	85.25	85.05	171.15	4,784.19	738.50	3,535.13	3,448.43	86.70	40.773	
13,900.00	9,226.00	17,407.16	12,718.00	86.78	86.57	171.15	4,884.18	737.62	3,535.12	3,447.02	88.10	40.127	

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

Pro Directional Anticollision Report

Company: Matador Resources
Project: Lea County, NM
Reference Site: Biggers Fed Com
Site Error: 0.00 usft
Reference Well: 024H
Well Error: 0.00 usft
Reference Wellbore: OH
Reference Design: Prelim Plan A

Local Co-ordinate Reference: Well 024H
TVD Reference: RIG @ 3362.00usft (GL:3333'+KB:29')
MD Reference: RIG @ 3362.00usft (GL:3333'+KB:29')
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Output errors are at: 2.00 sigma
Database: WellPlanner1
Offset TVD Reference: Offset Datum

Offset Design												Biggers Fed Com - 214H - OH - Prelim Plan A		Offset Site Error: 0.00 usft	
Survey Program:												0-MWD - OWSG, 5500-MWD - OWSG, 12981-MWD - OWSG		Offset Well Error: 0.00 usft	
Reference		Offset		Semi Major Axis			Distance						Warning		
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	Offset Wellbore Centre +N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor			
13,971.67	9,226.00	17,478.83	12,718.00	87.89	87.66	171.15	4,955.85	736.99	3,535.11	3,446.01	89.10	39.674			

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

Pro Directional Anticollision Report

Company: Matador Resources
Project: Lea County, NM
Reference Site: Biggers Fed Com
Site Error: 0.00 usft
Reference Well: 024H
Well Error: 0.00 usft
Reference Wellbore: OH
Reference Design: Prelim Plan A

Local Co-ordinate Reference: Well 024H
TVD Reference: RIG @ 3362.00usft (GL:3333'+KB:29')
MD Reference: RIG @ 3362.00usft (GL:3333'+KB:29')
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Output errors are at 2.00 sigma
Database: WellPlanner1
Offset TVD Reference: Offset Datum

Offset Design Biggers Fed Com - 217H - OH - Prelim Plan A													Offset Site Error: 0.00 usft
Survey Program: 0-MWD - OWSG, 5500-MWD - OWSG, 13004-MWD - OWSG													Offset Well Error: 0.00 usft
Reference		Offset		Semi Major Axis		Highside Toolface (°)	Distance				Minimum Separation (usft)	Separation Factor	Warning
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)		Offset Wellbore Centre +N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)			
0.00	0.00	1.00	-1.00	0.00	0.00	-135.94	-31.00	-30.00	43.14				
100.00	100.00	101.00	99.00	0.13	0.13	-135.94	-31.00	-30.00	43.14	42.88	0.26	167.142	
200.00	200.00	201.00	199.00	0.49	0.49	-135.94	-31.00	-30.00	43.14	42.16	0.98	44.243	
300.00	300.00	301.00	299.00	0.84	0.85	-135.94	-31.00	-30.00	43.14	41.45	1.69	25.496	
400.00	400.00	401.00	399.00	1.20	1.21	-135.94	-31.00	-30.00	43.14	40.73	2.41	17.908	
500.00	500.00	501.00	499.00	1.56	1.56	-135.94	-31.00	-30.00	43.14	40.01	3.13	13.801	
600.00	600.00	599.00	599.00	1.92	1.92	-135.94	-31.00	-30.00	43.14	39.30	3.84	11.247	CC, ES
700.00	700.00	698.21	698.20	2.28	2.26	-134.75	-30.99	-31.26	44.02	39.48	4.54	9.694	
800.00	800.00	797.29	797.20	2.64	2.61	-131.41	-30.95	-35.09	46.83	41.58	5.24	8.933	
900.00	900.00	896.10	895.80	3.00	2.96	-126.68	-30.88	-41.47	51.81	45.86	5.94	8.719	SF
1,000.00	1,000.00	994.51	993.81	3.35	3.31	-121.45	-30.79	-50.35	59.25	52.61	6.64	8.923	
1,100.00	1,100.00	1,107.72	1,090.92	3.71	3.73	-116.45	-30.68	-61.67	69.35	61.96	7.39	9.387	
1,200.00	1,200.00	1,208.57	1,189.22	4.07	4.12	-112.27	-30.55	-74.61	81.21	73.11	8.10	10.022	
1,300.00	1,300.00	1,309.43	1,287.51	4.43	4.51	-109.16	-30.42	-87.55	93.39	84.57	8.82	10.589	
1,400.00	1,400.00	1,389.72	1,385.81	4.79	4.83	-106.77	-30.29	-100.49	105.78	96.32	9.46	11.178	
1,500.00	1,499.99	1,488.68	1,483.93	5.14	5.22	155.42	-30.16	-113.41	119.49	109.33	10.17	11.754	
1,600.00	1,599.91	1,587.24	1,581.65	5.48	5.61	157.46	-30.03	-126.27	135.72	124.86	10.86	12.496	
1,700.00	1,699.69	1,685.33	1,678.89	5.82	6.01	159.39	-29.90	-139.07	154.51	142.95	11.56	13.370	
1,733.33	1,732.91	1,717.91	1,711.19	5.94	6.14	159.99	-29.86	-143.33	161.34	149.55	11.79	13.686	
1,800.00	1,799.32	1,783.00	1,775.73	6.17	6.40	161.16	-29.77	-151.82	175.33	163.08	12.25	14.312	
1,900.00	1,898.94	1,880.65	1,872.54	6.53	6.80	162.60	-29.64	-164.57	196.42	183.47	12.94	15.174	
2,000.00	1,998.56	1,978.29	1,969.35	6.88	7.19	163.76	-29.52	-177.31	217.60	203.96	13.64	15.952	
2,100.00	2,098.18	2,075.94	2,066.16	7.24	7.59	164.72	-29.39	-190.06	238.85	224.51	14.34	16.657	
2,200.00	2,197.80	2,173.58	2,162.97	7.61	7.99	165.52	-29.26	-202.80	260.16	245.12	15.04	17.298	
2,300.00	2,297.42	2,271.23	2,259.78	7.97	8.39	166.19	-29.13	-215.54	281.51	265.77	15.74	17.882	
2,400.00	2,397.04	2,368.87	2,356.59	8.34	8.79	166.78	-29.00	-228.29	302.89	286.44	16.45	18.417	
2,500.00	2,496.66	2,466.51	2,453.40	8.70	9.19	167.28	-28.87	-241.03	324.30	307.15	17.15	18.908	
2,600.00	2,596.28	2,564.16	2,550.21	9.07	9.59	167.72	-28.74	-253.78	345.73	327.87	17.86	19.360	
2,700.00	2,695.90	2,661.80	2,647.02	9.44	9.99	168.11	-28.62	-266.52	367.17	348.61	18.57	19.777	
2,800.00	2,795.52	2,759.45	2,743.82	9.82	10.39	168.46	-28.49	-279.27	388.63	369.36	19.27	20.164	
2,900.00	2,895.14	2,857.09	2,840.63	10.19	10.79	168.77	-28.36	-292.01	410.10	390.12	19.98	20.523	
3,000.00	2,994.76	2,954.74	2,937.44	10.56	11.20	169.05	-28.23	-304.76	431.59	410.89	20.69	20.858	
3,100.00	3,094.38	3,052.38	3,034.25	10.94	11.60	169.31	-28.10	-317.50	453.08	431.67	21.40	21.170	
3,200.00	3,194.00	3,150.03	3,131.06	11.31	12.00	169.54	-27.97	-330.25	474.58	452.46	22.11	21.461	
3,300.00	3,293.62	3,247.67	3,227.87	11.69	12.40	169.75	-27.84	-342.99	496.08	473.26	22.82	21.735	
3,400.00	3,393.23	3,345.31	3,324.66	12.06	12.81	169.94	-27.72	-355.73	517.59	494.06	23.54	21.991	
3,500.00	3,492.85	3,442.96	3,421.49	12.44	13.21	170.12	-27.59	-368.48	539.11	514.86	24.25	22.233	
3,600.00	3,592.47	3,540.60	3,518.30	12.82	13.61	170.29	-27.46	-381.22	560.63	535.67	24.96	22.460	
3,700.00	3,692.09	3,638.25	3,615.11	13.19	14.02	170.44	-27.33	-393.97	582.16	556.48	25.67	22.675	
3,800.00	3,791.71	3,735.89	3,711.92	13.57	14.42	170.58	-27.20	-406.71	603.69	577.30	26.39	22.877	
3,900.00	3,891.33	3,833.54	3,808.73	13.95	14.83	170.71	-27.07	-419.46	625.22	598.12	27.10	23.069	
4,000.00	3,990.95	3,931.18	3,905.53	14.33	15.23	170.83	-26.95	-432.20	646.75	618.94	27.82	23.251	
4,078.35	4,069.01	4,007.69	3,981.39	14.63	15.55	170.93	-26.84	-442.19	663.63	635.25	28.38	23.387	
4,100.00	4,090.58	4,028.84	4,002.36	14.71	15.63	170.96	-26.82	-444.95	668.23	639.70	28.53	23.422	
4,200.00	4,190.34	4,126.87	4,099.55	15.08	16.04	171.09	-26.69	-457.74	687.96	658.72	29.24	23.524	
4,300.00	4,290.25	4,225.37	4,197.21	15.44	16.45	171.18	-26.56	-470.60	705.15	675.19	29.96	23.536	
4,400.00	4,390.23	4,324.30	4,295.28	15.79	16.86	171.22	-26.43	-483.51	719.78	689.10	30.68	23.464	
4,411.69	4,401.92	4,335.88	4,306.77	15.83	16.91	-88.91	-26.41	-485.02	721.32	690.56	30.76	23.451	
4,500.00	4,490.23	4,423.44	4,393.58	16.13	17.27	-88.92	-26.30	-496.45	732.85	701.46	31.39	23.350	
4,600.00	4,590.23	4,522.58	4,491.87	16.47	17.68	-88.93	-26.17	-509.39	745.90	713.80	32.10	23.239	
4,700.00	4,690.23	4,621.73	4,590.17	16.81	18.09	-88.94	-26.04	-522.33	758.95	726.15	32.81	23.134	
4,800.00	4,790.23	4,720.87	4,688.47	17.16	18.50	-88.94	-25.91	-535.27	772.00	738.49	33.52	23.032	

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

Pro Directional Anticollision Report

Company: Malador Resources
Project: Lea County, NM
Reference Site: Biggers Fed Com
Site Error: 0.00 usft
Reference Well: 024H
Well Error: 0.00 usft
Reference Wellbore: OH
Reference Design: Prelim Plan A

Local Co-ordinate Reference: Well 024H
TVD Reference: RIG @ 3362.00usft (GL:3333'+KB:29')
MD Reference: RIG @ 3362.00usft (GL:3333'+KB:29')
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Output errors are at: 2.00 sigma
Database: WellPlanner1
Offset TVD Reference: Offset Datum

Offset Design Biggers Fed Com - 217H - OH - Prelim Plan A												Offset Site Error:	0.00 usft
Survey Program: 0-MWD - OWSG, 5500-MWD - OWSG 13004-MWD - OWSG												Offset Well Error:	0.00 usft
Reference		Offset		Semi Major Axis		Distance							
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	Offset Wellbore Centre +N-S (usft)	+E-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning
4,900.00	4,890.23	4,820.02	4,786.76	17.50	18.91	-88.95	-25.78	-548.21	785.06	750.83	34.23	22.934	
5,000.00	4,990.23	4,919.16	4,885.06	17.84	19.32	-88.96	-25.65	-561.15	798.11	763.17	34.94	22.840	
5,100.00	5,090.23	5,018.30	4,983.36	18.19	19.73	-88.97	-25.52	-574.09	811.16	775.51	35.66	22.750	
5,200.00	5,190.23	5,117.45	5,081.65	18.53	20.15	-88.98	-25.38	-587.03	824.21	787.84	36.37	22.662	
5,300.00	5,290.23	5,216.59	5,179.95	18.87	20.56	-88.98	-25.25	-599.97	837.27	800.18	37.08	22.578	
5,400.00	5,390.23	5,315.74	5,278.25	19.22	20.97	-88.99	-25.12	-612.91	850.32	812.52	37.80	22.497	
5,500.00	5,490.23	5,414.88	5,376.54	19.57	21.36	-89.00	-24.99	-625.85	863.37	824.89	38.48	22.434	
5,600.00	5,590.23	5,514.03	5,474.84	19.91	21.58	-89.00	-24.86	-638.79	876.42	837.43	38.99	22.477	
5,700.00	5,690.23	5,613.17	5,573.13	20.26	21.66	-89.01	-24.73	-651.73	889.48	850.13	39.35	22.605	
5,800.00	5,790.23	5,712.32	5,671.43	20.60	21.75	-89.01	-24.60	-664.67	902.53	862.82	39.71	22.727	
5,900.00	5,890.23	5,811.46	5,769.73	20.95	21.85	-89.02	-24.47	-677.61	915.58	875.50	40.08	22.842	
6,000.00	5,990.23	5,910.60	5,868.02	21.30	21.96	-89.03	-24.34	-690.55	928.63	888.17	40.46	22.952	
6,100.00	6,090.23	6,009.75	5,966.32	21.65	22.07	-89.03	-24.21	-703.49	941.68	900.84	40.84	23.055	
6,200.00	6,190.23	6,108.89	6,064.62	22.00	22.19	-89.04	-24.08	-716.44	954.74	913.50	41.24	23.153	
6,300.00	6,290.23	6,208.04	6,162.91	22.35	22.32	-89.04	-23.95	-729.38	967.79	926.15	41.64	23.245	
6,400.00	6,390.23	6,307.18	6,261.21	22.69	22.46	-89.05	-23.82	-742.32	980.84	938.80	42.04	23.331	
6,500.00	6,490.23	6,406.33	6,359.50	23.04	22.60	-89.05	-23.69	-755.26	993.89	951.44	42.45	23.412	
6,600.00	6,590.23	6,505.47	6,457.80	23.39	22.75	-89.06	-23.56	-768.20	1,006.95	964.07	42.87	23.487	
6,700.00	6,690.23	6,604.62	6,556.10	23.74	22.90	-89.06	-23.43	-781.14	1,020.00	976.70	43.30	23.558	
6,800.00	6,790.23	6,703.76	6,654.39	24.09	23.06	-89.07	-23.30	-794.08	1,033.05	989.32	43.73	23.623	
6,900.00	6,890.23	6,802.91	6,752.69	24.44	23.23	-89.07	-23.17	-807.02	1,046.10	1,001.93	44.17	23.684	
7,000.00	6,990.23	6,902.05	6,850.99	24.79	23.40	-89.07	-23.04	-819.96	1,059.16	1,014.54	44.61	23.740	
7,100.00	7,090.23	7,001.19	6,949.28	25.14	23.58	-89.08	-22.91	-832.90	1,072.21	1,027.14	45.07	23.792	
7,200.00	7,190.23	7,100.34	7,047.58	25.50	23.77	-89.08	-22.78	-845.84	1,085.26	1,039.74	45.52	23.839	
7,300.00	7,290.23	7,200.52	7,145.87	25.85	23.96	-89.09	-22.65	-858.78	1,098.31	1,052.32	45.99	23.882	
7,400.00	7,390.23	7,301.37	7,244.17	26.20	24.16	-89.09	-22.51	-871.72	1,111.37	1,064.90	46.46	23.920	
7,500.00	7,490.23	7,397.77	7,342.47	26.55	24.36	-89.09	-22.38	-884.66	1,124.42	1,077.48	46.93	23.957	
7,600.00	7,590.23	7,503.08	7,440.76	26.90	24.58	-89.10	-22.25	-897.60	1,137.47	1,090.05	47.42	23.985	
7,700.00	7,690.23	7,603.94	7,539.06	27.25	24.79	-89.10	-22.12	-910.54	1,150.52	1,102.61	47.91	24.012	
7,800.00	7,790.23	7,704.79	7,637.36	27.61	25.01	-89.11	-21.99	-923.48	1,163.57	1,115.16	48.41	24.036	
7,900.00	7,890.23	7,794.35	7,735.65	27.96	25.21	-89.11	-21.86	-936.42	1,176.63	1,127.73	48.90	24.064	
8,000.00	7,990.23	7,906.51	7,833.95	28.31	25.47	-89.11	-21.73	-949.36	1,189.68	1,140.26	49.42	24.073	
8,100.00	8,090.23	8,007.36	7,932.25	28.66	25.71	-89.12	-21.60	-962.30	1,202.73	1,152.80	49.93	24.087	
8,200.00	8,190.23	8,108.22	8,030.54	29.02	25.95	-89.12	-21.47	-975.24	1,215.78	1,165.33	50.45	24.099	
8,300.00	8,290.23	8,190.93	8,128.84	29.37	26.15	-89.12	-21.34	-988.18	1,228.84	1,177.89	50.94	24.122	
8,400.00	8,390.23	8,333.57	8,270.53	29.72	26.48	-89.13	-21.18	-1,004.47	1,240.30	1,188.65	51.65	24.011	
8,500.00	8,490.23	8,481.44	8,417.97	30.08	26.78	-89.13	-21.06	-1,015.77	1,247.95	1,195.60	52.34	23.842	
8,600.00	8,590.23	8,629.98	8,566.39	30.43	27.05	-89.13	-21.01	-1,021.36	1,251.72	1,198.73	52.98	23.625	
8,652.77	8,643.00	8,708.48	8,644.88	30.62	27.17	-89.13	-21.00	-1,021.99	1,252.14	1,198.84	53.30	23.494	
8,700.00	8,690.18	8,752.77	8,689.18	30.78	27.24	-88.97	-21.00	-1,022.00	1,252.11	1,198.57	53.54	23.386	
8,750.00	8,739.76	8,802.36	8,738.76	30.95	27.31	-89.27	-21.00	-1,022.00	1,252.01	1,198.21	53.80	23.272	
8,800.00	8,788.62	8,851.21	8,787.62	31.12	27.39	-89.75	-21.00	-1,022.00	1,251.92	1,197.86	54.05	23.160	
8,820.80	8,808.63	8,871.22	8,807.63	31.19	27.42	-90.00	-21.00	-1,022.00	1,251.91	1,197.75	54.16	23.115	
8,850.00	8,836.36	8,901.05	8,835.36	31.29	27.46	-90.39	-21.00	-1,022.00	1,251.94	1,197.63	54.31	23.052	
8,900.00	8,882.63	8,945.22	8,881.63	31.44	27.53	-91.17	-21.00	-1,022.00	1,252.22	1,197.67	54.55	22.954	
8,950.00	8,927.08	8,989.67	8,926.08	31.59	27.60	-92.02	-21.00	-1,022.00	1,252.94	1,198.14	54.80	22.865	
9,000.00	8,969.36	9,031.96	8,968.36	31.72	27.67	-92.92	-21.00	-1,022.00	1,254.31	1,199.27	55.04	22.789	
9,050.00	9,009.16	9,071.76	9,008.16	31.85	27.73	-93.79	-21.00	-1,022.00	1,256.54	1,201.26	55.28	22.730	
9,100.00	9,046.18	9,108.77	9,045.18	31.96	27.79	-94.59	-21.00	-1,022.00	1,259.87	1,204.34	55.52	22.691	
9,150.00	9,080.13	9,142.72	9,079.13	32.08	27.85	-95.25	-21.00	-1,022.00	1,264.51	1,208.74	55.77	22.674	
9,200.00	9,110.75	9,173.34	9,109.75	32.22	27.90	-95.73	-21.00	-1,022.00	1,270.67	1,214.66	56.02	22.684	
9,250.00	9,137.81	9,200.40	9,136.81	32.37	27.94	-95.97	-21.00	-1,022.00	1,278.54	1,222.28	56.27	22.723	

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

Pro Directional Anticollision Report

Company: Matador Resources
Project: Lea County, NM
Reference Site: Biggers Fed Com
Site Error: 0.00 usft
Reference Well: 024H
Well Error: 0.00 usft
Reference Wellbore: OH
Reference Design: Prelim Plan A

Local Co-ordinate Reference: Well 024H
TVD Reference: RIG @ 3362.00usft (GL:3333'+KB:29')
MD Reference: RIG @ 3362.00usft (GL:3333'+KB:29')
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Output errors are at 2.00 sigma
Database: WellPlanner1
Offset TVD Reference: Offset Datum

Offset Design Biggers Fed Com - 217H - OH - Prelim Plan A													Offset Site Error:	0.00 usft
Survey Program: 0-MWD - OWSG, 5500-MWD - OWSG, 13004-MWD - OWSG													Offset Well Error:	0.00 usft
Reference		Offset		Semi Major Axis			Distance							
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	Offset Wellbore Centre +N/-S (usft)	Offset Wellbore Centre +E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning	
9,300.00	9,161.10	9,223.69	9,160.10	32.54	27.98	-95.92	-21.00	-1,022.00	1,288.25	1,231.73	56.52	22.794		
9,350.00	9,180.45	9,243.04	9,179.45	32.72	28.01	-95.53	-21.00	-1,022.00	1,299.89	1,243.12	56.77	22.898		
9,400.00	9,195.71	9,258.30	9,194.71	32.91	28.04	-94.78	-21.00	-1,022.00	1,313.51	1,256.49	57.02	23.037		
9,452.77	9,207.25	9,269.85	9,206.25	33.11	28.06	-93.56	-21.00	-1,022.00	1,329.99	1,272.71	57.27	23.221		
9,477.77	9,211.59	9,274.19	9,210.59	33.22	28.06	-93.76	-21.00	-1,022.00	1,338.50	1,281.11	57.40	23.321		
9,500.00	9,215.20	9,277.79	9,214.20	33.31	28.07	-93.41	-21.00	-1,022.00	1,346.41	1,288.91	57.50	23.414		
9,550.00	9,221.44	9,284.03	9,220.44	33.53	28.08	-92.45	-21.00	-1,022.00	1,365.41	1,307.66	57.75	23.645		
9,600.00	9,225.07	9,287.66	9,224.07	33.76	28.09	-91.26	-21.00	-1,022.00	1,385.98	1,327.99	57.98	23.903		
9,644.49	9,226.11	9,288.70	9,225.11	33.97	28.09	-90.00	-21.00	-1,022.00	1,405.53	1,347.34	58.19	24.156		
9,700.00	9,226.10	9,288.70	9,225.10	34.25	28.09	-90.00	-21.00	-1,022.00	1,431.47	1,373.03	58.44	24.495		
9,800.00	9,226.10	9,288.69	9,225.10	34.82	28.09	-90.00	-21.00	-1,022.00	1,482.31	1,423.41	58.89	25.169		
9,900.00	9,226.10	9,288.69	9,225.10	35.45	28.09	-90.00	-21.00	-1,022.00	1,537.98	1,478.64	59.34	25.918		
10,000.00	9,226.10	9,288.69	9,225.10	36.14	28.09	-90.00	-21.00	-1,022.00	1,597.97	1,538.20	59.77	26.735		
10,100.00	9,226.09	9,288.69	9,225.09	36.90	28.09	-90.00	-21.00	-1,022.00	1,661.82	1,601.64	60.18	27.614		
10,200.00	9,226.09	9,288.68	9,225.09	37.71	28.09	-90.00	-21.00	-1,022.00	1,729.10	1,668.54	60.56	28.551		
10,300.00	9,226.09	9,288.68	9,225.09	38.58	28.09	-90.00	-21.00	-1,022.00	1,799.42	1,738.51	60.92	29.539		
10,400.00	9,226.09	9,288.68	9,225.09	39.49	28.09	-90.00	-21.00	-1,022.00	1,872.45	1,811.20	61.25	30.573		
10,500.00	9,226.08	9,288.68	9,225.08	40.46	28.09	-90.00	-21.00	-1,022.00	1,947.87	1,886.32	61.55	31.648		
10,600.00	9,226.08	9,288.67	9,225.08	41.47	28.09	-90.00	-21.00	-1,022.00	2,025.42	1,963.60	61.83	32.760		
10,700.00	9,226.08	9,288.67	9,225.08	42.52	28.09	-90.00	-21.00	-1,022.00	2,104.87	2,042.79	62.08	33.905		
10,800.00	9,226.08	9,288.67	9,225.08	43.60	28.09	-90.00	-21.00	-1,022.00	2,186.00	2,123.69	62.31	35.080		
10,900.00	9,226.07	9,288.67	9,225.07	44.73	28.09	-90.00	-21.00	-1,022.00	2,268.64	2,206.11	62.53	36.281		
11,000.00	9,226.07	9,288.66	9,225.07	45.88	28.09	-90.00	-21.00	-1,022.00	2,352.63	2,289.90	62.73	37.505		
11,100.00	9,226.07	9,288.66	9,225.07	47.06	28.09	-90.00	-21.00	-1,022.00	2,437.83	2,374.92	62.91	38.751		
11,200.00	9,226.07	9,288.66	9,225.07	48.28	28.09	-90.00	-21.00	-1,022.00	2,524.11	2,461.03	63.08	40.015		
11,300.00	9,226.06	9,288.66	9,225.06	49.52	28.09	-90.00	-21.00	-1,022.00	2,611.38	2,548.14	63.24	41.295		
11,400.00	9,226.06	9,288.65	9,225.06	50.78	28.09	-90.00	-21.00	-1,022.00	2,699.52	2,636.14	63.38	42.591		
11,500.00	9,226.06	9,288.65	9,225.06	52.06	28.09	-90.00	-21.00	-1,022.00	2,788.47	2,724.95	63.52	43.900		
11,600.00	9,226.06	9,288.65	9,225.06	53.37	28.09	-90.00	-21.00	-1,022.00	2,878.14	2,814.50	63.65	45.222		
11,700.00	9,226.06	9,288.65	9,225.06	54.69	28.09	-90.00	-21.00	-1,022.00	2,968.47	2,904.71	63.76	46.553		
11,800.00	9,226.05	9,288.64	9,225.05	56.03	28.09	-90.00	-21.00	-1,022.00	3,059.41	2,995.53	63.88	47.895		
11,900.00	9,226.05	9,288.64	9,225.05	57.39	28.09	-90.00	-21.00	-1,022.00	3,150.89	3,086.91	63.98	49.245		
12,000.00	9,226.05	9,288.64	9,225.05	58.77	28.09	-90.00	-21.00	-1,022.00	3,242.88	3,178.79	64.09	50.603		
12,100.00	9,226.05	9,288.64	9,225.05	60.15	28.09	-90.00	-21.00	-1,022.00	3,335.32	3,271.14	64.18	51.967		
12,200.00	9,226.04	9,288.64	9,225.04	61.56	28.09	-90.00	-21.00	-1,022.00	3,428.20	3,363.92	64.27	53.338		
12,300.00	9,226.04	9,288.63	9,225.04	62.97	28.09	-90.00	-21.00	-1,022.00	3,521.46	3,457.10	64.36	54.714		
12,400.00	9,226.04	9,288.63	9,225.04	64.40	28.09	-90.00	-21.00	-1,022.00	3,615.08	3,550.63	64.45	56.095		
12,500.00	9,226.04	9,288.63	9,225.04	65.83	28.09	-90.00	-21.00	-1,022.00	3,709.03	3,644.51	64.53	57.480		
12,600.00	9,226.03	16,115.93	12,718.03	67.28	68.02	-160.24	3,568.45	-1,050.93	3,711.51	3,632.10	79.42	46.735		
12,700.00	9,226.03	16,215.93	12,718.03	68.74	69.42	-160.24	3,668.45	-1,051.81	3,711.54	3,630.64	80.91	45.874		
12,800.00	9,226.03	16,315.93	12,718.03	70.20	70.84	-160.24	3,768.44	-1,052.69	3,711.58	3,629.16	82.41	45.035		
12,900.00	9,226.03	16,415.93	12,718.03	71.68	72.26	-160.24	3,868.44	-1,053.56	3,711.61	3,627.67	83.94	44.220		
13,000.00	9,226.02	16,515.93	12,718.02	73.16	73.70	-160.24	3,968.44	-1,054.44	3,711.64	3,626.17	85.47	43.427		
13,100.00	9,226.02	16,615.93	12,718.02	74.65	75.15	-160.23	4,068.43	-1,055.32	3,711.67	3,624.66	87.01	42.656		
13,200.00	9,226.02	16,715.92	12,718.02	76.14	76.60	-160.23	4,168.43	-1,056.20	3,711.71	3,623.13	88.57	41.906		
13,300.00	9,226.02	16,815.92	12,718.02	77.65	78.07	-160.23	4,268.42	-1,057.07	3,711.74	3,621.60	90.14	41.177		
13,400.00	9,226.01	16,915.92	12,718.01	79.16	79.54	-160.23	4,368.42	-1,057.95	3,711.77	3,620.05	91.72	40.468		
13,500.00	9,226.01	17,015.92	12,718.01	80.67	81.02	-160.23	4,468.42	-1,058.83	3,711.80	3,618.49	93.31	39.778		
13,600.00	9,226.01	17,115.92	12,718.01	82.19	82.51	-160.23	4,568.41	-1,059.70	3,711.84	3,616.92	94.91	39.108		
13,700.00	9,226.01	17,215.92	12,718.01	83.72	84.00	-160.23	4,668.41	-1,060.58	3,711.87	3,615.35	96.52	38.457		
13,800.00	9,226.00	17,315.92	12,718.00	85.25	85.51	-160.22	4,768.40	-1,061.46	3,711.90	3,613.76	98.14	37.823		
13,900.00	9,226.00	17,415.92	12,718.00	86.78	87.01	-160.22	4,868.40	-1,062.34	3,711.93	3,612.17	99.76	37.207		

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

Pro Directional Anticollision Report

Company: Matador Resources
Project: Lea County, NM
Reference Site: Biggers Fed Com
Site Error: 0.00 usft
Reference Well: 024H
Well Error: 0.00 usft
Reference Wellbore: OH
Reference Design: Prelim Plan A

Local Co-ordinate Reference: Well 024H
TVD Reference: RIG @ 3362.00usft (GL:3333'+KB:29')
MD Reference: RIG @ 3362.00usft (GL:3333'+KB:29')
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Output errors are at: 2.00 sigma
Database: WellPlanner1
Offset TVD Reference: Offset Datum

Offset Design Biggers Fed Com - 217H - OH - Prelim Plan A												Offset Site Error:	0.00 usft
Survey Program: 0-MWD - OWSG, 5500-MWD - OWSG, 13004-MWD - OWSG												Offset Well Error:	0.00 usft
Reference		Offset		Semi Major Axis			Distance						
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	Offset Wellbore Centre +N/-S (usft)	-E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning
13,971.67	9,226.00	17,487.59	12,718.00	87.89	88.10	-160.22	4,940.07	-1,062.97	3,711.96	3,611.02	100.93	36.776	


Pro Directional Anticollision Report

Company: Matador Resources
Project: Lea County, NM
Reference Site: Biggers Fed Com
Site Error: 0.00 usft
Reference Well: 024H
Well Error: 0.00 usft
Reference Wellbore: OH
Reference Design: Prelim Plan A

Local Co-ordinate Reference: Well 024H
TVD Reference: RIG @ 3362.00usft (GL:3333'+KB:29')
MD Reference: RIG @ 3362.00usft (GL:3333'+KB:29')
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Output errors are at: 2.00 sigma
Database: WellPlanner1
Offset TVD Reference: Offset Datum

Reference Depths are relative to RIG @ 3362.00usft (GL:3333'+KB:29')
Offset Depths are relative to Offset Datum
Central Meridian is 104° 20' 0.000 W

Coordinates are relative to: 024H
Coordinate System is US State Plane 1927 (Exact solution), New Mexico East 30
Grid Convergence at Surface is: 0.50°



Pro Directional Anticollision Report


Company: Matador Resources
Project: Lea County, NM
Reference Site: Biggers Fed Com
Site Error: 0.00 usft
Reference Well: 024H
Well Error: 0.00 usft
Reference Wellbore: OH
Reference Design: Prelim Plan A

Local Co-ordinate Reference: Well 024H
TVD Reference: RIG @ 3362.00usft (GL:3333'+KB:29')
MD Reference: RIG @ 3362.00usft (GL:3333'+KB:29')
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Output errors are at: 2.00 sigma
Database: WellPlanner1
Offset TVD Reference: Offset Datum

Reference Depths are relative to RIG @ 3362.00usft (GL:3333'+KB:29')
Offset Depths are relative to Offset Datum
Central Meridian is 104° 20' 0.000 W

Coordinates are relative to: 024H
Coordinate System is US State Plane 1927 (Exact solution), New Mexico East 30
Grid Convergence at Surface is: 0.50°

Separation Factor Plot



LEGEND

207H1, OH, Prelim Plan A v0 214H1, OH, Prelim Plan A v0 217H1, OH, Prelim Plan A v0

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

HOBBS CO.

Matador Production Company
Biggers Fed Com 24H FEB 15 2018
SHL 90' FSL & 1226' FEL
BHL 240' FNL & 994' FEL **RECEIVED**
Sec. 18, T. 25 S., R. 35 E., Lea County, NM

DRILL PLAN PAGE 1

Drilling Program

1. ESTIMATED TOPS

Formation Name	TVD	MD	Bearing
Quaternary	000'	000'	water
Dewey Lake red beds sandstone	441'	441'	water
Rustler anhydrite	931'	931'	barren
Top salt	1448'	1448'	barren
Castile anhydrite	3738'	3746'	barren
Base salt	5449'	5459'	barren
Bell Canyon sandstone	5489'	5499'	hydrocarbons
Cherry Canyon sandstone	6492'	6502'	hydrocarbons
Brushy Canyon sandstone	7963'	7973'	hydrocarbons & goal
(KOP	8690'	8700'	hydrocarbons)
TD	9226'	13972'	hydrocarbons

2. NOTABLE ZONES

Brushy Canyon is the goal. Hole will extend north of the last perforation point to allow for pump installation. All perforations will be $\geq 330'$ from the dedication perimeter. Closest water well (C 02296) is 3693' north. Depth to water is 230' in this 300' deep well.

3. PRESSURE CONTROL

A 10,000' 5000-psi BOP stack consisting of 3 rams with 2 pipe rams, 1 blind ram, and 1 annular preventer will be used below surface casing to TD. See attached BOP and choke manifold diagrams.

Matador Production Company
Biggers Fed Com 24H
SHL 90' FSL & 1226' FEL
BHL 240' FNL & 994' FEL
Sec. 18, T. 25 S., R. 35 E., Lea County, NM

DRILL PLAN PAGE 2

An accumulator complying with Onshore Order 2 requirements for the BOP stack pressure rating will be present. Rotating head will be installed as needed.

Pressure tests will be conducted before drilling out from under all casing strings. BOP will be inspected and operated as required in Onshore Order 2. Kelly cock and sub equipped with a full opening valve sized to fit the drill pipe and collars will be available on the rig floor in the open position.

A third party company will test the BOPs.

Surface casing will be pressure tested to 250 psi low and 2000 psi high. Intermediate casing pressure tests will be made to 250 psi low and 3000 psi high. Annular preventer will be tested to 250 psi low and 1000 psi high on the surface casing and tested to 250 psi low and 2500 psi high on the intermediate casing. In the case of running a speed head with landing mandrel for 9.625" casing, initial surface casing test pressures will be 250 psi low and 3000 psi high. Annular will be tested to 250 psi low and 2500 psi high. Wellhead seals will be tested to 5000 psi once the 9.625" casing has been landed and cemented.

Matador is requesting a variance to use a speed head. Speed head diameter range is 13.375" x 9.625" x 5.5" x 2.875". Wellhead diagram is attached.

Matador requests a variance to drill this well using a co-flex line between the BOP and choke manifold. Certification for proposed co-flex hose is attached. Manufacturer does not require the hose to be anchored. If the specific hose is not available, then one of equal or higher rating will be used.

Matador Production Company

DRILL PLAN PAGE 3

Biggers Fed Com 24H

SHL 90' FSL & 1226' FEL

BHL 240' FNL & 994' FEL

Sec. 18, T. 25 S., R. 35 E., Lea County, NM

4. CASING & CEMENT

All casing will be API and new.

Hole O. D.	Set MD	Set TVD	Casing O. D.	Weight (lb/ft)	Grade	Joint	Collapse	Burst	Tension
17.5"	0' - 1000'	0' - 1000'	Surface 13.375"	54.5	J-55	BTC	1.125	1.125	1.8
12.25"	0' - 5600'	0' - 5590'	Inter. 9.625"	40	J-55	BTC	1.125	1.125	1.8
8.75"	0' - 13972'	0' - 9226'	Product. 5.5"	20	P-110	BTC/TXP	1.125	1.125	1.8

Casing Name	Type	Sacks	Yield	Cu. Ft.	Weight	Blend
Surface	Lead	210	1.82	382	12.8	Class C + bentonite + 2% CaCl + 3% NaCl + LCM
	Tail	740	1.38	1021	14.8	Class C + 5% NaCl + LCM
TOC = GL		100% Excess			Centralizers per Onshore Order 2	
Intermediate	Lead	1170	2.13	2492	12.6	Class C + Bentonite + 1% CaCl ₂ + 8% NaCl + LCM
	Tail	620	1.38	855	14.8	Class C + 5% NaCl + LCM
TOC = GL		100% Excess			2 on btm jt, 1 on 2nd jt, 1 every 4th jt to GL	
Production	Lead	721	2.35	1694	11.5	TXI + Fluid Loss + Dispersant + Retarder + LCM
	Tail	1250	1.39	1737	13.2	TXI + Fluid Loss + Dispersant + Retarder + LCM
TOC = 4600'		35% Excess			2 on btm jt, 1 on 2nd jt, 1 every other jt to top of tail cement (1000' above TOC)	

Matador Production Company
Biggers Fed Com 24H
SHL 90' FSL & 1226' FEL
BHL 240' FNL & 994' FEL
Sec. 18, T. 25 S., R. 35 E., Lea County, NM

DRILL PLAN PAGE 4

5. MUD PROGRAM

An electronic Pason mud monitoring system complying with Onshore Order 1 will be used. All necessary mud products (barite, bentonite, LCM) for weight addition and fluid loss control will be on location at all times. Mud program is subject to change due to hole conditions. A closed loop system will be used.

Type	Interval (MD)	lb/gal	Viscosity	Fluid Loss
fresh water spud	0' - 1000'	8.3	28	NC
brine water	1000' - 5600'	10.0	30-32	NC
fresh water & cut brine	5600' - 13972'	9.0	30-32	NC

6. CORES, TESTS, & LOGS

No core or drill stem test is planned.

A 2-person mud logging program will be used from ≈5600' to TD.

No electric logs are planned at this time. GR will be collected through the MWD tools from intermediate casing to TD. CBL with CCL will be run as far as gravity will let it fall to TOC.

7. DOWN HOLE CONDITIONS

No abnormal pressure or temperature is expected. Maximum expected bottom hole pressure is ≈5000 psi. Expected bottom hole temperature is ≈130° F.

Matador does not anticipate that there will be enough H₂S to meet BLM's Onshore Order 6 requirements for submitting an "H₂S Drilling Operation Plan" or "Public Protection Plan" for drilling and completing this well. Matador has an H₂S safety package on all wells and an "H₂S Drilling Operations Plan" is attached. Adequate flare lines will be installed off the mud/gas separator where gas may

Matador Production Company
Biggers Fed Com 24H
SHL 90' FSL & 1226' FEL
BHL 240' FNL & 994' FEL
Sec. 18, T. 25 S., R. 35 E., Lea County, NM

DRILL PLAN PAGE 5

be flared safely. All personnel will be familiar with all aspects of safe operation of equipment being used.

8. OTHER INFORMATION

Anticipated spud date is upon approval. It is expected it will take $\approx$ 2 months to drill and complete the well.


Matador Production Company owns the majority working interest in this well. Per its discussions with its potential partners, Matador will be named operator upon execution of the final Operating Agreements signed by the partners or the issuance of a pooling order by the State.

TOP OF PAD ELEVATION: 3334.7'

CUT SLOPE: 33.33% 3.00:1 18.43°
FILL SLOPE: 33.33% 3.00:1 18.43°
BALANCE TOLERANCE (C.Y.): 0.00
CUT SWELL FACTOR: 1.00
FILL SHRINK FACTOR: 1.00

PAD EARTHWORK VOLUMES
CUT: 79,304.6 C.F., 2,937.21 C.Y.
FILL: 79,304.4 C.F., 2,937.20 C.Y.
BALANCE EXPORT: 0.2 C.F., 0.01 C.Y.
AREA: 166088.8 SQ.FT., 3.813 ACRES

SECTIONS 18 & 19, TOWNSHIP 25-S, RANGE 35-E, N.M.P.M.
LEA COUNTY, NEW MEXICO



TOPOGRAPHIC
LOYALTY INNOVATION LEGACY

1400 EVERMAN PARKWAY, Ste. 197 • FT. WORTH, TEXAS 76140
TELEPHONE: (817) 744-7512 • FAX (817) 744-7548
TEXAS FIRM REGISTRATION NO. 10042504
WWW.TOPOGRAPHIC.COM

Horizontal Scale = 1:60
Vertical Scale = 1:15



MAP 9

Michael Blake Brown, P.S. No. 18329

NOVEMBER 03, 2016

Field note description of even date accompanies this plat.

BIGGERS FED COM SURFACE PAD SITE PROFILE	REVISION:		NOTES: 1. ORIGINAL DOCUMENT SIZE: 8.5" X 11" 2. ALL BEARINGS, DISTANCES, AND COORDINATE VALUES CONTAINED HEREIN ARE GRID BASED UPON THE NEW MEXICO STATE PLANE COORDINATE SYSTEM, EAST ZONE, U.S. SURVEY FEET, NORTH AMERICAN DATUM 1927. 3. CERTIFICATION IS MADE ONLY TO THE LOCATION OF THIS EASEMENT, IN RELATION TO THE EVIDENCE FOUND DURING A FIELD SURVEY, MADE ON THE GROUND, UNDER MY SUPERVISION, AND USING DOCUMENTATION PROVIDED BY MATADOR RESOURCE COMPANY. ONLY UTILITIES/EASEMENTS THAT WERE VISIBLE ON THE DATE OF THIS SURVEY, WITHIN/ADJOINING THIS EASEMENT, HAVE BEEN LOCATED AS SHOWN HEREON OF WHICH I HAVE KNOWLEDGE. THIS CERTIFICATION IS LIMITED TO THOSE PERSONS OR ENTITIES SHOWN ON THE FACE OF THIS PLAT AND IS NON-TRANSFERABLE, AND MADE FOR THIS TRANSACTION ONLY.
	MML	11/03/16	
DATE: 10/03/16			
FILE: CD BIGGERS FED COM 203H SURFACE PAD SITE PRO REV1			
DRAWN BY: GJU			
SHEET : 2 OF 2			

Matador Production Company
Biggers Fed Com 24H
SHL 90' FSL & 1226' FEL
BHL 240' FSL & 994' FEL
Sec. 18, T. 20 S., R. 35 E., Lea

HOBBS OCD

FEB 15 2018

RECEIVED

SURFACE PLAN PAGE 1

Surface Use Plan

1. ROAD DIRECTIONS & DESCRIPTIONS (See MAPS 1 - 5)

From the junction of NM 18 and NM 128 in Jal...

Go West 13.8 miles on NM 128 to the equivalent of Mile Post 38.7

Then turn left and go South 4.3 miles on a caliche road to a T-junction

Then turn left and go Southeast 2/3 mile on a caliche road

Then turn left and go Northeast 579.65' cross-country to the SW pad corner

Non-state roads will be maintained as needed to Gold Book standards. This includes pulling ditches, preserving the crown, and cleaning culverts and cattle guards. This will be done at least once a year, and more often as needed.

2. ROAD TO BE BUILT OR UPGRADED (See MAPS 4 & 5)

The 579.65' of new resource road will be crowned and ditched, have a 14' wide driving surface, and be surfaced with caliche. Maximum disturbed width = 30'. Maximum grade = 1%. Maximum cut or fill = 2'. No culvert, cattle guard, or vehicle turn out is needed. Upgrading will consist of patching potholes with caliche.

3. EXISTING WELLS (See MAP 3)

Existing water and P & A wells are within a mile. No oil, gas, disposal, or injection wells are within a mile radius.

Matador Production Company

SURFACE PLAN PAGE 2

Biggers Fed Com 24H

SHL 90' FSL & 1226' FEL

BHL 240' FSL & 994' FEL

Sec. 18, T. 20 S., R. 35 E., Lea County, NM

4. PROPOSED PRODUCTION FACILITIES

Tank battery and related production equipment will be on the south and east sides of the pad. Gas line and power line plans have not been formulated.

5. WATER SUPPLY (See MAP 2)

Water will be trucked from Madera's existing water stations on private land in NWNE 21-24s-34e, SESW 30-24s-34e, and NENE 8-25s-35e.

6. CONSTRUCTION MATERIALS & METHODS (See MAP 2)

NM One Call (811) will be notified before construction starts. Top ~6" of soil and brush will be stockpiled west of the pad. V-door will face south. Closed loop drilling system will be used. Caliche will be hauled from existing caliche pits on private land (Destiny pit in NENE 4-25s-35e and Madera pit in SENW 6-25s-35e).

7. WASTE DISPOSAL

All trash will be placed in a portable trash cage. It will be hauled to the Lea County landfill. There will be no trash burning. Contents (drill cuttings, mud, salts, and other chemicals) of the mud tanks will be hauled to R360's state approved (NM-01-0006) disposal site at Halfway. Human waste will be disposed of in chemical toilets and hauled to the Jal wastewater treatment plant.

8. ANCILLARY FACILITIES

There will be no airstrip or camp. Camper trailers will be on location for the company man, tool pusher, and mud logger.

Matador Production Company

SURFACE PLAN PAGE 3

Biggers Fed Com 24H

SHL 90' FSL & 1226' FEL

BHL 240' FSL & 994' FEL

Sec. 18, T. 20 S., R. 35 E., Lea County, NM

9. WELL SITE LAYOUT (See MAPS 6 & 7)

Also see Rig Layout diagram for depictions of the well pad, trash cage, access onto the location, parking, living facilities, and rig orientation.

10. RECLAMATION (See MAPS 8 & 9)

Interim reclamation will be completed within 6 months of completing the last well on the pad. Interim reclamation will consist of shrinking the pad $\approx 33\%$ (1.22 acre) by removing caliche and reclaiming swaths on the west and north sides of the pad. This will leave 2.43 acres for the production equipment (e. g., tank battery, heater-treaters, flare), pump jacks, and tractor-trailer turn around. Disturbed areas will be contoured to match pre-construction grades. Soil and brush will be evenly spread over disturbed areas and harrowed on the contour. Disturbed areas will be seeded in accordance with BLM requirements.

Enough stockpiled topsoil will be retained to cover the remainder of the pad when the last well is plugged. Once the last well is plugged, then the rest of the pad will be similarly reclaimed within 6 months of plugging. Noxious weeds will be controlled. Land use:

579.65' x 30' new road =	0.40 acre
+ 370' x 430' pad =	3.65 acres
	4.05 acres short term
- 1.22 acre interim pad reclamation	
	2.83 acres long term

11. SURFACE OWNER

All construction will be on BLM.

Matador Production Company

SURFACE PLAN PAGE 4

Biggers Fed Com 24H

SHL 90' FSL & 1226' FEL

BHL 240' FSL & 994' FEL

Sec. 18, T. 20 S., R. 35 E., Lea County, NM

12. OTHER INFORMATION

On site inspection was held with Vance Wolf on October 27, 2016 and with Vance Wolf, Kelly Reid, and Stan Allison (all BLM) on November 30, 2016.

Lone Mountain filed archaeology report NMCRIS-138616 on July 28, 2017.

Matador Production Company

SURFACE PLAN PAGE 5

Biggers Fed Com 24H


SHL 90' FSL & 1226' FEL

BHL 240' FSL & 994' FEL

Sec. 18, T. 20 S., R. 35 E., Lea County, NM

CERTIFICATION

I hereby certify that I, or someone under my direct supervision, have inspected the drill site and access route proposed herein; that I am familiar with the conditions which currently exist; that I have full knowledge of state and Federal laws applicable to this operation; that the statements made in this APD package are, to the best of my knowledge, true and correct; and that the work associated with the operations proposed herein will be performed in conformity with this APD package and the terms and conditions under which it is approved. I also certify that I, or the company I represent, am responsible for the operations conducted under this application. These statements are subject to the provisions of 18 U. S. C. 1001 for the filing of false statements. Executed this 4th day of August, 2017.



Brian Wood, Consultant

Permits West, Inc.

37 Verano Loop, Santa Fe, NM 87508

(505) 466-8120

FAX: (505) 466-9682

Cellular: (505) 699-2276

Field representative will be:

Sam Pryor, Senior Staff Landman

Matador Production Company

5400 LBJ Freeway, Suite 1500

Dallas TX 75240

Phone: (972) 371-5241

FAX: (214) 866-4841