

Fulfer oil State I # 4

Location:	
Footage:	
Section:	N-SEC 16-T20S-R37E
Block:	
Township:	
Survey:	
County:	Lea
Lat:	
Long:	
Elevations:	
GL	NA
KB	
KB Calc:	
ck w/log?	

[illegible]

Tubing Detail (top to bottom)			
Joints	Description	Footage	Depth
183	2-7/8" I80 tubing	6,033.00	6,033.00
1	5-1/2"x2-7/8" BakerbTAC	3.00	6,036.00
12	2-7/8" L80 tubing	396.00	6,432.00
1	seat nipple	1.10	6,433.10
1	2-7/8" perf sub	4.00	6,437.10
1	mud anchor	31.00	6,468.10
		0.00	6,468.10
		0.00	6,468.10
		0.00	6,468.10
		0.00	6,468.10
		0.00	6,468.10
		6,468.10	6,468.10

Rod Detail (top to bottom)			
Rods	Description	Footage	Depth
1	polish rod	26.00	26.00
2	7/8" x4' pony rod	8.00	34.00
84	7/8" sucker rods	2,100.00	2,134.00
172	3/4" sucker rods	4,275.00	6,409.00
1	2-1/2"-1/2x1 5x20 pump	20.00	6,429.00
			6,429.00
			6,429.00
			6,429.00
			6,429.00
		6,429.00	0.00

Updated:	By:
4/13/18	Mike Dennis

PROPOSED
Wellbore Diagram

Field:

30-025-34954

spud date 7/05/01 re entry

Hole Size:	12-1/4" inches	
Surface Casing:	8-5/8" OD 32# J55	
Set @	1,207 ft	
Cement Lead:	644 sx	
	ppg	cf/sk
Cement Tail:	644	
TOC:	Surface	Circulated

FLINTCOAT:	NA	--	Casing Tally
------------	----	----	--------------

Est TOC: 2,546 ft CBL Wire Line

Short Joint: NA -- Wire LineShort Joint: NA Wire Line

tac 6036

seat nipple 6433.10

BOT 6468.00

HOBBS OCD
APR 12 2018
RECEIVED

Hole Size:	7-7/8"	inches
Prod. Csg:	5-1/2"	OD 15 50 & 17#
Set @:	7.712	ft
Cmt: Lead:	1380	sx Poz C
Lead info:	ppg	cf/sk
Tail:	sx	Poz H
Tail info:	ppg	cf/sk