

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised August 1, 2011

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-025-25887
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Quail Queen Unit
8. Well Number: 9
9. OGRID Number 4323
10. Pool name or Wildcat Quail, Queen
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3973' GL

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐	
2. Name of Operator Chevron USA, Inc.	
3. Address of Operator 6301 Deauville Blvd., Midland, TX 79706	
4. Well Location Unit Letter B : 600 feet from the NORTH line and 1980 feet from the EAST line Section 11 Township 19S Range 34E NMPM County Lea	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3973' GL	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBS	
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☒	REMEDIAL WORK ☐	ASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILL ☐	
PULL OR ALTER CASING ☐	MULTIPLE COMPL ☐	CASING/CEMENT ☐	
DOWNHOLE COMMINGLE ☐			
OTHER: ☐		OTHER: ☐	

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 13 3/8" 48# @ 30': TOC @ surface; 8 5/8" 24# @ 1898': TOC @ surface; 4 1/2" 11.6# @ 5380': TOC @ unknown

Chevron USA INC respectfully request to abandon this well as follows:

1. MIRU, pull rods, NU BOP, pull tubing
2. Set CIBP @ 4950', circulate well w/ 9.5 ppg gel KCl water, and pressure test casing t/ 500 psi for 10 min. If casing pressure tests, then RDMO rig and MIRU coil tubing unit to complete rest of P&A
3. Run CBL to verify TOC on 4 1/2" and if any spots need to be turned into perf & squeezes
4. Spot 25 sx CL "C" cement plug f/ 4950' t/ 4615' (Queen). If pressure test in Step 2 failed, then WOC & tag, and pressure test again. If pressure test in Step 2 was successful, then do not WOC & tag.
5. Based on CBL, Spot 30 sx plug or Perf & Squeeze 120 sx CL "C" cement f/ 3610' t/ 3195' (Yates, B. Salt).
6. Based on CBL, Spot 25 sx plug or Perf & Squeeze 120 sx CL "C" cement f/ 2025' t/ 1685' (T. Salt, Shoe, Anhydrite). WOC & TAG
7. Based on CBL, Spot 25 sx plug or Perf & Squeeze 120 sx CL "C" cement f/ 350' t/ surface. Verify TOC @ surface
8. Cut all casings & anchors & remove 3' below grade. Weld on dry hole marker. Clean location.
9. All cement plugs class "C" with closed loop system used.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE [Signature] TITLE Well Abandonment Engineer DATE 05/03/2018

Type or print name Nick Glann E-mail address: nglann@chevron.com PHONE: 432-687-7786

For State Use Only

APPROVED BY: [Signature] TITLE Petroleum Engr. Specialist DATE 05/08/2018

Conditions of Approval (if any):

NOTIFY OCD 24 HOURS PRIOR TO
BEGINNING PLUGGING OPERATIONS

C103 INTENT TO P&A EXPIRES
1 YEAR FROM DATE OF APPROVAL

Quail Queen #9 Current Wellbore Diagram (UCAL5)

Well----- Quail Queen #9
 Field----- Quail
 County----- Lea
 State----- New Mexico
 Chevro----- EQ1095
 API #----- 30-025-25887
 Status----- SI
 Battery

Surf. Loc----- 600' FNL & 1980' FEL
 Lat & Long----- 32.6799900, -103.5282200
 Section----- 11
 Township & Range 19S & 34E
 Spud Date----- 3/29/1978

13-3/8", @ 30' (48#)
 CMT CIRC (18" HOLE)

8-5/8", @ 1,898' (J-55 24#)
 CMT CIRC (11" HOLE)

Formation Tops
 Anhydrite 1852'
 T. Salt 1975'
 B. Salt 3295'
 Yates 3560'
 Queen 4715'

Tubing String Quantity (Top-Bottom Depth) Desc
 160 @ (10-5067) Unknown Grade/Thread/Weight 2 375 OD-
 1 @ (5067-5068) Seat Nipple - Standard (2 375) Cup Type-
 1 @ (5068-5072) Tubing Perforation-
 1 @ (5068-5072) Unknown Grade/Thread/Weight 2 375 OD-
 1 @ (5068-5072) Unknown Grade/Thread/Weight 2 375 OD-
 1 @ (5068-5072) Unknown Grade/Thread/Weight 2 375 OD-
 1 @ (5068-5072) Perforated Tubing Sub 2 375-
 20 @ (5072-5102) Unknown Grade/Thread/Weight 2 375 OD-
 1 @ (5102-5103) Bull Plug (Unknown Type) - 2 375-

Rod String Quantity (Top-Bottom Depth) Desc
 1 @ (10-32) 1 250 (1 1/4 in) Spray Metal x 22-
 1 @ (32-36) 0 875 (7/8 in) D x 4 Rod Sub-
 51 @ (36-1311) 0 875 (7/8 in) D x 25 Rod-
 151 @ (1311-5086) 0 750 (3/4 in) D x 25 Rod-
 1 @ (5086-5102) Rod Pump (Insert) (NON-SERIALIZED) - 20-125-R W BC -0-0
 (Bore = 1 25)-
 1 @ (5102-5108) Gas Anchor (Rod) 1 000 OD x 6-

QUEEN PERF DETAIL

4,982'-4,986' (8 holes)
 4,988'-4,992' (8 holes)
 5,034'-5,038' (8 holes)

TD @ 5,380'

4-1/2", @ 5,380' (J-55 10.5# & 11 6#)
 TOC UNKNOWN (7-7/8" HOLE)

Quail Queen #9 Proposed Wellbore Diagram (UC)

Well----- Quail Queen #9
 Field----- Quail
 County----- Lea
 State----- New Mexico
 Chevro----- EQ1095
 API #----- 30-025-25887
 Status----- SI
 Battery-----

Surf. Loc----- 600' FNL & 1980' FEL
 Lat & Long----- 32.6799900, -103.5282200
 Section----- 11
 Township & Range 19S & 34E
 Spud Date----- 3/29/1978

13-3/8", @ 30' (48#)
 CMT CIRC (18" HOLE)

Spot 25 sx or P/S 120 sx CL C cmt f/ 350' t/ surface (Fresh Water)

8-5/8", @ 1,898' (J-55 24#)
 CMT CIRC (11" HOLE)

Spot 25 sx or P/S 120 sx CL C cmt f/ 2025' t/ 1685' (T. Salt, Shoe, Anhydrite)

Formation Tops
 Anhydrite 1852'
 T. Salt 1975'
 B. Salt 3295'
 Yates 3560'
 Queen 4715'

Spot 30 sx or P/S 120 sx CL C cmt f/ 3610' t/ 3195' (Yates, B. Salt)

QUEEN PERF DETAIL
 4,982'-4,986' (8 holes)
 4,988'-4,992' (8 holes)
 5,034'-5,038' (8 holes)

Spot 25 sx CL C cmt f/ 4950' t/ 4615' (Queen)
 Set CIBP @ 4950'

TD @ 5,380'

4-1/2", @ 5,380' (J-55 10.5# & 11.6#)
 TOC UNKNOWN (7-7/8" HOLE)

