

Submit To Appropriate District Office Two Copies District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87401 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505		State of New Mexico Energy, Minerals and Natural Resources  Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505				Form C-105 Revised August 1, 2011					
1. WELL API NO. 30-025-44309											
2. Type of Lease <input checked="" type="checkbox"/> STATE <input type="checkbox"/> FEE <input type="checkbox"/> FED/INDIAN											
3. State Oil & Gas Lease No.											
<b>WELL COMPLETION OR RECOMPLETION REPORT AND LOG</b>											
4. Reason for filing:  <input checked="" type="checkbox"/> <b>COMPLETION REPORT</b> (Fill in boxes #1 through #31 for State and Fee wells only)  <input type="checkbox"/> <b>C-144 CLOSURE ATTACHMENT</b> (Fill in boxes #1 through #9, #15 Date Rig Released and #32 and/or #33; attach this and the plat to the C-144 closure report in accordance with 19.15.17.13.K NMAC)						5. Lease Name or Unit Agreement Name South Hobbs G/SA Unit					
7. Type of Completion: <input checked="" type="checkbox"/> NEW WELL <input type="checkbox"/> WORKOVER <input type="checkbox"/> DEEPENING <input type="checkbox"/> PLUGBACK <input type="checkbox"/> DIFFERENT RESERVOIR <input type="checkbox"/> OTHER						6. Well Number:  294					
8. Name of Operator Occidental Permian LTD						9. OGRID 157984					
10. Address of Operator P.O. Box 4294 Houston, TX 77210						11. Pool name or Wildcat Hobbs; Grayburg - San Andres					
12. Location	Unit Ltr	Section	Township	Range	Lot	Feet from the	N/S Line	Feet from the	E/W Line	County	
Surface:	O	6	19S	38E		341	S	2308	E	LEA	
BH:											
13. Date Spudded 02/25/2018	14. Date T.D. Reached 02/28/2018	15. Date Rig Released 03/02/2018		16. Date Completed (Ready to Produce) 03/28/2018		17. Elevations (DF and RKB, RT, GR, etc.) 3618' GR					
18. Total Measured Depth of Well 5566		19. Plug Back Measured Depth 4650		20. Was Directional Survey Made? No		21. Type Electric and Other Logs Run Compensated Neutron Log					
22. Producing Interval(s), of this completion - Top, Bottom, Name 4414 - 4612 San Andres											
<b>23. CASING RECORD (Report all strings set in well)</b>											
CASING SIZE		WEIGHT LB./FT.		DEPTH SET		HOLE SIZE		CEMENTING RECORD		AMOUNT PULLED	
9 5/8		36		1613		12 5/8		Cl. C 600 sx		0	
7		26		5551		8 3/4		Cl. C 635 sx		0	
7		26		3979 DV Tool		8 3/4		Cl. C 815 sx		0	
24. LINER RECORD						25. TUBING RECORD					
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN		SIZE	DEPTH SET	PACKER SET			
						2 7/8	4389'				
26. Perforation record (interval, size, and number) 4414 - 4612						27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.					
						DEPTH INTERVAL		AMOUNT AND KIND MATERIAL USED			
						4414 - 4612		acid job w/ 7400 gals 15% IC200			
<b>28. PRODUCTION</b>											
Date First Production 04/07/2018		Production Method (Flowing, gas lift, pumping - Size and type pump) ESP				Well Status (Prod. or Shut-in) Producing					
Date of Test 04/07/2018	Hours Tested 24	Choke Size	Prod'n For Test Period	Oil - Bbl 7	Gas - MCF 107	Water - Bbl 765	Gas - Oil Ratio 15286				
Flow Tubing Press.	Casing Pressure	Calculated 24-Hour Rate	Oil - Bbl 7	Gas - MCF 107	Water - Bbl 765	Oil Gravity - API - (Corr.) 32					
29. Disposition of Gas (Sold, used for fuel, vented, etc.) Produced gas is reinjected as a part of the South Hobbs Unit CO2 flood								30. Test Witnessed By			
31. List Attachments C102, C104, Inclination Report, Logs											
32. If a temporary pit was used at the well, attach a plat with the location of the temporary pit.											
33. If an on-site burial was used at the well, report the exact location of the on-site burial:											
				Latitude		Longitude		NAD 1927 1983			
I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief											
Signature		Printed Name			Title		Date				
April Hood		April Hood			Regulatory Specialist		04/30/2018				
E-mail Address april_hood@oxy.com											

SHU 294

## INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well and not later than 60 days after completion of closure. When submitted as a completion report, this shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 11, 12 and 26-31 shall be reported for each zone.

### INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy		T. Canyon	T. Ojo Alamo
T. Rustler	1597	T. Strawn	T. Kirtland
B. Salt	1654	T. Atoka	T. Fruitland
T. Yates	2932	T. Miss	T. Pictured Cliffs
T. 7 Rivers	3151	T. Devonian	T. Cliff House
T. Queen	3704	T. Silurian	T. Menefee
T. Grayburg	4053	T. Montoya	T. Point Lookout
T. San Andres	4341	T. Simpson	T. Mancos
T. Glorieta		T. McKee	T. Gallup
T. Paddock		T. Ellenburger	Base Greenhorn
T. Blinebry		T. Gr. Wash	T. Dakota
T. Tubb		T. Delaware Sand	T. Morrison
T. Drinkard		T. Bone Springs	T. Todilto
T. Abo		T.	T. Entrada
T. Wolfcamp		T.	T. Wingate
T. Penn		T.	T. Chinle
T. Cisco (Bough C)		T.	T. Permian

### OIL OR GAS SANDS OR ZONES

No. 1, from.....to..... No. 3, from.....to.....  
 No. 2, from.....to..... No. 4, from.....to.....

### IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....  
 No. 2, from.....to.....feet.....  
 No. 3, from.....to.....feet.....

### LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology	From	To	Thickness In Feet	Lithology
1597	1654	57	Anhydrite and red shales				
1654	2932	1278	Salt section with anhydrite stringers and some shales				
2932	3151	219	Interbedded brown-red-gray soft shale, fine sand, anhydrite, and reddish-brown salt stringers				
3151	3704	553	Mainly gray, dense anhydrite interbedded with occasional red shale and red-gray sandstone				
3704	4053	349	Upper 1/4 mainly red-gray, slightly anhydritic silty sand. Lower 3/4 mainly anhydrite with interbedded red-gray shale and tan anhydritic dolomite				
4053	4341	288	Interbedded brown-gray silty dolomite, shale, sand, and thin anhydrite stringers				
4341			Dolomite with rare silty sandstone, rare anhydrite				