

Submit 1 Copy To Appropriate District
Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-025-44672
1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐		5. Indicate Type of Lease STATE ☒ FEE ☐
2. Name of Operator EOG Resources, Inc.		6. State Oil & Gas Lease No.
3. Address of Operator P.O. Box 2267 Midland, TX 79702		7. Lease Name or Unit Agreement Name Condor 32 State
4. Well Location Unit Letter C : 843 feet from the North line and 2523 feet from the West line Section 32 Township 25S Range 34E NMPM County Lea		8. Well Number 711H (511H)
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3321' GR		9. OGRID Number 7377
		10. Pool name or Wildcat Hardin Tank; Bone Spring

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☒
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
CLOSED-LOOP SYSTEM ☐
OTHER: ☐ Change BHL, TVD ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

EOG Resources requests an amendment to our approved APD for this well to reflect changes in BHL, TVD, casing and well number.

Change BHL to: 230' FSL & 2315' FEL O-32-25S-34E

Change TVD to: 11046' 2nd BS Sand

Change casing as attached.

Change well name/number to: Condor 32 State 511H

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Stan Wagner TITLE Regulatory Analyst DATE 5/17/2018

Type or print name Stan Wagner E-mail address: _____ PHONE: 432-686-3689

For State Use Only

APPROVED BY: [Signature] TITLE Petroleum Engineer DATE 05/29/18

Conditions of Approval (if any): _____

Revised Permit Information 5/15/18:

Well Name: Condor 32 State No. 511H

Location:

SL: 843' FNL & 2523' FWL, Section 32, T-25-S, R-34-E, Lea Co., N.M.

BHL: 230' FSL & 2315' FEL, Section 32, T-25-S, R-34-E, Lea Co., N.M.

Casing Program:

Hole Size	Interval	Csg OD	Weight	Grade	Conn	DF _{min} Collapse	DF _{min} Burst	DF _{min} Tension
17.5"	0 - 860'	13.375"	54.5#	J55	STC	1.125	1.25	1.60
12.25"	0-4,000'	9.625"	40#	J55	LTC	1.125	1.25	1.60
12.25"	4,000' - 5,100'	9.625"	40#	HCK55	LTC	1.125	1.25	1.60
8.75"	0'-15,882'	5.5"	17#	HCP-110	LTC	1.125	1.25	1.60

Cement Program:

Depth	No. Sacks	Wt. lb/gal	Yld Ft ³ /ft	Slurry Description
840'	600	13.5	1.74	Lead: Class 'C' + 4.00% Bentonite + 2.00% CaCl ₂ (TOC @ Surface)
	300	14.8	1.35	Tail: Class 'C' + 0.6% FL-62 + 0.25 lb/sk Cello-Flake + 0.2% Sodium Metasilicate + 2.0% KCl (1.06 lb/sk)
5,100'	900	12.7	2.22	Lead: Class C + 0.15% C-20 + 11.63 pps Salt + 0.1% C-51 + 0.75% C-41P (TOC @ Surface)
	225	14.8	1.32	Tail: Class C + 0.13% C-20
15,882'	900	14.8	1.31	Class H + 0.1% C-20 + 0.05% CSA-1000 + 0.20% C-49 + 0.40% C-17 (TOC @ 4,600')

Mud Program:

Depth	Type	Weight (ppg)	Viscosity	Water Loss
0 - 860'	Fresh - Gel	8.6-8.8	28-34	N/c
860' - 5,100'	Brine	10.0-10.2	28-34	N/c
5,100' - 15,882' Lateral	Oil Base	10.0-11.5	58-68	3 - 6

HOBBS OCD
MAY 29 2018
RECEIVED

Condor 32 State #511H
Lea County, New Mexico

843' FNL
2523' FWL
Section 32
T-25-S, R-34-E

Proposed Wellbore
Revised 5/15/18
API: 30-025-44672

KB: 3,345'
GL: 3,320'

Bit Size: 17-1/2"

13-3/8", 54.5#, J-55, LTC 0' - 860'

Bit Size: 12-1/4"

9-5/8", 40#, J-55, LT&C 0' - 4,000'
9-5/8", 40#, HCK55, LT&C 4,000' - 5,100'

Bit Size: 8-3/4"

5-1/2", 17#, HCP-110, LTC @ 0' - 15,882'

TOC: 4,600'

KOP: 10,570'

Bit Size: 8-3/4"

HOEDS OGD
MAY 29 2018
RECEIVED

Lateral: 15,882' MD, 11,046' TVD

BH Location: 230' FSL & 2315' FEL
Section 32
T-25-S, R-34-E