

Submit 1 Copy To Appropriate District Office

District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised August 1, 2011

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-025-31549
1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐		5. Indicate Type of Lease STATE ☒ FEE ☐
2. Name of Operator Chevron USA INC Midcontinent, L.P.		6. State Oil & Gas Lease No.
3. Address of Operator 6301 DEAUVILLE BLVD., MIDLAND, TX 79706		7. Lease Name or Unit Agreement Name Lovington San Andres Unit
4. Well Location Unit Letter F : 1472 feet from the North line and 1520 feet from the West line Section 1 Township 17S Range 36E NMPM County Lea		8. Well Number: 83
11. Elevation (Show whether DR, RKB, RT, GR, etc.) GR 3,831' KB 3,847'		9. OGRID Number 241333
		10. Pool name or Wildcat Lovington Grayburg San Andres

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBS	
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☒	REMEDIAL WORK ☐	SING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRIL ☐	
PULL OR ALTER CASING ☐	MULTIPLE COMPL ☐	CASING/CEMENT ☐	
DOWNHOLE COMMINGLE ☐			
OTHER: ☐		OTHER: ☐	

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 8-5/8" 24# @ 1,325' TOC Surface, 5-1/2" 15.5# @ 5,120' TOC Surface, Perforations: 4,630'-5,056'.

Chevron USA INC respectfully request to abandon this well as follows:

- Call and notify NMOCD 24 hrs before operations begin.
- MIRU pulling unit, N/U BOP, Pull ESP and tubing. Verify pressure on surface casing with bubble test if no pressure registers on a low-pressure gauge. Discuss results with engineer.
- Set CIBP @ 4,600', spot MLF, pressure test casing to 500 psi f/ 10 minutes, spot 35 sx CL "C" cmt f/ 4,600' t/ 4,254', WOC & tag only if casing does not test (Perfs, Grayburg).
- Spot 90 sx CL "C" cmt f/ 3,740' t/ 2,851' (Queen, 7 Rivers, Yates, Salt).
- Spot 140 sx CL "C" cmt f/ 1,375' t/ Surface (Shoe, FW).
- Once the P&A is complete, cut all casings & anchors & remove 3' below grade. Verify cement to surface weld on dry hole marker. Clean location.

Note: All cement plugs class "C" with closed loop system used.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE [Signature] TITLE Well Abandonment Engineer, Attorney-in-fact DATE 6/2/18

Type or print name Howie Lucas E-mail address: howie.lucas@chevron.com PHONE: (832)-588-4044

For State Use Only

APPROVED BY: [Signature] TITLE Petroleum Engr. Specialist DATE 06/05/2018
Conditions of Approval (if any):

C103 INTENT TO P&A EXPIRES
1 YEAR FROM DATE OF APPROVAL

LSAU 83 WELLBORE DIAGRAM

Created: 08/07/17 By: MKHS
 Updated: By:
 Lease: Lovington San Andres Unit
 Field: Lovington Field
 Surf. Loc.: 1520' FWL and 1472' FNL
 Bot. Loc.:
 County: Lea St.: NM
 Status: Shut-In Oil

Well #: 83 St. Lse:
 API 30-025-31549
 Unit Ltr.: O Section: 1
 TSHP/Rng: 17S / 36E
 Unit Ltr.: Section:
 TSHP/Rng:
 Directions: Lovington, NM
 Chevno: OV6199

Surface Casing


Size: 8-5/8"
 Wt., Grd.: 24#
 Depth: 1325'
 Sxs Cmt: 550sx 'C'
 Circulate: Y
 TOC: Surface
 Hole Size: 12-1/4"

KB: 3847'
 DF:
 GL: 3831'
 Ini. Spud: 05/10/92
 Ini. Comp.: 06/11/92

Formation Tops	
Salt	2983'
Yates	3030'
7 Rivers	3277'
Queen	3690'
Grayburg	4387'
San Andres	4597'

Production Casing

Size: 5-1/2"
 Wt., Grd.: 15.5#
 Depth: 5120'
 Sxs Cmt: 1075sx 'C'
 Circulate: Y
 TOC: Surface
 Hole Size: 7-7/8"



J-55 2.875 OD/ 6.50# T&C
 External Upset 2.441 ID 2.347
 Drift New Yellow Band Tubing
 J-55 2.875 OD/ 6.50# T&C
 External Upset 2.441 I @ (4520)

Drain Valve @ (4489)
 ESP Pump (Non-Serialized/Centrilift) 178
 stages, TYPE FC-925, FPLT (NEW)
 @ (4520-4536)
 Check Valve @ (4536)
 ESP Bolt on Intake
 (Non-Serialized/Centrilift) INTERGRAL
 (NEW) @ (4537-4538)
 ESP Seal (Non-Serialized/Centrilift) FSB3
 FER PFS HL (NEW) @ (4538-4544)
 ESP Motor (Non-Serialized/Centrilift) 62HP,
 1170 VOLTS, 35 AMP, FMH (NEW)

San Andres Perfs: 4630-5056'

PBTD: 5074'
 TD: 5120'

LSAU 83 WELLBORE DIAGRAM

Created:	08/07/17	By:	MKHS	Well #:	83	St. Lse:	
Updated:		By:		API	30-025-31549		
Lease:	Lovington San Andres Unit			Unit Ltr.:	O	Section:	1
Field:	Lovington Field			TSHR/Rng:	17S / 36E		
Surf. Loc.:	1520' FWL and 1472' FNL			Unit Ltr.:		Section:	
Bot. Loc.:				TSHR/Rng:			
County:	Lea	St.:	NM	Directions:	Lovington, NM		
Status:	Shut-In Oil			Chevno:	OV6199		

Verify Cement to Surface

Surface Casing

Size:	8-5/8"
Wt., Grd.:	24#
Depth:	1325'
Sxs Cmt:	550sx 'C'
Circulate:	Y
TOC:	Surface
Hole Size:	12-1/4"

KB:	3847'
DF:	
GL:	3831'
Ini. Spud:	05/10/92
Ini. Comp.:	06/11/92

Formation Tops	
Salt	2983'
Yates	3030'
7 Rivers	3277'
Queen	3690'
Grayburg	4387'
San Andres	4597'

Production Casing

Size:	5-1/2"
Wt., Grd.:	15.5#
Depth:	5120'
Sxs Cmt:	1075sx 'C'
Circulate:	Y
TOC:	Surface
Hole Size:	7-7/8"

3 Spot 140 sx CL "C" cmt f/ 1,375' t/ surface
(Shoe, FW)

2 Spot 90 sx CL "C" cmt f/ 3,740' t/ 2,851'
(Queen, 7 Rivers, Yates, Salt)

1 MIRU, Pull ESP, set CIBP @ 4,600', spot MLF
test csg t/ 500 psi f/ 10 min, spot 35 sx CL "C" cmt
f/ 4,600' t/ 4,254', WOC & tag only if csg did not test
(Perfs, Grayburg)

San Andres Perfs: 4630-5056'

PBTD:	5074'
TD:	5120'