

Permit Information:

Well Name: Thor 21 No. 770H

Location:

SL: 670' FSL & 175' FEL, Section 21, T-26-S, R-33-E, Lea Co., N.M.

BHL: 230' FNL & 660' FEL, Section 21, T-26-S, R-33-E, Lea Co., N.M.

Casing Program:

Hole Size	Interval	Csg OD	Weight	Grade	Conn	DF _{min} Collapse	DF _{min} Burst	DF _{min} Tension
17.5"	0 - 850'	13.375"	54.5#	J55	STC	1.125	1.25	1.60
12.25"	0-4,000'	9.625"	40#	J55	LTC	1.125	1.25	1.60
12.25"	4,000' - 4,800'	9.625"	40#	HCK55	LTC	1.125	1.25	1.60
8.75"	0 - 11,300'	7.625"	29.7#	HCP110	FXL	1.125	1.25	1.60
6.75"	0'-18,411'	5.5"	17#	HCP-110	LTC	1.125	1.25	1.60

Cement Program:

Depth	No. Sacks	Wt. lb/gal	Yld Ft ³ /ft	Slurry Description
850'	600	13.5	1.74	Lead: Class 'C' + 4.00% Bentonite + 2.00% CaCl ₂ (TOC @ Surface)
	300	14.8	1.35	Tail: Class 'C' + 0.6% FL-62 + 0.25 lb/sk Cello-Flake + 0.2% Sodium Metasilicate + 2.0% KCl (1.06 lb/sk)
4,800'	900	12.7	2.22	Lead: Class C + 0.15% C-20 + 11.63 pps Salt + 0.1% C-51 + 0.75% C-41P (TOC @ Surface)
	225	14.8	1.32	Tail: Class C + 0.13% C-20
11,300'	375	10.8	3.67	Lead: Class C + 0.40% D013 + 0.20% D046 + 0.10% D065 + 0.20% D167 (TOC @ 4,300')
	400	14.8	2.38	Tail: Class H + 94.0 pps D909 + 0.25% D065 + 0.30% D167 + 0.02% D208 + 0.15% D800
18,411'	1100	14.8	1.31	Class H + 0.1% C-20 + 0.05% CSA-1000 + 0.20% C-49 + 0.40% C-17 (TOC @ 10,800')

Mud Program:

Depth	Type	Weight (ppg)	Viscosity	Water Loss
0 - 850'	Fresh - Gel	8.6-8.8	28-34	N/c
850' - 4,800'	Brine	10.0-10.2	28-34	N/c
4,800' - 11,300'	Oil Base	8.7-9.4	58-68	N/c - 6
11,300' - 18,411' Lateral	Oil Base	10.0-11.5	58-68	3 - 6

HOBBS OCD
JUN 14 2018
RECEIVED

Thor 21 #770H
Lea County, New Mexico


HOBBS OCD
JUN 14 2018
RECEIVED

670' FSL
175' FEL
Section 21
T-26-S, R-33-E

Proposed Wellbore

API: 30-025-*****

KB: 3,284'
GL: 3,259'



Lateral: 18,411' MD, 13,720' TVD

BH Location: 230' FNL & 660' FEL
Section 21
T-26-S, R-33-E