

Submit 1 Copy To Appropriate District Office
 District I - (575) 393-6161
 1625 N. French Dr., Hobbs, NM 88240
 District II - (575) 748-1283
 811 S. First St., Artesia, NM 88210
 District III - (505) 334-6178
 1000 Rio Brazos Rd., Aztec, NM 87410
 District IV - (505) 476-3460
 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
 Energy, Minerals and Natural Resources

Form C-103
 Revised August 1, 2011

HOBBS OGD

OIL CONSERVATION DIVISION
 20 South St. Francis Dr.
 Santa Fe, NM 87505

RECEIVED

JUL 02 2018

WELL API NO. 30-025-26118
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No. N/A
7. Lease Name or Unit Agreement Name South Hobbs (G/SA) Unit
8. Well Number 123
9. OGRID Number: 157984
10. Pool name or Wildcat: Hobbs (G/SA)

SUNDRY NOTICES AND REPORTS ON WELLS
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well Gas Well Other Temporarily Abandoned

2. Name of Operator
Occidental Permian Ltd.

3. Address of Operator
P.O. Box 4294, Houston, Tx 77210

4. Well Location (Surface)
 Unit Letter H : 2390 feet from the North line and 150 feet from the East line
 Section 6 Township 19S Range 38E NMPM Lea County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3624' (GR)

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

<p>NOTICE OF INTENTION TO:</p> <p>PERFORM REMEDIAL WORK <input type="checkbox"/> PLUG AND ABANDON <input type="checkbox"/></p> <p>TEMPORARILY ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/></p> <p>PULL OR ALTER CASING <input type="checkbox"/> MULTIPLE COMPL <input type="checkbox"/></p> <p>DOWNHOLE COMMINGLE <input type="checkbox"/></p> <p>OTHER: <input checked="" type="checkbox"/> RTP well in San Andres formation</p>	<p>SUBSEQUENT REPORT OF:</p> <p>REMEDIAL WORK <input type="checkbox"/> ALTERING CASING <input type="checkbox"/></p> <p>COMMENCE DRILLING OPNS. <input type="checkbox"/> P AND A <input type="checkbox"/></p> <p>CASING/CEMENT JOB <input type="checkbox"/></p> <p>OTHER: <input type="checkbox"/></p>
--	--

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

- MIRU PU. ND Wellhead. NU BOP.
 - Trip a bit and deepen well ~30' to new TD at ±4320' (within San Andres)
 - Selectively perforate San Andres
 - Design stimulation based on new pay. Stim with 15% HCL at ±50 gal/ft
 - Set RBP at ±3800' and ±1000' and prepare well for wellhead change
- Following wellhead change:
- MIRU PU; Pull plugs
 - RIH with ESP
 - ND BOP. NU Wellhead. RDMO PU. RTP Well

During this procedure we plan to use the closed-loop system with a steel tank and haul contents to the required disposal per ODC Rule 19.15.17

Spud Date: Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jacob S. Cox TITLE Production Engineer DATE 06/30/2018

Type or print name Jacob S. Cox E-mail address: Jacob_Cox@oxy.com PHONE: 713-497-2053

APPROVED BY: Maley Brown TITLE AO/I DATE 7/2/2018

Conditions of Approval (if any):

MB

SOUTH HOBBS UNIT 123 (957257)
 HOBBS GRAYBURG SAN ANDRES FIELD (REVISED 3/90 LPM)
 2390' FNL X 150' FEL, SEC 6, T19S, R38E
 LEA COUNTY, NEW MEXICO

GROUND 3620
 KB 3631
 GRAYBURG SAN ANDRES
 API # 30-025-26118

BOTTOM OF 11.75 IN OD, 42 LB/FT
 @ 1433, CMT W/750 SKS
 CIRC. HOLE SIZE 15 IN

RE: 5.5 IN CIRC 46 SX
 BOTTOM OF 5.5 IN OD LINER
 17 LB/FT , @ 3669, CMT W/575 SKS
 CLASS C
 TOP OF 5.5 IN LINER AT 3669

BOTTOM OF 8.625 IN OD, 32&24 LB/FT
 @ 3907, CMT W/1400 SKS
 CIRC. HOLE SIZE 11 IN

SQUEEZED 3956-4030 →

SQUEEZED 4054-4144 →

PERF 4144-4164 →

SET 5.5 IN CIBP SA 4185 CAP
 X 15 FT CAL SEAL

PBTD AT 4171 FT

COVERED PERFS: 4170-4176, 4188-4198

RE: 5.5 IN HOLE SIZE 7.75 IN

TOTAL DEPTH 4286 FT

BOTTOM OF 5.5 IN OD LINER
 14 LB/FT , @ 4284, CMT W/125 SKS