

PECOS DISTRICT DRILLING CONDITIONS OF APPROVAL

OPERATOR'S NAME:	DEVON ENERGY PRODUCTION
LEASE NO.:	NMNM097151
WELL NAME & NO.:	27H -FLAGLER 8 FED
SURFACE HOLE FOOTAGE:	380'S & 1680'E
BOTTOM HOLE FOOTAGE	330'N & 1605'E
LOCATION:	Section 8.,T25S., R.33E., NMP
COUNTY:	LEA County, New Mexico

Potash	<input checked="" type="radio"/> None	<input type="radio"/> Secretary	<input type="radio"/> R-111-P
Cave/Karst Potential	<input checked="" type="radio"/> Low	<input type="radio"/> Medium	<input type="radio"/> High
Variance	<input type="radio"/> None	<input checked="" type="radio"/> Flex Hose	<input type="radio"/> Other
Wellhead	<input type="radio"/> Conventional	<input checked="" type="radio"/> Multibowl	
Other	<input type="checkbox"/> 4 String Area	<input type="checkbox"/> Capitan Reef	<input type="checkbox"/> WIPP

A. Hydrogen Sulfide

1. Hydrogen Sulfide (H₂S) monitors shall be installed prior to drilling out the surface shoe. If H₂S is detected in concentrations greater than 100 ppm, the Hydrogen Sulfide area shall meet Onshore Order 6 requirements, which includes equipment and personnel/public protection items. If Hydrogen Sulfide is encountered, provide measured values and formations to the BLM.

B. CASING

1. The 13 3/8 inch surface casing shall be set at approximately 1150 feet (a minimum of 25 feet into the Rustler Anhydrite and above the salt) and cemented to the surface.
 - a. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with surface log readout will be used or a cement bond log shall be run to verify the top of the cement. Temperature survey will be run a minimum of six hours after pumping cement and ideally between 8-10 hours after completing the cement job.
 - b. Wait on cement (WOC) time for a primary cement job will be a minimum of **8 hours** or 500 pounds compressive strength, whichever is greater. (This is to include the lead cement)
 - c. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength,

whichever is greater.

- d. If cement falls back, remedial cementing will be done prior to drilling out that string.

Intermediate casing must be kept fluid filled to meet BLM minimum collapse requirement.

2. The minimum required fill of cement behind the 9 5/8 inch intermediate casing is:

- Cement to surface. If cement does not circulate see B.1.a, c-d above.

3. The minimum required fill of cement behind the 5 1/2 inch production casing is:

- Cement should tie-back at least **200** feet into previous casing string. Operator shall provide method of verification. **Excess calculates to 23% - additional cement might be required.**

C. PRESSURE CONTROL

1. Variance approved to use flex line from BOP to choke manifold. Manufacturer's specification to be readily available. No external damage to flex line. Flex line to be installed as straight as possible (no hard bends).
2. **Operator has proposed a multi-bowl wellhead assembly. This assembly will only be tested when installed on the surface casing. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be 3000 (3M) psi.**
 - a. **Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.**
 - b. **If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.**
 - c. **Manufacturer representative shall install the test plug for the initial BOP test.**
 - d. **Whenever any seal subject to test pressure is broken, all the tests in OOGO2.III.A.2.i must be followed.**
 - e. **If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.**

D. SPECIAL REQUIREMENT (S)

Waste Minimization Plan (WMP)

In the interest of resource development, submission of additional well gas capture development plan information is deferred but may be required by the BLM Authorized Officer at a later date.

MHH 06232018

GENERAL REQUIREMENTS

The BLM is to be notified in advance for a representative to witness:

- a. Spudding well (minimum of 24 hours)
 - b. Setting and/or Cementing of all casing strings (minimum of 4 hours)
 - c. BOPE tests (minimum of 4 hours)
- Chaves and Roosevelt Counties
Call the Roswell Field Office, 2909 West Second St., Roswell NM 88201.
During office hours call (575) 627-0272.
After office hours call (575)
- Eddy County
Call the Carlsbad Field Office, 620 East Greene St., Carlsbad, NM 88220,
(575) 361-2822
- Lea County
Call the Hobbs Field Station, 414 West Taylor, Hobbs NM 88240, (575)
393-3612
1. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval.
 - a. In the event the operator has proposed to drill multiple wells utilizing a skid/walking rig. Operator shall secure the wellbore on the current well, after installing and testing the wellhead, by installing a blind flange of like pressure rating to the wellhead and a pressure gauge that can be monitored while drilling is performed on the other well(s).
 - b. When the operator proposes to set surface casing with Spudder Rig
 - Notify the BLM when moving in and removing the Spudder Rig.
 - Notify the BLM when moving in the 2nd Rig. Rig to be moved in within 90 days of notification that Spudder Rig has left the location.
 - BOP/BOPE test to be conducted per Onshore Oil and Gas Order No. 2 as soon as 2nd Rig is rigged up on well.
 2. Floor controls are required for 3M or Greater systems. These controls will be on the rig floor, unobstructed, readily accessible to the driller and will be operational at all times during drilling and/or completion activities. Rig floor is defined as the area immediately around the rotary table; the area immediately above the substructure on which the draw works are located, this does not include the dog house or stairway area.

3. The record of the drilling rate along with the GR/N well log run from TD to surface (horizontal well – vertical portion of hole) shall be submitted to the BLM office as well as all other logs run on the borehole 30 days from completion. If available, a digital copy of the logs is to be submitted in addition to the paper copies. The Rustler top and top and bottom of Salt are to be recorded on the Completion Report.

A. CASING

1. Changes to the approved APD casing program need prior approval if the items substituted are of lesser grade or different casing size or are Non-API. The Operator can exchange the components of the proposal with that of superior strength (i.e. changing from J-55 to N-80, or from 36# to 40#). Changes to the approved cement program need prior approval if the altered cement plan has less volume or strength or if the changes are substantial (i.e. Multistage tool, ECP, etc.). The initial wellhead installed on the well will remain on the well with spools used as needed.
2. Wait on cement (WOC) for Potash Areas: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi for all cement blends, 2) until cement has been in place at least 24 hours. WOC time will be recorded in the driller's log.
3. Wait on cement (WOC) for Water Basin: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi at the shoe, 2) until cement has been in place at least 8 hours. WOC time will be recorded in the driller's log. See individual casing strings for details regarding lead cement slurry requirements.
4. Provide compressive strengths including hours to reach required 500 pounds compressive strength prior to cementing each casing string. Have well specific cement details onsite prior to pumping the cement for each casing string.
5. No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.
6. On that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Formation at the shoe shall be tested to a minimum of the mud weight equivalent anticipated to control the formation pressure to the next casing depth or at total depth of the well. This test shall be performed before drilling more than 20 feet of new hole.
7. If hardband drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.

8. Whenever a casing string is cemented in the R-111-P potash area, the NMOCD requirements shall be followed.

B. PRESSURE CONTROL

1. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in Onshore Oil and Gas Order No. 2 and API RP 53 Sec. 17.
2. If a variance is approved for a flexible hose to be installed from the BOP to the choke manifold, the following requirements apply: Check condition of flexible line from BOP to choke manifold, replace if exterior is damaged or if line fails test. Line to be as straight as possible with no hard bends and is to be anchored according to Manufacturer's requirements. The flexible hose can be exchanged with a hose of equal size and equal or greater pressure rating. Anchor requirements, specification sheet and hydrostatic pressure test certification matching the hose in service, to be onsite for review. These documents shall be posted in the company man's trailer and on the rig floor.
3. 5M or higher system requires an HCR valve, remote kill line and annular to match. The remote kill line is to be installed prior to testing the system and tested to stack pressure.
4. If the operator has proposed a multi-bowl wellhead assembly in the APD. The following requirements must be met:
 - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
 - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
 - c. Manufacturer representative shall install the test plug for the initial BOP test.
 - d. Whenever any seal subject to test pressure is broken, all the tests in OOGO2.III.A.2.i must be followed.
 - e. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
5. The appropriate BLM office shall be notified a minimum of 4 hours in advance for a representative to witness the tests.
 - a. In a water basin, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. The casing cut-off and BOP installation can be initiated four hours after installing the slips, which will be approximately six hours after bumping the

plug. For those casing strings not using slips, the minimum wait time before cut-off is eight hours after bumping the plug. BOP/BOPE testing can begin after cut-off or once cement reaches 500 psi compressive strength (including lead when specified), whichever is greater. However, if the float does not hold, cut-off cannot be initiated until cement reaches 500 psi compressive strength (including lead when specified).

- b. In potash areas, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. For all casing strings, casing cut-off and BOP installation can be initiated at twelve hours after bumping the plug. However, **no tests** shall commence until the cement has had a minimum of 24 hours setup time.
- c. The tests shall be done by an independent service company utilizing a test plug not a cup or J-packer. The operator also has the option of utilizing an independent tester to test without a plug (i.e. against the casing) pursuant to Onshore Order 2 with the pressure not to exceed 70% of the burst rating for the casing. Any test against the casing must meet the WOC time for water basin (8 hours) or potash (24 hours) or 500 pounds compressive strength, whichever is greater, prior to initiating the test (see casing segment as lead cement may be critical item).
- d. The test shall be run on a 5000 psi chart for a 2-3M BOP/BOP, on a 10000 psi chart for a 5M BOP/BOPE and on a 15000 psi chart for a 10M BOP/BOPE. If a linear chart is used, it shall be a one hour chart. A circular chart shall have a maximum 2 hour clock. If a twelve hour or twenty-four hour chart is used, tester shall make a notation that it is run with a two hour clock.
- e. The results of the test shall be reported to the appropriate BLM office.
- f. All tests are required to be recorded on a calibrated test chart. A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.
- g. The BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes if test is done with a test plug and 30 minutes without a test plug. This test shall be performed prior to the test at full stack pressure.
- h. BOP/BOPE must be tested by an independent service company within 500 feet of the top of the Wolfcamp formation if the time between the setting of the intermediate casing and reaching this depth exceeds 20 days. This test does not exclude the test prior to drilling out the casing shoe as per Onshore Order No. 2.

C. DRILLING MUD

Mud system monitoring equipment, with derrick floor indicators and visual and audio alarms, shall be operating before drilling into the Wolfcamp formation, and shall be used until production casing is run and cemented.

D. WASTE MATERIAL AND FLUIDS

All waste (i.e. drilling fluids, trash, salts, chemicals, sewage, gray water, etc.) created as a result of drilling operations and completion operations shall be safely contained and disposed of properly at a waste disposal facility. No waste material or fluid shall be disposed of on the well location or surrounding area.

Porto-johns and trash containers will be on-location during fracturing operations or any other crew-intensive operations.

**PECOS DISTRICT
SURFACE USE
CONDITIONS OF APPROVAL**

OPERATOR'S NAME:	DEVON ENERGY PRODUCTION
LEASE NO.:	NMNM097151
WELL NAME & NO.:	27H -FLAGLER 8 FED
SURFACE HOLE FOOTAGE:	380'S & 1680'E
BOTTOM HOLE FOOTAGE:	330'N & 1605'E
LOCATION:	Section 8.,T25S., R.33E., NMP
COUNTY:	LEA County, New Mexico

TABLE OF CONTENTS

Standard Conditions of Approval (COA) apply to this APD. If any deviations to these standards exist or special COAs are required, the section with the deviation or requirement will be checked below.

- General Provisions**
- Permit Expiration**
- Archaeology, Paleontology, and Historical Sites**
- Noxious Weeds**
- Special Requirements**
 - Lesser Prairie-Chicken Timing Stipulations
 - Ground-level Abandoned Well Marker
 - Range
- Construction**
 - Notification
 - Topsoil
 - Closed Loop System
 - Federal Mineral Material Pits
 - Well Pads
 - Roads
- Road Section Diagram**
- Production (Post Drilling)**
 - Well Structures & Facilities
 - Pipelines
 - Electric Lines
- Interim Reclamation**
- Final Abandonment & Reclamation**

I. GENERAL PROVISIONS

The approval of the Application For Permit To Drill (APD) is in compliance with all applicable laws and regulations: 43 Code of Federal Regulations 3160, the lease terms, Onshore Oil and Gas Orders, Notices To Lessees, New Mexico Oil Conservation Division (NMOCD) Rules, National Historical Preservation Act As Amended, and instructions and orders of the Authorized Officer. Any request for a variance shall be submitted to the Authorized Officer on Form 3160-5, Sundry Notices and Report on Wells.

II. PERMIT EXPIRATION

If the permit terminates prior to drilling and drilling cannot be commenced within 60 days after expiration, an operator is required to submit Form 3160-5, Sundry Notices and Reports on Wells, requesting surface reclamation requirements for any surface disturbance. However, if the operator will be able to initiate drilling within 60 days after the expiration of the permit, the operator must have set the conductor pipe in order to allow for an extension of 60 days beyond the expiration date of the APD. (Filing of a Sundry Notice is required for this 60 day extension.)

III. ARCHAEOLOGICAL, PALEONTOLOGY & HISTORICAL SITES

Any cultural and/or paleontological resource discovered by the operator or by any person working on the operator's behalf shall immediately report such findings to the Authorized Officer. The operator is fully accountable for the actions of their contractors and subcontractors. The operator shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery shall be made by the Authorized Officer to determine the appropriate actions that shall be required to prevent the loss of significant cultural or scientific values of the discovery. The operator shall be held responsible for the cost of the proper mitigation measures that the Authorized Officer assesses after consultation with the operator on the evaluation and decisions of the discovery. Any unauthorized collection or disturbance of cultural or paleontological resources may result in a shutdown order by the Authorized Officer.

IV. NOXIOUS WEEDS

The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes the roads, pads, associated pipeline corridor, and adjacent land affected by the establishment of weeds due to this action. The operator shall consult with the Authorized Officer for acceptable weed control methods, which include following EPA and BLM requirements and policies.

V. SPECIAL REQUIREMENT(S)

In May 2008, the Pecos District Special Status Species Resource Management Plan Amendment (RMPA) was approved and is being implemented. In addition to the standard practices that minimize impacts, as listed above, the following COA will apply:

- Timing Limitation Stipulation / Condition of Approval for lesser prairie-chicken, to minimize noise associated impacts which could disrupt breeding and nesting activities.
- Upon abandonment, a low profile abandoned well marker will be installed to prevent raptor perching.
- Devon would need to construct and maintain escape ramps according to the following criteria:
 - Earthen escape ramps would be required to be constructed to sufficiently support livestock at no more than a 30-degree slope and spaced no more than 500 feet apart.
 - If trench is left open under an 8-hour time period, it would not be required to have an escape ramp; however, before the trench is backfilled, Devon would inspect the trench for wildlife and remove any species that are trapped at a distance of at least 100 yards away from the trench.

Raptor Nest Mitigation

- A BLM Wildlife Biologist must be contacted by the operator prior to construction activities to determine if the raptor nest is active.
- Raptor nests on special, natural habitat features, such as trees, large brush, cliff faces and escarpments, will be protected by not allowing surface disturbance within up to 200 meters of nests or by delaying activity for up to 90 days, or a combination of both. Exceptions to this requirement for raptor nests will be considered if the nests expected to be disturbed are inactive, the proposed activity is of short duration (e.g. habitat enhancement projects, fences, pipelines), and will not result in continuing activity in proximity to the nest.
- Exhaust noise from pump jack engines must be muffled or otherwise controlled so as not to exceed 75 db measured at 30 ft. from the source of the noise.

Power lines shall be constructed and designed in accordance to standards outlined in "Suggested Practices for Avian Protection on Power Lines: The State of the Art in 2006" Edison Electric Institute, APLIC, and the California Energy Commission 2006. The holder shall assume the burden and expense of proving that pole designs not shown in the above publication deter raptor perching, roosting, and nesting. Such proof shall be provided by a raptor expert approved by the Authorized Officer. The BLM reserves the right to require modification or additions to all power line structures placed on this right-of-way, should they be necessary to ensure the safety of large perching birds. The holder without liability or expense shall make such modifications and/or additions to the United States.

Temporary Fence Crossing Requirement

Where entry is granted across a fence line, the fence must be braced and tied off on both sides of the passageway with H-braces prior to cutting. Once the work is completed, the fence will be restored to its prior condition, or better. Devon shall notify the private surface landowner or the grazing allotment holder prior to crossing any fences.

Cattle Guard Requirement

Where entry is granted across a fence line for an access road, the fence must be braced and tied off on both sides of the passageway with H-braces prior to cutting. Once the work is completed,

the fence will be restored to its prior condition with an appropriately sized cattle guard sufficient to carry out the project. Any new or existing cattle guards on the access route shall be repaired or replaced if they are damaged or have deteriorated beyond practical use. Devon shall be responsible for the condition of the existing cattle guards that are in place and are utilized during lease operations. Once the road is abandoned, the fence would be restored to its prior condition, or better. Devon shall notify the private surface landowner or the grazing allotment holder prior to crossing any fences.

Livestock Watering Requirement

Devon must contact the allotment holder prior to construction to identify the location of the pipeline. Devon must take measures to protect the pipeline from compression or other damages. If the pipeline is damaged or compromised in any way near the proposed project as a result of oil and gas activity, the operator is responsible for repairing the pipeline immediately. Devon must notify the BLM office (575-234-5972) and the private surface landowner or the grazing allotment holder if any damage occurs to structures that provide water to livestock.

During construction, Devon shall minimize disturbance to existing fences, water lines, troughs, windmills, and other improvements on public lands. Devon is required to promptly repair improvements to at least their former state. Functional use of these improvements will be maintained at all times. The holder will contact the grazing permittee/allottee prior to disturbing any range improvement projects. When necessary to pass through a fence line, the fence shall be braced on both sides of the passageway prior to cutting of the fence. No permanent gates will be allowed unless approved by the Authorized Officer.

VI. CONSTRUCTION

A. NOTIFICATION

The BLM shall administer compliance and monitor construction of the access road and well pad. Notify the Carlsbad Field Office at (575) 234-5909 at least 3 working days prior to commencing construction of the access road and/or well pad.

When construction operations are being conducted on this well, the operator shall have the approved APD and Conditions of Approval (COA) on the well site and they shall be made available upon request by the Authorized Officer.

B. TOPSOIL

The operator shall strip the top portion of the soil (root zone) from the entire well pad area and stockpile the topsoil along the edge of the well pad as depicted in the APD. The root zone is typically six (6) inches in depth. All the stockpiled topsoil will be redistributed over the interim reclamation areas. Topsoil shall not be used for berming the pad or facilities. For final reclamation, the topsoil shall be spread over the entire pad area for seeding preparation.

Other subsoil (below six inches) stockpiles must be completely segregated from the topsoil stockpile. Large rocks or subsoil clods (not evident in the surrounding terrain) must be buried within the approved area for interim and final reclamation.

C. CLOSED LOOP SYSTEM

Tanks are required for drilling operations: No Pits.

The operator shall properly dispose of drilling contents at an authorized disposal site.

D. FEDERAL MINERAL MATERIALS PIT

Payment shall be made to the BLM prior to removal of any federal mineral materials. Call the Carlsbad Field Office at (575) 234-5972.

E. WELL PAD SURFACING

Surfacing of the well pad is not required.

If the operator elects to surface the well pad, the surfacing material may be required to be removed at the time of reclamation. The well pad shall be constructed in a manner which creates the smallest possible surface disturbance, consistent with safety and operational needs.

F. EXCLOSURE FENCING (CELLARS & PITS)

Exclosure Fencing

The operator will install and maintain exclosure fencing for all open well cellars to prevent access to public, livestock, and large forms of wildlife before and after drilling operations until the pit is free of fluids and the operator initiates backfilling. (For examples of exclosure fencing design, refer to BLM's Oil and Gas Gold Book, Exclosure Fence Illustrations, Figure 1, Page 18.)

G. ON LEASE ACCESS ROADS**Road Width**

The access road shall have a driving surface that creates the smallest possible surface disturbance and does not exceed fourteen (14) feet in width. The maximum width of surface disturbance, when constructing the access road, shall not exceed twenty-five (25) feet.

Surfacing

Surfacing material is not required on the new access road driving surface. If the operator elects to surface the new access road or pad, the surfacing material may be required to be removed at the time of reclamation.

Where possible, no improvements should be made on the unsurfaced access road other than to remove vegetation as necessary, road irregularities, safety issues, or to fill low areas that may sustain standing water.

The Authorized Officer reserves the right to require surfacing of any portion of the access road at any time deemed necessary. Surfacing may be required in the event the road deteriorates, erodes, road traffic increases, or it is determined to be beneficial for future field development. The surfacing depth and type of material will be determined at the time of notification.

Crowning

Crowning shall be done on the access road driving surface. The road crown shall have a grade of approximately 2% (i.e., a 1" crown on a 14' wide road). The road shall conform to Figure 1; cross section and plans for typical road construction.

Ditching

Ditching shall be required on both sides of the road.

Turnouts


Vehicle turnouts shall be constructed on the road. Turnouts shall be intervisible with interval spacing distance less than 1000 feet. Turnouts shall conform to Figure 1; cross section and plans for typical road construction.

Drainage

Drainage control systems shall be constructed on the entire length of road (e.g. ditches, sidehill out-sloping and in-sloping, lead-off ditches, culvert installation, and low water crossings).

A typical lead-off ditch has a minimum depth of 1 foot below and a berm of 6 inches above natural ground level. The berm shall be on the down-slope side of the lead-off ditch.

Cross Section of a Typical Lead-off Ditch



All lead-off ditches shall be graded to drain water with a 1 percent minimum to 3 percent maximum ditch slope. The spacing interval are variable for lead-off ditches and shall be determined according to the formula for spacing intervals of lead-off ditches, but may be amended depending upon existing soil types and centerline road slope (in %);

Formula for Spacing Interval of Lead-off Ditches

Example - On a 4% road slope that is 400 feet long, the water flow shall drain water into a lead-off ditch. Spacing interval shall be determined by the following formula:

$$400 \text{ foot road with } 4\% \text{ road slope: } \frac{400'}{4\%} + 100' = 200' \text{ lead-off ditch interval}$$

Cattle guards

An appropriately sized cattle guard sufficient to carry out the project shall be installed and maintained at fence/road crossings. Any existing cattle guards on the access road route shall be repaired or replaced if they are damaged or have deteriorated beyond practical use. The operator shall be responsible for the condition of the existing cattle guards that are in place and are utilized during lease operations.

Fence Requirement

Where entry is granted across a fence line, the fence shall be braced and tied off on both sides of the passageway prior to cutting. The operator shall notify the private surface landowner or the grazing allotment holder prior to crossing any fences.

Public Access

Public access on this road shall not be restricted by the operator without specific written approval granted by the Authorized Officer.

Construction Steps

1. Salvage topsoil
2. Construct road

3. Redistribute topsoil
4. Revegetate slopes




Figure 1. Cross-sections and plans for typical road sections representative of BLM resource or FS local and higher-class roads.

VII. PRODUCTION (POST DRILLING)

A. WELL STRUCTURES & FACILITIES

Placement of Production Facilities

Production facilities should be placed on the well pad to allow for maximum interim recontouring and revegetation of the well location.

Exclosure Netting (Open-top Tanks)

Immediately following active drilling or completion operations, the operator will take actions necessary to prevent wildlife and livestock access, including avian wildlife, to all open-topped tanks that contain or have the potential to contain salinity sufficient to cause harm to wildlife or livestock, hydrocarbons, or Resource Conservation and Recovery Act of 1976-exempt hazardous substances. At a minimum, the operator will net, screen, or cover open-topped tanks to exclude wildlife and livestock and prevent mortality. If the operator uses netting, the operator will cover and secure the open portion of the tank to prevent wildlife entry. The operator will net, screen, or cover the tanks until the operator removes the tanks from the location or the tanks no longer contain substances that could be harmful to wildlife or livestock. Use a maximum netting mesh size of 1 ½ inches. The netting must not be in contact with fluids and must not have holes or gaps.

Chemical and Fuel Secondary Containment and Exclosure Screening

The operator will prevent all hazardous, poisonous, flammable, and toxic substances from coming into contact with soil and water. At a minimum, the operator will install and maintain an impervious secondary containment system for any tank or barrel containing hazardous, poisonous, flammable, or toxic substances sufficient to contain the contents of the tank or barrel and any drips, leaks, and anticipated precipitation. The operator will dispose of fluids within the containment system that do not meet applicable state or U. S. Environmental Protection Agency livestock water standards in accordance with state law; the operator must not drain the fluids to the soil or ground. The operator will design, construct, and maintain all secondary containment systems to prevent wildlife and livestock exposure to harmful substances. At a minimum, the operator will install effective wildlife and livestock exclosure systems such as fencing, netting, expanded metal mesh, lids, and grate covers. Use a maximum netting mesh size of 1 ½ inches.

Open-Vent Exhaust Stack Exclosures

The operator will construct, modify, equip, and maintain all open-vent exhaust stacks on production equipment to prevent birds and bats from entering, and to discourage perching, roosting, and nesting. (*Recommended exclosure structures on open-vent exhaust stacks are in the shape of a cone.*) Production equipment includes, but may not be limited to, tanks, heater-treaters, separators, dehydrators, flare stacks, in-line units, and compressor mufflers.

Containment Structures

Proposed production facilities such as storage tanks and other vessels will have a secondary containment structure that is constructed to hold the capacity of 1.5 times the largest tank, plus freeboard to account for precipitation, unless more stringent protective requirements are deemed necessary.

Painting Requirement

All above-ground structures including meter housing that are not subject to safety requirements shall be painted a flat non-reflective paint color, **Shale Green** from the BLM Standard Environmental Color Chart (CC-001: June 2008).

B. PIPELINES

BURIED PIPELINE STIPULATIONS

A copy of the application (Grant, APD, or Sundry Notice) and attachments, including conditions of approval, survey plat and/or map, will be on location during construction. BLM personnel may request to you a copy of your permit during construction to ensure compliance with all stipulations.

Holder agrees to comply with the following stipulations to the satisfaction of the Authorized Officer:

1. The Holder shall indemnify the United States against any liability for damage to life or property arising from the occupancy or use of public lands under this grant.
2. The Holder shall comply with all applicable Federal laws and regulations existing or hereafter enacted or promulgated. In any event, the holder shall comply with the Toxic Substances Control Act of 1976 as amended, 15 USC 2601 et seq. (1982) with regards to any toxic substances that are used, generated by or stored on the right-of-way or on facilities authorized under this right-of-way grant. (See 40 CFR Part 702-799 and especially, provisions on polychlorinated biphenyls, 40 CFR 761.1-761.193.) Additionally, any release of toxic substances (leaks, spills, etc.) in excess of the reportable quantity established by 40 CFR Part 117 shall be reported as required by the Comprehensive Environmental Response, Compensation, and Liability Act, section 102b. A copy of any report required or requested by any Federal agency or State government as a result of a reportable release or spill of any toxic substances shall be furnished to the authorized officer concurrent with the filing of the reports to the involved Federal agency or State government.
3. The holder agrees to indemnify the United States against any liability arising from the release of any hazardous substance or hazardous waste (as these terms are defined in the Comprehensive Environmental Response, Compensation and Liability Act of 1980, 42 U.S.C. 9601, et seq. or the Resource Conservation and Recovery Act, 42 U.S.C.6901, et seq.) on the Right-of-Way (unless the release or threatened release is wholly unrelated to the Right-of-Way holder's activity on the Right-of-Way), or resulting from the activity of the Right-of-Way holder on the Right-of-Way. This agreement applies without regard to whether a release is caused by the holder, its agent, or unrelated third parties.

4. If, during any phase of the construction, operation, maintenance, or termination of the pipeline, any oil or other pollutant should be discharged from the pipeline system, impacting Federal lands, the control and total removal, disposal, and cleaning up of such oil or other pollutant, wherever found, shall be the responsibility of holder, regardless of fault. Upon failure of holder to control, dispose of, or clean up such discharge on or affecting Federal lands, or to repair all damages resulting therefrom, on the Federal lands, the Authorized Officer may take such measures as he deems necessary to control and clean up the discharge and restore the area, including where appropriate, the aquatic environment and fish and wildlife habitats, at the full expense of the holder. Such action by the Authorized Officer shall not relieve holder of any responsibility as provided herein.

5. All construction and maintenance activity will be confined to the authorized right-of-way.
6. The pipeline will be buried with a minimum cover of 36 inches between the top of the pipe and ground level.
7. The maximum allowable disturbance for construction in this right-of-way will be 30 feet:
 - Blading of vegetation within the right-of-way will be allowed: maximum width of blading operations will not exceed 20 feet. The trench is included in this area. (*Blading is defined as the complete removal of brush and ground vegetation.*)
 - Clearing of brush species within the right-of-way will be allowed: maximum width of clearing operations will not exceed 30 feet. The trench and bladed area are included in this area. (*Clearing is defined as the removal of brush while leaving ground vegetation (grasses, weeds, etc.) intact. Clearing is best accomplished by holding the blade 4 to 6 inches above the ground surface.*)
 - The remaining area of the right-of-way (if any) shall only be disturbed by compressing the vegetation. (*Compressing can be caused by vehicle tires, placement of equipment, etc.*)
8. The holder shall stockpile an adequate amount of topsoil where blading is allowed. The topsoil to be stripped is approximately 6 inches in depth. The topsoil will be segregated from other spoil piles from trench construction. The topsoil will be evenly distributed over the bladed area for the preparation of seeding.
9. The holder shall minimize disturbance to existing fences and other improvements on public lands. The holder is required to promptly repair improvements to at least their former state. Functional use of these improvements will be maintained at all times. The holder will contact the owner of any improvements prior to disturbing them. When necessary to pass through a fence line, the fence shall be braced on both sides of the passageway prior to cutting of the fence. No permanent gates will be allowed unless approved by the Authorized Officer.
10. Vegetation, soil, and rocks left as a result of construction or maintenance activity will be randomly scattered on this right-of-way and will not be left in rows, piles, or berms, unless otherwise approved by the Authorized Officer. The entire right-of-way shall be recontoured to match the surrounding landscape. The backfilled soil shall be compacted and a 6 inch berm will be left over the ditch line to allow for settling back to grade.
11. In those areas where erosion control structures are required to stabilize soil conditions, the holder will install such structures as are suitable for the specific soil conditions being encountered and which are in accordance with sound resource management practices.

12. The holder will reseed all disturbed areas. Seeding will be done according to the attached seeding requirements, using the following seed mix.

- | | |
|--|--|
| <input type="checkbox"/> seed mixture 1 | <input type="checkbox"/> seed mixture 3 |
| <input type="checkbox"/> seed mixture 2 | <input type="checkbox"/> seed mixture 4 |
| <input checked="" type="checkbox"/> seed mixture 2/LPC | <input type="checkbox"/> Aplomado Falcon Mixture |

13. All above-ground structures not subject to safety requirements shall be painted by the holder to blend with the natural color of the landscape. The paint used shall be color which simulates "Standard Environmental Colors" – **Shale Green**, Munsell Soil Color No. 5Y 4/2.

14. The pipeline will be identified by signs at the point of origin and completion of the right-of-way and at all road crossings. At a minimum, signs will state the holder's name, BLM serial number, and the product being transported. All signs and information thereon will be posted in a permanent, conspicuous manner, and will be maintained in a legible condition for the life of the pipeline.

15. The holder shall not use the pipeline route as a road for purposes other than routine maintenance as determined necessary by the Authorized Officer in consultation with the holder before maintenance begins. The holder will take whatever steps are necessary to ensure that the pipeline route is not used as a roadway. As determined necessary during the life of the pipeline, the Authorized Officer may ask the holder to construct temporary deterrence structures.

16. Any cultural and/or paleontological resources (historic or prehistoric site or object) discovered by the holder, or any person working on his behalf, on public or Federal land shall be immediately reported to the Authorized Officer. Holder shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery will be made by the Authorized Officer to determine appropriate actions to prevent the loss of significant cultural or scientific values. The holder will be responsible for the cost of evaluation and any decision as to proper mitigation measures will be made by the Authorized Officer after consulting with the holder.

17. The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes associated roads, pipeline corridor and adjacent land affected by the establishment of weeds due to this action. The operator shall consult with the Authorized Officer for acceptable weed control methods, which include following EPA and BLM requirements and policies.

18. Escape Ramps - The operator will construct and maintain pipeline/utility trenches that are not otherwise fenced, screened, or netted to prevent livestock, wildlife, and humans from becoming entrapped. At a minimum, the operator will construct and maintain escape ramps, ladders, or

other methods of avian and terrestrial wildlife escape in the trenches according to the following criteria:

- a. Any trench left open for eight (8) hours or less is not required to have escape ramps; however, before the trench is backfilled, the contractor/operator shall inspect the trench for wildlife, remove all trapped wildlife, and release them at least 100 yards from the trench.
- b. For trenches left open for eight (8) hours or more, earthen escape ramps (built at no more than a 30 degree slope and spaced no more than 500 feet apart) shall be placed in the trench.

19. Special Stipulations:

Lesser Prairie-Chicken

Oil and gas activities will not be allowed in lesser prairie-chicken habitat during the period from March 1st through June 15th annually. During that period, other activities that produce noise or involve human activity, such as the maintenance of oil and gas facilities, geophysical exploration other than 3-D operations, and pipeline, road, and well pad construction, will be allowed except between 3:00 am and 9:00 am. The 3:00 am to 9:00 am restriction will not apply to normal, around-the-clock operations, such as venting, flaring, or pumping, which do not require a human presence during this period. Normal vehicle use on existing roads will not be restricted. Exhaust noise from pump jack engines must be muffled or otherwise controlled so as not to exceed 75 db measured at 30 ft. from the source of the noise.

C. ELECTRIC LINES

STANDARD STIPULATIONS FOR OVERHEAD ELECTRIC DISTRIBUTION LINES

A copy of the grant and attachments, including stipulations, survey plat and/or map, will be on location during construction. BLM personnel may request to you a copy of your permit during construction to ensure compliance with all stipulations.

Holder agrees to comply with the following stipulations to the satisfaction of the Authorized Officer:

1. The holder shall indemnify the United States against any liability for damage to life or property arising from the occupancy or use of public lands under this grant.
2. The holder shall comply with all applicable Federal laws and regulations existing or hereafter enacted or promulgated. In any event, the holder shall comply with the Toxic Substances Control Act of 1976 as amended, 15 USC 2601 et seq. (1982) with regards to any toxic substances that are used, generated by or stored on the right-of-way or on facilities authorized under this right-of-way grant. (See 40 CFR, Part 702-799 and especially, provisions on polychlorinated biphenyls, 40 CFR 761.1-761.193.) Additionally, any release of toxic substances (leaks, spills, etc.) in excess of the reportable quantity established by 40 CFR, Part 117 shall be reported as required by the Comprehensive Environmental Response, Compensation, and Liability Act, section 102b. A copy of any report required or requested by any Federal agency or State government as

a result of a reportable release or spill of any toxic substances shall be furnished to the authorized officer concurrent with the filing of the reports to the involved Federal agency or State government.

3. The holder agrees to indemnify the United States against any liability arising from the release of any hazardous substance or hazardous waste (as these terms are defined in the Comprehensive Environmental Response, Compensation and Liability Act of 1980, 42 U.S.C. 9601, et seq. or the Resource Conservation and Recovery Act, 42 U.S.C. 6901, et seq.) on the Right-of-Way (unless the release or threatened release is wholly unrelated to the Right-of-Way holder's activity on the Right-of-Way), or resulting from the activity of the Right-of-Way holder on the Right-of-Way. This agreement applies without regard to whether a release is caused by the holder, its agent, or unrelated third parties.

4. There will be no clearing or blading of the right-of-way unless otherwise agreed to in writing by the Authorized Officer.

5. Power lines shall be constructed and designed in accordance to standards outlined in "Suggested Practices for Avian Protection on Power lines: The State of the Art in 2006" Edison Electric Institute, APLIC, and the California Energy Commission 2006 . The holder shall assume the burden and expense of proving that pole designs not shown in the above publication deter raptor perching, roosting, and nesting. Such proof shall be provided by a raptor expert approved by the Authorized Officer. The BLM reserves the right to require modification or additions to all powerline structures placed on this right-of-way, should they be necessary to ensure the safety of large perching birds. Such modifications and/or additions shall be made by the holder without liability or expense to the United States.

Raptor deterrence will consist of but not limited to the following: triangle perch discouragers shall be placed on each side of the cross arms and a nonconductive perching deterrence shall be placed on all vertical poles that extend past the cross arms.

6. The holder shall minimize disturbance to existing fences and other improvements on public lands. The holder is required to promptly repair improvements to at least their former state. Functional use of these improvements will be maintained at all times. The holder will contact the owner of any improvements prior to disturbing them. When necessary to pass through a fence line, the fence shall be braced on both sides of the passageway prior to cutting the fence. No permanent gates will be allowed unless approved by the Authorized Officer.

7. The BLM serial number assigned to this authorization shall be posted in a permanent, conspicuous manner where the power line crosses roads and at all serviced facilities. Numbers will be at least two inches high and will be affixed to the pole nearest the road crossing and at the facilities served.

8. Upon cancellation, relinquishment, or expiration of this grant, the holder shall comply with those abandonment procedures as prescribed by the Authorized Officer.

9. All surface structures (poles, lines, transformers, etc.) shall be removed within 180 days of abandonment, relinquishment, or termination of use of the serviced facility or facilities or within 180 days of abandonment, relinquishment, cancellation, or expiration of this grant, whichever comes first. This will not apply where the power line extends service to an active, adjoining facility or facilities.

10. Any cultural and/or paleontological resource (historic or prehistoric site or object) discovered by the holder, or any person working on his behalf, on public or Federal land shall be immediately reported to the Authorized Officer. Holder shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery will be made by the Authorized Officer to determine appropriate actions to prevent the loss of significant cultural or scientific values. The holder will be responsible for the cost of evaluation and any decision as to proper mitigation measures will be made by the Authorized Officer after consulting with the holder.

11. Special Stipulations:

- For reclamation remove poles, lines, transformer, etc. and dispose of properly.
- Fill in any holes from the poles removed.

Timing Limitation Stipulation/Condition of Approval for Lesser Prairie-Chicken:

Oil and gas activities including 3-D geophysical exploration, and drilling will not be allowed in lesser prairie-chicken habitat during the period from March 1st through June 15th annually. During that period, other activities that produce noise or involve human activity, such as the maintenance of oil and gas facilities, geophysical exploration other than 3-D operations, and pipeline, road, and well pad construction, will be allowed except between 3:00 am and 9:00 am. The 3:00 am to 9:00 am restriction will not apply to normal, around-the-clock operations, such as venting, flaring, or pumping, which do not require a human presence during this period. Additionally, no new drilling will be allowed within up to 200 meters of leks known at the time of permitting. Normal vehicle use on existing roads will not be restricted. Exhaust noise from pump jack engines must be muffled or otherwise controlled so as not to exceed 75 db measured at 30 ft. from the source of the noise.

STANDARD STIPULATIONS FOR OIL AND GAS RELATED SITES

A copy of the application (Grant/Sundry Notice) and attachments, including stipulations and map, will be on location during construction. BLM personnel may request to view a copy of your permit during construction to ensure compliance with all stipulations.

The holder agrees to comply with the following stipulations to the satisfaction of the Authorized Officer, BLM.

1. The holder shall indemnify the United States against any liability for damage to life or property arising from the occupancy or use of public lands under this grant and for all response costs, penalties, damages, claims, and other costs arising from the provisions of the Resource Conservation and Recovery Act (RCRA), 42 U.S.C. Chap. 82, Section 6901 et. seq., from the Comprehensive Environmental Response, Compensation and Liability Act (CERCLA), 42 U.S.C. Chap. 109, Section 9601 et. seq., and from other applicable environmental statutes.
2. The holder shall comply with all applicable Federal laws and regulations existing or hereafter enacted or promulgated. In any event, the holder shall comply with the Toxic Substances Control Act of 1976, as amended (15 U.S.C. 2601, et. seq.) with regard to any toxic substances that are used, generated by or stored on the right-of-way or on facilities authorized by this grant. (See 40 CFR, Part 702-799 and especially, provisions on polychlorinated biphenyls, 40 CFR 761.1-761.193.) Additionally, any release of toxic substances (leaks, spills, etc.) in excess of the reportable quantity established by 40 CFR, Part 117 shall be reported as required by the Comprehensive Environmental Response, Compensation and Liability Act, Section 102b. A copy of any report required or requested by any Federal agency or State government as a result of a reportable release or spill of any toxic substances shall be furnished to the Authorized Officer concurrent with the filing of the reports to the involved Federal agency or State government.
3. The holder agrees to indemnify the United States against any liability arising from the release of any hazardous substance or hazardous waste (as these terms are defined in the Comprehensive Environmental Response, Compensation and Liability Act of 1980, 42 U.S.C. 9601, et. seq. or the Resource Conservation and Recovery Act, 42 U.S.C. 6901, et. seq.) on the right-of-way (unless the release or threatened release is wholly unrelated to the right-of-way holder's activity on the right-of-way). This agreement applies without regard to whether a release is caused by the holder, its agent, or unrelated third parties.
4. If, during any phase of the construction, operation, maintenance, or termination of the site or related pipeline(s), any oil or other pollutant should be discharged from site facilities, the pipeline(s) or from containers or vehicles impacting Federal lands, the control and total removal, disposal, and cleanup of such oil or other pollutant, wherever found, shall be the responsibility of the holder, regardless of fault. Upon failure of the holder to control, dispose of, or clean up such discharge on or affecting Federal lands, or to repair all damages to Federal lands resulting therefrom, the Authorized Officer may take such measures as deemed necessary to control and cleanup the discharge and restore the area, including, where appropriate, the aquatic environment and fish and wildlife habitats, at the full expense of the holder. Such action by the Authorized Officer shall not relieve the holder of any liability or responsibility.
5. Sites shall be maintained in an orderly, sanitary condition at all times. Waste materials, both liquid and solid, shall be disposed of promptly at an appropriate, authorized waste disposal facility in accordance with all applicable State and Federal laws. "Waste" means all discarded matter including, but not limited to, human waste,

trash, garbage, refuse, petroleum products, brines, chemicals, oil drums, ashes, and equipment.

6. The operator will notify the Bureau of Land Management (BLM) authorized officer and nearest Fish and Wildlife Service (FWS) Law Enforcement office within 24 hours, if the operator discovers a dead or injured federally protected species (i.e., migratory bird species, bald or golden eagle, or species listed by the FWS as threatened or endangered) in or adjacent to a pit, trench, tank, exhaust stack, or fence. (If the operator is unable to contact the FWS Law Enforcement office, the operator must contact the nearest FWS Ecological Services office.)

7. All above-ground structures not subject to safety requirements shall be painted by the holder to blend with the natural color of the landscape. The paint used shall be a color which simulates "Standard Environmental Colors" designated by the Rocky Mountain Five-State Interagency Committee. The color selected for this project is **Shale Green**, Munsell Soil Color Chart Number 5Y 4/2.

8. Any cultural and/or paleontological resource (historic or prehistoric site or object) discovered by the holder, or any person working on the holder's behalf, on public or Federal land shall be immediately reported to the Authorized Officer. The holder shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery will be made by the Authorized Officer to determine appropriate actions to prevent the loss of significant cultural or scientific values. The holder will be responsible for the cost of evaluation and any decision as to the proper mitigation measures will be made by the Authorized Officer after consulting with the holder.

9. A sales contract for removal of mineral material (caliche, sand, gravel, fill dirt) from an authorized pit, site, or on location must be obtained from the BLM prior to commencing construction. There are several options available for purchasing mineral material: contact the BLM office (575-234-5972).

10. The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes the roads, pads, associated pipeline corridor, and adjacent land affected by the establishment of weeds due to this action. The operator shall consult with the Authorized Officer for acceptable weed control methods, which include following EPA and BLM requirements and policies.

11. Once the site is no longer in service or use, the site must undergo final abandonment. At final abandonment, the site and access roads must undergo "final" reclamation so that the character and productivity of the land are restored. Earthwork for final reclamation must be completed within six (6) months of the abandonment of the site. All pads and facility locations and roads must be reclaimed to a satisfactory revegetated, safe, and stable condition, unless an agreement is made with the landowner or BLM to keep the

road and/or pad intact. After all disturbed areas have been satisfactorily prepared, these areas need to be revegetated with the seed mixture provided. Seeding should be accomplished by drilling on the contour whenever practical or by other approved methods. Seeding may need to be repeated until revegetation is successful, as determined by the BLM.

Operators shall contact a BLM surface protection specialist prior to surface abandonment operations for site specific objectives (Jim Amos: 575-234-5909).

12. The holder shall stockpile an adequate amount of topsoil where blading occurs. The topsoil to be stripped is approximately 6 inches in depth. The topsoil will be segregated from other spoil piles. The topsoil will be used for final reclamation.

13. The holder will reseed all disturbed areas. Seeding will be done according to the attached seeding requirements, using the following seed mix.

- seed mixture 1
- seed mixture 2
- seed mixture 2/LPC
- seed mixture 3
- seed mixture 4
- Aplomado Falcon Mixture

14. In those areas where erosion control structures are required to stabilize soil conditions, the holder shall install such structures as are suitable for the specific soil conditions being encountered and which are in accordance with sound management practices. Any earth work will require prior approval by the Authorized Officer.

15. Open-topped Tanks - The operator will take actions necessary to prevent wildlife and livestock access, including avian wildlife, to all open-topped tanks that contain or have the potential to contain salinity sufficient to cause harm to wildlife or livestock, hydrocarbons, or Resource Conservation and Recovery Act of 1976-exempt hazardous substances. At a minimum, the operator will net, screen, or cover open-topped tanks to exclude wildlife and livestock and prevent mortality. If the operator uses netting, the operator will cover and secure the open portion of the tank to prevent wildlife entry. The operator will net, screen, or cover the tanks until the operator removes the tanks from the location or the tanks no longer contain substances that could be harmful to wildlife or livestock. Use a maximum netting mesh size of 1 ½ inches. The netting must not be in contact with fluids and must not have holes or gaps

16. The operator will prevent all hazardous, poisonous, flammable, and toxic substances from coming into contact with soil and water. At a minimum, the operator will install and maintain an

impervious secondary containment system for any tank or barrel containing hazardous, poisonous, flammable, or toxic substances sufficient to contain the contents of the tank or barrel and any drips, leaks, and anticipated precipitation. The operator will dispose of

fluids within the containment system that do not meet applicable state or U. S. Environmental Protection Agency livestock water standards in accordance with state law; the operator must not drain the fluids to the soil or ground. The operator will design, construct, and maintain all secondary containment systems to prevent wildlife and livestock exposure to harmful substances. At a minimum, the operator will install effective wildlife and livestock enclosure systems such as fencing, netting, expanded metal mesh, lids, and grate covers. Use a maximum netting mesh size of 1 ½ inches.

17. Open-Vent Exhaust Stack Enclosures – The operator will construct, modify, equip, and maintain all open-vent exhaust stacks on production equipment to prevent birds and bats from entering, and to discourage perching, roosting, and nesting. (Recommended enclosure structures on open-vent exhaust stacks are in the shape of a cone.) Production equipment includes, but may not be limited to, tanks, heater-treaters, separators, dehydrators, flare stacks, in-line units, and compressor mufflers.

18. Containment Structures - Proposed production facilities such as storage tanks and other vessels will have a secondary containment structure that is constructed to hold the capacity of 1.5 times the largest tank, plus freeboard to account for precipitation, unless more stringent protective requirements are deemed necessary.

19. Special Stipulations:

Lesser Prairie-Chicken

Oil and gas activities will not be allowed in lesser prairie-chicken habitat during the period from March 1st through June 15th annually. During that period, other activities that produce noise or involve human activity, such as the maintenance of oil and gas facilities, geophysical exploration other than 3-D operations, and pipeline, road, and well pad construction, will be allowed except between 3:00 am and 9:00 am. The 3:00 am to 9:00 am restriction will not apply to normal, around-the-clock operations, such as venting, flaring, or pumping, which do not require a human presence during this period. Normal vehicle use on existing roads will not be restricted. Exhaust noise from permanent engines must be muffled or otherwise controlled so as not to exceed 75 db measured at 30 ft. from the source of the noise.

VIII. INTERIM RECLAMATION

During the life of the development, all disturbed areas not needed for active support of production operations should undergo interim reclamation in order to minimize the environmental impacts of development on other resources and uses.

Within six (6) months of well completion, operators should work with BLM surface management specialists (Jim Amos: 575-234-5909) to devise the best strategies to reduce the size of the location. Interim reclamation should allow for remedial well operations, as well as safe and efficient removal of oil and gas.

During reclamation, the removal of caliche is important to increasing the success of revegetating the site. Removed caliche that is free of contaminants may be used for road repairs, fire walls or for building other roads and locations. In order to operate the well or complete workover operations, it may be necessary to drive, park and operate on restored interim vegetation within the previously disturbed area. Disturbing revegetated areas for production or workover operations will be allowed. If there is significant disturbance and loss of vegetation, the area will need to be revegetated. Communicate with the appropriate BLM office for any exceptions/exemptions if needed.

All disturbed areas after they have been satisfactorily prepared need to be reseeded with the seed mixture provided below.

Upon completion of interim reclamation, the operator shall submit a Sundry Notices and Reports on Wells, Subsequent Report of Reclamation (Form 3160-5).

IX. FINAL ABANDONMENT & RECLAMATION

At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land are restored.

Earthwork for final reclamation must be completed within six (6) months of well plugging. All pads, pits, facility locations and roads must be reclaimed to a satisfactory revegetated, safe, and stable condition, unless an agreement is made with the landowner or BLM to keep the road and/or pad intact.

After all disturbed areas have been satisfactorily prepared, these areas need to be revegetated with the seed mixture provided below. Seeding should be accomplished by drilling on the contour whenever practical or by other approved methods. Seeding may need to be repeated until revegetation is successful, as determined by the BLM.

Operators shall contact a BLM surface protection specialist prior to surface abandonment operations for site specific objectives (Jim Amos: 575-234-5909).

Ground-level Abandoned Well Marker to avoid raptor perching: Upon the plugging and subsequent abandonment of the well, the well marker will be installed at ground level on a plate containing the pertinent information for the plugged well.

Seed Mixture for LPC Sand/Shinnery Sites

Holder shall seed all disturbed areas with the seed mixture listed below. The seed mixture shall be planted in the amounts specified in pounds of pure live seed (PLS)* per acre. There shall be no primary or secondary noxious weeds in the seed mixture. Seed will be tested and the viability testing of seed shall be done in accordance with State law(s) and within nine (9) months prior to purchase. Commercial seed shall be either certified or registered seed. The seed container shall be tagged in accordance with State law(s) and available for inspection by the Authorized Officer.

Seed will be planted using a drill equipped with a depth regulator to ensure proper depth of planting where drilling is possible. The seed mixture will be evenly and uniformly planted over the disturbed area (smaller/heavier seeds have a tendency to drop the bottom of the drill and are planted first). Holder shall take appropriate measures to ensure this does not occur. Where drilling is not possible, seed will be broadcast and the area shall be raked or chained to cover the seed. When broadcasting the seed, the pounds per acre are to be doubled. Seeding shall be repeated until a satisfactory stand is established as determined by the Authorized Officer. Evaluation of growth may not be made before completion of at least one full growing season after seeding.

Species to be planted in pounds of pure live seed* per acre:

<u>Species</u>	<u>lb/acre</u>
Plains Bristlegrass	5lbs/A
Sand Bluestem	5lbs/A
Little Bluestem	3lbs/A
Big Bluestem	6lbs/A
Plains Coreopsis	2lbs/A
Sand Dropseed	1lbs/A

*Pounds of pure live seed:

Pounds of seed x percent purity x percent germination = pounds pure live seed

**PECOS DISTRICT
SURFACE USE
CONDITIONS OF APPROVAL**

OPERATOR'S NAME:	DEVON ENERGY PRODUCTION
LEASE NO.:	NMNM097151
WELL NAME & NO.:	27H -FLAGLER 8 FED
SURFACE HOLE FOOTAGE:	380'/S & 1680'/E
BOTTOM HOLE FOOTAGE	330'/N & 1605'/E
LOCATION:	Section 8., T25S., R.33E., NMP
COUNTY:	LEA County, New Mexico

TABLE OF CONTENTS

Standard Conditions of Approval (COA) apply to this APD. If any deviations to these standards exist or special COAs are required, the section with the deviation or requirement will be checked below.

- General Provisions**
- Permit Expiration**
- Archaeology, Paleontology, and Historical Sites**
- Noxious Weeds**
- Special Requirements**
 - Lesser Prairie-Chicken Timing Stipulations
 - Ground-level Abandoned Well Marker
 - Range
- Construction**
 - Notification
 - Topsoil
 - Closed Loop System
 - Federal Mineral Material Pits
 - Well Pads
 - Roads
- Road Section Diagram**
- Production (Post Drilling)**
 - Well Structures & Facilities
 - Pipelines
 - Electric Lines
- Interim Reclamation**
- Final Abandonment & Reclamation**

I. GENERAL PROVISIONS

The approval of the Application For Permit To Drill (APD) is in compliance with all applicable laws and regulations: 43 Code of Federal Regulations 3160, the lease terms, Onshore Oil and Gas Orders, Notices To Lessees, New Mexico Oil Conservation Division (NMOCD) Rules, National Historical Preservation Act As Amended, and instructions and orders of the Authorized Officer. Any request for a variance shall be submitted to the Authorized Officer on Form 3160-5, Sundry Notices and Report on Wells.

II. PERMIT EXPIRATION

If the permit terminates prior to drilling and drilling cannot be commenced within 60 days after expiration, an operator is required to submit Form 3160-5, Sundry Notices and Reports on Wells, requesting surface reclamation requirements for any surface disturbance. However, if the operator will be able to initiate drilling within 60 days after the expiration of the permit, the operator must have set the conductor pipe in order to allow for an extension of 60 days beyond the expiration date of the APD. (Filing of a Sundry Notice is required for this 60 day extension.)

III. ARCHAEOLOGICAL, PALEONTOLOGY & HISTORICAL SITES

Any cultural and/or paleontological resource discovered by the operator or by any person working on the operator's behalf shall immediately report such findings to the Authorized Officer. The operator is fully accountable for the actions of their contractors and subcontractors. The operator shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery shall be made by the Authorized Officer to determine the appropriate actions that shall be required to prevent the loss of significant cultural or scientific values of the discovery. The operator shall be held responsible for the cost of the proper mitigation measures that the Authorized Officer assesses after consultation with the operator on the evaluation and decisions of the discovery. Any unauthorized collection or disturbance of cultural or paleontological resources may result in a shutdown order by the Authorized Officer.

IV. NOXIOUS WEEDS

The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes the roads, pads, associated pipeline corridor, and adjacent land affected by the establishment of weeds due to this action. The operator shall consult with the Authorized Officer for acceptable weed control methods, which include following EPA and BLM requirements and policies.

V. SPECIAL REQUIREMENT(S)

In May 2008, the Pecos District Special Status Species Resource Management Plan Amendment (RMPA) was approved and is being implemented. In addition to the standard practices that minimize impacts, as listed above, the following COA will apply:

- Timing Limitation Stipulation / Condition of Approval for lesser prairie-chicken, to minimize noise associated impacts which could disrupt breeding and nesting activities.
- Upon abandonment, a low profile abandoned well marker will be installed to prevent raptor perching.
- Devon would need to construct and maintain escape ramps according to the following criteria:
 - Earthen escape ramps would be required to be constructed to sufficiently support livestock at no more than a 30-degree slope and spaced no more than 500 feet apart.
 - If trench is left open under an 8-hour time period, it would not be required to have an escape ramp; however, before the trench is backfilled, Devon would inspect the trench for wildlife and remove any species that are trapped at a distance of at least 100 yards away from the trench.

Raptor Nest Mitigation

- A BLM Wildlife Biologist must be contacted by the operator prior to construction activities to determine if the raptor nest is active.
- Raptor nests on special, natural habitat features, such as trees, large brush, cliff faces and escarpments, will be protected by not allowing surface disturbance within up to 200 meters of nests or by delaying activity for up to 90 days, or a combination of both. Exceptions to this requirement for raptor nests will be considered if the nests expected to be disturbed are inactive, the proposed activity is of short duration (e.g. habitat enhancement projects, fences, pipelines), and will not result in continuing activity in proximity to the nest.
- Exhaust noise from pump jack engines must be muffled or otherwise controlled so as not to exceed 75 db measured at 30 ft. from the source of the noise.

Power lines shall be constructed and designed in accordance to standards outlined in "Suggested Practices for Avian Protection on Power lines: The State of the Art in 2006" Edison Electric Institute, APLIC, and the California Energy Commission 2006. The holder shall assume the burden and expense of proving that pole designs not shown in the above publication deter raptor perching, roosting, and nesting. Such proof shall be provided by a raptor expert approved by the Authorized Officer. The BLM reserves the right to require modification or additions to all power line structures placed on this right-of-way, should they be necessary to ensure the safety of large perching birds. The holder without liability or expense shall make such modifications and/or additions to the United States.

Temporary Fence Crossing Requirement

Where entry is granted across a fence line, the fence must be braced and tied off on both sides of the passageway with H-braces prior to cutting. Once the work is completed, the fence will be restored to its prior condition, or better. Devon shall notify the private surface landowner or the grazing allotment holder prior to crossing any fences.

Cattle Guard Requirement

Where entry is granted across a fence line for an access road, the fence must be braced and tied off on both sides of the passageway with H-braces prior to cutting. Once the work is completed,

the fence will be restored to its prior condition with an appropriately sized cattle guard sufficient to carry out the project. Any new or existing cattle guards on the access route shall be repaired or replaced if they are damaged or have deteriorated beyond practical use. Devon shall be responsible for the condition of the existing cattle guards that are in place and are utilized during lease operations. Once the road is abandoned, the fence would be restored to its prior condition, or better. Devon shall notify the private surface landowner or the grazing allotment holder prior to crossing any fences.

Livestock Watering Requirement

Devon must contact the allotment holder prior to construction to identify the location of the pipeline. Devon must take measures to protect the pipeline from compression or other damages. If the pipeline is damaged or compromised in any way near the proposed project as a result of oil and gas activity, the operator is responsible for repairing the pipeline immediately. Devon must notify the BLM office (575-234-5972) and the private surface landowner or the grazing allotment holder if any damage occurs to structures that provide water to livestock.

During construction, Devon shall minimize disturbance to existing fences, water lines, troughs, windmills, and other improvements on public lands. Devon is required to promptly repair improvements to at least their former state. Functional use of these improvements will be maintained at all times. The holder will contact the grazing permittee/allottee prior to disturbing any range improvement projects. When necessary to pass through a fence line, the fence shall be braced on both sides of the passageway prior to cutting of the fence. No permanent gates will be allowed unless approved by the Authorized Officer.

VI. CONSTRUCTION

A. NOTIFICATION

The BLM shall administer compliance and monitor construction of the access road and well pad. Notify the Carlsbad Field Office at (575) 234-5909 at least 3 working days prior to commencing construction of the access road and/or well pad.

When construction operations are being conducted on this well, the operator shall have the approved APD and Conditions of Approval (COA) on the well site and they shall be made available upon request by the Authorized Officer.

B. TOPSOIL

The operator shall strip the top portion of the soil (root zone) from the entire well pad area and stockpile the topsoil along the edge of the well pad as depicted in the APD. The root zone is typically six (6) inches in depth. All the stockpiled topsoil will be redistributed over the interim reclamation areas. Topsoil shall not be used for berming the pad or facilities. For final reclamation, the topsoil shall be spread over the entire pad area for seeding preparation.

Other subsoil (below six inches) stockpiles must be completely segregated from the topsoil stockpile. Large rocks or subsoil clods (not evident in the surrounding terrain) must be buried within the approved area for interim and final reclamation.

C. CLOSED LOOP SYSTEM

Tanks are required for drilling operations: No Pits.

The operator shall properly dispose of drilling contents at an authorized disposal site.

D. FEDERAL MINERAL MATERIALS PIT

Payment shall be made to the BLM prior to removal of any federal mineral materials. Call the Carlsbad Field Office at (575) 234-5972.

E. WELL PAD SURFACING

Surfacing of the well pad is not required.

If the operator elects to surface the well pad, the surfacing material may be required to be removed at the time of reclamation. The well pad shall be constructed in a manner which creates the smallest possible surface disturbance, consistent with safety and operational needs.

F. EXCLOSURE FENCING (CELLARS & PITS)

Exclosure Fencing

The operator will install and maintain exclosure fencing for all open well cellars to prevent access to public, livestock, and large forms of wildlife before and after drilling operations until the pit is free of fluids and the operator initiates backfilling. (For examples of exclosure fencing design, refer to BLM's Oil and Gas Gold Book, Exclosure Fence Illustrations, Figure 1, Page 18.)

G. ON LEASE ACCESS ROADS**Road Width**

The access road shall have a driving surface that creates the smallest possible surface disturbance and does not exceed fourteen (14) feet in width. The maximum width of surface disturbance, when constructing the access road, shall not exceed twenty-five (25) feet.

Surfacing

Surfacing material is not required on the new access road driving surface. If the operator elects to surface the new access road or pad, the surfacing material may be required to be removed at the time of reclamation.

Where possible, no improvements should be made on the unsurfaced access road other than to remove vegetation as necessary, road irregularities, safety issues, or to fill low areas that may sustain standing water.

The Authorized Officer reserves the right to require surfacing of any portion of the access road at any time deemed necessary. Surfacing may be required in the event the road deteriorates, erodes, road traffic increases, or it is determined to be beneficial for future field development. The surfacing depth and type of material will be determined at the time of notification.

Crowning

Crowning shall be done on the access road driving surface. The road crown shall have a grade of approximately 2% (i.e., a 1" crown on a 14' wide road). The road shall conform to Figure 1; cross section and plans for typical road construction.

Ditching

Ditching shall be required on both sides of the road.

Turnouts


Vehicle turnouts shall be constructed on the road. Turnouts shall be intervisible with interval spacing distance less than 1000 feet. Turnouts shall conform to Figure 1; cross section and plans for typical road construction.

Drainage

Drainage control systems shall be constructed on the entire length of road (e.g. ditches, sidehill out-sloping and in-sloping, lead-off ditches, culvert installation, and low water crossings).

A typical lead-off ditch has a minimum depth of 1 foot below and a berm of 6 inches above natural ground level. The berm shall be on the down-slope side of the lead-off ditch.

Cross Section of a Typical Lead-off Ditch



All lead-off ditches shall be graded to drain water with a 1 percent minimum to 3 percent maximum ditch slope. The spacing interval are variable for lead-off ditches and shall be determined according to the formula for spacing intervals of lead-off ditches, but may be amended depending upon existing soil types and centerline road slope (in %);

Formula for Spacing Interval of Lead-off Ditches

Example - On a 4% road slope that is 400 feet long, the water flow shall drain water into a lead-off ditch. Spacing interval shall be determined by the following formula:

$$400 \text{ foot road with } 4\% \text{ road slope: } \frac{400'}{4\%} + 100' = 200' \text{ lead-off ditch interval}$$

Cattle guards

An appropriately sized cattle guard sufficient to carry out the project shall be installed and maintained at fence/road crossings. Any existing cattle guards on the access road route shall be repaired or replaced if they are damaged or have deteriorated beyond practical use. The operator shall be responsible for the condition of the existing cattle guards that are in place and are utilized during lease operations.

Fence Requirement

Where entry is granted across a fence line, the fence shall be braced and tied off on both sides of the passageway prior to cutting. The operator shall notify the private surface landowner or the grazing allotment holder prior to crossing any fences.

Public Access

Public access on this road shall not be restricted by the operator without specific written approval granted by the Authorized Officer.

Construction Steps

1. Salvage topsoil
2. Construct road

3. Redistribute topsoil
4. Revegetate slopes




Figure 1. Cross-sections and plans for typical road sections representative of BLM resource or FS local and higher-class roads.

VII. PRODUCTION (POST DRILLING)

A. WELL STRUCTURES & FACILITIES

Placement of Production Facilities

Production facilities should be placed on the well pad to allow for maximum interim recontouring and revegetation of the well location.

Exclosure Netting (Open-top Tanks)

Immediately following active drilling or completion operations, the operator will take actions necessary to prevent wildlife and livestock access, including avian wildlife, to all open-topped tanks that contain or have the potential to contain salinity sufficient to cause harm to wildlife or livestock, hydrocarbons, or Resource Conservation and Recovery Act of 1976-exempt hazardous substances. At a minimum, the operator will net, screen, or cover open-topped tanks to exclude wildlife and livestock and prevent mortality. If the operator uses netting, the operator will cover and secure the open portion of the tank to prevent wildlife entry. The operator will net, screen, or cover the tanks until the operator removes the tanks from the location or the tanks no longer contain substances that could be harmful to wildlife or livestock. Use a maximum netting mesh size of 1 ½ inches. The netting must not be in contact with fluids and must not have holes or gaps.

Chemical and Fuel Secondary Containment and Exclosure Screening

The operator will prevent all hazardous, poisonous, flammable, and toxic substances from coming into contact with soil and water. At a minimum, the operator will install and maintain an impervious secondary containment system for any tank or barrel containing hazardous, poisonous, flammable, or toxic substances sufficient to contain the contents of the tank or barrel and any drips, leaks, and anticipated precipitation. The operator will dispose of fluids within the containment system that do not meet applicable state or U. S. Environmental Protection Agency livestock water standards in accordance with state law; the operator must not drain the fluids to the soil or ground. The operator will design, construct, and maintain all secondary containment systems to prevent wildlife and livestock exposure to harmful substances. At a minimum, the operator will install effective wildlife and livestock exclosure systems such as fencing, netting, expanded metal mesh, lids, and grate covers. Use a maximum netting mesh size of 1 ½ inches.

Open-Vent Exhaust Stack Exclosures

The operator will construct, modify, equip, and maintain all open-vent exhaust stacks on production equipment to prevent birds and bats from entering, and to discourage perching, roosting, and nesting. (*Recommended exclosure structures on open-vent exhaust stacks are in the shape of a cone.*) Production equipment includes, but may not be limited to, tanks, heater-treaters, separators, dehydrators, flare stacks, in-line units, and compressor mufflers.

Containment Structures

Proposed production facilities such as storage tanks and other vessels will have a secondary containment structure that is constructed to hold the capacity of 1.5 times the largest tank, plus freeboard to account for precipitation, unless more stringent protective requirements are deemed necessary.

Painting Requirement

All above-ground structures including meter housing that are not subject to safety requirements shall be painted a flat non-reflective paint color, **Shale Green** from the BLM Standard Environmental Color Chart (CC-001: June 2008).

B. PIPELINES

BURIED PIPELINE STIPULATIONS

A copy of the application (Grant, APD, or Sundry Notice) and attachments, including conditions of approval, survey plat and/or map, will be on location during construction. BLM personnel may request to you a copy of your permit during construction to ensure compliance with all stipulations.

Holder agrees to comply with the following stipulations to the satisfaction of the Authorized Officer:

1. The Holder shall indemnify the United States against any liability for damage to life or property arising from the occupancy or use of public lands under this grant.
2. The Holder shall comply with all applicable Federal laws and regulations existing or hereafter enacted or promulgated. In any event, the holder shall comply with the Toxic Substances Control Act of 1976 as amended, 15 USC 2601 et seq. (1982) with regards to any toxic substances that are used, generated by or stored on the right-of-way or on facilities authorized under this right-of-way grant. (See 40 CFR Part 702-799 and especially, provisions on polychlorinated biphenyls, 40 CFR 761.1-761.193.) Additionally, any release of toxic substances (leaks, spills, etc.) in excess of the reportable quantity established by 40 CFR Part 117 shall be reported as required by the Comprehensive Environmental Response, Compensation, and Liability Act, section 102b. A copy of any report required or requested by any Federal agency or State government as a result of a reportable release or spill of any toxic substances shall be furnished to the authorized officer concurrent with the filing of the reports to the involved Federal agency or State government.
3. The holder agrees to indemnify the United States against any liability arising from the release of any hazardous substance or hazardous waste (as these terms are defined in the Comprehensive Environmental Response, Compensation and Liability Act of 1980, 42 U.S.C. 9601, et seq. or the Resource Conservation and Recovery Act, 42 U.S.C.6901, et seq.) on the Right-of-Way (unless the release or threatened release is wholly unrelated to the Right-of-Way holder's activity on the Right-of-Way), or resulting from the activity of the Right-of-Way holder on the Right-of-Way. This agreement applies without regard to whether a release is caused by the holder, its agent, or unrelated third parties.

4. If, during any phase of the construction, operation, maintenance, or termination of the pipeline, any oil or other pollutant should be discharged from the pipeline system, impacting Federal lands, the control and total removal, disposal, and cleaning up of such oil or other pollutant, wherever found, shall be the responsibility of holder, regardless of fault. Upon failure of holder to control, dispose of, or clean up such discharge on or affecting Federal lands, or to repair all damages resulting therefrom, on the Federal lands, the Authorized Officer may take such measures as he deems necessary to control and clean up the discharge and restore the area, including where appropriate, the aquatic environment and fish and wildlife habitats, at the full expense of the holder. Such action by the Authorized Officer shall not relieve holder of any responsibility as provided herein.

5. All construction and maintenance activity will be confined to the authorized right-of-way.
6. The pipeline will be buried with a minimum cover of 36 inches between the top of the pipe and ground level.
7. The maximum allowable disturbance for construction in this right-of-way will be 30 feet:
 - Blading of vegetation within the right-of-way will be allowed: maximum width of blading operations will not exceed 20 feet. The trench is included in this area. (*Blading is defined as the complete removal of brush and ground vegetation.*)
 - Clearing of brush species within the right-of-way will be allowed: maximum width of clearing operations will not exceed 30 feet. The trench and bladed area are included in this area. (*Clearing is defined as the removal of brush while leaving ground vegetation (grasses, weeds, etc.) intact. Clearing is best accomplished by holding the blade 4 to 6 inches above the ground surface.*)
 - The remaining area of the right-of-way (if any) shall only be disturbed by compressing the vegetation. (*Compressing can be caused by vehicle tires, placement of equipment, etc.*)
8. The holder shall stockpile an adequate amount of topsoil where blading is allowed. The topsoil to be stripped is approximately 6 inches in depth. The topsoil will be segregated from other spoil piles from trench construction. The topsoil will be evenly distributed over the bladed area for the preparation of seeding.
9. The holder shall minimize disturbance to existing fences and other improvements on public lands. The holder is required to promptly repair improvements to at least their former state. Functional use of these improvements will be maintained at all times. The holder will contact the owner of any improvements prior to disturbing them. When necessary to pass through a fence line, the fence shall be braced on both sides of the passageway prior to cutting of the fence. No permanent gates will be allowed unless approved by the Authorized Officer.
10. Vegetation, soil, and rocks left as a result of construction or maintenance activity will be randomly scattered on this right-of-way and will not be left in rows, piles, or berms, unless otherwise approved by the Authorized Officer. The entire right-of-way shall be recontoured to match the surrounding landscape. The backfilled soil shall be compacted and a 6 inch berm will be left over the ditch line to allow for settling back to grade.
11. In those areas where erosion control structures are required to stabilize soil conditions, the holder will install such structures as are suitable for the specific soil conditions being encountered and which are in accordance with sound resource management practices.

12. The holder will reseed all disturbed areas. Seeding will be done according to the attached seeding requirements, using the following seed mix.

- | | |
|--|--|
| <input type="checkbox"/> seed mixture 1 | <input type="checkbox"/> seed mixture 3 |
| <input type="checkbox"/> seed mixture 2 | <input type="checkbox"/> seed mixture 4 |
| <input checked="" type="checkbox"/> seed mixture 2/LPC | <input type="checkbox"/> Aplomado Falcon Mixture |

13. All above-ground structures not subject to safety requirements shall be painted by the holder to blend with the natural color of the landscape. The paint used shall be color which simulates "Standard Environmental Colors" – **Shale Green**, Munsell Soil Color No. 5Y 4/2.

14. The pipeline will be identified by signs at the point of origin and completion of the right-of-way and at all road crossings. At a minimum, signs will state the holder's name, BLM serial number, and the product being transported. All signs and information thereon will be posted in a permanent, conspicuous manner, and will be maintained in a legible condition for the life of the pipeline.

15. The holder shall not use the pipeline route as a road for purposes other than routine maintenance as determined necessary by the Authorized Officer in consultation with the holder before maintenance begins. The holder will take whatever steps are necessary to ensure that the pipeline route is not used as a roadway. As determined necessary during the life of the pipeline, the Authorized Officer may ask the holder to construct temporary deterrence structures.

16. Any cultural and/or paleontological resources (historic or prehistoric site or object) discovered by the holder, or any person working on his behalf, on public or Federal land shall be immediately reported to the Authorized Officer. Holder shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery will be made by the Authorized Officer to determine appropriate actions to prevent the loss of significant cultural or scientific values. The holder will be responsible for the cost of evaluation and any decision as to proper mitigation measures will be made by the Authorized Officer after consulting with the holder.

17. The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes associated roads, pipeline corridor and adjacent land affected by the establishment of weeds due to this action. The operator shall consult with the Authorized Officer for acceptable weed control methods, which include following EPA and BLM requirements and policies.

18. Escape Ramps - The operator will construct and maintain pipeline/utility trenches that are not otherwise fenced, screened, or netted to prevent livestock, wildlife, and humans from becoming entrapped. At a minimum, the operator will construct and maintain escape ramps, ladders, or

other methods of avian and terrestrial wildlife escape in the trenches according to the following criteria:

- a. Any trench left open for eight (8) hours or less is not required to have escape ramps; however, before the trench is backfilled, the contractor/operator shall inspect the trench for wildlife, remove all trapped wildlife, and release them at least 100 yards from the trench.
- b. For trenches left open for eight (8) hours or more, earthen escape ramps (built at no more than a 30 degree slope and spaced no more than 500 feet apart) shall be placed in the trench.

19. Special Stipulations:

Lesser Prairie-Chicken

Oil and gas activities will not be allowed in lesser prairie-chicken habitat during the period from March 1st through June 15th annually. During that period, other activities that produce noise or involve human activity, such as the maintenance of oil and gas facilities, geophysical exploration other than 3-D operations, and pipeline, road, and well pad construction, will be allowed except between 3:00 am and 9:00 am. The 3:00 am to 9:00 am restriction will not apply to normal, around-the-clock operations, such as venting, flaring, or pumping, which do not require a human presence during this period. Normal vehicle use on existing roads will not be restricted. Exhaust noise from pump jack engines must be muffled or otherwise controlled so as not to exceed 75 db measured at 30 ft. from the source of the noise.

C. ELECTRIC LINES

STANDARD STIPULATIONS FOR OVERHEAD ELECTRIC DISTRIBUTION LINES

A copy of the grant and attachments, including stipulations, survey plat and/or map, will be on location during construction. BLM personnel may request to you a copy of your permit during construction to ensure compliance with all stipulations.

Holder agrees to comply with the following stipulations to the satisfaction of the Authorized Officer:

1. The holder shall indemnify the United States against any liability for damage to life or property arising from the occupancy or use of public lands under this grant.
2. The holder shall comply with all applicable Federal laws and regulations existing or hereafter enacted or promulgated. In any event, the holder shall comply with the Toxic Substances Control Act of 1976 as amended, 15 USC 2601 *et seq.* (1982) with regards to any toxic substances that are used, generated by or stored on the right-of-way or on facilities authorized under this right-of-way grant. (See 40 CFR, Part 702-799 and especially, provisions on polychlorinated biphenyls, 40 CFR 761.1-761.193.) Additionally, any release of toxic substances (leaks, spills, etc.) in excess of the reportable quantity established by 40 CFR, Part 117 shall be reported as required by the Comprehensive Environmental Response, Compensation, and Liability Act, section 102b. A copy of any report required or requested by any Federal agency or State government as

a result of a reportable release or spill of any toxic substances shall be furnished to the authorized officer concurrent with the filing of the reports to the involved Federal agency or State government.

3. The holder agrees to indemnify the United States against any liability arising from the release of any hazardous substance or hazardous waste (as these terms are defined in the Comprehensive Environmental Response, Compensation and Liability Act of 1980, 42 U.S.C. 9601, et seq. or the Resource Conservation and Recovery Act, 42 U.S.C. 6901, et seq.) on the Right-of-Way (unless the release or threatened release is wholly unrelated to the Right-of-Way holder's activity on the Right-of-Way), or resulting from the activity of the Right-of-Way holder on the Right-of-Way. This agreement applies without regard to whether a release is caused by the holder, its agent, or unrelated third parties.

4. There will be no clearing or blading of the right-of-way unless otherwise agreed to in writing by the Authorized Officer.

5. Power lines shall be constructed and designed in accordance to standards outlined in "Suggested Practices for Avian Protection on Power lines: The State of the Art in 2006" Edison Electric Institute, APLIC, and the California Energy Commission 2006 . The holder shall assume the burden and expense of proving that pole designs not shown in the above publication deter raptor perching, roosting, and nesting. Such proof shall be provided by a raptor expert approved by the Authorized Officer. The BLM reserves the right to require modification or additions to all powerline structures placed on this right-of-way, should they be necessary to ensure the safety of large perching birds. Such modifications and/or additions shall be made by the holder without liability or expense to the United States.

Raptor deterrence will consist of but not limited to the following: triangle perch discouragers shall be placed on each side of the cross arms and a nonconductive perching deterrence shall be placed on all vertical poles that extend past the cross arms.

6. The holder shall minimize disturbance to existing fences and other improvements on public lands. The holder is required to promptly repair improvements to at least their former state. Functional use of these improvements will be maintained at all times. The holder will contact the owner of any improvements prior to disturbing them. When necessary to pass through a fence line, the fence shall be braced on both sides of the passageway prior to cutting the fence. No permanent gates will be allowed unless approved by the Authorized Officer.

7. The BLM serial number assigned to this authorization shall be posted in a permanent, conspicuous manner where the power line crosses roads and at all serviced facilities. Numbers will be at least two inches high and will be affixed to the pole nearest the road crossing and at the facilities served.

8. Upon cancellation, relinquishment, or expiration of this grant, the holder shall comply with those abandonment procedures as prescribed by the Authorized Officer.

9. All surface structures (poles, lines, transformers, etc.) shall be removed within 180 days of abandonment, relinquishment, or termination of use of the serviced facility or facilities or within 180 days of abandonment, relinquishment, cancellation, or expiration of this grant, whichever comes first. This will not apply where the power line extends service to an active, adjoining facility or facilities.

10. Any cultural and/or paleontological resource (historic or prehistoric site or object) discovered by the holder, or any person working on his behalf, on public or Federal land shall be immediately reported to the Authorized Officer. Holder shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery will be made by the Authorized Officer to determine appropriate actions to prevent the loss of significant cultural or scientific values. The holder will be responsible for the cost of evaluation and any decision as to proper mitigation measures will be made by the Authorized Officer after consulting with the holder.

11. Special Stipulations:

- For reclamation remove poles, lines, transformer, etc. and dispose of properly.
- Fill in any holes from the poles removed.

Timing Limitation Stipulation/Condition of Approval for Lesser Prairie-Chicken:

Oil and gas activities including 3-D geophysical exploration, and drilling will not be allowed in lesser prairie-chicken habitat during the period from March 1st through June 15th annually. During that period, other activities that produce noise or involve human activity, such as the maintenance of oil and gas facilities, geophysical exploration other than 3-D operations, and pipeline, road, and well pad construction, will be allowed except between 3:00 am and 9:00 am. The 3:00 am to 9:00 am restriction will not apply to normal, around-the-clock operations, such as venting, flaring, or pumping, which do not require a human presence during this period. Additionally, no new drilling will be allowed within up to 200 meters of leks known at the time of permitting. Normal vehicle use on existing roads will not be restricted. Exhaust noise from pump jack engines must be muffled or otherwise controlled so as not to exceed 75 db measured at 30 ft. from the source of the noise.

STANDARD STIPULATIONS FOR OIL AND GAS RELATED SITES

A copy of the application (Grant/Sundry Notice) and attachments, including stipulations and map, will be on location during construction. BLM personnel may request to view a copy of your permit during construction to ensure compliance with all stipulations.

The holder agrees to comply with the following stipulations to the satisfaction of the Authorized Officer, BLM.

1. The holder shall indemnify the United States against any liability for damage to life or property arising from the occupancy or use of public lands under this grant and for all response costs, penalties, damages, claims, and other costs arising from the provisions of the Resource Conservation and Recovery Act (RCRA), 42 U.S.C. Chap. 82, Section 6901 et. seq., from the Comprehensive Environmental Response, Compensation and Liability Act (CERCLA), 42 U.S.C. Chap. 109, Section 9601 et. seq., and from other applicable environmental statutes.

2. The holder shall comply with all applicable Federal laws and regulations existing or hereafter enacted or promulgated. In any event, the holder shall comply with the Toxic Substances Control Act of 1976, as amended (15 U.S.C. 2601, et. seq.) with regard to any toxic substances that are used, generated by or stored on the right-of-way or on facilities authorized by this grant. (See 40 CFR, Part 702-799 and especially, provisions on polychlorinated biphenyls, 40 CFR 761.1-761.193.) Additionally, any release of toxic substances (leaks, spills, etc.) in excess of the reportable quantity established by 40 CFR, Part 117 shall be reported as required by the Comprehensive Environmental Response, Compensation and Liability Act, Section 102b. A copy of any report required or requested by any Federal agency or State government as a result of a reportable release or spill of any toxic substances shall be furnished to the Authorized Officer concurrent with the filing of the reports to the involved Federal agency or State government.

3. The holder agrees to indemnify the United States against any liability arising from the release of any hazardous substance or hazardous waste (as these terms are defined in the Comprehensive Environmental Response, Compensation and Liability Act of 1980, 42 U.S.C. 9601, et. seq. or the Resource Conservation and Recovery Act, 42 U.S.C. 6901, et. seq.) on the right-of-way (unless the release or threatened release is wholly unrelated to the right-of-way holder's activity on the right-of-way). This agreement applies without regard to whether a release is caused by the holder, its agent, or unrelated third parties.

4. If, during any phase of the construction, operation, maintenance, or termination of the site or related pipeline(s), any oil or other pollutant should be discharged from site facilities, the pipeline(s) or from containers or vehicles impacting Federal lands, the control and total removal, disposal, and cleanup of such oil or other pollutant, wherever found, shall be the responsibility of the holder, regardless of fault. Upon failure of the holder to control, dispose of, or clean up such discharge on or affecting Federal lands, or to repair all damages to Federal lands resulting therefrom, the Authorized Officer may take such measures as deemed necessary to control and cleanup the discharge and restore the area, including, where appropriate, the aquatic environment and fish and wildlife habitats, at the full expense of the holder. Such action by the Authorized Officer shall not relieve the holder of any liability or responsibility.

5. Sites shall be maintained in an orderly, sanitary condition at all times. Waste materials, both liquid and solid, shall be disposed of promptly at an appropriate, authorized waste disposal facility in accordance with all applicable State and Federal laws. "Waste" means all discarded matter including, but not limited to, human waste,

trash, garbage, refuse, petroleum products, brines, chemicals, oil drums, ashes, and equipment.

6. The operator will notify the Bureau of Land Management (BLM) authorized officer and nearest Fish and Wildlife Service (FWS) Law Enforcement office within 24 hours, if the operator discovers a dead or injured federally protected species (i.e., migratory bird species, bald or golden eagle, or species listed by the FWS as threatened or endangered) in or adjacent to a pit, trench, tank, exhaust stack, or fence. (If the operator is unable to contact the FWS Law Enforcement office, the operator must contact the nearest FWS Ecological Services office.)

7. All above-ground structures not subject to safety requirements shall be painted by the holder to blend with the natural color of the landscape. The paint used shall be a color which simulates "Standard Environmental Colors" designated by the Rocky Mountain Five-State Interagency Committee. The color selected for this project is **Shale Green**, Munsell Soil Color Chart Number 5Y 4/2.

8. Any cultural and/or paleontological resource (historic or prehistoric site or object) discovered by the holder, or any person working on the holder's behalf, on public or Federal land shall be immediately reported to the Authorized Officer. The holder shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery will be made by the Authorized Officer to determine appropriate actions to prevent the loss of significant cultural or scientific values. The holder will be responsible for the cost of evaluation and any decision as to the proper mitigation measures will be made by the Authorized Officer after consulting with the holder.

9. A sales contract for removal of mineral material (caliche, sand, gravel, fill dirt) from an authorized pit, site, or on location must be obtained from the BLM prior to commencing construction. There are several options available for purchasing mineral material: contact the BLM office (575-234-5972).

10. The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes the roads, pads, associated pipeline corridor, and adjacent land affected by the establishment of weeds due to this action. The operator shall consult with the Authorized Officer for acceptable weed control methods, which include following EPA and BLM requirements and policies.

11. Once the site is no longer in service or use, the site must undergo final abandonment. At final abandonment, the site and access roads must undergo "final" reclamation so that the character and productivity of the land are restored. Earthwork for final reclamation must be completed within six (6) months of the abandonment of the site. All pads and facility locations and roads must be reclaimed to a satisfactory revegetated, safe, and stable condition, unless an agreement is made with the landowner or BLM to keep the

road and/or pad intact. After all disturbed areas have been satisfactorily prepared, these areas need to be revegetated with the seed mixture provided. Seeding should be accomplished by drilling on the contour whenever practical or by other approved methods. Seeding may need to be repeated until revegetation is successful, as determined by the BLM.

Operators shall contact a BLM surface protection specialist prior to surface abandonment operations for site specific objectives (Jim Amos: 575-234-5909).

12. The holder shall stockpile an adequate amount of topsoil where blading occurs. The topsoil to be stripped is approximately 6 inches in depth. The topsoil will be segregated from other spoil piles. The topsoil will be used for final reclamation.

13. The holder will reseed all disturbed areas. Seeding will be done according to the attached seeding requirements, using the following seed mix.

- seed mixture 1
- seed mixture 2
- seed mixture 2/LPC
- seed mixture 3
- seed mixture 4
- Aplomado Falcon Mixture

14. In those areas where erosion control structures are required to stabilize soil conditions, the holder shall install such structures as are suitable for the specific soil conditions being encountered and which are in accordance with sound management practices. Any earth work will require prior approval by the Authorized Officer.

15. Open-topped Tanks - The operator will take actions necessary to prevent wildlife and livestock access, including avian wildlife, to all open-topped tanks that contain or have the potential to contain salinity sufficient to cause harm to wildlife or livestock, hydrocarbons, or Resource Conservation and Recovery Act of 1976-exempt hazardous substances. At a minimum, the operator will net, screen, or cover open-topped tanks to exclude wildlife and livestock and prevent mortality. If the operator uses netting, the operator will cover and secure the open portion of the tank to prevent wildlife entry. The operator will net, screen, or cover the tanks until the operator removes the tanks from the location or the tanks no longer contain substances that could be harmful to wildlife or livestock. Use a maximum netting mesh size of 1 ½ inches. The netting must not be in contact with fluids and must not have holes or gaps

16. The operator will prevent all hazardous, poisonous, flammable, and toxic substances from coming into contact with soil and water. At a minimum, the operator will install and maintain an

impervious secondary containment system for any tank or barrel containing hazardous, poisonous, flammable, or toxic substances sufficient to contain the contents of the tank or barrel and any drips, leaks, and anticipated precipitation. The operator will dispose of

fluids within the containment system that do not meet applicable state or U. S. Environmental Protection Agency livestock water standards in accordance with state law; the operator must not drain the fluids to the soil or ground. The operator will design, construct, and maintain all secondary containment systems to prevent wildlife and livestock exposure to harmful substances. At a minimum, the operator will install effective wildlife and livestock enclosure systems such as fencing, netting, expanded metal mesh, lids, and grate covers. Use a maximum netting mesh size of 1 ½ inches.

17. Open-Vent Exhaust Stack Enclosures – The operator will construct, modify, equip, and maintain all open-vent exhaust stacks on production equipment to prevent birds and bats from entering, and to discourage perching, roosting, and nesting. (Recommended enclosure structures on open-vent exhaust stacks are in the shape of a cone.) Production equipment includes, but may not be limited to, tanks, heater-treaters, separators, dehydrators, flare stacks, in-line units, and compressor mufflers.

18. Containment Structures - Proposed production facilities such as storage tanks and other vessels will have a secondary containment structure that is constructed to hold the capacity of 1.5 times the largest tank, plus freeboard to account for precipitation, unless more stringent protective requirements are deemed necessary.

19. Special Stipulations:

Lesser Prairie-Chicken

Oil and gas activities will not be allowed in lesser prairie-chicken habitat during the period from March 1st through June 15th annually. During that period, other activities that produce noise or involve human activity, such as the maintenance of oil and gas facilities, geophysical exploration other than 3-D operations, and pipeline, road, and well pad construction, will be allowed except between 3:00 am and 9:00 am. The 3:00 am to 9:00 am restriction will not apply to normal, around-the-clock operations, such as venting, flaring, or pumping, which do not require a human presence during this period. Normal vehicle use on existing roads will not be restricted. Exhaust noise from permanent engines must be muffled or otherwise controlled so as not to exceed 75 db measured at 30 ft. from the source of the noise.

VIII. INTERIM RECLAMATION

During the life of the development, all disturbed areas not needed for active support of production operations should undergo interim reclamation in order to minimize the environmental impacts of development on other resources and uses.

Within six (6) months of well completion, operators should work with BLM surface management specialists (Jim Amos: 575-234-5909) to devise the best strategies to reduce the size of the location. Interim reclamation should allow for remedial well operations, as well as safe and efficient removal of oil and gas.

During reclamation, the removal of caliche is important to increasing the success of revegetating the site. Removed caliche that is free of contaminants may be used for road repairs, fire walls or for building other roads and locations. In order to operate the well or complete workover operations, it may be necessary to drive, park and operate on restored interim vegetation within the previously disturbed area. Disturbing revegetated areas for production or workover operations will be allowed. If there is significant disturbance and loss of vegetation, the area will need to be revegetated. Communicate with the appropriate BLM office for any exceptions/exemptions if needed.

All disturbed areas after they have been satisfactorily prepared need to be reseeded with the seed mixture provided below.

Upon completion of interim reclamation, the operator shall submit a Sundry Notices and Reports on Wells, Subsequent Report of Reclamation (Form 3160-5).

IX. FINAL ABANDONMENT & RECLAMATION

At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land are restored.

Earthwork for final reclamation must be completed within six (6) months of well plugging. All pads, pits, facility locations and roads must be reclaimed to a satisfactory revegetated, safe, and stable condition, unless an agreement is made with the landowner or BLM to keep the road and/or pad intact.

After all disturbed areas have been satisfactorily prepared, these areas need to be revegetated with the seed mixture provided below. Seeding should be accomplished by drilling on the contour whenever practical or by other approved methods. Seeding may need to be repeated until revegetation is successful, as determined by the BLM.

Operators shall contact a BLM surface protection specialist prior to surface abandonment operations for site specific objectives (Jim Amos: 575-234-5909).

Ground-level Abandoned Well Marker to avoid raptor perching: Upon the plugging and subsequent abandonment of the well, the well marker will be installed at ground level on a plate containing the pertinent information for the plugged well.

Seed Mixture for LPC Sand/Shinnery Sites

Holder shall seed all disturbed areas with the seed mixture listed below. The seed mixture shall be planted in the amounts specified in pounds of pure live seed (PLS)* per acre. There shall be no primary or secondary noxious weeds in the seed mixture. Seed will be tested and the viability testing of seed shall be done in accordance with State law(s) and within nine (9) months prior to purchase. Commercial seed shall be either certified or registered seed. The seed container shall be tagged in accordance with State law(s) and available for inspection by the Authorized Officer.

Seed will be planted using a drill equipped with a depth regulator to ensure proper depth of planting where drilling is possible. The seed mixture will be evenly and uniformly planted over the disturbed area (smaller/heavier seeds have a tendency to drop the bottom of the drill and are planted first). Holder shall take appropriate measures to ensure this does not occur. Where drilling is not possible, seed will be broadcast and the area shall be raked or chained to cover the seed. When broadcasting the seed, the pounds per acre are to be doubled. Seeding shall be repeated until a satisfactory stand is established as determined by the Authorized Officer. Evaluation of growth may not be made before completion of at least one full growing season after seeding.

Species to be planted in pounds of pure live seed* per acre:

<u>Species</u>	<u>lb/acre</u>
Plains Bristlegrass	5lbs/A
Sand Bluestem	5lbs/A
Little Bluestem	3lbs/A
Big Bluestem	6lbs/A
Plains Coreopsis	2lbs/A
Sand Dropseed	1lbs/A

*Pounds of pure live seed:

Pounds of seed x percent purity x percent germination = pounds pure live seed



**Devon Energy Center
333 West Sheridan Avenue
Oklahoma City, Oklahoma 73102-5015**

Hydrogen Sulfide (H₂S) Contingency Plan

For



Flagler 8 Federal 27H

**Sec-8 T-25S R-33E
380' FSL & 1680' FEL
LAT. = 32.1388981' N (NAD83)
LONG = 103.5911771' W**

Lea County NM

Flagler 8 Federal 27H

This is an open drilling site. H₂S monitoring equipment and emergency response equipment will be used within 500' of zones known to contain H₂S, including warning signs, wind indicators and H₂S monitor.



Assumed 100 ppm ROE = 3000' (Radius of Exposure)
100 ppm H₂S concentration shall trigger activation of this plan.

Escape

Crews shall escape upwind of escaping gas in the event of an emergency release of gas. Escape can be facilitated from the location entrance road. Crews should then block the entrance to the location from the lease road so as not to allow anyone traversing into a hazardous area. The blockade should be at a safe distance outside of the ROE. There are no homes or buildings in or near the ROE.

Assumed 100 ppm ROE = 3000'

100 ppm H₂S concentration shall trigger activation of this plan.

Emergency Procedures

In the event of a release of gas containing H₂S, the first responder(s) must

- **Isolate the area and prevent entry by other persons into the 100 ppm ROE.**
- **Evacuate any public places encompassed by the 100 ppm ROE.**
- **Be equipped with H₂S monitors and air packs in order to control the release.**
- **Use the “buddy system” to ensure no injuries occur during the response**
- **Take precautions to avoid personal injury during this operation.**
- **Contact operator and/or local officials to aid in operation. See list of phone numbers attached.**
- **Have received training in the**
 - **Detection of H₂S, and**
 - **Measures for protection against the gas,**
 - **Equipment used for protection and emergency response.**

Ignition of Gas Source

Should control of the well be considered lost and ignition considered, take care to protect against exposure to Sulfur Dioxide (SO₂). Intentional ignition must be coordinated with the NMOCD and local officials. Additionally the NM State Police may become involved. NM State Police shall be the Incident Command on scene of any major release. Take care to protect downwind whenever there is an ignition of the gas

Characteristics of H₂S and SO₂

Common Name	Chemical Formula	Specific Gravity	Threshold Limit	Hazardous Limit	Lethal Concentration
Hydrogen Sulfide	H₂S	1.189 Air = 1	10 ppm	100 ppm/hr	600 ppm
Sulfur Dioxide	SO₂	2.21 Air = 1	2 ppm	N/A	1000 ppm

Contacting Authorities

Devon Energy Corp. personnel must liaison with local and state agencies to ensure a proper response to a major release. Additionally, the OCD must be notified of the release as soon as possible but no later than 4 hours. Agencies will ask for information such as type and volume of release, wind direction, location of release, etc. Be prepared with all information available. The following call list of essential and potential responders has been prepared for use during a release. Devon Energy Corp. Company response must be in coordination with the State of New Mexico’s ‘Hazardous Materials Emergency Response Plan’ (HMER)

Hydrogen Sulfide Drilling Operation Plan

I. HYDROGEN SULFIDE (H₂S) TRAINING

All personnel, whether regularly assigned, contracted, or employed on an unscheduled basis, will receive training from a qualified instructor in the following areas prior to commencing drilling operations on this well:

1. The hazards and characteristics of hydrogen sulfide (H₂S)
2. The proper use and maintenance of personal protective equipment and life support systems.
3. The proper use of H₂S detectors, alarms, warning systems, briefing areas, evacuation procedures, and prevailing winds.
4. The proper techniques for first aid and rescue procedures.

In addition, supervisory personnel will be trained in the following areas:

1. The effects of H₂S metal components. If high tensile tubulars are to be used, personnel will be trained in their special maintenance requirements.
2. Corrective action and shut-in procedures when drilling or reworking a well and blowout prevention and well control procedures.
3. The contents and requirements of the H₂S Drilling Operations Plan and Public Protection Plan.

There will be an initial training session just prior to encountering a known or probable H₂S zone (within 3 days or 500 feet) and weekly H₂S and well control drills for all personnel in each crew. The initial training session shall include a review of the site specific H₂S Drilling Operations Plan and the Public Protection Plan.

II. HYDROGEN SULFIDE TRAINING

Note: All H₂S safety equipment and systems will be installed, tested, and operational when drilling reaches a depth of 500 feet above, or three days prior to penetrating the first zone containing or reasonably expected to contain H₂S.

1. Well Control Equipment

- A. Flare line
- B. Choke manifold – Remotely Operated
- C. Blind rams and pipe rams to accommodate all pipe sizes with properly sized closing unit
- D. Auxiliary equipment may include if applicable: annular preventer and rotating head.
- E. Mud/Gas Separator

2. Protective equipment for essential personnel:

30-minute SCBA units located at briefing areas, as indicated on well site diagram, with escape units available in the top doghouse. As it may be difficult to communicate audibly while wearing these units, hand signals shall be utilized.

3. H₂S detection and monitoring equipment:

Portable H₂S monitors positioned on location for best coverage and response. These units have warning lights which activate when H₂S levels reach 10 ppm and audible sirens which activate at 15 ppm. Sensor locations:

- Bell nipple
- Possum Belly/Shale shaker
- Rig floor
- Choke manifold
- Cellar

Visual warning systems:

- A. Wind direction indicators as shown on well site diagram
- B. Caution/ Danger signs shall be posted on roads providing direct access to locations. Signs will be painted a high visibility yellow with black lettering of sufficient size to be reasonable distance from the immediate location. Bilingual signs will be used when appropriate.

4. Mud program:

The mud program has been designed to minimize the volume of H₂S circulated to surface. Proper mud weight, safe drilling practices and the use of H₂S scavengers will minimize hazards when penetrating H₂S bearing zones.

5. Metallurgy:

- A. All drill strings, casings, tubing, wellhead, blowout preventer, drilling spool, kill lines, choke manifold lines, and valves shall be H₂S trim.
- B. All elastomers used for packing and seals shall be H₂S trim.

6. Communication:

- A. Company personnel have/use cellular telephones in the field.
- B. Land line (telephone) communications at Office

7. Well testing:


- A. Drill stem testing will be performed with a minimum number of personnel in the immediate vicinity, which are necessary to safety and adequately conduct the test. The drill stem testing will be conducted during daylight hours and formation fluids will not be flowed to the surface. All drill-stem-testing operations conducted in an H₂S environment will use the closed chamber method of testing.
- B. There will be no drill stem testing.

<u>Devon Energy Corp. Company Call List</u>		
Drilling Supervisor – Basin – Mark Kramer		405-823-4796
EHS Professional – Laura Wright		405-439-8129
<u>Agency Call List</u>		
<u>Lea County (575)</u>	Hobbs	
	Lea County Communication Authority	393-3981
	State Police	392-5588
	City Police	397-9265
	Sheriff's Office	393-2515
	Ambulance	911
	Fire Department	397-9308
	LEPC (Local Emergency Planning Committee)	393-2870
	NMOCD	393-6161
	US Bureau of Land Management	393-3612
<u>Eddy County (575)</u>	Carlsbad	
	State Police	885-3137
	City Police	885-2111
	Sheriff's Office	887-7551
	Ambulance	911
	Fire Department	885-3125
	LEPC (Local Emergency Planning Committee)	887-3798
	US Bureau of Land Management	887-6544
	NM Emergency Response Commission (Santa Fe)	(505) 476-9600
	24 HR	(505) 827-9126
	National Emergency Response Center	(800) 424-8802
	National Pollution Control Center: Direct	(703) 872-6000
	For Oil Spills	(800) 280-7118
	Emergency Services	
	Wild Well Control	(281) 784-4700
	Cudd Pressure Control	(915) 699-0139 (915) 563-3356
	Halliburton	(575) 746-2757
	B. J. Services	(575) 746-3569
<u>Give GPS position:</u>	Native Air – Emergency Helicopter – Hobbs	(575) 392-6429
	Flight For Life - Lubbock, TX	(806) 743-9911
	Aerocare - Lubbock, TX	(806) 747-8923
	Med Flight Air Amb - Albuquerque, NM	(575) 842-4433
	Lifeguard Air Med Svc. Albuquerque, NM	(800) 222-1222
	Poison Control (24/7)	(575) 272-3115
	Oil & Gas Pipeline 24 Hour Service	(800) 364-4366
	NOAA – Website - www.nhc.noaa.gov	

Prepared in conjunction with
Dave Small



Devon Energy - Well Pad Rig Location Layout Safety Equipment Location



Location Dimensions
600 ft x 600 ft
Scale: 1 inch = 50 ft

● **Wellhead Location**

- | | |
|--|---|
| Wind Indicators | Self-Contained Breathing Apparatus (SCBA) |
| Location Entrance Warning Sign used to control location in event of an emergency | H2S Sensors Located Around the Rig |
| Safe Briefing Area | H2S Monitor Control/ Alarm box |

WCDSC Permian NM

Lea County (NAD83 New Mexico East)

Sec 08-T25S-R33E

Flagler 8 Fed 27H

Wellbore #1

Plan: Permit Plan 1

Standard Planning Report - Geographic

06 March, 2018

Planning Report - Geographic

Database:	EDM r5000.141_Prod US	Local Co-ordinate Reference:	Well Flagler 8 Fed 27H
Company:	WCDSC Permian NM	TVD Reference:	RKB @ 3463.20ft
Project:	Lea County (NAD83 New Mexico East)	MD Reference:	RKB @ 3463.20ft
Site:	Sec 08-T25S-R33E	North Reference:	Grid
Well:	Flagler 8 Fed 27H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Permit Plan 1		

Project	Lea County (NAD83 New Mexico East)		
Map System:	US State Plane 1983	System Datum:	Mean Sea Level
Geo Datum:	North American Datum 1983		
Map Zone:	New Mexico Eastern Zone		

Site	Sec 08-T25S-R33E				
Site Position:	Northing:	419,281.82 usft	Latitude:	32.150539	
From:	Map	Easting:	769,381.69 usft	Longitude:	-103.596481
Position Uncertainty:	0.00 ft	Slot Radius:	13-3/16 "	Grid Convergence:	0.39 °

Well	Flagler 8 Fed 27H					
Well Position	+N/-S	0.00 ft	Northing:	415,058.24 usft	Latitude:	32.138898
	+E/-W	0.00 ft	Easting:	771,052.39 usft	Longitude:	-103.591177
Position Uncertainty		0.50 ft	Wellhead Elevation:		Ground Level:	3,438.20 ft

Wellbore	Wellbore #1				
Magnetics	Model Name	Sample Date	Declination	Dip Angle	Field Strength
	IGRF2015	3/5/2018	(°)	(°)	(nT)
			6.88	59.97	47,811.91319467

Design	Permit Plan 1			
Audit Notes:				
Version:	Phase:	PROTOTYPE	Tie On Depth:	0.00
Vertical Section:	Depth From (TVD)	+N/-S	+E/-W	Direction
	(ft)	(ft)	(ft)	(°)
	0.00	0.00	0.00	0.60

Plan Survey Tool Program	Date	3/6/2018		
Depth From (ft)	Depth To (ft)	Survey (Wellbore)	Tool Name	Remarks
1	0.00	14,256.44 Permit Plan 1 (Wellbore #1)	MWD+IGRF	
			OWSG MWD + IGRF or WMM	

Plan Sections										
Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	TFO (°)	Target
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
2,400.00	0.00	0.00	2,400.00	0.00	0.00	0.00	0.00	0.00	0.00	
2,510.07	1.38	158.96	2,510.06	-1.23	0.47	1.25	1.25	0.00	158.96	
8,209.94	1.38	158.96	8,208.28	-128.97	49.60	0.00	0.00	0.00	0.00	
8,301.66	0.00	0.00	8,300.00	-130.00	50.00	1.50	-1.50	0.00	180.00	
9,228.70	0.00	0.00	9,227.04	-130.00	50.00	0.00	0.00	0.00	0.00	
10,128.70	90.00	359.98	9,800.00	442.96	49.77	10.00	10.00	0.00	359.98	PBHL - Flagler 8 Fed
14,256.44	90.00	359.98	9,800.00	4,570.69	48.13	0.00	0.00	0.00	0.00	PBHL - Flagler 8 Fed

Planning Report - Geographic

Database:	EDM r5000.141_Prod US	Local Co-ordinate Reference:	Well Flagler 8 Fed 27H
Company:	WCDSC Permian NM	TVD Reference:	RKB @ 3463.20ft
Project:	Lea County (NAD83 New Mexico East)	MD Reference:	RKB @ 3463.20ft
Site:	Sec 08-T25S-R33E	North Reference:	Grid
Well:	Flagler 8 Fed 27H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Permit Plan 1		

Planned Survey

Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Map Northing (usft)	Map Easting (usft)	Latitude	Longitude
0.00	0.00	0.00	0.00	0.00	0.00	415,058.24	771,052.39	32.138898	-103.591177
100.00	0.00	0.00	100.00	0.00	0.00	415,058.24	771,052.39	32.138898	-103.591177
200.00	0.00	0.00	200.00	0.00	0.00	415,058.24	771,052.39	32.138898	-103.591177
300.00	0.00	0.00	300.00	0.00	0.00	415,058.24	771,052.39	32.138898	-103.591177
400.00	0.00	0.00	400.00	0.00	0.00	415,058.24	771,052.39	32.138898	-103.591177
500.00	0.00	0.00	500.00	0.00	0.00	415,058.24	771,052.39	32.138898	-103.591177
600.00	0.00	0.00	600.00	0.00	0.00	415,058.24	771,052.39	32.138898	-103.591177
700.00	0.00	0.00	700.00	0.00	0.00	415,058.24	771,052.39	32.138898	-103.591177
800.00	0.00	0.00	800.00	0.00	0.00	415,058.24	771,052.39	32.138898	-103.591177
900.00	0.00	0.00	900.00	0.00	0.00	415,058.24	771,052.39	32.138898	-103.591177
1,000.00	0.00	0.00	1,000.00	0.00	0.00	415,058.24	771,052.39	32.138898	-103.591177
1,100.00	0.00	0.00	1,100.00	0.00	0.00	415,058.24	771,052.39	32.138898	-103.591177
1,200.00	0.00	0.00	1,200.00	0.00	0.00	415,058.24	771,052.39	32.138898	-103.591177
1,300.00	0.00	0.00	1,300.00	0.00	0.00	415,058.24	771,052.39	32.138898	-103.591177
1,400.00	0.00	0.00	1,400.00	0.00	0.00	415,058.24	771,052.39	32.138898	-103.591177
1,500.00	0.00	0.00	1,500.00	0.00	0.00	415,058.24	771,052.39	32.138898	-103.591177
1,600.00	0.00	0.00	1,600.00	0.00	0.00	415,058.24	771,052.39	32.138898	-103.591177
1,700.00	0.00	0.00	1,700.00	0.00	0.00	415,058.24	771,052.39	32.138898	-103.591177
1,800.00	0.00	0.00	1,800.00	0.00	0.00	415,058.24	771,052.39	32.138898	-103.591177
1,900.00	0.00	0.00	1,900.00	0.00	0.00	415,058.24	771,052.39	32.138898	-103.591177
2,000.00	0.00	0.00	2,000.00	0.00	0.00	415,058.24	771,052.39	32.138898	-103.591177
2,100.00	0.00	0.00	2,100.00	0.00	0.00	415,058.24	771,052.39	32.138898	-103.591177
2,200.00	0.00	0.00	2,200.00	0.00	0.00	415,058.24	771,052.39	32.138898	-103.591177
2,300.00	0.00	0.00	2,300.00	0.00	0.00	415,058.24	771,052.39	32.138898	-103.591177
2,400.00	0.00	0.00	2,400.00	0.00	0.00	415,058.24	771,052.39	32.138898	-103.591177
Begin Nudge									
2,500.00	1.25	158.96	2,499.99	-1.02	0.39	415,057.22	771,052.78	32.138895	-103.591176
2,510.07	1.38	158.96	2,510.06	-1.23	0.47	415,057.01	771,052.86	32.138895	-103.591176
EOB									
2,600.00	1.38	158.96	2,599.96	-3.25	1.25	415,054.99	771,053.64	32.138889	-103.591173
2,700.00	1.38	158.96	2,699.93	-5.49	2.11	415,052.75	771,054.50	32.138883	-103.591171
2,800.00	1.38	158.96	2,799.91	-7.73	2.97	415,050.51	771,055.36	32.138877	-103.591168
2,900.00	1.38	158.96	2,899.88	-9.97	3.84	415,048.27	771,056.22	32.138871	-103.591165
3,000.00	1.38	158.96	2,999.85	-12.21	4.70	415,046.03	771,057.08	32.138864	-103.591162
3,100.00	1.38	158.96	3,099.82	-14.45	5.56	415,043.79	771,057.95	32.138858	-103.591160
3,200.00	1.38	158.96	3,199.79	-16.70	6.42	415,041.54	771,058.81	32.138852	-103.591157
3,300.00	1.38	158.96	3,299.76	-18.94	7.28	415,039.30	771,059.67	32.138846	-103.591154
3,400.00	1.38	158.96	3,399.73	-21.18	8.15	415,037.06	771,060.53	32.138840	-103.591152
3,500.00	1.38	158.96	3,499.70	-23.42	9.01	415,034.82	771,061.39	32.138834	-103.591149
3,600.00	1.38	158.96	3,599.68	-25.66	9.87	415,032.58	771,062.26	32.138827	-103.591146
3,700.00	1.38	158.96	3,699.65	-27.90	10.73	415,030.34	771,063.12	32.138821	-103.591143
3,800.00	1.38	158.96	3,799.62	-30.14	11.59	415,028.10	771,063.98	32.138815	-103.591141
3,900.00	1.38	158.96	3,899.59	-32.38	12.45	415,025.86	771,064.84	32.138809	-103.591138
4,000.00	1.38	158.96	3,999.56	-34.62	13.32	415,023.62	771,065.70	32.138803	-103.591135
4,100.00	1.38	158.96	4,099.53	-36.87	14.18	415,021.37	771,066.57	32.138797	-103.591132
4,200.00	1.38	158.96	4,199.50	-39.11	15.04	415,019.13	771,067.43	32.138790	-103.591130
4,300.00	1.38	158.96	4,299.47	-41.35	15.90	415,016.89	771,068.29	32.138784	-103.591127
4,400.00	1.38	158.96	4,399.44	-43.59	16.76	415,014.65	771,069.15	32.138778	-103.591124
4,500.00	1.38	158.96	4,499.42	-45.83	17.63	415,012.41	771,070.01	32.138772	-103.591121
4,600.00	1.38	158.96	4,599.39	-48.07	18.49	415,010.17	771,070.88	32.138766	-103.591119
4,700.00	1.38	158.96	4,699.36	-50.31	19.35	415,007.93	771,071.74	32.138759	-103.591116
4,800.00	1.38	158.96	4,799.33	-52.55	20.21	415,005.69	771,072.60	32.138753	-103.591113
4,900.00	1.38	158.96	4,899.30	-54.79	21.07	415,003.45	771,073.46	32.138747	-103.591111
5,000.00	1.38	158.96	4,999.27	-57.03	21.94	415,001.20	771,074.32	32.138741	-103.591108

Planning Report - Geographic

Database: EDM r5000.141_Prod US
 Company: WCDSC Permian NM
 Project: Lea County (NAD83 New Mexico East)
 Site: Sec 08-T25S-R33E
 Well: Flagler 8 Fed 27H
 Wellbore: Wellbore #1
 Design: Permit Plan 1

Local Co-ordinate Reference: Well Flagler 8 Fed 27H
 TVD Reference: RKB @ 3463.20ft
 MD Reference: RKB @ 3463.20ft
 North Reference: Grid
 Survey Calculation Method: Minimum Curvature

Planned Survey

Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Map Northing (usft)	Map Easting (usft)	Latitude	Longitude
5,100.00	1.38	158.96	5,099.24	-59.28	22.80	414,998.96	771,075.19	32.138735	-103.591105
5,200.00	1.38	158.96	5,199.21	-61.52	23.66	414,996.72	771,076.05	32.138729	-103.591102
5,300.00	1.38	158.96	5,299.19	-63.76	24.52	414,994.48	771,076.91	32.138722	-103.591100
5,400.00	1.38	158.96	5,399.16	-66.00	25.38	414,992.24	771,077.77	32.138716	-103.591097
5,500.00	1.38	158.96	5,499.13	-68.24	26.25	414,990.00	771,078.63	32.138710	-103.591094
5,600.00	1.38	158.96	5,599.10	-70.48	27.11	414,987.76	771,079.50	32.138704	-103.591091
5,700.00	1.38	158.96	5,699.07	-72.72	27.97	414,985.52	771,080.36	32.138698	-103.591089
5,800.00	1.38	158.96	5,799.04	-74.96	28.83	414,983.28	771,081.22	32.138692	-103.591086
5,900.00	1.38	158.96	5,899.01	-77.20	29.69	414,981.03	771,082.08	32.138685	-103.591083
6,000.00	1.38	158.96	5,998.98	-79.45	30.56	414,978.79	771,082.94	32.138679	-103.591080
6,100.00	1.38	158.96	6,098.95	-81.69	31.42	414,976.55	771,083.81	32.138673	-103.591078
6,200.00	1.38	158.96	6,198.93	-83.93	32.28	414,974.31	771,084.67	32.138667	-103.591075
6,300.00	1.38	158.96	6,298.90	-86.17	33.14	414,972.07	771,085.53	32.138661	-103.591072
6,400.00	1.38	158.96	6,398.87	-88.41	34.00	414,969.83	771,086.39	32.138654	-103.591069
6,500.00	1.38	158.96	6,498.84	-90.65	34.87	414,967.59	771,087.25	32.138648	-103.591067
6,600.00	1.38	158.96	6,598.81	-92.89	35.73	414,965.35	771,088.11	32.138642	-103.591064
6,700.00	1.38	158.96	6,698.78	-95.13	36.59	414,963.11	771,088.98	32.138636	-103.591061
6,800.00	1.38	158.96	6,798.75	-97.37	37.45	414,960.87	771,089.84	32.138630	-103.591059
6,900.00	1.38	158.96	6,898.72	-99.62	38.31	414,958.62	771,090.70	32.138624	-103.591056
7,000.00	1.38	158.96	6,998.70	-101.86	39.18	414,956.38	771,091.56	32.138617	-103.591053
7,100.00	1.38	158.96	7,098.67	-104.10	40.04	414,954.14	771,092.42	32.138611	-103.591050
7,200.00	1.38	158.96	7,198.64	-106.34	40.90	414,951.90	771,093.29	32.138605	-103.591048
7,300.00	1.38	158.96	7,298.61	-108.58	41.76	414,949.66	771,094.15	32.138599	-103.591045
7,400.00	1.38	158.96	7,398.58	-110.82	42.62	414,947.42	771,095.01	32.138593	-103.591042
7,500.00	1.38	158.96	7,498.55	-113.06	43.49	414,945.18	771,095.87	32.138587	-103.591039
7,600.00	1.38	158.96	7,598.52	-115.30	44.35	414,942.94	771,096.73	32.138580	-103.591037
7,700.00	1.38	158.96	7,698.49	-117.54	45.21	414,940.70	771,097.60	32.138574	-103.591034
7,800.00	1.38	158.96	7,798.46	-119.79	46.07	414,938.45	771,098.46	32.138568	-103.591031
7,900.00	1.38	158.96	7,898.44	-122.03	46.93	414,936.21	771,099.32	32.138562	-103.591028
8,000.00	1.38	158.96	7,998.41	-124.27	47.80	414,933.97	771,100.18	32.138556	-103.591026
8,100.00	1.38	158.96	8,098.38	-126.51	48.66	414,931.73	771,101.04	32.138549	-103.591023
8,200.00	1.38	158.96	8,198.35	-128.75	49.52	414,929.49	771,101.91	32.138543	-103.591020
8,209.94	1.38	158.96	8,208.29	-128.97	49.60	414,929.27	771,101.99	32.138543	-103.591020
EOH									
8,300.00	0.02	158.96	8,298.34	-130.00	50.00	414,928.24	771,102.39	32.138540	-103.591019
8,301.66	0.00	0.00	8,300.00	-130.00	50.00	414,928.24	771,102.39	32.138540	-103.591019
Drop to Vertical									
8,400.00	0.00	0.00	8,398.34	-130.00	50.00	414,928.24	771,102.39	32.138540	-103.591019
8,500.00	0.00	0.00	8,498.34	-130.00	50.00	414,928.24	771,102.39	32.138540	-103.591019
8,600.00	0.00	0.00	8,598.34	-130.00	50.00	414,928.24	771,102.39	32.138540	-103.591019
8,700.00	0.00	0.00	8,698.34	-130.00	50.00	414,928.24	771,102.39	32.138540	-103.591019
8,800.00	0.00	0.00	8,798.34	-130.00	50.00	414,928.24	771,102.39	32.138540	-103.591019
8,900.00	0.00	0.00	8,898.34	-130.00	50.00	414,928.24	771,102.39	32.138540	-103.591019
9,000.00	0.00	0.00	8,998.34	-130.00	50.00	414,928.24	771,102.39	32.138540	-103.591019
9,100.00	0.00	0.00	9,098.34	-130.00	50.00	414,928.24	771,102.39	32.138540	-103.591019
9,200.00	0.00	0.00	9,198.34	-130.00	50.00	414,928.24	771,102.39	32.138540	-103.591019
9,228.70	0.00	0.00	9,227.04	-130.00	50.00	414,928.24	771,102.39	32.138540	-103.591019
KOP @ 9229' MD, 250' FSL, 1630' FEL									
9,300.00	7.13	359.98	9,298.15	-125.57	50.00	414,932.67	771,102.39	32.138552	-103.591019
9,400.00	17.13	359.98	9,395.80	-104.58	49.99	414,953.66	771,102.38	32.138610	-103.591018
9,500.00	27.13	359.98	9,488.31	-66.96	49.97	414,991.28	771,102.36	32.138713	-103.591017
9,535.12	30.64	359.98	9,519.06	-50.00	49.97	415,008.24	771,102.36	32.138760	-103.591017
1st Take Point @ 9535' MD, 330' FSL, 1630' FEL									
9,600.00	37.13	359.98	9,572.89	-13.84	49.95	415,044.39	771,102.34	32.138859	-103.591016

Planning Report - Geographic

Database:	EDM r5000.141_Prod US	Local Co-ordinate Reference:	Well Flagler 8 Fed 27H
Company:	WCDCS Permian NM	TVD Reference:	RKB @ 3463.20ft
Project:	Lea County (NAD83 New Mexico East)	MD Reference:	RKB @ 3463.20ft
Site:	Sec 08-T25S-R33E	North Reference:	Grid
Well:	Flagler 8 Fed 27H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Permit Plan 1		

Planned Survey										
Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Map Northing (usft)	Map Easting (usft)	Latitude	Longitude	
9,700.00	47.13	359.98	9,646.96	53.15	49.93	415,111.39	771,102.31	32.139043	-103.591015	
9,800.00	57.13	359.98	9,708.27	131.99	49.90	415,190.23	771,102.28	32.139260	-103.591013	
9,900.00	67.13	359.98	9,754.96	220.28	49.86	415,278.52	771,102.25	32.139503	-103.591011	
10,000.00	77.13	359.98	9,785.60	315.33	49.82	415,373.57	771,102.21	32.139764	-103.591009	
10,100.00	87.13	359.98	9,799.28	414.27	49.78	415,472.50	771,102.17	32.140036	-103.591007	
10,128.70	90.00	359.98	9,800.00	442.95	49.77	415,501.19	771,102.16	32.140115	-103.591007	
Land Point										
10,200.00	90.00	359.98	9,800.00	514.25	49.74	415,572.49	771,102.13	32.140311	-103.591005	
10,300.00	90.00	359.98	9,800.00	614.25	49.70	415,672.49	771,102.09	32.140586	-103.591003	
10,400.00	90.00	359.98	9,800.00	714.25	49.66	415,772.49	771,102.05	32.140860	-103.591001	
10,500.00	90.00	359.98	9,800.00	814.25	49.62	415,872.49	771,102.01	32.141135	-103.590999	
10,600.00	90.00	359.98	9,800.00	914.25	49.58	415,972.49	771,101.97	32.141410	-103.590997	
10,700.00	90.00	359.98	9,800.00	1,014.25	49.54	416,072.49	771,101.93	32.141685	-103.590995	
10,800.00	90.00	359.98	9,800.00	1,114.25	49.51	416,172.49	771,101.89	32.141960	-103.590993	
10,900.00	90.00	359.98	9,800.00	1,214.25	49.47	416,272.49	771,101.85	32.142235	-103.590991	
11,000.00	90.00	359.98	9,800.00	1,314.25	49.43	416,372.49	771,101.81	32.142510	-103.590988	
11,100.00	90.00	359.98	9,800.00	1,414.25	49.39	416,472.49	771,101.77	32.142785	-103.590986	
11,200.00	90.00	359.98	9,800.00	1,514.25	49.35	416,572.49	771,101.73	32.143059	-103.590984	
11,300.00	90.00	359.98	9,800.00	1,614.25	49.31	416,672.49	771,101.69	32.143334	-103.590982	
11,400.00	90.00	359.98	9,800.00	1,714.25	49.27	416,772.49	771,101.65	32.143609	-103.590980	
11,500.00	90.00	359.98	9,800.00	1,814.25	49.23	416,872.49	771,101.61	32.143884	-103.590978	
11,600.00	90.00	359.98	9,800.00	1,914.25	49.19	416,972.49	771,101.57	32.144159	-103.590976	
11,700.00	90.00	359.98	9,800.00	2,014.25	49.15	417,072.49	771,101.53	32.144434	-103.590974	
11,800.00	90.00	359.98	9,800.00	2,114.25	49.11	417,172.49	771,101.49	32.144709	-103.590972	
11,900.00	90.00	359.98	9,800.00	2,214.25	49.07	417,272.49	771,101.45	32.144984	-103.590970	
12,000.00	90.00	359.98	9,800.00	2,314.25	49.03	417,372.49	771,101.41	32.145258	-103.590967	
12,100.00	90.00	359.98	9,800.00	2,414.25	48.99	417,472.49	771,101.38	32.145533	-103.590965	
12,200.00	90.00	359.98	9,800.00	2,514.25	48.95	417,572.49	771,101.34	32.145808	-103.590963	
12,300.00	90.00	359.98	9,800.00	2,614.25	48.91	417,672.49	771,101.30	32.146083	-103.590961	
12,400.00	90.00	359.98	9,800.00	2,714.25	48.87	417,772.49	771,101.26	32.146358	-103.590959	
12,500.00	90.00	359.98	9,800.00	2,814.25	48.83	417,872.49	771,101.22	32.146633	-103.590957	
12,600.00	90.00	359.98	9,800.00	2,914.25	48.79	417,972.49	771,101.18	32.146908	-103.590955	
12,700.00	90.00	359.98	9,800.00	3,014.25	48.75	418,072.49	771,101.14	32.147183	-103.590953	
12,800.00	90.00	359.98	9,800.00	3,114.25	48.71	418,172.49	771,101.10	32.147457	-103.590951	
12,900.00	90.00	359.98	9,800.00	3,214.25	48.67	418,272.49	771,101.06	32.147732	-103.590949	
13,000.00	90.00	359.98	9,800.00	3,314.25	48.63	418,372.49	771,101.02	32.148007	-103.590946	
13,100.00	90.00	359.98	9,800.00	3,414.25	48.59	418,472.49	771,100.98	32.148282	-103.590944	
13,200.00	90.00	359.98	9,800.00	3,514.25	48.55	418,572.49	771,100.94	32.148557	-103.590942	
13,300.00	90.00	359.98	9,800.00	3,614.25	48.51	418,672.49	771,100.90	32.148832	-103.590940	
13,400.00	90.00	359.98	9,800.00	3,714.25	48.47	418,772.49	771,100.86	32.149107	-103.590938	
13,500.00	90.00	359.98	9,800.00	3,814.25	48.43	418,872.49	771,100.82	32.149381	-103.590936	
13,600.00	90.00	359.98	9,800.00	3,914.25	48.39	418,972.49	771,100.78	32.149656	-103.590934	
13,700.00	90.00	359.98	9,800.00	4,014.25	48.35	419,072.49	771,100.74	32.149931	-103.590932	
13,800.00	90.00	359.98	9,800.00	4,114.25	48.31	419,172.49	771,100.70	32.150206	-103.590930	
13,900.00	90.00	359.98	9,800.00	4,214.25	48.27	419,272.48	771,100.66	32.150481	-103.590928	
14,000.00	90.00	359.98	9,800.00	4,314.25	48.23	419,372.48	771,100.62	32.150756	-103.590925	
14,100.00	90.00	359.98	9,800.00	4,414.25	48.19	419,472.48	771,100.58	32.151031	-103.590923	
14,200.00	90.00	359.98	9,800.00	4,514.25	48.15	419,572.48	771,100.54	32.151306	-103.590921	
14,256.44	90.00	359.98	9,800.00	4,570.69	48.13	419,628.92	771,100.52	32.151461	-103.590920	

PBHL; 330' FNL, 1605' FEL

Planning Report - Geographic

Database:	EDM r5000.141_Prod US	Local Co-ordinate Reference:	Well Flagler 8 Fed 27H
Company:	WCDSC Permian NM	TVD Reference:	RKB @ 3463.20ft
Project:	Lea County (NAD83 New Mexico East)	MD Reference:	RKB @ 3463.20ft
Site:	Sec 08-T25S-R33E	North Reference:	Grid
Well:	Flagler 8 Fed 27H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Permit Plan 1		

Design Targets

Target Name	Dip Angle - hit/miss target - Shape	Dip Dir. (°)	TVD (ft)	+N/-S (ft)	+E/-W (ft)	Northing (usft)	Easting (usft)	Latitude	Longitude
PBHL - Flagler 8 Fed 27		0.00	0.00	4,570.69	48.13	419,628.92	771,100.52	32.151461	-103.590920
	- plan misses target center by 4570.94ft at 0.00ft MD (0.00 TVD, 0.00 N, 0.00 E)								
	- Point								
Vertical Point - Flagler 8		0.00	8,300.00	-179.35	75.93	414,878.89	771,128.31	32.138404	-103.590936
	- plan misses target center by 55.75ft at 8301.66ft MD (8300.00 TVD, -130.00 N, 50.00 E)								
	- Point								

Plan Annotations

Measured Depth (ft)	Vertical Depth (ft)	Local Coordinates		Comment
		+N/-S (ft)	+E/-W (ft)	
2,400.00	2,400.00	0.00	0.00	Begin Nudge
2,510.07	2,510.06	-1.23	0.47	EOB
8,209.94	8,208.29	-128.97	49.60	EOH
8,301.66	8,300.00	-130.00	50.00	Drop to Vertical
9,228.70	9,227.04	-130.00	50.00	KOP @ 9229' MD, 250' FSL, 1630' FEL
9,535.12	9,519.06	-50.00	49.97	1st Take Point @ 9535' MD, 330' FSL, 1630' FEL
10,128.70	9,800.00	442.95	49.77	Land Point
14,256.44	9,800.00	4,570.69	48.13	PBHL; 330' FNL, 1605' FEL

WCDSC Permian NM


WELL DETAILS: Flagler 8 Fed 27H

RKB @ 3463.20R
3438.20

Northing 415058.24 Easting 771052.39 Latitude 32.136698 Longitude -103.591177

SECTION DETAILS Permit Plan 1

MD	Inc	Azi	TVD	+N/-S	+E/-W	D/leg	VSect	Annotation
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
2400.00	0.00	0.00	2400.00	0.00	0.00	0.00	0.00	Begin Nudge
2510.07	1.38	158.96	2510.06	-1.23	0.47	1.25	-1.23	EOB
8209.94	1.38	158.96	8208.28	-128.97	49.60	0.00	-128.44	EOH
5 8301.66	0.00	0.00	8300.00	-130.00	50.00	1.50	-129.47	Drop to Vertical
6 9228.70	0.00	0.00	9227.04	-130.00	50.00	0.00	-129.47	KOP @ 9229' MD, 250' FSL, 1630' FEL
7 10128.70	90.00	359.98	9800.00	442.96	49.77	10.00	443.46	Land Point
8 14256.44	90.00	359.98	9800.00	4570.69	48.13	0.00	4570.94	PBHL; 330' FNL, 1605' FEL



Flagler 8 Fed 27H

Devon Energy, Flagler 8 Fed 27H


1. Geologic Formations

TVD of target	9,800'	Pilot hole depth	N/A
MD at TD:	14,256'	Deepest expected fresh water:	

Basin

Formation	Depth (TVD) from KB	Water/Mineral Bearing/ Target Zone?	Hazards*
RUSTLER	1145		
TOP SALT	1508		
BASE OF SALT	5000		
BELL CANYON	5000		
CHERRY CANYON	6040		
BRUSHY CANYON	7690		
BONE SPRING	9110		
BONE SPRING 1ST	10016		
BONE SPRING 2ND	10610		

*H2S, water flows, loss of circulation, abnormal pressures, etc.



Devon Energy, Flagler 8 Fed 27H

2. Casing Program

Hole Size	Casing Interval		Csg. Size	Weight (lbs)	Grade	Conn.	SF Collapse	SF Burst	SF Tension
	From	To							
17.5"	0	1,150'	13.375"	48	H40	STC	1.125	1	1.6
12.25"	0	5,000'	9.625"	40	J55	LTC	1.125	1	1.6
8.75"	0	14,256'	5.5"	17	P110	BTC	1.125	1	1.6
BLM Minimum Safety Factor							1.125	1	1.6 Dry 1.8 Wet

All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.h

Must have table for contingency casing

	Y or N
Is casing new? If used, attach certification as required in Onshore Order #1	Y
Does casing meet API specifications? If no, attach casing specification sheet.	Y
Is premium or uncommon casing planned? If yes attach casing specification sheet.	N
Does the above casing design meet or exceed BLM's minimum standards? If not provide justification (loading assumptions, casing design criteria).	Y
Will the intermediate pipe be kept at a minimum 1/3 fluid filled to avoid approaching the collapse pressure rating of the casing?	Y
Is well located within Capitan Reef?	N
If yes, does production casing cement tie back a minimum of 50' above the Reef?	
Is well within the designated 4 string boundary.	
Is well located in SOPA but not in R-111-P?	N
If yes, are the first 2 strings cemented to surface and 3 rd string cement tied back 500' into previous casing?	
Is well located in R-111-P and SOPA?	N
If yes, are the first three strings cemented to surface?	
Is 2 nd string set 100' to 600' below the base of salt?	
Is well located in high Cave/Karst?	N
If yes, are there two strings cemented to surface?	
(For 2 string wells) If yes, is there a contingency casing if lost circulation occurs?	
Is well located in critical Cave/Karst?	N
If yes, are there three strings cemented to surface?	

Devon Energy, Flagler 8 Fed 27H

3. Cementing Program

Casing	# Sks	Wt. lb/gal	Yld ft ³ /sack	H ₂ O gal/sk	500# Comp. Strength (hours)	Slurry Description
Surf.	901	14.8	1.33	6.32	6	Lead: Class C Cement + 0.125 lbs/sack Poly-F-Flake
Inter.	511	10.3	3.65	22.06	24	Lead: (50:50) Poz (Silica) 3 lbm/sk Kol-Seal, .125 lbm/sk Poly-E-Flake
	306	14.8	1.33	6.32	6	Tail: Class C Cement + 0.125 lbs/sack Poly-F-Flake
Prod.	457	9	3.27	13.5	21	Lead: Tuned Light Cement
	1207	14.5	1.2	5.31	25	Tail: (50:50) Clas H Cement: Poz (Fly Ash) + 0.5% bwoc HALAD-344 + 0.4% bwoc CFR-3 + 0.2% BWOC HR-601 + 2% bwoc Bentonite

Casing String	TOC	% Excess
13-3/8" Surface	0'	50%
9-5/8" Intermediate	0'	30%
5-1/2" Production	4800'	25%

4. Pressure Control Equipment

N	A variance is requested for the use of a diverter on the surface casing. See attached for schematic.
---	--

BOP installed and tested before drilling which hole?	Size?	Min. Required WP	Type	✓	Tested to:
12-1/4"	13-5/8"	3M	Annular	x	50% of working pressure 3M
			Blind Ram		
			Pipe Ram		
			Double Ram	x	
			Other*		
8-3/4"	13-5/8"	3M	Annular	x	50% of working pressure 3M
			Blind Ram		
			Pipe Ram		
			Double Ram	x	
			Other*		
			Annular		
			Blind Ram		

Devon Energy, Flagler 8 Fed 27H

			Pipe Ram		
			Double Ram		
			Other *		

*Specify if additional ram is utilized.

BOP/BOPE will be tested by an independent service company to 250 psi low and the high pressure indicated above per Onshore Order 2 requirements. The System may be upgraded to a higher pressure but still tested to the working pressure listed in the table above. If the system is upgraded all the components installed will be functional and tested.

Pipe rams will be operationally checked each 24 hour period. Blind rams will be operationally checked on each trip out of the hole. These checks will be noted on the daily tour sheets. Other accessories to the BOP equipment will include a Kelly cock and floor safety valve (inside BOP) and choke lines and choke manifold. See attached schematics.

Y	Formation integrity test will be performed per Onshore Order #2. On Exploratory wells or on that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.i.
Y	A variance is requested for the use of a flexible choke line from the BOP to Choke Manifold. See attached for specs and hydrostatic test chart.
Y	Are anchors required by manufacturer?
Y	<p>A multibowl wellhead is being used. The BOP will be tested per Onshore Order #2 after installation on the surface casing which will cover testing requirements for a maximum of 30 days. If any seal subject to test pressure is broken the system must be tested.</p> <p>Devon proposes using a multi-bowl wellhead assembly. This assembly will only be tested when installed on the surface casing. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be 3000 (3M) psi.</p> <ul style="list-style-type: none"> o Wellhead will be installed by wellhead representatives. o If the welding is performed by a third party, the wellhead representative will monitor the temperature to verify that it does not exceed the maximum temperature of the seal. o Wellhead representative will install the test plug for the initial BOP test. o Wellhead company will install a solid steel body pack-off to completely isolate the lower head after cementing intermediate casing. After installation of the packoff, the pack-off and the lower flange will be tested to 3M, as shown on the attached schematic. Everything above the pack-off will not have been altered whatsoever from the initial nipple up. Therefore the BOP components will not be retested at that time.

Devon Energy, Flagler 8 Fed 27H

- If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head will be cut and top out operations will be conducted.
- Devon will pressure test all seals above and below the mandrel (but still above the casing) to full working pressure rating.
- Devon will test the casing to 0.22 psi/ft or 1500 psi, whichever is greater, as per Onshore Order #2.

After running the 13-3/8" surface casing, a 13-5/8" BOP/BOPE system with a minimum rating of 3M will be installed on the wellhead system and will undergo a 250 psi low pressure test followed by a 3,000 psi high pressure test. The 3,000 psi high and 250 psi. Low test will cover testing requirements a maximum of 30 days, as per Onshore Order #2. If the well is not complete within 30 days of this BOP test, another full BOP test will be conducted, as per Onshore Order #2.

After running the 9-5/8' intermediate casing with a mandrel hanger, the 13-5/8" BOP/BOPE system with a minimum rating of 3M will already be installed on the wellhead.

The pipe rams will be operated and checked each 24 hour period and each time the drill pipe is out of the hole. These tests will be logged in the daily driller's log. A 2" kill line and 3" choke line will be incorporated into the drilling spool below the ram BOP. In addition to the rams and annular preventer, additional BOP accessories include a Kelly cock, floor safety valve, choke lines, and choke manifold rated at 3,000 psi WP.

Devon's proposed wellhead manufacturers will be EMC Technologies, Cactus Wellhead, or Cameron.

The pipe rams will be operated and checked each 24 hour period and each time the drill pipe is out of the hole. These tests will be logged in the daily driller's log. A 2" kill line and 3" choke line will be incorporated into the drilling spool below the ram BOP. In addition to the rams and annular preventer, additional BOP accessories include a kelly cock, floor safety valve, choke lines, and choke manifold rated at 3,000 psi WP.

5. Mud Program

Depth		Type	Weight (ppg)	Viscosity	Water Loss
From	To				
0	1150	FW Gel	8.5-9.0	28-34	N/C
1150	5,000	Saturated Brine	10.0-11.0	28-34	N/C
5,000	14,256	Cut Brine	8.5-9.3	28-34	N/C

Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept on location at all times.

What will be used to monitor the loss or gain of fluid?	PVT/Pason/Visual Monitoring
---	-----------------------------

6. Logging and Testing Procedures

Logging, Coring and Testing.	
X	Will run GR/CNL from TD to surface (horizontal well – vertical portion of hole). Stated logs run will be in the Completion Report and submitted to the BLM.
	No Logs are planned based on well control or offset log information.
	Drill stem test? If yes, explain
	Coring? If yes, explain

Additional logs planned	Interval
Resistivity	Int. shoe to KOP
Density	Int. shoe to KOP
X CBL	Production casing
X Mud log	KOP to TD
PEX	

7. Drilling Conditions

Condition	Specify what type and where?
BH Pressure at deepest TVD	4720 psi
Abnormal Temperature	No

Mitigation measure for abnormal conditions. Describe. Lost circulation material/sweeps/mud scavengers.

Hydrogen Sulfide (H ₂ S) monitors will be installed prior to drilling out the surface shoe. If H ₂ S is detected in concentrations greater than 100 ppm, the operator will comply with the provisions of Onshore Oil and Gas Order #6. If Hydrogen Sulfide is encountered, measured values and formations will be provided to the BLM.	
N	H ₂ S is present
Y	H ₂ S Plan attached

8. Other facets of operation

Is this a walking operation? Yes

1. In the event the spudder rig is unable to drill the surface holes the drilling rig will batch drill the surface holes and run/cement surface casing; walking the rig to next wells on the pad.
2. The drilling rig will then batch drill the intermediate sections with either OBM or cut brine and run/cement intermediate casing; the wellbore will be isolated with a blind flange and pressure gauge installed for monitoring the well before walking to the next well.
3. The drilling rig will then batch drill the production hole sections on the wells with OBM, run/cement production casing, and install TA caps or tubing heads for completions.

Devon Energy, Flagler 8 Fed 27H

NOTE: During batch operations the drilling rig will be moved from well to well however, it will not be removed from the pad until all wells have production casing run/cemented.

Will be pre-setting casing? Yes

1. Spudder rig will move in and drill surface hole.
 - a. Rig will utilize fresh water based mud to drill 17½" surface hole to TD. Solids control will be handled entirely on a closed loop basis.
2. After drilling the surface hole section, the spudder rig will run casing and cement following all of the applicable rules and regulations (OnShore Order 2, all COAs and NMOCD regulations).
3. The wellhead will be installed and tested once the 13-3/8" surface casing is cut off and the WOC time has been reached.
4. A blind flange with the same pressure rating as the wellhead will be installed to seal the wellbore. Pressure will be monitored with a pressure gauge installed on the wellhead.
5. Spudder rig operations is expected to take 4-5 days per well on a multi well pad.
6. The NMOCD will be contacted and notified 24 hours prior to commencing spudder rig operations.
7. Drilling operations will be performed with the drilling rig. At that time an approved BOP stack will be nipped up and tested on the wellhead before drilling operations commences on each well.
 - a. The NMOCD will be contacted / notified 24 hours before the drilling rig moves back on to the pad with the pre-set surface casing.

Attachments

- Directional Plan
 Other, describe

A multibowl wellhead may be used. The BOP will be tested per Onshore Order #2 after installation on the surface casing which will cover testing requirements for a maximum of 30 days. If any seal subject to test pressure is broken the system must be tested.

Devon proposes using a multi-bowl wellhead assembly. This assembly will only be tested when installed on the surface casing. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be 3000 (3M) psi.

- Wellhead will be installed by wellhead representatives.
- If the welding is performed by a third party, the wellhead representative will monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
- Wellhead representative will install the test plug for the initial BOP test.
- Wellhead company will install a solid steel body pack-off to completely isolate the lower head after cementing intermediate casing. After installation of the pack-off, the pack-off and the lower flange will be tested to 3M, as shown on the attached schematic. Everything above the pack-off will not have been altered whatsoever from the initial nipple up. Therefore the BOP components will not be retested at that time.
- If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head will be cut and top out operations will be conducted.
- Devon will pressure test all seals above and below the mandrel (but still above the casing) to full working pressure rating.
- Devon will test the casing to 0.22 psi/ft or 1500 psi, whichever is greater, as per Onshore Order #2.

After running the 13-3/8" surface casing, a 13-5/8" BOP/BOPE system with a minimum rating of 3M will be installed on the wellhead system and will undergo a 250 psi low pressure test followed by a 3,000 psi high pressure test. The 3,000 psi high and 250 psi low test will cover testing requirements a maximum of 30 days, as per Onshore Order #2. If the well is not complete within 30 days of this BOP test, another full BOP test will be conducted, as per Onshore Order #2.

After running the 9-5/8" intermediate casing with a mandrel hanger, the 13-5/8" BOP/BOPE system with a minimum rating of 3M will already be installed on the wellhead.

The pipe rams will be operated and checked each 24 hour period and each time the drill pipe is out of the hole. These tests will be logged in the daily driller's log. A 2" kill line and 3" choke line will be incorporated into the drilling spool below the ram BOP. In addition to the rams and annular preventer, additional BOP accessories include a kelly cock, floor safety valve, choke lines, and choke manifold rated at 3,000 psi WP.

Devon's proposed wellhead manufactures will be FMC Technologies, Cactus Wellhead, or Cameron.

Devon Energy
APD VARIANCE DATA

OPERATOR NAME: Devon Energy

1. SUMMARY OF Variance:

Devon Energy respectfully requests approval for the following additions to the drilling plan:


1. Potential utilization of a spudder rig to pre-set surface casing.

2. Description of Operations

1. A spudder rig contractor may move in their rig to drill the surface hole section and pre-set surface casing on this well.
 - a. After drilling the surface hole section, the rig will run casing and cement following all of the applicable rules and regulations (OnShore Order 2, all COAs and NMOCD regulations).
 - b. Rig will utilize fresh water based mud to drill surface hole to TD.
2. The wellhead will be installed and tested once the surface casing is cut off and the WOC time has been reached.
3. A blind flange with the same pressure rating as the wellhead will be installed to seal the wellbore. Pressure will be monitored with needle valves installed on two wingvalves.
 - a. A means for intervention will be maintained while the drilling rig is not over the well.
4. The BLM will be contacted and notified 24 hours prior to commencing spudder rig operations.
5. Drilling operation will be performed with the big rig. At that time an approved BOP stack will be nipped up and tested on the wellhead before drilling operations commences on each well.
 - a. The BLM will be contacted / notified 24 hours before the big rig moves back on to the pad with the pre-set surface casing.
6. Devon Energy will have supervision on the rig to ensure compliance with all BLM and NMOCD regulations and to oversee operations.
7. Once the rig is removed, Devon Energy will secure the wellhead area by placing a guard rail around the cellar area.



Commitment Runs Deep



Design Plan
Operation and Maintenance Plan
Closure Plan

SENM - Closed Loop Systems
June 2010

I. Design Plan

Devon uses MI SWACO closed loop system (CLS). The MI SWACO CLS is designed to maintain drill solids at or below 5%. The equipment is arranged to progressively remove solids from the largest to the smallest size. Drilling fluids can thus be reused and savings is realized on mud and disposal costs. Dewatering may be required with the centrifuges to insure removal of ultra fine solids.

The drilling location is constructed to allow storm water to flow to a central sump normally the cellar. This insures no contamination leaves the drilling pad in the event of a spill. Storm water is reused in the mud system or stored in a reserve fluid tank farm until it can be reused. All lubricants, oils, or chemicals are removed immediately from the ground to prevent the contamination of storm water. An oil trap is normally installed on the sump if an oil spill occurs during a storm.

A tank farm is utilized to store drilling fluids including fresh water and brine fluids. The tank farm is constructed on a 20 ml plastic lined, bermed pad to prevent the contamination of the drilling site during a spill. Fluids from other sites may be stored in these tanks for processing by the solids control equipment and reused in the mud system. At the end of the well the fluids are transported from the tank farm to an adjoining well or to the next well for the rig.

Prior to installing a closed-loop system on site, the topsoil, if present, will be stripped and stockpiled for use as the final cover or fill at the time of closure.

Signs will be posted on the fence surrounding the closed-loop system unless the closed-loop system is located on a site where there is an existing well, that is operated by Devon.


II. Operations and Maintenance Plan

Primary Shakers: The primary shakers make the first removal of drill solids from the drilling mud as it leaves the well bore. The shakers are sized to handle maximum drilling rate at optimal screen size. The shakers normally remove solids down to 74 microns.

Mud Cleaner: The Mud Cleaner cleans the fluid after it leaves the shakers. A set of hydrocyclones are sized to handle 1.25 to 1.5 times the maximum circulating rate. This ensures all the fluid is being processed to an average cut point of 25 microns. The wet discharged is dewatered on a shaker equipped with ultra fine mesh screens and generally cut at 40 microns.



Closed Loop Schematic



Centrifuges: The centrifuges can be one or two in number depending on the well geometry or depth of well. The centrifuges are sized to maintain low gravity solids at 5% or below. They may or may not need a dewatering system to enhance the removal rates. The centrifuges can make a cut point of 8-10 microns depending on bowl speed, feed rate, solids loading and other factors.

The centrifuge system is designed to work on the active system and be flexible to process incoming fluids from other locations. This set-up is also dependant on well factors.

Dewatering System: The dewatering system is a chemical mixing and dosing system designed to enhance the solids removal of the centrifuge. Not commonly used in shallow wells. It may contain pH adjustment, coagulant mixing and dosing, and polymer mixing and dosing. Chemical flocculation binds ultra fine solids into a mass that is within the centrifuge operating design. The

dewatering system improves the centrifuge cut point to infinity or allows for the return of clear water or brine fluid. This ability allows for the ultimate control of low gravity solids.

Cuttings Boxes: Cuttings boxes are utilized to capture drill solids that are discarded from the solids control equipment. These boxes are set upon a rail system that allows for the removal and replacement of a full box of cuttings with an empty one. They are equipped with a cover that insures no product is spilled into the environment during the transportation phase.

Process Tank: (Optional) The process tank allows for the holding and process of fluids that are being transferred into the mud system. Additionally, during times of lost circulation the process tank may hold active fluids that are removed for additional treatment. It can further be used as a mixing tank during well control conditions.

Sump and Sump Pump: The sump is used to collect storm water and the pump is used to transfer this fluid to the active system or to the tank for to hold in reserve. It can also be used to collect fluids that may escape during spills. The location contains drainage ditches that allow the location fluids to drain to the sump.

Reserve Fluids (Tank Farm): A series of frac tanks are used to replace the reserve pit. These are steel tanks that are equipped with a manifold system and a transfer pump. These tanks can contain any number of fluids used during the drilling process. These can include fresh water, cut brine, and saturated salt fluid. The fluid can be from the active well or reclaimed fluid from other locations. A 20 ml liner and berm system is employed to ensure the fluids do not migrate to the environment during a spill.

If a leak develops, the appropriate division district office will be notified within 48 hours of the discovery and the leak will be addressed. Spill prevention is accomplished by maintaining pump packing, hoses, and pipe fittings to insure no leaks are occurring. During an upset condition the source of the spill is isolated and repaired as soon as it is discovered. Free liquid is removed by a diaphragm pump and returned to the mud system. Loose topsoil may be used to stabilize the spill and the contaminated soil is excavated and placed in the cuttings boxes. After the well is finished and the rig has moved, the entire location is scrapped and testing will be performed to determine if a release has occurred.

All trash is kept in a wire mesh enclosure and removed to an approved landfill when full. All spent motor oils are kept in separate containers and they are removed and sent to an approved recycling center. Any spilled lubricants, pipe

dope, or regulated chemicals are removed from soil and sent to landfills approved for these products.

These operations are monitored by Mi Swaco service technicians. Daily logs are maintained to ensure optimal equipment operation and maintenance. Screen and chemical use is logged to maintain inventory control. Fluid properties are monitored and recorded and drilling mud volumes are accounted for in the mud storage farm. This data is kept for end of well review to insure performance goals are met. Lessons learned are logged and used to help with continuous improvement.

A MI SWACO field supervisor manages from 3-5 wells. They are responsible for training personnel, supervising installations, and inspecting sites for compliance of MI SWACO safety and operational policy.

III. Closure Plan

A maximum 340' X 340' caliche pad is built per well. All of the trucks and steel tanks fit on this pad. All fluid cuttings go to the steel tanks to be hauled by various trucking companies to an agency approved disposal.

WCDSC Permian NM

Lea County (NAD83 New Mexico East)

Sec 08-T25S-R33E

Flagler 8 Fed 27H

Wellbore #1

Permit Plan 1

Anticollision Report

06 March, 2018

Anticollision Report

Company: WCDSC Permian NM	Local Co-ordinate Reference: Well Flagler 8 Fed 27H
Project: Lea County (NAD83 New Mexico East)	TVD Reference: RKB @ 3463.20ft
Reference Site: Sec 08-T25S-R33E	MD Reference: RKB @ 3463.20ft
Site Error: 0.00 ft	North Reference: Grid
Reference Well: Flagler 8 Fed 27H	Survey Calculation Method: Minimum Curvature
Well Error: 0.50 ft	Output errors are at 2.00 sigma
Reference Wellbore: Wellbore #1	Database: EDM r5000.141_Prod US
Reference Design: Permit Plan 1	Offset TVD Reference: Offset Datum

Reference	Permit Plan 1		
Filter type:	NO GLOBAL FILTER: Using user defined selection & filtering criteria		
Interpolation Method:	MD Interval 100.00ft	Error Model:	ISCWSA
Depth Range:	Unlimited	Scan Method:	Closest Approach 3D
Results Limited by:	Maximum center-center distance of 1,000.00 ft	Error Surface:	Pedal Curve
Warning Levels Evaluated at:	2.00 Sigma	Casing Method:	Not applied

Survey Tool Program	Date 3/6/2018			
From (ft)	To (ft)	Survey (Wellbore)	Tool Name	Description
0.00	14,256.44	Permit Plan 1 (Wellbore #1)	MWD+IGRF	OWSG MWD + IGRF or WMM

Site Name	Reference Measured Depth (ft)	Offset Measured Depth (ft)	Distance Between Centres (ft)	Distance Between Ellipses (ft)	Separation Factor	Warning
Offset Well - Wellbore - Design						
Sec 08-T25S-R33E						
Flagler 8 Fed 12H - Wellbore #1 - Permit Plan 2	8,384.30	8,381.64	105.43	46.30	1.783	Minor Risk, CC
Flagler 8 Fed 12H - Wellbore #1 - Permit Plan 2	9,200.00	9,202.66	105.44	40.58	1.626	Minor Risk, ES, SF
Flagler 8 Fed 16H - Wellbore #1 - Permit Plan 1	2,400.00	2,400.40	59.98	43.19	3.572	Alert, CC
Flagler 8 Fed 16H - Wellbore #1 - Permit Plan 1	2,500.00	2,500.21	60.52	43.06	3.465	Alert, ES
Flagler 8 Fed 16H - Wellbore #1 - Permit Plan 1	9,200.00	9,201.60	144.34	80.11	2.247	Minor Risk, SF
Flagler 8 Fed 21H - Wellbore #1 - Permit Plan 1	2,400.00	2,399.60	30.00	13.21	1.787	Minor Risk, CC
Flagler 8 Fed 21H - Wellbore #1 - Permit Plan 1	2,500.00	2,499.24	30.22	12.75	1.730	Minor Risk, ES
Flagler 8 Fed 21H - Wellbore #1 - Permit Plan 1	3,100.00	3,101.03	36.76	15.31	1.714	Minor Risk, SF
Flagler 8 Fed 33H - Wellbore #1 - Permit Plan 1	2,400.00	2,400.60	89.98	73.19	5.359	CC
Flagler 8 Fed 33H - Wellbore #1 - Permit Plan 1	2,500.00	2,500.59	90.37	72.88	5.168	ES
Flagler 8 Fed 33H - Wellbore #1 - Permit Plan 1	14,256.44	14,096.43	472.31	301.82	2.770	Alert, SF
Flagler 8 Fed 40H - Wellbore #1 - Permit Plan 1	2,400.00	2,400.20	29.99	13.20	1.786	Minor Risk, CC
Flagler 8 Fed 40H - Wellbore #1 - Permit Plan 1	2,500.00	2,500.19	30.39	12.91	1.738	Minor Risk, ES
Flagler 8 Fed 40H - Wellbore #1 - Permit Plan 1	2,700.00	2,700.13	32.54	13.68	1.726	Minor Risk, SF
Flagler 8 Fed 4H - Wellbore #1 - Permit Plan 2	8,223.56	8,219.99	164.16	106.91	2.867	Alert, CC
Flagler 8 Fed 4H - Wellbore #1 - Permit Plan 2	8,300.00	8,303.58	164.53	106.71	2.846	Alert, ES
Flagler 8 Fed 4H - Wellbore #1 - Permit Plan 2	9,200.00	9,203.74	175.73	111.69	2.744	Alert, SF
Flagler 8 Fed 8H - Wellbore #1 - Permit Plan 1	3,144.19	3,140.28	209.03	187.14	9.549	CC
Flagler 8 Fed 8H - Wellbore #1 - Permit Plan 1	3,200.00	3,194.75	209.21	186.95	9.399	ES
Flagler 8 Fed 8H - Wellbore #1 - Permit Plan 1	5,000.00	4,984.31	290.43	255.76	8.378	SF

Offset Design - Sec 08-T25S-R33E - Flagler 8 Fed 12H - Wellbore #1 - Permit Plan 2											Offset Site Error: 0.00 ft		
Survey Program: 0-MWD+IGRF											Offset Well Error: 0.50 ft		
Measured Depth (ft)	Vertical Depth (ft)	Offset		Semi Major Axis		Highside Toolface (°)	Offset Wellbore Centre		Distance		Minimum Separation (ft)	Separation Factor	Warning
		Measured Depth (ft)	Vertical Depth (ft)	Reference (ft)	Offset (ft)		+N/-S (ft)	+E/-W (ft)	Between Centres (ft)	Between Ellipses (ft)			
0.00	0.00	1.00	-1.00	0.50	0.50	-171.83	-200.15	-28.72	202.20				
100.00	100.00	101.00	99.00	0.52	0.52	-171.83	-200.15	-28.72	202.20	201.16	1.04	195.089	
200.00	200.00	201.00	199.00	0.70	0.70	-171.83	-200.15	-28.72	202.20	200.79	1.41	143.738	
300.00	300.00	301.00	299.00	0.99	0.99	-171.83	-200.15	-28.72	202.20	200.22	1.98	102.237	
400.00	400.00	401.00	399.00	1.31	1.31	-171.83	-200.15	-28.72	202.20	199.58	2.62	77.132	
500.00	500.00	501.00	499.00	1.65	1.65	-171.83	-200.15	-28.72	202.20	198.90	3.30	61.355	
600.00	600.00	601.00	599.00	1.99	1.99	-171.83	-200.15	-28.72	202.20	198.22	3.98	50.745	
700.00	700.00	701.00	699.00	2.34	2.34	-171.83	-200.15	-28.72	202.20	197.52	4.68	43.186	

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

Anticollision Report

Company:	WCDSC Permian NM	Local Co-ordinate Reference:	Well Flagler 8 Fed 27H
Project:	Lea County (NAD83 New Mexico East)	TVD Reference:	RKB @ 3463.20ft
Reference Site:	Sec 08-T25S-R33E	MD Reference:	RKB @ 3463.20ft
Site Error:	0.00 ft	North Reference:	Grid
Reference Well:	Flagler 8 Fed 27H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 ft	Output errors are at:	2.00 sigma
Reference Wellbore:	Wellbore #1	Database:	EDM r5000.141_Prod US
Reference Design:	Permit Plan 1	Offset TVD Reference:	Offset Datum

Offset Design Sec 08-T25S-R33E - Flagler 8 Fed 12H - Wellbore #1 - Permit Plan 2 Offset Site Error: 0.00 ft
 Survey Program: 0-MWD+IGRF Offset Well Error: 0.50 ft

Reference		Offset		Semi Major Axis		Highside Tooface (')	Offset Wellbore Centre		Distance				Warning
Measured Depth (ft)	Vertical Depth (ft)	Measured Depth (ft)	Vertical Depth (ft)	Reference (ft)	Offset (ft)		+N/-S (ft)	+E/-W (ft)	Between Centres (ft)	Between Ellipses (ft)	Minimum Separation (ft)	Separation Factor	
800.00	800.00	801.00	799.00	2.69	2.69	-171.83	-200.15	-28.72	202.20	196.82	5.38	37.551	
900.00	900.00	901.00	899.00	3.04	3.05	-171.83	-200.15	-28.72	202.20	196.11	6.09	33.199	
1,000.00	1,000.00	1,001.00	999.00	3.40	3.40	-171.83	-200.15	-28.72	202.20	195.40	6.80	29.740	
1,100.00	1,100.00	1,101.00	1,099.00	3.75	3.76	-171.83	-200.15	-28.72	202.20	194.69	7.51	26.929	
1,200.00	1,200.00	1,201.00	1,199.00	4.11	4.11	-171.83	-200.15	-28.72	202.20	193.98	8.22	24.599	
1,300.00	1,300.00	1,301.00	1,299.00	4.46	4.47	-171.83	-200.15	-28.72	202.20	193.27	8.93	22.638	
1,400.00	1,400.00	1,401.00	1,399.00	4.82	4.82	-171.83	-200.15	-28.72	202.20	192.56	9.64	20.965	
1,500.00	1,500.00	1,501.00	1,499.00	5.18	5.18	-171.83	-200.15	-28.72	202.20	191.84	10.36	19.521	
1,600.00	1,600.00	1,601.00	1,599.00	5.53	5.54	-171.83	-200.15	-28.72	202.20	191.13	11.07	18.263	
1,700.00	1,700.00	1,701.00	1,699.00	5.89	5.89	-171.83	-200.15	-28.72	202.20	190.41	11.79	17.156	
1,800.00	1,800.00	1,801.00	1,799.00	6.25	6.25	-171.83	-200.15	-28.72	202.20	189.70	12.50	16.175	
1,900.00	1,900.00	1,901.00	1,899.00	6.61	6.61	-171.83	-200.15	-28.72	202.20	188.99	13.22	15.300	
2,000.00	2,000.00	2,001.00	1,999.00	6.96	6.97	-171.83	-200.15	-28.72	202.20	188.27	13.93	14.515	
2,100.00	2,100.00	2,101.00	2,099.00	7.32	7.32	-171.83	-200.15	-28.72	202.20	187.55	14.65	13.806	
2,200.00	2,200.00	2,201.00	2,199.00	7.68	7.68	-171.83	-200.15	-28.72	202.20	186.84	15.36	13.163	
2,300.00	2,300.00	2,301.00	2,299.00	8.04	8.04	-171.83	-200.15	-28.72	202.20	186.12	16.08	12.578	
2,400.00	2,400.00	2,401.00	2,399.00	8.39	8.40	-171.83	-200.15	-28.72	202.20	185.41	16.79	12.042	
2,500.00	2,499.99	2,501.01	2,498.99	8.73	8.76	29.36	-200.15	-28.72	201.25	183.76	17.49	11.506	
2,600.00	2,599.96	2,601.04	2,598.96	9.06	9.11	29.70	-200.15	-28.72	199.17	181.00	18.17	10.960	
2,700.00	2,699.93	2,701.07	2,698.93	9.39	9.47	30.04	-200.15	-28.72	197.09	178.23	18.86	10.451	
2,800.00	2,799.91	2,801.09	2,798.91	9.72	9.83	30.40	-200.15	-28.72	195.01	175.47	19.55	9.977	
2,900.00	2,899.88	2,901.12	2,898.88	10.05	10.19	30.76	-200.15	-28.72	192.94	172.71	20.24	9.535	
3,000.00	2,999.85	3,001.15	2,998.85	10.38	10.55	31.13	-200.15	-28.72	190.89	169.96	20.93	9.121	
3,100.00	3,099.82	3,101.18	3,098.82	10.72	10.90	31.50	-200.15	-28.72	188.83	167.21	21.62	8.734	
3,200.00	3,199.79	3,201.21	3,198.79	11.05	11.26	31.89	-200.15	-28.72	186.79	164.47	22.32	8.370	
3,300.00	3,299.76	3,301.24	3,298.76	11.39	11.62	32.28	-200.15	-28.72	184.76	161.74	23.01	8.029	
3,400.00	3,399.73	3,401.27	3,398.73	11.73	11.98	32.68	-200.15	-28.72	182.73	159.02	23.71	7.707	
3,500.00	3,499.70	3,501.30	3,498.70	12.08	12.34	33.10	-200.15	-28.72	180.71	156.31	24.41	7.404	
3,600.00	3,599.68	3,601.32	3,598.68	12.42	12.70	33.52	-200.15	-28.72	178.71	153.60	25.11	7.117	
3,700.00	3,699.65	3,701.35	3,698.65	12.76	13.05	33.95	-200.15	-28.72	176.71	150.90	25.81	6.847	
3,800.00	3,799.62	3,801.38	3,798.62	13.11	13.41	34.39	-200.15	-28.72	174.72	148.21	26.51	6.590	
3,900.00	3,899.59	3,901.41	3,898.59	13.45	13.77	34.83	-200.15	-28.72	172.75	145.53	27.21	6.348	
4,000.00	3,999.56	4,001.44	3,998.56	13.80	14.13	35.29	-200.15	-28.72	170.78	142.86	27.92	6.117	
4,100.00	4,099.53	4,101.47	4,098.53	14.15	14.49	35.77	-200.15	-28.72	168.83	140.20	28.62	5.898	
4,200.00	4,199.50	4,201.50	4,198.50	14.49	14.85	36.25	-200.15	-28.72	166.88	137.56	29.33	5.690	
4,300.00	4,299.47	4,301.53	4,298.47	14.84	15.20	36.74	-200.15	-28.72	164.95	134.92	30.03	5.492	
4,400.00	4,399.44	4,401.56	4,398.44	15.19	15.56	37.25	-200.15	-28.72	163.04	132.30	30.74	5.304	
4,500.00	4,499.42	4,501.58	4,498.42	15.54	15.92	37.76	-200.15	-28.72	161.13	129.68	31.45	5.124	
4,600.00	4,599.39	4,601.61	4,598.39	15.89	16.28	38.29	-200.15	-28.72	159.24	127.08	32.15	4.952 Alert	
4,700.00	4,699.36	4,701.64	4,698.36	16.24	16.64	38.83	-200.15	-28.72	157.36	124.50	32.86	4.788 Alert	
4,800.00	4,799.33	4,801.67	4,798.33	16.59	17.00	39.39	-200.15	-28.72	155.50	121.93	33.57	4.632 Alert	
4,900.00	4,899.30	4,901.70	4,898.30	16.94	17.35	39.96	-200.15	-28.72	153.65	119.37	34.28	4.482 Alert	
5,000.00	4,999.27	5,001.73	4,998.27	17.30	17.71	40.54	-200.15	-28.72	151.82	116.83	34.99	4.339 Alert	
5,100.00	5,099.24	5,101.76	5,098.24	17.65	18.07	41.13	-200.15	-28.72	150.00	114.30	35.70	4.202 Alert	
5,200.00	5,199.21	5,201.79	5,198.21	18.00	18.43	41.74	-200.15	-28.72	148.20	111.79	36.41	4.070 Alert	
5,300.00	5,299.19	5,301.82	5,298.19	18.36	18.79	42.37	-200.15	-28.72	146.42	109.29	37.12	3.944 Alert	
5,400.00	5,399.16	5,401.84	5,398.16	18.71	19.15	43.01	-200.15	-28.72	144.65	106.82	37.83	3.823 Alert	
5,500.00	5,499.13	5,501.87	5,498.13	19.06	19.51	43.67	-200.15	-28.72	142.90	104.36	38.54	3.708 Alert	
5,600.00	5,599.10	5,601.90	5,598.10	19.42	19.86	44.34	-200.15	-28.72	141.18	101.92	39.26	3.596 Alert	
5,700.00	5,699.07	5,701.93	5,698.07	19.77	20.22	45.03	-200.15	-28.72	139.47	99.50	39.97	3.490 Alert	
5,800.00	5,799.04	5,801.96	5,798.04	20.13	20.58	45.74	-200.15	-28.72	137.78	97.10	40.68	3.387 Alert	
5,900.00	5,899.01	5,901.99	5,898.01	20.48	20.94	46.46	-200.15	-28.72	136.12	94.72	41.39	3.288 Alert	

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

Anticollision Report

Company:	WCDSC Permian NM	Local Co-ordinate Reference:	Well Flagler 8 Fed 27H
Project:	Lea County (NAD83 New Mexico East)	TVD Reference:	RKB @ 3463.20ft
Reference Site:	Sec 08-T25S-R33E	MD Reference:	RKB @ 3463.20ft
Site Error:	0.00 ft	North Reference:	Grid
Reference Well:	Flagler 8 Fed 27H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 ft	Output errors are at	2.00 sigma
Reference Wellbore	Wellbore #1	Database:	EDM r5000.141_Prod US
Reference Design:	Permit Plan 1	Offset TVD Reference:	Offset Datum

Offset Design: Sec 08-T25S-R33E - Flagler 8 Fed 12H - Wellbore #1 - Permit Plan 2													Offset Site Error:	0.00 ft
Survey Program: 0-MWD+IGRF													Offset Well Error:	0.50 ft
Reference				Offset			Semi Major Axis			Distance			Warning	
Measured Depth (ft)	Vertical Depth (ft)	Measured Depth (ft)	Vertical Depth (ft)	Reference (ft)	Offset (ft)	Highside Tooface (')	Offset Wellbore Centre +N/-S (ft)	+E/-W (ft)	Between Centres (ft)	Between Ellipses (ft)	Minimum Separation (ft)	Separation Factor		
6,000.00	5,998.98	6,002.02	5,997.98	20.84	21.30	47.20	-200.15	-28.72	134.47	92.37	42.11	3.194	Alert	
6,100.00	6,098.95	6,102.05	6,097.95	21.19	21.66	47.96	-200.15	-28.72	132.85	90.03	42.82	3.103	Alert	
6,200.00	6,198.93	6,202.07	6,197.93	21.55	22.01	48.74	-200.15	-28.72	131.26	87.72	43.53	3.015	Alert	
6,300.00	6,298.90	6,302.10	6,297.90	21.90	22.37	49.54	-200.15	-28.72	129.69	85.44	44.25	2.931	Alert	
6,400.00	6,398.87	6,402.13	6,397.87	22.26	22.73	50.35	-200.15	-28.72	128.14	83.18	44.96	2.850	Alert	
6,500.00	6,498.84	6,502.16	6,497.84	22.62	23.09	51.19	-200.15	-28.72	126.62	80.95	45.68	2.772	Alert	
6,600.00	6,598.81	6,602.19	6,597.81	22.97	23.45	52.05	-200.15	-28.72	125.13	78.74	46.39	2.697	Alert	
6,700.00	6,698.78	6,702.22	6,697.78	23.33	23.81	52.92	-200.15	-28.72	123.67	76.56	47.11	2.625	Alert	
6,800.00	6,798.75	6,802.25	6,797.75	23.69	24.17	53.82	-200.15	-28.72	122.24	74.41	47.82	2.556	Alert	
6,900.00	6,898.72	6,902.28	6,897.72	24.04	24.52	54.74	-200.15	-28.72	120.83	72.30	48.54	2.489	Minor Risk	
7,000.00	6,998.70	7,002.31	6,997.70	24.40	24.88	55.68	-200.15	-28.72	119.46	70.21	49.25	2.425	Minor Risk	
7,100.00	7,098.67	7,102.33	7,097.67	24.76	25.24	56.64	-200.15	-28.72	118.13	68.16	49.97	2.364	Minor Risk	
7,200.00	7,198.64	7,202.36	7,197.64	25.11	25.60	57.62	-200.15	-28.72	116.82	66.14	50.69	2.305	Minor Risk	
7,300.00	7,298.61	7,302.39	7,297.61	25.47	25.96	58.63	-200.15	-28.72	115.55	64.15	51.40	2.248	Minor Risk	
7,400.00	7,398.58	7,402.42	7,397.58	25.83	26.32	59.66	-200.15	-28.72	114.32	62.20	52.12	2.193	Minor Risk	
7,500.00	7,498.55	7,502.45	7,497.55	26.19	26.67	60.71	-200.15	-28.72	113.13	60.29	52.84	2.141	Minor Risk	
7,600.00	7,598.52	7,602.48	7,597.52	26.55	27.03	61.78	-200.15	-28.72	111.97	58.42	53.55	2.091	Minor Risk	
7,700.00	7,698.49	7,702.51	7,697.49	26.90	27.39	62.87	-200.15	-28.72	110.86	56.59	54.27	2.043	Minor Risk	
7,800.00	7,798.46	7,802.54	7,797.46	27.26	27.75	63.99	-200.15	-28.72	109.78	54.79	54.99	1.996	Minor Risk	
7,900.00	7,898.44	7,902.56	7,897.44	27.62	28.11	65.12	-200.15	-28.72	108.75	53.04	55.71	1.952	Minor Risk	
8,000.00	7,998.41	8,002.59	7,997.41	27.98	28.47	66.28	-200.15	-28.72	107.76	51.34	56.42	1.910	Minor Risk	
8,100.00	8,098.38	8,102.62	8,097.38	28.34	28.83	67.46	-200.15	-28.72	106.82	49.68	57.14	1.869	Minor Risk	
8,200.00	8,198.35	8,202.65	8,197.35	28.69	29.18	68.66	-200.15	-28.72	105.92	48.06	57.86	1.831	Minor Risk	
8,300.00	8,298.34	8,302.66	8,297.34	29.04	29.54	69.33	-200.15	-28.72	105.44	46.87	58.57	1.800	Minor Risk	
8,384.30	8,382.64	8,381.64	8,381.64	29.33	29.83	-131.69	-200.15	-28.72	105.43	46.30	59.14	1.783	Minor Risk, CC	
8,400.00	8,398.34	8,402.66	8,397.34	29.38	29.90	-131.71	-200.15	-28.72	105.44	46.17	59.27	1.779	Minor Risk	
8,500.00	8,498.34	8,502.66	8,497.34	29.72	30.26	-131.71	-200.15	-28.72	105.44	45.48	59.97	1.758	Minor Risk	
8,600.00	8,598.34	8,602.66	8,597.34	30.06	30.62	-131.71	-200.15	-28.72	105.44	44.78	60.66	1.738	Minor Risk	
8,700.00	8,698.34	8,702.66	8,697.34	30.40	30.98	-131.71	-200.15	-28.72	105.44	44.08	61.36	1.718	Minor Risk	
8,800.00	8,798.34	8,802.66	8,797.34	30.74	31.33	-131.71	-200.15	-28.72	105.44	43.38	62.06	1.699	Minor Risk	
8,900.00	8,898.34	8,902.66	8,897.34	31.08	31.69	-131.71	-200.15	-28.72	105.44	42.68	62.76	1.680	Minor Risk	
9,000.00	8,998.34	9,002.66	8,997.34	31.42	32.05	-131.71	-200.15	-28.72	105.44	41.98	63.46	1.662	Minor Risk	
9,100.00	9,098.34	9,102.66	9,097.34	31.76	32.41	-131.71	-200.15	-28.72	105.44	41.28	64.16	1.643	Minor Risk	
9,200.00	9,198.34	9,202.66	9,197.34	32.11	32.77	-131.71	-200.15	-28.72	105.44	40.58	64.86	1.626	Minor Risk, ES, SF	
9,300.00	9,298.15	9,302.85	9,297.15	32.44	33.13	-133.21	-200.15	-28.72	108.44	42.88	65.56	1.654	Minor Risk	
9,400.00	9,395.80	9,405.20	9,394.80	32.76	33.49	-139.22	-200.15	-28.72	123.81	57.57	66.23	1.869	Minor Risk	
9,500.00	9,488.31	9,487.31	9,487.31	33.05	33.79	-146.40	-200.15	-28.72	154.70	87.89	66.81	2.316	Minor Risk	
9,600.00	9,572.89	9,571.89	9,571.89	33.33	34.09	-152.07	-200.15	-28.72	202.24	134.88	67.36	3.003	Alert	
9,700.00	9,646.96	9,645.96	9,645.96	33.62	34.36	-155.44	-200.15	-28.72	265.23	197.41	67.82	3.911	Alert	
9,800.00	9,708.27	9,707.27	9,707.27	33.93	34.58	-156.40	-200.15	-28.72	341.32	273.13	68.19	5.006		
9,900.00	9,754.96	9,753.96	9,753.96	34.29	34.74	-154.27	-200.15	-28.72	427.71	359.26	68.45	6.249		
10,000.00	9,785.60	9,784.60	9,784.60	34.69	34.85	-145.56	-200.15	-28.72	521.43	452.82	68.61	7.600		
10,100.00	9,799.28	9,801.72	9,798.28	35.14	34.92	-111.34	-200.15	-28.72	619.41	550.72	68.69	9.017		
10,200.00	9,800.00	9,801.00	9,799.00	35.65	34.91	-90.00	-200.15	-28.72	718.70	650.00	68.70	10.462		
10,300.00	9,800.00	9,801.00	9,799.00	36.26	34.91	-90.00	-200.15	-28.72	818.17	749.47	68.70	11.909		
10,400.00	9,800.00	9,801.00	9,799.00	36.95	34.91	-90.00	-200.15	-28.72	917.76	849.05	68.71	13.357		

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

Anticollision Report

Company:	WCDSC Permian NM	Local Co-ordinate Reference:	Well Flagler 8 Fed 27H
Project:	Lea County (NAD83 New Mexico East)	TVD Reference:	RKB @ 3463.20ft
Reference Site:	Sec 08-T25S-R33E	MD Reference:	RKB @ 3463.20ft
Site Error:	0.00 ft	North Reference:	Grid
Reference Well:	Flagler 8 Fed 27H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 ft	Output errors are at	2.00 sigma
Reference Wellbore	Wellbore #1	Database:	EDM r5000.141_Prod US
Reference Design:	Permit Plan 1	Offset TVD Reference:	Offset Datum

Offset Design Sec 08-T25S-R33E - Flagler 8 Fed 16H - Wellbore #1 - Permit Plan 1 **Offset Site Error:** 0.00 ft
Survey Program: 0-MWD+IGRF **Offset Well Error:** 0.50 ft

Reference		Offset		Semi Major Axis		Highside Toolface (°)	Offset Wellbore Centre		Distance		Minimum Separation (ft)	Separation Factor	Warning
Measured Depth (ft)	Vertical Depth (ft)	Measured Depth (ft)	Vertical Depth (ft)	Reference (ft)	Offset (ft)		+N-S (ft)	+E-W (ft)	Between Centres (ft)	Between Ellipses (ft)			
0.00	0.00	0.40	0.40	0.50	0.50	-90.37	-0.39	-59.98	59.98				
100.00	100.00	100.40	100.40	0.52	0.52	-90.37	-0.39	-59.98	59.98	58.95	1.04	57.904	
200.00	200.00	200.40	200.40	0.70	0.70	-90.37	-0.39	-59.98	59.98	58.58	1.41	42.885	
300.00	300.00	300.40	300.40	0.99	0.99	-90.37	-0.39	-59.98	59.98	58.01	1.98	30.356	
400.00	400.00	400.40	400.40	1.31	1.31	-90.37	-0.39	-59.98	59.98	57.36	2.62	22.898	
500.00	500.00	500.40	500.40	1.65	1.65	-90.37	-0.39	-59.98	59.98	56.69	3.29	18.212	
600.00	600.00	600.40	600.40	1.99	1.99	-90.37	-0.39	-59.98	59.98	56.00	3.98	15.061	
700.00	700.00	700.40	700.40	2.34	2.34	-90.37	-0.39	-59.98	59.98	55.30	4.68	12.816	
800.00	800.00	800.40	800.40	2.69	2.69	-90.37	-0.39	-59.98	59.98	54.60	5.38	11.144	
900.00	900.00	900.40	900.40	3.04	3.04	-90.37	-0.39	-59.98	59.98	53.89	6.09	9.852	
1,000.00	1,000.00	1,000.40	1,000.40	3.40	3.40	-90.37	-0.39	-59.98	59.98	53.18	6.80	8.825	
1,100.00	1,100.00	1,100.40	1,100.40	3.75	3.75	-90.37	-0.39	-59.98	59.98	52.47	7.51	7.990	
1,200.00	1,200.00	1,200.40	1,200.40	4.11	4.11	-90.37	-0.39	-59.98	59.98	51.76	8.22	7.299	
1,300.00	1,300.00	1,300.40	1,300.40	4.46	4.47	-90.37	-0.39	-59.98	59.98	51.05	8.93	6.717	
1,400.00	1,400.00	1,400.40	1,400.40	4.82	4.82	-90.37	-0.39	-59.98	59.98	50.34	9.64	6.220	
1,500.00	1,500.00	1,500.40	1,500.40	5.18	5.18	-90.37	-0.39	-59.98	59.98	49.63	10.36	5.792	
1,600.00	1,600.00	1,600.40	1,600.40	5.53	5.54	-90.37	-0.39	-59.98	59.98	48.91	11.07	5.419	
1,700.00	1,700.00	1,700.40	1,700.40	5.89	5.89	-90.37	-0.39	-59.98	59.98	48.20	11.78	5.090	
1,800.00	1,800.00	1,800.40	1,800.40	6.25	6.25	-90.37	-0.39	-59.98	59.98	47.48	12.50	4.799 Alert	
1,900.00	1,900.00	1,900.40	1,900.40	6.61	6.61	-90.37	-0.39	-59.98	59.98	46.77	13.21	4.540 Alert	
2,000.00	2,000.00	2,000.40	2,000.40	6.96	6.96	-90.37	-0.39	-59.98	59.98	46.05	13.93	4.306 Alert	
2,100.00	2,100.00	2,100.40	2,100.40	7.32	7.32	-90.37	-0.39	-59.98	59.98	45.34	14.64	4.096 Alert	
2,200.00	2,200.00	2,200.40	2,200.40	7.68	7.68	-90.37	-0.39	-59.98	59.98	44.62	15.36	3.905 Alert	
2,300.00	2,300.00	2,300.40	2,300.40	8.04	8.04	-90.37	-0.39	-59.98	59.98	43.91	16.07	3.732 Alert	
2,400.00	2,400.00	2,400.40	2,400.40	8.39	8.40	-90.37	-0.39	-59.98	59.98	43.19	16.79	3.572 Alert, CC	
2,500.00	2,499.99	2,500.21	2,500.20	8.73	8.73	110.60	-1.48	-60.13	60.52	43.06	17.47	3.463 Alert, ES	
2,600.00	2,599.96	2,600.11	2,600.06	9.06	9.06	109.97	-4.39	-60.53	61.79	43.68	18.12	3.411 Alert	
2,700.00	2,699.93	2,700.10	2,700.00	9.39	9.38	109.18	-7.52	-60.97	63.11	44.34	18.77	3.363 Alert	
2,800.00	2,799.91	2,800.09	2,799.94	9.72	9.71	108.43	-10.65	-61.40	64.44	45.01	19.43	3.317 Alert	
2,900.00	2,899.88	2,900.07	2,899.87	10.05	10.04	107.70	-13.78	-61.83	65.78	45.69	20.09	3.274 Alert	
3,000.00	2,999.85	3,000.06	2,999.81	10.38	10.38	107.01	-16.92	-62.27	67.13	46.37	20.76	3.234 Alert	
3,100.00	3,099.82	3,100.05	3,099.75	10.72	10.71	106.34	-20.05	-62.70	68.49	47.06	21.43	3.196 Alert	
3,200.00	3,199.79	3,200.04	3,199.69	11.05	11.05	105.70	-23.18	-63.13	69.86	47.76	22.10	3.161 Alert	
3,300.00	3,299.76	3,300.03	3,299.62	11.39	11.39	105.08	-26.31	-63.57	71.23	48.45	22.78	3.127 Alert	
3,400.00	3,399.73	3,400.01	3,399.56	11.73	11.73	104.49	-29.44	-64.00	72.62	49.16	23.46	3.096 Alert	
3,500.00	3,499.70	3,500.00	3,499.50	12.08	12.07	103.91	-32.58	-64.43	74.01	49.87	24.14	3.066 Alert	
3,600.00	3,599.68	3,600.01	3,599.44	12.42	12.41	103.36	-35.71	-64.87	75.41	50.58	24.83	3.037 Alert	
3,700.00	3,699.65	3,700.02	3,699.37	12.76	12.76	102.83	-38.84	-65.30	76.82	51.30	25.52	3.011 Alert	
3,800.00	3,799.62	3,800.04	3,799.31	13.11	13.10	102.32	-41.97	-65.73	78.23	52.02	26.20	2.985 Alert	
3,900.00	3,899.59	3,900.05	3,899.25	13.45	13.45	101.83	-45.10	-66.17	79.65	52.75	26.90	2.961 Alert	
4,000.00	3,999.56	4,000.06	3,999.19	13.80	13.80	101.35	-48.24	-66.60	81.07	53.48	27.59	2.938 Alert	
4,100.00	4,099.53	4,100.07	4,099.12	14.15	14.14	100.90	-51.37	-67.03	82.50	54.21	28.28	2.917 Alert	
4,200.00	4,199.50	4,200.09	4,199.06	14.49	14.49	100.45	-54.50	-67.46	83.93	54.95	28.98	2.896 Alert	
4,300.00	4,299.47	4,300.10	4,299.00	14.84	14.84	100.02	-57.63	-67.90	85.37	55.69	29.68	2.877 Alert	
4,400.00	4,399.44	4,400.11	4,398.94	15.19	15.19	99.61	-60.76	-68.33	86.82	56.44	30.38	2.858 Alert	
4,500.00	4,499.42	4,500.12	4,498.88	15.54	15.54	99.21	-63.90	-68.76	88.27	57.19	31.08	2.840 Alert	
4,600.00	4,599.39	4,600.14	4,598.81	15.89	15.90	98.82	-67.03	-69.20	89.72	57.94	31.78	2.823 Alert	
4,700.00	4,699.36	4,700.15	4,698.75	16.24	16.25	98.44	-70.16	-69.63	91.17	58.69	32.48	2.807 Alert	
4,800.00	4,799.33	4,800.16	4,798.69	16.59	16.60	98.08	-73.29	-70.06	92.63	59.45	33.19	2.791 Alert	
4,900.00	4,899.30	4,900.17	4,898.63	16.94	16.95	97.73	-76.42	-70.50	94.10	60.21	33.89	2.777 Alert	
5,000.00	4,999.27	5,000.19	4,998.56	17.30	17.31	97.39	-79.56	-70.93	95.57	60.97	34.59	2.762 Alert	
5,100.00	5,099.24	5,100.20	5,098.50	17.65	17.66	97.06	-82.69	-71.36	97.04	61.74	35.30	2.749 Alert	

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

Anticollision Report

Company:	WCDSC Permian NM	Local Co-ordinate Reference:	Well Flagler 8 Fed 27H
Project:	Lea County (NAD83 New Mexico East)	TVD Reference:	RKB @ 3463.20ft
Reference Site:	Sec 08-T25S-R33E	MD Reference:	RKB @ 3463.20ft
Site Error:	0.00 ft	North Reference:	Grid
Reference Well:	Flagler 8 Fed 27H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 ft	Output errors are at	2.00 sigma
Reference Wellbore	Wellbore #1	Database:	EDM r5000.141_Prod US
Reference Design:	Permit Plan 1	Offset TVD Reference:	Offset Datum

Offset Design													Sec 08-T25S-R33E - Flagler 8 Fed 16H - Wellbore #1 - Permit Plan 1	Offset Site Error:	0.00 ft
Survey Program: 0-MWD+IGRF														Offset Well Error:	0.50 ft
Reference				Semi Major Axis			Distance				Minimum Separation		Warning		
Measured Depth (ft)	Vertical Depth (ft)	Measured Depth (ft)	Vertical Depth (ft)	Reference (ft)	Offset (ft)	Highside Tooface (")	Offset Wellbore Centre +N/-S (ft)	+E/-W (ft)	Between Centres (ft)	Between Ellipses (ft)	Minimum Separation (ft)	Separation Factor			
5,200.00	5,199.21	5,200.21	5,198.44	18.00	18.02	96.73	-85.82	-71.80	98.51	62.50	36.01	2.736	Alert		
5,300.00	5,299.19	5,300.22	5,298.38	18.36	18.37	96.42	-88.95	-72.23	99.99	63.27	36.71	2.723	Alert		
5,400.00	5,399.16	5,400.23	5,398.31	18.71	18.73	96.12	-92.09	-72.66	101.47	64.04	37.42	2.711	Alert		
5,500.00	5,499.13	5,500.25	5,498.25	19.06	19.08	95.83	-95.22	-73.10	102.95	64.82	38.13	2.700	Alert		
5,600.00	5,599.10	5,600.26	5,598.19	19.42	19.44	95.54	-98.35	-73.53	104.43	65.59	38.84	2.689	Alert		
5,700.00	5,699.07	5,700.27	5,698.13	19.77	19.79	95.26	-101.48	-73.96	105.92	66.37	39.55	2.678	Alert		
5,800.00	5,799.04	5,800.28	5,798.06	20.13	20.15	94.99	-104.61	-74.40	107.41	67.15	40.26	2.668	Alert		
5,900.00	5,899.01	5,900.30	5,898.00	20.48	20.51	94.73	-107.75	-74.83	108.90	67.93	40.97	2.658	Alert		
6,000.00	5,998.98	6,000.31	5,997.94	20.84	20.86	94.48	-110.88	-75.26	110.40	68.72	41.68	2.649	Alert		
6,100.00	6,098.95	6,100.32	6,097.88	21.19	21.22	94.23	-114.01	-75.70	111.89	69.50	42.39	2.639	Alert		
6,200.00	6,198.93	6,200.33	6,197.81	21.55	21.58	93.98	-117.14	-76.13	113.39	70.29	43.11	2.631	Alert		
6,300.00	6,298.90	6,300.35	6,297.75	21.90	21.94	93.75	-120.27	-76.56	114.89	71.08	43.82	2.622	Alert		
6,400.00	6,398.87	6,400.36	6,397.69	22.26	22.29	93.52	-123.41	-77.00	116.40	71.87	44.53	2.614	Alert		
6,500.00	6,498.84	6,500.37	6,497.63	22.62	22.65	93.30	-126.54	-77.43	117.90	72.66	45.24	2.606	Alert		
6,600.00	6,598.81	6,600.38	6,597.57	22.97	23.01	93.08	-129.67	-77.86	119.41	73.45	45.96	2.598	Alert		
6,700.00	6,698.78	6,700.40	6,697.50	23.33	23.37	92.86	-132.80	-78.30	120.91	74.24	46.67	2.591	Alert		
6,800.00	6,798.75	6,800.41	6,797.44	23.69	23.73	92.66	-135.93	-78.73	122.42	75.04	47.39	2.584	Alert		
6,900.00	6,898.72	6,900.42	6,897.38	24.04	24.09	92.45	-139.07	-79.16	123.93	75.83	48.10	2.577	Alert		
7,000.00	6,998.70	7,000.43	6,997.32	24.40	24.45	92.26	-142.20	-79.59	125.45	76.63	48.81	2.570	Alert		
7,100.00	7,098.67	7,100.44	7,097.25	24.76	24.81	92.06	-145.33	-80.03	126.96	77.43	49.53	2.563	Alert		
7,200.00	7,198.64	7,200.46	7,197.19	25.11	25.16	91.88	-148.46	-80.46	128.48	78.23	50.25	2.557	Alert		
7,300.00	7,298.61	7,300.47	7,297.13	25.47	25.52	91.69	-151.59	-80.89	129.99	79.03	50.96	2.551	Alert		
7,400.00	7,398.58	7,400.48	7,397.07	25.83	25.88	91.51	-154.73	-81.33	131.51	79.83	51.68	2.545	Alert		
7,500.00	7,498.55	7,500.49	7,497.00	26.19	26.24	91.34	-157.86	-81.76	133.03	80.64	52.39	2.539	Alert		
7,600.00	7,598.52	7,600.51	7,596.94	26.55	26.60	91.17	-160.99	-82.19	134.55	81.44	53.11	2.533	Alert		
7,700.00	7,698.49	7,700.52	7,696.88	26.90	26.96	91.00	-164.12	-82.63	136.07	82.25	53.83	2.528	Alert		
7,800.00	7,798.46	7,800.53	7,796.82	27.26	27.32	90.83	-167.25	-83.06	137.60	83.05	54.54	2.523	Alert		
7,900.00	7,898.44	7,900.54	7,896.75	27.62	27.68	90.67	-170.39	-83.49	139.12	83.86	55.26	2.518	Alert		
8,000.00	7,998.41	8,000.56	7,996.69	27.98	28.04	90.52	-173.52	-83.93	140.64	84.67	55.98	2.513	Alert		
8,100.00	8,098.38	8,099.43	8,096.63	28.34	28.40	90.36	-176.65	-84.36	142.17	85.48	56.69	2.508	Alert		
8,200.00	8,198.35	8,199.74	8,196.89	28.69	28.76	90.23	-179.75	-84.79	143.68	86.27	57.41	2.503	Alert		
8,300.00	8,298.34	8,301.58	8,298.71	29.04	29.12	90.29	-181.13	-84.98	144.34	86.23	58.11	2.484	Minor Risk		
8,400.00	8,398.34	8,401.60	8,398.74	29.38	29.45	-110.75	-181.13	-84.98	144.34	85.55	58.79	2.455	Minor Risk		
8,500.00	8,498.34	8,501.60	8,498.74	29.72	29.79	-110.75	-181.13	-84.98	144.34	84.87	59.47	2.427	Minor Risk		
8,600.00	8,598.34	8,601.60	8,598.74	30.06	30.13	-110.75	-181.13	-84.98	144.34	84.20	60.14	2.400	Minor Risk		
8,700.00	8,698.34	8,701.60	8,698.74	30.40	30.47	-110.75	-181.13	-84.98	144.34	83.52	60.82	2.373	Minor Risk		
8,800.00	8,798.34	8,801.60	8,798.74	30.74	30.80	-110.75	-181.13	-84.98	144.34	82.84	61.50	2.347	Minor Risk		
8,900.00	8,898.34	8,901.60	8,898.74	31.08	31.14	-110.75	-181.13	-84.98	144.34	82.16	62.18	2.321	Minor Risk		
9,000.00	8,998.34	9,001.60	8,998.74	31.42	31.48	-110.75	-181.13	-84.98	144.34	81.48	62.86	2.296	Minor Risk		
9,100.00	9,098.34	9,101.60	9,098.74	31.76	31.82	-110.75	-181.13	-84.98	144.34	80.79	63.55	2.271	Minor Risk		
9,200.00	9,198.34	9,201.60	9,198.74	32.11	32.16	-110.75	-181.13	-84.98	144.34	80.11	64.23	2.247	Minor Risk, SF		
9,300.00	9,298.15	9,301.42	9,298.55	32.44	32.50	-112.19	-181.13	-84.98	145.97	81.07	64.90	2.249	Minor Risk		
9,400.00	9,398.80	9,400.94	9,398.20	32.76	32.84	-118.43	-181.13	-84.98	155.17	89.63	65.54	2.368	Minor Risk		
9,500.00	9,498.31	9,508.42	9,498.71	33.05	33.21	-126.95	-181.13	-84.98	176.77	110.61	66.16	2.672	Alert		
9,600.00	9,572.89	9,576.15	9,573.29	33.33	33.44	-134.64	-181.13	-84.98	214.92	148.32	66.61	3.227	Alert		
9,700.00	9,646.96	9,650.22	9,647.36	33.62	33.69	-139.73	-181.13	-84.98	270.35	203.30	67.04	4.032	Alert		
9,800.00	9,708.27	9,711.53	9,708.67	33.93	33.90	-141.53	-181.13	-84.98	340.94	273.54	67.39	5.059			
9,900.00	9,754.96	9,758.22	9,755.36	34.29	34.06	-139.13	-181.13	-84.98	423.45	355.81	67.85	6.260			
10,000.00	9,785.60	9,788.87	9,786.00	34.69	34.17	-129.32	-181.13	-84.98	514.44	446.64	67.80	7.587			
10,100.00	9,799.28	9,802.54	9,799.68	35.14	34.22	-102.45	-181.13	-84.98	610.46	542.59	67.87	8.995			
10,200.00	9,800.00	9,803.26	9,800.40	35.65	34.22	-90.00	-181.13	-84.98	708.32	640.44	67.88	10.435			
10,300.00	9,800.00	9,803.26	9,800.40	36.26	34.22	-90.00	-181.13	-84.98	806.71	738.83	67.88	11.884			

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

Anticollision Report

Company:	WCDSC Permian NM	Local Co-ordinate Reference:	Well Flagler 8 Fed 27H
Project:	Lea County (NAD83 New Mexico East)	TVD Reference:	RKB @ 3463.20ft
Reference Site:	Sec 08-T25S-R33E	MD Reference:	RKB @ 3463.20ft
Site Error:	0.00 ft	North Reference:	Grid
Reference Well:	Flagler 8 Fed 27H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 ft	Output errors are at	2.00 sigma
Reference Wellbore	Wellbore #1	Database:	EDM r5000.141_Prod US
Reference Design:	Permit Plan 1	Offset TVD Reference:	Offset Datum

Offset Design													Offset Site Error:	0.00 ft
Sec 08-T25S-R33E - Flagler 8 Fed 16H - Wellbore #1 - Permit Plan 1													Offset Well Error:	0.50 ft
Survey Program: 0-MWD+IGRF														
Reference		Offset		Semi Major Axis			Distance					Warning		
Measured Depth (ft)	Vertical Depth (ft)	Measured Depth (ft)	Vertical Depth (ft)	Reference (ft)	Offset (ft)	Highside Toolface (°)	Offset Wellbore Centre +N/-S (ft)	+E/-W (ft)	Between Centres (ft)	Between Ellipses (ft)	Minimum Separation (ft)	Separation Factor		
10,400.00	9,800.00	9,803.28	9,800.40	36.95	34.22	-90.00	-181.13	-84.98	905.45	837.56	67.89	13.337		

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

Anticollision Report

Company:	WCDCS Permian NM	Local Co-ordinate Reference:	Well Flagler 8 Fed 27H
Project:	Lea County (NAD83 New Mexico East)	TVD Reference:	RKB @ 3463.20ft
Reference Site:	Sec 08-T25S-R33E	MD Reference:	RKB @ 3463.20ft
Site Error:	0.00 ft	North Reference:	Grid
Reference Well:	Flagler 8 Fed 27H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 ft	Output errors are at	2.00 sigma
Reference Wellbore	Wellbore #1	Database:	EDM r5000.141_Prod US
Reference Design:	Permit Plan 1	Offset TVD Reference:	Offset Datum

Offset Design														Offset Site Error:	0.00 ft	
Survey Program: 0-MWD+IGRF														Offset Well Error:		0.50 ft
Reference		Offset		Semi Major Axis			Distance							Warning		
Measured Depth (ft)	Vertical Depth (ft)	Measured Depth (ft)	Vertical Depth (ft)	Reference (ft)	Offset (ft)	Highside Tooface (")	Offset Wellbore Centre +N-S (ft)	+E-W (ft)	Between Centres (ft)	Between Ellipses (ft)	Minimum Separation (ft)	Separation Factor				
0.00	0.00	0.40	-0.40	0.50	0.50	89.62	0.20	30.00	30.00							
100.00	100.00	100.40	99.60	0.52	0.52	89.62	0.20	30.00	30.00	28.96	1.04	28.961				
200.00	200.00	200.40	199.60	0.70	0.70	89.62	0.20	30.00	30.00	28.60	1.41	21.350				
300.00	300.00	300.40	299.60	0.99	0.99	89.62	0.20	30.00	30.00	28.02	1.98	15.183				
400.00	400.00	400.40	399.60	1.31	1.31	89.62	0.20	30.00	30.00	27.38	2.62	11.453				
500.00	500.00	500.40	499.60	1.65	1.65	89.62	0.20	30.00	30.00	26.71	3.29	9.109				
600.00	600.00	600.40	599.60	1.99	1.99	89.62	0.20	30.00	30.00	26.02	3.98	7.533				
700.00	700.00	700.40	699.60	2.34	2.34	89.62	0.20	30.00	30.00	25.32	4.68	6.410				
800.00	800.00	800.40	799.60	2.69	2.69	89.62	0.20	30.00	30.00	24.62	5.38	5.574				
900.00	900.00	900.40	899.60	3.04	3.04	89.62	0.20	30.00	30.00	23.91	6.09	4.927	Alert			
1,000.00	1,000.00	1,000.40	999.60	3.40	3.40	89.62	0.20	30.00	30.00	23.20	6.80	4.414	Alert			
1,100.00	1,100.00	1,100.40	1,099.60	3.75	3.75	89.62	0.20	30.00	30.00	22.49	7.51	3.997	Alert			
1,200.00	1,200.00	1,200.40	1,199.60	4.11	4.11	89.62	0.20	30.00	30.00	21.78	8.22	3.651	Alert			
1,300.00	1,300.00	1,300.40	1,299.60	4.46	4.47	89.62	0.20	30.00	30.00	21.07	8.93	3.360	Alert			
1,400.00	1,400.00	1,400.40	1,399.60	4.82	4.82	89.62	0.20	30.00	30.00	20.36	9.64	3.111	Alert			
1,500.00	1,500.00	1,500.40	1,499.60	5.18	5.18	89.62	0.20	30.00	30.00	19.64	10.36	2.897	Alert			
1,600.00	1,600.00	1,600.40	1,599.60	5.53	5.54	89.62	0.20	30.00	30.00	18.93	11.07	2.710	Alert			
1,700.00	1,700.00	1,700.40	1,699.60	5.89	5.89	89.62	0.20	30.00	30.00	18.22	11.78	2.546	Alert			
1,800.00	1,800.00	1,800.40	1,799.60	6.25	6.25	89.62	0.20	30.00	30.00	17.50	12.50	2.400	Minor Risk			
1,900.00	1,900.00	1,900.40	1,899.60	6.61	6.61	89.62	0.20	30.00	30.00	16.79	13.21	2.271	Minor Risk			
2,000.00	2,000.00	2,000.40	1,999.60	6.96	6.96	89.62	0.20	30.00	30.00	16.07	13.93	2.154	Minor Risk			
2,100.00	2,100.00	2,100.40	2,099.60	7.32	7.32	89.62	0.20	30.00	30.00	15.36	14.64	2.049	Minor Risk			
2,200.00	2,200.00	2,200.40	2,199.60	7.68	7.68	89.62	0.20	30.00	30.00	14.64	15.36	1.953	Minor Risk			
2,300.00	2,300.00	2,300.40	2,299.60	8.04	8.04	89.62	0.20	30.00	30.00	13.93	16.07	1.866	Minor Risk			
2,400.00	2,400.00	2,399.60	2,399.60	8.39	8.39	89.62	0.20	30.00	30.00	13.21	16.79	1.787	Minor Risk, CC			
2,500.00	2,499.99	2,499.24	2,499.23	8.73	8.73	-69.58	-0.69	30.61	30.22	12.75	17.47	1.730	Minor Risk, ES			
2,600.00	2,599.96	2,600.99	2,598.95	9.06	9.07	-68.98	-3.23	32.34	31.10	12.98	18.12	1.716	Minor Risk			
2,700.00	2,699.93	2,701.00	2,698.88	9.39	9.40	-67.85	-6.10	34.31	32.21	13.43	18.78	1.715	Minor Risk			
2,800.00	2,799.91	2,801.01	2,798.81	9.72	9.73	-66.79	-8.98	36.27	33.33	13.89	19.44	1.715	Minor Risk			
2,900.00	2,899.88	2,901.02	2,898.75	10.05	10.06	-65.81	-11.86	38.24	34.46	14.36	20.10	1.714	Minor Risk			
3,000.00	2,999.85	3,001.02	2,998.68	10.38	10.40	-64.88	-14.73	40.20	35.60	14.83	20.77	1.714	Minor Risk			
3,100.00	3,099.82	3,101.03	3,098.61	10.72	10.74	-64.02	-17.61	42.17	36.76	15.31	21.44	1.714	Minor Risk, SF			
3,200.00	3,199.79	3,201.04	3,198.54	11.05	11.08	-63.20	-20.49	44.14	37.91	15.80	22.12	1.714	Minor Risk			
3,300.00	3,299.76	3,301.05	3,298.47	11.39	11.42	-62.44	-23.36	46.10	39.08	16.28	22.80	1.714	Minor Risk			
3,400.00	3,399.73	3,401.06	3,398.40	11.73	11.76	-61.72	-26.24	48.07	40.25	16.77	23.48	1.714	Minor Risk			
3,500.00	3,499.70	3,501.06	3,498.33	12.08	12.10	-61.04	-29.11	50.03	41.43	17.27	24.16	1.715	Minor Risk			
3,600.00	3,599.68	3,601.07	3,598.26	12.42	12.45	-60.39	-31.99	52.00	42.61	17.77	24.85	1.715	Minor Risk			
3,700.00	3,699.65	3,701.08	3,698.20	12.76	12.80	-59.79	-34.87	53.96	43.80	18.27	25.54	1.715	Minor Risk			
3,800.00	3,799.62	3,801.09	3,798.13	13.11	13.14	-59.21	-37.74	55.93	45.00	18.77	26.23	1.716	Minor Risk			
3,900.00	3,899.59	3,901.10	3,898.06	13.45	13.49	-58.67	-40.62	57.89	46.19	19.28	26.92	1.716	Minor Risk			
4,000.00	3,999.56	4,001.10	3,997.99	13.80	13.84	-58.15	-43.50	59.86	47.40	19.79	27.61	1.717	Minor Risk			
4,100.00	4,099.53	4,101.11	4,097.92	14.15	14.19	-57.66	-46.37	61.83	48.60	20.30	28.30	1.717	Minor Risk			
4,200.00	4,199.50	4,201.12	4,197.85	14.49	14.54	-57.19	-49.25	63.79	49.81	20.81	29.00	1.718	Minor Risk			
4,300.00	4,299.47	4,301.13	4,297.78	14.84	14.89	-56.74	-52.13	65.76	51.02	21.32	29.70	1.718	Minor Risk			
4,400.00	4,399.44	4,401.14	4,397.71	15.19	15.25	-56.32	-55.00	67.72	52.24	21.84	30.40	1.719	Minor Risk			
4,500.00	4,499.42	4,501.15	4,497.65	15.54	15.60	-55.91	-57.88	69.69	53.45	22.36	31.09	1.719	Minor Risk			
4,600.00	4,599.39	4,601.15	4,597.58	15.89	15.95	-55.52	-60.76	71.65	54.67	22.88	31.79	1.720	Minor Risk			
4,700.00	4,699.36	4,698.84	4,697.51	16.24	16.30	-55.15	-63.63	73.62	55.90	23.41	32.49	1.721	Minor Risk			
4,800.00	4,799.33	4,801.17	4,797.44	16.59	16.66	-54.80	-66.51	75.58	57.12	23.92	33.20	1.721	Minor Risk			
4,900.00	4,899.30	4,901.18	4,897.37	16.94	17.01	-54.46	-69.38	77.55	58.35	24.45	33.90	1.721	Minor Risk			
5,000.00	4,999.27	5,001.19	4,997.30	17.30	17.37	-54.13	-72.26	79.51	59.58	24.97	34.60	1.722	Minor Risk			
5,100.00	5,099.24	5,101.19	5,097.23	17.65	17.72	-53.82	-75.14	81.48	60.81	25.50	35.31	1.722	Minor Risk			

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

Anticollision Report

Company:	WCDSC Permian NM	Local Co-ordinate Reference:	Well Flagler 8 Fed 27H
Project:	Lea County (NAD83 New Mexico East)	TVD Reference:	RKB @ 3463.20ft
Reference Site:	Sec 08-T25S-R33E	MD Reference:	RKB @ 3463.20ft
Site Error:	0.00 ft	North Reference:	Grid
Reference Well:	Flagler 8 Fed 27H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 ft	Output errors are at	2.00 sigma
Reference Wellbore	Wellbore #1	Database:	EDM r5000.141_Prod US
Reference Design:	Permit Plan 1	Offset TVD Reference:	Offset Datum

Offset Design	Sec 08-T25S-R33E - Flagler 8 Fed 21H - Wellbore #1 - Permit Plan 1	Offset Site Error:	0.00 ft
Survey Program:	0-MWD+IGRF	Offset Well Error:	0.50 ft

Reference		Offset		Semi Major Axis			Offset Wellbore Centre		Distance		Minimum Separation	Separation Factor	Warning
Measured Depth (ft)	Vertical Depth (ft)	Measured Depth (ft)	Vertical Depth (ft)	Reference (ft)	Offset (ft)	Highside Toolface (°)	+N/S (ft)	+E/W (ft)	Between Centres (ft)	Between Ellipses (ft)	(ft)		
5,200.00	5,199.21	5,201.20	5,197.16	18.00	18.08	-53.52	-78.01	83.45	62.04	26.03	36.01	1.723	Minor Risk
5,300.00	5,299.19	5,301.21	5,297.09	18.36	18.44	-53.23	-80.89	85.41	63.28	26.58	36.72	1.723	Minor Risk
5,400.00	5,399.16	5,401.22	5,397.03	18.71	18.79	-52.95	-83.77	87.38	64.51	27.09	37.43	1.724	Minor Risk
5,500.00	5,499.13	5,501.23	5,496.96	19.06	19.15	-52.68	-86.64	89.34	65.75	27.62	38.13	1.724	Minor Risk
5,600.00	5,599.10	5,601.23	5,596.89	19.42	19.51	-52.42	-89.52	91.31	66.99	28.15	38.84	1.725	Minor Risk
5,700.00	5,699.07	5,701.24	5,696.82	19.77	19.87	-52.18	-92.40	93.27	68.23	28.68	39.55	1.725	Minor Risk
5,800.00	5,799.04	5,801.25	5,796.75	20.13	20.22	-51.94	-95.27	95.24	69.47	29.21	40.26	1.726	Minor Risk
5,900.00	5,899.01	5,901.26	5,896.68	20.48	20.58	-51.71	-98.15	97.20	70.71	29.75	40.97	1.726	Minor Risk
6,000.00	5,998.98	6,001.27	5,996.61	20.84	20.94	-51.48	-101.02	99.17	71.95	30.28	41.67	1.727	Minor Risk
6,100.00	6,098.95	6,101.28	6,096.54	21.19	21.30	-51.27	-103.90	101.14	73.20	30.81	42.38	1.727	Minor Risk
6,200.00	6,198.93	6,201.28	6,196.48	21.55	21.66	-51.06	-106.78	103.10	74.44	31.35	43.09	1.727	Minor Risk
6,300.00	6,298.90	6,301.29	6,296.41	21.90	22.02	-50.86	-109.65	105.07	75.69	31.89	43.80	1.728	Minor Risk
6,400.00	6,398.87	6,401.30	6,396.34	22.26	22.38	-50.66	-112.53	107.03	76.94	32.42	44.52	1.728	Minor Risk
6,500.00	6,498.84	6,501.31	6,496.27	22.62	22.73	-50.48	-115.41	109.00	78.19	32.96	45.23	1.729	Minor Risk
6,600.00	6,598.81	6,601.32	6,596.20	22.97	23.09	-50.29	-118.28	110.96	79.44	33.50	45.94	1.729	Minor Risk
6,700.00	6,698.78	6,701.32	6,696.13	23.33	23.45	-50.12	-121.16	112.93	80.68	34.04	46.65	1.730	Minor Risk
6,800.00	6,798.75	6,801.33	6,796.06	23.69	23.81	-49.94	-124.04	114.89	81.94	34.57	47.36	1.730	Minor Risk
6,900.00	6,898.72	6,901.34	6,895.99	24.04	24.17	-49.78	-126.91	116.86	83.19	35.11	48.07	1.730	Minor Risk
7,000.00	6,998.70	7,001.35	6,995.92	24.40	24.53	-49.62	-129.79	118.83	84.44	35.65	48.79	1.731	Minor Risk
7,100.00	7,098.67	7,101.36	7,095.86	24.76	24.89	-49.46	-132.66	120.79	85.69	36.19	49.50	1.731	Minor Risk
7,200.00	7,198.64	7,201.36	7,195.79	25.11	25.25	-49.31	-135.54	122.76	86.94	36.73	50.21	1.732	Minor Risk
7,300.00	7,298.61	7,301.37	7,295.72	25.47	25.62	-49.16	-138.42	124.72	88.20	37.27	50.92	1.732	Minor Risk
7,400.00	7,398.58	7,401.38	7,395.65	25.83	25.98	-49.02	-141.29	126.69	89.45	37.81	51.64	1.732	Minor Risk
7,500.00	7,498.55	7,501.39	7,495.58	26.19	26.34	-48.88	-144.17	128.65	90.71	38.36	52.35	1.733	Minor Risk
7,600.00	7,598.52	7,601.40	7,595.51	26.55	26.70	-48.74	-147.05	130.62	91.96	38.90	53.07	1.733	Minor Risk
7,700.00	7,698.49	7,701.41	7,695.44	26.90	27.06	-48.61	-149.92	132.58	93.22	39.44	53.78	1.733	Minor Risk
7,800.00	7,798.46	7,801.41	7,795.37	27.26	27.42	-48.48	-152.80	134.55	94.48	39.98	54.49	1.734	Minor Risk
7,900.00	7,898.44	7,901.42	7,895.31	27.62	27.78	-48.35	-155.68	136.51	95.73	40.52	55.21	1.734	Minor Risk
8,000.00	7,998.41	8,001.43	7,995.24	27.98	28.14	-48.23	-158.55	138.48	96.99	41.07	55.92	1.734	Minor Risk
8,100.00	8,098.38	8,101.44	8,095.17	28.34	28.50	-48.11	-161.43	140.45	98.25	41.61	56.64	1.735	Minor Risk
8,200.00	8,198.35	8,201.45	8,195.10	28.69	28.87	-48.00	-164.30	142.41	99.51	42.15	57.35	1.735	Minor Risk
8,300.00	8,298.34	8,301.47	8,295.01	29.04	29.23	-47.46	-167.18	144.38	101.48	43.42	58.06	1.748	Minor Risk
8,400.00	8,398.34	8,401.53	8,394.89	29.38	29.59	112.58	-170.06	146.34	104.38	45.63	58.75	1.777	Minor Risk
8,500.00	8,498.34	8,501.59	8,494.77	29.72	29.95	113.59	-172.93	148.31	107.32	47.88	59.44	1.805	Minor Risk
8,600.00	8,598.34	8,598.35	8,594.65	30.06	30.30	114.55	-175.81	150.27	110.29	50.17	60.12	1.834	Minor Risk
8,700.00	8,698.34	8,699.01	8,695.25	30.40	30.67	115.44	-178.61	152.19	113.20	52.38	60.82	1.861	Minor Risk
8,800.00	8,798.34	8,801.65	8,797.88	30.74	31.02	115.80	-179.80	153.00	114.41	52.90	61.51	1.860	Minor Risk
8,900.00	8,898.34	8,901.71	8,897.94	31.08	31.36	115.80	-179.80	153.00	114.41	52.22	62.19	1.840	Minor Risk
9,000.00	8,998.34	9,001.71	8,997.94	31.42	31.70	115.80	-179.80	153.00	114.41	51.54	62.87	1.820	Minor Risk
9,100.00	9,098.34	9,101.71	9,097.94	31.76	32.04	115.80	-179.80	153.00	114.41	50.85	63.55	1.800	Minor Risk
9,200.00	9,198.34	9,201.71	9,197.94	32.11	32.37	115.80	-179.80	153.00	114.41	50.17	64.24	1.781	Minor Risk
9,300.00	9,298.15	9,301.52	9,297.75	32.44	32.71	117.61	-179.80	153.00	116.41	51.50	64.90	1.793	Minor Risk
9,400.00	9,395.80	9,400.83	9,395.40	32.76	33.05	124.93	-179.80	153.00	127.55	62.02	65.52	1.947	Minor Risk
9,500.00	9,488.31	9,508.32	9,487.91	33.05	33.42	134.29	-179.80	153.00	152.80	86.64	66.16	2.310	Minor Risk
9,600.00	9,572.89	9,576.26	9,572.49	33.33	33.65	142.11	-179.80	153.00	195.34	128.70	66.65	2.931	Alert
9,700.00	9,646.96	9,650.33	9,646.56	33.62	33.90	146.99	-179.80	153.00	254.74	187.61	67.12	3.795	Alert
9,800.00	9,708.27	9,711.64	9,707.87	33.93	34.11	148.68	-179.80	153.00	328.40	260.89	67.51	4.865	Alert
9,900.00	9,754.96	9,758.33	9,754.56	34.29	34.27	146.49	-179.80	153.00	413.16	345.37	67.79	6.095	
10,000.00	9,785.60	9,788.97	9,785.20	34.69	34.37	136.97	-179.80	153.00	505.77	437.81	67.96	7.442	
10,100.00	9,799.28	9,802.65	9,798.88	35.14	34.42	106.11	-179.80	153.00	602.97	534.93	68.04	8.862	
10,200.00	9,800.00	10,876.90	10,425.00	35.65	37.91	170.62	514.25	153.01	633.87	593.49	40.38	15.697	
10,300.00	9,800.00	10,976.90	10,425.00	36.26	38.49	170.62	614.25	153.02	633.88	593.09	40.79	15.541	

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

Anticollision Report

Company:	WCDSC Permian NM	Local Co-ordinate Reference:	Well Flagler 8 Fed 27H
Project:	Lea County (NAD83 New Mexico East)	TVD Reference:	RKB @ 3463.20ft
Reference Site:	Sec 08-T25S-R33E	MD Reference:	RKB @ 3463.20ft
Site Error:	0.00 ft	North Reference:	Grid
Reference Well:	Flagler 8 Fed 27H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 ft	Output errors are at	2.00 sigma
Reference Wellbore	Wellbore #1	Database:	EDM r5000.141_Prod US
Reference Design:	Permit Plan 1	Offset TVD Reference:	Offset Datum

Offset Design Sec 08-T25S-R33E - Flagler 8 Fed 21H - Wellbore #1 - Permit Plan 1													Offset Site Error:	0.00 ft
Survey Program: 0-MWD+IGRF													Offset Well Error:	0.50 ft
Reference		Offset		Semi Major Axis			Distance						Warning	
Measured Depth (ft)	Vertical Depth (ft)	Measured Depth (ft)	Vertical Depth (ft)	Reference (ft)	Offset (ft)	Highside Toolface (°)	Offset Wellbore Centre +N/-S (ft)	+E/-W (ft)	Between Centres (ft)	Between Ellipses (ft)	Minimum Separation (ft)	Separation Factor		
10,400.00	9,800.00	11,076.90	10,425.00	36.95	39.15	170.62	714.25	153.02	633.88	592.63	41.26	15.365		
10,500.00	9,800.00	11,176.90	10,425.00	37.73	39.89	170.61	814.25	153.02	633.89	592.10	41.79	15.170		
10,600.00	9,800.00	11,276.90	10,425.00	38.59	40.72	170.61	914.25	153.02	633.90	591.52	42.38	14.959		
10,700.00	9,800.00	11,376.90	10,425.00	39.52	41.61	170.60	1,014.25	153.03	633.90	590.88	43.02	14.734		
10,800.00	9,800.00	11,476.90	10,425.00	40.52	42.57	170.60	1,114.25	153.03	633.91	590.18	43.73	14.498		
10,900.00	9,800.00	11,576.90	10,425.00	41.59	43.59	170.60	1,214.25	153.03	633.92	589.44	44.48	14.252		
11,000.00	9,800.00	11,676.90	10,425.00	42.72	44.67	170.59	1,314.25	153.03	633.92	588.64	45.28	14.000		
11,100.00	9,800.00	11,776.90	10,425.00	43.90	45.81	170.59	1,414.25	153.03	633.93	587.80	46.13	13.742		
11,200.00	9,800.00	11,876.90	10,425.00	45.13	47.00	170.59	1,514.25	153.04	633.94	586.91	47.02	13.481		
11,300.00	9,800.00	11,976.90	10,425.00	46.41	48.23	170.58	1,614.25	153.04	633.94	585.99	47.96	13.219		
11,400.00	9,800.00	12,076.90	10,425.00	47.73	49.51	170.58	1,714.25	153.04	633.95	585.02	48.93	12.955		
11,500.00	9,800.00	12,176.90	10,425.00	49.09	50.83	170.57	1,814.25	153.04	633.96	584.01	49.94	12.693		
11,600.00	9,800.00	12,276.90	10,425.00	50.48	52.18	170.57	1,914.25	153.04	633.96	582.97	50.99	12.433		
11,700.00	9,800.00	12,376.90	10,425.00	51.91	53.57	170.57	2,014.25	153.05	633.97	581.90	52.07	12.175		
11,800.00	9,800.00	12,476.90	10,425.00	53.37	54.99	170.56	2,114.25	153.05	633.98	580.80	53.18	11.921		
11,900.00	9,800.00	12,576.90	10,425.00	54.86	56.45	170.56	2,214.25	153.05	633.99	579.67	54.32	11.672		
12,000.00	9,800.00	12,676.90	10,425.00	56.38	57.92	170.56	2,314.25	153.05	633.99	578.51	55.48	11.426		
12,100.00	9,800.00	12,776.90	10,425.00	57.91	59.43	170.55	2,414.25	153.05	634.00	577.32	56.68	11.186		
12,200.00	9,800.00	12,876.90	10,425.00	59.47	60.95	170.55	2,514.25	153.06	634.01	576.11	57.89	10.952		
12,300.00	9,800.00	12,976.90	10,425.00	61.06	62.50	170.55	2,614.25	153.06	634.01	574.88	59.13	10.723		
12,400.00	9,800.00	13,076.90	10,425.00	62.65	64.07	170.54	2,714.25	153.06	634.02	573.63	60.39	10.499		
12,500.00	9,800.00	13,176.90	10,425.00	64.27	65.65	170.54	2,814.25	153.06	634.03	572.36	61.67	10.282		
12,600.00	9,800.00	13,276.90	10,425.00	65.90	67.26	170.53	2,914.25	153.07	634.03	571.07	62.96	10.070		
12,700.00	9,800.00	13,376.90	10,425.00	67.55	68.88	170.53	3,014.25	153.07	634.04	569.76	64.28	9.864		
12,800.00	9,800.00	13,476.90	10,425.00	69.21	70.51	170.53	3,114.25	153.07	634.05	568.44	65.61	9.664		
12,900.00	9,800.00	13,576.90	10,425.00	70.89	72.16	170.52	3,214.25	153.07	634.05	567.10	66.96	9.470		
13,000.00	9,800.00	13,676.90	10,425.00	72.58	73.82	170.52	3,314.25	153.07	634.06	565.74	68.32	9.281		
13,100.00	9,800.00	13,776.90	10,425.00	74.27	75.49	170.52	3,414.25	153.08	634.07	564.38	69.69	9.098		
13,200.00	9,800.00	13,876.90	10,425.00	75.98	77.18	170.51	3,514.25	153.08	634.08	562.99	71.08	8.921		
13,300.00	9,800.00	13,976.90	10,425.00	77.70	78.87	170.51	3,614.25	153.08	634.08	561.60	72.48	8.748		
13,400.00	9,800.00	14,076.90	10,425.00	79.43	80.58	170.50	3,714.25	153.08	634.09	560.20	73.89	8.581		
13,500.00	9,800.00	14,176.90	10,425.00	81.16	82.30	170.50	3,814.25	153.08	634.10	558.78	75.31	8.419		
13,600.00	9,800.00	14,276.90	10,425.00	82.91	84.02	170.50	3,914.25	153.09	634.10	557.36	76.75	8.262		
13,700.00	9,800.00	14,376.90	10,425.00	84.66	85.75	170.49	4,014.25	153.09	634.11	555.92	78.19	8.110		
13,800.00	9,800.00	14,476.90	10,425.00	86.42	87.49	170.49	4,114.25	153.09	634.12	554.47	79.64	7.962		
13,900.00	9,800.00	14,576.90	10,425.00	88.18	89.24	170.49	4,214.25	153.09	634.12	553.02	81.10	7.819		
14,000.00	9,800.00	14,676.90	10,425.00	89.95	90.99	170.48	4,314.25	153.09	634.13	551.56	82.57	7.680		
14,100.00	9,800.00	14,776.90	10,425.00	91.73	92.75	170.48	4,414.25	153.10	634.14	550.09	84.05	7.545		
14,200.00	9,800.00	14,876.90	10,425.00	93.51	94.52	170.47	4,514.25	153.10	634.14	548.61	85.53	7.414		
14,256.44	9,800.00	14,933.34	10,425.00	94.52	95.52	170.47	4,570.69	153.10	634.15	547.78	86.37	7.342		

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

Anticollision Report

Company:	WCDCS Permian NM	Local Co-ordinate Reference:	Well Flagler 8 Fed 27H
Project:	Lea County (NAD83 New Mexico East)	TVD Reference:	RKB @ 3463.20ft
Reference Site:	Sec 08-T25S-R33E	MD Reference:	RKB @ 3463.20ft
Site Error:	0.00 ft	North Reference:	Grid
Reference Well:	Flagler 8 Fed 27H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 ft	Output errors are at	2.00 sigma
Reference Wellbore	Wellbore #1	Database:	EDM r5000.141_Prod US
Reference Design:	Permit Plan 1	Offset TVD Reference:	Offset Datum

Offset Design													Offset Site Error:	0.00 ft		
Survey Program: 0-MWD+IGRF													Offset Well Error:	0.50 ft		
Reference													Distance		Warning	
Measured Depth (ft)	Vertical Depth (ft)	Measured Depth (ft)	Vertical Depth (ft)	Reference (ft)	Offset (ft)	Highside Toolface (°)	Offset Wellbore Centre +N-S (ft)	+E/W (ft)	Between Centres (ft)	Between Ellipses (ft)	Minimum Separation (ft)	Separation Factor				
0.00	0.00	0.60	0.60	0.50	0.50	-90.37	-0.58	-89.98	89.98							
100.00	100.00	100.60	100.60	0.52	0.52	-90.37	-0.58	-89.98	89.98	88.95	1.04	86.849				
200.00	200.00	200.60	200.60	0.70	0.70	-90.37	-0.58	-89.98	89.98	88.58	1.41	64.011				
300.00	300.00	300.60	300.60	0.99	0.99	-90.37	-0.58	-89.98	89.98	88.01	1.98	45.525				
400.00	400.00	400.60	400.60	1.31	1.31	-90.37	-0.58	-89.98	89.98	87.36	2.62	34.342				
500.00	500.00	500.60	500.60	1.65	1.65	-90.37	-0.58	-89.98	89.98	86.69	3.29	27.315				
600.00	600.00	600.60	600.60	1.99	1.99	-90.37	-0.58	-89.98	89.98	86.00	3.98	22.590				
700.00	700.00	700.60	700.60	2.34	2.34	-90.37	-0.58	-89.98	89.98	85.30	4.68	19.224				
800.00	800.00	800.60	800.60	2.69	2.69	-90.37	-0.58	-89.98	89.98	84.60	5.38	16.715				
900.00	900.00	900.60	900.60	3.04	3.05	-90.37	-0.58	-89.98	89.98	83.89	6.09	14.777				
1,000.00	1,000.00	1,000.60	1,000.60	3.40	3.40	-90.37	-0.58	-89.98	89.98	83.18	6.80	13.238				
1,100.00	1,100.00	1,100.60	1,100.60	3.75	3.75	-90.37	-0.58	-89.98	89.98	82.47	7.51	11.986				
1,200.00	1,200.00	1,200.60	1,200.60	4.11	4.11	-90.37	-0.58	-89.98	89.98	81.76	8.22	10.949				
1,300.00	1,300.00	1,300.60	1,300.60	4.46	4.47	-90.37	-0.58	-89.98	89.98	81.05	8.93	10.076				
1,400.00	1,400.00	1,400.60	1,400.60	4.82	4.82	-90.37	-0.58	-89.98	89.98	80.34	9.64	9.331				
1,500.00	1,500.00	1,500.60	1,500.60	5.18	5.18	-90.37	-0.58	-89.98	89.98	79.63	10.36	8.688				
1,600.00	1,600.00	1,600.60	1,600.60	5.53	5.54	-90.37	-0.58	-89.98	89.98	78.91	11.07	8.128				
1,700.00	1,700.00	1,700.60	1,700.60	5.89	5.89	-90.37	-0.58	-89.98	89.98	78.20	11.78	7.636				
1,800.00	1,800.00	1,800.60	1,800.60	6.25	6.25	-90.37	-0.58	-89.98	89.98	77.48	12.50	7.199				
1,900.00	1,900.00	1,900.60	1,900.60	6.61	6.61	-90.37	-0.58	-89.98	89.98	76.77	13.21	6.810				
2,000.00	2,000.00	2,000.60	2,000.60	6.96	6.97	-90.37	-0.58	-89.98	89.98	76.05	13.93	6.460				
2,100.00	2,100.00	2,100.60	2,100.60	7.32	7.32	-90.37	-0.58	-89.98	89.98	75.34	14.64	6.145				
2,200.00	2,200.00	2,200.60	2,200.60	7.68	7.68	-90.37	-0.58	-89.98	89.98	74.62	15.36	5.858				
2,300.00	2,300.00	2,300.60	2,300.60	8.04	8.04	-90.37	-0.58	-89.98	89.98	73.91	16.07	5.598				
2,400.00	2,400.00	2,400.60	2,400.60	8.39	8.40	-90.37	-0.58	-89.98	89.98	73.19	16.79	5.359 CC				
2,500.00	2,499.99	2,500.59	2,500.59	8.73	8.75	111.31	-0.58	-89.98	90.37	72.88	17.49	5.168 ES				
2,600.00	2,599.96	2,600.56	2,600.56	9.06	9.11	112.71	-0.58	-89.98	91.27	73.10	18.17	5.023				
2,700.00	2,699.93	2,700.53	2,700.53	9.39	9.47	114.08	-0.58	-89.98	92.22	73.37	18.86	4.891 Alert				
2,800.00	2,799.91	2,800.51	2,800.51	9.72	9.83	115.43	-0.58	-89.98	93.23	73.69	19.54	4.771 Alert				
2,900.00	2,899.88	2,900.48	2,900.48	10.05	10.19	116.75	-0.58	-89.98	94.28	74.05	20.23	4.660 Alert				
3,000.00	2,999.85	3,000.45	3,000.45	10.38	10.54	118.04	-0.58	-89.98	95.39	74.47	20.92	4.559 Alert				
3,100.00	3,099.82	3,100.42	3,100.42	10.72	10.90	119.29	-0.58	-89.98	96.54	74.92	21.62	4.466 Alert				
3,200.00	3,199.79	3,200.39	3,200.39	11.05	11.26	120.52	-0.58	-89.98	97.74	75.43	22.31	4.381 Alert				
3,300.00	3,299.76	3,300.36	3,300.36	11.39	11.62	121.72	-0.58	-89.98	98.98	75.97	23.01	4.302 Alert				
3,400.00	3,399.73	3,400.33	3,400.33	11.73	11.98	122.88	-0.58	-89.98	100.26	76.56	23.71	4.229 Alert				
3,500.00	3,499.70	3,500.30	3,500.30	12.08	12.33	124.02	-0.58	-89.98	101.59	77.18	24.40	4.163 Alert				
3,600.00	3,599.68	3,600.28	3,600.28	12.42	12.69	125.13	-0.58	-89.98	102.95	77.85	25.11	4.101 Alert				
3,700.00	3,699.65	3,700.25	3,700.25	12.76	13.05	126.21	-0.58	-89.98	104.35	78.55	25.81	4.044 Alert				
3,800.00	3,799.62	3,800.22	3,800.22	13.11	13.41	127.26	-0.58	-89.98	105.79	79.28	26.51	3.991 Alert				
3,900.00	3,899.59	3,900.19	3,900.19	13.45	13.77	128.28	-0.58	-89.98	107.26	80.05	27.21	3.942 Alert				
4,000.00	3,999.56	4,000.16	4,000.16	13.80	14.12	129.27	-0.58	-89.98	108.76	80.85	27.91	3.896 Alert				
4,100.00	4,099.53	4,100.13	4,100.13	14.15	14.48	130.24	-0.58	-89.98	110.30	81.68	28.62	3.854 Alert				
4,200.00	4,199.50	4,200.10	4,200.10	14.49	14.84	131.17	-0.58	-89.98	111.86	82.54	29.32	3.815 Alert				
4,300.00	4,299.47	4,300.07	4,300.07	14.84	15.20	132.09	-0.58	-89.98	113.46	83.43	30.03	3.778 Alert				
4,400.00	4,399.44	4,400.04	4,400.04	15.19	15.56	132.97	-0.58	-89.98	115.08	84.35	30.74	3.744 Alert				
4,500.00	4,499.42	4,500.02	4,500.02	15.54	15.92	133.84	-0.58	-89.98	116.73	85.29	31.44	3.713 Alert				
4,600.00	4,599.39	4,600.01	4,599.99	15.89	16.27	134.67	-0.58	-89.98	118.41	86.26	32.15	3.683 Alert				
4,700.00	4,699.36	4,700.04	4,699.96	16.24	16.63	135.49	-0.58	-89.98	120.11	87.25	32.86	3.656 Alert				
4,800.00	4,799.33	4,800.07	4,799.93	16.59	16.99	136.28	-0.58	-89.98	121.83	88.27	33.57	3.630 Alert				
4,900.00	4,899.30	4,900.10	4,899.90	16.94	17.35	137.05	-0.58	-89.98	123.58	89.31	34.27	3.606 Alert				
5,000.00	4,999.27	5,000.13	4,999.87	17.30	17.71	137.80	-0.58	-89.98	125.35	90.37	34.98	3.583 Alert				
5,100.00	5,099.24	5,100.16	5,099.84	17.65	18.07	138.52	-0.58	-89.98	127.14	91.45	35.69	3.562 Alert				

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

Anticollision Report

Company: WCDSC Permian NM
Project: Lea County (NAD83 New Mexico East)
Reference Site: Sec 08-T25S-R33E
Site Error: 0.00 ft
Reference Well: Flagler 8 Fed 27H
Well Error: 0.50 ft
Reference Wellbore: Wellbore #1
Reference Design: Permit Plan 1

Local Co-ordinate Reference: Well Flagler 8 Fed 27H
TVD Reference: RKB @ 3463.20ft
MD Reference: RKB @ 3463.20ft
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Output errors are at: 2.00 sigma
Database: EDM r5000.141_Prod US
Offset TVD Reference: Offset Datum

Offset Design													Offset Site Error:	0.00 ft		
Survey Program: 0-MWD+IGRF													Offset Well Error:	0.50 ft		
Reference													Distance		Warning	
Offset				Semi Major Axis			Offset Wellbore Centre		Between Centres	Between Ellipses	Minimum Separation	Separation Factor				
Measured Depth (ft)	Vertical Depth (ft)	Measured Depth (ft)	Vertical Depth (ft)	Reference (ft)	Offset (ft)	Highside Toolface (°)	+N/-S (ft)	+E/-W (ft)	(ft)	(ft)	(ft)					
5,200.00	5,199.21	5,199.81	5,199.81	18.00	18.42	139.23	-0.58	-89.98	128.95	92.55	36.40	3.542	Alert			
5,300.00	5,299.19	5,298.33	5,298.32	18.36	18.76	139.41	-1.32	-91.00	131.33	94.24	37.09	3.541	Alert			
5,400.00	5,399.16	5,396.75	5,396.66	18.71	19.09	138.60	-3.56	-94.08	134.83	97.08	37.76	3.571	Alert			
5,500.00	5,499.13	5,494.94	5,494.65	19.06	19.41	136.92	-7.27	-99.19	139.56	101.14	38.42	3.632	Alert			
5,600.00	5,599.10	5,592.77	5,592.08	19.42	19.74	134.49	-12.44	-106.30	145.69	106.62	39.08	3.728	Alert			
5,700.00	5,699.07	5,708.81	5,689.88	19.77	20.13	131.55	-18.93	-115.24	153.30	113.50	39.80	3.852	Alert			
5,800.00	5,799.04	5,809.43	5,788.59	20.13	20.47	128.78	-25.67	-124.52	161.46	120.98	40.48	3.989	Alert			
5,900.00	5,899.01	5,889.94	5,887.30	20.48	20.75	126.27	-32.41	-133.80	169.97	128.87	41.10	4.136	Alert			
6,000.00	5,998.98	5,989.32	5,986.01	20.84	21.09	124.01	-39.15	-143.08	178.77	136.99	41.78	4.279	Alert			
6,100.00	6,098.95	6,088.69	6,084.72	21.19	21.44	121.96	-45.89	-152.36	187.82	145.35	42.47	4.423	Alert			
6,200.00	6,198.93	6,188.07	6,183.43	21.55	21.79	120.10	-52.63	-161.64	197.09	153.94	43.15	4.567	Alert			
6,300.00	6,298.90	6,287.44	6,282.14	21.90	22.14	118.41	-59.37	-170.92	206.55	162.70	43.84	4.711	Alert			
6,400.00	6,398.87	6,386.82	6,380.85	22.26	22.49	116.87	-66.11	-180.20	216.17	171.63	44.53	4.854	Alert			
6,500.00	6,498.84	6,486.19	6,479.56	22.62	22.85	115.46	-72.85	-189.48	225.93	180.70	45.23	4.995	Alert			
6,600.00	6,598.81	6,585.57	6,578.27	22.97	23.20	114.17	-79.59	-198.76	235.82	189.89	45.92	5.135				
6,700.00	6,698.78	6,684.94	6,676.99	23.33	23.56	112.98	-86.33	-208.04	245.81	199.19	46.62	5.273				
6,800.00	6,798.75	6,784.31	6,775.70	23.69	23.92	111.88	-93.07	-217.32	255.90	208.59	47.31	5.409				
6,900.00	6,898.72	6,883.69	6,874.41	24.04	24.29	110.87	-99.81	-226.60	266.08	218.07	48.01	5.542				
7,000.00	6,998.70	6,983.06	6,973.12	24.40	24.65	109.93	-106.54	-235.88	276.34	227.63	48.71	5.673				
7,100.00	7,098.67	7,082.44	7,071.83	24.76	25.02	109.06	-113.28	-245.16	286.66	237.25	49.41	5.802				
7,200.00	7,198.64	7,181.81	7,170.54	25.11	25.39	108.25	-120.02	-254.44	297.05	246.93	50.11	5.928				
7,300.00	7,298.61	7,281.19	7,269.25	25.47	25.75	107.50	-126.76	-263.72	307.49	256.67	50.81	6.051				
7,400.00	7,398.58	7,380.56	7,367.96	25.83	26.13	106.79	-133.50	-273.00	317.97	266.46	51.52	6.172				
7,500.00	7,498.55	7,479.94	7,466.67	26.19	26.50	106.13	-140.24	-282.28	328.51	276.29	52.22	6.291				
7,600.00	7,598.52	7,579.31	7,565.38	26.55	26.87	105.51	-146.98	-291.56	339.08	286.16	52.92	6.407				
7,700.00	7,698.49	7,678.69	7,664.09	26.90	27.25	104.93	-153.72	-300.84	349.69	296.06	53.63	6.520				
7,800.00	7,798.46	7,778.08	7,762.80	27.26	27.62	104.38	-160.46	-310.12	360.33	306.00	54.34	6.632				
7,900.00	7,898.44	7,877.66	7,861.73	27.62	28.00	103.87	-167.22	-319.42	371.01	315.96	55.04	6.740				
8,000.00	7,998.41	7,986.59	7,970.11	27.98	28.41	103.45	-173.65	-328.28	380.41	324.54	55.87	6.809				
8,100.00	8,098.38	8,086.03	8,079.26	28.34	28.81	103.27	-178.29	-334.66	387.31	330.64	56.66	6.835				
8,200.00	8,198.35	8,205.80	8,188.92	28.69	29.20	103.32	-181.09	-338.52	391.68	334.25	57.43	6.820				
8,300.00	8,298.34	8,315.72	8,298.83	29.04	29.58	103.43	-182.04	-339.83	393.29	335.12	58.17	6.762				
8,400.00	8,398.34	8,415.83	8,398.94	29.38	29.93	-97.60	-182.04	-339.83	393.29	334.43	58.86	6.682				
8,500.00	8,498.34	8,515.83	8,498.94	29.72	30.28	-97.60	-182.04	-339.83	393.29	333.74	59.55	6.605				
8,600.00	8,598.34	8,615.83	8,598.94	30.06	30.62	-97.60	-182.04	-339.83	393.29	333.05	60.24	6.529				
8,700.00	8,698.34	8,715.83	8,698.94	30.40	30.97	-97.60	-182.04	-339.83	393.29	332.36	60.93	6.455				
8,800.00	8,798.34	8,815.83	8,798.94	30.74	31.32	-97.60	-182.04	-339.83	393.29	331.67	61.62	6.382				
8,900.00	8,898.34	8,915.83	8,898.94	31.08	31.67	-97.60	-182.04	-339.83	393.29	330.97	62.31	6.311				
9,000.00	8,998.34	9,015.83	8,998.94	31.42	32.02	-97.60	-182.04	-339.83	393.29	330.28	63.01	6.242				
9,100.00	9,098.34	9,123.87	9,106.39	31.76	32.38	-96.22	-172.46	-339.88	392.26	328.56	63.70	6.158				
9,200.00	9,198.34	9,225.19	9,203.87	32.11	32.67	-92.25	-145.32	-340.04	390.37	325.99	64.38	6.063				
9,238.18	9,236.51	9,261.27	9,237.22	32.24	32.77	-90.34	-131.55	-340.12	390.12	325.49	64.63	6.036				
9,300.00	9,298.15	9,316.64	9,286.53	32.44	32.91	-86.97	-106.42	-340.26	390.92	325.93	64.99	6.015				
9,400.00	9,395.80	9,402.84	9,357.86	32.76	33.09	-81.86	-58.17	-340.53	395.16	329.80	65.36	6.046				
9,500.00	9,488.31	9,485.13	9,418.47	33.05	33.22	-77.10	-2.62	-340.85	402.30	336.92	65.38	6.153				
9,600.00	9,572.89	9,564.35	9,468.74	33.33	33.32	-72.80	58.54	-341.20	411.35	346.30	65.05	6.323				
9,700.00	9,646.96	9,641.18	9,508.99	33.62	33.44	-69.06	123.91	-341.57	421.28	356.79	64.49	6.532				
9,800.00	9,708.27	9,716.16	9,539.49	33.93	33.69	-65.92	192.34	-341.96	431.14	367.27	63.87	6.750				
9,900.00	9,754.96	9,789.73	9,560.49	34.29	33.96	-63.41	262.80	-342.36	440.10	376.74	63.37	6.946				
10,000.00	9,785.60	9,862.27	9,572.20	34.69	34.26	-61.53	334.34	-342.76	447.53	384.37	63.16	7.086				
10,100.00	9,799.28	9,940.06	9,575.00	35.14	34.61	-60.26	412.03	-343.20	452.79	389.39	63.40	7.142				
10,200.00	9,800.00	10,040.05	9,575.00	35.65	35.13	-60.17	512.02	-343.77	453.60	389.31	64.29	7.056				

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

Anticollision Report

Company:	WCDSC Permian NM	Local Co-ordinate Reference:	Well Flagler 8 Fed 27H
Project:	Lea County (NAD83 New Mexico East)	TVD Reference:	RKB @ 3463.20ft
Reference Site:	Sec 08-T25S-R33E	MD Reference:	RKB @ 3463.20ft
Site Error:	0.00 ft	North Reference:	Grid
Reference Well:	Flagler 8 Fed 27H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 ft	Output errors are at	2.00 sigma
Reference Wellbore	Wellbore #1	Database:	EDM r5000.141_Prod US
Reference Design:	Permit Plan 1	Offset TVD Reference:	Offset Datum

Offset Design Sec 08-T25S-R33E - Flagler 8 Fed 33H - Wellbore #1 - Permit Plan 1													Offset Site Error:	0.00 ft
Survey Program: 0-MWD+IGRF													Offset Well Error:	0.50 ft
Reference		Offset		Semi Major Axis			Distance						Warning	
Measured Depth (ft)	Vertical Depth (ft)	Measured Depth (ft)	Vertical Depth (ft)	Reference (ft)	Offset (ft)	Highside Toolface (°)	Offset Wellbore Centre +N/-S (ft)	+E/-W (ft)	Between Centres (ft)	Between Ellipses (ft)	Minimum Separation (ft)	Separation Factor		
10,300.00	9,800.00	10,140.05	9,575.00	36.26	35.74	-60.21	612.02	-344.34	454.06	388.69	65.37	6.946		
10,400.00	9,800.00	10,240.04	9,575.00	36.95	36.44	-60.24	712.01	-344.91	454.52	387.90	66.62	6.823		
10,500.00	9,800.00	10,340.04	9,575.00	37.73	37.22	-60.27	812.01	-345.48	454.98	386.97	68.01	6.690		
10,600.00	9,800.00	10,440.04	9,575.00	38.59	38.08	-60.31	912.01	-346.04	455.44	385.89	69.55	6.549		
10,700.00	9,800.00	10,540.04	9,575.00	39.52	39.02	-60.34	1,012.00	-346.61	455.90	384.68	71.21	6.402		
10,800.00	9,800.00	10,640.04	9,575.00	40.52	40.02	-60.37	1,112.00	-347.18	456.36	383.35	73.01	6.251		
10,900.00	9,800.00	10,740.04	9,575.00	41.59	41.09	-60.41	1,212.00	-347.75	456.81	381.90	74.91	6.098		
11,000.00	9,800.00	10,840.04	9,575.00	42.72	42.22	-60.44	1,311.99	-348.32	457.27	380.34	76.93	5.944		
11,100.00	9,800.00	10,940.03	9,575.00	43.90	43.41	-60.47	1,411.99	-348.89	457.73	378.69	79.04	5.791		
11,200.00	9,800.00	11,040.03	9,575.00	45.13	44.64	-60.50	1,511.99	-349.45	458.19	376.94	81.25	5.639		
11,300.00	9,800.00	11,140.03	9,575.00	46.41	45.92	-60.54	1,611.99	-350.02	458.65	375.11	83.54	5.490		
11,400.00	9,800.00	11,240.03	9,575.00	47.73	47.25	-60.57	1,711.98	-350.59	459.11	373.21	85.91	5.344		
11,500.00	9,800.00	11,340.03	9,575.00	49.09	48.62	-60.60	1,811.98	-351.16	459.57	371.23	88.35	5.202		
11,600.00	9,800.00	11,440.03	9,575.00	50.48	50.02	-60.63	1,911.98	-351.73	460.03	369.18	90.85	5.063		
11,700.00	9,800.00	11,540.03	9,575.00	51.91	51.45	-60.67	2,011.97	-352.29	460.49	367.07	93.42	4.929 Alert		
11,800.00	9,800.00	11,640.03	9,575.00	53.37	52.92	-60.70	2,111.97	-352.86	460.95	364.91	96.05	4.799 Alert		
11,900.00	9,800.00	11,740.02	9,575.00	54.86	54.41	-60.73	2,211.97	-353.43	461.42	362.69	98.72	4.674 Alert		
12,000.00	9,800.00	11,840.02	9,575.00	56.38	55.93	-60.76	2,311.96	-354.00	461.88	360.43	101.45	4.553 Alert		
12,100.00	9,800.00	11,940.02	9,575.00	57.91	57.47	-60.79	2,411.96	-354.57	462.34	358.12	104.22	4.436 Alert		
12,200.00	9,800.00	12,040.02	9,575.00	59.47	59.04	-60.83	2,511.96	-355.13	462.80	355.77	107.03	4.324 Alert		
12,300.00	9,800.00	12,140.02	9,575.00	61.06	60.63	-60.86	2,611.96	-355.70	463.26	353.39	109.87	4.216 Alert		
12,400.00	9,800.00	12,240.02	9,575.00	62.65	62.23	-60.89	2,711.95	-356.27	463.72	350.96	112.76	4.113 Alert		
12,500.00	9,800.00	12,340.02	9,575.00	64.27	63.85	-60.92	2,811.95	-356.84	464.18	348.51	115.67	4.013 Alert		
12,600.00	9,800.00	12,440.01	9,575.00	65.90	65.49	-60.95	2,911.95	-357.41	464.64	346.02	118.62	3.917 Alert		
12,700.00	9,800.00	12,540.01	9,575.00	67.55	67.14	-60.98	3,011.94	-357.97	465.11	343.51	121.60	3.825 Alert		
12,800.00	9,800.00	12,640.01	9,575.00	69.21	68.81	-61.02	3,111.94	-358.54	465.57	340.97	124.60	3.737 Alert		
12,900.00	9,800.00	12,740.01	9,575.00	70.89	70.49	-61.05	3,211.94	-359.11	466.03	338.41	127.63	3.652 Alert		
13,000.00	9,800.00	12,840.01	9,575.00	72.58	72.18	-61.08	3,311.93	-359.68	466.49	335.82	130.68	3.570 Alert		
13,100.00	9,800.00	12,940.01	9,575.00	74.27	73.88	-61.11	3,411.93	-360.25	466.96	333.21	133.75	3.491 Alert		
13,200.00	9,800.00	13,040.01	9,575.00	75.98	75.60	-61.14	3,511.93	-360.81	467.42	330.58	136.84	3.416 Alert		
13,300.00	9,800.00	13,140.00	9,575.00	77.70	77.32	-61.17	3,611.93	-361.38	467.88	327.93	139.95	3.343 Alert		
13,400.00	9,800.00	13,240.00	9,575.00	79.43	79.05	-61.20	3,711.92	-361.95	468.34	325.26	143.08	3.273 Alert		
13,500.00	9,800.00	13,340.00	9,575.00	81.16	80.79	-61.23	3,811.92	-362.52	468.81	322.58	146.23	3.206 Alert		
13,600.00	9,800.00	13,440.00	9,575.00	82.91	82.54	-61.27	3,911.92	-363.09	469.27	319.88	149.39	3.141 Alert		
13,700.00	9,800.00	13,540.00	9,575.00	84.66	84.30	-61.30	4,011.91	-363.65	469.73	317.16	152.57	3.079 Alert		
13,800.00	9,800.00	13,640.00	9,575.00	86.42	86.06	-61.33	4,111.91	-364.22	470.20	314.44	155.76	3.019 Alert		
13,900.00	9,800.00	13,740.00	9,575.00	88.18	87.83	-61.36	4,211.91	-364.79	470.66	311.69	158.97	2.961 Alert		
14,000.00	9,800.00	13,839.99	9,575.00	89.95	89.60	-61.39	4,311.90	-365.36	471.12	308.94	162.19	2.905 Alert		
14,100.00	9,800.00	13,939.99	9,575.00	91.73	91.39	-61.42	4,411.90	-365.93	471.59	306.17	165.42	2.851 Alert		
14,200.00	9,800.00	14,039.99	9,575.00	93.51	93.17	-61.45	4,511.90	-366.49	472.05	303.39	168.66	2.799 Alert		
14,256.44	9,800.00	14,096.43	9,575.00	94.52	94.18	-61.47	4,568.33	-366.82	472.31	301.82	170.49	2.770 Alert, SF		

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

Anticollision Report

Company: WCDCS Permian NM
Project: Lea County (NAD83 New Mexico East)
Reference Site: Sec 08-T25S-R33E
Site Error: 0.00 ft
Reference Well: Flagler 8 Fed 27H
Well Error: 0.50 ft
Reference Wellbore: Wellbore #1
Reference Design: Permit Plan 1

Local Co-ordinate Reference: Well Flagler 8 Fed 27H
TVD Reference: RKB @ 3463.20ft
MD Reference: RKB @ 3463.20ft
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Output errors are at: 2.00 sigma
Database: EDM r5000.141_Prod US
Offset TVD Reference: Offset Datum

Offset Design													Offset Site Error:	0.00 ft					
Survey Program: 0-MWD+IGRF													Offset Well Error:	0.50 ft					
Reference													Semi Major Axis		Distance		Minimum Separation (ft)	Separation Factor	Warning
Measured Depth (ft)	Vertical Depth (ft)	Measured Depth (ft)	Vertical Depth (ft)	Reference (ft)	Offset (ft)	Highside Toolface (°)	Offset Wellbore Centra +N/-S (ft)	Offset Wellbore Centra +E/-W (ft)	Between Centres (ft)	Between Ellipses (ft)									
0.00	0.00	0.20	0.20	0.50	0.50	-90.36	-0.19	-29.99	29.99										
100.00	100.00	100.20	100.20	0.52	0.52	-90.36	-0.19	-29.99	29.99	28.95	1.04	28.957							
200.00	200.00	200.20	200.20	0.70	0.70	-90.36	-0.19	-29.99	29.99	28.59	1.40	21.350							
300.00	300.00	300.20	300.20	0.99	0.99	-90.36	-0.19	-29.99	29.99	28.02	1.98	15.183							
400.00	400.00	400.20	400.20	1.31	1.31	-90.36	-0.19	-29.99	29.99	27.37	2.62	11.452							
500.00	500.00	500.20	500.20	1.65	1.65	-90.36	-0.19	-29.99	29.99	26.70	3.29	9.108							
600.00	600.00	600.20	600.20	1.99	1.99	-90.36	-0.19	-29.99	29.99	26.01	3.98	7.532							
700.00	700.00	700.20	700.20	2.34	2.34	-90.36	-0.19	-29.99	29.99	25.31	4.68	6.409							
800.00	800.00	800.20	800.20	2.69	2.69	-90.36	-0.19	-29.99	29.99	24.61	5.38	5.573							
900.00	900.00	900.20	900.20	3.04	3.04	-90.36	-0.19	-29.99	29.99	23.90	6.09	4.926 Alert							
1,000.00	1,000.00	1,000.20	1,000.20	3.40	3.40	-90.36	-0.19	-29.99	29.99	23.19	6.80	4.413 Alert							
1,100.00	1,100.00	1,100.20	1,100.20	3.75	3.75	-90.36	-0.19	-29.99	29.99	22.48	7.51	3.996 Alert							
1,200.00	1,200.00	1,200.20	1,200.20	4.11	4.11	-90.36	-0.19	-29.99	29.99	21.77	8.22	3.650 Alert							
1,300.00	1,300.00	1,300.20	1,300.20	4.46	4.46	-90.36	-0.19	-29.99	29.99	21.06	8.93	3.359 Alert							
1,400.00	1,400.00	1,400.20	1,400.20	4.82	4.82	-90.36	-0.19	-29.99	29.99	20.35	9.64	3.110 Alert							
1,500.00	1,500.00	1,500.20	1,500.20	5.18	5.18	-90.36	-0.19	-29.99	29.99	19.64	10.36	2.896 Alert							
1,600.00	1,600.00	1,600.20	1,600.20	5.53	5.53	-90.36	-0.19	-29.99	29.99	18.92	11.07	2.709 Alert							
1,700.00	1,700.00	1,700.20	1,700.20	5.89	5.89	-90.36	-0.19	-29.99	29.99	18.21	11.78	2.545 Alert							
1,800.00	1,800.00	1,800.20	1,800.20	6.25	6.25	-90.36	-0.19	-29.99	29.99	17.49	12.50	2.400 Minor Risk							
1,900.00	1,900.00	1,900.20	1,900.20	6.61	6.61	-90.36	-0.19	-29.99	29.99	16.78	13.21	2.270 Minor Risk							
2,000.00	2,000.00	2,000.20	2,000.20	6.96	6.96	-90.36	-0.19	-29.99	29.99	16.06	13.93	2.153 Minor Risk							
2,100.00	2,100.00	2,100.20	2,100.20	7.32	7.32	-90.36	-0.19	-29.99	29.99	15.35	14.64	2.048 Minor Risk							
2,200.00	2,200.00	2,200.20	2,200.20	7.68	7.68	-90.36	-0.19	-29.99	29.99	14.63	15.36	1.953 Minor Risk							
2,300.00	2,300.00	2,300.20	2,300.20	8.04	8.04	-90.36	-0.19	-29.99	29.99	13.92	16.07	1.866 Minor Risk							
2,400.00	2,400.00	2,400.20	2,400.20	8.39	8.39	-90.36	-0.19	-29.99	29.99	13.20	16.79	1.786 Minor Risk, CC							
2,500.00	2,499.99	2,500.19	2,500.19	8.73	8.75	112.59	-0.19	-29.99	30.39	12.91	17.49	1.738 Minor Risk, ES							
2,600.00	2,599.96	2,600.16	2,600.16	9.06	9.11	116.62	-0.19	-29.99	31.39	13.22	18.17	1.728 Minor Risk							
2,700.00	2,699.93	2,700.13	2,700.13	9.39	9.47	120.41	-0.19	-29.99	32.54	13.68	18.85	1.726 Minor Risk, SF							
2,800.00	2,799.91	2,800.11	2,800.11	9.72	9.83	123.92	-0.19	-29.99	33.82	14.27	19.54	1.730 Minor Risk							
2,900.00	2,899.88	2,900.08	2,900.08	10.05	10.18	127.16	-0.19	-29.99	35.21	14.98	20.23	1.741 Minor Risk							
3,000.00	2,899.85	3,000.05	3,000.05	10.38	10.54	130.15	-0.19	-29.99	36.71	15.79	20.92	1.755 Minor Risk							
3,100.00	3,099.82	3,100.02	3,100.02	10.72	10.90	132.89	-0.19	-29.99	38.30	16.69	21.61	1.772 Minor Risk							
3,200.00	3,199.79	3,200.01	3,199.99	11.05	11.26	135.41	-0.19	-29.99	39.98	17.67	22.31	1.792 Minor Risk							
3,300.00	3,299.76	3,300.04	3,299.96	11.39	11.62	137.73	-0.19	-29.99	41.72	18.72	23.01	1.814 Minor Risk							
3,400.00	3,399.73	3,400.07	3,399.93	11.73	11.97	139.86	-0.19	-29.99	43.53	19.83	23.70	1.836 Minor Risk							
3,500.00	3,499.70	3,500.10	3,499.90	12.08	12.33	141.81	-0.19	-29.99	45.39	20.99	24.40	1.860 Minor Risk							
3,600.00	3,599.68	3,600.12	3,599.88	12.42	12.69	143.61	-0.19	-29.99	47.30	22.20	25.10	1.884 Minor Risk							
3,700.00	3,699.65	3,700.15	3,699.85	12.76	13.05	145.27	-0.19	-29.99	49.26	23.45	25.80	1.909 Minor Risk							
3,800.00	3,799.62	3,800.18	3,799.82	13.11	13.41	146.79	-0.19	-29.99	51.25	24.74	26.50	1.934 Minor Risk							
3,900.00	3,899.59	3,900.21	3,899.79	13.45	13.77	148.21	-0.19	-29.99	53.27	26.07	27.21	1.958 Minor Risk							
4,000.00	3,999.56	4,000.24	3,999.76	13.80	14.12	149.52	-0.19	-29.99	55.33	27.42	27.91	1.982 Minor Risk							
4,100.00	4,099.53	4,100.27	4,099.73	14.15	14.48	150.73	-0.19	-29.99	57.41	28.80	28.61	2.006 Minor Risk							
4,200.00	4,199.50	4,200.30	4,199.70	14.49	14.84	151.86	-0.19	-29.99	59.52	30.20	29.32	2.030 Minor Risk							
4,300.00	4,299.47	4,300.33	4,299.67	14.84	15.20	152.92	-0.19	-29.99	61.64	31.62	30.02	2.053 Minor Risk							
4,400.00	4,399.44	4,400.36	4,399.64	15.19	15.56	153.90	-0.19	-29.99	63.79	33.06	30.73	2.076 Minor Risk							
4,500.00	4,499.42	4,500.38	4,499.62	15.54	15.92	154.82	-0.19	-29.99	65.96	34.52	31.44	2.098 Minor Risk							
4,600.00	4,599.39	4,600.41	4,599.59	15.89	16.27	155.68	-0.19	-29.99	68.14	36.00	32.14	2.120 Minor Risk							
4,700.00	4,699.36	4,700.44	4,699.56	16.24	16.63	156.48	-0.19	-29.99	70.33	37.48	32.85	2.141 Minor Risk							
4,800.00	4,799.33	4,800.47	4,799.53	16.59	16.99	157.24	-0.19	-29.99	72.54	38.98	33.56	2.162 Minor Risk							
4,900.00	4,899.30	4,900.50	4,899.50	16.94	17.35	157.95	-0.19	-29.99	74.76	40.50	34.26	2.182 Minor Risk							
5,000.00	4,999.27	5,000.53	4,999.47	17.30	17.71	158.62	-0.19	-29.99	76.99	42.02	34.97	2.201 Minor Risk							
5,100.00	5,099.24	5,100.56	5,099.44	17.65	18.07	159.25	-0.19	-29.99	79.23	43.55	35.68	2.221 Minor Risk							

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

Anticollision Report

Company: WCDSC Permian NM
 Project: Lea County (NAD83 New Mexico East)
 Reference Site: Sec 08-T25S-R33E
 Site Error: 0.00 ft
 Reference Well: Flagler 8 Fed 27H
 Well Error: 0.50 ft
 Reference Wellbore: Wellbore #1
 Reference Design: Permit Plan 1

Local Co-ordinate Reference: Well Flagler 8 Fed 27H
 TVD Reference: RKB @ 3463.20ft
 MD Reference: RKB @ 3463.20ft
 North Reference: Grid
 Survey Calculation Method: Minimum Curvature
 Output errors are at: 2.00 sigma
 Database: EDM r5000.141_Prod US
 Offset TVD Reference: Offset Datum

Offset Design Sec 08-T25S-R33E - Flagler 8 Fed 40H - Wellbore #1 - Permit Plan 1														Offset Site Error:	0.00 ft	
Survey Program: 0-MWD+IGRF														Offset Well Error:		0.50 ft
Reference				Offset		Semi Major Axis			Distance					Warning		
Measured Depth (ft)	Vertical Depth (ft)	Measured Depth (ft)	Vertical Depth (ft)	Reference (ft)	Offset (ft)	Highside Tooface (')	Offset Wellbore Centre +N/-S (ft)	+E/-W (ft)	Between Centres (ft)	Between Ellipses (ft)	Minimum Separation (ft)	Separation Factor				
5,200.00	5,199.21	5,200.59	5,199.41	18.00	18.43	159.85	-0.19	-29.99	81.48	45.09	36.39	2.239	Minor Risk			
5,300.00	5,299.19	5,300.62	5,299.39	18.36	18.78	160.42	-0.19	-29.99	83.74	46.64	37.10	2.257	Minor Risk			
5,400.00	5,399.16	5,400.64	5,399.36	18.71	19.14	160.95	-0.19	-29.99	86.01	48.20	37.81	2.275	Minor Risk			
5,500.00	5,499.13	5,500.67	5,499.33	19.06	19.50	161.46	-0.19	-29.99	88.28	49.76	38.52	2.292	Minor Risk			
5,600.00	5,599.10	5,600.70	5,599.30	19.42	19.86	161.95	-0.19	-29.99	90.56	51.33	39.23	2.308	Minor Risk			
5,700.00	5,699.07	5,700.73	5,699.27	19.77	20.22	162.40	-0.19	-29.99	92.85	52.90	39.94	2.325	Minor Risk			
5,800.00	5,799.04	5,800.76	5,799.24	20.13	20.58	162.84	-0.19	-29.99	95.14	54.49	40.65	2.340	Minor Risk			
5,900.00	5,899.01	5,900.79	5,899.21	20.48	20.93	163.26	-0.19	-29.99	97.43	56.07	41.36	2.356	Minor Risk			
6,000.00	5,998.98	6,000.82	5,999.18	20.84	21.29	163.66	-0.19	-29.99	99.74	57.66	42.07	2.371	Minor Risk			
6,100.00	6,098.95	6,100.85	6,099.15	21.19	21.65	164.04	-0.19	-29.99	102.04	59.26	42.79	2.385	Minor Risk			
6,200.00	6,198.93	6,200.87	6,199.13	21.55	22.01	164.40	-0.19	-29.99	104.35	60.86	43.50	2.399	Minor Risk			
6,300.00	6,298.90	6,300.90	6,299.10	21.90	22.37	164.74	-0.19	-29.99	106.67	62.46	44.21	2.413	Minor Risk			
6,400.00	6,398.87	6,400.93	6,399.07	22.26	22.73	165.08	-0.19	-29.99	108.99	64.07	44.92	2.426	Minor Risk			
6,500.00	6,498.84	6,500.96	6,499.04	22.62	23.09	165.39	-0.19	-29.99	111.31	65.68	45.63	2.439	Minor Risk			
6,600.00	6,598.81	6,600.99	6,599.01	22.97	23.44	165.70	-0.19	-29.99	113.63	67.29	46.34	2.452	Minor Risk			
6,700.00	6,698.78	6,701.02	6,698.98	23.33	23.80	165.99	-0.19	-29.99	115.96	68.90	47.06	2.464	Minor Risk			
6,800.00	6,798.75	6,801.05	6,798.95	23.69	24.16	166.27	-0.19	-29.99	118.29	70.52	47.77	2.476	Minor Risk			
6,900.00	6,898.72	6,901.08	6,898.92	24.04	24.52	166.55	-0.19	-29.99	120.63	72.14	48.48	2.488	Minor Risk			
7,000.00	6,998.70	7,001.11	6,998.90	24.40	24.88	166.81	-0.19	-29.99	122.96	73.77	49.20	2.499	Minor Risk			
7,100.00	7,098.67	7,101.13	7,098.87	24.76	25.24	167.06	-0.19	-29.99	125.30	75.39	49.91	2.511	Alert			
7,200.00	7,198.64	7,201.16	7,198.84	25.11	25.59	167.30	-0.19	-29.99	127.64	77.02	50.62	2.522	Alert			
7,300.00	7,298.61	7,301.19	7,298.81	25.47	25.95	167.53	-0.19	-29.99	129.99	78.65	51.34	2.532	Alert			
7,400.00	7,398.58	7,401.22	7,398.78	25.83	26.31	167.75	-0.19	-29.99	132.33	80.28	52.05	2.542	Alert			
7,500.00	7,498.55	7,501.25	7,498.75	26.19	26.67	167.97	-0.19	-29.99	134.68	81.92	52.76	2.553	Alert			
7,600.00	7,598.52	7,601.28	7,598.72	26.55	27.03	168.18	-0.19	-29.99	137.03	83.55	53.48	2.562	Alert			
7,700.00	7,698.49	7,701.31	7,698.69	26.90	27.39	168.38	-0.19	-29.99	139.38	85.19	54.19	2.572	Alert			
7,800.00	7,798.46	7,801.34	7,798.66	27.26	27.75	168.58	-0.19	-29.99	141.73	86.83	54.90	2.582	Alert			
7,900.00	7,898.44	7,901.36	7,898.64	27.62	28.10	168.77	-0.19	-29.99	144.09	88.47	55.62	2.591	Alert			
8,000.00	7,998.41	8,001.39	7,998.61	27.98	28.46	168.95	-0.19	-29.99	146.44	90.11	56.33	2.600	Alert			
8,100.00	8,098.38	8,101.42	8,098.58	28.34	28.82	169.13	-0.19	-29.99	148.80	91.76	57.04	2.608	Alert			
8,200.00	8,198.35	8,201.45	8,198.55	28.69	29.18	169.30	-0.19	-29.99	151.16	93.40	57.76	2.617	Alert			
8,300.00	8,298.34	8,301.46	8,298.54	29.04	29.54	169.40	-0.19	-29.99	152.48	94.01	58.47	2.608	Alert			
8,400.00	8,398.34	8,401.46	8,398.54	29.38	29.90	-31.64	-0.19	-29.99	152.48	93.31	59.16	2.577	Alert			
8,500.00	8,498.34	8,501.46	8,498.54	29.72	30.26	-31.64	-0.19	-29.99	152.48	92.61	59.86	2.547	Alert			
8,600.00	8,598.34	8,601.46	8,598.54	30.06	30.61	-31.64	-0.19	-29.99	152.48	91.91	60.56	2.518	Alert			
8,700.00	8,698.34	8,701.46	8,698.54	30.40	30.97	-31.64	-0.19	-29.99	152.48	91.21	61.26	2.489	Minor Risk			
8,800.00	8,798.34	8,798.54	8,798.54	30.74	31.32	-31.64	-0.19	-29.99	152.48	90.52	61.95	2.461	Minor Risk			
8,900.00	8,898.34	8,880.38	8,880.13	31.08	31.61	-30.59	5.16	-29.90	158.08	95.85	62.23	2.540	Alert			
9,000.00	8,998.34	8,958.55	8,956.61	31.42	31.89	-27.80	21.05	-29.63	175.83	114.06	61.77	2.847	Alert			
9,100.00	9,098.34	9,031.19	9,025.13	31.76	32.13	-24.35	45.02	-29.22	205.66	145.07	60.59	3.394	Alert			
9,200.00	9,198.34	9,100.00	9,086.75	32.11	32.36	-20.95	75.54	-28.70	246.86	187.70	59.15	4.173	Alert			
9,300.00	9,298.15	9,156.59	9,134.40	32.44	32.55	-17.33	106.04	-28.17	294.34	237.49	56.85	5.178				
9,400.00	9,395.80	9,215.09	9,180.23	32.76	32.75	-14.50	142.34	-27.55	336.95	282.42	54.53	6.179				
9,500.00	9,488.31	9,272.84	9,221.62	33.05	32.96	-12.58	182.57	-26.87	373.37	321.36	52.00	7.180				
9,600.00	9,572.89	9,330.05	9,258.42	33.33	33.17	-11.26	226.33	-26.12	403.10	353.77	49.33	8.171				
9,700.00	9,646.96	9,386.86	9,290.47	33.62	33.96	-10.36	273.20	-25.32	425.80	379.19	46.62	9.134				
9,800.00	9,708.27	9,450.00	9,320.45	33.93	33.66	-9.73	328.73	-24.37	441.34	396.92	44.42	9.936				
9,900.00	9,754.96	9,500.00	9,339.74	34.29	33.88	-9.41	374.83	-23.58	449.28	407.71	41.57	10.808				
10,000.00	9,785.60	9,550.00	9,354.94	34.69	34.12	-9.28	422.44	-22.77	449.87	410.62	39.24	11.463				
10,100.00	9,799.28	9,612.48	9,368.01	35.14	34.44	-9.34	483.50	-21.72	442.80	404.72	38.08	11.628				
10,200.00	9,800.00	9,669.23	9,374.06	35.65	34.74	-9.39	539.89	-20.76	432.69	395.33	37.37	11.580				
10,300.00	9,800.00	9,744.80	9,375.00	36.26	35.18	-9.24	615.44	-19.47	430.79	393.33	37.46	11.499				

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

Anticollision Report

Company:	WCDSC Permian NM	Local Co-ordinate Reference:	Well Flagler 8 Fed 27H
Project:	Lea County (NAD83 New Mexico East)	TVD Reference:	RKB @ 3463.20ft
Reference Site:	Sec 08-T25S-R33E	MD Reference:	RKB @ 3463.20ft
Site Error:	0.00 ft	North Reference:	Grid
Reference Well:	Flagler 8 Fed 27H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 ft	Output errors are at	2.00 sigma
Reference Wellbore	Wellbore #1	Database:	EDM r5000.141_Prod US
Reference Design:	Permit Plan 1	Offset TVD Reference:	Offset Datum

Offset Design Sec 08-T25S-R33E - Flagler 8 Fed 40H - Wellbore #1 - Permit Plan 1													Offset Site Error:	0.00 ft
Survey Program: 0-MWD+IGRF													Offset Well Error:	0.50 ft
Reference		Offset		Semi Major Axis			Distance						Warning	
Measured Depth (ft)	Vertical Depth (ft)	Measured Depth (ft)	Vertical Depth (ft)	Reference (ft)	Offset (ft)	Highside Toolface (°)	Offset Wellbore Centre +N/-S (ft)	+E/-W (ft)	Between Centres (ft)	Between Ellipses (ft)	Minimum Separation (ft)	Separation Factor		
10,400.00	9,800.00	9,844.78	9,375.00	36.95	35.82	-9.01	715.41	-17.76	430.51	392.67	37.85	11.375		
10,500.00	9,800.00	9,944.77	9,375.00	37.73	36.56	-8.78	815.38	-16.05	430.24	391.95	38.30	11.234		
10,600.00	9,800.00	10,044.75	9,375.00	38.59	37.38	-8.55	915.35	-14.34	429.98	391.17	38.81	11.080		
10,700.00	9,800.00	10,144.74	9,375.00	39.52	38.27	-8.32	1,015.32	-12.63	429.72	390.35	39.38	10.913		
10,800.00	9,800.00	10,244.72	9,375.00	40.52	39.24	-8.09	1,115.29	-10.93	429.47	389.47	40.00	10.737		
10,900.00	9,800.00	10,344.71	9,375.00	41.59	40.27	-7.86	1,215.26	-9.22	429.23	388.56	40.68	10.553		
11,000.00	9,800.00	10,444.89	9,375.00	42.72	41.37	-7.63	1,315.23	-7.51	429.00	387.60	41.40	10.363		
11,100.00	9,800.00	10,544.68	9,375.00	43.90	42.53	-7.39	1,415.20	-5.80	428.77	386.60	42.17	10.168		
11,200.00	9,800.00	10,644.66	9,375.00	45.13	43.74	-7.16	1,515.17	-4.09	428.55	385.57	42.98	9.972		
11,300.00	9,800.00	10,744.65	9,375.00	46.41	44.99	-6.93	1,615.14	-2.38	428.33	384.50	43.83	9.773		
11,400.00	9,800.00	10,844.63	9,375.00	47.73	46.30	-6.70	1,715.11	-0.67	428.12	383.41	44.71	9.575		
11,500.00	9,800.00	10,944.62	9,375.00	49.09	47.64	-6.47	1,815.08	1.03	427.92	382.29	45.63	9.377		
11,600.00	9,800.00	11,044.60	9,375.00	50.48	49.02	-6.23	1,915.05	2.74	427.73	381.14	46.59	9.181		
11,700.00	9,800.00	11,144.59	9,375.00	51.91	50.44	-6.00	2,015.02	4.45	427.54	379.97	47.57	8.988		
11,800.00	9,800.00	11,244.57	9,375.00	53.37	51.88	-5.77	2,114.99	6.16	427.36	378.78	48.58	8.797		
11,900.00	9,800.00	11,344.55	9,375.00	54.86	53.36	-5.53	2,214.96	7.87	427.19	377.57	49.62	8.610		
12,000.00	9,800.00	11,444.54	9,375.00	56.38	54.86	-5.30	2,314.93	9.58	427.03	376.35	50.68	8.426		
12,100.00	9,800.00	11,544.52	9,375.00	57.91	56.39	-5.07	2,414.90	11.29	426.87	375.11	51.76	8.247		
12,200.00	9,800.00	11,644.51	9,375.00	59.47	57.94	-4.83	2,514.87	12.99	426.72	373.85	52.87	8.071		
12,300.00	9,800.00	11,744.49	9,375.00	61.06	59.52	-4.60	2,614.84	14.70	426.57	372.58	53.99	7.900		
12,400.00	9,800.00	11,844.48	9,375.00	62.65	61.11	-4.37	2,714.81	16.41	426.44	371.30	55.14	7.734		
12,500.00	9,800.00	11,944.46	9,375.00	64.27	62.72	-4.13	2,814.78	18.12	426.31	370.01	56.30	7.572		
12,600.00	9,800.00	12,044.45	9,375.00	65.90	64.34	-3.90	2,914.75	19.83	426.19	368.70	57.48	7.414		
12,700.00	9,800.00	12,144.43	9,375.00	67.55	65.98	-3.66	3,014.72	21.54	426.07	367.39	58.68	7.261		
12,800.00	9,800.00	12,244.42	9,375.00	69.21	67.64	-3.43	3,114.69	23.25	425.96	366.07	59.89	7.112		
12,900.00	9,800.00	12,344.40	9,375.00	70.89	69.31	-3.19	3,214.66	24.95	425.86	364.74	61.12	6.968		
13,000.00	9,800.00	12,444.39	9,375.00	72.58	70.99	-2.96	3,314.63	26.66	425.77	363.41	62.36	6.827		
13,100.00	9,800.00	12,544.37	9,375.00	74.27	72.68	-2.72	3,414.60	28.37	425.68	362.06	63.62	6.691		
13,200.00	9,800.00	12,644.36	9,375.00	75.98	74.38	-2.49	3,514.57	30.08	425.60	360.71	64.89	6.559		
13,300.00	9,800.00	12,744.34	9,375.00	77.70	76.09	-2.25	3,614.54	31.79	425.53	359.36	66.17	6.431		
13,400.00	9,800.00	12,844.33	9,375.00	79.43	77.82	-2.02	3,714.51	33.50	425.46	358.00	67.47	6.306		
13,500.00	9,800.00	12,944.31	9,375.00	81.16	79.55	-1.78	3,814.48	35.21	425.41	356.63	68.78	6.185		
13,600.00	9,800.00	13,044.30	9,375.00	82.91	81.28	-1.55	3,914.45	36.91	425.35	355.26	70.10	6.068		
13,700.00	9,800.00	13,144.28	9,375.00	84.66	83.03	-1.31	4,014.42	38.62	425.31	353.88	71.43	5.954		
13,800.00	9,800.00	13,244.26	9,375.00	86.42	84.78	-1.08	4,114.39	40.33	425.27	352.50	72.78	5.843		
13,900.00	9,800.00	13,344.25	9,375.00	88.18	86.54	-0.84	4,214.36	42.04	425.25	351.11	74.14	5.736		
14,000.00	9,800.00	13,444.23	9,375.00	89.95	88.31	-0.60	4,314.33	43.75	425.22	349.71	75.51	5.631		
14,100.00	9,800.00	13,544.22	9,375.00	91.73	90.08	-0.37	4,414.30	45.46	425.21	348.31	76.89	5.530		
14,200.00	9,800.00	13,644.20	9,375.00	93.51	91.86	-0.13	4,514.27	47.17	425.20	346.91	78.29	5.431		
14,256.44	9,800.00	13,700.63	9,375.00	94.52	92.87	0.00	4,570.69	48.13	425.20	346.12	79.08	5.377		

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

Anticollision Report

Company:	WCDSC Permian NM	Local Co-ordinate Reference:	Well Flagler 8 Fed 27H
Project:	Lea County (NAD83 New Mexico East)	TVD Reference:	RKB @ 3463.20ft
Reference Site:	Sec 08-T25S-R33E	MD Reference:	RKB @ 3463.20ft
Site Error:	0.00 ft	North Reference:	Grid
Reference Well:	Flagler 8 Fed 27H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 ft	Output errors are at	2.00 sigma
Reference Wellbore	Wellbore #1	Database:	EDM r5000.141_Prod US
Reference Design:	Permit Plan 1	Offset TVD Reference:	Offset Datum

Offset Design Sec 08-T25S-R33E - Flagler 8 Fed 4H - Wellbore #1 - Permit Plan 2 Offset Site Error: 0.00 ft
 Survey Program: 0-MWD+IGRF Offset Well Error: 0.50 ft

Measured Depth (ft)	Vertical Depth (ft)	Offset		Semi Major Axis		Highside Toolface (°)	Offset Wellbore Centre		Distance		Minimum Separation (ft)	Separation Factor	Warning
		Measured Depth (ft)	Vertical Depth (ft)	Reference (ft)	Offset (ft)		+N-S (ft)	+E-W (ft)	Between Centres (ft)	Between Ellipses (ft)			
0.00	0.00	0.70	-0.70	0.50	0.50	-163.67	-200.34	-58.71	208.77				
100.00	100.00	100.70	99.30	0.52	0.52	-163.67	-200.34	-58.71	208.77	207.73	1.04	201.479	
200.00	200.00	200.70	199.30	0.70	0.70	-163.67	-200.34	-58.71	208.77	207.36	1.41	148.485	
300.00	300.00	300.70	299.30	0.99	0.99	-163.67	-200.34	-58.71	208.77	206.79	1.98	105.606	
400.00	400.00	400.70	399.30	1.31	1.31	-163.67	-200.34	-58.71	208.77	206.15	2.62	79.666	
500.00	500.00	500.70	499.30	1.65	1.65	-163.67	-200.34	-58.71	208.77	205.47	3.29	63.367	
600.00	600.00	600.70	599.30	1.99	1.99	-163.67	-200.34	-58.71	208.77	204.78	3.98	52.406	
700.00	700.00	700.70	699.30	2.34	2.34	-163.67	-200.34	-58.71	208.77	204.08	4.68	44.598	
800.00	800.00	800.70	799.30	2.69	2.69	-163.67	-200.34	-58.71	208.77	203.38	5.38	38.778	
900.00	900.00	900.70	899.30	3.04	3.05	-163.67	-200.34	-58.71	208.77	202.68	6.09	34.282	
1,000.00	1,000.00	1,000.70	999.30	3.40	3.40	-163.67	-200.34	-58.71	208.77	201.97	6.80	30.711	
1,100.00	1,100.00	1,100.70	1,099.30	3.75	3.76	-163.67	-200.34	-58.71	208.77	201.26	7.51	27.807	
1,200.00	1,200.00	1,200.70	1,199.30	4.11	4.11	-163.67	-200.34	-58.71	208.77	200.55	8.22	25.401	
1,300.00	1,300.00	1,300.70	1,299.30	4.46	4.47	-163.67	-200.34	-58.71	208.77	199.83	8.93	23.376	
1,400.00	1,400.00	1,400.70	1,399.30	4.82	4.82	-163.67	-200.34	-58.71	208.77	199.12	9.64	21.648	
1,500.00	1,500.00	1,500.70	1,499.30	5.18	5.18	-163.67	-200.34	-58.71	208.77	198.41	10.36	20.157	
1,600.00	1,600.00	1,600.70	1,599.30	5.53	5.54	-163.67	-200.34	-58.71	208.77	197.70	11.07	18.857	
1,700.00	1,700.00	1,700.70	1,699.30	5.89	5.89	-163.67	-200.34	-58.71	208.77	196.98	11.78	17.715	
1,800.00	1,800.00	1,800.70	1,799.30	6.25	6.25	-163.67	-200.34	-58.71	208.77	196.27	12.50	16.702	
1,900.00	1,900.00	1,900.70	1,899.30	6.61	6.61	-163.67	-200.34	-58.71	208.77	195.55	13.21	15.799	
2,000.00	2,000.00	2,000.70	1,999.30	6.96	6.97	-163.67	-200.34	-58.71	208.77	194.84	13.93	14.988	
2,100.00	2,100.00	2,100.70	2,099.30	7.32	7.32	-163.67	-200.34	-58.71	208.77	194.12	14.64	14.256	
2,200.00	2,200.00	2,200.70	2,199.30	7.68	7.68	-163.67	-200.34	-58.71	208.77	193.41	15.36	13.592	
2,300.00	2,300.00	2,300.70	2,299.30	8.04	8.04	-163.67	-200.34	-58.71	208.77	192.69	16.08	12.987	
2,400.00	2,400.00	2,400.70	2,399.30	8.39	8.40	-163.67	-200.34	-58.71	208.77	191.97	16.79	12.433	
2,500.00	2,499.99	2,500.71	2,499.29	8.73	8.75	37.56	-200.34	-58.71	207.90	190.41	17.49	11.887	
2,600.00	2,599.96	2,600.74	2,599.26	9.06	9.11	37.97	-200.34	-58.71	206.01	187.84	18.17	11.337	
2,700.00	2,699.93	2,700.77	2,699.23	9.39	9.47	38.38	-200.34	-58.71	204.12	185.27	18.86	10.825	
2,800.00	2,799.91	2,800.79	2,799.21	9.72	9.83	38.80	-200.34	-58.71	202.25	182.70	19.55	10.348	
2,900.00	2,899.88	2,900.82	2,899.18	10.05	10.19	39.23	-200.34	-58.71	200.38	180.14	20.23	9.903	
3,000.00	2,999.85	3,000.85	2,999.15	10.38	10.55	39.67	-200.34	-58.71	198.53	177.60	20.93	9.487	
3,100.00	3,099.82	3,100.88	3,099.12	10.72	10.90	40.12	-200.34	-58.71	196.68	175.06	21.62	9.097	
3,200.00	3,199.79	3,200.91	3,199.09	11.05	11.26	40.57	-200.34	-58.71	194.85	172.54	22.32	8.732	
3,300.00	3,299.76	3,300.94	3,299.06	11.39	11.62	41.04	-200.34	-58.71	193.04	170.02	23.01	8.388	
3,400.00	3,399.73	3,400.97	3,399.03	11.73	11.98	41.51	-200.34	-58.71	191.23	167.52	23.71	8.065	
3,500.00	3,499.70	3,501.00	3,499.00	12.08	12.34	41.99	-200.34	-58.71	189.44	165.03	24.41	7.761	
3,600.00	3,599.68	3,601.02	3,598.98	12.42	12.69	42.48	-200.34	-58.71	187.66	162.55	25.11	7.474	
3,700.00	3,699.65	3,701.05	3,698.95	12.76	13.05	42.98	-200.34	-58.71	185.90	160.09	25.81	7.202	
3,800.00	3,799.62	3,801.08	3,798.92	13.11	13.41	43.49	-200.34	-58.71	184.15	157.63	26.51	6.946	
3,900.00	3,899.59	3,901.11	3,898.89	13.45	13.77	44.01	-200.34	-58.71	182.41	155.20	27.22	6.702	
4,000.00	3,999.56	3,998.86	3,998.86	13.80	14.12	44.54	-200.34	-58.71	180.69	152.78	27.91	6.474	
4,100.00	4,099.53	4,096.71	4,096.71	14.15	14.45	44.88	-201.10	-58.41	179.57	150.98	28.59	6.281	
4,200.00	4,199.50	4,203.52	4,196.46	14.49	14.80	44.99	-202.83	-57.72	179.17	149.89	29.29	6.118	
4,300.00	4,299.47	4,303.52	4,296.44	14.84	15.13	45.11	-204.57	-57.02	178.79	148.83	29.96	5.968	
4,400.00	4,399.44	4,403.52	4,396.42	15.19	15.45	45.22	-206.31	-56.33	178.40	147.76	30.63	5.823	
4,500.00	4,499.42	4,503.52	4,496.40	15.54	15.78	45.34	-208.05	-55.64	178.01	146.70	31.31	5.685	
4,600.00	4,599.39	4,603.53	4,596.38	15.89	16.11	45.45	-209.79	-54.94	177.62	145.63	31.99	5.552	
4,700.00	4,699.36	4,703.53	4,696.36	16.24	16.44	45.57	-211.53	-54.25	177.23	144.56	32.67	5.425	
4,800.00	4,799.33	4,803.53	4,796.34	16.59	16.78	45.69	-213.27	-53.55	176.85	143.49	33.35	5.302	
4,900.00	4,899.30	4,903.53	4,896.33	16.94	17.11	45.81	-215.01	-52.86	176.46	142.43	34.04	5.184	
5,000.00	4,999.27	5,003.53	4,996.31	17.30	17.44	45.92	-216.75	-52.17	176.08	141.36	34.72	5.071	
5,100.00	5,099.24	5,103.53	5,096.29	17.65	17.78	46.04	-218.49	-51.47	175.70	140.28	35.41	4.962 Alert	

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

Anticollision Report

Company: WCDSC Permian NM
Project: Lea County (NAD83 New Mexico East)
Reference Site: Sec 08-T25S-R33E
Site Error: 0.00 ft
Reference Well: Flagler 8 Fed 27H
Well Error: 0.50 ft
Reference Wellbore: Wellbore #1
Reference Design: Permit Plan 1

Local Co-ordinate Reference: Well Flagler 8 Fed 27H
TVD Reference: RKB @ 3463.20ft
MD Reference: RKB @ 3463.20ft
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Output errors are at: 2.00 sigma
Database: EDM r5000.141_Prod US
Offset TVD Reference: Offset Datum

Offset Design													Offset Site Error:	0.00 ft					
Survey Program: 0-MWD+IGRF													Offset Well Error:	0.50 ft					
Reference													Semi Major Axis		Distance		Minimum Separation	Separation Factor	Warning
Measured Depth (ft)	Vertical Depth (ft)	Measured Depth (ft)	Vertical Depth (ft)	Reference (ft)	Offset (ft)	Highside Toolface (°)	Offset Wellbore Centre +N/-S (ft)	+E/-W (ft)	Between Centres (ft)	Between Ellipses (ft)	Separation	Factor							
5,200.00	5,199.21	5,203.53	5,196.27	18.00	18.12	46.16	-220.23	-50.78	175.31	139.21	36.10	4.856	Alert						
5,300.00	5,299.19	5,303.54	5,296.25	18.36	18.45	46.28	-221.97	-50.08	174.93	138.14	36.79	4.755	Alert						
5,400.00	5,399.16	5,403.54	5,396.23	18.71	18.79	46.40	-223.71	-49.39	174.55	137.07	37.48	4.657	Alert						
5,500.00	5,499.13	5,503.54	5,496.21	19.06	19.13	46.52	-225.45	-48.70	174.17	136.00	38.17	4.563	Alert						
5,600.00	5,599.10	5,603.54	5,596.19	19.42	19.47	46.64	-227.19	-48.00	173.79	134.93	38.86	4.472	Alert						
5,700.00	5,699.07	5,703.54	5,696.17	19.77	19.81	46.76	-228.93	-47.31	173.41	133.85	39.56	4.384	Alert						
5,800.00	5,799.04	5,803.54	5,796.15	20.13	20.15	46.89	-230.67	-46.61	173.03	132.78	40.25	4.299	Alert						
5,900.00	5,899.01	5,896.46	5,896.14	20.48	20.47	47.01	-232.41	-45.92	172.66	131.73	40.92	4.219	Alert						
6,000.00	5,998.98	6,003.55	5,996.12	20.84	20.84	47.13	-234.15	-45.23	172.28	130.63	41.64	4.137	Alert						
6,100.00	6,098.95	6,103.55	6,096.10	21.19	21.18	47.26	-235.89	-44.53	171.90	129.56	42.34	4.060	Alert						
6,200.00	6,198.93	6,203.55	6,196.08	21.55	21.52	47.38	-237.63	-43.84	171.53	128.49	43.04	3.985	Alert						
6,300.00	6,298.90	6,303.55	6,296.06	21.90	21.87	47.50	-239.37	-43.14	171.15	127.42	43.74	3.913	Alert						
6,400.00	6,398.87	6,403.55	6,396.04	22.26	22.21	47.63	-241.11	-42.45	170.78	126.34	44.44	3.843	Alert						
6,500.00	6,498.84	6,503.55	6,496.02	22.62	22.56	47.76	-242.85	-41.76	170.41	125.27	45.14	3.775	Alert						
6,600.00	6,598.81	6,603.55	6,596.00	22.97	22.91	47.88	-244.59	-41.06	170.04	124.20	45.84	3.709	Alert						
6,700.00	6,698.78	6,703.56	6,695.98	23.33	23.25	48.01	-246.33	-40.37	169.67	123.13	46.54	3.646	Alert						
6,800.00	6,798.75	6,803.56	6,795.97	23.69	23.60	48.14	-248.07	-39.67	169.30	122.05	47.24	3.584	Alert						
6,900.00	6,898.72	6,903.56	6,895.95	24.04	23.95	48.27	-249.81	-38.98	168.93	120.98	47.94	3.523	Alert						
7,000.00	6,998.70	7,003.56	6,995.93	24.40	24.29	48.39	-251.55	-38.29	168.56	119.91	48.65	3.465	Alert						
7,100.00	7,098.67	7,103.56	7,095.91	24.76	24.64	48.52	-253.29	-37.59	168.19	118.84	49.35	3.408	Alert						
7,200.00	7,198.64	7,203.56	7,195.89	25.11	24.99	48.65	-255.03	-36.90	167.82	117.77	50.06	3.353	Alert						
7,300.00	7,298.61	7,303.56	7,295.87	25.47	25.34	48.78	-256.77	-36.20	167.46	116.70	50.76	3.299	Alert						
7,400.00	7,398.58	7,403.57	7,395.85	25.83	25.69	48.91	-258.51	-35.51	167.09	115.63	51.46	3.247	Alert						
7,500.00	7,498.55	7,503.57	7,495.83	26.19	26.04	49.05	-260.25	-34.82	166.73	114.56	52.17	3.196	Alert						
7,600.00	7,598.52	7,603.57	7,595.81	26.55	26.39	49.18	-261.99	-34.12	166.37	113.49	52.88	3.146	Alert						
7,700.00	7,698.49	7,703.57	7,695.80	26.90	26.74	49.31	-263.73	-33.43	166.00	112.42	53.58	3.098	Alert						
7,800.00	7,798.46	7,803.57	7,795.78	27.26	27.09	49.44	-265.47	-32.73	165.64	111.35	54.29	3.051	Alert						
7,900.00	7,898.44	7,903.57	7,895.76	27.62	27.44	49.58	-267.21	-32.04	165.28	110.29	55.00	3.005	Alert						
8,000.00	7,998.41	8,003.57	7,995.74	27.98	27.79	49.71	-268.95	-31.35	164.92	109.22	55.70	2.961	Alert						
8,100.00	8,098.38	8,103.57	8,095.72	28.34	28.14	49.85	-270.69	-30.65	164.56	108.15	56.41	2.917	Alert						
8,200.00	8,198.35	8,203.58	8,195.70	28.69	28.49	49.98	-272.43	-29.96	164.21	107.09	57.12	2.875	Alert						
8,223.56	8,221.91	8,219.99	8,219.26	28.78	28.55	50.00	-272.84	-29.80	164.16	106.91	57.26	2.867	Alert, CC						
8,300.00	8,298.34	8,303.58	8,295.68	29.04	28.84	49.84	-274.17	-29.26	164.53	106.71	57.82	2.846	Alert, ES						
8,400.00	8,398.34	8,403.60	8,395.64	29.38	29.19	-151.70	-275.91	-28.57	165.73	107.22	58.51	2.833	Alert						
8,500.00	8,498.34	8,503.62	8,495.61	29.72	29.54	-152.19	-277.65	-27.88	166.94	107.74	59.20	2.820	Alert						
8,600.00	8,598.34	8,603.63	8,595.57	30.06	29.90	-152.68	-279.39	-27.18	168.16	108.27	59.89	2.808	Alert						
8,700.00	8,698.34	8,696.35	8,695.54	30.40	30.22	-153.15	-281.13	-26.49	169.39	108.84	60.55	2.797	Alert						
8,800.00	8,798.34	8,796.33	8,795.50	30.74	30.57	-153.63	-282.87	-25.80	170.64	109.39	61.25	2.786	Alert						
8,900.00	8,898.34	8,903.69	8,895.47	31.08	30.95	-154.09	-284.61	-25.10	171.89	109.93	61.96	2.774	Alert						
9,000.00	8,998.34	9,003.70	8,995.43	31.42	31.31	-154.55	-286.35	-24.41	173.16	110.51	62.66	2.764	Alert						
9,100.00	9,098.34	9,103.72	9,095.40	31.76	31.66	-155.00	-288.08	-23.71	174.44	111.09	63.35	2.754	Alert						
9,200.00	9,198.34	9,203.74	9,195.36	32.11	32.01	-155.45	-289.82	-23.02	175.73	111.69	64.04	2.744	Alert, SF						
9,300.00	9,298.15	9,304.02	9,295.07	32.44	32.37	-156.23	-291.56	-22.33	181.08	116.34	64.73	2.797	Alert						
9,400.00	9,395.80	9,406.76	9,392.31	32.76	32.73	-158.22	-293.25	-21.65	201.83	136.42	65.41	3.085	Alert						
9,500.00	9,488.31	9,485.09	9,484.14	33.05	33.01	-160.54	-294.85	-21.02	238.72	172.74	65.98	3.818	Alert						
9,600.00	9,572.89	9,568.73	9,567.76	33.33	33.30	-162.42	-296.31	-20.43	291.13	224.62	66.52	4.377	Alert						
9,700.00	9,646.96	9,641.62	9,640.64	33.62	33.56	-163.38	-297.57	-19.93	357.66	290.69	66.97	5.341							
9,800.00	9,708.27	9,701.54	9,700.56	33.93	33.77	-163.02	-298.62	-19.51	436.22	368.90	67.33	6.479							
9,900.00	9,754.96	9,746.69	9,745.69	34.29	33.93	-160.36	-299.40	-19.20	524.32	456.74	67.58	7.758							
10,000.00	9,785.60	9,775.68	9,774.67	34.69	34.04	-151.47	-299.91	-19.00	619.16	551.43	67.73	9.141							
10,100.00	9,799.28	9,787.63	9,786.62	35.14	34.08	-109.06	-300.11	-18.92	717.78	649.98	67.80	10.587							
10,200.00	9,800.00	9,786.61	9,785.60	35.65	34.07	-78.77	-300.10	-18.92	817.36	749.56	67.80	12.055							

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

Anticollision Report

Company:	WCDCS Permian NM	Local Co-ordinate Reference:	Well Flagler 8 Fed 27H
Project:	Lea County (NAD83 New Mexico East)	TVD Reference:	RKB @ 3463.20ft
Reference Site:	Sec 08-T25S-R33E	MD Reference:	RKB @ 3463.20ft
Site Error:	0.00 ft	North Reference:	Grid
Reference Well:	Flagler 8 Fed 27H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 ft	Output errors are at	2.00 sigma
Reference Wellbore	Wellbore #1	Database:	EDM r5000.141_Prod US
Reference Design:	Permit Plan 1	Offset TVD Reference:	Offset Datum

Offset Design													Offset Site Error:	0.00 ft
Survey Program: 0-MWD+IGRF													Offset Well Error:	0.50 ft
Sec 08-T25S-R33E - Flagler 8 Fed 4H - Wellbore #1 - Permit Plan 2														
Reference		Offset		Semi Major Axis			Distance						Warning	
Measured Depth (ft)	Vertical Depth (ft)	Measured Depth (ft)	Vertical Depth (ft)	Reference (ft)	Offset (ft)	Highside Toolface (°)	Offset Wellbore Centre +N/-S (ft)	+E/-W (ft)	Between Centres (ft)	Between Ellipses (ft)	Minimum Separation (ft)	Separation Factor		
10,300.00	9,800.00	9,784.87	9,783.86	36.26	34.07	-77.39	-300.07	-18.93	917.02	849.22	67.80	13.525		

Anticollision Report

Company: WCDSC Permian NM
Project: Lea County (NAD83 New Mexico East)
Reference Site: Sec 08-T25S-R33E
Site Error: 0.00 ft
Reference Well: Flagler 8 Fed 27H
Well Error: 0.50 ft
Reference Wellbore: Wellbore #1
Reference Design: Permit Plan 1

Local Co-ordinate Reference: Well Flagler 8 Fed 27H
TVD Reference: RKB @ 3463.20ft
MD Reference: RKB @ 3463.20ft
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Output errors are at: 2.00 sigma
Database: EDM r5000.141_Prod US
Offset TVD Reference: Offset Datum

Offset Design: Sec 08-T25S-R33E - Flagler 8 Fed 8H - Wellbore #1 - Permit Plan 1														Offset Site Error:	0.00 ft
Survey Program: 0-MWD+IGRF														Offset Well Error:	0.50 ft
Reference		Offset		Semi Major Axis			Distance		Offset Wellbore Centre		Between Centres		Minimum Separation	Separation Factor	Warning
Measured Depth (ft)	Vertical Depth (ft)	Measured Depth (ft)	Vertical Depth (ft)	Reference (ft)	Offset (ft)	Highside Toeface (')	+N/-S (ft)	+E/-W (ft)	Between Centres (ft)	Between Ellipses (ft)	(ft)	(ft)	(ft)		
0.00	0.00	0.40	-0.40	0.50	0.50	-156.14	-200.54	-88.70	219.28						
100.00	100.00	100.40	99.60	0.52	0.52	-156.14	-200.54	-88.70	219.28	218.25	1.04	211.685			
200.00	200.00	200.40	199.60	0.70	0.70	-156.14	-200.54	-88.70	219.28	217.88	1.41	156.048			
300.00	300.00	300.40	299.60	0.99	0.99	-156.14	-200.54	-88.70	219.28	217.31	1.98	110.977			
400.00	400.00	400.40	399.60	1.31	1.31	-156.14	-200.54	-88.70	219.28	216.66	2.62	83.711			
500.00	500.00	500.40	499.60	1.65	1.65	-156.14	-200.54	-88.70	219.28	215.99	3.29	66.579			
600.00	600.00	600.40	599.60	1.99	1.99	-156.14	-200.54	-88.70	219.28	215.30	3.98	55.060			
700.00	700.00	700.40	699.60	2.34	2.34	-156.14	-200.54	-88.70	219.28	214.60	4.68	46.855			
800.00	800.00	800.40	799.60	2.69	2.69	-156.14	-200.54	-88.70	219.28	213.90	5.38	40.739			
900.00	900.00	900.40	899.60	3.04	3.04	-156.14	-200.54	-88.70	219.28	213.19	6.09	36.016			
1,000.00	1,000.00	1,000.40	999.60	3.40	3.40	-156.14	-200.54	-88.70	219.28	212.48	6.80	32.263			
1,100.00	1,100.00	1,100.40	1,099.60	3.75	3.75	-156.14	-200.54	-88.70	219.28	211.77	7.51	29.212			
1,200.00	1,200.00	1,200.40	1,199.60	4.11	4.11	-156.14	-200.54	-88.70	219.28	211.06	8.22	26.684			
1,300.00	1,300.00	1,300.40	1,299.60	4.46	4.47	-156.14	-200.54	-88.70	219.28	210.35	8.93	24.556			
1,400.00	1,400.00	1,400.40	1,399.60	4.82	4.82	-156.14	-200.54	-88.70	219.28	209.64	9.64	22.741			
1,500.00	1,500.00	1,500.40	1,499.60	5.18	5.18	-156.14	-200.54	-88.70	219.28	208.93	10.36	21.175			
1,600.00	1,600.00	1,600.40	1,599.60	5.53	5.54	-156.14	-200.54	-88.70	219.28	208.21	11.07	19.809			
1,700.00	1,700.00	1,700.40	1,699.60	5.89	5.89	-156.14	-200.54	-88.70	219.28	207.50	11.78	18.609			
1,800.00	1,800.00	1,800.40	1,799.60	6.25	6.25	-156.14	-200.54	-88.70	219.28	206.78	12.50	17.545			
1,900.00	1,900.00	1,900.40	1,899.60	6.61	6.61	-156.14	-200.54	-88.70	219.28	206.07	13.21	16.596			
2,000.00	2,000.00	2,000.40	1,999.60	6.96	6.96	-156.14	-200.54	-88.70	219.28	205.35	13.93	15.744			
2,100.00	2,100.00	2,100.40	2,099.60	7.32	7.32	-156.14	-200.54	-88.70	219.28	204.64	14.64	14.975			
2,200.00	2,200.00	2,200.40	2,199.60	7.68	7.68	-156.14	-200.54	-88.70	219.28	203.92	15.36	14.277			
2,300.00	2,300.00	2,300.40	2,299.60	8.04	8.04	-156.14	-200.54	-88.70	219.28	203.21	16.07	13.642			
2,400.00	2,400.00	2,400.40	2,399.60	8.39	8.40	-156.14	-200.54	-88.70	219.28	202.49	16.79	13.060			
2,500.00	2,499.99	2,500.41	2,499.59	8.73	8.75	45.11	-200.54	-88.70	218.51	201.02	17.49	12.495			
2,600.00	2,599.96	2,600.44	2,599.56	9.06	9.11	45.56	-200.54	-88.70	216.83	198.66	18.17	11.933			
2,700.00	2,699.93	2,700.47	2,699.53	9.39	9.47	46.01	-200.54	-88.70	215.15	196.30	18.86	11.410			
2,800.00	2,799.91	2,800.49	2,799.51	9.72	9.83	46.48	-200.54	-88.70	213.49	193.95	19.54	10.924			
2,900.00	2,899.88	2,900.52	2,899.48	10.05	10.19	46.95	-200.54	-88.70	211.85	191.61	20.23	10.470			
3,000.00	2,999.85	2,999.45	2,999.45	10.38	10.54	47.42	-200.54	-88.70	210.21	189.29	20.92	10.048			
3,100.00	3,099.82	3,097.14	3,097.13	10.72	10.88	48.07	-200.73	-89.50	209.14	187.54	21.60	9.684			
3,144.19	3,144.00	3,140.28	3,140.27	10.87	11.03	48.47	-200.93	-90.37	209.03	187.14	21.89	9.549 CC			
3,200.00	3,199.79	3,194.75	3,194.71	11.05	11.21	49.07	-201.29	-91.92	209.21	186.95	22.26	9.399 ES			
3,300.00	3,299.76	3,292.23	3,292.11	11.39	11.54	50.40	-202.23	-95.96	210.49	187.57	22.92	9.183			
3,400.00	3,399.73	3,389.54	3,389.24	11.73	11.87	52.03	-203.54	-101.59	213.08	189.49	23.58	9.035			
3,500.00	3,499.70	3,488.83	3,488.29	12.08	12.21	53.86	-205.13	-108.40	216.62	192.36	24.26	8.929			
3,600.00	3,599.68	3,588.53	3,587.74	12.42	12.56	55.63	-206.73	-115.26	220.40	195.46	24.94	8.836			
3,700.00	3,699.65	3,688.23	3,687.19	12.76	12.91	57.35	-208.33	-122.12	224.38	198.75	25.63	8.755			
3,800.00	3,799.62	3,787.93	3,786.64	13.11	13.26	59.00	-209.92	-128.98	228.56	202.24	26.32	8.685			
3,900.00	3,899.59	3,887.63	3,886.08	13.45	13.61	60.59	-211.52	-135.83	232.92	205.91	27.01	8.625			
4,000.00	3,999.56	3,987.33	3,985.53	13.80	13.96	62.13	-213.12	-142.69	237.46	209.76	27.70	8.574			
4,100.00	4,099.53	4,087.02	4,084.98	14.15	14.32	63.60	-214.72	-149.55	242.15	213.77	28.39	8.530			
4,200.00	4,199.50	4,186.72	4,184.43	14.49	14.67	65.02	-216.31	-156.41	247.01	217.93	29.08	8.494			
4,300.00	4,299.47	4,286.42	4,283.88	14.84	15.03	66.39	-217.91	-163.27	252.01	222.23	29.78	8.463			
4,400.00	4,399.44	4,386.12	4,383.33	15.19	15.39	67.70	-219.51	-170.12	257.14	226.67	30.47	8.439			
4,500.00	4,499.42	4,485.82	4,482.78	15.54	15.74	68.96	-221.11	-176.98	262.41	231.24	31.17	8.419			
4,600.00	4,599.39	4,585.51	4,582.23	15.89	16.10	70.16	-222.70	-183.84	267.80	235.93	31.87	8.404			
4,700.00	4,699.36	4,685.21	4,681.68	16.24	16.47	71.32	-224.30	-190.70	273.30	240.73	32.56	8.392			
4,800.00	4,799.33	4,784.91	4,781.13	16.59	16.83	72.44	-225.90	-197.56	278.91	245.64	33.26	8.385			
4,900.00	4,899.30	4,884.61	4,880.58	16.94	17.19	73.51	-227.50	-204.41	284.62	250.65	33.96	8.380			
5,000.00	4,999.27	4,984.31	4,980.03	17.30	17.55	74.54	-229.10	-211.27	290.43	255.76	34.67	8.378 SF			

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

Anticollision Report

Company:	WCDSC Permian NM	Local Co-ordinate Reference:	Well Flagler 8 Fed 27H
Project:	Lea County (NAD83 New Mexico East)	TVD Reference:	RKB @ 3463.20ft
Reference Site:	Sec 08-T25S-R33E	MD Reference:	RKB @ 3463.20ft
Site Error:	0.00 ft	North Reference:	Grid
Reference Well:	Flagler 8 Fed 27H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 ft	Output errors are at	2.00 sigma
Reference Wellbore	Wellbore #1	Database:	EDM #500.141_Prod US
Reference Design:	Permit Plan 1	Offset TVD Reference:	Offset Datum

Offset Design													Offset Site Error:	0.00 ft
Sec 08-T25S-R33E - Flagler 8 Fed 8H - Wellbore #1 - Permit Plan 1													Offset Well Error:	0.50 ft
Survey Program: 0-MWD+IGRF														
Reference		Offset		Semi Major Axis			Distance						Warning	
Measured Depth (ft)	Vertical Depth (ft)	Measured Depth (ft)	Vertical Depth (ft)	Reference (ft)	Offset (ft)	Highside Toolface (°)	Offset Wellbore Centre +N/-S (ft)	+E/-W (ft)	Between Centres (ft)	Between Ellipses (ft)	Minimum Separation (ft)	Separation Factor		
5,100.00	5,099.24	5,084.00	5,079.47	17.65	17.92	75.52	-230.69	-218.13	296.32	260.95	35.37	8.378		
5,200.00	5,199.21	5,183.70	5,178.92	18.00	18.28	76.47	-232.29	-224.99	302.30	266.23	36.07	8.381		
5,300.00	5,299.19	5,283.40	5,278.37	18.36	18.65	77.38	-233.89	-231.85	308.36	271.59	36.77	8.386		
5,400.00	5,399.16	5,383.10	5,377.82	18.71	19.02	78.26	-235.49	-238.71	314.50	277.02	37.48	8.392		
5,500.00	5,499.13	5,482.80	5,477.27	19.06	19.38	79.10	-237.08	-245.56	320.70	282.52	38.18	8.400		
5,600.00	5,599.10	5,582.50	5,576.72	19.42	19.75	79.91	-238.68	-252.42	326.97	288.09	38.89	8.409		
5,700.00	5,699.07	5,682.19	5,676.17	19.77	20.12	80.69	-240.28	-259.28	333.31	293.72	39.59	8.419		
5,800.00	5,799.04	5,781.89	5,775.62	20.13	20.49	81.44	-241.88	-266.14	339.70	299.41	40.30	8.430		
5,900.00	5,899.01	5,881.59	5,875.07	20.48	20.85	82.17	-243.48	-273.00	346.15	305.15	41.00	8.442		
6,000.00	5,998.98	5,981.29	5,974.52	20.84	21.22	82.86	-245.07	-279.85	352.66	310.95	41.71	8.455		
6,100.00	6,098.95	6,080.99	6,073.97	21.19	21.59	83.53	-246.67	-286.71	359.21	316.79	42.42	8.468		
6,200.00	6,198.93	6,180.68	6,173.41	21.55	21.96	84.18	-248.27	-293.57	365.81	322.68	43.13	8.482		
6,300.00	6,298.90	6,280.38	6,272.86	21.90	22.33	84.81	-249.87	-300.43	372.46	328.62	43.83	8.497		
6,400.00	6,398.87	6,380.08	6,372.31	22.26	22.71	85.41	-251.46	-307.29	379.14	334.60	44.54	8.512		
6,500.00	6,498.84	6,479.78	6,471.76	22.62	23.08	85.99	-253.06	-314.14	385.87	340.62	45.25	8.527		
6,600.00	6,598.81	6,579.48	6,571.21	22.97	23.45	86.55	-254.66	-321.00	392.64	346.68	45.96	8.543		
6,700.00	6,698.78	6,679.17	6,670.66	23.33	23.82	87.09	-256.26	-327.86	399.44	352.77	46.67	8.559		
6,800.00	6,798.75	6,778.87	6,770.11	23.69	24.19	87.62	-257.85	-334.72	406.28	358.90	47.38	8.575		
6,900.00	6,898.72	6,878.57	6,869.56	24.04	24.56	88.12	-259.45	-341.58	413.15	365.06	48.09	8.591		
7,000.00	6,998.70	6,978.27	6,969.01	24.40	24.94	88.61	-261.05	-348.43	420.05	371.25	48.80	8.607		
7,100.00	7,098.67	7,077.97	7,068.46	24.76	25.31	89.09	-262.65	-355.29	426.98	377.47	49.51	8.623		
7,200.00	7,198.64	7,177.67	7,167.91	25.11	25.68	89.55	-264.25	-362.15	433.94	383.71	50.23	8.640		
7,300.00	7,298.61	7,277.36	7,267.36	25.47	26.06	89.99	-265.84	-369.01	440.93	389.99	50.94	8.656		
7,400.00	7,398.58	7,377.06	7,366.80	25.83	26.43	90.42	-267.44	-375.87	447.94	396.29	51.65	8.673		
7,500.00	7,498.55	7,476.76	7,466.25	26.19	26.80	90.84	-269.04	-382.73	454.97	402.61	52.36	8.689		
7,600.00	7,598.52	7,576.46	7,565.70	26.55	27.18	91.24	-270.64	-389.58	462.03	408.96	53.07	8.705		
7,700.00	7,698.49	7,676.16	7,665.15	26.90	27.55	91.64	-272.23	-396.44	469.12	415.33	53.79	8.722		
7,800.00	7,798.46	7,775.85	7,764.60	27.26	27.93	92.02	-273.83	-403.30	476.22	421.72	54.50	8.738		
7,900.00	7,898.44	7,875.55	7,864.05	27.62	28.30	92.39	-275.43	-410.16	483.34	428.13	55.21	8.754		
8,000.00	7,998.41	7,975.25	7,963.50	27.98	28.68	92.75	-277.03	-417.02	490.48	434.56	55.93	8.770		
8,100.00	8,098.38	8,074.95	8,062.95	28.34	29.05	93.10	-278.62	-423.87	497.65	441.00	56.64	8.786		
8,200.00	8,198.35	8,174.65	8,162.40	28.69	29.43	93.43	-280.22	-430.73	504.83	447.47	57.36	8.801		
8,300.00	8,298.34	8,274.37	8,261.87	29.04	29.80	93.74	-281.82	-437.59	511.95	453.89	58.06	8.817		
8,400.00	8,398.34	8,374.12	8,361.37	29.38	30.18	-107.24	-283.42	-444.45	519.00	460.24	58.76	8.833		
8,500.00	8,498.34	8,473.87	8,460.88	29.72	30.55	-107.18	-285.02	-451.32	526.04	466.59	59.45	8.848		
8,600.00	8,598.34	8,573.62	8,560.38	30.06	30.93	-107.13	-286.62	-458.18	533.09	472.94	60.15	8.863		
8,700.00	8,698.34	8,673.37	8,659.88	30.40	31.30	-107.08	-288.21	-465.04	540.13	479.29	60.85	8.877		
8,800.00	8,798.34	8,773.12	8,759.38	30.74	31.68	-107.03	-289.81	-471.90	547.18	485.64	61.55	8.891		
8,900.00	8,898.34	8,872.87	8,858.88	31.08	32.06	-106.98	-291.41	-478.76	554.23	491.98	62.24	8.904		
9,000.00	8,998.34	8,972.62	8,958.38	31.42	32.43	-106.93	-293.01	-485.62	561.27	498.33	62.94	8.917		
9,100.00	9,098.34	9,072.37	9,057.88	31.76	32.81	-106.88	-294.61	-492.49	568.32	504.68	63.64	8.930		
9,200.00	9,198.34	9,172.12	9,157.38	32.11	33.19	-106.83	-296.21	-499.35	575.37	511.03	64.34	8.943		
9,300.00	9,298.15	9,271.62	9,256.63	32.44	33.56	-106.58	-297.80	-506.19	583.70	518.66	65.04	8.975		
9,400.00	9,395.80	9,368.68	9,353.45	32.76	33.93	-107.14	-299.36	-512.87	597.08	531.38	65.70	9.088		
9,500.00	9,488.31	9,460.37	9,444.91	33.05	34.28	-108.31	-300.83	-519.17	616.83	550.49	66.34	9.298		
9,600.00	9,572.89	9,543.88	9,528.21	33.33	34.59	-109.44	-302.16	-524.92	644.65	577.71	66.93	9.631		
9,700.00	9,646.96	9,616.70	9,600.84	33.62	34.87	-109.81	-303.33	-529.93	682.20	614.71	67.49	10.108		
9,800.00	9,708.27	9,676.59	9,660.59	33.93	35.09	-108.63	-304.29	-534.05	730.46	662.47	67.99	10.743		
9,900.00	9,754.96	9,721.75	9,705.64	34.29	35.26	-105.15	-305.02	-537.15	789.25	720.83	68.42	11.535		
10,000.00	9,785.60	9,750.80	9,734.61	34.69	35.37	-98.58	-305.48	-539.15	857.24	788.49	68.76	12.468		
10,100.00	9,799.28	9,762.86	9,746.64	35.14	35.42	-88.43	-305.67	-539.98	932.13	863.14	68.99	13.512		

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation


Anticollision Report

Company: WCDSC Permian NM
Project: Lea County (NAD83 New Mexico East)
Reference Site: Sec 08-T25S-R33E
Site Error: 0.00 ft
Reference Well: Flagler 8 Fed 27H
Well Error: 0.50 ft
Reference Wellbore: Wellbore #1
Reference Design: Permit Plan 1

Local Co-ordinate Reference: Well Flagler 8 Fed 27H
TVD Reference: RKB @ 3463.20ft
MD Reference: RKB @ 3463.20ft
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Output errors are at: 2.00 sigma
Database: EDM r5000.141_Prod US
Offset TVD Reference: Offset Datum

Reference Depths are relative to RKB @ 3463.20ft
 Offset Depths are relative to Offset Datum
 Central Meridian is -104.333334

Coordinates are relative to: Flagler 8 Fed 27H
 Coordinate System is US State Plane 1983, New Mexico Eastern Zone
 Grid Convergence at Surface is: 0.39°




CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

Anticollision Report

Company:	WCDSC Permian NM	Local Co-ordinate Reference:	Well Flagler 8 Fed 27H
Project:	Lea County (NAD83 New Mexico East)	TVD Reference:	RKB @ 3463.20ft
Reference Site:	Sec 08-T25S-R33E	MD Reference:	RKB @ 3463.20ft
Site Error:	0.00 ft	North Reference:	Grid
Reference Well:	Flagler 8 Fed 27H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 ft	Output errors are at:	2.00 sigma
Reference Wellbore:	Wellbore #1	Database:	EDM r5000.141_Prod US
Reference Design:	Permit Plan 1	Offset TVD Reference:	Offset Datum

Reference Depths are relative to RKB @ 3463.20ft
 Offset Depths are relative to Offset Datum
 Central Meridian is -104.333334

Coordinates are relative to: Flagler 8 Fed 27H
 Coordinate System is US State Plane 1983, New Mexico Eastern Zone
 Grid Convergence at Surface is: 0.39°



CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

106