

HOBES OCD

JUL 25 2018

RECEIVED



EOG Resources - Midland

Lea County, NM (NAD 27 NME)

Dragon 36 State

#10H

OH

Design: OH

EOG PVA

05 January, 2015



EOG Resources, Inc.
EOG PVA

Company:	EOG Resources - Midland	Local Co-ordinate Reference:	Well #10H
Project:	Lea County, NM (NAD 27 NME)	TYD Reference:	KB = 25 @ 3498.0usft (H&P 260)
Site:	Dragon 36 State	MD Reference:	KB = 25 @ 3498.0usft (H&P 260)
Well:	#10H	North Reference:	Grid
Wellbore:	OH	Survey Calculation Method:	Minimum Curvature
Design:	OH	Database:	EDM 5000.1 Single User Db

Project:	Lea County, NM (NAD 27 NME)		
Map System:	US State Plane 1927 (Exact solution)	System Datum:	Mean Sea Level
Geo Datum:	NAD 1927 (NADCON CONUS)		
Map Zone:	New Mexico East 3001		

Site:	Dragon 36 State		
Site Position:		Northing:	425,530.00 usft
From:	Map	Easting:	751,878.00 usft
Position Uncertainty:	0.0 usft	Grid Radius:	13-3/16 "
		Latitude:	32° 10' 2.208 N
		Longitude:	103° 31' 8.626 W
		Grid Convergence:	0.43 "

Well	#10H					
Well Position	+N-S	0.0 usft	Northing:	425,517.00 usft	Latitude:	32° 10' 2.237 N
	+E-W	0.0 usft	Easting:	749,767.00 usft	Longitude:	103° 31' 34.184 W
Position Uncertainty	0.0 usft	Wellhead Elevation:	0.0 usft	Ground Level:	3,473.0 usft	

Wellbore	OH				
Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	IGRF201014	12/27/2014	7.12	80.05	48,233

Design:	OH				
Audit Notes:					
Version:	1.0	Phase:	ACTUAL	Tie On Depth:	0.0
Vertical Section:	Depth From (TYD)	+N-S	+E-W	Direction	
	(usft)	(usft)	(usft)	(°)	
	9,425.0	0.0	0.0	3.99	

Survey Program:	Date	1/5/2015		
From (usft)	To (usft)	Survey (Wellbore)	Tool Name	Description
163.0	14,278.0	MWD #1 (OH)	MWD	MWD - Standard



EOG Resources, Inc.
EOG PVA

Company:	EOG Resources - Midland	Local Co-ordinate Reference:	Well #10H
Project:	Lee County, NM (NAD 27 NME)	TVD Reference:	KB = 25 @ 3498.0usft (H&P 260)
Site:	Dragon 36 State	MD Reference:	KB = 25 @ 3498.0usft (H&P 260)
Well:	#10H	North Reference:	Grid
Wellbore:	OH	Survey Calculation Method:	Minimum Curvature
Design:	OH	Database:	EDM 5000.1 Single User Db

Survey											
MD (usft)	Inc (°)	Asl (grid_north_east)	TVD (usft)	N/S (usft)	E/W (usft)	D/Leg (°/100usft)	Build (°/100usft)	Turn (°/100usft)	High to Plan (usft)	Right to Plan (usft)	
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.00	0.0	0.0	
163.0	1.20	228.50	163.0	-1.1	-1.3	0.74	0.74	0.00	-1.7	0.0	
349.0	2.50	112.00	348.9	-3.9	1.0	1.73	0.70	-62.83	-2.4	-3.3	
532.0	2.50	110.90	531.8	-6.0	8.5	0.03	0.00	-0.60	-10.3	-3.4	
722.0	2.50	111.50	721.6	-6.9	16.2	0.01	0.00	0.32	-18.7	-3.2	
911.0	2.50	110.20	910.4	-12.8	23.9	0.03	0.00	-0.69	-26.8	-3.8	
1,101.0	2.10	106.40	1,100.2	-15.2	31.1	0.23	-0.21	-2.00	-34.1	-5.8	
1,210.0	2.10	110.60	1,209.2	-16.5	34.9	0.14	0.00	3.85	-38.5	-3.1	
1,298.0	1.80	111.50	1,297.1	-17.5	37.7	0.34	-0.34	1.02	-41.5	-2.5	
1,488.0	1.80	148.70	1,487.0	-21.2	42.0	0.60	0.00	19.58	-39.9	24.9	
1,678.0	1.40	144.70	1,677.0	-25.6	44.9	0.22	-0.21	-2.11	-45.9	21.8	
1,867.0	2.50	114.60	1,865.8	-29.2	50.0	0.78	0.58	-15.83	-57.6	-5.8	
2,057.0	2.80	109.70	2,055.8	-32.5	58.1	0.20	0.16	-2.58	-65.7	-11.0	
2,246.0	2.10	103.70	2,244.5	-34.9	65.6	0.39	-0.37	-3.17	-72.2	-18.3	
2,436.0	2.10	102.00	2,434.3	-38.4	72.8	0.03	0.00	-0.69	-78.6	-20.6	
2,625.0	2.10	91.80	2,623.2	-37.3	79.3	0.20	0.00	-5.40	-80.6	-34.8	
2,815.0	2.50	82.30	2,813.1	-36.8	87.1	0.29	0.21	-5.00	-81.3	-48.2	
3,005.0	4.20	111.60	3,002.7	-36.6	97.6	1.24	0.89	15.42	-105.1	-0.2	
3,194.0	4.80	100.90	3,191.2	-42.6	111.5	0.48	0.21	-8.66	-117.6	-21.0	
3,384.0	6.70	114.50	3,380.3	-48.9	129.1	1.30	1.11	7.16	-137.7	9.1	
3,573.0	7.20	113.60	3,567.9	-58.2	150.0	0.27	0.26	-0.48	-160.7	6.8	
3,763.0	6.50	111.10	3,756.5	-66.8	170.9	0.40	-0.37	-1.32	-183.5	-0.8	
3,953.0	6.90	112.30	3,945.2	-75.0	191.5	0.22	0.21	0.63	-205.7	3.3	
4,142.0	6.30	112.30	4,133.0	-83.3	211.6	0.32	-0.32	0.00	-227.4	3.3	
4,331.0	5.60	121.80	4,321.0	-92.0	229.0	0.64	-0.37	5.03	-243.1	42.7	
4,521.0	7.20	119.20	4,509.8	-102.7	247.3	0.86	0.84	-1.37	-266.0	31.2	
4,711.0	8.90	124.10	4,698.3	-115.0	267.2	0.35	-0.16	2.56	-285.6	55.0	



EOG Resources, Inc.
EOG PVA

Company:	EOG Resources - Midland	Local Co-ordinate Reference:	Well #10H
Project:	Lea County, NM (NAD 27 NME)	TVD Reference:	KB = 25 @ 3498.0usft (H&P 250)
Site:	Dragon 36 State	MD Reference:	KB = 25 @ 3498.0usft (H&P 250)
Well:	#10H	North Reference:	Grid
Wellbore:	OH	Survey Calculation Method:	Minimum Curvature
Design:	OH	Database:	EDM 5000.1 Single User Db

Survey											
MD (usft)	Inc (°)	Asl (grid_north_asl)	TVD (usft)	N/S (usft)	E/W (usft)	DLog (°/100usft)	Build (°/100usft)	Turn (°/100usft)	High to Plan (usft)	Right to Plan (usft)	
4,900.0	8.80	119.00	4,885.5	-128.3	289.2	1.07	1.01	-2.70	-315.1	28.3	
5,089.0	10.60	105.80	5,071.9	-140.1	318.8	1.51	0.95	-6.98	-344.8	-48.9	
5,279.0	5.30	112.20	5,260.0	-148.1	343.5	2.82	-2.79	3.37	-374.1	-7.4	
5,468.0	3.30	155.60	5,448.5	-158.4	353.9	1.95	-1.06	22.96	-288.1	255.5	
5,658.0	1.80	185.30	5,638.3	-164.4	355.9	1.03	-0.79	15.63	-126.4	356.9	
5,847.0	1.60	203.80	5,827.2	-169.7	354.5	0.31	-0.11	9.79	-11.3	362.8	
6,037.0	1.60	199.00	6,017.1	-174.7	352.8	0.07	0.00	-2.53	-43.8	340.1	
6,226.0	0.90	307.30	6,206.1	-178.3	350.5	1.08	-0.37	57.30	315.8	-60.3	
6,416.0	0.90	329.10	6,396.1	-174.1	348.6	0.18	0.00	11.47	250.4	-162.1	
6,605.0	1.10	320.80	6,585.1	-171.4	346.7	0.13	0.11	-4.39	249.2	-116.4	
6,795.0	1.20	318.50	6,775.0	-168.5	344.2	0.06	0.05	-1.21	230.7	-99.1	
6,984.0	1.10	333.10	6,964.0	-165.4	342.1	0.18	-0.05	7.72	177.9	-141.8	
7,174.0	0.70	336.80	7,154.0	-162.7	340.8	0.21	-0.21	1.95	149.7	-139.8	
7,363.0	0.70	319.80	7,342.9	-160.8	339.6	0.11	0.00	-8.99	162.9	-82.5	
7,553.0	0.70	342.80	7,532.9	-158.8	338.5	0.15	0.00	12.11	101.1	-124.6	
7,743.0	0.40	322.10	7,722.9	-157.1	337.8	0.19	-0.16	-10.89	116.3	-72.6	
7,932.0	0.40	287.20	7,911.9	-156.6	336.7	0.20	0.00	-29.05	108.7	44.3	
8,122.0	0.70	173.90	8,101.8	-157.8	336.2	0.43	0.16	-49.11	-40.3	88.3	
8,311.0	0.40	216.00	8,290.9	-159.5	335.9	0.25	-0.16	21.75	23.5	73.5	
8,501.0	0.50	220.10	8,480.9	-160.7	335.0	0.06	0.05	2.68	24.0	51.2	
8,690.0	0.70	211.10	8,669.9	-162.3	333.9	0.12	0.11	-4.78	12.4	33.9	
8,880.0	0.90	229.40	8,859.9	-164.3	332.1	0.17	0.11	9.63	12.2	9.6	
8,933.0	0.90	245.90	8,912.9	-164.7	331.4	0.49	0.00	31.13	10.1	1.4	
8,981.0	4.40	16.90	8,960.8	-163.1	331.6	10.49	7.29	272.92	-8.1	-3.1	
9,028.0	11.40	19.50	9,007.3	-157.0	333.7	14.91	14.89	5.53	-13.0	1.5	
9,076.0	18.30	26.20	9,053.7	-145.7	338.6	14.79	14.37	13.96	-18.6	5.5	
9,123.0	22.30	24.60	9,097.6	-131.0	345.6	8.59	8.51	-3.40	-24.6	4.6	



EOG Resources, Inc.
EOG PVA

Company:	EOG Resources - Midland	Local Co-ordinates Reference:	Well #10H
Project:	Lee County, NM (NAD 27 NME)	TVD Reference:	KB = 25 @ 3488.0usft (H&P 260)
Site:	Dragon 36 State	MD Reference:	KB = 25 @ 3488.0usft (H&P 260)
Well:	#10H	North Reference:	Grid
Wellbore:	OH	Survey Calculation Method:	Minimum Curvature
Design:	OH	Database:	EDM 5000.1 Single User Db

Survey											
MD (usft)	Inc (°)	Asl (grid_north_azim)	TVD (usft)	N/S (usft)	E/W (usft)	D/Leg (°/100usft)	Build (°/100usft)	Turn (°/100usft)	High to Plan (usft)	Right to Plan (usft)	
9,171.0	24.60	15.30	9,141.8	-113.1	352.0	9.06	4.79	-19.37	-26.9	-0.5	
9,218.0	26.20	10.90	9,184.3	-93.5	356.6	5.26	3.40	-9.36	-29.6	-3.0	
9,265.0	27.60	14.10	9,226.2	-72.7	361.2	4.28	2.98	6.81	-26.9	-3.2	
9,312.0	30.30	18.50	9,267.3	-50.9	367.6	7.31	5.74	9.36	-21.6	-6.3	
9,360.0	33.30	22.00	9,308.1	-27.2	376.4	7.33	6.25	7.29	-14.4	-13.4	
9,407.0	41.50	22.00	9,345.4	-0.7	387.1	17.45	17.45	0.00	-7.5	-23.9	
9,455.0	51.40	23.00	9,378.5	31.3	400.4	20.68	20.62	2.08	-2.7	-36.4	
9,502.0	60.40	20.80	9,404.8	67.4	414.8	19.94	19.15	-4.68	0.6	-49.3	
9,550.0	69.50	13.00	9,425.1	109.0	427.3	23.99	18.96	-16.25	4.2	-59.8	
9,593.3	70.07	12.56	9,426.3	112.0	428.0	21.15	17.06	-13.33	4.3	-60.3	
FTP(Dragon 36 State #10H)											
9,554.1	70.20	12.45	9,426.5	112.7	428.2	21.15	17.06	-13.27	4.3	-60.4	
HL Crossing, MD:9554.1', TVD:9426.5', N/S:112.7', E/W:428.2', INC:70.20											
9,601.0	79.30	6.50	9,439.3	157.2	435.6	21.15	17.27	-12.70	3.2	-66.2	
9,649.0	79.20	6.50	9,448.6	204.0	440.9	1.87	1.87	0.00	0.1	-70.6	
9,696.0	80.40	5.10	9,457.0	250.0	445.6	3.89	2.55	-2.68	1.1	-74.8	
9,744.0	82.90	3.40	9,464.1	297.3	449.1	5.60	4.37	-3.54	5.3	-78.3	
9,791.0	85.90	1.30	9,468.8	344.0	451.0	8.49	7.23	-4.47	10.7	-80.6	
9,839.0	88.50	358.30	9,471.2	392.0	450.8	8.26	5.42	-6.25	13.7	-80.7	
9,886.0	89.70	354.20	9,471.9	438.9	447.8	9.09	2.55	-6.72	14.9	-78.0	
9,931.0	94.80	349.60	9,468.2	532.8	434.4	7.23	5.37	-4.84	11.1	-65.5	
10,075.0	94.10	349.30	9,460.9	624.9	417.2	0.81	-0.74	-0.32	4.8	-48.9	
10,170.0	92.00	349.80	9,455.6	718.2	400.0	2.27	-2.21	0.53	0.9	-32.4	
10,265.0	90.30	349.80	9,453.9	811.7	383.2	1.79	-1.79	0.00	-0.1	-16.3	
10,360.0	88.90	351.80	9,454.6	905.4	367.9	2.40	-1.47	1.89	1.4	-1.5	
10,455.0	89.20	354.70	9,456.2	999.7	356.5	3.28	0.32	3.26	3.6	9.0	
10,549.0	88.70	357.20	9,457.9	1,093.5	348.9	2.71	-0.53	2.66	6.3	14.6	



EOG Resources, Inc.
EOG PVA

Company:	EOG Resources - Midland	Local Co-ordinate Reference:	Well #10H
Project:	Lee County, NM (NAD 27 NME)	TVD Reference:	KB = 25 @ 3498.0usft (H&P 260)
Site:	Dragon 36 State	MD Reference:	KB = 25 @ 3488.0usft (H&P 260)
Well:	#10H	North Reference:	Grid
Wellbore:	OH	Survey Calculation Method:	Minimum Curvature
Design:	OH	Database:	EDM 5000.1 Single User Db

MD (usft)	Inc (°)	Azi (grid_north_usft)	TVD (usft)	N/S (usft)	EW (usft)	DLeg (°/100usft)	Budd (°/100usft)	Turn (°/100usft)	High to Plan (usft)	Right to Plan (usft)
10,644.0	88.30	359.50	9,460.4	1,188.4	347.2	2.46	-0.42	2.42	9.5	17.0
10,739.0	88.90	359.70	9,462.7	1,263.3	346.5	0.87	0.63	0.21	12.7	16.9
10,834.0	88.90	359.50	9,464.5	1,378.3	345.8	0.21	0.00	-0.21	15.3	16.9
10,928.0	89.70	359.30	9,465.7	1,472.3	344.9	0.88	0.85	-0.21	17.2	17.1
11,023.0	89.90	0.40	9,466.0	1,567.3	344.6	1.16	0.21	1.16	18.4	16.7
11,118.0	91.50	0.20	9,464.8	1,662.3	345.1	1.70	1.68	-0.21	18.0	15.5
11,213.0	91.00	2.10	9,462.8	1,757.3	347.0	2.07	-0.53	2.00	16.7	12.8
11,307.0	90.10	2.70	9,461.9	1,851.2	350.9	1.15	-0.96	0.64	16.6	8.2
11,402.0	94.10	6.50	9,458.4	1,945.8	358.6	5.81	4.21	4.00	13.9	-0.1
11,497.0	94.50	7.80	9,451.3	2,039.8	370.2	1.23	0.42	1.16	7.7	-12.4
11,592.0	94.10	7.80	9,444.1	2,133.7	382.9	0.47	-0.42	0.21	1.5	-25.8
11,686.0	90.30	6.30	9,440.5	2,228.9	394.4	4.35	-4.04	-1.60	-1.6	-38.1
11,781.0	88.30	3.70	9,441.7	2,321.5	402.7	3.45	-2.11	-2.74	0.3	-47.1
11,876.0	84.50	359.10	9,447.7	2,418.2	405.0	6.27	-4.00	-4.84	7.1	-50.1
11,942.8	84.65	356.01	9,453.9	2,462.6	402.2	4.64	0.52	-4.63	14.1	-47.7
TOTAL(Dragon 36 State #10H)										
11,971.0	85.00	354.70	9,456.4	2,510.7	398.9	4.64	0.54	-4.63	16.8	-45.6
12,065.0	90.60	353.50	9,459.8	2,604.0	390.2	6.30	6.17	-1.28	20.6	-36.7
12,160.0	90.30	354.00	9,458.9	2,696.5	379.9	0.74	-0.53	0.53	20.3	-27.0
12,255.0	91.10	354.00	9,457.7	2,793.0	370.0	0.84	0.84	0.00	19.7	-17.8
12,349.0	91.50	356.30	9,455.6	2,886.8	362.0	2.48	0.43	2.45	16.2	-10.6
12,444.0	91.00	357.60	9,453.5	2,981.4	357.0	1.47	-0.53	1.37	16.7	-6.2
12,539.0	90.80	357.90	9,482.0	3,076.3	353.2	0.38	-0.21	0.32	15.8	-3.2
12,634.0	89.90	357.60	9,451.5	3,171.3	349.5	1.00	-0.95	-0.32	15.9	-0.2
12,728.0	91.00	359.10	9,450.7	3,265.2	346.8	1.98	1.17	1.60	15.7	1.8
12,823.0	93.60	359.70	9,446.9	3,360.1	345.8	2.81	2.74	0.63	12.5	2.1
12,918.0	91.70	0.20	9,442.5	3,455.0	345.7	2.07	-2.00	0.53	6.7	1.5



EOG Resources, Inc.
EOG PVA

Company:	EOG Resources - Midland	Local Co-ordinate Reference:	Well #10H
Project:	Lee County, NM (NAD 27 NME)	TVD Reference:	KB = 25 @ 3498.0usft (H&P 260)
Site:	Dragon 36 State	MD Reference:	KB = 25 @ 3498.0usft (H&P 260)
Well:	#10H	North Reference:	Grid
Wellbore:	OH	Survey Calculation Method:	Minimum Curvature
Design:	OH	Database:	EDM 5000.1 Single User Db

MD (usft)	Inc (°)	Azi (grid_north_azim)	TVD (usft)	N/S (usft)	E/W (usft)	D/Leg (°/100usft)	Build (°/100usft)	Turn (°/100usft)	High to Plan (usft)	Right to Plan (usft)
13,013.0	90.80	0.40	9,440.4	3,550.0	345.2	0.97	-0.85	0.21	7.3	0.3
13,107.0	92.20	0.90	9,438.0	3,844.0	347.3	1.58	1.49	0.53	5.4	-1.5
13,202.0	91.30	1.30	9,435.1	3,738.9	349.1	1.04	-0.95	0.42	3.1	-4.0
13,297.0	90.30	1.30	9,433.8	3,833.9	351.3	1.05	-1.05	0.00	2.4	-6.8
13,392.0	91.70	359.80	9,432.1	3,928.8	352.2	2.16	1.47	-1.58	1.3	-8.5
13,487.0	90.80	0.70	9,430.2	4,023.8	352.8	1.50	-1.16	0.95	0.0	-9.8
13,581.0	91.10	0.50	9,428.8	4,117.8	353.6	0.57	0.53	-0.21	-0.8	-11.3
13,676.0	89.90	0.40	9,428.0	4,212.8	354.3	1.27	-1.26	-0.11	-1.0	-12.7
13,771.0	89.20	0.90	9,428.7	4,307.8	355.4	0.91	-0.74	0.53	0.4	-14.5
13,866.0	89.70	0.70	9,429.8	4,402.8	356.7	0.57	0.53	-0.21	1.9	-16.8
13,960.0	90.80	0.90	9,429.2	4,498.8	358.0	1.19	1.17	0.21	2.1	-18.6
14,055.0	90.40	1.60	9,428.2	4,591.7	360.1	0.85	-0.42	0.74	1.7	-21.3
14,150.0	90.80	1.40	9,427.4	4,686.7	362.6	0.30	0.21	-0.21	1.5	-24.5
14,194.1	91.23	1.19	9,428.7	4,730.8	363.6	1.51	1.43	-0.48	1.1	-25.9
HL Crossing, MD:14194.1', TVD:9428.7', N/S:4730.8', E/W:363.6', INC:91.23										
14,213.0	91.50	1.10	9,426.2	4,749.7	364.0	1.51	1.43	-0.48	0.7	-26.4
Last MWD Survey										
14,278.0	91.50	1.10	9,424.5	4,814.6	365.2	0.00	0.00	0.00	-0.5	-28.1
Projection To BH - PBHL(Dragon 36 State #10H)										

Measured Depth (usft)	Vertical Depth (usft)	Local Coordinates	
		N/S (usft)	E/W (usft)
9,554.1	9,426.5	112.7	428.2
14,194.1	9,426.7	4,730.8	363.6
14,213.0	9,426.2	4,749.7	364.0
14,278.0	9,424.5	4,814.6	365.2
Comment			
HL Crossing, MD:9554.1', TVD:9426.5', N/S:112.7', E/W:428.2', INC:70.20			
HL Crossing, MD:14194.1', TVD:9428.7', N/S:4730.8', E/W:363.6', INC:91.23			
Last MWD Survey			
Projection To BH			



EOG Resources, Inc.
EOG PVA

Company:	EOG Resources - Midland	Local Co-ordinate Reference:	Well #10H
Project:	Les County, NM (NAD 27 NME)	TVD Reference:	KB = 25 @ 3400.0ush (H&P 260)
Site:	Dragon 36 State	MD Reference:	KB = 25 @ 3400.0ush (H&P 260)
Well:	#10H	North Reference:	Grid
Wellbore:	OH	Survey Calculation Method:	Minimum Curvature
Design:	OH	Database:	EDM 5000.1 Single User Db

Checked By: _____	Approved By: _____	Date: _____
-------------------	--------------------	-------------



Lea County, NM (NAD 27 NME)

Dragon 36 State #10H

H&P 260

Plan #3

PROJECT DETAILS: Lea County, NM (NAD 27 NME)

Geodetic System: US State Plane 1927 (Exact solution)
Datum: NAD 1927 (NADCON CONUS)
Ellipsoid: Clarke 1866
Zone: New Mexico East 3001
System Datum: Mean Sea Level

WELL DETAILS: #10H

Ground Level: 5473.0
KB = 28 @ 3488.0user (H&P 260)
Northing: 428617.00 Easting: 749767.00
Latitude: 37° 10' 2.237" N Longitude: 103° 31' 34.194" W



Azimuths to Grid North
True North: -0.43°
Magnetic North: 6.70°
Magnetic Field
Strength: 48332.8 nT
Dip Angle: 60.50°
Date: 1/27/2014
Model: IGRF201014

To convert a Magnetic Direction to a Grid Direction, Add 6.70°
To convert a Magnetic Direction to a True Direction, Add 7.13° East
To convert a True Direction to a Grid Direction, Subtract 0.43°

SECTION DETAILS

Sec	WD	Inc	Adj	TVD	+/-E	+/-W	Deq	Tface	Vsect	Target	Annotation
1	0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.0		
2	6260.0	0.00	0.00	6260.0	0.0	0.0	0.00	0.00	0.0		
3	6479.1	4.18	117.61	6377.9	-18.4	29.6	1.00	117.61	-13.3		
4	6579.2	6.19	117.61	6568.9	-168.8	126.1	0.00	0.00	-148.7		
5	6799.3	90.42	358.67	6468.2	911.3	370.7	12.00	-117.76	316.4		
6	11928.4	90.42	358.67	6468.0	2481.3	356.4	0.00	0.00	7800.0		TOT#1(Dragon 36 State #10H)
7	11928.1	90.37	358.67	6467.0	356.4	3.00	177.61	7806.7			
8	14278.2	90.37	358.67	6429.0	6830.0	337.0	0.00	0.00	4361.7		PEH#1(Dragon 36 State #10H)

CADWQ DETAILS

No casing data is available

WELLBORE TARGET DETAILS (MAP CO-ORDINATES)

Name	TVD	+/-E	+/-W	Northing	Easting
PEH#1(Dragon 36 State #10H)	6429.0	4320.0	337.0	430347.00	750104.00
TOT#1(Dragon 36 State #10H)	6468.0	2481.3	356.4	427868.30	750121.42
PT#1(Dragon 36 State #10H)	6468.0	117.0	677.0	425629.00	750139.90

