

Submit 1 Copy To Appropriate District Office

District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3466
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

HOBBS OCD
JUL 30 2018
RECEIVED

WELL API NO. 30-025-43231
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name DMT 7 Fee
8. Well Number 2
9. OGRID Number 24010
10. Pool name or Wildcat Denton; Wolfcamp
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3,773' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well Gas Well Other

2. Name of Operator
V-F PETROLEUM INC.

3. Address of Operator
P.O. Box 1889, Midland, Texas 79702

4. Well Location
Unit Letter **A** : **1200** feet from the **North** line and **1300** feet from the **East** line
Section **7** Township **15-S** Range **38-E** NMPM **Lea** County

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

- PERFORM REMEDIAL WORK
- TEMPORARILY ABANDON
- PULL OR ALTER CASING
- DOWNHOLE COMMINGLE
- OTHER:
- PLUG AND ABANDON
- CHANGE PLANS
- MULTIPLE COMPL
- CLOSED-LOOP SYSTEM
- OTHER:

SUBSEQUENT REPORT OF:

- REMEDIAL WORK
- COMMENCE DRILLING OPNS
- CASING/CEMENT JOB
- OTHER:
- ALTERING CASING
- P AND A

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

07/09/18 -
07/15/18 Test 9 5/8" casing to 1500 psi, test good. Drilling ahead in 8 3/4" hole to 9,616'
07/16/18 Ran 240 Jts 17# 5 1/2" HCL-80
Cemented w/ lead of 430 sacks of Class C + 60:40 Class C + 5% A10 (Gypsum) + 65% ASA301 antissettling + 10lb/sk BA90 (Silca Fume) + 5% BA10 (Bonding agent) + 7% R21(Retarder) + 1%A2 + .13 lb/sk Cello Flake, followed by 630 sacks of Class C + .3% FL 52(Fluid Loss)+ .15 R21 (Retarder). Release Rig.

Spud Date: **06/27/18**

Rig Release Date: **07/16/18**

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE *Eric Sprinkle* TITLE Petroleum Engineer DATE 7/24/2018

Type or print name Eric Sprinkle E-mail address: eric@vfpetroleum.com PHONE: 432-683-3344

APPROVED BY: *[Signature]* TITLE Petroleum Engineer DATE 07/30/18

Conditions of Approval (if any):