

HOBBS OCDIntent ☒ As Drilled ☐

AUG 09 2018

API #
30-025-**RECEIVED**

Operator Name: EOG Resources, Inc.	Property Name: Red Raider 25 State	Well Number 704H
---------------------------------------	---------------------------------------	---------------------

Kick Off Point (KOP)

UL O	Section 25	Township 24S	Range 33E	Lot	Feet	From N/S	Feet	From E/W	County Lea
Latitude					Longitude				NAD

First Take Point (FTP)

UL O	Section 25	Township 24S	Range 33E	Lot	Feet 100	From N/S South	Feet 1652	From E/W East	County Lea
Latitude N 32.1815854					Longitude W -103.5228387				NAD 83

Last Take Point (LTP)

UL B	Section 25	Township 24S	Range 33E	Lot	Feet 100	From N/S North	Feet 1650	From E/W East	County Lea
Latitude N 32.1955452					Longitude W -103.5228385				NAD 83

Is this well the defining well for the Horizontal Spacing Unit?

☐ No

Is this well an infill well?

☐ Yes

If infill is yes please provide API if available, Operator Name and well number for Defining well for Horizontal Spacing Unit.

API #
30-025-44448

Operator Name: EOG Resources, Inc.	Property Name: Red Raider 25 State	Well Number 703H
---------------------------------------	---------------------------------------	---------------------

KZ 06/29/2018

Permit Information:

AUG 09 2018

Well Name: Red Raider 25 State Com No. 704H

RECEIVED**Location:**

SL: 280' FSL & 2232' FEL, Section 25, T-24-S, R-33-E, Lea Co., N.M.

BHL: 100' FNL & 1650' FEL, Section 25, T-24-S, R-33-E, Lea Co., N.M.

Casing Program:

Hole Size	Interval	Csg OD	Weight	Grade	Conn	DF _{min} Collapse	DF _{min} Burst	DF _{min} Tension
17.5"	0 – 1,300'	13.375"	54.5#	J55	STC	1.125	1.25	1.60
12.25"	0-4,000'	9.625"	40#	J55	LTC	1.125	1.25	1.60
12.25"	4,000' – 5,100'	9.625"	40#	HCK55	LTC	1.125	1.25	1.60
8.75"	0 – 11,400'	7.625"	29.7#	HCP110	FXL	1.125	1.25	1.60
6.75"	0'-17,350'	5.5"	17#	HCP-110	LTC	1.125	1.25	1.60

Cement Program:

Depth	No. Sacks	Wt. lb/gal	Yld Ft ³ /ft	Slurry Description
1,300'	1100	13.5	1.74	Lead: Class 'C' + 4.00% Bentonite + 2.00% CaCl ₂ (TOC @ Surface)
	300	14.8	1.35	Tail: Class 'C' + 0.6% FL-62 + 0.25 lb/sk Cello-Flake + 0.2% Sodium Metasilicate + 2.0% KCl (1.06 lb/sk)
5,100'	1150	12.7	2.22	Lead: Class C + 0.15% C-20 + 11.63 pps Salt + 0.1% C-51 + 0.75% C-41P (TOC @ Surface)
	200	14.8	1.32	Tail: Class C + 0.13% C-20
11,400'	345	10.8	3.67	Lead: Class C + 0.40% D013 + 0.20% D046 + 0.10% D065 + 0.20% D167 (TOC @ 4,600')
	220	14.8	2.38	Tail: Class H + 94.0 pps D909 + 0.25% D065 + 0.30% D167 + 0.02% D208 + 0.15% D800
17,350'	850	14.8	1.31	Class H + 0.1% C-20 + 0.05% CSA-1000 + 0.20% C-49 + 0.40% C-17 (TOC @ 10,900')

Mud Program:

Depth	Type	Weight (ppg)	Viscosity	Water Loss
0 – 1,300'	Fresh - Gel	8.6-8.8	28-34	N/c
1,200' – 5,100'	Brine	10.0-10.2	28-34	N/c
5,100' – 11,400'	Oil Base	8.7-9.4	58-68	N/c - 6
11,400' – 17,350' Lateral	Oil Base	10.0-11.5	58-68	3 - 6

Red Raider 25 State Com #704H
Lea County, New Mexico

HOBBS OCD

AUG 09 2018


280' FSL
2232' FEL
Section 25
T-24-S, R-33-E

Proposed Wellbore

RECEIVED

KB: 3,548'
GL: 3,523'

API: 30-025-*****



Lateral: 17,350' MD, 12,404' TVD

BH Location: 100' FNL & 1650' FEL
Section 25
T-24-S, R-33-E