Office	State of New Mexico	Form C-103
District I – (575) 393-6161 1625 N. French Dr., Hobbs, NM 88240 District II – (575) 748-1283	Minerals and Natural Resources NSERVATION DIVISION RO South St. Eropeia Dr.	Revised July 18, 2013 WELL API NO.
811 S. First St., Artesia, NM 88210	NSERVATION DIVISION	30-025-01153
1000 Rio Provos Rd. Artes. NM 7010	20 South St. Francis Dr.	5. Indicate Type of Lease STATE X FEE
District IV – (505) 476-3460 1220 S. St. Francis Dr., Santa Fe, NM	Santa Fe, NM 87505	6. State Oil & Gas Lease No.
87505		305986
SUNDRY NOTICES AND REP (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL O		7. Lease Name or Unit Agreement Name
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERM PROPOSALS.)		Abalone AMB State
· · · · · · · · · · · · · · · · · · ·	Other	8. Well Number 001
2. Name of Operator Foundation Energy M	lanagement, LLC	9. OGRID Number 370740
3. Address of Operator		10. Pool name or Wildcat
5057 Keller Springs Rd., Ste 650, A	Addison, TX 75001	Saunders Permo U/Penn
4. Well Location Unit Letter D: 660 feet	from the North line and	660 feet from the West line
	nship 148 Range 33E	NMPM County Lea
	(Show whether DR, RKB, RT, GR, etc.	
	4,191' GR	<b>新城市,一个大村,大村,城市</b>
12 Check Appropriate B	ox to Indicate Nature of Notice	Report or Other Data
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data		
Approved for Plugging of wellbore only. Liabil	iity ,	SEQUENT REPORT OF:  K
under bond is retained pending restoration an completion of the C-103, Specific for Subsequ	INIT TO PA	ILLING OPNS.□ PANDA 🛛
Report of Well Plugging, which may be found	on P&A NR 🛂 🗀 🗎	T JOB 🔲
he OCD web page under forms.	P&A R	
Restoration Due By <u>6-26-2019</u>		
13. Describe proposed or completed operations		
<ol> <li>Describe proposed or completed operations.         of starting any proposed work). SEE RULE proposed completion or recompletion.</li> </ol>		
of starting any proposed work). SEE RULI	E 19.15.7.14 NMAC. For Multiple Co	mpletions: Attach wellbore diagram of
of starting any proposed work). SEE RULE proposed completion or recompletion.  1. Plugging work began 6/21/2018. Mud  2. Plug #2 perforated at 6,100' and sque	E 19.15.7.14 NMAC. For Multiple Co wt 10.5#. Plug #1 balanced the eezed from 6,150' to 5,972' wi	from 9,083' to 8,923' with 25 SX th 25 SX.
of starting any proposed work). SEE RULF proposed completion or recompletion.  1. Plugging work began 6/21/2018. Mud	E 19.15.7.14 NMAC. For Multiple Co wt 10.5#. Plug #1 balanced the eezed from 6,150' to 5,972' wi	from 9,083' to 8,923' with 25 SX th 25 SX.
of starting any proposed work). SEE RULE proposed completion or recompletion.  1. Plugging work began 6/21/2018. Mud  2. Plug #2 perforated at 6,100' and sque	E 19.15.7.14 NMAC. For Multiple Co wt 10.5#. Plug #1 balanced the eezed from 6,150' to 5,972' with eezed from 4,279' to 4,014' with	ith 25 SX.
of starting any proposed work). SEE RULE proposed completion or recompletion.  1. Plugging work began 6/21/2018. Mud  2. Plug #2 perforated at 6,100' and sque  3. Plug #3 perforated at 4,229' and sque	E 19.15.7.14 NMAC. For Multiple Co wt 10.5#. Plug #1 balanced to eezed from 6,150' to 5,972' wi eezed from 4,279' to 4,014' wi eezed from 2,925' to 2,670' wi	from 9,083' to 8,923' with 25 SX ith 25 SX.
of starting any proposed work). SEE RULE proposed completion or recompletion.  1. Plugging work began 6/21/2018. Mud  2. Plug #2 perforated at 6,100' and sque  3. Plug #3 perforated at 4,229' and sque  4. Plug #4 perforated at 2,875' and sque	E 19.15.7.14 NMAC. For Multiple Co wt 10.5#. Plug #1 balanced to eezed from 6,150' to 5,972' wi eezed from 4,279' to 4,014' wi eezed from 2,925' to 2,670' wi eezed from 1,795' to 1,690' wi	in pletions: Attach wellbore diagram of from 9,083' to 8,923' with 25 SX in th 25 SX. In th 25 SX. In th 25 SX. In th 25 SX. In th 30 SX.
of starting any proposed work). SEE RULE proposed completion or recompletion.  1. Plugging work began 6/21/2018. Mud 2. Plug #2 perforated at 6,100' and sque 3. Plug #3 perforated at 4,229' and sque 4. Plug #4 perforated at 2,875' and sque 5. Plug #5 perforated at 1,795' and sque 6. Plug #6 perforated at 400' and squee 7. Dug out from around wellhead, cut off	E 19.15.7.14 NMAC. For Multiple Co wt 10.5#. Plug #1 balanced to eezed from 6,150' to 5,972' wi eezed from 4,279' to 4,014' wi eezed from 2,925' to 2,670' wi eezed from 1,795' to 1,690' wi zed from 400' to surface with f wellhead & welded on ID ca	irom 9,083' to 8,923' with 25 SX ith 25 SX. ith 25 SX. ith 25 SX. ith 25 SX. ith 30 SX.
of starting any proposed work). SEE RULE proposed completion or recompletion.  1. Plugging work began 6/21/2018. Mud  2. Plug #2 perforated at 6,100' and sque  3. Plug #3 perforated at 4,229' and sque  4. Plug #4 perforated at 2,875' and sque  5. Plug #5 perforated at 1,795' and sque  6. Plug #6 perforated at 400' and squees	E 19.15.7.14 NMAC. For Multiple Co wt 10.5#. Plug #1 balanced to eezed from 6,150' to 5,972' wi eezed from 4,279' to 4,014' wi eezed from 2,925' to 2,670' wi eezed from 1,795' to 1,690' wi zed from 400' to surface with f wellhead & welded on ID ca	irom 9,083' to 8,923' with 25 SX ith 25 SX. ith 25 SX. ith 25 SX. ith 25 SX. ith 30 SX.
of starting any proposed work). SEE RULE proposed completion or recompletion.  1. Plugging work began 6/21/2018. Mud 2. Plug #2 perforated at 6,100' and sque 3. Plug #3 perforated at 4,229' and sque 4. Plug #4 perforated at 2,875' and sque 5. Plug #5 perforated at 1,795' and sque 6. Plug #6 perforated at 400' and squee 7. Dug out from around wellhead, cut off	E 19.15.7.14 NMAC. For Multiple Co wt 10.5#. Plug #1 balanced to eezed from 6,150' to 5,972' wi eezed from 4,279' to 4,014' wi eezed from 2,925' to 2,670' wi eezed from 1,795' to 1,690' wi zed from 400' to surface with f wellhead & welded on ID ca	irom 9,083' to 8,923' with 25 SX ith 25 SX. ith 25 SX. ith 25 SX. ith 25 SX. ith 30 SX.
of starting any proposed work). SEE RULE proposed completion or recompletion.  1. Plugging work began 6/21/2018. Mud 2. Plug #2 perforated at 6,100' and sque 3. Plug #3 perforated at 4,229' and sque 4. Plug #4 perforated at 2,875' and sque 5. Plug #5 perforated at 1,795' and sque 6. Plug #6 perforated at 400' and squee 7. Dug out from around wellhead, cut off Plugging work completed All strings left in hole.	E 19.15.7.14 NMAC. For Multiple Co wt 10.5#. Plug #1 balanced to eezed from 6,150' to 5,972' wi eezed from 4,279' to 4,014' wi eezed from 2,925' to 2,670' wi eezed from 1,795' to 1,690' wi zed from 400' to surface with f wellhead & welded on ID ca 13-3/8" Csg to 350', 8-5/8" Cs	irom 9,083' to 8,923' with 25 SX ith 25 SX. ith 25 SX. ith 25 SX. ith 25 SX. ith 30 SX.
of starting any proposed work). SEE RULE proposed completion or recompletion.  1. Plugging work began 6/21/2018. Mud  2. Plug #2 perforated at 6,100' and sque  3. Plug #3 perforated at 4,229' and sque  4. Plug #4 perforated at 2,875' and sque  5. Plug #5 perforated at 1,795' and sque  6. Plug #6 perforated at 400' and squee  7. Dug out from around wellhead, cut off Plugging work completed	E 19.15.7.14 NMAC. For Multiple Co wt 10.5#. Plug #1 balanced to eezed from 6,150' to 5,972' wi eezed from 4,279' to 4,014' wi eezed from 2,925' to 2,670' wi eezed from 1,795' to 1,690' wi zed from 400' to surface with f wellhead & welded on ID ca	irom 9,083' to 8,923' with 25 SX ith 25 SX. ith 25 SX. ith 25 SX. ith 25 SX. ith 30 SX.
of starting any proposed work). SEE RULE proposed completion or recompletion.  1. Plugging work began 6/21/2018. Mud 2. Plug #2 perforated at 6,100' and sque 3. Plug #3 perforated at 4,229' and sque 4. Plug #4 perforated at 2,875' and sque 5. Plug #5 perforated at 1,795' and sque 6. Plug #6 perforated at 400' and squee 7. Dug out from around wellhead, cut off Plugging work completed All strings left in hole.	E 19.15.7.14 NMAC. For Multiple Co wt 10.5#. Plug #1 balanced to eezed from 6,150' to 5,972' wi eezed from 4,279' to 4,014' wi eezed from 2,925' to 2,670' wi eezed from 1,795' to 1,690' wi zed from 400' to surface with f wellhead & welded on ID ca 13-3/8" Csg to 350', 8-5/8" Cs	irom 9,083' to 8,923' with 25 SX ith 25 SX. ith 25 SX. ith 25 SX. ith 25 SX. ith 30 SX.
of starting any proposed work). SEE RULE proposed completion or recompletion.  1. Plugging work began 6/21/2018. Mud 2. Plug #2 perforated at 6,100' and sque 3. Plug #3 perforated at 4,229' and sque 4. Plug #4 perforated at 2,875' and sque 5. Plug #5 perforated at 1,795' and sque 6. Plug #6 perforated at 400' and squee 7. Dug out from around wellhead, cut off Plugging work completed All strings left in hole.	E 19.15.7.14 NMAC. For Multiple Coll wt 10.5#. Plug #1 balanced feezed from 6,150' to 5,972' will be ezed from 4,279' to 4,014' will be ezed from 2,925' to 2,670' will be ezed from 1,795' to 1,690' will be ezed from 400' to surface with f wellhead & welded on ID call 13-3/8" Csg to 350', 8-5/8" Csg Rig Release Date:	from 9,083' to 8,923' with 25 SX of th 25 SX.  Ith 25 SX.  Ith 25 SX.  Ith 30
of starting any proposed work). SEE RULE proposed completion or recompletion.  1. Plugging work began 6/21/2018. Mud 2. Plug #2 perforated at 6,100' and sque 3. Plug #3 perforated at 4,229' and sque 4. Plug #4 perforated at 2,875' and sque 5. Plug #5 perforated at 1,795' and sque 6. Plug #6 perforated at 400' and squees 7. Dug out from around wellhead, cut off Plugging work completed All strings left in hole.  Spud Date:	ezed from 6,150' to 5,972' we ezed from 4,279' to 4,014' we ezed from 2,925' to 2,670' we ezed from 1,795' to 1,690' we ezed from 400' to surface with f wellhead & welded on ID ca 13-3/8" Csg to 350', 8-5/8" Csg Rig Release Date:	from 9,083' to 8,923' with 25 SX ath 25 SX. Ith 25 SX. Ith 25 SX. Ith 30 SX.
of starting any proposed work). SEE RULE proposed completion or recompletion.  1. Plugging work began 6/21/2018. Mud 2. Plug #2 perforated at 6,100' and sque 3. Plug #3 perforated at 4,229' and sque 4. Plug #4 perforated at 2,875' and sque 5. Plug #5 perforated at 1,795' and sque 6. Plug #6 perforated at 400' and squees 7. Dug out from around wellhead, cut off Plugging work completed All strings left in hole.  Spud Date:	ezed from 6,150' to 5,972' we ezed from 4,279' to 4,014' we ezed from 2,925' to 2,670' we ezed from 1,795' to 1,690' we ezed from 400' to surface with f wellhead & welded on ID ca 13-3/8" Csg to 350', 8-5/8" Csg Rig Release Date:	from 9,083' to 8,923' with 25 SX ath 25 SX. Ith 25 SX. Ith 25 SX. Ith 30 SX.
of starting any proposed work). SEE RULE proposed completion or recompletion.  1. Plugging work began 6/21/2018. Mud 2. Plug #2 perforated at 6,100' and sque 3. Plug #3 perforated at 4,229' and sque 4. Plug #4 perforated at 2,875' and sque 5. Plug #5 perforated at 1,795' and sque 6. Plug #6 perforated at 400' and squees 7. Dug out from around wellhead, cut off Plugging work completed All strings left in hole.  Spud Date:	ezed from 6,150' to 5,972' we ezed from 4,279' to 4,014' we ezed from 2,925' to 2,670' we ezed from 1,795' to 1,690' we ezed from 400' to surface with f wellhead & welded on ID ca 13-3/8" Csg to 350', 8-5/8" Csg Rig Release Date:	from 9,083' to 8,923' with 25 SX ath 25 SX. Ith 25 SX. Ith 25 SX. Ith 30 SX.
of starting any proposed work). SEE RULE proposed completion or recompletion.  1. Plugging work began 6/21/2018. Mud 2. Plug #2 perforated at 6,100' and sque 3. Plug #3 perforated at 4,229' and sque 4. Plug #4 perforated at 2,875' and sque 5. Plug #5 perforated at 1,795' and sque 6. Plug #6 perforated at 400' and sque 7. Dug out from around wellhead, cut off Plugging work completed All strings left in hole.  Spud Date:  Type or print name Bill John Son For State Use Only	E 19.15.7.14 NMAC. For Multiple Coll wt 10.5#. Plug #1 balanced to ezed from 6,150' to 5,972' with ezed from 4,279' to 4,014' with ezed from 2,925' to 2,670' with ezed from 1,795' to 1,690' with ezed from 400' to surface with f wellhead & welded on ID call 13-3/8" Csg to 350', 8-5/8" Csg Release Date:  Rig Release Date:  TITLE PEA Lead Englished and Email address: big has an Eleana.	In the second property com PHONE: 918-526-5549
of starting any proposed work). SEE RULE proposed completion or recompletion.  1. Plugging work began 6/21/2018. Mud 2. Plug #2 perforated at 6,100' and sque 3. Plug #3 perforated at 4,229' and sque 4. Plug #4 perforated at 2,875' and sque 5. Plug #5 perforated at 1,795' and sque 6. Plug #6 perforated at 400' and sque 7. Dug out from around wellhead, cut off Plugging work completed All strings left in hole.  Spud Date:  Type or print name Bill John Son For State Use Only	E 19.15.7.14 NMAC. For Multiple Coll wt 10.5#. Plug #1 balanced to ezed from 6,150' to 5,972' with ezed from 4,279' to 4,014' with ezed from 2,925' to 2,670' with ezed from 1,795' to 1,690' with ezed from 400' to surface with f wellhead & welded on ID call 13-3/8" Csg to 350', 8-5/8" Csg Release Date:  Rig Release Date:  TITLE PEA Lead Englished and Email address: big has an Eleana.	from 9,083' to 8,923' with 25 SX ath 25 SX. Ith 25 SX. Ith 25 SX. Ith 30 SX.