

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
May 27, 2004

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-025-26541
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No. LG - 6004
7. Lease Name or Unit Agreement Name Getty 36 St. Com.
8. Well Number 2
9. OGRID Number 372098
10. Pool name or Wildcat E. Grama Ridge Morrow

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR RUN BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)
1. Type of Well: Oil Well ☐ Gas Well ☒ Other

2. Name of Operator
Marathon Oil Permian, LLC

3. Address of Operator
5555 San Felipe Houston, TX 77056

4. Well Location
Unit Letter J: 1980 feet from the S line and 1980 feet from the E line
Section 36 Township 21S Range 34E NMPM County LEA

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3664 GL

Pit or Below-grade Tank Application ☐ or Closure ☐
Pit type _____ Depth to Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water _____
Pit Liner Thickness: _____ mil Below-Grade Tank: Volume _____ bbls; Construction Material _____

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐

OTHER: ☐

SUBSEQU

REMEDIAL WORK
COMMENCE DRILLING C
CASING/CEMENT JOB

INT TO PA ☒
P&A NR _____
P&A R _____

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

- DUMP 3 SX CNT on CIBP @ 13,038'
1. 5" CIBP @ 12,800' w/10sx cmt. 12,900' w/135' w/BAILER OR 25 SX by thg.
2. 25sx 10,817'-10,717' Tag. ← (11,135' (50' below 7") to 10,716' (50' above 5" liner) TAG
3. 25sx 8450'-8350'.
4. 25sx 5660'-5560'. (SHOE) TAG PRESSURE TEST CSG.
5. 50sx 4227'-3938' Tag.
6. 25sx 1780'-1680'.
7. 25sx 1069'-969' Tag.
8. 20sx 100'-Surf. Verify. Install DHM.

ALL STRINGS

Closed loop.
All fluids to licensed facility.

NOTIFY OCD 24 HOURS PRIOR TO
BEGINNING PLUGGING OPERATIONS

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE Brody Pinkerton TITLE Agent DATE 8-22-18

Type or print name Brody Pinkerton E-mail address: Brody@maverickwellpluggers.com Telephone No. 432-458-3780
For State Use Only

APPROVED BY: Mark W. Pinkerton TITLE P.E.S. DATE 08/23/2018
Conditions of Approval (if any):

C103 INTENT TO P&A EXPIRES
1 YEAR FROM DATE OF APPROVAL

Copy of Getty 36 State Com 2 - Current WBD

Marathon Oil Corporation

VERTICAL WELLBORE DIAGRAM

Getty 36 State Com 2

Eddy County, New Mexico
SL: 1980'FSL, 1980'FEL
Sec J-36-21S-34E
BHL: Vertical
Sec J-36-21S-34E

API No. 30-025-26541

17-1/2" hole cmt circulated →

12-1/4" hole cmt circulated →

8-1/2" hole cmt circulated →

packer @ 12500 w 2-3/8' tbg →

perfs 12946-12954 →

CIBP @ 13038' w/ 1 sx cmt on top →

perfs 13062-13127

PBTD 13028'

TD 13360'

Casing

Size	No Jts	Wt	Grade/Thrds	Depth Set (MD)	Depth Set (TVD)
13-3/8"		48		1019	
9-5/8"		40		5610	
7"		26		11085	
5"		18	liner	13,360	

Description	Length	Depth Set (MD)	Depth Set (TVD)
		0.00'	
		0.00'	
		0.00'	
		0.00'	
		0.00'	
		0.00'	

Prior to P+A

Copy of Getty 36 State Com 2 - Current WBD

Marathon Oil Corporation

D.H.M.

VERTICAL WELLBORE DIAGRAM

205X
100' SURF Verify

Getty 36 State Com 2

Eddy County, New Mexico
SL: 1980'FSL, 1980'FEL 255X
Sec J-36-21S-34E 1069-909
BHL: Vertical
Sec J-36-21S-34E 255X

API No. 30-025-26541 1780-1680
17-1/2" hole cmt circulated →
12-1/4" hole cmt circulated →
8-1/2" hole cmt circulated →

255X 8450-
TAG 8350

255X
10,817-10,717

perfs 12946-12954 →

CIBP @13038' w/ 1 sx cmt on top →

perfs 13062-13127

PBTD 13028'
TD 13360'

Casing

Size	No Jts	Wt	Grade/Thrds	Depth Set (MD)	Depth Set (TVD)
13-3/8"		48		1019	
9-5/8"		40		5610	
7"		26		11085	
5"		18	liner	13,360	

505X 4227-3938 TAG

255X 5660-5560

Description	Length	Depth Set (MD)	Depth Set (TVD)
		0.00'	
		0.00'	
		0.00'	
		0.00'	
		0.00'	
		0.00'	

AFTER P/A

CIBP
@ 12,800' w/ 105X.

NOTE 5" 18# Liner 10,766' - 13,360