

Submit 1 Copy To Appropriate District
Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.

30-025-41715

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator

BC Operating, Inc.

3. Address of Operator

P.O. Box 50820 Midland, TX 79710

4. Well Location

Unit Letter O : 265 feet from the South line and 1350 feet from the East line
Section 14 Township 17S Range 37E NMPM Lea County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
CLOSED-LOOP SYSTEM ☐
OTHER: ☐

SUBS

REMEDIAL WORK ☐
COMMENCE DRIL ☐
CASING/CEMENT ☐
INT TO PA Am ☐
P&A NR ☐
P&A R ☐
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

TAG CBP, Circ MLF, Pressure test CSG.

- 1.) Spot 30 sxs @ 8600'-8400' Tag.
- 2.) Spot 25 sxs @ 6464'-6364'.
- 3.) Spot 25 sxs @ 5377'-5277'.
- 4.) Spot 25 sxs @ 3750'-3650' Tag.
- 5.) Perf @ 3554' sqz 45 sxs to 3454'.
- 6.) Perf @ 2394' sqz 65 sxs to 2168'.
- 7.) Perf @ 2015' sqz 40 sxs to 1915' Tag.
- 6.) Perf @ 450' sqz 130 sxs to surface verify RDMO.

Cut off 3' below ground level, verify cmt to surface all strings
Install upright DTM

NOTIFY OCD 24 HOURS PRIOR TO
BEGINNING PLUGGING OPERATIONS

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Chris Romero

TITLE

P&A Tech

DATE

8/24/18

Type or print name

Chris Romero

E-mail address:

PHONE:

432-563-3355

For State Use Only

APPROVED BY:

Mark Whitman

TITLE

P.E.S.

DATE

08/27/2018

Conditions of Approval (if any):

C103 INTENT TO P&A EXPIRES
1 YEAR FROM DATE OF APPROVAL

WEISSBIER 23 #1H

API # 30-025-41715
265' FSL & 1350' FEL - Sec 14 - T17S - R37E
LEA COUNTY, NEW MEXICO

KB: 3728.7'
GL: 26.5'

SURFACE CASING:

13-3/8" 68# J-55 (0' - 2,275')
W/ 1,965 SX CMT TO SURF

17-1/2" HOLE

INTERMEDIATE CASING:

9-5/8" 40# J-55 LTC (0' - 3,700')
W/ 975 SX CMT TO SURF

12-1/2" HOLE

TOC 3570

PRODUCTION CASING:

7" 29# P-110 TO 8,452'
5-1/2" 17# P-110 (8,452' - 14,295')
CMT W/ 1,840 SX CL H TOC @ 3,570'

BONE SPRING 2nd
18 STG. OA PERF INTERVAL 9,675' TO 14,150'

CIBP @ 9250
w/ 35' cmt

CIBP @ 9625

8-3/4" HOLE

TVQ: 9,296'
MD: 14,301'

FC @ 14,248'
BPS @ 14,202'

400 FW
2218 Rus
2344 TS
3504 BS
3544 Y
4574 an
5377 GB
6464 BC
6779
8184

BC Operating Inc
Weissbier 23 #1H

P/S 450-0 w/ 130 SKS cut
 //

$13\frac{3}{8}$
1965
CIRC

P/S 2015-1915 w/ 40 SKS cut
 Tag

P/S 2394-2168 w/ 65 SKS cut

P/S 3554-3454 w/ 45 SKS cut

TOL 3570

40 #

$9\frac{5}{8}$
3700
CIRC

Spot 3750-3650 w/ 25 SKS cut
 Tag

Spot 5377-5277 w/ 25 SKS cut

Spot 6464-6364 w/ 25 SKS cut

Spot 8600-8400 w/ 30 SKS cut
 Tag

7" + 5 1/2 8452

Set @ 9250 w/ 35 cut

7" 0-8452
 5 1/2 8452 to 14 295
 TOL @ 3570