

# PECOS DISTRICT DRILLING CONDITIONS OF APPROVAL

<b>OPERATOR'S NAME:</b>	<b>Devon Energy Production Company, L.P.</b>
<b>LEASE NO.:</b>	<b>NMNM-114990</b>
<b>WELL NAME &amp; NO.:</b>	<b>Jayhawk 6-7 Fed Fee Com 1H</b>
<b>SURFACE HOLE FOOTAGE:</b>	<b>0365' FNL &amp; 0230' FEL</b>
<b>BOTTOM HOLE FOOTAGE:</b>	<b>0330' FSL &amp; 0360' FEL Sec. 07, T. 26 S., R 34 E.</b>
<b>LOCATION:</b>	<b>Section 06, T. 26 S., R 34 E., NMPM</b>
<b>COUNTY:</b>	<b>County, New Mexico</b>

## Communitization Agreement

The operator will submit a Communitization Agreement to the Carlsbad Field Office, 620 E Greene St. Carlsbad, New Mexico 88220, at least 90 days before the anticipated date of first production from a well subject to a spacing order issued by the New Mexico Oil Conservation Division. The Communitization Agreement will include the signatures of all working interest owners in all Federal and Indian leases subject to the Communitization Agreement (i.e., operating rights owners and lessees of record), or certification that the operator has obtained the written signatures of all such owners and will make those signatures available to the BLM immediately upon request.

If the operator does not comply with this condition of approval, the BLM may take enforcement actions that include, but are not limited to, those specified in 43 CFR 3163.1.

In addition, the well sign shall include the surface and bottom hole lease numbers. When the Communitization Agreement number is known, it shall also be on the sign.

## A. DRILLING OPERATIONS REQUIREMENTS

The BLM is to be notified in advance for a representative to witness:

- a. Spudding well (minimum of 24 hours)
- b. Setting and/or Cementing of all casing strings (minimum of 4 hours)
- c. BOPE tests (minimum of 4 hours)

**Lea County**

Call the Hobbs Field Station, 414 West Taylor, Hobbs NM 88240,  
(575) 3933612

1. **Hydrogen Sulfide (H<sub>2</sub>S) monitors shall be installed prior to drilling out the surface shoe. If H<sub>2</sub>S is detected in concentrations greater than 100 ppm, the**

**Hydrogen Sulfide area shall meet Onshore Order 6 requirements, which includes equipment and personnel/public protection items. If Hydrogen Sulfide is encountered, provide measured values and formations to the BLM.**

2. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval. **If the drilling rig is removed without approval – an Incident of Non-Compliance will be written and will be a “Major” violation.**
3. **The operator has proposed to drill multiple wells utilizing a skid/walking rig. Operator shall secure the wellbore on the current well, after installing and testing the wellhead, by installing a blind flange of like pressure rating to the wellhead and a pressure gauge that can be monitored while drilling is performed on the other wells.**
4. Option – Setting surface casing with Spudder Rig
  - a. Notify the BLM when removing the Spudder Rig.
  - b. Notify the BLM when moving in the H&P Flex Rig. Rig to be moved in within 60 days of notification that Spudder Rig has left the location. Failure to notify or have rig on location within 60 days will result in an Incident of Non-Compliance.
  - c. Once the H&P Flex Rig is on location, it shall not be removed from over the hole without prior approval unless the production casing has been run and cemented or the well has been properly plugged. **If the drilling rig is removed without approval – an Incident of Non-Compliance will be written and will be a “Major” violation.**
  - d. BOP/BOPE test to be conducted per Onshore Oil and Gas Order No. 2 as soon as H&P Flex Rig is rigged up on well. CIT for the surface casing shall be performed and results recorded on subsequent sundry – pressure to be 1200 psi.
5. Floor controls are required for 3M or Greater systems. These controls will be on the rig floor, unobstructed, readily accessible to the driller and will be operational at all times during drilling and/or completion activities. Rig floor is defined as the area immediately around the rotary table; the area immediately above the substructure on which the draw works is located, this does not include the dog house or stairway area.
6. **The record of the drilling rate along with the GR/N well log run from TD to surface (horizontal well – vertical portion of hole) shall be submitted to the BLM office as well as all other logs run on the borehole 30 days from completion. If**

available, a digital copy of the logs is to be submitted in addition to the paper copies. The Rustler top and top and bottom of Salt are to be recorded on the Completion Report.

## B. CASING

Changes to the approved APD casing program need prior approval if the items substituted are of lesser grade or different casing size or are Non-API. The Operator can exchange the components of the proposal with that of superior strength (i.e. changing from J-55 to N-80, or from 36# to 40#). Changes to the approved cement program need prior approval if the altered cement plan has less volume or strength or if the changes are substantial (i.e. Multistage tool, ECP, etc.). The initial wellhead installed on the well will remain on the well with spools used as needed.

Centralizers required on surface casing per Onshore Order 2.III.B.1.f.

### Wait on cement (WOC) for Water Basin:

After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi at the shoe, 2) until cement has been in place at least 8 hours. WOC time will be recorded in the driller's log. See individual casing strings for details regarding lead cement slurry requirements.

Provide compressive strengths including hours to reach required 500 pounds compressive strength prior to cementing each casing string. Have well specific cement details onsite prior to pumping the cement for each casing string.

No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.

Possibility of water flows in the Salado and Castile.

Possibility of lost circulation in the Red Beds, Rustler, and Delaware.

Abnormal pressures may be encountered upon penetrating the 3rd Bone Spring Sandstone and all subsequent formations.

1. The 10-3/4 inch surface casing shall be set at approximately 905 feet (a minimum of 25 feet into the Rustler Anhydrite and above the salt) and cemented to the surface. If salt is encountered, set casing at least 25 feet above the salt.

- a. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with surface log readout will be used or a cement bond log shall be run to verify the top of the cement. Temperature survey will be run a minimum of six hours after pumping cement and ideally between 8-10 hours after completing the cement job.
- b. **Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry.**
- c. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength, whichever is greater.
- d. If cement falls back, remedial cementing will be done prior to drilling out that string.

**Formation below the 10-3/4" shoe to be tested according to Onshore Order 2.III.B.1.i. Test to be done as a mud equivalency test using the mud weight necessary for the pore pressure of the formation below the shoe and the mud weight for the bottom of the hole. Report results to BLM office.**

**7-5/8" Intermediate casing shall be kept fluid filled while running into hole to meet BLM minimum collapse requirements.**

2. The minimum required fill of cement behind the 7-5/8 inch intermediate casing is:

- Cement as proposed. If cement does not circulate see B.1.a, c-d above.

**Formation below the 7-5/8" shoe to be tested according to Onshore Order 2.III.B.1.i. Test to be done as a mud equivalency test using the mud weight necessary for the pore pressure of the formation below the shoe (not the mud weight required to prevent dissolving the salt formation) and the mud weight for the bottom of the hole. Report results to BLM office.**

**Centralizers required on horizontal leg, must be type for horizontal service and a minimum of one every other joint.**

3. The minimum required fill of cement behind the 5-1/2 inch production casing is:

- Cement should tie-back at least 200 feet into previous casing string. Operator shall provide method of verification.

4. If hardband drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.

### C. PRESSURE CONTROL

1. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in Onshore Oil and Gas Order No. 2 and API 53.
2. Variance approved to use flex line from BOP to choke manifold. Check condition of flexible line from BOP to choke manifold, replace if exterior is damaged or if line fails test. Line to be as straight as possible with no hard bends and is to be anchored according to Manufacturer's requirements. The flexible hose can be exchanged with a hose of equal size and equal or greater pressure rating. **Anchor requirements, specification sheet and hydrostatic pressure test certification matching the hose in service, to be onsite for review. These documents shall be posted in the company man's trailer and on the rig floor.** If the BLM inspector questions the straightness of the hose, a BLM engineer will be contacted and will review in the field or via picture supplied by inspector to determine if changes are required (operator shall expect delays if this occurs).
3. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be psi.

**10M system requires an HCR valve, remote kill line and annular to match. The remote kill line is to be installed prior to testing the system and tested to stack pressure.**

**Variance approved to use a 5M annular. The annular must be tested to full working pressure (5000 psi.)**

#### **Multibowl Option:**

4. **Operator has proposed a multi-bowl wellhead assembly. This assembly will only be tested when installed on the surface casing. Minimum working pressure of**

**the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be psi.**

- a. **Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.**
  - b. **If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.**
  - c. **Manufacturer representative shall install the test plug for the initial BOP test.**
  - d. **Operator shall perform the intermediate casing integrity test to 70% of the casing burst. This will test the multi-bowl seals.**
  - e. **If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.**
5. The appropriate BLM office shall be notified a minimum of hours in advance for a representative to witness the tests.
- a. In a water basin, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. The casing cut-off and BOP installation can be initiated four hours after installing the slips, which will be approximately six hours after bumping the plug. For those casing strings not using slips, the minimum wait time before cut-off is eight hours after bumping the plug. BOP/BOPE testing can begin after cut-off or once cement reaches 500 psi compressive strength (including lead when specified), whichever is greater. However, if the float does not hold, cut-off cannot be initiated until cement reaches 500 psi compressive strength (including lead when specified).
  - a. The tests shall be done by an independent service company utilizing a test plug **not a cup or J-packer.**
  - b. The test shall be run on a 5000 psi chart for a 2-3M BOP/BOP, on a 10000 psi chart for a 5M BOP/BOPE and on a 15000 psi chart for a 10M BOP/BOPE. If a linear chart is used, it shall be a one hour chart. A circular chart shall have a maximum 2 hour clock. If a twelve hour or twenty-four hour chart is used, tester shall make a notation that it is run with a two hour clock.
  - c. The results of the test shall be reported to the appropriate BLM office.
  - d. All tests are required to be recorded on a calibrated test chart. **A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.**

- e. The BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes if test is done with a test plug and 30 minutes without a test plug. This test shall be performed prior to the test at full stack pressure.
- f. BOP/BOPE must be tested by an independent service company within 500 feet of the top of the **Wolfcamp** formation if the time between the setting of the intermediate casing and reaching this depth exceeds 20 days. This test does not exclude the test prior to drilling out the casing shoe as per Onshore Order No. 2.

**D. DRILLING MUD**

Mud system monitoring equipment, with derrick floor indicators and visual and audio alarms, shall be operating before drilling into the **Wolfcamp** formation, and shall be used until production casing is run and cemented.

**E. DRILL STEM TEST**

If drill stem tests are performed, Onshore Order 2.III.D shall be followed.

**F. WASTE MATERIAL AND FLUIDS**

All waste (i.e. drilling fluids, trash, salts, chemicals, sewage, gray water, etc.) created as a result of drilling operations and completion operations shall be safely contained and disposed of properly at a waste disposal facility. No waste material or fluid shall be disposed of on the well location or surrounding area.

Porto-johns and trash containers will be on-location during fracturing operations or any other crew-intensive operations.

**JAM 081418**

**PECOS DISTRICT  
SURFACE USE  
CONDITIONS OF APPROVAL**

OPERATOR'S NAME:	DEVON ENERGY PRODUCTION
LEASE NO.:	NMNM114990
WELL NAME & NO.:	4H -JAYHAWK 6-7 FED FEE COM
SURFACE HOLE FOOTAGE:	515'/N & 530'/E
BOTTOM HOLE FOOTAGE:	330'/S & 1284'/E
LOCATION:	Section. 6., T26S., R.34E., NMP
COUNTY:	LEA County, New Mexico

**TABLE OF CONTENTS**

Standard Conditions of Approval (COA) apply to this APD. If any deviations to these standards exist or special COAs are required, the section with the deviation or requirement will be checked below.

- General Provisions**
- Permit Expiration**
- Archaeology, Paleontology, and Historical Sites**
- Noxious Weeds**
- Special Requirements**
  - Escape Ramps
  - Well and CTB Pad Berms
  - Range
  - Watershed
  - Karst
- Construction**
  - Notification
  - Topsoil
  - Closed Loop System
  - Federal Mineral Material Pits
  - Well Pads
  - Roads
- Road Section Diagram**
- Production (Post Drilling)**
  - Well Structures & Facilities
  - Pipelines
  - Electric Lines
- Interim Reclamation**
- Final Abandonment & Reclamation**

Blasting fractures in bedrock can serve as direct conduits for transfer of contaminants into cave and groundwater systems. Blasting also creates an expanded volume of rock rubble that cannot be reclaimed to natural contours, soil condition, or native vegetative condition. As such, surface and subsurface disruptions from blasting procedures can lead to permanent changes in vegetation, rainfall percolation, silting/erosion factors, aquifer recharge, and freshwater quality and can increase the risk of contaminant migration from drilling/production facilities built atop the blast are additional or special Conditions of Approval may apply at that time.

#### **CONSTRUCTION MITIGATION**

In order to mitigate the impacts from construction activities on cave and karst resources, the following Conditions of Approval will apply to this APD or project:

- In the event that any underground voids are encountered during construction activities, construction activities will be halted and the BLM will be notified immediately.
- No Blasting to prevent geologic structure instabilities.
- Pad Berming to minimize effects of any spilled contaminants.

#### **DRILLING IMPACT ANALYSIS**

During drilling, previously unknown cave and karst features could be encountered. If a void is encountered while drilling and a loss of circulation occurs, lost drilling fluids can directly contaminate groundwater recharge areas, aquifers, and groundwater quality. Drilling operations can also lead to sudden collapse of underground voids. Cementing operations may plug or alter groundwater flow, potentially reducing the water quantity at springs and water wells. Inadequate subsurface cementing, casing, and cave/aquifer protection measures can lead to the migration of oil, gas, drilling fluids, and produced saltwater into cave systems and freshwater aquifers.

#### **DRILLING MITIGATION**

Federal regulations and standard Conditions of Approval applied to all APDs require that adequate measures are taken to prevent contamination to the environment. Due to the extreme sensitivity of the cave and karst resources in this project area, the following additional Conditions of Approval will be added to this APD.

To prevent cave and karst resource contamination the following will be required.

- Closed Mud System Using Steel Tanks with All Fluids and Cuttings Hauled Off.
- Rotary drilling with fresh water where cave or karst features are expected to prevent contamination of freshwater aquifers.
- Directional Drilling allowed after at least 100 feet below the cave occurrence zone to prevent additional impacts resulting from directional drilling.
- Lost Circulation zones logged and reported in the drilling report so BLM can assess the situation and work with the operator on corrective actions.
- Additional drilling, casing, and cementing procedures to protect cave zones and fresh water aquifers. See Drilling COAs.

#### **PRODUCTION IMPACT ANALYSIS**

Production facilities such as tank batteries, pump-jacks, compressors, transfer stations, and pipe may fail and allow contaminants to enter caves and freshwater systems. Downhole casing and cementing failures can allow migration of fluids and/or gas between formations and aquifers. Facilities may also be subject to slow subsidence or sudden collapse of the underlying bedrock.

#### **PRODUCTION MITIGATION**

notify the BLM office (575-234-5972) and the private surface landowner or the grazing allotment holder if any damage occurs to structures that provide water to livestock.

#### Cattle Guard Requirement

Where entry is granted across a fence line for an access road, the fence must be braced and tied off on both sides of the passageway with H-braces prior to cutting. Once the work is completed, the fence will be restored to its prior condition with an appropriately sized cattle guard sufficient to carry out the project. Any new or existing cattle guards on the access route shall be repaired or replaced if they are damaged or have deteriorated beyond practical use. The operator shall be responsible for the condition of the existing cattle guards that are in place and are utilized during lease operations. Once the road is abandoned, the fence would be restored to its prior condition, or better. The operator shall notify the private surface landowner or the grazing allotment holder prior to crossing any fences.

The operator must contact the allotment holder prior to construction to identify the location of the pipeline. The operator must take measures to protect the pipeline from compression or other damages. If the pipeline is damaged or compromised in any way near the proposed project as a result of oil and gas activity, the operator is responsible for repairing the pipeline immediately. The operator must notify the BLM office (575-234-5972) and the private surface landowner or the grazing allotment holder if any damage occurs to structures that provide water to livestock.

During construction, the proponent shall minimize disturbance to existing fences, water lines, troughs, windmills, and other improvements on public lands. The proponent is required to promptly repair improvements to at least their former state. Functional use of these improvements will be maintained at all times. The holder will contact the grazing permittee/leasee prior to disturbing any range improvement projects. When necessary to pass through a fence line, the fence shall be braced on both sides of the passageway prior to cutting of the fence. No permanent gates will be allowed unless approved by the Authorized Officer.

- The entire well pad will be bermed to prevent oil, salt, and other chemical contaminants from leaving the well pad. Topsoil shall not be used to construct the berm. No water flow from the uphill side(s) of the pad shall be allowed to enter the well pad. The berm shall be maintained through the life of the well and after interim reclamation has been completed.
- Any water erosion that may occur due to the construction of the well pad during the life of the well will be quickly corrected and proper measures will be taken to prevent future erosion.
- Tank battery locations will be lined and bermed. A 20-mil permanent liner will be installed with a 4 oz. felt backing to prevent tears or punctures. Tank battery berms must be large enough to contain 1 ½ times the content of the largest tank.
- Stockpiling of topsoil is required. The top soil shall be stockpiled in an appropriate location to prevent loss of soil due to water or wind erosion and not used for berming or erosion control.

#### **CONSTRUCTION IMPACT ANALYSIS**

The construction of roads, pipelines, compressor station pads and utilities can impact bedrock integrity and reroute, impede, focus, or erode natural surface drainage systems. Increased silting and sedimentation from construction can plug downstream sinkholes, caves, springs, and other components of aquifer recharge systems and result in adverse impacts to aquifer quality and cave environments. Any contaminants released into the environment during or after construction can impact aquifers and cave systems. A possibility exists for slow subsidence or sudden surface collapse during construction operations due to collapse of underlying cave passages and voids. This would cause associated safety hazards to the operator and the potential for increased environmental impact. Subsidence processes can be triggered by blasting, intense vibrations, rerouting of surface drainages, focusing of surface drainage, and general surface disturbance.

## V. SPECIAL REQUIREMENT(S)

In May 2008, the Pecos District Special Status Species Resource Management Plan Amendment (RMPA) was approved and is being implemented. In addition to the standard practices that minimize impacts, as listed above, the following COA will apply:

- Upon abandonment, a low profile abandoned well marker will be installed to prevent raptor perching.

Power lines shall be constructed and designed in accordance to standards outlined in "Suggested Practices for Avian Protection on Power lines: The State of the Art in 2006" Edison Electric Institute, APLIC, and the California Energy Commission 2006. The holder shall assume the burden and expense of proving that pole designs not shown in the above publication deter raptor perching, roosting, and nesting. Such proof shall be provided by a raptor expert approved by the Authorized Officer. The BLM reserves the right to require modification or additions to all power line structures placed on this right-of-way, should they be necessary to ensure the safety of large perching birds. The holder without liability or expense shall make such modifications and/or additions to the United States.

### **Trenches-Escape Ramps**

Devon would need to construct and maintain escape ramps according to the following criteria:

- Earthen escape ramps would be required to be constructed to sufficiently support livestock at no more than a 30- degree slope and spaced no more than 500 feet apart.
- If the trench is left open under an 8-hour time period, it would not be required to have an escape ramp; however, before the trench is backfilled the trench will be inspected for wildlife and remove any species that are trapped at a distance of at least 100 yards away from the trench.

### **Well and CTB Pad Berms**

- The entire well pad will be bermed to prevent oil, salt, and other chemical contaminants from leaving the well pad. Topsoil shall not be used to construct the berm. No water flow from the uphill side(s) of the pad shall be allowed to enter the well pad. The berm shall be maintained through the life of the well and after interim reclamation has been completed.
- Any water erosion that may occur due to the construction of the well pad during the life of the well will be quickly corrected and proper measures will be taken to prevent future erosion.
- Tank battery locations will be lined and bermed. A 20-mil permanent liner will be installed with a 4 oz. felt backing to prevent tears or punctures. Tank battery berms must be large enough to contain 1 ½ times the content of the largest tank.
- Stockpiling of topsoil is required. The top soil shall be stockpiled in an appropriate location to prevent loss of soil due to water or wind erosion and not used for berming or erosion control.

### Fence Requirement

Where entry is granted across a fence line, the fence must be braced and tied off on both sides of the passageway with H-braces prior to cutting. Once the work is completed, the fence will be restored to its prior condition, or better. The operator shall notify the private surface landowner or the grazing allotment holder prior to crossing any fence(s).

### Livestock Watering Requirement

Any damage to structures that provide water to livestock throughout the life of the well, caused by operations from the well site, must be immediately corrected by the operator. The operator must

## **I. GENERAL PROVISIONS**

The approval of the Application For Permit To Drill (APD) is in compliance with all applicable laws and regulations: 43 Code of Federal Regulations 3160, the lease terms, Onshore Oil and Gas Orders, Notices To Lessees, New Mexico Oil Conservation Division (NMOCD) Rules, National Historical Preservation Act As Amended, and instructions and orders of the Authorized Officer. Any request for a variance shall be submitted to the Authorized Officer on Form 3160-5, Sundry Notices and Report on Wells.

## **II. PERMIT EXPIRATION**

If the permit terminates prior to drilling and drilling cannot be commenced within 60 days after expiration, an operator is required to submit Form 3160-5, Sundry Notices and Reports on Wells, requesting surface reclamation requirements for any surface disturbance. However, if the operator will be able to initiate drilling within 60 days after the expiration of the permit, the operator must have set the conductor pipe in order to allow for an extension of 60 days beyond the expiration date of the APD. (Filing of a Sundry Notice is required for this 60 day extension.)

## **III. ARCHAEOLOGICAL, PALEONTOLOGY & HISTORICAL SITES**

Any cultural and/or paleontological resource discovered by the operator or by any person working on the operator's behalf shall immediately report such findings to the Authorized Officer. The operator is fully accountable for the actions of their contractors and subcontractors. The operator shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery shall be made by the Authorized Officer to determine the appropriate actions that shall be required to prevent the loss of significant cultural or scientific values of the discovery. The operator shall be held responsible for the cost of the proper mitigation measures that the Authorized Officer assesses after consultation with the operator on the evaluation and decisions of the discovery. Any unauthorized collection or disturbance of cultural or paleontological resources may result in a shutdown order by the Authorized Officer.

## **IV. NOXIOUS WEEDS**

The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes the roads, pads, associated pipeline corridor, and adjacent land affected by the establishment of weeds due to this action. The operator shall consult with the Authorized Officer for acceptable weed control methods, which include following EPA and BLM requirements and policies.

In order to mitigate the impacts from production activities and due to the nature of karst terrain, the following Conditions of Approval will apply to this APD:

- Tank battery liners and berms to minimize the impact resulting from leaks.
- Leak detection system to provide an early alert to operators when a leak has occurred.
- Automatic shut off, check valves, or similar systems will be installed for pipelines and tanks to minimize the effects of line failures used in production or drilling.

**RESIDUAL AND CUMULATIVE IMPACT ANALYSIS**

Any industrial activities that take place upon or within karst terrains or freshwater aquifer zones have the potential to create both short-term and long-term negative impacts to freshwater aquifers and cave systems. While a number of mitigation measures can be implemented to mitigate many impacts, it is still possible for impacts to occur from containment failures, well blowouts, accidents, spills, and structural collapses. It is therefore necessary to implement long-term monitoring studies to determine if current mitigations measures are sufficient enough to prevent long-term or cumulative impacts.

**RESIDUAL AND CUMULATIVE MITIGATION**

- Nontoxic fluorescent dyes will be added to the drilling fluid when the hole is spudded and will be circulated to the bottom of the karst layers. This provides data as part of a long-term monitoring study.
- Annual pressure monitoring will be performed by the operator. If the test results indicate a casing failure has occurred, remedial action will be undertaken to correct the problem to the BLM's approval.

**PLUGGING AND ABANDONMENT IMPACT ANALYSIS**

Failure of a plugged and abandoned well can lead to migration of contaminants to karst resources and fresh water aquifers. While this action does not specifically approve plugging and abandonment procedures, the operator should be made aware that additional or special Conditions of Approval may apply at that time.

**PLUGGING AND ABANDONMENT MITIGATION**

Abandonment Cementing: Upon well abandonment in high cave karst areas additional plugging conditions of approval may be required. The BLM will assess the situation and work with the operator to ensure proper plugging of the wellbore.

**MITIGATING MEASURES for ROADS:**

- Roads will be routed around sinkholes and other karst features to avoid or lessen the possibility of encountering near surface voids and to minimize changes to runoff or possible leaks and spills from entering karst systems.
- The BLM, Carlsbad Field Office, will be informed immediately if any subsurface drainage channels, cave passages, or voids are penetrated during construction and no further construction will be done until clearance has been issued by the Authorized Officer.
- Turnout ditches and drainage leadoffs will not be constructed in such a manner as to increase or decrease the natural flow of water into or out of cave or karst features.
- Special restoration stipulations or realignment may be required.

**MITIGATING MEASURES FOR POWERLINES:**

Smaller powerlines will be routed around sinkholes and other karst features to avoid or lessen the possibility of encountering near surface voids and to minimize changes to runoff or possible leaks and spills from entering karst systems. Larger powerlines will adjust their pole spacing to avoid cave and karst features.

Commented [TH1]: Too many spaces between paragraphs

The BLM, Carlsbad Field Office, will be informed immediately if any subsurface drainage channels, cave passages, or voids are penetrated during construction. No further construction will be done until clearance has been issued by the Authorized Officer. Special restoration stipulations or realignment may be required.

**MITIGATING MEASURES for BURIED PIPELINES AND CABLES:**

The BLM, Carlsbad Field Office, will be informed immediately if any subsurface drainage channels, passages, or voids are intersected by trenching, and no pipe will be laid in the trench at that point until clearance has been issued by the Authorized Officer. If a void is encountered alignments may be rerouted to avoid the karst feature and lessen; the potential of subsidence or collapse of karst features, buildup of toxic or combustible gas, or other possible impacts to cave and karst resources from the buried pipeline. Special restoration stipulations or realignment may be required at such intersections, if any. A leak detection plan **will be submitted to the BLM Carlsbad Field Office for approval** prior to pipeline installation. The method could incorporate gauges to detect pressure drops, situating valves and lines so they can be visually inspected periodically or installing electronic sensors to alarm when a leak is present. The leak detection plan will incorporate an automatic shut off system that will be installed for proposed pipelines to minimize the effects of an undesirable event. Regular monitoring is required to quickly identify leaks for their immediate and proper treatment.

**MITIGATING MEASURES for SURFACE FLOWLINES:**

Flowlines will be routed around sinkholes and other karst features to avoid or lessen the possibility of encountering near surface voids and to minimize the possibility of leaks and spills from entering karst systems. If a void is encountered alignments may be rerouted to avoid the karst feature and lessen; the potential of subsidence or collapse of karst features, buildup of toxic or combustible gas, or other possible impacts to cave and karst resources from the buried pipeline. Regular monitoring is required to quickly identify leaks for their immediate and proper treatment. All spills or leaks will be reported to the BLM immediately for their immediate and proper treatment.

## **VI. CONSTRUCTION**

### **A. NOTIFICATION**

The BLM shall administer compliance and monitor construction of the access road and well pad. Notify the Carlsbad Field Office at (575) 234-5909 at least 3 working days prior to commencing construction of the access road and/or well pad.

When construction operations are being conducted on this well, the operator shall have the approved APD and Conditions of Approval (COA) on the well site and they shall be made available upon request by the Authorized Officer.

### **B. TOPSOIL**

The operator shall strip the top portion of the soil (root zone) from the entire well pad area and stockpile the topsoil along the edge of the well pad as depicted in the APD. The root zone is typically six (6) inches in depth. All the stockpiled topsoil will be redistributed over the interim reclamation areas. Topsoil shall not be used for berming the pad or facilities. For final reclamation, the topsoil shall be spread over the entire pad area for seeding preparation.

Other subsoil (below six inches) stockpiles must be completely segregated from the topsoil stockpile. Large rocks or subsoil clods (not evident in the surrounding terrain) must be buried within the approved area for interim and final reclamation.

### **C. CLOSED LOOP SYSTEM**

Tanks are required for drilling operations: No Pits.

The operator shall properly dispose of drilling contents at an authorized disposal site.

### **D. FEDERAL MINERAL MATERIALS PIT**

Payment shall be made to the BLM prior to removal of any federal mineral materials. Call the Carlsbad Field Office at (575) 234-5972.

### **E. WELL PAD SURFACING**

Surfacing of the well pad is not required.

If the operator elects to surface the well pad, the surfacing material may be required to be removed at the time of reclamation. The well pad shall be constructed in a manner which creates the smallest possible surface disturbance, consistent with safety and operational needs.

### **F. EXCLOSURE FENCING (CELLARS & PITS)**

**Exclosure Fencing**

The operator will install and maintain exclosure fencing for all open well cellars to prevent access to public, livestock, and large forms of wildlife before and after drilling operations until the pit is free of fluids and the operator initiates backfilling. (For examples of exclosure fencing design, refer to BLM's Oil and Gas Gold Book, Exclosure Fence Illustrations, Figure 1, Page 18.)

**G. ON LEASE ACCESS ROADS****Road Width**

The access road shall have a driving surface that creates the smallest possible surface disturbance and does not exceed fourteen (14) feet in width. The maximum width of surface disturbance, when constructing the access road, shall not exceed twenty-five (25) feet.

**Surfacing**

Surfacing material is not required on the new access road driving surface. If the operator elects to surface the new access road or pad, the surfacing material may be required to be removed at the time of reclamation.

Where possible, no improvements should be made on the unsurfaced access road other than to remove vegetation as necessary, road irregularities, safety issues, or to fill low areas that may sustain standing water.

The Authorized Officer reserves the right to require surfacing of any portion of the access road at any time deemed necessary. Surfacing may be required in the event the road deteriorates, erodes, road traffic increases, or it is determined to be beneficial for future field development. The surfacing depth and type of material will be determined at the time of notification.

**Crowning**

Crowning shall be done on the access road driving surface. The road crown shall have a grade of approximately 2% (i.e., a 1" crown on a 14' wide road). The road shall conform to Figure 1; cross section and plans for typical road construction.

**Ditching**

Ditching shall be required on both sides of the road.


**Turnouts**

Vehicle turnouts shall be constructed on the road. Turnouts shall be intervisible with interval spacing distance less than 1000 feet. Turnouts shall conform to Figure 1; cross section and plans for typical road construction.

**Drainage**

Drainage control systems shall be constructed on the entire length of road (e.g. ditches, sidehill out sloping and insloping, lead-off ditches, culvert installation, and low water crossings).

A typical lead-off ditch has a minimum depth of 1 foot below and a berm of 6 inches above natural ground level. The berm shall be on the down-slope side of the lead-off ditch.



All lead-off ditches shall be graded to drain water with a 1 percent minimum to 3 percent maximum ditch slope. The spacing interval are variable for lead-off ditches and shall be determined according to the formula for spacing intervals of lead-off ditches, but may be amended depending upon existing soil types and centerline road slope (in %);

**Formula for Spacing Interval of Lead-off Ditches**

Example - On a 4% road slope that is 400 feet long, the water flow shall drain water into a lead-off ditch. Spacing interval shall be determined by the following formula:

$$400 \text{ foot road with } 4\% \text{ road slope: } \frac{400'}{4\%} + 100' = 200' \text{ lead-off ditch interval}$$

**Cattle guards**

An appropriately sized cattle guard sufficient to carry out the project shall be installed and maintained at fence/road crossings. Any existing cattle guards on the access road route shall be repaired or replaced if they are damaged or have deteriorated beyond practical use. The operator shall be responsible for the condition of the existing cattle guards that are in place and are utilized during lease operations.

**Fence Requirement**

Where entry is granted across a fence line, the fence shall be braced and tied off on both sides of the passageway prior to cutting. The operator shall notify the private surface landowner or the grazing allotment holder prior to crossing any fences.

**Public Access**

Public access on this road shall not be restricted by the operator without specific written approval granted by the Authorized Officer.

**Construction Steps**

1. Salvage topsoil
2. Construct road
3. Redistribute topsoil
4. Revegetate slopes




Figure 1. Cross-sections and plans for typical road sections representative of BLM resource or FS local and higher-class roads.

## VII. PRODUCTION (POST DRILLING)

### A. WELL STRUCTURES & FACILITIES

#### Placement of Production Facilities

Production facilities should be placed on the well pad to allow for maximum interim recontouring and revegetation of the well location.

#### Exclosure Netting (Open-top Tanks)

Immediately following active drilling or completion operations, the operator will take actions necessary to prevent wildlife and livestock access, including avian wildlife, to all open-topped tanks that contain or have the potential to contain salinity sufficient to cause harm to wildlife or livestock, hydrocarbons, or Resource Conservation and Recovery Act of 1976-exempt hazardous substances. At a minimum, the operator will net, screen, or cover open-topped tanks to exclude wildlife and livestock and prevent mortality. If the operator uses netting, the operator will cover and secure the open portion of the tank to prevent wildlife entry. The operator will net, screen, or cover the tanks until the operator removes the tanks from the location or the tanks no longer contain substances that could be harmful to wildlife or livestock. Use a maximum netting mesh size of 1 ½ inches. The netting must not be in contact with fluids and must not have holes or gaps.

#### Chemical and Fuel Secondary Containment and Exclosure Screening

The operator will prevent all hazardous, poisonous, flammable, and toxic substances from coming into contact with soil and water. At a minimum, the operator will install and maintain an impervious secondary containment system for any tank or barrel containing hazardous, poisonous, flammable, or toxic substances sufficient to contain the contents of the tank or barrel and any drips, leaks, and anticipated precipitation. The operator will dispose of fluids within the containment system that do not meet applicable state or U. S. Environmental Protection Agency livestock water standards in accordance with state law; the operator must not drain the fluids to the soil or ground. The operator will design, construct, and maintain all secondary containment systems to prevent wildlife and livestock exposure to harmful substances. At a minimum, the operator will install effective wildlife and livestock exclosure systems such as fencing, netting, expanded metal mesh, lids, and grate covers. Use a maximum netting mesh size of 1 ½ inches.

#### Open-Vent Exhaust Stack Exclosures

The operator will construct, modify, equip, and maintain all open-vent exhaust stacks on production equipment to prevent birds and bats from entering, and to discourage perching, roosting, and nesting. (*Recommended exclosure structures on open-vent exhaust stacks are in the shape of a cone.*) Production equipment includes, but may not be limited to, tanks, heater-treaters, separators, dehydrators, flare stacks, in-line units, and compressor mufflers.

#### Containment Structures

Proposed production facilities such as storage tanks and other vessels will have a secondary containment structure that is constructed to hold the capacity of 1.5 times the largest tank, plus

freeboard to account for precipitation, unless more stringent protective requirements are deemed necessary.

**Painting Requirement**

All above-ground structures including meter housing that are not subject to safety requirements shall be painted a flat non-reflective paint color, **Shale Green** from the BLM Standard Environmental Color Chart (CC-001: June 2008).

**STANDARD STIPULATIONS FOR OIL AND GAS RELATED SITES**

A copy of the application (Grant/Sundry Notice) and attachments, including stipulations and map, will be on location during construction. BLM personnel may request to view a copy of your permit during construction to ensure compliance with all stipulations.

The holder agrees to comply with the following stipulations to the satisfaction of the Authorized Officer, BLM.

1. The holder shall indemnify the United States against any liability for damage to life or property arising from the occupancy or use of public lands under this grant and for all response costs, penalties, damages, claims, and other costs arising from the provisions of the Resource Conservation and Recovery Act (RCRA), 42 U.S.C. Chap. 82, Section 6901 et. seq., from the Comprehensive Environmental Response, Compensation and Liability Act (CERCLA), 42 U.S.C. Chap. 109, Section 9601 et. seq., and from other applicable environmental statutes.
2. The holder shall comply with all applicable Federal laws and regulations existing or hereafter enacted or promulgated. In any event, the holder shall comply with the Toxic Substances Control Act of 1976, as amended (15 U.S.C. 2601, et. seq.) with regard to any toxic substances that are used, generated by or stored on the right-of-way or on facilities authorized by this grant. (See 40 CFR, Part 702-799 and especially, provisions on polychlorinated biphenyls, 40 CFR 761.1-761.193.) Additionally, any release of toxic substances (leaks, spills, etc.) in excess of the reportable quantity established by 40 CFR, Part 117 shall be reported as required by the Comprehensive Environmental Response, Compensation and Liability Act, Section 102b. A copy of any report required or requested by any Federal agency or State government as a result of a reportable release or spill of any toxic substances shall be furnished to the Authorized Officer concurrent with the filing of the reports to the involved Federal agency or State government.
3. The holder agrees to indemnify the United States against any liability arising from the release of any hazardous substance or hazardous waste (as these terms are defined in the Comprehensive Environmental Response, Compensation and Liability Act of 1980, 42 U.S.C. 9601, et. seq. or the Resource Conservation and Recovery Act, 42 U.S.C. 6901, et. seq.) on the right-of-way (unless the release or threatened release is wholly unrelated to the right-of-way holder's activity on the right-of-way). This agreement applies without regard to whether a release is caused by the holder, its agent, or unrelated third parties.

4. If, during any phase of the construction, operation, maintenance, or termination of the site or related pipeline(s), any oil or other pollutant should be discharged from site facilities, the pipeline(s) or from containers or vehicles impacting Federal lands, the control and total removal, disposal, and cleanup of such oil or other pollutant, wherever found, shall be the responsibility of the holder, regardless of fault. Upon failure of the holder to control, dispose of, or clean up such discharge on or affecting Federal lands, or to repair all damages to Federal lands resulting therefrom, the Authorized Officer may take such measures as deemed necessary to control and cleanup the discharge and restore the area, including, where appropriate, the aquatic environment and fish and wildlife habitats, at the full expense of the holder. Such action by the Authorized Officer shall not relieve the holder of any liability or responsibility.
5. Sites shall be maintained in an orderly, sanitary condition at all times. Waste materials, both liquid and solid, shall be disposed of promptly at an appropriate, authorized waste disposal facility in accordance with all applicable State and Federal laws. "Waste" means all discarded matter including, but not limited to, human waste, trash, garbage, refuse, petroleum products, brines, chemicals, oil drums, ashes, and equipment.
6. The operator will notify the Bureau of Land Management (BLM) authorized officer and nearest Fish and Wildlife Service (FWS) Law Enforcement office within 24 hours, if the operator discovers a dead or injured federally protected species (i.e., migratory bird species, bald or golden eagle, or species listed by the FWS as threatened or endangered) in or adjacent to a pit, trench, tank, exhaust stack, or fence. (If the operator is unable to contact the FWS Law Enforcement office, the operator must contact the nearest FWS Ecological Services office.)
7. All above-ground structures not subject to safety requirements shall be painted by the holder to blend with the natural color of the landscape. The paint used shall be a color which simulates "Standard Environmental Colors" designated by the Rocky Mountain Five-State Interagency Committee. The color selected for this project is **Shale Green**, Munsell Soil Color Chart Number 5Y 4/2.
8. Any cultural and/or paleontological resource (historic or prehistoric site or object) discovered by the holder, or any person working on the holder's behalf, on public or Federal land shall be immediately reported to the Authorized Officer. The holder shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery will be made by the Authorized Officer to determine appropriate actions to prevent the loss of significant cultural or scientific values. The holder will be responsible for the cost of evaluation and any decision as to the proper mitigation measures will be made by the Authorized Officer after consulting with the holder.
9. A sales contract for removal of mineral material (caliche, sand, gravel, fill dirt) from an authorized pit, site, or on location must be obtained from the BLM prior to commencing construction. There are several options available for purchasing mineral material: contact the BLM office (575-234-5972).

10. The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes the roads, pads, associated pipeline corridor, and adjacent land affected by the establishment of weeds due to this action. The operator shall consult with the Authorized Officer for acceptable weed control methods, which include following EPA and BLM requirements and policies.

11. Once the site is no longer in service or use, the site must undergo final abandonment. At final abandonment, the site and access roads must undergo "final" reclamation so that the character and productivity of the land are restored. Earthwork for final reclamation must be completed within six (6) months of the abandonment of the site. All pads and facility locations and roads must be reclaimed to a satisfactory revegetated, safe, and stable condition, unless an agreement is made with the landowner or BLM to keep the road and/or pad intact. After all disturbed areas have been satisfactorily prepared, these areas need to be revegetated with the seed mixture provided. Seeding should be accomplished by drilling on the contour whenever practical or by other approved methods. Seeding may need to be repeated until revegetation is successful, as determined by the BLM.

Operators shall contact a BLM surface protection specialist prior to surface abandonment operations for site specific objectives (Jim Amos: 575-234-5909).

12. The holder shall stockpile an adequate amount of topsoil where blading occurs. The topsoil to be stripped is approximately 6 inches in depth. The topsoil will be segregated from other spoil piles. The topsoil will be used for final reclamation.

13. The holder will reseed all disturbed areas. Seeding will be done according to the attached seeding requirements, using the following seed mix.

- |  |  |
|--|--|
| <input type="checkbox"/> seed mixture 1            | <input type="checkbox"/> seed mixture 3          |
| <input checked="" type="checkbox"/> seed mixture 2 | <input type="checkbox"/> seed mixture 4          |
| <input type="checkbox"/> seed mixture 2/LPC        | <input type="checkbox"/> Aplomado Falcon Mixture |

14. In those areas where erosion control structures are required to stabilize soil conditions, the holder shall install such structures as are suitable for the specific soil conditions being encountered and which are in accordance with sound management practices. Any earth work will require prior approval by the Authorized Officer.

15. Open-topped Tanks - The operator will take actions necessary to prevent wildlife and livestock access, including avian wildlife, to all open-topped tanks that contain or have the potential to contain salinity sufficient to cause harm to wildlife or livestock, hydrocarbons, or Resource Conservation and Recovery Act of 1976-exempt hazardous substances. At a minimum, the operator will net, screen, or cover open-topped tanks to exclude wildlife and livestock and prevent mortality. If the operator uses netting, the operator will cover and secure the open portion of the tank to prevent wildlife entry. The operator will net, screen, or cover the tanks until the operator removes the tanks from the location or the tanks no longer contain substances that could be harmful to wildlife or livestock. Use a maximum netting mesh size of 1 ½ inches. The netting must not be in contact with fluids and must not have holes or gaps

16. The operator will prevent all hazardous, poisonous, flammable, and toxic substances from coming into contact with soil and water. At a minimum, the operator will install and maintain an

impervious secondary containment system for any tank or barrel containing hazardous, poisonous, flammable, or toxic substances sufficient to contain the contents of the tank or barrel and any drips, leaks, and anticipated precipitation. The operator will dispose of fluids within the containment system that do not meet applicable state or U. S. Environmental Protection Agency livestock water standards in accordance with state law; the operator must not drain the fluids to the soil or ground. The operator will design, construct, and maintain all secondary containment systems to prevent wildlife and livestock exposure to harmful substances. At a minimum, the operator will install effective wildlife and livestock enclosure systems such as fencing, netting, expanded metal mesh, lids, and grate covers. Use a maximum netting mesh size of 1 ½ inches.

17. Open-Vent Exhaust Stack Enclosures – The operator will construct, modify, equip, and maintain all open-vent exhaust stacks on production equipment to prevent birds and bats from entering, and to discourage perching, roosting, and nesting. (Recommended enclosure structures on open-vent exhaust stacks are in the shape of a cone.) Production equipment includes, but may not be limited to, tanks, heater-treaters, separators, dehydrators, flare stacks, in-line units, and compressor mufflers.

18. Containment Structures - Proposed production facilities such as storage tanks and other vessels will have a secondary containment structure that is constructed to hold the capacity of 1.5 times the largest tank, plus freeboard to account for precipitation, unless more stringent protective requirements are deemed necessary.

## **B. PIPELINES**

### **BURIED PIPELINE STIPULATIONS**

A copy of the application (Grant, APD, or Sundry Notice) and attachments, including conditions of approval, survey plat and/or map, will be on location during construction. BLM personnel may request to you a copy of your permit during construction to ensure compliance with all stipulations.

Holder agrees to comply with the following stipulations to the satisfaction of the Authorized Officer:

1. The Holder shall indemnify the United States against any liability for damage to life or property arising from the occupancy or use of public lands under this grant.

2. The Holder shall comply with all applicable Federal laws and regulations existing or hereafter enacted or promulgated. In any event, the holder shall comply with the Toxic Substances Control Act of 1976 as amended, 15 USC 2601 et seq. (1982) with regards to any toxic substances that are used, generated by or stored on the right-of-way or on facilities authorized under this right-of-way grant. (See 40 CFR Part 702-799 and especially, provisions on polychlorinated biphenyls, 40 CFR 761.1-761.193.) Additionally, any release of toxic substances (leaks, spills, etc.) in excess of the reportable quantity established by 40 CFR Part 117 shall be reported as required by the Comprehensive Environmental Response, Compensation, and Liability Act, section 102b. A copy of any report required or requested by any Federal agency or State government as a result of a reportable release or spill of any toxic substances shall be furnished to the authorized officer concurrent with the filing of the reports to the involved Federal agency or State government.

3. The holder agrees to indemnify the United States against any liability arising from the release of any hazardous substance or hazardous waste (as these terms are defined in the Comprehensive Environmental Response, Compensation and Liability Act of 1980, 42 U.S.C. 9601, et seq. or the Resource Conservation and Recovery Act, 42 U.S.C.6901, et seq.) on the Right-of-Way (unless the release or threatened release is wholly unrelated to the Right-of-Way holder's activity on the Right-of-Way), or resulting from the activity of the Right-of-Way holder on the Right-of-Way. This agreement applies without regard to whether a release is caused by the holder, its agent, or unrelated third parties.

4. If, during any phase of the construction, operation, maintenance, or termination of the pipeline, any oil or other pollutant should be discharged from the pipeline system, impacting Federal lands, the control and total removal, disposal, and cleaning up of such oil or other pollutant, wherever found, shall be the responsibility of holder, regardless of fault. Upon failure of holder to control, dispose of, or clean up such discharge on or affecting Federal lands, or to repair all damages resulting therefrom, on the Federal lands, the Authorized Officer may take such measures as he deems necessary to control and clean up the discharge and restore the area, including where appropriate, the aquatic environment and fish and wildlife habitats, at the full expense of the holder. Such action by the Authorized Officer shall not relieve holder of any responsibility as provided herein.

5. All construction and maintenance activity will be confined to the authorized right-of-way.

6. The pipeline will be buried with a minimum cover of 36 inches between the top of the pipe and ground level.

7. The maximum allowable disturbance for construction in this right-of-way will be 30 feet:

- Blading of vegetation within the right-of-way will be allowed: maximum width of blading operations will not exceed 20 feet. The trench is included in this area. (*Blading is defined as the complete removal of brush and ground vegetation.*)
- Clearing of brush species within the right-of-way will be allowed: maximum width of clearing operations will not exceed 30 feet. The trench and bladed area are included in this area. (*Clearing is defined as the removal of brush while leaving ground vegetation (grasses, weeds, etc.) intact. Clearing is best accomplished by holding the blade 4 to 6 inches above the ground surface.*)
- The remaining area of the right-of-way (if any) shall only be disturbed by compressing the vegetation. (*Compressing can be caused by vehicle tires, placement of equipment, etc.*)

8. The holder shall stockpile an adequate amount of topsoil where blading is allowed. The topsoil to be stripped is approximately 6 inches in depth. The topsoil will be segregated from other spoil piles from trench construction. The topsoil will be evenly distributed over the bladed area for the preparation of seeding.

9. The holder shall minimize disturbance to existing fences and other improvements on public lands. The holder is required to promptly repair improvements to at least their former state. Functional use of these improvements will be maintained at all times. The holder will contact the owner of any improvements prior to disturbing them. When necessary to pass through a fence line, the fence shall be braced on both sides of the passageway prior to cutting of the fence. No permanent gates will be allowed unless approved by the Authorized Officer.

10. Vegetation, soil, and rocks left as a result of construction or maintenance activity will be randomly scattered on this right-of-way and will not be left in rows, piles, or berms, unless otherwise approved by the Authorized Officer. The entire right-of-way shall be recontoured to match the surrounding landscape. The backfilled soil shall be compacted and a 6 inch berm will be left over the ditch line to allow for settling back to grade.

11. In those areas where erosion control structures are required to stabilize soil conditions, the holder will install such structures as are suitable for the specific soil conditions being encountered and which are in accordance with sound resource management practices.

12. The holder will reseed all disturbed areas. Seeding will be done according to the attached seeding requirements, using the following seed mix.

- |  |  |
|--|--|
| <input type="checkbox"/> seed mixture 1            | <input type="checkbox"/> seed mixture 3          |
| <input checked="" type="checkbox"/> seed mixture 2 | <input type="checkbox"/> seed mixture 4          |
| <input type="checkbox"/> seed mixture 2/LPC        | <input type="checkbox"/> Aplomado Falcon Mixture |

13. All above-ground structures not subject to safety requirements shall be painted by the holder to blend with the natural color of the landscape. The paint used shall be color which simulates "Standard Environmental Colors" – **Shale Green**, Munsell Soil Color No. 5Y 4/2.

14. The pipeline will be identified by signs at the point of origin and completion of the right-of-way and at all road crossings. At a minimum, signs will state the holder's name, BLM serial number, and the product being transported. All signs and information thereon will be posted in a permanent, conspicuous manner, and will be maintained in a legible condition for the life of the pipeline.

15. The holder shall not use the pipeline route as a road for purposes other than routine maintenance as determined necessary by the Authorized Officer in consultation with the holder before maintenance begins. The holder will take whatever steps are necessary to ensure that the pipeline route is not used as a roadway. As determined necessary during the life of the pipeline, the Authorized Officer may ask the holder to construct temporary deterrence structures.

16. Any cultural and/or paleontological resources (historic or prehistoric site or object) discovered by the holder, or any person working on his behalf, on public or Federal land shall be immediately reported to the Authorized Officer. Holder shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery will be made by the Authorized Officer to determine appropriate actions to prevent the loss of significant cultural or scientific values. The holder will be responsible for the cost of evaluation and any decision as to proper mitigation measures will be made by the Authorized Officer after consulting with the holder.

17. The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes associated roads, pipeline corridor and adjacent land affected by the establishment of weeds due to this action. The operator shall consult with the Authorized Officer for acceptable weed control methods, which include following EPA and BLM requirements and policies.

18. Escape Ramps - The operator will construct and maintain pipeline/utility trenches that are not otherwise fenced, screened, or netted to prevent livestock, wildlife, and humans from becoming entrapped. At a minimum, the operator will construct and maintain escape ramps, ladders, or

other methods of avian and terrestrial wildlife escape in the trenches according to the following criteria:

- a. Any trench left open for eight (8) hours or less is not required to have escape ramps; however, before the trench is backfilled, the contractor/operator shall inspect the trench for wildlife, remove all trapped wildlife, and release them at least 100 yards from the trench.
- b. For trenches left open for eight (8) hours or more, earthen escape ramps (built at no more than a 30 degree slope and spaced no more than 500 feet apart) shall be placed in the trench.

### C. ELECTRIC LINES

#### STANDARD STIPULATIONS FOR OVERHEAD ELECTRIC DISTRIBUTION LINES

**A copy of the grant and attachments, including stipulations, survey plat and/or map, will be on location during construction. BLM personnel may request to you a copy of your permit during construction to ensure compliance with all stipulations.**

Holder agrees to comply with the following stipulations to the satisfaction of the Authorized Officer:

1. The holder shall indemnify the United States against any liability for damage to life or property arising from the occupancy or use of public lands under this grant.
2. The holder shall comply with all applicable Federal laws and regulations existing or hereafter enacted or promulgated. In any event, the holder shall comply with the Toxic Substances Control Act of 1976 as amended, 15 USC 2601 et seq. (1982) with regards to any toxic substances that are used, generated by or stored on the right-of-way or on facilities authorized under this right-of-way grant. (See 40 CFR, Part 702-799 and especially, provisions on polychlorinated biphenyls, 40 CFR 761.1-761.193.) Additionally, any release of toxic substances (leaks, spills, etc.) in excess of the reportable quantity established by 40 CFR, Part 117 shall be reported as required by the Comprehensive Environmental Response, Compensation, and Liability Act, section 102b. A copy of any report required or requested by any Federal agency or State government as a result of a reportable release or spill of any toxic substances shall be furnished to the authorized officer concurrent with the filing of the reports to the involved Federal agency or State government.
3. The holder agrees to indemnify the United States against any liability arising from the release of any hazardous substance or hazardous waste (as these terms are defined in the Comprehensive Environmental Response, Compensation and Liability Act of 1980, 42 U.S.C. 9601, et seq. or the Resource Conservation and Recovery Act, 42 U.S.C. 6901, et seq.) on the Right-of-Way (unless the release or threatened release is wholly unrelated to the Right-of-Way holder's activity on the Right-of-Way), or resulting from the activity of the Right-of-Way holder on the Right-of-Way. This agreement applies without regard to whether a release is caused by the holder, its agent, or unrelated third parties.

4. There will be no clearing or blading of the right-of-way unless otherwise agreed to in writing by the Authorized Officer.

5. Power lines shall be constructed and designed in accordance to standards outlined in "Suggested Practices for Avian Protection on Power lines: The State of the Art in 2006" Edison Electric Institute, APLIC, and the California Energy Commission 2006 . The holder shall assume the burden and expense of proving that pole designs not shown in the above publication deter raptor perching, roosting, and nesting. Such proof shall be provided by a raptor expert approved by the Authorized Officer. The BLM reserves the right to require modification or additions to all powerline structures placed on this right-of-way, should they be necessary to ensure the safety of large perching birds. Such modifications and/or additions shall be made by the holder without liability or expense to the United States.

Raptor deterrence will consist of but not limited to the following: triangle perch discouragers shall be placed on each side of the cross arms and a nonconductive perching deterrence shall be placed on all vertical poles that extend past the cross arms.

6. The holder shall minimize disturbance to existing fences and other improvements on public lands. The holder is required to promptly repair improvements to at least their former state. Functional use of these improvements will be maintained at all times. The holder will contact the owner of any improvements prior to disturbing them. When necessary to pass through a fence line, the fence shall be braced on both sides of the passageway prior to cutting the fence. No permanent gates will be allowed unless approved by the Authorized Officer.

7. The BLM serial number assigned to this authorization shall be posted in a permanent, conspicuous manner where the power line crosses roads and at all serviced facilities. Numbers will be at least two inches high and will be affixed to the pole nearest the road crossing and at the facilities served.

8. Upon cancellation, relinquishment, or expiration of this grant, the holder shall comply with those abandonment procedures as prescribed by the Authorized Officer.

9. All surface structures (poles, lines, transformers, etc.) shall be removed within 180 days of abandonment, relinquishment, or termination of use of the serviced facility or facilities or within 180 days of abandonment, relinquishment, cancellation, or expiration of this grant, whichever comes first. This will not apply where the power line extends service to an active, adjoining facility or facilities.

10. Any cultural and/or paleontological resource (historic or prehistoric site or object) discovered by the holder, or any person working on his behalf, on public or Federal land shall be immediately reported to the Authorized Officer. Holder shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery will be made by the

Authorized Officer to determine appropriate actions to prevent the loss of significant cultural or scientific values. The holder will be responsible for the cost of evaluation and any decision as to proper mitigation measures will be made by the Authorized Officer after consulting with the holder.

11. Special Stipulations:

- For reclamation remove poles, lines, transformer, etc. and dispose of properly.
- Fill in any holes from the poles removed.

## **VIII. INTERIM RECLAMATION**

During the life of the development, all disturbed areas not needed for active support of production operations should undergo interim reclamation in order to minimize the environmental impacts of development on other resources and uses.

Within six (6) months of well completion, operators should work with BLM surface management specialists (Jim Amos: 575-234-5909) to devise the best strategies to reduce the size of the location. Interim reclamation should allow for remedial well operations, as well as safe and efficient removal of oil and gas.

During reclamation, the removal of caliche is important to increasing the success of revegetating the site. Removed caliche that is free of contaminants may be used for road repairs, fire walls or for building other roads and locations. In order to operate the well or complete workover operations, it may be necessary to drive, park and operate on restored interim vegetation within the previously disturbed area. Disturbing revegetated areas for production or workover operations will be allowed. If there is significant disturbance and loss of vegetation, the area will need to be revegetated. Communicate with the appropriate BLM office for any exceptions/exemptions if needed.

All disturbed areas after they have been satisfactorily prepared need to be reseeded with the seed mixture provided below.

Upon completion of interim reclamation, the operator shall submit a Sundry Notices and Reports on Wells, Subsequent Report of Reclamation (Form 3160-5).

## **IX. FINAL ABANDONMENT & RECLAMATION**

At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land are restored.

Earthwork for final reclamation must be completed within six (6) months of well plugging. All pads, pits, facility locations and roads must be reclaimed to a satisfactory revegetated, safe, and stable condition, unless an agreement is made with the landowner or BLM to keep the road and/or pad intact.

After all disturbed areas have been satisfactorily prepared, these areas need to be revegetated with the seed mixture provided below. Seeding should be accomplished by drilling on the contour whenever practical or by other approved methods. Seeding may need to be repeated until revegetation is successful, as determined by the BLM.

Operators shall contact a BLM surface protection specialist prior to surface abandonment operations for site specific objectives (Jim Amos: 575-234-5909).

Ground-level Abandoned Well Marker to avoid raptor perching: Upon the plugging and subsequent abandonment of the well, the well marker will be installed at ground level on a plate containing the pertinent information for the plugged well.

Seed Mixture 2, for Sandy Sites

The holder shall seed all disturbed areas with the seed mixture listed below. The seed mixture shall be planted in the amounts specified in pounds of pure live seed (PLS)\* per acre. There shall be no primary or secondary noxious weeds in the seed mixture. Seed will be tested and the viability testing of seed will be done in accordance with State law (s) and within nine (9) months prior to purchase. Commercial seed will be either certified or registered seed. The seed container will be tagged in accordance with State law(s) and available for inspection by the authorized officer.

Seed will be planted using a drill equipped with a depth regulator to ensure proper depth of planting where drilling is possible. The seed mixture will be evenly and uniformly planted over the disturbed area (smaller/heavier seeds have a tendency to drop the bottom of the drill and are planted first). The holder shall take appropriate measures to ensure this does not occur. Where drilling is not possible, seed will be broadcast and the area shall be raked or chained to cover the seed. When broadcasting the seed, the pounds per acre are to be doubled. The seeding will be repeated until a satisfactory stand is established as determined by the authorized officer. Evaluation of growth will not be made before completion of at least one full growing season after seeding.

Species to be planted in pounds of pure live seed\* per acre:

<u>Species</u>	<u>lb/acre</u>
Sand dropseed (Sporobolus cryptandrus)	1.0
Sand love grass (Eragrostis trichodes)	1.0
Plains bristlegrass (Setaria macrostachya)	2.0

\*Pounds of pure live seed:

Pounds of seed x percent purity x percent germination = pounds pure live seed

**PECOS DISTRICT  
SURFACE USE  
CONDITIONS OF APPROVAL**

OPERATOR'S NAME:	DEVON ENERGY PRODUCTION
LEASE NO.:	NMNM114990
WELL NAME & NO.:	4H -JAYHAWK 6-7 FED FEE COM
SURFACE HOLE FOOTAGE:	515'/N & 530'/E
BOTTOM HOLE FOOTAGE:	330'/S & 1284'/E
LOCATION:	Section. 6., T26S., R.34E., NMP
COUNTY:	LEA County, New Mexico

**TABLE OF CONTENTS**

Standard Conditions of Approval (COA) apply to this APD. If any deviations to these standards exist or special COAs are required, the section with the deviation or requirement will be checked below.

- General Provisions**
- Permit Expiration**
- Archaeology, Paleontology, and Historical Sites**
- Noxious Weeds**
- Special Requirements**
  - Escape Ramps
  - Well and CTB Pad Berms
  - Range
  - Watershed
  - Karst
- Construction**
  - Notification
  - Topsoil
  - Closed Loop System
  - Federal Mineral Material Pits
  - Well Pads
  - Roads
- Road Section Diagram**
- Production (Post Drilling)**
  - Well Structures & Facilities
  - Pipelines
  - Electric Lines
- Interim Reclamation**
- Final Abandonment & Reclamation**

## **I. GENERAL PROVISIONS**

The approval of the Application For Permit To Drill (APD) is in compliance with all applicable laws and regulations: 43 Code of Federal Regulations 3160, the lease terms, Onshore Oil and Gas Orders, Notices To Lessees, New Mexico Oil Conservation Division (NMOCD) Rules, National Historical Preservation Act As Amended, and instructions and orders of the Authorized Officer. Any request for a variance shall be submitted to the Authorized Officer on Form 3160-5, Sundry Notices and Report on Wells.

## **II. PERMIT EXPIRATION**

If the permit terminates prior to drilling and drilling cannot be commenced within 60 days after expiration, an operator is required to submit Form 3160-5, Sundry Notices and Reports on Wells, requesting surface reclamation requirements for any surface disturbance. However, if the operator will be able to initiate drilling within 60 days after the expiration of the permit, the operator must have set the conductor pipe in order to allow for an extension of 60 days beyond the expiration date of the APD. (Filing of a Sundry Notice is required for this 60 day extension.)

## **III. ARCHAEOLOGICAL, PALEONTOLOGY & HISTORICAL SITES**

Any cultural and/or paleontological resource discovered by the operator or by any person working on the operator's behalf shall immediately report such findings to the Authorized Officer. The operator is fully accountable for the actions of their contractors and subcontractors. The operator shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery shall be made by the Authorized Officer to determine the appropriate actions that shall be required to prevent the loss of significant cultural or scientific values of the discovery. The operator shall be held responsible for the cost of the proper mitigation measures that the Authorized Officer assesses after consultation with the operator on the evaluation and decisions of the discovery. Any unauthorized collection or disturbance of cultural or paleontological resources may result in a shutdown order by the Authorized Officer.

## **IV. NOXIOUS WEEDS**

The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes the roads, pads, associated pipeline corridor, and adjacent land affected by the establishment of weeds due to this action. The operator shall consult with the Authorized Officer for acceptable weed control methods, which include following EPA and BLM requirements and policies.

## V. SPECIAL REQUIREMENT(S)

In May 2008, the Pecos District Special Status Species Resource Management Plan Amendment (RMPA) was approved and is being implemented. In addition to the standard practices that minimize impacts, as listed above, the following COA will apply:

- Upon abandonment, a low profile abandoned well marker will be installed to prevent raptor perching.

Power lines shall be constructed and designed in accordance to standards outlined in "Suggested Practices for Avian Protection on Power lines: The State of the Art in 2006" Edison Electric Institute, APLIC, and the California Energy Commission 2006. The holder shall assume the burden and expense of proving that pole designs not shown in the above publication deter raptor perching, roosting, and nesting. Such proof shall be provided by a raptor expert approved by the Authorized Officer. The BLM reserves the right to require modification or additions to all power line structures placed on this right-of-way, should they be necessary to ensure the safety of large perching birds. The holder without liability or expense shall make such modifications and/or additions to the United States.

### **Trenches-Escape Ramps**

Devon would need to construct and maintain escape ramps according to the following criteria:

- Earthen escape ramps would be required to be constructed to sufficiently support livestock at no more than a 30- degree slope and spaced no more than 500 feet apart.
- If the trench is left open under an 8-hour time period, it would not be required to have an escape ramp; however, before the trench is backfilled the trench will be inspected for wildlife and remove any species that are trapped at a distance of at least 100 yards away from the trench.

### **Well and CTB Pad Berms**

- The entire well pad will be bermed to prevent oil, salt, and other chemical contaminants from leaving the well pad. Topsoil shall not be used to construct the berm. No water flow from the uphill side(s) of the pad shall be allowed to enter the well pad. The berm shall be maintained through the life of the well and after interim reclamation has been completed.
- Any water erosion that may occur due to the construction of the well pad during the life of the well will be quickly corrected and proper measures will be taken to prevent future erosion.
- Tank battery locations will be line and bermed. A 20-mil permanent liner will be installed with a 4 oz. felt backing to prevent tears or punctures. Tank battery berms must be large enough to contain 1 ½ times the content of the largest tank.
- Stockpiling of topsoil is required. The top soil shall be stockpiled in an appropriate location to prevent loss of soil due to water or wind erosion and not used for berming or erosion control.

### Fence Requirement

Where entry is granted across a fence line, the fence must be braced and tied off on both sides of the passageway with H-braces prior to cutting. Once the work is completed, the fence will be restored to its prior condition, or better. The operator shall notify the private surface landowner or the grazing allotment holder prior to crossing any fence(s).

### Livestock Watering Requirement

Any damage to structures that provide water to livestock throughout the life of the well, caused by operations from the well site, must be immediately corrected by the operator. The operator must

notify the BLM office (575-234-5972) and the private surface landowner or the grazing allotment holder if any damage occurs to structures that provide water to livestock.

#### Cattle Guard Requirement

Where entry is granted across a fence line for an access road, the fence must be braced and tied off on both sides of the passageway with H-braces prior to cutting. Once the work is completed, the fence will be restored to its prior condition with an appropriately sized cattle guard sufficient to carry out the project. Any new or existing cattle guards on the access route shall be repaired or replaced if they are damaged or have deteriorated beyond practical use. The operator shall be responsible for the condition of the existing cattle guards that are in place and are utilized during lease operations. Once the road is abandoned, the fence would be restored to its prior condition, or better. The operator shall notify the private surface landowner or the grazing allotment holder prior to crossing any fences.

The operator must contact the allotment holder prior to construction to identify the location of the pipeline. The operator must take measures to protect the pipeline from compression or other damages. If the pipeline is damaged or compromised in any way near the proposed project as a result of oil and gas activity, the operator is responsible for repairing the pipeline immediately. The operator must notify the BLM office (575-234-5972) and the private surface landowner or the grazing allotment holder if any damage occurs to structures that provide water to livestock.

During construction, the proponent shall minimize disturbance to existing fences, water lines, troughs, windmills, and other improvements on public lands. The proponent is required to promptly repair improvements to at least their former state. Functional use of these improvements will be maintained at all times. The holder will contact the grazing permittee/leasee prior to disturbing any range improvement projects. When necessary to pass through a fence line, the fence shall be braced on both sides of the passageway prior to cutting of the fence. No permanent gates will be allowed unless approved by the Authorized Officer.

- The entire well pad will be bermed to prevent oil, salt, and other chemical contaminants from leaving the well pad. Topsoil shall not be used to construct the berm. No water flow from the uphill side(s) of the pad shall be allowed to enter the well pad. The berm shall be maintained through the life of the well and after interim reclamation has been completed.
- Any water erosion that may occur due to the construction of the well pad during the life of the well will be quickly corrected and proper measures will be taken to prevent future erosion.
- Tank battery locations will be lined and bermed. A 20-mil permanent liner will be installed with a 4 oz. felt backing to prevent tears or punctures. Tank battery berms must be large enough to contain 1 ½ times the content of the largest tank.
- Stockpiling of topsoil is required. The top soil shall be stockpiled in an appropriate location to prevent loss of soil due to water or wind erosion and not used for berming or erosion control.

#### **CONSTRUCTION IMPACT ANALYSIS**

The construction of roads, pipelines, compressor station pads and utilities can impact bedrock integrity and reroute, impede, focus, or erode natural surface drainage systems. Increased silting and sedimentation from construction can plug downstream sinkholes, caves, springs, and other components of aquifer recharge systems and result in adverse impacts to aquifer quality and cave environments. Any contaminants released into the environment during or after construction can impact aquifers and cave systems. A possibility exists for slow subsidence or sudden surface collapse during construction operations due to collapse of underlying cave passages and voids. This would cause associated safety hazards to the operator and the potential for increased environmental impact. Subsidence processes can be triggered by blasting, intense vibrations, rerouting of surface drainages, focusing of surface drainage, and general surface disturbance.

Blasting fractures in bedrock can serve as direct conduits for transfer of contaminants into cave and groundwater systems. Blasting also creates an expanded volume of rock rubble that cannot be reclaimed to natural contours, soil condition, or native vegetative condition. As such, surface and subsurface disruptions from blasting procedures can lead to permanent changes in vegetation, rainfall percolation, silting/erosion factors, aquifer recharge, and freshwater quality and can increase the risk of contaminant migration from drilling/production facilities built atop the blast are additional or special Conditions of Approval may apply at that time.

#### **CONSTRUCTION MITIGATION**

In order to mitigate the impacts from construction activities on cave and karst resources, the following Conditions of Approval will apply to this APD or project:

- In the event that any underground voids are encountered during construction activities, construction activities will be halted and the BLM will be notified immediately.
- No Blasting to prevent geologic structure instabilities.
- Pad Berming to minimize effects of any spilled contaminants.

#### **DRILLING IMPACT ANALYSIS**

During drilling, previously unknown cave and karst features could be encountered. If a void is encountered while drilling and a loss of circulation occurs, lost drilling fluids can directly contaminate groundwater recharge areas, aquifers, and groundwater quality. Drilling operations can also lead to sudden collapse of underground voids. Cementing operations may plug or alter groundwater flow, potentially reducing the water quantity at springs and water wells. Inadequate subsurface cementing, casing, and cave/aquifer protection measures can lead to the migration of oil, gas, drilling fluids, and produced saltwater into cave systems and freshwater aquifers.

#### **DRILLING MITIGATION**

Federal regulations and standard Conditions of Approval applied to all APDs require that adequate measures are taken to prevent contamination to the environment. Due to the extreme sensitivity of the cave and karst resources in this project area, the following additional Conditions of Approval will be added to this APD.

To prevent cave and karst resource contamination the following will be required.

- Closed Mud System Using Steel Tanks with All Fluids and Cuttings Hauled Off.
- Rotary drilling with fresh water where cave or karst features are expected to prevent contamination of freshwater aquifers.
- Directional Drilling allowed after at least 100 feet below the cave occurrence zone to prevent additional impacts resulting from directional drilling.
- Lost Circulation zones logged and reported in the drilling report so BLM can assess the situation and work with the operator on corrective actions.
- Additional drilling, casing, and cementing procedures to protect cave zones and fresh water aquifers. See Drilling COAs.

#### **PRODUCTION IMPACT ANALYSIS**

Production facilities such as tank batteries, pump-jacks, compressors, transfer stations, and pipe may fail and allow contaminants to enter caves and freshwater systems. Downhole casing and cementing failures can allow migration of fluids and/or gas between formations and aquifers. Facilities may also be subject to slow subsidence or sudden collapse of the underlying bedrock.

#### **PRODUCTION MITIGATION**

In order to mitigate the impacts from production activities and due to the nature of karst terrain, the following Conditions of Approval will apply to this APD:

- Tank battery liners and berms to minimize the impact resulting from leaks.
- Leak detection system to provide an early alert to operators when a leak has occurred.
- Automatic shut off, check valves, or similar systems will be installed for pipelines and tanks to minimize the effects of line failures used in production or drilling.

**RESIDUAL AND CUMULATIVE IMPACT ANALYSIS**

Any industrial activities that take place upon or within karst terrains or freshwater aquifer zones have the potential to create both short-term and long-term negative impacts to freshwater aquifers and cave systems. While a number of mitigation measures can be implemented to mitigate many impacts, it is still possible for impacts to occur from containment failures, well blowouts, accidents, spills, and structural collapses. It is therefore necessary to implement long-term monitoring studies to determine if current mitigations measures are sufficient enough to prevent long-term or cumulative impacts.

**RESIDUAL AND CUMULATIVE MITIGATION**

- Nontoxic fluorescent dyes will be added to the drilling fluid when the hole is spudded and will be circulated to the bottom of the karst layers. This provides data as part of a long-term monitoring study.
- Annual pressure monitoring will be performed by the operator. If the test results indicate a casing failure has occurred, remedial action will be undertaken to correct the problem to the BLM's approval.

**PLUGGING AND ABANDONMENT IMPACT ANALYSIS**

Failure of a plugged and abandoned well can lead to migration of contaminants to karst resources and fresh water aquifers. While this action does not specifically approve plugging and abandonment procedures, the operator should be made aware that additional or special Conditions of Approval may apply at that time.

**PLUGGING AND ABANDONMENT MITIGATION**

Abandonment Cementing: Upon well abandonment in high cave karst areas additional plugging conditions of approval may be required. The BLM will assess the situation and work with the operator to ensure proper plugging of the wellbore.

**MITIGATING MEASURES for ROADS:**

- Roads will be routed around sinkholes and other karst features to avoid or lessen the possibility of encountering near surface voids and to minimize changes to runoff or possible leaks and spills from entering karst systems.
- The BLM, Carlsbad Field Office, will be informed immediately if any subsurface drainage channels, cave passages, or voids are penetrated during construction and no further construction will be done until clearance has been issued by the Authorized Officer.
- Turnout ditches and drainage leadoffs will not be constructed in such a manner as to increase or decrease the natural flow of water into or out of cave or karst features.
- Special restoration stipulations or realignment may be required.

**MITIGATING MEASURES FOR POWERLINES:**

Smaller powerlines will be routed around sinkholes and other karst features to avoid or lessen the possibility of encountering near surface voids and to minimize changes to runoff or possible leaks and spills from entering karst systems. Larger powerlines will adjust their pole spacing to avoid cave and karst features.

Commented [TH1]: Too many spaces between paragraphs

The BLM, Carlsbad Field Office, will be informed immediately if any subsurface drainage channels, cave passages, or voids are penetrated during construction. No further construction will be done until clearance has been issued by the Authorized Officer. Special restoration stipulations or realignment may be required.

**MITIGATING MEASURES for BURIED PIPELINES AND CABLES:**

The BLM, Carlsbad Field Office, will be informed immediately if any subsurface drainage channels, passages, or voids are intersected by trenching, and no pipe will be laid in the trench at that point until clearance has been issued by the Authorized Officer. If a void is encountered alignments may be rerouted to avoid the karst feature and lessen; the potential of subsidence or collapse of karst features, buildup of toxic or combustible gas, or other possible impacts to cave and karst resources from the buried pipeline. Special restoration stipulations or realignment may be required at such intersections, if any. A leak detection plan **will be submitted to the BLM Carlsbad Field Office for approval** prior to pipeline installation. The method could incorporate gauges to detect pressure drops, situating valves and lines so they can be visually inspected periodically or installing electronic sensors to alarm when a leak is present. The leak detection plan will incorporate an automatic shut off system that will be installed for proposed pipelines to minimize the effects of an undesirable event. Regular monitoring is required to quickly identify leaks for their immediate and proper treatment.

**MITIGATING MEASURES for SURFACE FLOWLINES:**

Flowlines will be routed around sinkholes and other karst features to avoid or lessen the possibility of encountering near surface voids and to minimize the possibility of leaks and spills from entering karst systems. If a void is encountered alignments may be rerouted to avoid the karst feature and lessen; the potential of subsidence or collapse of karst features, buildup of toxic or combustible gas, or other possible impacts to cave and karst resources from the buried pipeline. Regular monitoring is required to quickly identify leaks for their immediate and proper treatment. All spills or leaks will be reported to the BLM immediately for their immediate and proper treatment.

## **VI. CONSTRUCTION**

### **A. NOTIFICATION**

The BLM shall administer compliance and monitor construction of the access road and well pad. Notify the Carlsbad Field Office at (575) 234-5909 at least 3 working days prior to commencing construction of the access road and/or well pad.

When construction operations are being conducted on this well, the operator shall have the approved APD and Conditions of Approval (COA) on the well site and they shall be made available upon request by the Authorized Officer.

### **B. TOPSOIL**

The operator shall strip the top portion of the soil (root zone) from the entire well pad area and stockpile the topsoil along the edge of the well pad as depicted in the APD. The root zone is typically six (6) inches in depth. All the stockpiled topsoil will be redistributed over the interim reclamation areas. Topsoil shall not be used for berming the pad or facilities. For final reclamation, the topsoil shall be spread over the entire pad area for seeding preparation.

Other subsoil (below six inches) stockpiles must be completely segregated from the topsoil stockpile. Large rocks or subsoil clods (not evident in the surrounding terrain) must be buried within the approved area for interim and final reclamation.

### **C. CLOSED LOOP SYSTEM**

Tanks are required for drilling operations: No Pits.

The operator shall properly dispose of drilling contents at an authorized disposal site.

### **D. FEDERAL MINERAL MATERIALS PIT**

Payment shall be made to the BLM prior to removal of any federal mineral materials. Call the Carlsbad Field Office at (575) 234-5972.

### **E. WELL PAD SURFACING**

Surfacing of the well pad is not required.

If the operator elects to surface the well pad, the surfacing material may be required to be removed at the time of reclamation. The well pad shall be constructed in a manner which creates the smallest possible surface disturbance, consistent with safety and operational needs.

### **F. EXCLOSURE FENCING (CELLARS & PITS)**

**Exclosure Fencing**

The operator will install and maintain exclosure fencing for all open well cellars to prevent access to public, livestock, and large forms of wildlife before and after drilling operations until the pit is free of fluids and the operator initiates backfilling. (For examples of exclosure fencing design, refer to BLM's Oil and Gas Gold Book, Exclosure Fence Illustrations, Figure 1, Page 18.)

**G. ON LEASE ACCESS ROADS****Road Width**

The access road shall have a driving surface that creates the smallest possible surface disturbance and does not exceed fourteen (14) feet in width. The maximum width of surface disturbance, when constructing the access road, shall not exceed twenty-five (25) feet.

**Surfacing**

Surfacing material is not required on the new access road driving surface. If the operator elects to surface the new access road or pad, the surfacing material may be required to be removed at the time of reclamation.

Where possible, no improvements should be made on the unsurfaced access road other than to remove vegetation as necessary, road irregularities, safety issues, or to fill low areas that may sustain standing water.

The Authorized Officer reserves the right to require surfacing of any portion of the access road at any time deemed necessary. Surfacing may be required in the event the road deteriorates, erodes, road traffic increases, or it is determined to be beneficial for future field development. The surfacing depth and type of material will be determined at the time of notification.

**Crowning**

Crowning shall be done on the access road driving surface. The road crown shall have a grade of approximately 2% (i.e., a 1" crown on a 14' wide road). The road shall conform to Figure 1; cross section and plans for typical road construction.

**Ditching**

Ditching shall be required on both sides of the road.


**Turnouts**

Vehicle turnouts shall be constructed on the road. Turnouts shall be intervisible with interval spacing distance less than 1000 feet. Turnouts shall conform to Figure 1; cross section and plans for typical road construction.

**Drainage**

Drainage control systems shall be constructed on the entire length of road (e.g. ditches, sidehill out-sloping and in-sloping, lead-off ditches, culvert installation, and low water crossings).

A typical lead-off ditch has a minimum depth of 1 foot below and a berm of 6 inches above natural ground level. The berm shall be on the down-slope side of the lead-off ditch.



All lead-off ditches shall be graded to drain water with a 1 percent minimum to 3 percent maximum ditch slope. The spacing interval are variable for lead-off ditches and shall be determined according to the formula for spacing intervals of lead-off ditches, but may be amended depending upon existing soil types and centerline road slope (in %);

#### Formula for Spacing Interval of Lead-off Ditches

Example - On a 4% road slope that is 400 feet long, the water flow shall drain water into a lead-off ditch. Spacing interval shall be determined by the following formula:

$$400 \text{ foot road with } 4\% \text{ road slope: } \frac{400'}{4\%} + 100' = 200' \text{ lead-off ditch interval}$$

#### **Cattle guards**

An appropriately sized cattle guard sufficient to carry out the project shall be installed and maintained at fence/road crossings. Any existing cattle guards on the access road route shall be repaired or replaced if they are damaged or have deteriorated beyond practical use. The operator shall be responsible for the condition of the existing cattle guards that are in place and are utilized during lease operations.

#### **Fence Requirement**

Where entry is granted across a fence line, the fence shall be braced and tied off on both sides of the passageway prior to cutting. The operator shall notify the private surface landowner or the grazing allotment holder prior to crossing any fences.

#### **Public Access**

Public access on this road shall not be restricted by the operator without specific written approval granted by the Authorized Officer.

**Construction Steps**

1. Salvage topsoil
2. Construct road
3. Redistribute topsoil
4. Revegetate slopes




Figure 1. Cross-sections and plans for typical road sections representative of BLM resource or FS local and higher-class roads.

## VII. PRODUCTION (POST DRILLING)

### A. WELL STRUCTURES & FACILITIES

#### **Placement of Production Facilities**

Production facilities should be placed on the well pad to allow for maximum interim recontouring and revegetation of the well location.

#### **Exclosure Netting (Open-top Tanks)**

Immediately following active drilling or completion operations, the operator will take actions necessary to prevent wildlife and livestock access, including avian wildlife, to all open-topped tanks that contain or have the potential to contain salinity sufficient to cause harm to wildlife or livestock, hydrocarbons, or Resource Conservation and Recovery Act of 1976-exempt hazardous substances. At a minimum, the operator will net, screen, or cover open-topped tanks to exclude wildlife and livestock and prevent mortality. If the operator uses netting, the operator will cover and secure the open portion of the tank to prevent wildlife entry. The operator will net, screen, or cover the tanks until the operator removes the tanks from the location or the tanks no longer contain substances that could be harmful to wildlife or livestock. Use a maximum netting mesh size of 1 ½ inches. The netting must not be in contact with fluids and must not have holes or gaps.

#### **Chemical and Fuel Secondary Containment and Exclosure Screening**

The operator will prevent all hazardous, poisonous, flammable, and toxic substances from coming into contact with soil and water. At a minimum, the operator will install and maintain an impervious secondary containment system for any tank or barrel containing hazardous, poisonous, flammable, or toxic substances sufficient to contain the contents of the tank or barrel and any drips, leaks, and anticipated precipitation. The operator will dispose of fluids within the containment system that do not meet applicable state or U. S. Environmental Protection Agency livestock water standards in accordance with state law; the operator must not drain the fluids to the soil or ground. The operator will design, construct, and maintain all secondary containment systems to prevent wildlife and livestock exposure to harmful substances. At a minimum, the operator will install effective wildlife and livestock exclosure systems such as fencing, netting, expanded metal mesh, lids, and grate covers. Use a maximum netting mesh size of 1 ½ inches.

#### **Open-Vent Exhaust Stack Exclosures**

The operator will construct, modify, equip, and maintain all open-vent exhaust stacks on production equipment to prevent birds and bats from entering, and to discourage perching, roosting, and nesting. (*Recommended exclosure structures on open-vent exhaust stacks are in the shape of a cone.*) Production equipment includes, but may not be limited to, tanks, heater-treaters, separators, dehydrators, flare stacks, in-line units, and compressor mufflers.

#### **Containment Structures**

Proposed production facilities such as storage tanks and other vessels will have a secondary containment structure that is constructed to hold the capacity of 1.5 times the largest tank, plus

freeboard to account for precipitation, unless more stringent protective requirements are deemed necessary.

**Painting Requirement**

All above-ground structures including meter housing that are not subject to safety requirements shall be painted a flat non-reflective paint color, **Shale Green** from the BLM Standard Environmental Color Chart (CC-001: June 2008).

**STANDARD STIPULATIONS FOR OIL AND GAS RELATED SITES**

A copy of the application (Grant/Sundry Notice) and attachments, including stipulations and map, will be on location during construction. BLM personnel may request to view a copy of your permit during construction to ensure compliance with all stipulations.

The holder agrees to comply with the following stipulations to the satisfaction of the Authorized Officer, BLM.

1. The holder shall indemnify the United States against any liability for damage to life or property arising from the occupancy or use of public lands under this grant and for all response costs, penalties, damages, claims, and other costs arising from the provisions of the Resource Conservation and Recovery Act (RCRA), 42 U.S.C. Chap. 82, Section 6901 et. seq., from the Comprehensive Environmental Response, Compensation and Liability Act (CERCLA), 42 U.S.C. Chap. 109, Section 9601 et. seq., and from other applicable environmental statutes.
2. The holder shall comply with all applicable Federal laws and regulations existing or hereafter enacted or promulgated. In any event, the holder shall comply with the Toxic Substances Control Act of 1976, as amended (15 U.S.C. 2601, et. seq.) with regard to any toxic substances that are used, generated by or stored on the right-of-way or on facilities authorized by this grant. (See 40 CFR, Part 702-799 and especially, provisions on polychlorinated biphenyls, 40 CFR 761.1-761.193.) Additionally, any release of toxic substances (leaks, spills, etc.) in excess of the reportable quantity established by 40 CFR, Part 117 shall be reported as required by the Comprehensive Environmental Response, Compensation and Liability Act, Section 102b. A copy of any report required or requested by any Federal agency or State government as a result of a reportable release or spill of any toxic substances shall be furnished to the Authorized Officer concurrent with the filing of the reports to the involved Federal agency or State government.
3. The holder agrees to indemnify the United States against any liability arising from the release of any hazardous substance or hazardous waste (as these terms are defined in the Comprehensive Environmental Response, Compensation and Liability Act of 1980, 42 U.S.C. 9601, et. seq. or the Resource Conservation and Recovery Act, 42 U.S.C. 6901, et. seq.) on the right-of-way (unless the release or threatened release is wholly unrelated to the right-of-way holder's activity on the right-of-way). This agreement applies without regard to whether a release is caused by the holder, its agent, or unrelated third parties.

4. If, during any phase of the construction, operation, maintenance, or termination of the site or related pipeline(s), any oil or other pollutant should be discharged from site facilities, the pipeline(s) or from containers or vehicles impacting Federal lands, the control and total removal, disposal, and cleanup of such oil or other pollutant, wherever found, shall be the responsibility of the holder, regardless of fault. Upon failure of the holder to control, dispose of, or clean up such discharge on or affecting Federal lands, or to repair all damages to Federal lands resulting therefrom, the Authorized Officer may take such measures as deemed necessary to control and cleanup the discharge and restore the area, including, where appropriate, the aquatic environment and fish and wildlife habitats, at the full expense of the holder. Such action by the Authorized Officer shall not relieve the holder of any liability or responsibility.

5. Sites shall be maintained in an orderly, sanitary condition at all times. Waste materials, both liquid and solid, shall be disposed of promptly at an appropriate, authorized waste disposal facility in accordance with all applicable State and Federal laws. "Waste" means all discarded matter including, but not limited to, human waste, trash, garbage, refuse, petroleum products, brines, chemicals, oil drums, ashes, and equipment.

6. The operator will notify the Bureau of Land Management (BLM) authorized officer and nearest Fish and Wildlife Service (FWS) Law Enforcement office within 24 hours, if the operator discovers a dead or injured federally protected species (i.e., migratory bird species, bald or golden eagle, or species listed by the FWS as threatened or endangered) in or adjacent to a pit, trench, tank, exhaust stack, or fence. (If the operator is unable to contact the FWS Law Enforcement office, the operator must contact the nearest FWS Ecological Services office.)

7. All above-ground structures not subject to safety requirements shall be painted by the holder to blend with the natural color of the landscape. The paint used shall be a color which simulates "Standard Environmental Colors" designated by the Rocky Mountain Five-State Interagency Committee. The color selected for this project is **Shale Green**, Munsell Soil Color Chart Number 5Y 4/2.

8. Any cultural and/or paleontological resource (historic or prehistoric site or object) discovered by the holder, or any person working on the holder's behalf, on public or Federal land shall be immediately reported to the Authorized Officer. The holder shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery will be made by the Authorized Officer to determine appropriate actions to prevent the loss of significant cultural or scientific values. The holder will be responsible for the cost of evaluation and any decision as to the proper mitigation measures will be made by the Authorized Officer after consulting with the holder.

9. A sales contract for removal of mineral material (caliche, sand, gravel, fill dirt) from an authorized pit, site, or on location must be obtained from the BLM prior to commencing construction. There are several options available for purchasing mineral material: contact the BLM office (575-234-5972).

10. The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes the roads, pads, associated pipeline corridor, and adjacent land affected by the establishment of weeds due to this action. The operator shall consult with the Authorized Officer for acceptable weed control methods, which include following EPA and BLM requirements and policies.

11. Once the site is no longer in service or use, the site must undergo final abandonment. At final abandonment, the site and access roads must undergo "final" reclamation so that the character and productivity of the land are restored. Earthwork for final reclamation must be completed within six (6) months of the abandonment of the site. All pads and facility locations and roads must be reclaimed to a satisfactory revegetated, safe, and stable condition, unless an agreement is made with the landowner or BLM to keep the road and/or pad intact. After all disturbed areas have been satisfactorily prepared, these areas need to be revegetated with the seed mixture provided. Seeding should be accomplished by drilling on the contour whenever practical or by other approved methods. Seeding may need to be repeated until revegetation is successful, as determined by the BLM.

Operators shall contact a BLM surface protection specialist prior to surface abandonment operations for site specific objectives (Jim Amos: 575-234-5909).

12. The holder shall stockpile an adequate amount of topsoil where blading occurs. The topsoil to be stripped is approximately   6   inches in depth. The topsoil will be segregated from other spoil piles. The topsoil will be used for final reclamation.

13. The holder will reseed all disturbed areas. Seeding will be done according to the attached seeding requirements, using the following seed mix.

- |  |  |
|--|--|
| <input type="checkbox"/> seed mixture 1            | <input type="checkbox"/> seed mixture 3          |
| <input checked="" type="checkbox"/> seed mixture 2 | <input type="checkbox"/> seed mixture 4          |
| <input type="checkbox"/> seed mixture 2/LPC        | <input type="checkbox"/> Aplomado Falcon Mixture |

14. In those areas where erosion control structures are required to stabilize soil conditions, the holder shall install such structures as are suitable for the specific soil conditions being encountered and which are in accordance with sound management practices. Any earth work will require prior approval by the Authorized Officer.

15. Open-topped Tanks - The operator will take actions necessary to prevent wildlife and livestock access, including avian wildlife, to all open-topped tanks that contain or have the potential to contain salinity sufficient to cause harm to wildlife or livestock, hydrocarbons, or Resource Conservation and Recovery Act of 1976-exempt hazardous substances. At a minimum, the operator will net, screen, or cover open-topped tanks to exclude wildlife and livestock and prevent mortality. If the operator uses netting, the operator will cover and secure the open portion of the tank to prevent wildlife entry. The operator will net, screen, or cover the tanks until the operator removes the tanks from the location or the tanks no longer contain substances that could be harmful to wildlife or livestock. Use a maximum netting mesh size of 1 ½ inches. The netting must not be in contact with fluids and must not have holes or gaps

16. The operator will prevent all hazardous, poisonous, flammable, and toxic substances from coming into contact with soil and water. At a minimum, the operator will install and maintain an

impervious secondary containment system for any tank or barrel containing hazardous, poisonous, flammable, or toxic substances sufficient to contain the contents of the tank or barrel and any drips, leaks, and anticipated precipitation. The operator will dispose of fluids within the containment system that do not meet applicable state or U. S. Environmental Protection Agency livestock water standards in accordance with state law; the operator must not drain the fluids to the soil or ground. The operator will design, construct, and maintain all secondary containment systems to prevent wildlife and livestock exposure to harmful substances. At a minimum, the operator will install effective wildlife and livestock enclosure systems such as fencing, netting, expanded metal mesh, lids, and grate covers. Use a maximum netting mesh size of 1 ½ inches.

17. Open-Vent Exhaust Stack Enclosures – The operator will construct, modify, equip, and maintain all open-vent exhaust stacks on production equipment to prevent birds and bats from entering, and to discourage perching, roosting, and nesting. (Recommended enclosure structures on open-vent exhaust stacks are in the shape of a cone.) Production equipment includes, but may not be limited to, tanks, heater-treaters, separators, dehydrators, flare stacks, in-line units, and compressor mufflers.

18. Containment Structures - Proposed production facilities such as storage tanks and other vessels will have a secondary containment structure that is constructed to hold the capacity of 1.5 times the largest tank, plus freeboard to account for precipitation, unless more stringent protective requirements are deemed necessary.

## **B. PIPELINES**

### **BURIED PIPELINE STIPULATIONS**

A copy of the application (Grant, APD, or Sundry Notice) and attachments, including conditions of approval, survey plat and/or map, will be on location during construction. BLM personnel may request to you a copy of your permit during construction to ensure compliance with all stipulations.

Holder agrees to comply with the following stipulations to the satisfaction of the Authorized Officer:

1. The Holder shall indemnify the United States against any liability for damage to life or property arising from the occupancy or use of public lands under this grant.

2. The Holder shall comply with all applicable Federal laws and regulations existing or hereafter enacted or promulgated. In any event, the holder shall comply with the Toxic Substances Control Act of 1976 as amended, 15 USC 2601 et seq. (1982) with regards to any toxic substances that are used, generated by or stored on the right-of-way or on facilities authorized under this right-of-way grant. (See 40 CFR Part 702-799 and especially, provisions on polychlorinated biphenyls, 40 CFR 761.1-761.193.) Additionally, any release of toxic substances (leaks, spills, etc.) in excess of the reportable quantity established by 40 CFR Part 117 shall be reported as required by the Comprehensive Environmental Response, Compensation, and Liability Act, section 102b. A copy of any report required or requested by any Federal agency or State government as a result of a reportable release or spill of any toxic substances shall be furnished to the authorized officer concurrent with the filing of the reports to the involved Federal agency or State government.

3. The holder agrees to indemnify the United States against any liability arising from the release of any hazardous substance or hazardous waste (as these terms are defined in the Comprehensive Environmental Response, Compensation and Liability Act of 1980, 42 U.S.C. 9601, et seq. or the Resource Conservation and Recovery Act, 42 U.S.C.6901, et seq.) on the Right-of-Way (unless the release or threatened release is wholly unrelated to the Right-of-Way holder's activity on the Right-of-Way), or resulting from the activity of the Right-of-Way holder on the Right-of-Way. This agreement applies without regard to whether a release is caused by the holder, its agent, or unrelated third parties.

4. If, during any phase of the construction, operation, maintenance, or termination of the pipeline, any oil or other pollutant should be discharged from the pipeline system, impacting Federal lands, the control and total removal, disposal, and cleaning up of such oil or other pollutant, wherever found, shall be the responsibility of holder, regardless of fault. Upon failure of holder to control, dispose of, or clean up such discharge on or affecting Federal lands, or to repair all damages resulting therefrom, on the Federal lands, the Authorized Officer may take such measures as he deems necessary to control and clean up the discharge and restore the area, including where appropriate, the aquatic environment and fish and wildlife habitats, at the full expense of the holder. Such action by the Authorized Officer shall not relieve holder of any responsibility as provided herein.

5. All construction and maintenance activity will be confined to the authorized right-of-way.
6. The pipeline will be buried with a minimum cover of 36 inches between the top of the pipe and ground level.
7. The maximum allowable disturbance for construction in this right-of-way will be 30 feet:
- Blading of vegetation within the right-of-way will be allowed: maximum width of blading operations will not exceed 20 feet. The trench is included in this area. (*Blading is defined as the complete removal of brush and ground vegetation.*)
  - Clearing of brush species within the right-of-way will be allowed: maximum width of clearing operations will not exceed 30 feet. The trench and bladed area are included in this area. (*Clearing is defined as the removal of brush while leaving ground vegetation (grasses, weeds, etc.) intact. Clearing is best accomplished by holding the blade 4 to 6 inches above the ground surface.*)
  - The remaining area of the right-of-way (if any) shall only be disturbed by compressing the vegetation. (*Compressing can be caused by vehicle tires, placement of equipment, etc.*)
8. The holder shall stockpile an adequate amount of topsoil where blading is allowed. The topsoil to be stripped is approximately 6 inches in depth. The topsoil will be segregated from other spoil piles from trench construction. The topsoil will be evenly distributed over the bladed area for the preparation of seeding.
9. The holder shall minimize disturbance to existing fences and other improvements on public lands. The holder is required to promptly repair improvements to at least their former state. Functional use of these improvements will be maintained at all times. The holder will contact the owner of any improvements prior to disturbing them. When necessary to pass through a fence line, the fence shall be braced on both sides of the passageway prior to cutting of the fence. No permanent gates will be allowed unless approved by the Authorized Officer.
10. Vegetation, soil, and rocks left as a result of construction or maintenance activity will be randomly scattered on this right-of-way and will not be left in rows, piles, or berms, unless otherwise approved by the Authorized Officer. The entire right-of-way shall be recontoured to match the surrounding landscape. The backfilled soil shall be compacted and a 6 inch berm will be left over the ditch line to allow for settling back to grade.
11. In those areas where erosion control structures are required to stabilize soil conditions, the holder will install such structures as are suitable for the specific soil conditions being encountered and which are in accordance with sound resource management practices.

12. The holder will reseed all disturbed areas. Seeding will be done according to the attached seeding requirements, using the following seed mix.

- |  |  |
|--|--|
| <input type="checkbox"/> seed mixture 1            | <input type="checkbox"/> seed mixture 3          |
| <input checked="" type="checkbox"/> seed mixture 2 | <input type="checkbox"/> seed mixture 4          |
| <input type="checkbox"/> seed mixture 2/LPC        | <input type="checkbox"/> Aplomado Falcon Mixture |

13. All above-ground structures not subject to safety requirements shall be painted by the holder to blend with the natural color of the landscape. The paint used shall be color which simulates "Standard Environmental Colors" – **Shale Green**, Munsell Soil Color No. 5Y 4/2.

14. The pipeline will be identified by signs at the point of origin and completion of the right-of-way and at all road crossings. At a minimum, signs will state the holder's name, BLM serial number, and the product being transported. All signs and information thereon will be posted in a permanent, conspicuous manner, and will be maintained in a legible condition for the life of the pipeline.

15. The holder shall not use the pipeline route as a road for purposes other than routine maintenance as determined necessary by the Authorized Officer in consultation with the holder before maintenance begins. The holder will take whatever steps are necessary to ensure that the pipeline route is not used as a roadway. As determined necessary during the life of the pipeline, the Authorized Officer may ask the holder to construct temporary deterrence structures.

16. Any cultural and/or paleontological resources (historic or prehistoric site or object) discovered by the holder, or any person working on his behalf, on public or Federal land shall be immediately reported to the Authorized Officer. Holder shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery will be made by the Authorized Officer to determine appropriate actions to prevent the loss of significant cultural or scientific values. The holder will be responsible for the cost of evaluation and any decision as to proper mitigation measures will be made by the Authorized Officer after consulting with the holder.

17. The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes associated roads, pipeline corridor and adjacent land affected by the establishment of weeds due to this action. The operator shall consult with the Authorized Officer for acceptable weed control methods, which include following EPA and BLM requirements and policies.

18. Escape Ramps - The operator will construct and maintain pipeline/utility trenches that are not otherwise fenced, screened, or netted to prevent livestock, wildlife, and humans from becoming entrapped. At a minimum, the operator will construct and maintain escape ramps, ladders, or

other methods of avian and terrestrial wildlife escape in the trenches according to the following criteria:

- a. Any trench left open for eight (8) hours or less is not required to have escape ramps; however, before the trench is backfilled, the contractor/operator shall inspect the trench for wildlife, remove all trapped wildlife, and release them at least 100 yards from the trench.
- b. For trenches left open for eight (8) hours or more, earthen escape ramps (built at no more than a 30 degree slope and spaced no more than 500 feet apart) shall be placed in the trench.

### C. ELECTRIC LINES

#### STANDARD STIPULATIONS FOR OVERHEAD ELECTRIC DISTRIBUTION LINES

**A copy of the grant and attachments, including stipulations, survey plat and/or map, will be on location during construction. BLM personnel may request to you a copy of your permit during construction to ensure compliance with all stipulations.**

Holder agrees to comply with the following stipulations to the satisfaction of the Authorized Officer:

1. The holder shall indemnify the United States against any liability for damage to life or property arising from the occupancy or use of public lands under this grant.
2. The holder shall comply with all applicable Federal laws and regulations existing or hereafter enacted or promulgated. In any event, the holder shall comply with the Toxic Substances Control Act of 1976 as amended, 15 USC 2601 et seq. (1982) with regards to any toxic substances that are used, generated by or stored on the right-of-way or on facilities authorized under this right-of-way grant. (See 40 CFR, Part 702-799 and especially, provisions on polychlorinated biphenyls, 40 CFR 761.1-761.193.) Additionally, any release of toxic substances (leaks, spills, etc.) in excess of the reportable quantity established by 40 CFR, Part 117 shall be reported as required by the Comprehensive Environmental Response, Compensation, and Liability Act, section 102b. A copy of any report required or requested by any Federal agency or State government as a result of a reportable release or spill of any toxic substances shall be furnished to the authorized officer concurrent with the filing of the reports to the involved Federal agency or State government.
3. The holder agrees to indemnify the United States against any liability arising from the release of any hazardous substance or hazardous waste (as these terms are defined in the Comprehensive Environmental Response, Compensation and Liability Act of 1980, 42 U.S.C. 9601, et seq. or the Resource Conservation and Recovery Act, 42 U.S.C. 6901, et seq.) on the Right-of-Way (unless the release or threatened release is wholly unrelated to the Right-of-Way holder's activity on the Right-of-Way), or resulting from the activity of the Right-of-Way holder on the Right-of-Way. This agreement applies without regard to whether a release is caused by the holder, its agent, or unrelated third parties.

4. There will be no clearing or blading of the right-of-way unless otherwise agreed to in writing by the Authorized Officer.

5. Power lines shall be constructed and designed in accordance to standards outlined in "Suggested Practices for Avian Protection on Power lines: The State of the Art in 2006" Edison Electric Institute, APLIC, and the California Energy Commission 2006 . The holder shall assume the burden and expense of proving that pole designs not shown in the above publication deter raptor perching, roosting, and nesting. Such proof shall be provided by a raptor expert approved by the Authorized Officer. The BLM reserves the right to require modification or additions to all powerline structures placed on this right-of-way, should they be necessary to ensure the safety of large perching birds. Such modifications and/or additions shall be made by the holder without liability or expense to the United States.

Raptor deterrence will consist of but not limited to the following: triangle perch discouragers shall be placed on each side of the cross arms and a nonconductive perching deterrence shall be placed on all vertical poles that extend past the cross arms.

6. The holder shall minimize disturbance to existing fences and other improvements on public lands. The holder is required to promptly repair improvements to at least their former state. Functional use of these improvements will be maintained at all times. The holder will contact the owner of any improvements prior to disturbing them. When necessary to pass through a fence line, the fence shall be braced on both sides of the passageway prior to cutting the fence. No permanent gates will be allowed unless approved by the Authorized Officer.

7. The BLM serial number assigned to this authorization shall be posted in a permanent, conspicuous manner where the power line crosses roads and at all serviced facilities. Numbers will be at least two inches high and will be affixed to the pole nearest the road crossing and at the facilities served.

8. Upon cancellation, relinquishment, or expiration of this grant, the holder shall comply with those abandonment procedures as prescribed by the Authorized Officer.

9. All surface structures (poles, lines, transformers, etc.) shall be removed within 180 days of abandonment, relinquishment, or termination of use of the serviced facility or facilities or within 180 days of abandonment, relinquishment, cancellation, or expiration of this grant, whichever comes first. This will not apply where the power line extends service to an active, adjoining facility or facilities.

10. Any cultural and/or paleontological resource (historic or prehistoric site or object) discovered by the holder, or any person working on his behalf, on public or Federal land shall be immediately reported to the Authorized Officer. Holder shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery will be made by the

Authorized Officer to determine appropriate actions to prevent the loss of significant cultural or scientific values. The holder will be responsible for the cost of evaluation and any decision as to proper mitigation measures will be made by the Authorized Officer after consulting with the holder.

11. Special Stipulations:

- For reclamation remove poles, lines, transformer, etc. and dispose of properly.
- Fill in any holes from the poles removed.

### **VIII. INTERIM RECLAMATION**

During the life of the development, all disturbed areas not needed for active support of production operations should undergo interim reclamation in order to minimize the environmental impacts of development on other resources and uses.

Within six (6) months of well completion, operators should work with BLM surface management specialists (Jim Amos: 575-234-5909) to devise the best strategies to reduce the size of the location. Interim reclamation should allow for remedial well operations, as well as safe and efficient removal of oil and gas.

During reclamation, the removal of caliche is important to increasing the success of revegetating the site. Removed caliche that is free of contaminants may be used for road repairs, fire walls or for building other roads and locations. In order to operate the well or complete workover operations, it may be necessary to drive, park and operate on restored interim vegetation within the previously disturbed area. Disturbing revegetated areas for production or workover operations will be allowed. If there is significant disturbance and loss of vegetation, the area will need to be revegetated. Communicate with the appropriate BLM office for any exceptions/exemptions if needed.

All disturbed areas after they have been satisfactorily prepared need to be reseeded with the seed mixture provided below.

Upon completion of interim reclamation, the operator shall submit a Sundry Notices and Reports on Wells, Subsequent Report of Reclamation (Form 3160-5).

### **IX. FINAL ABANDONMENT & RECLAMATION**

At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land are restored.

Earthwork for final reclamation must be completed within six (6) months of well plugging. All pads, pits, facility locations and roads must be reclaimed to a satisfactory revegetated, safe, and stable condition, unless an agreement is made with the landowner or BLM to keep the road and/or pad intact.

After all disturbed areas have been satisfactorily prepared, these areas need to be revegetated with the seed mixture provided below. Seeding should be accomplished by drilling on the contour whenever practical or by other approved methods. Seeding may need to be repeated until revegetation is successful, as determined by the BLM.

Operators shall contact a BLM surface protection specialist prior to surface abandonment operations for site specific objectives (Jim Amos: 575-234-5909).

Ground-level Abandoned Well Marker to avoid raptor perching: Upon the plugging and subsequent abandonment of the well, the well marker will be installed at ground level on a plate containing the pertinent information for the plugged well.

Seed Mixture 2, for Sandy Sites

The holder shall seed all disturbed areas with the seed mixture listed below. The seed mixture shall be planted in the amounts specified in pounds of pure live seed (PLS)\* per acre. There shall be no primary or secondary noxious weeds in the seed mixture. Seed will be tested and the viability testing of seed will be done in accordance with State law (s) and within nine (9) months prior to purchase. Commercial seed will be either certified or registered seed. The seed container will be tagged in accordance with State law(s) and available for inspection by the authorized officer.

Seed will be planted using a drill equipped with a depth regulator to ensure proper depth of planting where drilling is possible. The seed mixture will be evenly and uniformly planted over the disturbed area (smaller/heavier seeds have a tendency to drop the bottom of the drill and are planted first). The holder shall take appropriate measures to ensure this does not occur. Where drilling is not possible, seed will be broadcast and the area shall be raked or chained to cover the seed. When broadcasting the seed, the pounds per acre are to be doubled. The seeding will be repeated until a satisfactory stand is established as determined by the authorized officer. Evaluation of growth will not be made before completion of at least one full growing season after seeding.

Species to be planted in pounds of pure live seed\* per acre:

<u>Species</u>	<u>lb/acre</u>
Sand dropseed (Sporobolus cryptandrus)	1.0
Sand love grass (Eragrostis trichodes)	1.0
Plains bristlegrass (Setaria macrostachya)	2.0

\*Pounds of pure live seed:

Pounds of seed x percent purity x percent germination = pounds pure live seed



U.S. Department of the Interior  
BUREAU OF LAND MANAGEMENT

### Operator Certification

*I hereby certify that I, or someone under my direct supervision, have inspected the drill site and access route proposed herein; that I am familiar with the conditions which currently exist; that I have full knowledge of state and Federal laws applicable to this operation; that the statements made in this APD package are, to the best of my knowledge, true and correct; and that the work associated with the operations proposed herein will be performed in conformity with this APD package and the terms and conditions under which it is approved. I also certify that I, or the company I represent, am responsible for the operations conducted under this application. These statements are subject to the provisions of 18 U.S.C. 1001 for the filing of false statements.*

**NAME:** Rebecca Deal

**Signed on:** 04/02/2018

**Title:** Regulatory Compliance Professional

**Street Address:** 333 West Sheridan Avenue

**City:** Oklahoma City                      **State:** OK

**Zip:** 73102

**Phone:** (405)228-8429

**Email address:** Rebecca.Deal@dvn.com

### Field Representative

**Representative Name:** Travis Phibbs

**Street Address:** 6488 Seven Rivers Hwy

**City:** Artesia                                      **State:** NM

**Zip:** 88210

**Phone:** (575)748-9929

**Email address:** travis.phibbs@dvn.com



**Devon Energy Center  
333 West Sheridan Avenue  
Oklahoma City, Oklahoma 73102-5015**

# **Hydrogen Sulfide (H<sub>2</sub>S) Contingency Plan**

**For**

**Jayhawk 6-7 Fed Fee Com 1H**

**Sec-6 T-26S R-34E  
365' FNL & 230' FEL  
LAT. = 32.0787266' N (NAD83)  
LONG = 103.5012113' W**

**Lea County NM**

Casing Assumptions and Load Cases

Surface

All casing design assumptions were ran in Stress Check to determine safety factor which meet or exceed both Devon Energy and BLM minimum requirements. All casing strings will be filled while running in hole in order to not exceed collapse rating of the pipe.



<b>Surface Casing Burst Design</b>		
<b>Load Case</b>	<b>External Pressure</b>	<b>Internal Pressure</b>
Pressure Test	Formation Pore Pressure	Max mud weight of next hole-section plus Test psi
Drill Ahead	Formation Pore Pressure	Max mud weight of next hole section
Displace to Gas	Formation Pore Pressure	Dry gas from next casing point

<b>Surface Casing Collapse Design</b>		
<b>Load Case</b>	<b>External Pressure</b>	<b>Internal Pressure</b>
Full Evacuation	Water gradient in cement, mud above TOC	None
Cementing	Wet cement weight	Water (8.33ppg)

<b>Surface Casing Tension Design</b>	
<b>Load Case</b>	<b>Assumptions</b>
Overpull	100kips
Runing in hole	3 ft/s
Service Loads	N/A

## Jayhawk 6-7 Fed Fee Com 1H

This is an open drilling site. H<sub>2</sub>S monitoring equipment and emergency response equipment will be used within 500' of zones known to contain H<sub>2</sub>S, including warning signs, wind indicators and H<sub>2</sub>S monitor.



**Assumed 100 ppm ROE = 3000' (Radius of Exposure)**  
**100 ppm H<sub>2</sub>S concentration shall trigger activation of this plan.**

### Escape

Crews shall escape upwind of escaping gas in the event of an emergency release of gas. Escape can be facilitated from the location entrance road. Crews should then block the entrance to the location from the lease road so as not to allow anyone traversing into a hazardous area. The blockade should be at a safe distance outside of the ROE. There are no homes or buildings in or near the ROE.

**Assumed 100 ppm ROE = 3000'**

**100 ppm H<sub>2</sub>S concentration shall trigger activation of this plan.**

### **Emergency Procedures**

**In the event of a release of gas containing H<sub>2</sub>S, the first responder(s) must**

- **Isolate the area and prevent entry by other persons into the 100 ppm ROE.**
- **Evacuate any public places encompassed by the 100 ppm ROE.**
- **Be equipped with H<sub>2</sub>S monitors and air packs in order to control the release.**
- **Use the “buddy system” to ensure no injuries occur during the response**
- **Take precautions to avoid personal injury during this operation.**
- **Contact operator and/or local officials to aid in operation. See list of phone numbers attached.**
- **Have received training in the**
  - **Detection of H<sub>2</sub>S, and**
  - **Measures for protection against the gas,**
  - **Equipment used for protection and emergency response.**

### **Ignition of Gas Source**

Should control of the well be considered lost and ignition considered, take care to protect against exposure to Sulfur Dioxide (SO<sub>2</sub>). Intentional ignition must be coordinated with the NMOCD and local officials. Additionally the NM State Police may become involved. NM State Police shall be the Incident Command on scene of any major release. Take care to protect downwind whenever there is an ignition of the gas

### **Characteristics of H<sub>2</sub>S and SO<sub>2</sub>**

<b>Common Name</b>	<b>Chemical Formula</b>	<b>Specific Gravity</b>	<b>Threshold Limit</b>	<b>Hazardous Limit</b>	<b>Lethal Concentration</b>
<b>Hydrogen Sulfide</b>	<b>H<sub>2</sub>S</b>	<b>1.189 Air = 1</b>	<b>10 ppm</b>	<b>100 ppm/hr</b>	<b>600 ppm</b>
<b>Sulfur Dioxide</b>	<b>SO<sub>2</sub></b>	<b>2.21 Air = 1</b>	<b>2 ppm</b>	<b>N/A</b>	<b>1000 ppm</b>

### **Contacting Authorities**

Devon Energy Corp. personnel must liaison with local and state agencies to ensure a proper response to a major release. Additionally, the OCD must be notified of the release as soon as possible but no later than 4 hours. Agencies will ask for information such as type and volume of release, wind direction, location of release, etc. Be prepared with all information available. The following call list of essential and potential responders has been prepared for use during a release. Devon Energy Corp. Company response must be in coordination with the State of New Mexico's 'Hazardous Materials Emergency Response Plan' (HMER)

## **Hydrogen Sulfide Drilling Operation Plan**

### **I. HYDROGEN SULFIDE (H<sub>2</sub>S) TRAINING**

All personnel, whether regularly assigned, contracted, or employed on an unscheduled basis, will receive training from a qualified instructor in the following areas prior to commencing drilling operations on this well:

1. The hazards and characteristics of hydrogen sulfide (H<sub>2</sub>S)
2. The proper use and maintenance of personal protective equipment and life support systems.
3. The proper use of H<sub>2</sub>S detectors, alarms, warning systems, briefing areas, evacuation procedures, and prevailing winds.
4. The proper techniques for first aid and rescue procedures.

In addition, supervisory personnel will be trained in the following areas:

1. The effects of H<sub>2</sub>S metal components. If high tensile tubulars are to be used, personnel will be trained in their special maintenance requirements.
2. Corrective action and shut-in procedures when drilling or reworking a well and blowout prevention and well control procedures.
3. The contents and requirements of the H<sub>2</sub>S Drilling Operations Plan and Public Protection Plan.

There will be an initial training session just prior to encountering a known or probable H<sub>2</sub>S zone (within 3 days or 500 feet) and weekly H<sub>2</sub>S and well control drills for all personnel in each crew. The initial training session shall include a review of the site specific H<sub>2</sub>S Drilling Operations Plan and the Public Protection Plan.

### **II. HYDROGEN SULFIDE TRAINING**

Note: All H<sub>2</sub>S safety equipment and systems will be installed, tested, and operational when drilling reaches a depth of 500 feet above, or three days prior to penetrating the first zone containing or reasonably expected to contain H<sub>2</sub>S.

## **1. Well Control Equipment**

- A. Flare line
- B. Choke manifold – Remotely Operated
- C. Blind rams and pipe rams to accommodate all pipe sizes with properly sized closing unit
- D. Auxiliary equipment may include if applicable: annular preventer and rotating head.
- E. Mud/Gas Separator

## **2. Protective equipment for essential personnel:**

30-minute SCBA units located at briefing areas, as indicated on well site diagram, with escape units available in the top doghouse. As it may be difficult to communicate audibly while wearing these units, hand signals shall be utilized.

## **3. H<sub>2</sub>S detection and monitoring equipment:**

Portable H<sub>2</sub>S monitors positioned on location for best coverage and response. These units have warning lights which activate when H<sub>2</sub>S levels reach 10 ppm and audible sirens which activate at 15 ppm. Sensor locations:

- Bell nipple
- Possum Belly/Shale shaker
- Rig floor
- Choke manifold
- Cellar

### **Visual warning systems:**

- A. Wind direction indicators as shown on well site diagram
- B. Caution/ Danger signs shall be posted on roads providing direct access to locations. Signs will be painted a high visibility yellow with black lettering of sufficient size to be reasonable distance from the immediate location. Bilingual signs will be used when appropriate.

#### **4. Mud program:**

The mud program has been designed to minimize the volume of H<sub>2</sub>S circulated to surface. Proper mud weight, safe drilling practices and the use of H<sub>2</sub>S scavengers will minimize hazards when penetrating H<sub>2</sub>S bearing zones.

#### **5. Metallurgy:**

- A. All drill strings, casings, tubing, wellhead, blowout preventer, drilling spool, kill lines, choke manifold lines, and valves shall be H<sub>2</sub>S trim.
- B. All elastomers used for packing and seals shall be H<sub>2</sub>S trim.

#### **6. Communication:**

- A. Company personnel have/use cellular telephones in the field.
- B. Land line (telephone) communications at Office

#### **7. Well testing:**


- A. Drill stem testing will be performed with a minimum number of personnel in the immediate vicinity, which are necessary to safety and adequately conduct the test. The drill stem testing will be conducted during daylight hours and formation fluids will not be flowed to the surface. All drill-stem-testing operations conducted in an H<sub>2</sub>S environment will use the closed chamber method of testing.
- B. There will be no drill stem testing.

<b>Devon Energy Corp. Company Call List</b>		
Drilling Supervisor – Basin – Mark Kramer		405-823-4796
EHS Professional – Laura Wright		405-439-8129
<b>Agency Call List</b>		
<b>Lea County (575)</b>	<b>Hobbs</b>	
	Lea County Communication Authority	393-3981
	State Police	392-5588
	City Police	397-9265
	Sheriff's Office	393-2515
	<b>Ambulance</b>	<b>911</b>
	Fire Department	397-9308
	LEPC (Local Emergency Planning Committee)	393-2870
	NMOCD	393-6161
	US Bureau of Land Management	393-3612
<b>Eddy County (575)</b>	<b>Carlsbad</b>	
	State Police	885-3137
	City Police	885-2111
	Sheriff's Office	887-7551
	<b>Ambulance</b>	<b>911</b>
	Fire Department	885-3125
	LEPC (Local Emergency Planning Committee)	887-3798
	US Bureau of Land Management	887-6544
	NM Emergency Response Commission (Santa Fe)	(505) 476-9600
	24 HR	(505) 827-9126
	National Emergency Response Center	(800) 424-8802
	National Pollution Control Center: Direct	(703) 872-6000
	For Oil Spills	(800) 280-7118
	<b>Emergency Services</b>	
	Wild Well Control	(281) 784-4700
	Cudd Pressure Control	(915) 699-0139 (915) 563-3356
	Halliburton	(575) 746-2757
	B. J. Services	(575) 746-3569
<b>Give GPS position:</b>	Native Air – Emergency Helicopter – Hobbs	(575) 392-6429
	Flight For Life - Lubbock, TX	(806) 743-9911
	Aerocare - Lubbock, TX	(806) 747-8923
	Med Flight Air Amb - Albuquerque, NM	(575) 842-4433
	Lifeguard Air Med Svc. Albuquerque, NM	(800) 222-1222
	Poison Control (24/7)	(575) 272-3115
	Oil & Gas Pipeline 24 Hour Service	(800) 364-4366
	NOAA – Website - <a href="http://www.nhc.noaa.gov">www.nhc.noaa.gov</a>	

Prepared in conjunction with  
Dave Small



# Devon Energy - Well Pad Rig Location Layout Safety Equipment Location





# **WCDSC Permian NM**

**Lea County (NAD83 New Mexico East)**

**Sec 06-T26S-R34E**

**Jayhawk FED FEE COM 1H**

**Wellbore #1**

**Plan: Permit Plan 1**

## **Standard Planning Report - Geographic**

**23 March, 2018**

Planning Report - Geographic

<b>Database:</b>	EDM r5000.141_Prod US	<b>Local Co-ordinate Reference:</b>	Well Jayhawk FED FEE COM 1H
<b>Company:</b>	WCDSC Permian NM	<b>TVD Reference:</b>	RKB @ 3357.70ft
<b>Project:</b>	Lea County (NAD83 New Mexico East)	<b>MD Reference:</b>	RKB @ 3357.70ft
<b>Site:</b>	Sec 06-T26S-R34E	<b>North Reference:</b>	Grid
<b>Well:</b>	Jayhawk FED FEE COM 1H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Permit Plan 1		

<b>Project</b>	Lea County (NAD83 New Mexico East)		
<b>Map System:</b>	US State Plane 1983	<b>System Datum:</b>	Mean Sea Level
<b>Geo Datum:</b>	North American Datum 1983		
<b>Map Zone:</b>	New Mexico Eastern Zone		

<b>Site</b>	Sec 06-T26S-R34E		
<b>Site Position:</b>	<b>Northing:</b>	393,700.60 usft	<b>Latitude:</b> 32.079736
<b>From:</b> Map	<b>Easting:</b>	794,011.60 usft	<b>Longitude:</b> -103.517530
<b>Position Uncertainty:</b>	5.00 ft	<b>Slot Radius:</b> 13-3/16 "	<b>Grid Convergence:</b> 0.43 °

<b>Well</b>	Jayhawk FED FEE COM 1H			
<b>Well Position</b>	<b>+N/-S</b>	0.00 ft	<b>Northing:</b> 393,371.93 usft	<b>Latitude:</b> 32.078727
	<b>+E/-W</b>	0.00 ft	<b>Easting:</b> 799,068.73 usft	<b>Longitude:</b> -103.501212
<b>Position Uncertainty</b>	0.50 ft	<b>Wellhead Elevation:</b>		<b>Ground Level:</b> 3,332.70 ft

<b>Wellbore</b>	Wellbore #1				
<b>Magnetics</b>	<b>Model Name</b>	<b>Sample Date</b>	<b>Declination</b>	<b>Dip Angle</b>	<b>Field Strength</b>
	IGRF2015	3/23/2018	(°) 6.83	(°) 59.93	(nT) 47,781.29403058

<b>Design</b>	Permit Plan 1			
<b>Audit Notes:</b>				
<b>Version:</b>	<b>Phase:</b>	PROTOTYPE	<b>Tie On Depth:</b> 0.00	
<b>Vertical Section:</b>	<b>Depth From (TVD)</b>	<b>+N/-S</b>	<b>+E/-W</b>	<b>Direction</b>
	(ft)	(ft)	(ft)	(°)
	0.00	0.00	0.00	180.28

<b>Plan Survey Tool Program</b>	Date: 3/23/2018			
<b>Depth From</b>	<b>Depth To</b>	<b>Survey (Wellbore)</b>	<b>Tool Name</b>	<b>Remarks</b>
(ft)	(ft)			
1	0.00	22,750.61 Permit Plan 1 (Wellbore #1)	MWD+HDGM OWSG MWD + HDGM	

<b>Plan Sections</b>										
<b>Measured</b>	<b>Inclination</b>	<b>Azimuth</b>	<b>Vertical</b>	<b>+N/-S</b>	<b>+E/-W</b>	<b>Dogleg</b>	<b>Build</b>	<b>Turn</b>	<b>TFO</b>	<b>Target</b>
<b>Depth</b>	<b>(°)</b>	<b>(°)</b>	<b>Depth</b>	<b>(ft)</b>	<b>(ft)</b>	<b>Rate</b>	<b>Rate</b>	<b>Rate</b>	<b>(°)</b>	
(ft)			(ft)			(°/100usft)	(°/100usft)	(°/100usft)		
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
5,000.00	0.00	0.00	5,000.00	0.00	0.00	0.00	0.00	0.00	0.00	
5,508.59	6.36	3.14	5,507.54	28.14	1.55	1.25	1.25	0.00	3.14	
7,892.75	6.36	3.14	7,877.05	291.74	16.02	0.00	0.00	0.00	0.00	
8,316.57	0.00	0.00	8,300.00	315.20	17.30	1.50	-1.50	0.00	180.00	Vertical Point - Jayhw
11,956.57	0.00	0.00	11,940.00	315.20	17.30	0.00	0.00	0.00	0.00	
12,074.72	11.81	298.68	12,057.31	321.02	6.66	10.00	10.00	0.00	298.68	
13,283.40	90.00	179.50	12,840.00	-400.00	-130.00	7.92	6.47	-9.86	-118.66	
22,750.85	90.00	179.50	12,840.00	-9,867.10	-47.38	0.00	0.00	0.00	0.00	PBHL - Jayhawk FED

Planning Report - Geographic

<b>Database:</b>	EDM r5000.141_Prod US	<b>Local Co-ordinate Reference:</b>	Well Jayhawk FED FEE COM 1H
<b>Company:</b>	WCDCS Permian NM	<b>TVD Reference:</b>	RKB @ 3357.70ft
<b>Project:</b>	Lea County (NAD83 New Mexico East)	<b>MD Reference:</b>	RKB @ 3357.70ft
<b>Site:</b>	Sec 06-T26S-R34E	<b>North Reference:</b>	Grid
<b>Well:</b>	Jayhawk FED FEE COM 1H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Permit Plan 1		

Planned Survey

Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Map Northing (usft)	Map Easting (usft)	Latitude	Longitude
0.00	0.00	0.00	0.00	0.00	0.00	393,371.93	799,068.73	32.078727	-103.501212
100.00	0.00	0.00	100.00	0.00	0.00	393,371.93	799,068.73	32.078727	-103.501212
200.00	0.00	0.00	200.00	0.00	0.00	393,371.93	799,068.73	32.078727	-103.501212
300.00	0.00	0.00	300.00	0.00	0.00	393,371.93	799,068.73	32.078727	-103.501212
400.00	0.00	0.00	400.00	0.00	0.00	393,371.93	799,068.73	32.078727	-103.501212
500.00	0.00	0.00	500.00	0.00	0.00	393,371.93	799,068.73	32.078727	-103.501212
600.00	0.00	0.00	600.00	0.00	0.00	393,371.93	799,068.73	32.078727	-103.501212
700.00	0.00	0.00	700.00	0.00	0.00	393,371.93	799,068.73	32.078727	-103.501212
800.00	0.00	0.00	800.00	0.00	0.00	393,371.93	799,068.73	32.078727	-103.501212
900.00	0.00	0.00	900.00	0.00	0.00	393,371.93	799,068.73	32.078727	-103.501212
1,000.00	0.00	0.00	1,000.00	0.00	0.00	393,371.93	799,068.73	32.078727	-103.501212
1,100.00	0.00	0.00	1,100.00	0.00	0.00	393,371.93	799,068.73	32.078727	-103.501212
1,200.00	0.00	0.00	1,200.00	0.00	0.00	393,371.93	799,068.73	32.078727	-103.501212
1,300.00	0.00	0.00	1,300.00	0.00	0.00	393,371.93	799,068.73	32.078727	-103.501212
1,400.00	0.00	0.00	1,400.00	0.00	0.00	393,371.93	799,068.73	32.078727	-103.501212
1,500.00	0.00	0.00	1,500.00	0.00	0.00	393,371.93	799,068.73	32.078727	-103.501212
1,600.00	0.00	0.00	1,600.00	0.00	0.00	393,371.93	799,068.73	32.078727	-103.501212
1,700.00	0.00	0.00	1,700.00	0.00	0.00	393,371.93	799,068.73	32.078727	-103.501212
1,800.00	0.00	0.00	1,800.00	0.00	0.00	393,371.93	799,068.73	32.078727	-103.501212
1,900.00	0.00	0.00	1,900.00	0.00	0.00	393,371.93	799,068.73	32.078727	-103.501212
2,000.00	0.00	0.00	2,000.00	0.00	0.00	393,371.93	799,068.73	32.078727	-103.501212
2,100.00	0.00	0.00	2,100.00	0.00	0.00	393,371.93	799,068.73	32.078727	-103.501212
2,200.00	0.00	0.00	2,200.00	0.00	0.00	393,371.93	799,068.73	32.078727	-103.501212
2,300.00	0.00	0.00	2,300.00	0.00	0.00	393,371.93	799,068.73	32.078727	-103.501212
2,400.00	0.00	0.00	2,400.00	0.00	0.00	393,371.93	799,068.73	32.078727	-103.501212
2,500.00	0.00	0.00	2,500.00	0.00	0.00	393,371.93	799,068.73	32.078727	-103.501212
2,600.00	0.00	0.00	2,600.00	0.00	0.00	393,371.93	799,068.73	32.078727	-103.501212
2,700.00	0.00	0.00	2,700.00	0.00	0.00	393,371.93	799,068.73	32.078727	-103.501212
2,800.00	0.00	0.00	2,800.00	0.00	0.00	393,371.93	799,068.73	32.078727	-103.501212
2,900.00	0.00	0.00	2,900.00	0.00	0.00	393,371.93	799,068.73	32.078727	-103.501212
3,000.00	0.00	0.00	3,000.00	0.00	0.00	393,371.93	799,068.73	32.078727	-103.501212
3,100.00	0.00	0.00	3,100.00	0.00	0.00	393,371.93	799,068.73	32.078727	-103.501212
3,200.00	0.00	0.00	3,200.00	0.00	0.00	393,371.93	799,068.73	32.078727	-103.501212
3,300.00	0.00	0.00	3,300.00	0.00	0.00	393,371.93	799,068.73	32.078727	-103.501212
3,400.00	0.00	0.00	3,400.00	0.00	0.00	393,371.93	799,068.73	32.078727	-103.501212
3,500.00	0.00	0.00	3,500.00	0.00	0.00	393,371.93	799,068.73	32.078727	-103.501212
3,600.00	0.00	0.00	3,600.00	0.00	0.00	393,371.93	799,068.73	32.078727	-103.501212
3,700.00	0.00	0.00	3,700.00	0.00	0.00	393,371.93	799,068.73	32.078727	-103.501212
3,800.00	0.00	0.00	3,800.00	0.00	0.00	393,371.93	799,068.73	32.078727	-103.501212
3,900.00	0.00	0.00	3,900.00	0.00	0.00	393,371.93	799,068.73	32.078727	-103.501212
4,000.00	0.00	0.00	4,000.00	0.00	0.00	393,371.93	799,068.73	32.078727	-103.501212
4,100.00	0.00	0.00	4,100.00	0.00	0.00	393,371.93	799,068.73	32.078727	-103.501212
4,200.00	0.00	0.00	4,200.00	0.00	0.00	393,371.93	799,068.73	32.078727	-103.501212
4,300.00	0.00	0.00	4,300.00	0.00	0.00	393,371.93	799,068.73	32.078727	-103.501212
4,400.00	0.00	0.00	4,400.00	0.00	0.00	393,371.93	799,068.73	32.078727	-103.501212
4,500.00	0.00	0.00	4,500.00	0.00	0.00	393,371.93	799,068.73	32.078727	-103.501212
4,600.00	0.00	0.00	4,600.00	0.00	0.00	393,371.93	799,068.73	32.078727	-103.501212
4,700.00	0.00	0.00	4,700.00	0.00	0.00	393,371.93	799,068.73	32.078727	-103.501212
4,800.00	0.00	0.00	4,800.00	0.00	0.00	393,371.93	799,068.73	32.078727	-103.501212
4,900.00	0.00	0.00	4,900.00	0.00	0.00	393,371.93	799,068.73	32.078727	-103.501212
5,000.00	0.00	0.00	5,000.00	0.00	0.00	393,371.93	799,068.73	32.078727	-103.501212
<b>Begin Nudge</b>									
5,100.00	1.25	3.14	5,099.99	1.09	0.06	393,373.02	799,068.79	32.078730	-103.501211
5,200.00	2.50	3.14	5,199.94	4.36	0.24	393,376.28	799,068.97	32.078739	-103.501211

Planning Report - Geographic

**Database:** EDM r5000.141\_Prod US  
**Company:** WCDSC Permian NM  
**Project:** Lea County (NAD83 New Mexico East)  
**Site:** Sec 06-T26S-R34E  
**Well:** Jayhawk FED FEE COM 1H  
**Wellbore:** Wellbore #1  
**Design:** Permit Plan 1

**Local Co-ordinate Reference:** Well Jayhawk FED FEE COM 1H  
**TVD Reference:** RKB @ 3357.70ft  
**MD Reference:** RKB @ 3357.70ft  
**North Reference:** Grid  
**Survey Calculation Method:** Minimum Curvature

Planned Survey										
Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Map Northing (usft)	Map Easting (usft)	Latitude	Longitude	
5,300.00	3.75	3.14	5,299.79	9.80	0.54	393,381.73	799,069.27	32.078754	-103.501210	
5,400.00	5.00	3.14	5,399.49	17.42	0.96	393,389.34	799,069.68	32.078775	-103.501208	
5,500.00	6.25	3.14	5,499.01	27.20	1.49	393,399.13	799,070.22	32.078801	-103.501206	
5,508.59	6.36	3.14	5,507.55	28.14	1.55	393,400.07	799,070.27	32.078804	-103.501206	
<b>EOB</b>										
5,600.00	6.36	3.14	5,598.40	38.25	2.10	393,410.18	799,070.83	32.078832	-103.501204	
5,700.00	6.36	3.14	5,697.78	49.31	2.71	393,421.24	799,071.43	32.078862	-103.501202	
5,800.00	6.36	3.14	5,797.17	60.36	3.31	393,432.29	799,072.04	32.078893	-103.501199	
5,900.00	6.36	3.14	5,896.55	71.42	3.92	393,443.35	799,072.65	32.078923	-103.501197	
6,000.00	6.36	3.14	5,995.94	82.48	4.53	393,454.40	799,073.26	32.078953	-103.501195	
6,100.00	6.36	3.14	6,095.32	93.53	5.14	393,465.46	799,073.86	32.078984	-103.501193	
6,200.00	6.36	3.14	6,194.71	104.59	5.74	393,476.52	799,074.47	32.079014	-103.501190	
6,300.00	6.36	3.14	6,294.09	115.64	6.35	393,487.57	799,075.08	32.079044	-103.501188	
6,400.00	6.36	3.14	6,393.48	126.70	6.96	393,498.63	799,075.68	32.079075	-103.501186	
6,500.00	6.36	3.14	6,492.86	137.76	7.56	393,509.69	799,076.29	32.079105	-103.501184	
6,600.00	6.36	3.14	6,592.25	148.81	8.17	393,520.74	799,076.90	32.079136	-103.501181	
6,700.00	6.36	3.14	6,691.63	159.87	8.78	393,531.80	799,077.50	32.079166	-103.501179	
6,800.00	6.36	3.14	6,791.02	170.93	9.38	393,542.85	799,078.11	32.079196	-103.501177	
6,900.00	6.36	3.14	6,890.40	181.98	9.99	393,553.91	799,078.72	32.079227	-103.501175	
7,000.00	6.36	3.14	6,989.79	193.04	10.60	393,564.97	799,079.33	32.079257	-103.501173	
7,100.00	6.36	3.14	7,089.17	204.09	11.21	393,576.02	799,079.93	32.079287	-103.501170	
7,200.00	6.36	3.14	7,188.56	215.15	11.81	393,587.08	799,080.54	32.079318	-103.501168	
7,300.00	6.36	3.14	7,287.94	226.21	12.42	393,598.13	799,081.15	32.079348	-103.501166	
7,400.00	6.36	3.14	7,387.33	237.26	13.03	393,609.19	799,081.75	32.079379	-103.501164	
7,500.00	6.36	3.14	7,486.71	248.32	13.63	393,620.25	799,082.36	32.079409	-103.501161	
7,600.00	6.36	3.14	7,586.10	259.38	14.24	393,631.30	799,082.97	32.079439	-103.501159	
7,700.00	6.36	3.14	7,685.48	270.43	14.85	393,642.36	799,083.57	32.079470	-103.501157	
7,800.00	6.36	3.14	7,784.87	281.49	15.45	393,653.42	799,084.18	32.079500	-103.501155	
7,892.75	6.36	3.14	7,877.05	291.74	16.02	393,663.67	799,084.74	32.079528	-103.501153	
<b>EOH</b>										
7,900.00	6.25	3.14	7,884.25	292.54	16.06	393,664.47	799,084.79	32.079530	-103.501152	
8,000.00	4.75	3.14	7,983.79	302.10	16.59	393,674.03	799,085.31	32.079557	-103.501151	
8,100.00	3.25	3.14	8,083.54	309.07	16.97	393,681.00	799,085.70	32.079576	-103.501149	
8,200.00	1.75	3.14	8,183.45	313.42	17.21	393,685.35	799,085.93	32.079588	-103.501148	
8,300.00	0.25	3.14	8,283.43	315.16	17.30	393,687.09	799,086.03	32.079593	-103.501148	
8,316.57	0.00	0.00	8,300.00	315.20	17.30	393,687.12	799,086.03	32.079593	-103.501148	
<b>Drop to Vertical</b>										
8,400.00	0.00	0.00	8,383.43	315.20	17.30	393,687.12	799,086.03	32.079593	-103.501148	
8,500.00	0.00	0.00	8,483.43	315.20	17.30	393,687.12	799,086.03	32.079593	-103.501148	
8,600.00	0.00	0.00	8,583.43	315.20	17.30	393,687.12	799,086.03	32.079593	-103.501148	
8,700.00	0.00	0.00	8,683.43	315.20	17.30	393,687.12	799,086.03	32.079593	-103.501148	
8,800.00	0.00	0.00	8,783.43	315.20	17.30	393,687.12	799,086.03	32.079593	-103.501148	
8,900.00	0.00	0.00	8,883.43	315.20	17.30	393,687.12	799,086.03	32.079593	-103.501148	
9,000.00	0.00	0.00	8,983.43	315.20	17.30	393,687.12	799,086.03	32.079593	-103.501148	
9,100.00	0.00	0.00	9,083.43	315.20	17.30	393,687.12	799,086.03	32.079593	-103.501148	
9,200.00	0.00	0.00	9,183.43	315.20	17.30	393,687.12	799,086.03	32.079593	-103.501148	
9,300.00	0.00	0.00	9,283.43	315.20	17.30	393,687.12	799,086.03	32.079593	-103.501148	
9,400.00	0.00	0.00	9,383.43	315.20	17.30	393,687.12	799,086.03	32.079593	-103.501148	
9,500.00	0.00	0.00	9,483.43	315.20	17.30	393,687.12	799,086.03	32.079593	-103.501148	
9,600.00	0.00	0.00	9,583.43	315.20	17.30	393,687.12	799,086.03	32.079593	-103.501148	
9,700.00	0.00	0.00	9,683.43	315.20	17.30	393,687.12	799,086.03	32.079593	-103.501148	
9,800.00	0.00	0.00	9,783.43	315.20	17.30	393,687.12	799,086.03	32.079593	-103.501148	
9,900.00	0.00	0.00	9,883.43	315.20	17.30	393,687.12	799,086.03	32.079593	-103.501148	
10,000.00	0.00	0.00	9,983.43	315.20	17.30	393,687.12	799,086.03	32.079593	-103.501148	

Planning Report - Geographic

<b>Database:</b>	EDM r5000.141_Prod US	<b>Local Co-ordinate Reference:</b>	Well Jayhawk FED FEE COM 1H
<b>Company:</b>	WCDSC Permian NM	<b>TVD Reference:</b>	RKB @ 3357.70ft
<b>Project:</b>	Lea County (NAD83 New Mexico East)	<b>MD Reference:</b>	RKB @ 3357.70ft
<b>Site:</b>	Sec 06-T26S-R34E	<b>North Reference:</b>	Grid
<b>Well:</b>	Jayhawk FED FEE COM 1H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Permit Plan 1		

Planned Survey

Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Map Northing (usft)	Map Easting (usft)	Latitude	Longitude
10,100.00	0.00	0.00	10,083.43	315.20	17.30	393,687.12	799,086.03	32.079593	-103.501148
10,200.00	0.00	0.00	10,183.43	315.20	17.30	393,687.12	799,086.03	32.079593	-103.501148
10,300.00	0.00	0.00	10,283.43	315.20	17.30	393,687.12	799,086.03	32.079593	-103.501148
10,400.00	0.00	0.00	10,383.43	315.20	17.30	393,687.12	799,086.03	32.079593	-103.501148
10,500.00	0.00	0.00	10,483.43	315.20	17.30	393,687.12	799,086.03	32.079593	-103.501148
10,600.00	0.00	0.00	10,583.43	315.20	17.30	393,687.12	799,086.03	32.079593	-103.501148
10,700.00	0.00	0.00	10,683.43	315.20	17.30	393,687.12	799,086.03	32.079593	-103.501148
10,800.00	0.00	0.00	10,783.43	315.20	17.30	393,687.12	799,086.03	32.079593	-103.501148
10,900.00	0.00	0.00	10,883.43	315.20	17.30	393,687.12	799,086.03	32.079593	-103.501148
11,000.00	0.00	0.00	10,983.43	315.20	17.30	393,687.12	799,086.03	32.079593	-103.501148
11,100.00	0.00	0.00	11,083.43	315.20	17.30	393,687.12	799,086.03	32.079593	-103.501148
11,200.00	0.00	0.00	11,183.43	315.20	17.30	393,687.12	799,086.03	32.079593	-103.501148
11,300.00	0.00	0.00	11,283.43	315.20	17.30	393,687.12	799,086.03	32.079593	-103.501148
11,400.00	0.00	0.00	11,383.43	315.20	17.30	393,687.12	799,086.03	32.079593	-103.501148
11,500.00	0.00	0.00	11,483.43	315.20	17.30	393,687.12	799,086.03	32.079593	-103.501148
11,600.00	0.00	0.00	11,583.43	315.20	17.30	393,687.12	799,086.03	32.079593	-103.501148
11,700.00	0.00	0.00	11,683.43	315.20	17.30	393,687.12	799,086.03	32.079593	-103.501148
11,800.00	0.00	0.00	11,783.43	315.20	17.30	393,687.12	799,086.03	32.079593	-103.501148
11,900.00	0.00	0.00	11,883.43	315.20	17.30	393,687.12	799,086.03	32.079593	-103.501148
11,956.57	0.00	0.00	11,940.00	315.20	17.30	393,687.12	799,086.03	32.079593	-103.501148
<b>KOP @ 11957' MD, 50' FNL, 213' FEL</b>									
12,000.00	4.34	298.68	11,983.39	315.99	15.86	393,687.91	799,084.59	32.079595	-103.501152
12,074.72	11.81	298.68	12,057.31	321.02	6.66	393,692.95	799,075.38	32.079609	-103.501182
<b>EOB @ 298.68° TF</b>									
12,100.00	10.99	289.43	12,082.09	323.07	2.11	393,694.99	799,070.84	32.079615	-103.501197
12,200.00	11.16	247.30	12,180.39	322.50	-15.84	393,694.43	799,052.89	32.079613	-103.501255
12,300.00	15.88	219.43	12,277.69	308.18	-33.48	393,680.11	799,035.25	32.079574	-103.501312
12,400.00	22.45	205.73	12,372.14	280.36	-50.49	393,652.29	799,018.24	32.079498	-103.501368
12,500.00	29.66	198.20	12,461.94	239.59	-66.53	393,611.52	799,002.19	32.079387	-103.501420
12,600.00	37.14	193.45	12,545.38	186.64	-81.31	393,558.57	798,987.42	32.079241	-103.501469
12,700.00	44.76	190.11	12,620.86	122.52	-94.54	393,494.44	798,974.19	32.079065	-103.501514
12,800.00	52.45	187.57	12,686.95	48.45	-105.96	393,420.37	798,962.77	32.078862	-103.501552
12,877.61	58.44	185.94	12,730.95	-15.00	-113.44	393,356.93	798,955.29	32.078688	-103.501578
<b>1st Take Point @ 12878' MD, 330' FNL, 343' FEL</b>									
12,900.00	60.18	185.51	12,742.37	-34.16	-115.36	393,337.77	798,953.37	32.078635	-103.501585
13,000.00	67.94	183.74	12,786.09	-123.72	-122.56	393,248.21	798,946.16	32.078389	-103.501610
13,100.00	75.72	182.17	12,817.25	-218.53	-127.43	393,153.40	798,941.30	32.078129	-103.501628
13,200.00	83.50	180.69	12,835.28	-316.78	-129.86	393,055.15	798,938.86	32.077859	-103.501639
13,283.40	90.00	179.50	12,840.00	-400.00	-130.00	392,971.93	798,938.73	32.077630	-103.501641
<b>Land Point</b>									
13,300.00	90.00	179.50	12,840.00	-416.60	-129.86	392,955.33	798,938.87	32.077584	-103.501641
13,400.00	90.00	179.50	12,840.00	-516.60	-128.98	392,855.33	798,939.75	32.077309	-103.501641
13,500.00	90.00	179.50	12,840.00	-616.59	-128.11	392,755.34	798,940.62	32.077035	-103.501640
13,600.00	90.00	179.50	12,840.00	-716.59	-127.24	392,655.34	798,941.49	32.076760	-103.501640
13,700.00	90.00	179.50	12,840.00	-816.59	-126.36	392,555.34	798,942.36	32.076485	-103.501640
13,800.00	90.00	179.50	12,840.00	-916.58	-125.49	392,455.35	798,943.24	32.076210	-103.501640
13,900.00	90.00	179.50	12,840.00	-1,016.58	-124.62	392,355.35	798,944.11	32.075935	-103.501639
14,000.00	90.00	179.50	12,840.00	-1,116.58	-123.75	392,255.36	798,944.98	32.075660	-103.501639
14,100.00	90.00	179.50	12,840.00	-1,216.57	-122.87	392,155.36	798,945.85	32.075385	-103.501639
14,200.00	90.00	179.50	12,840.00	-1,316.57	-122.00	392,055.36	798,946.73	32.075110	-103.501638
14,300.00	90.00	179.50	12,840.00	-1,416.56	-121.13	391,955.37	798,947.60	32.074836	-103.501638
14,400.00	90.00	179.50	12,840.00	-1,516.56	-120.26	391,855.37	798,948.47	32.074561	-103.501638
14,500.00	90.00	179.50	12,840.00	-1,616.56	-119.38	391,755.38	798,949.34	32.074286	-103.501637
14,600.00	90.00	179.50	12,840.00	-1,716.55	-118.51	391,655.38	798,950.22	32.074011	-103.501637

Planning Report - Geographic

**Database:** EDM r5000.141\_Prod US  
**Company:** WCDCS Permian NM  
**Project:** Lea County (NAD83 New Mexico East)  
**Site:** Sec 06-T26S-R34E  
**Well:** Jayhawk FED FEE COM 1H  
**Wellbore:** Wellbore #1  
**Design:** Permit Plan 1

**Local Co-ordinate Reference:** Well Jayhawk FED FEE COM 1H  
**TVD Reference:** RKB @ 3357.70ft  
**MD Reference:** RKB @ 3357.70ft  
**North Reference:** Grid  
**Survey Calculation Method:** Minimum Curvature

Planned Survey										
Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Map Northing (usft)	Map Easting (usft)	Latitude	Longitude	
14,700.00	90.00	179.50	12,840.00	-1,816.55	-117.64	391,555.38	798,951.09	32.073736	-103.501637	
14,800.00	90.00	179.50	12,840.00	-1,916.54	-116.77	391,455.39	798,951.96	32.073461	-103.501636	
14,900.00	90.00	179.50	12,840.00	-2,016.54	-115.89	391,355.39	798,952.84	32.073186	-103.501636	
15,000.00	90.00	179.50	12,840.00	-2,116.54	-115.02	391,255.40	798,953.71	32.072911	-103.501636	
15,100.00	90.00	179.50	12,840.00	-2,216.53	-114.15	391,155.40	798,954.58	32.072637	-103.501635	
15,200.00	90.00	179.50	12,840.00	-2,316.53	-113.27	391,055.40	798,955.45	32.072362	-103.501635	
15,300.00	90.00	179.50	12,840.00	-2,416.53	-112.40	390,955.41	798,956.33	32.072087	-103.501635	
15,400.00	90.00	179.50	12,840.00	-2,516.52	-111.53	390,855.41	798,957.20	32.071812	-103.501634	
15,500.00	90.00	179.50	12,840.00	-2,616.52	-110.66	390,755.42	798,958.07	32.071537	-103.501634	
15,600.00	90.00	179.50	12,840.00	-2,716.51	-109.78	390,655.42	798,958.94	32.071262	-103.501634	
15,700.00	90.00	179.50	12,840.00	-2,816.51	-108.91	390,555.42	798,959.82	32.070987	-103.501633	
15,800.00	90.00	179.50	12,840.00	-2,916.51	-108.04	390,455.43	798,960.69	32.070712	-103.501633	
15,900.00	90.00	179.50	12,840.00	-3,016.50	-107.17	390,355.43	798,961.56	32.070438	-103.501633	
16,000.00	90.00	179.50	12,840.00	-3,116.50	-106.29	390,255.44	798,962.43	32.070163	-103.501632	
16,100.00	90.00	179.50	12,840.00	-3,216.50	-105.42	390,155.44	798,963.31	32.069888	-103.501632	
16,200.00	90.00	179.50	12,840.00	-3,316.49	-104.55	390,055.44	798,964.18	32.069613	-103.501632	
16,300.00	90.00	179.50	12,840.00	-3,416.49	-103.68	389,955.45	798,965.05	32.069338	-103.501631	
16,400.00	90.00	179.50	12,840.00	-3,516.48	-102.80	389,855.45	798,965.93	32.069063	-103.501631	
16,500.00	90.00	179.50	12,840.00	-3,616.48	-101.93	389,755.46	798,966.80	32.068788	-103.501631	
16,600.00	90.00	179.50	12,840.00	-3,716.48	-101.06	389,655.46	798,967.67	32.068513	-103.501630	
16,700.00	90.00	179.50	12,840.00	-3,816.47	-100.18	389,555.46	798,968.54	32.068239	-103.501630	
16,800.00	90.00	179.50	12,840.00	-3,916.47	-99.31	389,455.47	798,969.42	32.067964	-103.501630	
16,900.00	90.00	179.50	12,840.00	-4,016.46	-98.44	389,355.47	798,970.29	32.067689	-103.501629	
17,000.00	90.00	179.50	12,840.00	-4,116.46	-97.57	389,255.48	798,971.16	32.067414	-103.501629	
17,100.00	90.00	179.50	12,840.00	-4,216.46	-96.69	389,155.48	798,972.03	32.067139	-103.501629	
17,200.00	90.00	179.50	12,840.00	-4,316.45	-95.82	389,055.48	798,972.91	32.066864	-103.501628	
17,300.00	90.00	179.50	12,840.00	-4,416.45	-94.95	388,955.49	798,973.78	32.066589	-103.501628	
17,400.00	90.00	179.50	12,840.00	-4,516.45	-94.08	388,855.49	798,974.65	32.066314	-103.501628	
17,500.00	90.00	179.50	12,840.00	-4,616.44	-93.20	388,755.50	798,975.52	32.066040	-103.501627	
17,600.00	90.00	179.50	12,840.00	-4,716.44	-92.33	388,655.50	798,976.40	32.065765	-103.501627	
17,700.00	90.00	179.50	12,840.00	-4,816.43	-91.46	388,555.50	798,977.27	32.065490	-103.501627	
17,800.00	90.00	179.50	12,840.00	-4,916.43	-90.59	388,455.51	798,978.14	32.065215	-103.501626	
17,900.00	90.00	179.50	12,840.00	-5,016.43	-89.71	388,355.51	798,979.01	32.064940	-103.501626	
18,000.00	90.00	179.50	12,840.00	-5,116.42	-88.84	388,255.52	798,979.89	32.064665	-103.501626	
18,100.00	90.00	179.50	12,840.00	-5,216.42	-87.97	388,155.52	798,980.76	32.064390	-103.501625	
18,200.00	90.00	179.50	12,840.00	-5,316.42	-87.10	388,055.52	798,981.63	32.064115	-103.501625	
18,300.00	90.00	179.50	12,840.00	-5,416.41	-86.22	387,955.53	798,982.51	32.063841	-103.501625	
18,400.00	90.00	179.50	12,840.00	-5,516.41	-85.35	387,855.53	798,983.38	32.063566	-103.501624	
18,500.00	90.00	179.50	12,840.00	-5,616.40	-84.48	387,755.54	798,984.25	32.063291	-103.501624	
18,600.00	90.00	179.50	12,840.00	-5,716.40	-83.60	387,655.54	798,985.12	32.063016	-103.501624	
18,700.00	90.00	179.50	12,840.00	-5,816.40	-82.73	387,555.54	798,986.00	32.062741	-103.501623	
18,800.00	90.00	179.50	12,840.00	-5,916.39	-81.86	387,455.55	798,986.87	32.062466	-103.501623	
18,900.00	90.00	179.50	12,840.00	-6,016.39	-80.99	387,355.55	798,987.74	32.062191	-103.501623	
19,000.00	90.00	179.50	12,840.00	-6,116.38	-80.11	387,255.56	798,988.61	32.061916	-103.501622	
19,100.00	90.00	179.50	12,840.00	-6,216.38	-79.24	387,155.56	798,989.49	32.061642	-103.501622	
19,200.00	90.00	179.50	12,840.00	-6,316.38	-78.37	387,055.56	798,990.36	32.061367	-103.501622	
19,300.00	90.00	179.50	12,840.00	-6,416.37	-77.50	386,955.57	798,991.23	32.061092	-103.501621	
19,400.00	90.00	179.50	12,840.00	-6,516.37	-76.62	386,855.57	798,992.10	32.060817	-103.501621	
19,500.00	90.00	179.50	12,840.00	-6,616.37	-75.75	386,755.58	798,992.98	32.060542	-103.501621	
19,600.00	90.00	179.50	12,840.00	-6,716.36	-74.88	386,655.58	798,993.85	32.060267	-103.501620	
19,700.00	90.00	179.50	12,840.00	-6,816.36	-74.01	386,555.58	798,994.72	32.059992	-103.501620	
19,800.00	90.00	179.50	12,840.00	-6,916.35	-73.13	386,455.59	798,995.60	32.059717	-103.501620	
19,900.00	90.00	179.50	12,840.00	-7,016.35	-72.26	386,355.59	798,996.47	32.059443	-103.501619	
20,000.00	90.00	179.50	12,840.00	-7,116.35	-71.39	386,255.60	798,997.34	32.059168	-103.501619	
20,100.00	90.00	179.50	12,840.00	-7,216.34	-70.51	386,155.60	798,998.21	32.058893	-103.501619	

Planning Report - Geographic

<b>Database:</b>	EDM r5000.141_Prod US	<b>Local Co-ordinate Reference:</b>	Well Jayhawk FED FEE COM 1H
<b>Company:</b>	WCDSC Permian NM	<b>TVD Reference:</b>	RKB @ 3357.70ft
<b>Project:</b>	Lea County (NAD83 New Mexico East)	<b>MD Reference:</b>	RKB @ 3357.70ft
<b>Site:</b>	Sec 06-T26S-R34E	<b>North Reference:</b>	Grid
<b>Well:</b>	Jayhawk FED FEE COM 1H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Permit Plan 1		

Planned Survey

Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Map Northing (usft)	Map Easting (usft)	Latitude	Longitude
20,200.00	90.00	179.50	12,840.00	-7,316.34	-69.64	386,055.60	798,999.09	32.058618	-103.501618
20,300.00	90.00	179.50	12,840.00	-7,416.34	-68.77	385,955.61	798,999.96	32.058343	-103.501618
20,400.00	90.00	179.50	12,840.00	-7,516.33	-67.90	385,855.61	799,000.83	32.058068	-103.501618
20,500.00	90.00	179.50	12,840.00	-7,616.33	-67.02	385,755.62	799,001.70	32.057793	-103.501617
20,600.00	90.00	179.50	12,840.00	-7,716.32	-66.15	385,655.62	799,002.58	32.057518	-103.501617
20,700.00	90.00	179.50	12,840.00	-7,816.32	-65.28	385,555.62	799,003.45	32.057244	-103.501617
20,800.00	90.00	179.50	12,840.00	-7,916.32	-64.41	385,455.63	799,004.32	32.056969	-103.501616
20,900.00	90.00	179.50	12,840.00	-8,016.31	-63.53	385,355.63	799,005.19	32.056694	-103.501616
21,000.00	90.00	179.50	12,840.00	-8,116.31	-62.66	385,255.64	799,006.07	32.056419	-103.501616
21,100.00	90.00	179.50	12,840.00	-8,216.30	-61.79	385,155.64	799,006.94	32.056144	-103.501615
21,200.00	90.00	179.50	12,840.00	-8,316.30	-60.92	385,055.64	799,007.81	32.055869	-103.501615
21,300.00	90.00	179.50	12,840.00	-8,416.30	-60.04	384,955.65	799,008.69	32.055594	-103.501615
21,400.00	90.00	179.50	12,840.00	-8,516.29	-59.17	384,855.65	799,009.56	32.055319	-103.501614
21,500.00	90.00	179.50	12,840.00	-8,616.29	-58.30	384,755.66	799,010.43	32.055045	-103.501614
21,600.00	90.00	179.50	12,840.00	-8,716.29	-57.42	384,655.66	799,011.30	32.054770	-103.501614
21,700.00	90.00	179.50	12,840.00	-8,816.28	-56.55	384,555.66	799,012.18	32.054495	-103.501614
21,800.00	90.00	179.50	12,840.00	-8,916.28	-55.68	384,455.67	799,013.05	32.054220	-103.501613
21,900.00	90.00	179.50	12,840.00	-9,016.27	-54.81	384,355.67	799,013.92	32.053945	-103.501613
22,000.00	90.00	179.50	12,840.00	-9,116.27	-53.93	384,255.68	799,014.79	32.053670	-103.501613
22,100.00	90.00	179.50	12,840.00	-9,216.27	-53.06	384,155.68	799,015.67	32.053395	-103.501612
22,200.00	90.00	179.50	12,840.00	-9,316.26	-52.19	384,055.68	799,016.54	32.053120	-103.501612
22,300.00	90.00	179.50	12,840.00	-9,416.26	-51.32	383,955.69	799,017.41	32.052846	-103.501612
22,400.00	90.00	179.50	12,840.00	-9,516.26	-50.44	383,855.69	799,018.28	32.052571	-103.501611
22,500.00	90.00	179.50	12,840.00	-9,616.25	-49.57	383,755.70	799,019.16	32.052296	-103.501611
22,600.00	90.00	179.50	12,840.00	-9,716.25	-48.70	383,655.70	799,020.03	32.052021	-103.501611
22,700.00	90.00	179.50	12,840.00	-9,816.24	-47.83	383,555.70	799,020.90	32.051746	-103.501610
22,750.85	90.00	179.50	12,840.00	-9,867.09	-47.38	383,504.86	799,021.35	32.051606	-103.501610

PBHL; 330' FSL, 360' FEL

Design Targets

Target Name	Dip Angle (°)	Dip Dir. (°)	TVD (ft)	+N/-S (ft)	+E/-W (ft)	Northing (usft)	Easting (usft)	Latitude	Longitude
PBHL - Jayhawk FED Ff	0.00	0.00	0.00	-9,867.10	-46.62	383,504.85	799,022.11	32.051606	-103.501608
- hit/miss target									
- Shape									
- plan misses target center by 9867.21ft at 0.00ft MD (0.00 TVD, 0.00 N, 0.00 E)									
- Point									
Vertical Point - Jayhawk	0.00	0.00	8,300.00	315.20	17.30	393,687.12	799,086.03	32.079593	-103.501148
- plan hits target center									
- Point									

Planning Report - Geographic

<b>Database:</b>	EDM r5000.141_Prod US	<b>Local Co-ordinate Reference:</b>	Well Jayhawk FED FEE COM 1H
<b>Company:</b>	WCDSC Permian NM	<b>TVD Reference:</b>	RKB @ 3357.70ft
<b>Project:</b>	Lea County (NAD83 New Mexico East)	<b>MD Reference:</b>	RKB @ 3357.70ft
<b>Site:</b>	Sec 06-T26S-R34E	<b>North Reference:</b>	Grid
<b>Well:</b>	Jayhawk FED FEE COM 1H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Permit Plan 1		

Plan Annotations				
Measured Depth (ft)	Vertical Depth (ft)	Local Coordinates		Comment
		+N/-S (ft)	+E/-W (ft)	
5,000.00	5,000.00	0.00	0.00	Begin Nudge
5,508.59	5,507.55	28.14	1.55	EOB
7,892.75	7,877.05	291.74	16.02	EOH
8,316.57	8,300.00	315.20	17.30	Drop to Vertical
11,956.57	11,940.00	315.20	17.30	KOP @ 11957' MD, 50' FNL, 213' FEL
12,074.72	12,057.31	321.02	6.66	EOB @ 298.68° TF
12,877.61	12,730.95	-15.00	-113.44	1st Take Point @ 12878' MD, 330' FNL, 343' FEL
13,283.40	12,840.00	-400.00	-130.00	Land Point
22,750.85	12,840.00	-9,867.09	-47.38	PBHL; 330' FSL, 360' FEL

# WCDC Permian NM



WELL DETAILS: Jayhawk FED FEE COM 1H

RKB @ 3357.70ft  
3332.70

Northing 393371.93 Easting 799068.73 Latitude 32.078727 Longitude -103.501211

SECTION DETAILS Permit Plan 1

MD	Inc	Azi	TVD	+N/-S	+E/-W	Dleg	V Sect	Annotation
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
5000.00	0.00	0.00	5000.00	0.00	0.00	0.00	0.00	Begin Nudge
5508.59	6.36	3.14	5507.54	28.14	1.55	1.25	-28.15	EOH
7832.75	8.36	3.14	7877.05	291.74	16.02	0.00	-291.82	EOH
8316.57	0.00	0.00	8300.00	315.20	17.30	1.50	-315.28	Drop to Vertical
11956.57	0.00	0.00	11940.00	315.20	17.30	0.00	-315.28	KOP @ 11957' MD, 50' FNL, 213' FEL
12074.72	11.81	298.68	12057.31	321.02	6.66	10.00	-321.05	EOB @ 298.68° TF
13283.40	90.00	179.50	12840.00	-400.00	-130.00	7.92	400.62	Land Point
22750.85	90.00	179.50	12840.00	-9867.10	-47.38	0.00	9867.21	PBHL: 330' FSL, 360' FEL




**devon**



Azimuths to Grid North:  
True North: -0.44°  
Magnetic North: 6.35°

Magnetic Field  
Strength: 47781.3auT  
Dip Angle: 59.93°  
Date: 3/23/2018  
Model: IGRF2015

Vertical Section at 180.28° (400 ft/in)

# 10M BOPE & Closed Loop Equipment Schematic







End View

Top chokes will be hydraulic

Bottom chokes will be manual



Side View



Helmerich & Payne  
Flex 3 Rig w/ 3 Chokes

devon

Name: Mike Potts	Date: 6-23-2010	Working Pressure: 10M	J-5132-E
------------------	-----------------	-----------------------	----------

# **WCDSC Permian NM**

**Lea County (NAD83 New Mexico East)**

**Sec 06-T26S-R34E**

**Jayhawk FED FEE COM 1H**

**Wellbore #1**

**Permit Plan 1**

## **Anticollision Report**

**23 March, 2018**

## Anticollision Report

<b>Company:</b> WCDSC Permian NM	<b>Local Co-ordinate Reference:</b> Well Jayhawk FED FEE COM 1H
<b>Project:</b> Lea County (NAD83 New Mexico East)	<b>TVD Reference:</b> RKB @ 3357.70ft
<b>Reference Site:</b> Sec 06-T26S-R34E	<b>MD Reference:</b> RKB @ 3357.70ft
<b>Site Error:</b> 5.00 ft	<b>North Reference:</b> Grid
<b>Reference Well:</b> Jayhawk FED FEE COM 1H	<b>Survey Calculation Method:</b> Minimum Curvature
<b>Well Error:</b> 0.50 ft	<b>Output errors are at</b> 2.00 sigma
<b>Reference Wellbore</b> Wellbore #1	<b>Database:</b> EDM r5000.141_Prod US
<b>Reference Design:</b> Permit Plan 1	<b>Offset TVD Reference:</b> Offset Datum

<b>Reference</b> Permit Plan 1	
<b>Filter type:</b>	NO GLOBAL FILTER: Using user defined selection & filtering criteria
<b>Interpolation Method:</b>	MD Interval 100.00ft
<b>Depth Range:</b>	Unlimited
<b>Results Limited by:</b>	Maximum center-center distance of 1,000.00 ft
<b>Warning Levels Evaluated at:</b>	2.00 Sigma
<b>Error Model:</b>	ISCWSA
<b>Scan Method:</b>	Closest Approach 3D
<b>Error Surface:</b>	Pedal Curve
<b>Casing Method:</b>	Not applied

<b>Survey Tool Program</b>	<b>Date</b> 3/23/2018			
<b>From (ft)</b>	<b>To (ft)</b>	<b>Survey (Wellbore)</b>	<b>Tool Name</b>	<b>Description</b>
0.00	22,750.61	Permit Plan 1 (Wellbore #1)	MWD+HDGM	OWSG MWD + HDGM

Site Name	Reference	Offset	Distance		Separation Factor	Warning
	Measured Depth (ft)	Measured Depth (ft)	Between Centres (ft)	Between Ellipses (ft)		
<b>Offset Well - Wellbore - Design</b>						
Sec 06-T26S-R34E						
Jayhawk 6-7 FED FEE COM 2H - Wellbore #1 - Permit P	2,700.00	2,699.10	30.00	11.07	1.585	Minor Risk, CC
Jayhawk 6-7 FED FEE COM 2H - Wellbore #1 - Permit P	2,800.00	2,798.87	30.38	10.73	1.546	Minor Risk, ES
Jayhawk 6-7 FED FEE COM 2H - Wellbore #1 - Permit P	22,750.85	22,587.48	199.10	30.95	1.184	Major Risk, SF
Jayhawk 6-7 FED FEE COM 3H - Wellbore #1 - Permit P	4,000.00	3,998.20	59.98	31.74	2.124	Minor Risk, CC, ES
Jayhawk 6-7 FED FEE COM 3H - Wellbore #1 - Permit P	22,750.85	22,590.98	667.95	325.06	1.948	Minor Risk, SF
Jayhawk 6-7 FED FEE COM 4H - Wellbore #1 - Permit P	2,700.00	2,694.90	335.22	316.30	17.720	CC, ES
Jayhawk 6-7 FED FEE COM 4H - Wellbore #1 - Permit P	3,500.00	3,455.33	388.41	364.07	15.958	SF
Jayhawk 6-7 FED FEE COM 5H - Wellbore #1 - Permit P	5,010.68	5,011.52	149.95	114.45	4.225	Alert, CC
Jayhawk 6-7 FED FEE COM 5H - Wellbore #1 - Permit P	5,700.00	5,716.70	152.70	112.39	3.788	Alert, ES
Jayhawk 6-7 FED FEE COM 5H - Wellbore #1 - Permit P	10,300.00	10,300.00	212.16	138.41	2.877	Alert, SF
NE Salado Draw Deep Unit 1 / INC / AUD - Original Hole						Out of range
Salado Draw 6 Fed 1H - Original Hole - Actual						Out of range
Salado Draw 6 Fed 2H - Original Hole - BRN						Out of range
Salado Draw 6 Fed 2H - Original Hole - Original Hole						Out of range
Salado Draw 6 Fed 2H - Original Hole - Plan 4						Out of range
Salado Draw 6 Fed 2H - Original Hole - Plan 5						Out of range
Salado Draw 6 Fed 2H - Original Hole - Plan 6						Out of range
Salado Draw 6 Fed 2H - Original Hole - Plan 7						Out of range
Salado Draw 6 Fed 2H - Original Hole - Plan 8						Out of range
Salado Draw 6 Fed 2H - Original Hole - T&D						Out of range
Sec 07-T26S-R34E						
Ichabod 7 Federal 01H - Wellbore #1 - Wellbore #1						Out of range
Ichabod 7 Federal 04H - Wellbore #1 - Wellbore #1						Out of range

Offset Design													Offset Site Error:	5.00 ft
Survey Program: 0-MWD+HDGM													Offset Well Error:	0.50 ft
Reference		Offset		Semi Major Axis			Distance					Warning		
Measured Depth (ft)	Vertical Depth (ft)	Measured Depth (ft)	Vertical Depth (ft)	Reference (ft)	Offset (ft)	Highside Toolface (°)	Offset Wellbore Centre +N/-S (ft)	+E/-W (ft)	Between Centres (ft)	Between Ellipses (ft)	Minimum Separation (ft)		Separation Factor	
0.00	0.00	0.90	-0.90	0.50	0.50	-90.40	-0.21	-30.00	30.00					
100.00	100.00	100.90	99.10	0.52	0.52	-90.40	-0.21	-30.00	30.00	28.96	1.04	28.948		
200.00	200.00	200.90	199.10	0.70	0.70	-90.40	-0.21	-30.00	30.00	28.59	1.41	21.330		
300.00	300.00	300.90	299.10	0.99	0.99	-90.40	-0.21	-30.00	30.00	28.02	1.98	15.171		
400.00	400.00	400.90	399.10	1.31	1.31	-90.40	-0.21	-30.00	30.00	27.38	2.62	11.446		

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

# Anticollision Report

**Company:** WCDCS Permian NM  
**Project:** Lea County (NAD83 New Mexico East)  
**Reference Site:** Sec 06-T26S-R34E  
**Site Error:** 5.00 ft  
**Reference Well:** Jayhawk FED FEE COM 1H  
**Well Error:** 0.50 ft  
**Reference Wellbore:** Wellbore #1  
**Reference Design:** Permit Plan 1

**Local Co-ordinate Reference:** Well Jayhawk FED FEE COM 1H  
**TVD Reference:** RKB @ 3357.70ft  
**MD Reference:** RKB @ 3357.70ft  
**North Reference:** Grid  
**Survey Calculation Method:** Minimum Curvature  
**Output errors are at:** 2.00 sigma  
**Database:** EDM r5000.141\_Prod US  
**Offset TVD Reference:** Offset Datum

Offset Design														Offset Site Error:
Sec 06-T26S-R34E - Jayhawk 6-7 FED FEE COM 2H - Wellbore #1 - Permit Plan 1														5.00 ft
Survey Program: 0-MWD+HDGM														Offset Well Error:
														0.50 ft
Reference		Offset		Semi Major Axis		Distance								Warning
Measured Depth (ft)	Vertical Depth (ft)	Measured Depth (ft)	Vertical Depth (ft)	Reference (ft)	Offset (ft)	Highside Toolface (°)	Offset Wellbore Centre +N/-S (ft)	Offset Wellbore Centre +E/-W (ft)	Between Centres (ft)	Between Ellipses (ft)	Minimum Separation (ft)	Separation Factor		
500.00	500.00	500.90	499.10	1.65	1.65	-90.40	-0.21	-30.00	30.00	26.71	3.30	9.104		
600.00	600.00	600.90	599.10	1.99	1.99	-90.40	-0.21	-30.00	30.00	26.02	3.98	7.530		
700.00	700.00	700.90	699.10	2.34	2.34	-90.40	-0.21	-30.00	30.00	25.32	4.68	6.408		
800.00	800.00	800.90	799.10	2.69	2.69	-90.40	-0.21	-30.00	30.00	24.62	5.38	5.572		
900.00	900.00	900.90	899.10	3.04	3.05	-90.40	-0.21	-30.00	30.00	23.91	6.09	4.926	Alert	
1,000.00	1,000.00	1,000.90	999.10	3.40	3.40	-90.40	-0.21	-30.00	30.00	23.20	6.80	4.413	Alert	
1,100.00	1,100.00	1,100.90	1,099.10	3.75	3.76	-90.40	-0.21	-30.00	30.00	22.49	7.51	3.996	Alert	
1,200.00	1,200.00	1,200.90	1,199.10	4.11	4.11	-90.40	-0.21	-30.00	30.00	21.78	8.22	3.650	Alert	
1,300.00	1,300.00	1,300.90	1,299.10	4.46	4.47	-90.40	-0.21	-30.00	30.00	21.07	8.93	3.359	Alert	
1,400.00	1,400.00	1,400.90	1,399.10	4.82	4.82	-90.40	-0.21	-30.00	30.00	20.36	9.64	3.111	Alert	
1,500.00	1,500.00	1,500.90	1,499.10	5.18	5.18	-90.40	-0.21	-30.00	30.00	19.64	10.36	2.896	Alert	
1,600.00	1,600.00	1,600.90	1,599.10	5.53	5.54	-90.40	-0.21	-30.00	30.00	18.93	11.07	2.710	Alert	
1,700.00	1,700.00	1,700.90	1,699.10	5.89	5.89	-90.40	-0.21	-30.00	30.00	18.22	11.79	2.546	Alert	
1,800.00	1,800.00	1,800.90	1,799.10	6.25	6.25	-90.40	-0.21	-30.00	30.00	17.50	12.50	2.400	Minor Risk	
1,900.00	1,900.00	1,900.90	1,899.10	6.61	6.61	-90.40	-0.21	-30.00	30.00	16.79	13.21	2.270	Minor Risk	
2,000.00	2,000.00	2,000.90	1,999.10	6.96	6.97	-90.40	-0.21	-30.00	30.00	16.07	13.93	2.154	Minor Risk	
2,100.00	2,100.00	2,100.90	2,099.10	7.32	7.32	-90.40	-0.21	-30.00	30.00	15.36	14.65	2.049	Minor Risk	
2,200.00	2,200.00	2,200.90	2,199.10	7.68	7.68	-90.40	-0.21	-30.00	30.00	14.64	15.36	1.953	Minor Risk	
2,300.00	2,300.00	2,300.90	2,299.10	8.04	8.04	-90.40	-0.21	-30.00	30.00	13.92	16.08	1.866	Minor Risk	
2,400.00	2,400.00	2,400.90	2,399.10	8.39	8.40	-90.40	-0.21	-30.00	30.00	13.21	16.79	1.787	Minor Risk	
2,500.00	2,500.00	2,500.90	2,499.10	8.75	8.76	-90.40	-0.21	-30.00	30.00	12.49	17.51	1.714	Minor Risk	
2,600.00	2,600.00	2,600.90	2,599.10	9.11	9.11	-90.40	-0.21	-30.00	30.00	11.78	18.22	1.646	Minor Risk	
2,700.00	2,700.00	2,699.10	2,699.10	9.47	9.46	-90.40	-0.21	-30.00	30.00	11.07	18.93	1.585	Minor Risk, CC	
2,800.00	2,800.00	2,798.87	2,798.86	9.83	9.82	-88.95	0.56	-30.37	30.38	10.73	19.65	1.546	Minor Risk, ES	
2,900.00	2,900.00	2,898.57	2,898.53	10.18	10.18	-84.77	2.88	-31.50	31.64	11.28	20.36	1.554	Minor Risk	
3,000.00	3,000.00	2,998.16	2,998.02	10.54	10.53	-78.54	6.77	-33.39	34.08	13.02	21.06	1.618	Minor Risk	
3,100.00	3,100.00	3,102.35	3,097.34	10.90	10.90	-71.33	12.17	-36.01	38.05	16.27	21.78	1.747	Minor Risk	
3,200.00	3,200.00	3,202.57	3,196.90	11.26	11.26	-65.05	18.09	-38.89	42.95	20.46	22.49	1.910	Minor Risk	
3,300.00	3,300.00	3,302.78	3,296.47	11.62	11.62	-60.11	24.01	-41.77	48.25	25.05	23.20	2.079	Minor Risk	
3,400.00	3,400.00	3,397.00	3,396.03	11.97	11.96	-56.16	29.93	-44.64	53.84	29.94	23.89	2.253	Minor Risk	
3,500.00	3,500.00	3,503.22	3,495.59	12.33	12.34	-52.97	35.85	-47.52	59.63	35.00	24.63	2.421	Minor Risk	
3,600.00	3,600.00	3,603.44	3,595.16	12.69	12.70	-50.34	41.78	-50.40	65.58	40.24	25.34	2.588	Alert	
3,700.00	3,700.00	3,703.65	3,694.72	13.05	13.06	-48.16	47.70	-53.27	71.64	45.58	26.06	2.749	Alert	
3,800.00	3,800.00	3,803.87	3,794.29	13.41	13.42	-46.32	53.62	-56.15	77.79	51.01	26.77	2.905	Alert	
3,900.00	3,900.00	3,904.09	3,893.85	13.77	13.78	-44.75	59.54	-59.03	84.00	56.52	27.49	3.056	Alert	
4,000.00	4,000.00	4,004.31	3,993.42	14.12	14.14	-43.40	65.46	-61.90	90.28	62.07	28.21	3.201	Alert	
4,100.00	4,100.00	4,104.53	4,092.98	14.48	14.50	-42.22	71.38	-64.78	96.59	67.67	28.92	3.340	Alert	
4,200.00	4,200.00	4,195.26	4,192.55	14.84	14.83	-41.19	77.30	-67.66	102.94	73.34	29.60	3.477	Alert	
4,300.00	4,300.00	4,304.96	4,292.11	15.20	15.23	-40.28	83.23	-70.53	109.32	78.96	30.36	3.601	Alert	
4,400.00	4,400.00	4,405.18	4,391.68	15.56	15.59	-39.47	89.15	-73.41	115.72	84.65	31.07	3.724	Alert	
4,500.00	4,500.00	4,505.40	4,491.24	15.92	15.95	-38.74	95.07	-76.29	122.15	90.36	31.79	3.842	Alert	
4,600.00	4,600.00	4,605.62	4,590.81	16.27	16.32	-38.09	100.99	-79.16	128.59	96.08	32.51	3.956	Alert	
4,700.00	4,700.00	4,705.83	4,690.37	16.63	16.68	-37.50	106.91	-82.04	135.05	101.82	33.22	4.065	Alert	
4,800.00	4,800.00	4,793.95	4,789.94	16.99	17.00	-36.96	112.83	-84.92	141.52	107.62	33.90	4.175	Alert	
4,900.00	4,900.00	4,906.27	4,889.50	17.35	17.41	-36.48	118.76	-87.79	148.00	113.34	34.66	4.270	Alert	
5,000.00	5,000.00	5,006.49	4,989.07	17.71	17.77	-36.03	124.68	-90.67	154.49	119.11	35.38	4.367	Alert	
5,100.00	5,099.99	5,106.65	5,088.68	18.06	18.14	-38.96	130.60	-93.55	160.14	124.04	36.10	4.437	Alert	
5,200.00	5,199.94	5,206.73	5,188.38	18.42	18.50	-39.25	136.53	-96.43	164.10	127.29	36.81	4.458	Alert	
5,300.00	5,299.79	5,306.79	5,288.11	18.78	18.87	-40.01	142.46	-99.31	166.39	128.86	37.53	4.434	Alert	
5,400.00	5,399.49	5,406.86	5,387.82	19.14	19.23	-41.26	148.39	-102.19	167.07	128.82	38.25	4.368	Alert	
5,500.00	5,499.01	5,506.99	5,487.47	19.49	19.59	-43.01	154.32	-105.07	166.22	127.25	38.96	4.266	Alert	
5,600.00	5,598.40	5,592.81	5,587.06	19.85	19.91	-45.09	160.24	-107.95	164.63	125.00	39.63	4.154	Alert	

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

Anticollision Report

Company: WCDSC Permian NM  
 Project: Lea County (NAD83 New Mexico East)  
 Reference Site: Sec 06-T26S-R34E  
 Site Error: 5.00 ft  
 Reference Well: Jayhawk FED FEE COM 1H  
 Well Error: 0.50 ft  
 Reference Wellbore: Wellbore #1  
 Reference Design: Permit Plan 1

Local Co-ordinate Reference: Well Jayhawk FED FEE COM 1H  
 TVD Reference: RKB @ 3357.70ft  
 MD Reference: RKB @ 3357.70ft  
 North Reference: Grid  
 Survey Calculation Method: Minimum Curvature  
 Output errors are at: 2.00 sigma  
 Database: EDM r5000.141\_Prod US  
 Offset TVD Reference: Offset Datum

Offset Design Sec 06-T26S-R34E - Jayhawk 6-7 FED FEE COM 2H - Wellbore #1 - Permit Plan 1														Offset Site Error:	5.00 ft
Survey Program: 0-MWD+HDGM														Offset Well Error:	0.50 ft
Reference		Offset		Semi Major Axis			Distance							Warning	
Measured Depth (ft)	Vertical Depth (ft)	Measured Depth (ft)	Vertical Depth (ft)	Reference (ft)	Offset (ft)	Highside Toolface (°)	Offset Wellbore Centre +N/-S (ft)	+E/-W (ft)	Between Centres (ft)	Between Ellipses (ft)	Minimum Separation (ft)	Separation Factor	Warning		
5,700.00	5,697.78	5,707.38	5,686.65	20.20	20.32	-47.20	166.17	-110.83	163.25	122.85	40.40	4.041	Alert		
5,800.00	5,797.17	5,807.57	5,786.24	20.56	20.69	-49.34	172.09	-113.70	162.10	120.98	41.12	3.942	Alert		
5,900.00	5,896.55	5,907.77	5,885.83	20.92	21.06	-51.52	178.01	-116.58	161.18	119.34	41.84	3.852	Alert		
6,000.00	5,995.94	5,992.04	5,985.42	21.28	21.36	-53.71	183.93	-119.46	160.50	117.99	42.51	3.776	Alert		
6,100.00	6,095.32	6,108.15	6,085.01	21.64	21.79	-55.92	189.86	-122.34	160.05	116.76	43.29	3.697	Alert		
6,200.00	6,194.71	6,208.34	6,184.60	22.00	22.15	-58.14	195.78	-125.21	159.84	115.83	44.02	3.632	Alert		
6,235.50	6,229.99	6,227.09	6,219.96	22.13	22.22	-58.93	197.88	-126.24	159.83	115.62	44.21	3.615	Alert		
6,300.00	6,294.09	6,308.54	6,284.19	22.37	22.52	-60.36	201.70	-128.09	159.88	115.14	44.74	3.573	Alert		
6,400.00	6,393.48	6,408.73	6,383.78	22.73	22.88	-62.57	207.63	-130.97	160.16	114.68	45.47	3.522	Alert		
6,500.00	6,492.86	6,491.08	6,483.37	23.09	23.18	-64.78	213.55	-133.85	160.67	114.53	46.14	3.482	Alert		
6,600.00	6,592.25	6,609.12	6,582.96	23.46	23.62	-66.97	219.47	-136.72	161.42	114.49	46.94	3.439	Alert		
6,700.00	6,691.63	6,709.31	6,682.55	23.82	23.98	-69.13	225.40	-139.60	162.41	114.74	47.67	3.407	Alert		
6,800.00	6,791.02	6,809.50	6,782.14	24.19	24.35	-71.27	231.32	-142.48	163.63	115.22	48.40	3.380	Alert		
6,900.00	6,890.40	6,909.69	6,881.73	24.56	24.71	-73.37	237.24	-145.36	165.07	115.93	49.14	3.359	Alert		
7,000.00	6,989.79	7,009.89	6,981.32	24.92	25.08	-75.43	243.17	-148.23	166.73	116.85	49.88	3.343	Alert		
7,100.00	7,089.17	7,089.92	7,080.91	25.29	25.37	-77.45	249.09	-151.11	168.60	118.06	50.54	3.336	Alert		
7,200.00	7,188.56	7,189.73	7,180.49	25.66	25.74	-79.42	255.01	-153.99	170.68	119.40	51.28	3.328	Alert		
7,300.00	7,287.94	7,289.54	7,280.08	26.03	26.10	-81.35	260.93	-156.87	172.95	120.93	52.02	3.325	Alert		
7,400.00	7,387.33	7,389.34	7,379.67	26.40	26.47	-83.22	266.86	-159.74	175.42	122.66	52.76	3.325	Alert		
7,500.00	7,486.71	7,489.15	7,479.26	26.77	26.83	-85.04	272.78	-162.62	178.06	124.57	53.50	3.329	Alert		
7,600.00	7,586.10	7,588.96	7,578.85	27.14	27.20	-86.80	278.70	-165.50	180.89	126.65	54.24	3.335	Alert		
7,700.00	7,685.48	7,688.76	7,678.44	27.51	27.56	-88.51	284.63	-168.38	183.87	128.90	54.98	3.345	Alert		
7,800.00	7,784.87	7,788.57	7,778.03	27.88	27.93	-90.16	290.55	-171.25	187.02	131.30	55.72	3.357	Alert		
7,900.00	7,884.25	7,888.38	7,877.62	28.25	28.30	-91.76	296.47	-174.13	190.32	133.86	56.46	3.371	Alert		
8,000.00	7,983.79	7,988.25	7,977.28	28.62	28.66	-92.91	302.40	-177.01	193.68	136.48	57.20	3.386	Alert		
8,100.00	8,083.54	8,088.86	8,077.67	28.98	29.03	-93.29	308.27	-179.86	196.89	138.96	57.93	3.399	Alert		
8,200.00	8,183.45	8,191.13	8,179.84	29.34	29.40	-93.41	312.39	-181.86	199.09	140.42	58.67	3.393	Alert		
8,300.00	8,283.43	8,293.43	8,282.12	29.70	29.76	-93.46	314.05	-182.62	199.98	140.59	59.39	3.367	Alert		
8,400.00	8,383.43	8,406.16	8,382.53	30.06	30.16	-93.32	314.09	-182.69	200.00	139.85	60.14	3.325	Alert		
8,500.00	8,483.43	8,506.16	8,482.53	30.41	30.52	-93.32	314.09	-182.69	200.00	139.14	60.85	3.287	Alert		
8,600.00	8,583.43	8,606.16	8,582.53	30.77	30.87	-93.32	314.09	-182.69	200.00	138.44	61.56	3.249	Alert		
8,700.00	8,683.43	8,706.16	8,682.53	31.12	31.22	-93.32	314.09	-182.69	200.00	137.73	62.27	3.212	Alert		
8,800.00	8,783.43	8,806.16	8,782.53	31.48	31.58	-93.32	314.09	-182.69	200.00	137.02	62.98	3.176	Alert		
8,900.00	8,883.43	8,906.16	8,882.53	31.83	31.93	-93.32	314.09	-182.69	200.00	136.31	63.69	3.140	Alert		
9,000.00	8,983.43	9,006.16	8,982.53	32.19	32.28	-93.32	314.09	-182.69	200.00	135.60	64.40	3.106	Alert		
9,100.00	9,083.43	9,106.16	9,082.53	32.54	32.64	-93.32	314.09	-182.69	200.00	134.89	65.11	3.072	Alert		
9,200.00	9,183.43	9,206.16	9,182.53	32.90	32.99	-93.32	314.09	-182.69	200.00	134.18	65.82	3.039	Alert		
9,300.00	9,283.43	9,306.16	9,282.53	33.25	33.35	-93.32	314.09	-182.69	200.00	133.47	66.53	3.006	Alert		
9,400.00	9,383.43	9,406.16	9,382.53	33.61	33.70	-93.32	314.09	-182.69	200.00	132.76	67.23	2.975	Alert		
9,500.00	9,483.43	9,506.16	9,482.53	33.96	34.06	-93.32	314.09	-182.69	200.00	132.05	67.94	2.944	Alert		
9,600.00	9,583.43	9,606.16	9,582.53	34.32	34.41	-93.32	314.09	-182.69	200.00	131.34	68.65	2.913	Alert		
9,700.00	9,683.43	9,706.16	9,682.53	34.67	34.76	-93.32	314.09	-182.69	200.00	130.63	69.37	2.883	Alert		
9,800.00	9,783.43	9,806.16	9,782.53	35.03	35.12	-93.32	314.09	-182.69	200.00	129.92	70.08	2.854	Alert		
9,900.00	9,883.43	9,906.16	9,882.53	35.38	35.47	-93.32	314.09	-182.69	200.00	129.21	70.79	2.825	Alert		
10,000.00	9,983.43	10,006.16	9,982.53	35.74	35.83	-93.32	314.09	-182.69	200.00	128.50	71.50	2.797	Alert		
10,100.00	10,083.43	10,106.16	10,082.53	36.10	36.18	-93.32	314.09	-182.69	200.00	127.79	72.21	2.770	Alert		
10,200.00	10,183.43	10,206.16	10,182.53	36.45	36.54	-93.32	314.09	-182.69	200.00	127.08	72.92	2.743	Alert		
10,300.00	10,283.43	10,306.16	10,282.53	36.81	36.89	-93.32	314.09	-182.69	200.00	126.37	73.63	2.716	Alert		
10,400.00	10,383.43	10,406.16	10,382.53	37.16	37.25	-93.32	314.09	-182.69	200.00	125.66	74.34	2.690	Alert		
10,500.00	10,483.43	10,506.16	10,482.53	37.52	37.60	-93.32	314.09	-182.69	200.00	124.95	75.05	2.665	Alert		
10,600.00	10,583.43	10,606.16	10,582.53	37.87	37.96	-93.32	314.09	-182.69	200.00	124.24	75.76	2.640	Alert		
10,700.00	10,683.43	10,706.16	10,682.53	38.23	38.31	-93.32	314.09	-182.69	200.00	123.52	76.47	2.615	Alert		

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

### Anticollision Report

**Company:** WCDSC Permian NM  
**Project:** Lea County (NAD83 New Mexico East)  
**Reference Site:** Sec 06-T26S-R34E  
**Site Error:** 5.00 ft  
**Reference Well:** Jayhawk FED FEE COM 1H  
**Well Error:** 0.50 ft  
**Reference Wellbore:** Wellbore #1  
**Reference Design:** Permit Plan 1

**Local Co-ordinate Reference:** Well Jayhawk FED FEE COM 1H  
**TVD Reference:** RKB @ 3357.70ft  
**MD Reference:** RKB @ 3357.70ft  
**North Reference:** Grid  
**Survey Calculation Method:** Minimum Curvature  
**Output errors are at:** 2.00 sigma  
**Database:** EDM r5000.141\_Prod US  
**Offset TVD Reference:** Offset Datum

Offset Design														Offset Site Error:	5.00 ft	
Sec 06-T26S-R34E - Jayhawk 6-7 FED FEE COM 2H - Wellbore #1 - Permit Plan 1														Offset Well Error:		0.50 ft
Survey Program: 0-MWD+HDGM																
Reference				Offset		Semi Major Axis			Distance					Warning		
Measured Depth (ft)	Vertical Depth (ft)	Measured Depth (ft)	Vertical Depth (ft)	Reference (ft)	Offset (ft)	Highside Toolface (°)	Offset Wellbore Centre +N/-S (ft)	Offset Wellbore Centre +E/-W (ft)	Between Centres (ft)	Between Ellipses (ft)	Minimum Separation (ft)	Separation Factor	Warning			
10,800.00	10,783.43	10,806.16	10,782.53	38.59	38.67	-90.32	314.09	-182.69	200.00	122.81	77.19	2.591	Alert			
10,900.00	10,883.43	10,906.16	10,882.53	38.94	39.02	-90.32	314.09	-182.69	200.00	122.10	77.90	2.567	Alert			
11,000.00	10,983.43	11,006.16	10,982.53	39.30	39.38	-90.32	314.09	-182.69	200.00	121.39	78.61	2.544	Alert			
11,100.00	11,083.43	11,106.16	11,082.53	39.65	39.74	-90.32	314.09	-182.69	200.00	120.68	79.32	2.521	Alert			
11,200.00	11,183.43	11,206.16	11,182.53	40.01	40.09	-90.32	314.09	-182.69	200.00	119.97	80.03	2.499	Minor Risk			
11,300.00	11,283.43	11,306.16	11,282.53	40.37	40.45	-90.32	314.09	-182.69	200.00	119.25	80.74	2.477	Minor Risk			
11,400.00	11,383.43	11,406.16	11,382.53	40.72	40.80	-90.32	314.09	-182.69	200.00	118.54	81.46	2.455	Minor Risk			
11,500.00	11,483.43	11,506.16	11,482.53	41.08	41.16	-90.32	314.09	-182.69	200.00	117.83	82.17	2.434	Minor Risk			
11,600.00	11,583.43	11,606.16	11,582.53	41.44	41.51	-90.32	314.09	-182.69	200.00	117.12	82.88	2.413	Minor Risk			
11,700.00	11,683.43	11,706.16	11,682.53	41.79	41.87	-90.32	314.09	-182.69	200.00	116.40	83.59	2.393	Minor Risk			
11,800.00	11,783.43	11,806.16	11,782.53	42.15	42.22	-90.32	314.09	-182.69	200.00	115.69	84.31	2.372	Minor Risk			
11,900.00	11,883.43	11,906.16	11,882.53	42.51	42.58	-90.32	314.09	-182.69	200.00	114.98	85.02	2.352	Minor Risk			
12,000.00	11,983.39	12,006.20	11,982.49	42.86	42.94	-29.30	314.09	-182.69	198.56	112.83	85.73	2.316	Minor Risk			
12,100.00	12,082.09	12,092.34	12,081.03	43.21	43.24	-22.63	313.92	-182.69	185.03	98.64	86.39	2.142	Minor Risk			
12,200.00	12,180.39	12,188.23	12,176.25	43.54	43.54	16.46	303.59	-182.55	167.82	80.80	87.01	1.929	Minor Risk			
12,300.00	12,277.69	12,282.00	12,266.43	43.84	43.80	39.60	278.28	-182.21	152.06	64.59	87.47	1.738	Minor Risk			
12,400.00	12,372.14	12,373.45	12,349.26	44.11	44.03	46.68	239.77	-181.70	139.09	51.68	87.41	1.591	Minor Risk			
12,500.00	12,461.94	12,462.46	12,423.02	44.36	44.22	45.80	190.10	-181.03	130.40	44.26	86.15	1.514	Minor Risk			
12,600.00	12,545.38	12,549.03	12,486.54	44.60	44.38	40.93	131.41	-180.25	127.26	44.29	82.97	1.534	Minor Risk			
12,601.84	12,546.85	12,550.60	12,487.61	44.60	44.38	40.82	130.26	-180.23	127.26	44.37	82.89	1.535	Minor Risk			
12,700.00	12,620.86	12,633.20	12,539.15	44.82	44.52	34.48	65.80	-179.37	130.17	52.30	77.87	1.672	Minor Risk			
12,800.00	12,686.95	12,715.07	12,580.56	45.04	44.66	28.07	-4.72	-178.43	138.58	66.73	71.85	1.929	Minor Risk			
12,900.00	12,742.37	12,794.75	12,610.83	45.24	44.79	22.61	-78.35	-177.45	151.24	84.93	66.31	2.281	Minor Risk			
13,000.00	12,786.09	12,872.36	12,630.22	45.44	44.91	18.37	-153.44	-176.44	166.73	104.48	62.25	2.678	Alert			
13,100.00	12,817.25	12,950.00	12,639.30	45.65	45.03	15.19	-230.48	-175.41	183.83	123.68	60.16	3.056	Alert			
13,200.00	12,835.28	13,036.92	12,640.00	45.85	45.18	12.93	-317.38	-174.25	199.38	139.79	59.59	3.346	Alert			
13,300.00	12,840.00	13,136.73	12,640.00	46.05	45.38	12.20	-417.18	-172.92	203.71	144.05	59.66	3.414	Alert			
13,400.00	12,840.00	13,236.73	12,640.00	46.28	45.63	12.08	-517.17	-171.58	203.61	143.68	59.93	3.397	Alert			
13,500.00	12,840.00	13,336.73	12,640.00	46.56	45.92	11.95	-617.16	-170.24	203.51	143.26	60.25	3.378	Alert			
13,600.00	12,840.00	13,436.72	12,640.00	46.88	46.26	11.82	-717.15	-168.91	203.42	142.81	60.60	3.356	Alert			
13,700.00	12,840.00	13,536.72	12,640.00	47.24	46.64	11.69	-817.14	-167.57	203.32	142.32	61.00	3.333	Alert			
13,800.00	12,840.00	13,636.72	12,640.00	47.64	47.06	11.57	-917.13	-166.24	203.23	141.79	61.44	3.308	Alert			
13,900.00	12,840.00	13,736.72	12,640.00	48.08	47.53	11.44	-1,017.12	-164.90	203.14	141.21	61.92	3.281	Alert			
14,000.00	12,840.00	13,836.72	12,640.00	48.57	48.03	11.31	-1,117.11	-163.56	203.04	140.61	62.44	3.252	Alert			
14,100.00	12,840.00	13,936.72	12,640.00	49.09	48.57	11.18	-1,217.10	-162.23	202.95	139.96	62.99	3.222	Alert			
14,200.00	12,840.00	14,036.72	12,640.00	49.65	49.15	11.05	-1,317.09	-160.89	202.86	139.28	63.58	3.191	Alert			
14,300.00	12,840.00	14,136.72	12,640.00	50.24	49.76	10.92	-1,417.08	-159.55	202.78	138.57	64.20	3.158	Alert			
14,400.00	12,840.00	14,236.72	12,640.00	50.87	50.41	10.80	-1,517.07	-158.22	202.69	137.83	64.86	3.125	Alert			
14,500.00	12,840.00	14,336.71	12,640.00	51.53	51.09	10.67	-1,617.06	-156.88	202.60	137.05	65.55	3.091	Alert			
14,600.00	12,840.00	14,436.71	12,640.00	52.23	51.80	10.54	-1,717.05	-155.54	202.52	136.25	66.27	3.056	Alert			
14,700.00	12,840.00	14,536.71	12,640.00	52.95	52.55	10.41	-1,817.04	-154.21	202.43	135.41	67.02	3.020	Alert			
14,800.00	12,840.00	14,636.71	12,640.00	53.71	53.32	10.28	-1,917.03	-152.87	202.35	134.55	67.80	2.985	Alert			
14,900.00	12,840.00	14,736.71	12,640.00	54.49	54.12	10.15	-2,017.02	-151.54	202.27	133.66	68.60	2.948	Alert			
15,000.00	12,840.00	14,836.71	12,640.00	55.30	54.95	10.02	-2,117.01	-150.20	202.19	132.75	69.44	2.912	Alert			
15,100.00	12,840.00	14,936.71	12,640.00	56.14	55.81	9.89	-2,217.00	-148.86	202.11	131.81	70.29	2.875	Alert			
15,200.00	12,840.00	15,036.71	12,640.00	57.00	56.69	9.76	-2,316.99	-147.53	202.03	130.85	71.18	2.838	Alert			
15,300.00	12,840.00	15,136.71	12,640.00	57.89	57.59	9.63	-2,416.98	-146.19	201.95	129.87	72.08	2.802	Alert			
15,400.00	12,840.00	15,236.70	12,640.00	58.80	58.51	9.50	-2,516.97	-144.85	201.87	128.86	73.01	2.765	Alert			
15,500.00	12,840.00	15,336.70	12,640.00	59.73	59.46	9.37	-2,616.96	-143.52	201.80	127.84	73.96	2.729	Alert			
15,600.00	12,840.00	15,436.70	12,640.00	60.68	60.43	9.24	-2,716.95	-142.18	201.72	126.79	74.93	2.692	Alert			
15,700.00	12,840.00	15,536.70	12,640.00	61.65	61.41	9.11	-2,816.94	-140.84	201.65	125.73	75.91	2.656	Alert			
15,800.00	12,840.00	15,636.70	12,640.00	62.64	62.42	8.98	-2,916.93	-139.51	201.57	124.65	76.92	2.621	Alert			

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

# Anticollision Report

<b>Company:</b> WCDSC Permian NM	<b>Local Co-ordinate Reference:</b> Well Jayhawk FED FEE COM 1H
<b>Project:</b> Lea County (NAD83 New Mexico East)	<b>TVD Reference:</b> RKB @ 3357.70ft
<b>Reference Site:</b> Sec 06-T26S-R34E	<b>MD Reference:</b> RKB @ 3357.70ft
<b>Site Error:</b> 5.00 ft	<b>North Reference:</b> Grid
<b>Reference Well:</b> Jayhawk FED FEE COM 1H	<b>Survey Calculation Method:</b> Minimum Curvature
<b>Well Error:</b> 0.50 ft	<b>Output errors are at</b> 2.00 sigma
<b>Reference Wellbore:</b> Wellbore #1	<b>Database:</b> EDM r5000.141_Prod US
<b>Reference Design:</b> Permit Plan 1	<b>Offset TVD Reference:</b> Offset Datum

Offset Design      Sec 06-T26S-R34E - Jayhawk 6-7 FED FEE COM 2H - Wellbore #1 - Permit Plan 1														Offset Site Error:	5.00 ft
Survey Program: 0-MWD+HDGM														Offset Well Error:	0.50 ft
Reference				Offset				Distance						Warning	
Measured Depth (ft)	Vertical Depth (ft)	Measured Depth (ft)	Vertical Depth (ft)	Reference (ft)	Offset (ft)	Highside Toolface (°)	Offset Wellbore Centre +N/-S (ft)	+E/-W (ft)	Between Centres (ft)	Between Ellipses (ft)	Minimum Separation (ft)	Separation Factor			
15,900.00	12,840.00	15,736.70	12,640.00	63.64	63.44	8.85	-3,016.92	-138.17	201.50	123.56	77.95	2.585	Alert		
16,000.00	12,840.00	15,836.70	12,640.00	64.67	64.48	8.72	-3,116.91	-136.84	201.43	122.44	78.99	2.550	Alert		
16,100.00	12,840.00	15,936.70	12,640.00	65.71	65.53	8.59	-3,216.90	-135.50	201.36	121.32	80.05	2.516	Alert		
16,200.00	12,840.00	16,036.70	12,640.00	66.76	66.60	8.46	-3,316.89	-134.16	201.29	120.17	81.12	2.481	Minor Risk		
16,300.00	12,840.00	16,136.70	12,640.00	67.83	67.69	8.33	-3,416.88	-132.83	201.22	119.02	82.21	2.448	Minor Risk		
16,400.00	12,840.00	16,236.69	12,640.00	68.92	68.78	8.20	-3,516.87	-131.49	201.16	117.85	83.31	2.415	Minor Risk		
16,500.00	12,840.00	16,336.69	12,640.00	70.02	69.89	8.07	-3,616.86	-130.15	201.09	116.67	84.43	2.382	Minor Risk		
16,600.00	12,840.00	16,436.69	12,640.00	71.13	71.02	7.94	-3,716.85	-128.82	201.03	115.47	85.55	2.350	Minor Risk		
16,700.00	12,840.00	16,536.69	12,640.00	72.25	72.15	7.81	-3,816.84	-127.48	200.96	114.27	86.70	2.318	Minor Risk		
16,800.00	12,840.00	16,636.69	12,640.00	73.39	73.30	7.68	-3,916.83	-126.14	200.90	113.05	87.85	2.287	Minor Risk		
16,900.00	12,840.00	16,736.69	12,640.00	74.53	74.46	7.54	-4,016.82	-124.81	200.84	111.83	89.01	2.256	Minor Risk		
17,000.00	12,840.00	16,836.69	12,640.00	75.69	75.63	7.41	-4,116.81	-123.47	200.78	110.59	90.19	2.226	Minor Risk		
17,100.00	12,840.00	16,936.69	12,640.00	76.85	76.81	7.28	-4,216.80	-122.14	200.72	109.35	91.37	2.197	Minor Risk		
17,200.00	12,840.00	17,036.69	12,640.00	78.03	77.99	7.15	-4,316.79	-120.80	200.66	108.09	92.57	2.168	Minor Risk		
17,300.00	12,840.00	17,136.68	12,640.00	79.22	79.19	7.02	-4,416.78	-119.46	200.60	106.83	93.78	2.139	Minor Risk		
17,400.00	12,840.00	17,236.68	12,640.00	80.41	80.39	6.89	-4,516.77	-118.13	200.55	105.56	94.99	2.111	Minor Risk		
17,500.00	12,840.00	17,336.68	12,640.00	81.61	81.61	6.76	-4,616.76	-116.79	200.49	104.28	96.21	2.084	Minor Risk		
17,600.00	12,840.00	17,436.68	12,640.00	82.82	82.83	6.62	-4,716.75	-115.45	200.44	102.99	97.45	2.057	Minor Risk		
17,700.00	12,840.00	17,536.68	12,640.00	84.04	84.06	6.49	-4,816.74	-114.12	200.39	101.70	98.69	2.031	Minor Risk		
17,800.00	12,840.00	17,636.68	12,640.00	85.27	85.29	6.36	-4,916.73	-112.78	200.33	100.40	99.93	2.005	Minor Risk		
17,900.00	12,840.00	17,736.68	12,640.00	86.50	86.54	6.23	-5,016.72	-111.44	200.28	99.09	101.19	1.979	Minor Risk		
18,000.00	12,840.00	17,836.68	12,640.00	87.74	87.79	6.10	-5,116.71	-110.11	200.23	97.78	102.45	1.954	Minor Risk		
18,100.00	12,840.00	17,936.68	12,640.00	88.99	89.04	5.97	-5,216.70	-108.77	200.19	96.46	103.72	1.930	Minor Risk		
18,200.00	12,840.00	18,036.67	12,640.00	90.24	90.30	5.83	-5,316.69	-107.44	200.14	95.14	105.00	1.906	Minor Risk		
18,300.00	12,840.00	18,136.67	12,640.00	91.50	91.57	5.70	-5,416.68	-106.10	200.09	93.81	106.28	1.883	Minor Risk		
18,400.00	12,840.00	18,236.67	12,640.00	92.76	92.84	5.57	-5,516.67	-104.76	200.05	92.47	107.57	1.860	Minor Risk		
18,500.00	12,840.00	18,336.67	12,640.00	94.03	94.12	5.44	-5,616.66	-103.43	200.00	91.13	108.87	1.837	Minor Risk		
18,600.00	12,840.00	18,436.67	12,640.00	95.31	95.41	5.30	-5,716.65	-102.09	199.96	89.79	110.17	1.815	Minor Risk		
18,700.00	12,840.00	18,536.67	12,640.00	96.59	96.69	5.17	-5,816.64	-100.75	199.92	88.44	111.48	1.793	Minor Risk		
18,800.00	12,840.00	18,636.67	12,640.00	97.88	97.99	5.04	-5,916.63	-99.42	199.87	87.08	112.79	1.772	Minor Risk		
18,900.00	12,840.00	18,736.67	12,640.00	99.17	99.29	4.91	-6,016.62	-98.08	199.83	85.72	114.11	1.751	Minor Risk		
19,000.00	12,840.00	18,836.67	12,640.00	100.46	100.59	4.78	-6,116.61	-96.74	199.79	84.36	115.43	1.731	Minor Risk		
19,100.00	12,840.00	18,936.67	12,640.00	101.76	101.89	4.64	-6,216.60	-95.41	199.76	82.99	116.76	1.711	Minor Risk		
19,200.00	12,840.00	19,036.66	12,640.00	103.06	103.21	4.51	-6,316.59	-94.07	199.72	81.62	118.10	1.691	Minor Risk		
19,300.00	12,840.00	19,136.66	12,640.00	104.37	104.52	4.38	-6,416.58	-92.74	199.68	80.25	119.44	1.672	Minor Risk		
19,400.00	12,840.00	19,236.66	12,640.00	105.68	105.84	4.24	-6,516.57	-91.40	199.65	78.87	120.78	1.653	Minor Risk		
19,500.00	12,840.00	19,336.66	12,640.00	106.99	107.16	4.11	-6,616.56	-90.06	199.61	77.49	122.13	1.634	Minor Risk		
19,600.00	12,840.00	19,436.66	12,640.00	108.31	108.48	3.98	-6,716.55	-88.73	199.58	76.10	123.48	1.616	Minor Risk		
19,700.00	12,840.00	19,536.66	12,640.00	109.63	109.81	3.85	-6,816.54	-87.39	199.55	74.71	124.84	1.598	Minor Risk		
19,800.00	12,840.00	19,636.66	12,640.00	110.96	111.14	3.71	-6,916.53	-86.05	199.52	73.32	126.20	1.581	Minor Risk		
19,900.00	12,840.00	19,736.66	12,640.00	112.29	112.48	3.58	-7,016.52	-84.72	199.49	71.92	127.57	1.564	Minor Risk		
20,000.00	12,840.00	19,836.66	12,640.00	113.62	113.82	3.45	-7,116.51	-83.38	199.46	70.53	128.94	1.547	Minor Risk		
20,100.00	12,840.00	19,936.65	12,640.00	114.95	115.16	3.31	-7,216.50	-82.04	199.43	69.12	130.31	1.530	Minor Risk		
20,200.00	12,840.00	20,036.65	12,640.00	116.29	116.50	3.18	-7,316.49	-80.71	199.41	67.72	131.69	1.514	Minor Risk		
20,300.00	12,840.00	20,136.65	12,640.00	117.63	117.85	3.05	-7,416.48	-79.37	199.38	66.31	133.07	1.498	Major Risk		
20,400.00	12,840.00	20,236.65	12,640.00	118.97	119.20	2.92	-7,516.47	-78.04	199.36	64.90	134.46	1.483	Major Risk		
20,500.00	12,840.00	20,336.65	12,640.00	120.32	120.55	2.78	-7,616.46	-76.70	199.34	63.49	135.85	1.467	Major Risk		
20,600.00	12,840.00	20,436.65	12,640.00	121.66	121.90	2.65	-7,716.45	-75.36	199.31	62.07	137.24	1.452	Major Risk		
20,700.00	12,840.00	20,536.65	12,640.00	123.01	123.26	2.52	-7,816.44	-74.03	199.29	60.65	138.64	1.437	Major Risk		
20,800.00	12,840.00	20,636.65	12,640.00	124.37	124.62	2.38	-7,916.43	-72.69	199.27	59.23	140.05	1.423	Major Risk		
20,900.00	12,840.00	20,736.65	12,640.00	125.72	125.98	2.25	-8,016.42	-71.35	199.25	57.80	141.45	1.409	Major Risk		
21,000.00	12,840.00	20,836.64	12,640.00	127.08	127.34	2.12	-8,116.41	-70.02	199.24	56.38	142.86	1.395	Major Risk		

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

# Anticollision Report

<b>Company:</b>	WCDSC Permian NM	<b>Local Co-ordinate Reference:</b>	Well Jayhawk FED FEE COM 1H
<b>Project:</b>	Lea County (NAD83 New Mexico East)	<b>TVD Reference:</b>	RKB @ 3357.70ft
<b>Reference Site:</b>	Sec 06-T26S-R34E	<b>MD Reference:</b>	RKB @ 3357.70ft
<b>Site Error:</b>	5.00 ft	<b>North Reference:</b>	Grid
<b>Reference Well:</b>	Jayhawk FED FEE COM 1H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Well Error:</b>	0.50 ft	<b>Output errors are at</b>	2.00 sigma
<b>Reference Wellbore</b>	Wellbore #1	<b>Database:</b>	EDM r5000.141_Prod US
<b>Reference Design:</b>	Permit Plan 1	<b>Offset TVD Reference:</b>	Offset Datum

Offset Design: Sec 06-T26S-R34E - Jayhawk 6-7 FED FEE COM 2H - Wellbore #1 - Permit Plan 1													Offset Site Error:	5.00 ft
Survey Program: 0-MWD+HDGM													Offset Well Error:	0.50 ft
Reference		Offset		Semi Major Axis			Distance				Warning			
Measured Depth (ft)	Vertical Depth (ft)	Measured Depth (ft)	Vertical Depth (ft)	Reference (ft)	Offset (ft)	Highside Toolface (°)	Offset Wellbore Centre +N-S (ft)	+E-W (ft)	Between Centres (ft)	Between Ellipses (ft)	Minimum Separation (ft)	Separation Factor	Warning	
21,100.00	12,840.00	20,936.64	12,640.00	128.44	128.70	1.98	-8,216.40	-68.68	199.22	54.94	144.28	1.381	Major Risk	
21,200.00	12,840.00	21,036.64	12,640.00	129.80	130.07	1.85	-8,316.39	-67.35	199.20	53.51	145.69	1.367	Major Risk	
21,300.00	12,840.00	21,136.64	12,640.00	131.16	131.44	1.72	-8,416.38	-66.01	199.19	52.08	147.11	1.354	Major Risk	
21,400.00	12,840.00	21,236.64	12,640.00	132.53	132.81	1.58	-8,516.37	-64.67	199.18	50.64	148.54	1.341	Major Risk	
21,500.00	12,840.00	21,336.64	12,640.00	133.89	134.18	1.45	-8,616.36	-63.34	199.16	49.20	149.97	1.328	Major Risk	
21,600.00	12,840.00	21,436.64	12,640.00	135.26	135.56	1.32	-8,716.35	-62.00	199.15	47.75	151.40	1.315	Major Risk	
21,700.00	12,840.00	21,536.64	12,640.00	136.63	136.93	1.18	-8,816.34	-60.66	199.14	46.31	152.84	1.303	Major Risk	
21,800.00	12,840.00	21,636.64	12,640.00	138.01	138.31	1.05	-8,916.33	-59.33	199.13	44.86	154.28	1.291	Major Risk	
21,900.00	12,840.00	21,736.64	12,640.00	139.38	139.69	0.92	-9,016.32	-57.99	199.13	43.41	155.72	1.279	Major Risk	
22,000.00	12,840.00	21,836.63	12,640.00	140.76	141.07	0.78	-9,116.31	-56.65	199.12	41.95	157.17	1.267	Major Risk	
22,100.00	12,840.00	21,936.63	12,640.00	142.13	142.45	0.65	-9,216.30	-55.32	199.11	40.50	158.62	1.255	Major Risk	
22,200.00	12,840.00	22,036.63	12,640.00	143.51	143.84	0.52	-9,316.29	-53.98	199.11	39.04	160.07	1.244	Major Risk	
22,300.00	12,840.00	22,136.63	12,640.00	144.89	145.22	0.38	-9,416.28	-52.65	199.11	37.57	161.53	1.233	Major Risk	
22,400.00	12,840.00	22,236.63	12,640.00	146.27	146.61	0.25	-9,516.27	-51.31	199.10	36.11	162.99	1.222	Major Risk	
22,500.00	12,840.00	22,336.63	12,640.00	147.66	148.00	0.12	-9,616.26	-49.97	199.10	34.64	164.46	1.211	Major Risk	
22,586.60	12,840.00	22,423.23	12,640.00	148.86	149.20	0.00	-9,702.85	-48.82	199.10	33.37	165.73	1.201	Major Risk	
22,600.00	12,840.00	22,436.63	12,640.00	149.04	149.39	-0.02	-9,716.25	-48.64	199.10	33.17	165.93	1.200	Major Risk	
22,700.00	12,840.00	22,536.63	12,640.00	150.43	150.78	-0.15	-9,816.24	-47.30	199.10	31.70	167.40	1.189	Major Risk	
22,750.85	12,840.00	22,587.48	12,640.00	151.13	151.49	-0.22	-9,867.09	-46.62	199.10	30.95	168.15	1.184	Major Risk, SF	

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

# Anticollision Report

**Company:** WCDSC Permian NM  
**Project:** Lea County (NAD83 New Mexico East)  
**Reference Site:** Sec 06-T26S-R34E  
**Site Error:** 5.00 ft  
**Reference Well:** Jayhawk FED FEE COM 1H  
**Well Error:** 0.50 ft  
**Reference Wellbore:** Wellbore #1  
**Reference Design:** Permit Plan 1

**Local Co-ordinate Reference:** Well Jayhawk FED FEE COM 1H  
**TVD Reference:** RKB @ 3357.70ft  
**MD Reference:** RKB @ 3357.70ft  
**North Reference:** Grid  
**Survey Calculation Method:** Minimum Curvature  
**Output errors are at:** 2.00 sigma  
**Database:** EDM r5000.141\_Prod US  
**Offset TVD Reference:** Offset Datum

Offset Design													Offset Site Error:	5.00 ft
Survey Program: 0-MWD+IGRF													Offset Well Error:	0.50 ft
Sec 06-T26S-R34E - Jayhawk 6-7 FED FEE COM 3H - Wellbore #1 - Permit Plan 1														
Reference		Offset		Semi Major Axis			Distance						Warning	
Measured Depth (ft)	Vertical Depth (ft)	Measured Depth (ft)	Vertical Depth (ft)	Reference (ft)	Offset (ft)	Highside Toolface (°)	Offset Wellbore Centre +N/-S (ft)	Offset Wellbore Centre +E/-W (ft)	Between Centres (ft)	Between Ellipses (ft)	Minimum Separation (ft)	Separation Factor		
0.00	0.00	1.80	-1.80	0.50	0.50	-90.42	-0.44	-59.98	59.98					
100.00	100.00	101.80	98.20	0.52	0.52	-90.42	-0.44	-59.98	59.98	58.94	1.04	57.829		
200.00	200.00	201.80	198.20	0.70	0.71	-90.42	-0.44	-59.98	59.98	58.57	1.41	42.578		
300.00	300.00	301.80	298.20	0.99	0.99	-90.42	-0.44	-59.98	59.98	58.00	1.98	30.290		
400.00	400.00	401.80	398.20	1.31	1.32	-90.42	-0.44	-59.98	59.98	57.36	2.62	22.858		
500.00	500.00	501.80	498.20	1.65	1.65	-90.42	-0.44	-59.98	59.98	56.68	3.30	18.186		
600.00	600.00	601.80	598.20	1.99	2.00	-90.42	-0.44	-59.98	59.98	55.99	3.99	15.043		
700.00	700.00	701.80	698.20	2.34	2.35	-90.42	-0.44	-59.98	59.98	55.30	4.68	12.803		
800.00	800.00	801.80	798.20	2.69	2.70	-90.42	-0.44	-59.98	59.98	54.59	5.39	11.133		
900.00	900.00	901.80	898.20	3.04	3.05	-90.42	-0.44	-59.98	59.98	53.89	6.09	9.844		
1,000.00	1,000.00	1,001.80	998.20	3.40	3.40	-90.42	-0.44	-59.98	59.98	53.18	6.80	8.819		
1,100.00	1,100.00	1,101.80	1,098.20	3.75	3.76	-90.42	-0.44	-59.98	59.98	52.47	7.51	7.985		
1,200.00	1,200.00	1,201.80	1,198.20	4.11	4.11	-90.42	-0.44	-59.98	59.98	51.76	8.22	7.295		
1,300.00	1,300.00	1,301.80	1,298.20	4.46	4.47	-90.42	-0.44	-59.98	59.98	51.05	8.93	6.713		
1,400.00	1,400.00	1,401.80	1,398.20	4.82	4.83	-90.42	-0.44	-59.98	59.98	50.33	9.65	6.217		
1,500.00	1,500.00	1,501.80	1,498.20	5.18	5.18	-90.42	-0.44	-59.98	59.98	49.62	10.36	5.789		
1,600.00	1,600.00	1,601.80	1,598.20	5.53	5.54	-90.42	-0.44	-59.98	59.98	48.91	11.07	5.416		
1,700.00	1,700.00	1,701.80	1,698.20	5.89	5.90	-90.42	-0.44	-59.98	59.98	48.19	11.79	5.088		
1,800.00	1,800.00	1,801.80	1,798.20	6.25	6.25	-90.42	-0.44	-59.98	59.98	47.48	12.50	4.797	Alert	
1,900.00	1,900.00	1,901.80	1,898.20	6.61	6.61	-90.42	-0.44	-59.98	59.98	46.76	13.22	4.538	Alert	
2,000.00	2,000.00	2,001.80	1,998.20	6.96	6.97	-90.42	-0.44	-59.98	59.98	46.05	13.93	4.305	Alert	
2,100.00	2,100.00	2,101.80	2,098.20	7.32	7.33	-90.42	-0.44	-59.98	59.98	45.33	14.65	4.095	Alert	
2,200.00	2,200.00	2,201.80	2,198.20	7.68	7.69	-90.42	-0.44	-59.98	59.98	44.62	15.36	3.904	Alert	
2,300.00	2,300.00	2,301.80	2,298.20	8.04	8.04	-90.42	-0.44	-59.98	59.98	43.90	16.08	3.730	Alert	
2,400.00	2,400.00	2,401.80	2,398.20	8.39	8.40	-90.42	-0.44	-59.98	59.98	43.19	16.79	3.571	Alert	
2,500.00	2,500.00	2,501.80	2,498.20	8.75	8.76	-90.42	-0.44	-59.98	59.98	42.47	17.51	3.425	Alert	
2,600.00	2,600.00	2,601.80	2,598.20	9.11	9.12	-90.42	-0.44	-59.98	59.98	41.76	18.23	3.291	Alert	
2,700.00	2,700.00	2,701.80	2,698.20	9.47	9.47	-90.42	-0.44	-59.98	59.98	41.04	18.94	3.167	Alert	
2,800.00	2,800.00	2,801.80	2,798.20	9.83	9.83	-90.42	-0.44	-59.98	59.98	40.32	19.66	3.051	Alert	
2,900.00	2,900.00	2,901.80	2,898.20	10.18	10.19	-90.42	-0.44	-59.98	59.98	39.61	20.37	2.944	Alert	
3,000.00	3,000.00	3,001.80	2,998.20	10.54	10.55	-90.42	-0.44	-59.98	59.98	38.89	21.09	2.844	Alert	
3,100.00	3,100.00	3,101.80	3,098.20	10.90	10.91	-90.42	-0.44	-59.98	59.98	38.18	21.81	2.751	Alert	
3,200.00	3,200.00	3,201.80	3,198.20	11.26	11.26	-90.42	-0.44	-59.98	59.98	37.46	22.52	2.663	Alert	
3,300.00	3,300.00	3,301.80	3,298.20	11.62	11.62	-90.42	-0.44	-59.98	59.98	36.74	23.24	2.581	Alert	
3,400.00	3,400.00	3,401.80	3,398.20	11.97	11.98	-90.42	-0.44	-59.98	59.98	36.03	23.96	2.504	Alert	
3,500.00	3,500.00	3,501.80	3,498.20	12.33	12.34	-90.42	-0.44	-59.98	59.98	35.31	24.67	2.431	Minor Risk	
3,600.00	3,600.00	3,601.80	3,598.20	12.69	12.70	-90.42	-0.44	-59.98	59.98	34.59	25.39	2.363	Minor Risk	
3,700.00	3,700.00	3,701.80	3,698.20	13.05	13.06	-90.42	-0.44	-59.98	59.98	33.88	26.10	2.298	Minor Risk	
3,800.00	3,800.00	3,801.80	3,798.20	13.41	13.41	-90.42	-0.44	-59.98	59.98	33.16	26.82	2.236	Minor Risk	
3,900.00	3,900.00	3,901.80	3,898.20	13.77	13.77	-90.42	-0.44	-59.98	59.98	32.44	27.54	2.178	Minor Risk	
4,000.00	4,000.00	3,998.20	3,998.20	14.12	14.12	-90.42	-0.44	-59.98	59.98	31.74	28.24	2.124	Minor Risk, CC, ES	
4,100.00	4,100.00	4,096.95	4,096.94	14.48	14.46	-90.21	-0.22	-60.98	61.00	32.05	28.94	2.108	Minor Risk	
4,200.00	4,200.00	4,195.58	4,195.52	14.84	14.81	-89.60	0.45	-64.06	64.11	34.49	29.62	2.164	Minor Risk	
4,300.00	4,300.00	4,294.04	4,293.84	15.20	15.15	-88.70	1.57	-69.19	69.35	39.06	30.29	2.289	Minor Risk	
4,400.00	4,400.00	4,392.22	4,391.74	15.56	15.49	-87.65	3.14	-76.37	76.70	45.75	30.95	2.478	Minor Risk	
4,500.00	4,500.00	4,490.05	4,489.11	15.92	15.83	-86.56	5.14	-85.55	86.18	54.59	31.59	2.728	Alert	
4,600.00	4,600.00	4,587.42	4,585.82	16.27	16.18	-85.52	7.58	-96.70	97.79	65.57	32.22	3.035	Alert	
4,700.00	4,700.00	4,684.27	4,681.73	16.63	16.53	-84.57	10.43	-109.79	111.51	78.68	32.83	3.397	Alert	
4,800.00	4,800.00	4,780.51	4,776.74	16.99	16.88	-83.73	13.70	-124.75	127.32	93.89	33.42	3.809	Alert	
4,900.00	4,900.00	4,876.05	4,870.73	17.35	17.24	-83.01	17.36	-141.52	145.21	111.20	34.01	4.270	Alert	
5,000.00	5,000.00	4,970.84	4,963.59	17.71	17.60	-82.38	21.41	-160.05	165.14	130.57	34.57	4.777	Alert	
5,100.00	5,099.99	5,067.49	5,057.98	18.06	17.98	-85.06	25.85	-180.39	186.52	151.30	35.22	5.296		

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

Anticollision Report

Company: WCDSC Permian NM  
 Project: Lea County (NAD83 New Mexico East)  
 Reference Site: Sec 06-T26S-R34E  
 Site Error: 5.00 ft  
 Reference Well: Jayhawk FED FEE COM 1H  
 Well Error: 0.50 ft  
 Reference Wellbore: Wellbore #1  
 Reference Design: Permit Plan 1

Local Co-ordinate Reference: Well Jayhawk FED FEE COM 1H  
 TVD Reference: RKB @ 3357.70ft  
 MD Reference: RKB @ 3357.70ft  
 North Reference: Grid  
 Survey Calculation Method: Minimum Curvature  
 Output errors are at: 2.00 sigma  
 Database: EDM r5000.141\_Prod US  
 Offset TVD Reference: Offset Datum

Offset Design Sec 06-T26S-R34E - Jayhawk 6-7 FED FEE COM 3H - Wellbore #1 - Permit Plan 1													Offset Site Error:	5.00 ft
Survey Program: G-MWD+IGRF													Offset Well Error:	0.50 ft
Reference		Offset		Semi Major Axis			Distance						Warning	
Measured Depth (ft)	Vertical Depth (ft)	Measured Depth (ft)	Vertical Depth (ft)	Reference (ft)	Offset (ft)	Highside Toolface (°)	Offset Wellbore Centre +N/-S (ft)	Offset Wellbore Centre +E/-W (ft)	Between Centres (ft)	Between Ellipses (ft)	Minimum Separation (ft)	Separation Factor		
5,200.00	5,199.94	5,165.18	5,153.36	18.42	18.38	-85.24	30.35	-201.02	207.82	171.90	35.91	5.786		
5,300.00	5,299.79	5,262.86	5,248.73	18.78	18.77	-85.89	34.85	-221.66	228.97	192.35	36.61	6.254		
5,400.00	5,399.49	5,360.47	5,344.03	19.14	19.18	-86.90	39.36	-242.28	250.05	212.74	37.31	6.702		
5,500.00	5,499.01	5,457.97	5,439.22	19.49	19.59	-88.18	43.85	-262.87	271.16	233.15	38.01	7.134		
5,600.00	5,598.40	5,555.39	5,534.34	19.85	20.01	-89.73	48.34	-283.45	292.44	253.72	38.72	7.553		
5,700.00	5,697.78	5,652.80	5,629.45	20.20	20.43	-91.09	52.84	-304.03	313.89	274.46	39.43	7.961		
5,800.00	5,797.17	5,750.22	5,724.56	20.56	20.86	-92.28	57.33	-324.61	335.49	295.35	40.14	8.358		
5,900.00	5,896.55	5,847.63	5,819.67	20.92	21.29	-93.33	61.82	-345.19	357.22	316.36	40.86	8.744		
6,000.00	5,995.94	5,945.05	5,914.78	21.28	21.73	-94.25	66.31	-365.77	379.05	337.47	41.57	9.117		
6,100.00	6,095.32	6,042.47	6,009.89	21.64	22.17	-95.08	70.81	-386.34	400.96	358.66	42.29	9.480		
6,200.00	6,194.71	6,139.88	6,105.00	22.00	22.62	-95.82	75.30	-406.92	422.94	379.92	43.02	9.832		
6,300.00	6,294.09	6,237.30	6,200.12	22.37	23.07	-96.48	79.79	-427.50	444.98	401.24	43.74	10.172		
6,400.00	6,393.48	6,334.71	6,295.23	22.73	23.52	-97.09	84.28	-448.08	467.07	422.60	44.47	10.500		
6,500.00	6,492.86	6,432.13	6,390.34	23.09	23.98	-97.64	88.78	-468.66	489.21	444.01	45.20	10.822		
6,600.00	6,592.25	6,529.55	6,485.45	23.46	24.44	-98.14	93.27	-489.24	511.39	465.46	45.94	11.132		
6,700.00	6,691.63	6,626.96	6,580.56	23.82	24.90	-98.60	97.76	-509.81	533.61	486.93	46.67	11.433		
6,800.00	6,791.02	6,724.38	6,675.67	24.19	25.36	-99.02	102.25	-530.39	555.85	508.44	47.41	11.725		
6,900.00	6,890.40	6,821.79	6,770.78	24.56	25.83	-99.41	106.74	-550.97	578.12	529.97	48.15	12.005		
7,000.00	6,989.79	6,919.21	6,865.90	24.92	26.30	-99.78	111.24	-571.55	600.41	551.52	48.89	12.281		
7,100.00	7,089.17	7,016.62	6,961.01	25.29	26.78	-100.11	115.73	-592.13	622.73	573.09	49.63	12.547		
7,200.00	7,188.56	7,114.04	7,056.12	25.66	27.25	-100.42	120.22	-612.71	645.06	594.68	50.37	12.805		
7,300.00	7,287.94	7,211.46	7,151.23	26.03	27.73	-100.72	124.71	-633.28	667.41	616.29	51.12	13.056		
7,400.00	7,387.33	7,308.87	7,246.34	26.40	28.21	-100.99	129.21	-653.86	689.77	637.91	51.87	13.299		
7,500.00	7,486.71	7,406.29	7,341.45	26.77	28.69	-101.24	133.70	-674.44	712.15	659.54	52.62	13.535		
7,600.00	7,586.10	7,503.70	7,436.56	27.14	29.18	-101.49	138.19	-695.02	734.55	681.18	53.37	13.764		
7,700.00	7,685.48	7,614.41	7,544.80	27.51	29.72	-101.76	143.15	-717.75	756.43	702.15	54.29	13.934		
7,800.00	7,784.87	7,734.87	7,663.23	27.88	30.29	-102.14	147.84	-739.20	775.71	720.42	55.29	14.029		
7,900.00	7,884.25	7,856.48	7,783.45	28.25	30.82	-102.62	151.75	-757.14	792.12	735.86	56.26	14.079		
8,000.00	7,983.79	7,979.18	7,905.26	28.62	31.34	-103.24	154.87	-771.44	805.32	748.13	57.20	14.080		
8,100.00	8,083.54	8,102.81	8,028.41	28.98	31.82	-103.68	157.17	-781.97	815.00	756.92	58.08	14.033		
8,200.00	8,183.45	8,227.08	8,152.50	29.34	32.27	-103.95	158.63	-788.63	821.09	762.19	58.90	13.940		
8,300.00	8,283.43	8,351.71	8,277.09	29.70	32.68	-104.06	159.22	-791.35	823.56	763.89	59.68	13.801		
8,400.00	8,383.43	8,456.25	8,381.63	30.06	33.02	-100.92	159.24	-791.42	823.62	763.24	60.38	13.640		
8,500.00	8,483.43	8,556.25	8,481.63	30.41	33.34	-100.92	159.24	-791.42	823.62	762.55	61.08	13.485		
8,600.00	8,583.43	8,656.25	8,581.63	30.77	33.66	-100.92	159.24	-791.42	823.62	761.85	61.78	13.332		
8,700.00	8,683.43	8,756.25	8,681.63	31.12	33.98	-100.92	159.24	-791.42	823.62	761.15	62.48	13.183		
8,800.00	8,783.43	8,856.25	8,781.63	31.48	34.30	-100.92	159.24	-791.42	823.62	760.45	63.17	13.037		
8,900.00	8,883.43	8,956.25	8,881.63	31.83	34.63	-100.92	159.24	-791.42	823.62	759.75	63.87	12.895		
9,000.00	8,983.43	9,056.25	8,981.63	32.19	34.95	-100.92	159.24	-791.42	823.62	759.05	64.57	12.755		
9,100.00	9,083.43	9,156.25	9,081.63	32.54	35.27	-100.92	159.24	-791.42	823.62	758.35	65.27	12.618		
9,200.00	9,183.43	9,256.25	9,181.63	32.90	35.60	-100.92	159.24	-791.42	823.62	757.65	65.97	12.484		
9,300.00	9,283.43	9,356.25	9,281.63	33.25	35.92	-100.92	159.24	-791.42	823.62	756.95	66.68	12.353		
9,400.00	9,383.43	9,456.25	9,381.63	33.61	36.25	-100.92	159.24	-791.42	823.62	756.25	67.38	12.224		
9,500.00	9,483.43	9,556.25	9,481.63	33.96	36.58	-100.92	159.24	-791.42	823.62	755.55	68.08	12.098		
9,600.00	9,583.43	9,656.25	9,581.63	34.32	36.90	-100.92	159.24	-791.42	823.62	754.84	68.78	11.975		
9,700.00	9,683.43	9,756.25	9,681.63	34.67	37.23	-100.92	159.24	-791.42	823.62	754.14	69.48	11.854		
9,800.00	9,783.43	9,856.25	9,781.63	35.03	37.56	-100.92	159.24	-791.42	823.62	753.44	70.18	11.735		
9,900.00	9,883.43	9,956.25	9,881.63	35.38	37.89	-100.92	159.24	-791.42	823.62	752.74	70.89	11.619		
10,000.00	9,983.43	10,056.25	9,981.63	35.74	38.22	-100.92	159.24	-791.42	823.62	752.03	71.59	11.505		
10,100.00	10,083.43	10,156.25	10,081.63	36.10	38.55	-100.92	159.24	-791.42	823.62	751.33	72.29	11.393		
10,200.00	10,183.43	10,256.25	10,181.63	36.45	38.88	-100.92	159.24	-791.42	823.62	750.63	73.00	11.283		
10,300.00	10,283.43	10,356.25	10,281.63	36.81	39.21	-100.92	159.24	-791.42	823.62	749.92	73.70	11.175		

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

### Anticollision Report

**Company:** WCDSC Permian NM  
**Project:** Lea County (NAD83 New Mexico East)  
**Reference Site:** Sec 06-T26S-R34E  
**Site Error:** 5.00 ft  
**Reference Well:** Jayhawk FED FEE COM 1H  
**Well Error:** 0.50 ft  
**Reference Wellbore:** Wellbore #1  
**Reference Design:** Permit Plan 1

**Local Co-ordinate Reference:** Well Jayhawk FED FEE COM 1H  
**TVD Reference:** RKB @ 3357.70ft  
**MD Reference:** RKB @ 3357.70ft  
**North Reference:** Grid  
**Survey Calculation Method:** Minimum Curvature  
**Output errors are at:** 2.00 sigma  
**Database:** EDM r5000.141\_Prod US  
**Offset TVD Reference:** Offset Datum

Offset Design													Offset Site Error:	5.00 ft	
Survey Program: 0-MWD+IGRF													Offset Well Error:	0.50 ft	
Sec 06-T26S-R34E - Jayhawk 6-7 FED FEE COM 3H - Wellbore #1 - Permit Plan 1															
Reference				Offset			Semi Major Axis			Distance				Warning	
Measured Depth (ft)	Vertical Depth (ft)	Measured Depth (ft)	Vertical Depth (ft)	Reference (ft)	Offset (ft)	Highside Toolface (°)	Offset Wellbore Centre +N/-S (ft)	+E/-W (ft)	Between Centres (ft)	Between Ellipses (ft)	Minimum Separation (ft)	Separation Factor			
10,400.00	10,383.43	10,456.25	10,381.63	37.16	39.54	-100.92	159.24	-791.42	823.62	749.22	74.40	11.070			
10,500.00	10,483.43	10,556.25	10,481.63	37.52	39.88	-100.92	159.24	-791.42	823.62	748.52	75.11	10.966			
10,600.00	10,583.43	10,656.25	10,581.63	37.87	40.21	-100.92	159.24	-791.42	823.62	747.81	75.81	10.864			
10,700.00	10,683.43	10,756.25	10,681.63	38.23	40.54	-100.92	159.24	-791.42	823.62	747.11	76.52	10.764			
10,800.00	10,783.43	10,856.25	10,781.63	38.59	40.87	-100.92	159.24	-791.42	823.62	746.40	77.22	10.666			
10,900.00	10,883.43	10,956.25	10,881.63	38.94	41.21	-100.92	159.24	-791.42	823.62	745.70	77.93	10.569			
11,000.00	10,983.43	11,056.25	10,981.63	39.30	41.54	-100.92	159.24	-791.42	823.62	744.99	78.63	10.474			
11,100.00	11,083.43	11,156.25	11,081.63	39.65	41.88	-100.92	159.24	-791.42	823.62	744.29	79.34	10.381			
11,200.00	11,183.43	11,256.25	11,181.63	40.01	42.21	-100.92	159.24	-791.42	823.62	743.58	80.04	10.290			
11,300.00	11,283.43	11,356.25	11,281.63	40.37	42.55	-100.92	159.24	-791.42	823.62	742.87	80.75	10.200			
11,400.00	11,383.43	11,456.25	11,381.63	40.72	42.88	-100.92	159.24	-791.42	823.62	742.17	81.46	10.111			
11,500.00	11,483.43	11,556.25	11,481.63	41.08	43.22	-100.92	159.24	-791.42	823.62	741.46	82.16	10.024			
11,600.00	11,583.43	11,656.25	11,581.63	41.44	43.56	-100.92	159.24	-791.42	823.62	740.75	82.87	9.939			
11,700.00	11,683.43	11,756.25	11,681.63	41.79	43.89	-100.92	159.24	-791.42	823.62	740.05	83.58	9.855			
11,800.00	11,783.43	11,856.25	11,781.63	42.15	44.23	-100.92	159.24	-791.42	823.62	739.34	84.28	9.772			
11,900.00	11,883.43	11,956.25	11,881.63	42.51	44.57	-100.92	159.24	-791.42	823.62	738.63	84.99	9.691			
12,000.00	11,983.39	12,056.21	11,981.59	42.86	44.90	-39.75	159.24	-791.42	822.36	736.66	85.70	9.596			
12,100.00	12,082.09	12,154.92	12,080.29	43.21	45.24	-31.57	159.24	-791.42	810.27	723.85	86.42	9.376			
12,200.00	12,180.39	12,248.58	12,173.95	43.54	45.55	10.98	158.99	-791.42	792.64	705.56	87.08	9.102			
12,300.00	12,277.69	12,325.98	12,250.93	43.84	45.78	39.65	151.49	-791.35	774.30	686.68	87.62	8.837			
12,400.00	12,372.14	12,403.96	12,326.75	44.11	46.00	54.15	133.53	-791.20	756.38	668.32	88.06	8.589			
12,500.00	12,461.94	12,482.62	12,400.05	44.36	46.19	62.43	105.15	-790.96	739.24	650.81	88.43	8.360			
12,600.00	12,545.38	12,562.05	12,469.42	44.60	46.36	67.86	66.60	-790.63	723.22	634.48	88.74	8.150			
12,700.00	12,620.86	12,642.28	12,533.40	44.82	46.51	71.74	18.29	-790.23	708.65	619.63	89.02	7.961			
12,800.00	12,686.95	12,723.34	12,590.56	45.04	46.63	74.66	-39.09	-789.74	695.82	606.53	89.29	7.793			
12,900.00	12,742.37	12,805.20	12,639.48	45.24	46.73	76.88	-104.63	-789.18	685.00	595.41	89.59	7.646			
13,000.00	12,786.09	12,887.80	12,678.88	45.44	46.83	78.54	-177.14	-788.57	676.41	586.47	89.93	7.521			
13,100.00	12,817.25	12,971.03	12,707.63	45.65	46.93	79.70	-255.17	-787.91	670.23	579.89	90.34	7.419			
13,200.00	12,835.28	13,054.75	12,724.84	45.85	47.07	80.40	-337.02	-787.22	666.58	575.77	90.80	7.341			
13,286.11	12,840.83	13,137.14	12,730.00	46.02	47.24	80.57	-408.23	-786.61	665.50	574.22	91.28	7.290			
13,300.00	12,840.00	13,140.12	12,730.00	46.05	47.25	80.64	-422.16	-786.50	665.52	574.19	91.33	7.287			
13,400.00	12,840.00	13,240.12	12,730.00	46.28	47.55	80.64	-522.16	-785.65	665.55	573.59	91.96	7.238			
13,500.00	12,840.00	13,340.12	12,730.00	46.56	47.93	80.64	-622.15	-784.80	665.57	572.88	92.69	7.180			
13,600.00	12,840.00	13,440.12	12,730.00	46.88	48.41	80.64	-722.15	-783.96	665.60	572.05	93.54	7.115			
13,700.00	12,840.00	13,540.12	12,730.00	47.24	48.96	80.64	-822.15	-783.11	665.62	571.12	94.51	7.043			
13,800.00	12,840.00	13,640.12	12,730.00	47.64	49.60	80.65	-922.14	-782.26	665.65	570.07	95.58	6.964			
13,900.00	12,840.00	13,740.12	12,730.00	48.08	50.30	80.65	-1,022.14	-781.42	665.67	568.92	96.75	6.880			
14,000.00	12,840.00	13,840.12	12,730.00	48.57	51.07	80.65	-1,122.14	-780.57	665.70	567.67	98.03	6.791			
14,100.00	12,840.00	13,940.12	12,730.00	49.09	51.90	80.65	-1,222.13	-779.72	665.73	566.32	99.40	6.697			
14,200.00	12,840.00	14,040.12	12,730.00	49.65	52.79	80.65	-1,322.13	-778.88	665.75	564.88	100.87	6.600			
14,300.00	12,840.00	14,140.12	12,730.00	50.24	53.74	80.65	-1,422.13	-778.03	665.78	563.36	102.42	6.500			
14,400.00	12,840.00	14,240.12	12,730.00	50.87	54.74	80.65	-1,522.12	-777.18	665.80	561.74	104.06	6.398			
14,500.00	12,840.00	14,340.12	12,730.00	51.53	55.79	80.65	-1,622.12	-776.34	665.83	560.05	105.78	6.295			
14,600.00	12,840.00	14,440.12	12,730.00	52.23	56.88	80.65	-1,722.11	-775.49	665.85	558.28	107.57	6.190			
14,700.00	12,840.00	14,540.12	12,730.00	52.95	58.02	80.65	-1,822.11	-774.64	665.88	556.44	109.44	6.085			
14,800.00	12,840.00	14,640.12	12,730.00	53.71	59.19	80.65	-1,922.11	-773.80	665.91	554.53	111.37	5.979			
14,900.00	12,840.00	14,740.12	12,730.00	54.49	60.41	80.65	-2,022.10	-772.95	665.93	552.56	113.37	5.874			
15,000.00	12,840.00	14,840.12	12,730.00	55.30	61.66	80.65	-2,122.10	-772.10	665.96	550.52	115.44	5.769			
15,100.00	12,840.00	14,940.12	12,730.00	56.14	62.94	80.65	-2,222.10	-771.26	665.98	548.43	117.56	5.665			
15,200.00	12,840.00	15,040.12	12,730.00	57.00	64.26	80.65	-2,322.09	-770.41	666.01	546.28	119.73	5.563			
15,300.00	12,840.00	15,140.12	12,730.00	57.89	65.61	80.65	-2,422.09	-769.56	666.03	544.08	121.96	5.461			
15,400.00	12,840.00	15,240.12	12,730.00	58.80	66.98	80.65	-2,522.09	-768.72	666.06	541.82	124.24	5.361			

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

Anticollision Report

Company: WCDSC Permian NM  
 Project: Lea County (NAD83 New Mexico East)  
 Reference Site: Sec 06-T26S-R34E  
 Site Error: 5.00 ft  
 Reference Well: Jayhawk FED FEE COM 1H  
 Well Error: 0.50 ft  
 Reference Wellbore: Wellbore #1  
 Reference Design: Permit Plan 1

Local Co-ordinate Reference: Well Jayhawk FED FEE COM 1H  
 TVD Reference: RKB @ 3357.70ft  
 MD Reference: RKB @ 3357.70ft  
 North Reference: Grid  
 Survey Calculation Method: Minimum Curvature  
 Output errors are at: 2.00 sigma  
 Database: EDM r5000.141\_Prod US  
 Offset TVD Reference: Offset Datum

Offset Design Sec 06-T26S-R34E - Jayhawk 6-7 FED FEE COM 3H - Wellbore #1 - Permit Plan 1													Offset Site Error:	5.00 ft
Survey Program: 0-MWD+IGRF													Offset Well Error:	0.50 ft
Reference				Offset		Semi Major Axis			Distance				Warning	
Measured Depth (ft)	Vertical Depth (ft)	Measured Depth (ft)	Vertical Depth (ft)	Reference (ft)	Offset (ft)	Highside Toolface (°)	Offset Wellbore Centre +N/-S (ft)	Offset Wellbore Centre +E/-W (ft)	Between Centres (ft)	Between Ellipses (ft)	Minimum Separation (ft)	Separation Factor		
15,500.00	12,840.00	15,340.12	12,730.00	59.73	68.38	80.65	-2,622.08	-767.87	666.09	539.53	126.56	5.263		
15,600.00	12,840.00	15,440.12	12,730.00	60.68	69.81	80.65	-2,722.08	-767.03	666.11	537.18	128.93	5.167		
15,700.00	12,840.00	15,540.12	12,730.00	61.65	71.26	80.65	-2,822.07	-766.18	666.14	534.80	131.34	5.072		
15,800.00	12,840.00	15,640.12	12,730.00	62.64	72.73	80.65	-2,922.07	-765.33	666.16	532.37	133.79	4.979	Alert	
15,900.00	12,840.00	15,740.12	12,730.00	63.64	74.22	80.65	-3,022.07	-764.49	666.19	529.91	136.28	4.889	Alert	
16,000.00	12,840.00	15,840.12	12,730.00	64.67	75.73	80.65	-3,122.06	-763.64	666.21	527.42	138.80	4.800	Alert	
16,100.00	12,840.00	15,940.12	12,730.00	65.71	77.25	80.65	-3,222.06	-762.79	666.24	524.89	141.35	4.713	Alert	
16,200.00	12,840.00	16,040.12	12,730.00	66.76	78.80	80.65	-3,322.06	-761.95	666.27	522.32	143.94	4.629	Alert	
16,300.00	12,840.00	16,140.12	12,730.00	67.83	80.36	80.65	-3,422.05	-761.10	666.29	519.73	146.56	4.546	Alert	
16,400.00	12,840.00	16,240.12	12,730.00	68.92	81.94	80.65	-3,522.05	-760.25	666.32	517.11	149.21	4.466	Alert	
16,500.00	12,840.00	16,340.12	12,730.00	70.02	83.53	80.65	-3,622.05	-759.41	666.34	514.46	151.88	4.387	Alert	
16,600.00	12,840.00	16,440.12	12,730.00	71.13	85.13	80.66	-3,722.04	-758.56	666.37	511.79	154.58	4.311	Alert	
16,700.00	12,840.00	16,540.12	12,730.00	72.25	86.75	80.66	-3,822.04	-757.71	666.39	509.09	157.30	4.236	Alert	
16,800.00	12,840.00	16,640.12	12,730.00	73.39	88.38	80.66	-3,922.04	-756.87	666.42	506.37	160.05	4.164	Alert	
16,900.00	12,840.00	16,740.12	12,730.00	74.53	90.02	80.66	-4,022.03	-756.02	666.45	503.63	162.82	4.093	Alert	
17,000.00	12,840.00	16,840.12	12,730.00	75.69	91.67	80.66	-4,122.03	-755.17	666.47	500.87	165.61	4.024	Alert	
17,100.00	12,840.00	16,940.12	12,730.00	76.85	93.33	80.66	-4,222.02	-754.33	666.50	498.08	168.41	3.957	Alert	
17,200.00	12,840.00	17,040.12	12,730.00	78.03	95.01	80.66	-4,322.02	-753.48	666.52	495.28	171.24	3.892	Alert	
17,300.00	12,840.00	17,140.12	12,730.00	79.22	96.69	80.66	-4,422.02	-752.63	666.55	492.46	174.09	3.829	Alert	
17,400.00	12,840.00	17,240.12	12,730.00	80.41	98.38	80.66	-4,522.01	-751.79	666.57	489.62	176.95	3.767	Alert	
17,500.00	12,840.00	17,340.12	12,730.00	81.61	100.07	80.66	-4,622.01	-750.94	666.60	486.77	179.83	3.707	Alert	
17,600.00	12,840.00	17,440.12	12,730.00	82.82	101.78	80.66	-4,722.01	-750.09	666.63	483.90	182.73	3.648	Alert	
17,700.00	12,840.00	17,540.12	12,730.00	84.04	103.49	80.66	-4,822.00	-749.25	666.65	481.02	185.63	3.591	Alert	
17,800.00	12,840.00	17,640.12	12,730.00	85.27	105.21	80.66	-4,922.00	-748.40	666.68	478.12	188.56	3.536	Alert	
17,900.00	12,840.00	17,740.12	12,730.00	86.50	106.94	80.66	-5,022.00	-747.55	666.70	475.21	191.50	3.482	Alert	
18,000.00	12,840.00	17,840.12	12,730.00	87.74	108.67	80.66	-5,121.99	-746.71	666.73	472.28	194.45	3.429	Alert	
18,100.00	12,840.00	17,940.12	12,730.00	88.99	110.41	80.66	-5,221.99	-745.86	666.75	469.35	197.41	3.378	Alert	
18,200.00	12,840.00	18,040.12	12,730.00	90.24	112.16	80.66	-5,321.99	-745.01	666.78	466.40	200.38	3.328	Alert	
18,300.00	12,840.00	18,140.12	12,730.00	91.50	113.91	80.66	-5,421.98	-744.17	666.81	463.44	203.37	3.279	Alert	
18,400.00	12,840.00	18,240.12	12,730.00	92.76	115.67	80.66	-5,521.98	-743.32	666.83	460.47	206.36	3.231	Alert	
18,500.00	12,840.00	18,340.12	12,730.00	94.03	117.43	80.66	-5,621.97	-742.47	666.86	457.49	209.37	3.185	Alert	
18,600.00	12,840.00	18,440.12	12,730.00	95.31	119.19	80.66	-5,721.97	-741.63	666.88	454.50	212.39	3.140	Alert	
18,700.00	12,840.00	18,540.12	12,730.00	96.59	120.97	80.66	-5,821.97	-740.78	666.91	451.50	215.41	3.096	Alert	
18,800.00	12,840.00	18,640.12	12,730.00	97.88	122.74	80.66	-5,921.96	-739.94	666.94	448.49	218.45	3.053	Alert	
18,900.00	12,840.00	18,740.12	12,730.00	99.17	124.52	80.66	-6,021.96	-739.09	666.96	445.47	221.49	3.011	Alert	
19,000.00	12,840.00	18,840.12	12,730.00	100.46	126.30	80.66	-6,121.96	-738.24	666.99	442.45	224.54	2.970	Alert	
19,100.00	12,840.00	18,940.12	12,730.00	101.76	128.09	80.66	-6,221.95	-737.40	667.01	439.41	227.60	2.931	Alert	
19,200.00	12,840.00	19,040.12	12,730.00	103.06	129.88	80.66	-6,321.95	-736.55	667.04	436.37	230.67	2.892	Alert	
19,300.00	12,840.00	19,140.12	12,730.00	104.37	131.68	80.67	-6,421.95	-735.70	667.06	433.32	233.74	2.854	Alert	
19,400.00	12,840.00	19,240.12	12,730.00	105.68	133.48	80.67	-6,521.94	-734.86	667.09	430.26	236.83	2.817	Alert	
19,500.00	12,840.00	19,340.12	12,730.00	106.99	135.28	80.67	-6,621.94	-734.01	667.12	427.20	239.91	2.781	Alert	
19,600.00	12,840.00	19,440.12	12,730.00	108.31	137.08	80.67	-6,721.94	-733.16	667.14	424.13	243.01	2.745	Alert	
19,700.00	12,840.00	19,540.12	12,730.00	109.63	138.89	80.67	-6,821.93	-732.32	667.17	421.05	246.11	2.711	Alert	
19,800.00	12,840.00	19,640.12	12,730.00	110.96	140.70	80.67	-6,921.93	-731.47	667.19	417.97	249.22	2.677	Alert	
19,900.00	12,840.00	19,740.12	12,730.00	112.29	142.52	80.67	-7,021.92	-730.62	667.22	414.88	252.33	2.644	Alert	
20,000.00	12,840.00	19,840.12	12,730.00	113.62	144.33	80.67	-7,121.92	-729.78	667.24	411.79	255.45	2.612	Alert	
20,100.00	12,840.00	19,940.12	12,730.00	114.95	146.15	80.67	-7,221.92	-728.93	667.27	408.69	258.58	2.581	Alert	
20,200.00	12,840.00	20,040.12	12,730.00	116.29	147.98	80.67	-7,321.91	-728.08	667.30	405.59	261.71	2.550	Alert	
20,300.00	12,840.00	20,140.12	12,730.00	117.63	149.80	80.67	-7,421.91	-727.24	667.32	402.48	264.84	2.520	Alert	
20,400.00	12,840.00	20,240.12	12,730.00	118.97	151.63	80.67	-7,521.91	-726.39	667.35	399.36	267.98	2.490	Minor Risk	
20,500.00	12,840.00	20,340.12	12,730.00	120.32	153.46	80.67	-7,621.90	-725.54	667.37	396.24	271.13	2.461	Minor Risk	
20,600.00	12,840.00	20,440.12	12,730.00	121.66	155.29	80.67	-7,721.90	-724.70	667.40	393.12	274.28	2.433	Minor Risk	

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

## Anticollision Report

<b>Company:</b> WCDSC Permian NM	<b>Local Co-ordinate Reference:</b> Well Jayhawk FED FEE COM 1H
<b>Project:</b> Lea County (NAD83 New Mexico East)	<b>TVD Reference:</b> RKB @ 3357.70ft
<b>Reference Site:</b> Sec 06-T26S-R34E	<b>MD Reference:</b> RKB @ 3357.70ft
<b>Site Error:</b> 5.00 ft	<b>North Reference:</b> Grid
<b>Reference Well:</b> Jayhawk FED FEE COM 1H	<b>Survey Calculation Method:</b> Minimum Curvature
<b>Well Error:</b> 0.50 ft	<b>Output errors are at:</b> 2.00 sigma
<b>Reference Wellbore:</b> Wellbore #1	<b>Database:</b> EDM r5000.141_Prod US
<b>Reference Design:</b> Permit Plan 1	<b>Offset TVD Reference:</b> Offset Datum

Offset Design      Sec 06-T26S-R34E - Jayhawk 6-7 FED FEE COM 3H - Wellbore #1 - Permit Plan 1													Offset Site Error:	5.00 ft
Survey Program: 0-MWD+IGRF													Offset Well Error:	0.50 ft
Reference		Offset		Semi Major Axis			Distance						Warning	
Measured Depth (ft)	Vertical Depth (ft)	Measured Depth (ft)	Vertical Depth (ft)	Reference (ft)	Offset (ft)	Highside Toolface (°)	Offset Wellbore Centre +N/-S (ft)	Offset Wellbore Centre +E/-W (ft)	Between Centres (ft)	Between Ellipses (ft)	Minimum Separation (ft)	Separation Factor		
20,700.00	12,840.00	20,540.12	12,730.00	123.01	157.12	80.67	-7,821.90	-723.85	667.42	389.99	277.43	2.406	Minor Risk	
20,800.00	12,840.00	20,640.12	12,730.00	124.37	158.95	80.67	-7,921.89	-723.00	667.45	386.86	280.59	2.379	Minor Risk	
20,900.00	12,840.00	20,740.12	12,730.00	125.72	160.79	80.67	-8,021.89	-722.16	667.48	383.72	283.75	2.352	Minor Risk	
21,000.00	12,840.00	20,840.12	12,730.00	127.08	162.63	80.67	-8,121.88	-721.31	667.50	380.58	286.92	2.326	Minor Risk	
21,100.00	12,840.00	20,940.12	12,730.00	128.44	164.47	80.67	-8,221.88	-720.46	667.53	377.44	290.09	2.301	Minor Risk	
21,200.00	12,840.00	21,040.12	12,730.00	129.80	166.31	80.67	-8,321.88	-719.62	667.55	374.29	293.26	2.276	Minor Risk	
21,300.00	12,840.00	21,140.12	12,730.00	131.16	168.16	80.67	-8,421.87	-718.77	667.58	371.14	296.44	2.252	Minor Risk	
21,400.00	12,840.00	21,240.12	12,730.00	132.53	170.01	80.67	-8,521.87	-717.92	667.60	367.98	299.62	2.228	Minor Risk	
21,500.00	12,840.00	21,340.12	12,730.00	133.89	171.85	80.67	-8,621.87	-717.08	667.63	364.82	302.81	2.205	Minor Risk	
21,600.00	12,840.00	21,440.12	12,730.00	135.26	173.70	80.67	-8,721.86	-716.23	667.66	361.66	305.99	2.182	Minor Risk	
21,700.00	12,840.00	21,540.12	12,730.00	136.63	175.55	80.67	-8,821.86	-715.38	667.68	358.50	309.19	2.159	Minor Risk	
21,800.00	12,840.00	21,640.12	12,730.00	138.01	177.41	80.67	-8,921.86	-714.54	667.71	355.33	312.38	2.137	Minor Risk	
21,900.00	12,840.00	21,740.12	12,730.00	139.38	179.26	80.67	-9,021.85	-713.69	667.73	352.16	315.58	2.116	Minor Risk	
22,000.00	12,840.00	21,840.12	12,730.00	140.76	181.11	80.67	-9,121.85	-712.84	667.76	348.98	318.78	2.095	Minor Risk	
22,100.00	12,840.00	21,940.12	12,730.00	142.13	182.97	80.68	-9,221.85	-712.00	667.78	345.80	321.98	2.074	Minor Risk	
22,200.00	12,840.00	22,040.12	12,730.00	143.51	184.83	80.68	-9,321.84	-711.15	667.81	342.62	325.19	2.054	Minor Risk	
22,300.00	12,840.00	22,140.12	12,730.00	144.89	186.69	80.68	-9,421.84	-710.31	667.84	339.44	328.39	2.034	Minor Risk	
22,400.00	12,840.00	22,240.12	12,730.00	146.27	188.55	80.68	-9,521.83	-709.46	667.86	336.26	331.60	2.014	Minor Risk	
22,500.00	12,840.00	22,340.12	12,730.00	147.66	190.41	80.68	-9,621.83	-708.61	667.89	333.07	334.82	1.995	Minor Risk	
22,600.00	12,840.00	22,440.12	12,730.00	149.04	192.27	80.68	-9,721.83	-707.77	667.91	329.88	338.03	1.976	Minor Risk	
22,700.00	12,840.00	22,540.12	12,730.00	150.43	194.13	80.68	-9,821.82	-706.92	667.94	326.69	341.25	1.957	Minor Risk	
22,750.85	12,840.00	22,590.98	12,730.00	151.13	195.08	80.68	-9,872.68	-706.49	667.95	325.06	342.89	1.948	Minor Risk, SF	

Anticollision Report

Company: WCDSC Permian NM  
 Project: Lea County (NAD83 New Mexico East)  
 Reference Site: Sec 06-T26S-R34E  
 Site Error: 5.00 ft  
 Reference Well: Jayhawk FED FEE COM 1H  
 Well Error: 0.50 ft  
 Reference Wellbore: Wellbore #1  
 Reference Design: Permit Plan 1

Local Co-ordinate Reference: Well Jayhawk FED FEE COM 1H  
 TVD Reference: RKB @ 3357.70ft  
 MD Reference: RKB @ 3357.70ft  
 North Reference: Grid  
 Survey Calculation Method: Minimum Curvature  
 Output errors are at: 2.00 sigma  
 Database: EDM r5000.141\_Prod US  
 Offset TVD Reference: Offset Datum

Offset Design													Offset Site Error:	5.00 ft						
Survey Program: 0-MWD+IGRF													Offset Well Error:	0.50 ft						
Reference													Semi Major Axis		Distance				Warning	
Measured Depth (ft)	Vertical Depth (ft)	Measured Depth (ft)	Vertical Depth (ft)	Reference (ft)	Offset (ft)	Highside Toolface (°)	Offset Wellbore Centre +N/-S (ft)	+E/-W (ft)	Between Centres (ft)	Between Ellipses (ft)	Minimum Separation (ft)	Separation Factor								
0.00	0.00	5.10	-5.10	0.50	0.50	-117.03	-152.36	-298.59	335.22											
100.00	100.00	105.10	94.90	0.52	0.52	-117.03	-152.36	-298.59	335.22	334.18	1.04	322.151								
200.00	200.00	205.10	194.90	0.70	0.72	-117.03	-152.36	-298.59	335.22	333.80	1.42	236.541								
300.00	300.00	305.10	294.90	0.99	1.00	-117.03	-152.36	-298.59	335.22	333.23	1.99	168.410								
400.00	400.00	405.10	394.90	1.31	1.33	-117.03	-152.36	-298.59	335.22	332.58	2.64	127.212								
500.00	500.00	505.10	494.90	1.65	1.66	-117.03	-152.36	-298.59	335.22	331.91	3.31	101.286								
600.00	600.00	605.10	594.90	1.99	2.01	-117.03	-152.36	-298.59	335.22	331.22	4.00	83.827								
700.00	700.00	705.10	694.90	2.34	2.36	-117.03	-152.36	-298.59	335.22	330.52	4.70	71.376								
800.00	800.00	805.10	794.90	2.69	2.71	-117.03	-152.36	-298.59	335.22	329.82	5.40	62.087								
900.00	900.00	905.10	894.90	3.04	3.06	-117.03	-152.36	-298.59	335.22	329.11	6.11	54.907								
1,000.00	1,000.00	1,005.10	994.90	3.40	3.42	-117.03	-152.36	-298.59	335.22	328.40	6.81	49.200								
1,100.00	1,100.00	1,105.10	1,094.90	3.75	3.77	-117.03	-152.36	-298.59	335.22	327.69	7.52	44.557								
1,200.00	1,200.00	1,205.10	1,194.90	4.11	4.13	-117.03	-152.36	-298.59	335.22	326.98	8.23	40.709								
1,300.00	1,300.00	1,305.10	1,294.90	4.46	4.48	-117.03	-152.36	-298.59	335.22	326.27	8.95	37.469								
1,400.00	1,400.00	1,405.10	1,394.90	4.82	4.84	-117.03	-152.36	-298.59	335.22	325.56	9.66	34.704								
1,500.00	1,500.00	1,505.10	1,494.90	5.18	5.20	-117.03	-152.36	-298.59	335.22	324.84	10.37	32.317								
1,600.00	1,600.00	1,605.10	1,594.90	5.53	5.55	-117.03	-152.36	-298.59	335.22	324.13	11.09	30.237								
1,700.00	1,700.00	1,705.10	1,694.90	5.89	5.91	-117.03	-152.36	-298.59	335.22	323.42	11.80	28.407								
1,800.00	1,800.00	1,805.10	1,794.90	6.25	6.27	-117.03	-152.36	-298.59	335.22	322.70	12.52	26.785								
1,900.00	1,900.00	1,905.10	1,894.90	6.61	6.62	-117.03	-152.36	-298.59	335.22	321.99	13.23	25.338								
2,000.00	2,000.00	2,005.10	1,994.90	6.96	6.98	-117.03	-152.36	-298.59	335.22	321.27	13.94	24.039								
2,100.00	2,100.00	2,105.10	2,094.90	7.32	7.34	-117.03	-152.36	-298.59	335.22	320.56	14.66	22.866								
2,200.00	2,200.00	2,205.10	2,194.90	7.68	7.70	-117.03	-152.36	-298.59	335.22	319.84	15.38	21.802								
2,300.00	2,300.00	2,305.10	2,294.90	8.04	8.05	-117.03	-152.36	-298.59	335.22	319.13	16.09	20.833								
2,400.00	2,400.00	2,405.10	2,394.90	8.39	8.41	-117.03	-152.36	-298.59	335.22	318.41	16.81	19.946								
2,500.00	2,500.00	2,505.10	2,494.90	8.75	8.77	-117.03	-152.36	-298.59	335.22	317.69	17.52	19.131								
2,600.00	2,600.00	2,605.10	2,594.90	9.11	9.13	-117.03	-152.36	-298.59	335.22	316.98	18.24	18.380								
2,700.00	2,700.00	2,694.90	2,694.90	9.47	9.45	-117.03	-152.36	-298.59	335.22	316.30	18.92	17.720	CC, ES							
2,800.00	2,800.00	2,789.55	2,789.54	9.83	9.78	-116.89	-151.95	-299.60	335.97	316.36	19.61	17.135								
2,900.00	2,900.00	2,883.80	2,883.72	10.18	10.11	-116.44	-150.62	-302.85	338.42	318.13	20.29	16.682								
3,000.00	3,000.00	2,977.80	2,977.53	10.54	10.44	-115.70	-148.38	-308.31	342.60	321.64	20.96	16.347								
3,100.00	3,100.00	3,071.44	3,070.80	10.90	10.77	-114.69	-145.24	-315.97	348.58	326.96	21.62	16.120								
3,200.00	3,200.00	3,164.60	3,163.36	11.26	11.11	-113.44	-141.23	-325.76	356.46	334.17	22.28	15.999								
3,300.00	3,300.00	3,257.58	3,255.44	11.62	11.44	-111.99	-136.34	-337.70	366.31	343.38	22.93	15.975								
3,400.00	3,400.00	3,356.46	3,353.20	11.97	11.81	-110.41	-130.73	-351.38	377.23	353.59	23.63	15.961								
3,500.00	3,500.00	3,455.33	3,450.96	12.33	12.18	-108.92	-125.12	-365.07	388.41	364.07	24.34	15.958	SF							
3,600.00	3,600.00	3,554.21	3,548.73	12.69	12.56	-107.51	-119.51	-378.76	399.84	374.80	25.05	15.964								
3,700.00	3,700.00	3,653.08	3,646.49	13.05	12.94	-106.18	-113.90	-392.45	411.50	385.74	25.76	15.977								
3,800.00	3,800.00	3,751.95	3,744.25	13.41	13.33	-104.93	-108.30	-406.13	423.37	396.90	26.47	15.996								
3,900.00	3,900.00	3,850.83	3,842.01	13.77	13.72	-103.74	-102.69	-419.82	435.42	408.24	27.18	16.021								
4,000.00	4,000.00	3,949.70	3,939.77	14.12	14.11	-102.62	-97.08	-433.51	447.65	419.76	27.89	16.051								
4,100.00	4,100.00	4,048.58	4,037.54	14.48	14.51	-101.56	-91.47	-447.20	460.05	431.44	28.60	16.084								
4,200.00	4,200.00	4,147.45	4,135.30	14.84	14.91	-100.55	-85.86	-460.88	472.59	443.27	29.32	16.120								
4,300.00	4,300.00	4,246.33	4,233.06	15.20	15.31	-99.60	-80.25	-474.57	485.27	455.24	30.03	16.159								
4,400.00	4,400.00	4,345.20	4,330.82	15.56	15.72	-98.69	-74.65	-488.26	498.07	467.33	30.75	16.200								
4,500.00	4,500.00	4,444.08	4,428.58	15.92	16.13	-97.83	-69.04	-501.95	510.99	479.53	31.46	16.242								
4,600.00	4,600.00	4,542.95	4,526.35	16.27	16.53	-97.01	-63.43	-515.63	524.03	491.85	32.18	16.286								
4,700.00	4,700.00	4,641.83	4,624.11	16.63	16.95	-96.23	-57.82	-529.32	537.16	504.27	32.89	16.331								
4,800.00	4,800.00	4,740.70	4,721.87	16.99	17.36	-95.49	-52.21	-543.01	550.38	516.77	33.61	16.377								
4,900.00	4,900.00	4,839.58	4,819.63	17.35	17.78	-94.79	-46.60	-556.70	563.69	529.37	34.32	16.423								
5,000.00	5,000.00	4,938.45	4,917.39	17.71	18.19	-94.11	-41.00	-570.38	577.08	542.05	35.04	16.470								
5,100.00	5,099.99	5,037.37	5,015.20	18.06	18.61	-96.54	-35.39	-584.08	590.68	554.92	35.76	16.519								

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

### Anticollision Report

<b>Company:</b>	WCDSC Permian NM	<b>Local Co-ordinate Reference:</b>	Well Jayhawk FED FEE COM 1H
<b>Project:</b>	Lea County (NAD83 New Mexico East)	<b>TVD Reference:</b>	RKB @ 3357.70ft
<b>Reference Site:</b>	Sec 06-T26S-R34E	<b>MD Reference:</b>	RKB @ 3357.70ft
<b>Site Error:</b>	5.00 ft	<b>North Reference:</b>	Grid
<b>Reference Well:</b>	Jayhawk FED FEE COM 1H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Well Error:</b>	0.50 ft	<b>Output errors are at</b>	2.00 sigma
<b>Reference Wellbore</b>	Wellbore #1	<b>Database:</b>	EDM r5000.141_Prod US
<b>Reference Design:</b>	Permit Plan 1	<b>Offset TVD Reference:</b>	Offset Datum

Offset Design      Sec 06-T26S-R34E - Jayhawk 6-7 FED FEE COM 4H - Wellbore #1 - Permit Plan 1													Offset Site Error:	5.00 ft
Survey Program:    0-MWD+IGRF													Offset Well Error:	0.50 ft
Reference		Offset		Semi Major Axis			Distance						Warning	
Measured Depth (ft)	Vertical Depth (ft)	Measured Depth (ft)	Vertical Depth (ft)	Reference (ft)	Offset (ft)	Highside Toolface (°)	Offset Wellbore +N/-S (ft)	Centre +E/-W (ft)	Between Centres (ft)	Between Ellipses (ft)	Minimum Separation (ft)	Separation Factor		
5,200.00	5,199.94	5,136.35	5,113.07	18.42	19.03	-96.06	-29.77	-597.78	604.55	568.07	36.48	16.573		
5,300.00	5,299.79	5,235.34	5,210.95	18.78	19.45	-95.80	-24.16	-611.48	618.66	581.46	37.20	16.630		
5,400.00	5,399.49	5,334.30	5,308.79	19.14	19.88	-95.73	-18.54	-625.18	632.99	595.06	37.93	16.690		
5,500.00	5,499.01	5,433.18	5,406.55	19.49	20.30	-95.84	-12.93	-638.87	647.54	608.89	38.66	16.751		
5,600.00	5,598.40	5,531.99	5,504.25	19.85	20.73	-96.23	-7.33	-652.55	662.25	622.86	39.39	16.813		
5,700.00	5,697.78	5,630.80	5,601.95	20.20	21.15	-96.61	-1.73	-666.23	676.99	636.86	40.12	16.873		
5,800.00	5,797.17	5,729.61	5,699.65	20.56	21.58	-96.97	3.88	-679.91	691.75	650.89	40.86	16.930		
5,900.00	5,896.55	5,828.42	5,797.35	20.92	22.01	-97.32	9.48	-693.59	706.55	664.95	41.60	16.986		
6,000.00	5,995.94	5,927.23	5,895.04	21.28	22.43	-97.66	15.09	-707.26	721.36	679.03	42.34	17.039		
6,100.00	6,095.32	6,026.04	5,992.74	21.64	22.86	-97.98	20.69	-720.94	736.20	693.13	43.08	17.090		
6,200.00	6,194.71	6,124.85	6,090.44	22.00	23.29	-98.29	26.30	-734.62	751.07	707.25	43.82	17.140		
6,300.00	6,294.09	6,223.66	6,188.14	22.37	23.72	-98.58	31.90	-748.30	765.95	721.39	44.56	17.188		
6,400.00	6,393.48	6,322.47	6,285.83	22.73	24.15	-98.87	37.51	-761.98	780.85	735.54	45.31	17.234		
6,500.00	6,492.86	6,421.28	6,383.53	23.09	24.59	-99.14	43.11	-775.66	795.77	749.72	46.06	17.278		
6,600.00	6,592.25	6,520.09	6,481.23	23.46	25.02	-99.41	48.72	-789.34	810.71	763.91	46.80	17.321		
6,700.00	6,691.63	6,618.90	6,578.93	23.82	25.45	-99.66	54.32	-803.01	825.67	778.11	47.55	17.363		
6,800.00	6,791.02	6,717.71	6,676.63	24.19	25.89	-99.91	59.93	-816.69	840.64	792.33	48.30	17.403		
6,900.00	6,890.40	6,816.52	6,774.32	24.56	26.32	-100.15	65.53	-830.37	855.62	806.56	49.06	17.442		
7,000.00	6,989.79	6,915.33	6,872.02	24.92	26.76	-100.38	71.13	-844.05	870.62	820.81	49.81	17.479		
7,100.00	7,089.17	7,014.14	6,969.72	25.29	27.19	-100.60	76.74	-857.73	885.63	835.07	50.56	17.516		
7,200.00	7,188.56	7,112.95	7,067.42	25.66	27.63	-100.81	82.34	-871.41	900.65	849.34	51.32	17.551		
7,300.00	7,287.94	7,211.75	7,165.11	26.03	28.06	-101.02	87.95	-885.09	915.69	863.62	52.07	17.585		
7,400.00	7,387.33	7,310.56	7,262.81	26.40	28.50	-101.22	93.55	-898.76	930.74	877.91	52.83	17.618		
7,500.00	7,486.71	7,409.37	7,360.51	26.77	28.94	-101.42	99.16	-912.44	945.80	892.21	53.59	17.650		
7,600.00	7,586.10	7,508.18	7,458.21	27.14	29.37	-101.60	104.76	-926.12	960.86	906.52	54.34	17.681		
7,700.00	7,685.48	7,606.99	7,555.91	27.51	29.81	-101.79	110.37	-939.80	975.94	920.84	55.10	17.711		
7,800.00	7,784.87	7,705.80	7,653.60	27.88	30.25	-101.96	115.97	-953.48	991.03	935.17	55.86	17.740		

Anticollision Report

Company: WCDSC Permian NM  
 Project: Lea County (NAD83 New Mexico East)  
 Reference Site: Sec 06-T26S-R34E  
 Site Error: 5.00 ft  
 Reference Well: Jayhawk FED FEE COM 1H  
 Well Error: 0.50 ft  
 Reference Wellbore: Wellbore #1  
 Reference Design: Permit Plan 1

Local Co-ordinate Reference: Well Jayhawk FED FEE COM 1H  
 TVD Reference: RKB @ 3357.70ft  
 MD Reference: RKB @ 3357.70ft  
 North Reference: Grid  
 Survey Calculation Method: Minimum Curvature  
 Output errors are at: 2.00 sigma  
 Database: EDM r5000.141\_Prod US  
 Offset TVD Reference: Offset Datum

Offset Design													Offset Site Error:	5.00 ft
Survey Program: 0-MWD+IGRF													Offset Well Error:	0.50 ft
Reference		Offset		Semi Major Axis		Distance							Warning	
Measured Depth (ft)	Vertical Depth (ft)	Measured Depth (ft)	Vertical Depth (ft)	Reference (ft)	Offset (ft)	Highside Toolface (°)	Offset Wellbore Centre +N/-S (ft)	Offset Wellbore Centre +E/-W (ft)	Between Centres (ft)	Between Ellipses (ft)	Minimum Separation (ft)	Separation Factor		
0.00	0.00	0.50	0.50	0.50	0.50	179.49	-149.94	1.34	149.95					
100.00	100.00	100.50	100.50	0.52	0.52	179.49	-149.94	1.34	149.95	148.91	1.04	144.739		
200.00	200.00	200.50	200.50	0.70	0.70	179.49	-149.94	1.34	149.95	148.54	1.41	106.688		
300.00	300.00	300.50	300.50	0.99	0.99	179.49	-149.94	1.34	149.95	147.97	1.98	75.875		
400.00	400.00	400.50	400.50	1.31	1.31	179.49	-149.94	1.34	149.95	147.33	2.62	57.235		
500.00	500.00	500.50	500.50	1.65	1.65	179.49	-149.94	1.34	149.95	146.65	3.29	45.523		
600.00	600.00	600.50	600.50	1.99	1.99	179.49	-149.94	1.34	149.95	145.96	3.98	37.647		
700.00	700.00	700.50	700.50	2.34	2.34	179.49	-149.94	1.34	149.95	145.27	4.68	32.037		
800.00	800.00	800.50	800.50	2.69	2.69	179.49	-149.94	1.34	149.95	144.56	5.38	27.856		
900.00	900.00	900.50	900.50	3.04	3.05	179.49	-149.94	1.34	149.95	143.86	6.09	24.626		
1,000.00	1,000.00	1,000.50	1,000.50	3.40	3.40	179.49	-149.94	1.34	149.95	143.15	6.80	22.060		
1,100.00	1,100.00	1,100.50	1,100.50	3.75	3.75	179.49	-149.94	1.34	149.95	142.44	7.51	19.974		
1,200.00	1,200.00	1,200.50	1,200.50	4.11	4.11	179.49	-149.94	1.34	149.95	141.73	8.22	18.246		
1,300.00	1,300.00	1,300.50	1,300.50	4.46	4.47	179.49	-149.94	1.34	149.95	141.02	8.93	16.791		
1,400.00	1,400.00	1,400.50	1,400.50	4.82	4.82	179.49	-149.94	1.34	149.95	140.30	9.64	15.550		
1,500.00	1,500.00	1,500.50	1,500.50	5.18	5.18	179.49	-149.94	1.34	149.95	139.59	10.36	14.479		
1,600.00	1,600.00	1,600.50	1,600.50	5.53	5.54	179.49	-149.94	1.34	149.95	138.88	11.07	13.545		
1,700.00	1,700.00	1,700.50	1,700.50	5.89	5.89	179.49	-149.94	1.34	149.95	138.16	11.78	12.724		
1,800.00	1,800.00	1,800.50	1,800.50	6.25	6.25	179.49	-149.94	1.34	149.95	137.45	12.50	11.997		
1,900.00	1,900.00	1,900.50	1,900.50	6.61	6.61	179.49	-149.94	1.34	149.95	136.73	13.21	11.348		
2,000.00	2,000.00	2,000.50	2,000.50	6.96	6.97	179.49	-149.94	1.34	149.95	136.02	13.93	10.765		
2,100.00	2,100.00	2,100.50	2,100.50	7.32	7.32	179.49	-149.94	1.34	149.95	135.30	14.64	10.240		
2,200.00	2,200.00	2,200.50	2,200.50	7.68	7.68	179.49	-149.94	1.34	149.95	134.59	15.36	9.763		
2,300.00	2,300.00	2,300.50	2,300.50	8.04	8.04	179.49	-149.94	1.34	149.95	133.87	16.07	9.328		
2,400.00	2,400.00	2,400.50	2,400.50	8.39	8.40	179.49	-149.94	1.34	149.95	133.16	16.79	8.931		
2,500.00	2,500.00	2,500.50	2,500.50	8.75	8.75	179.49	-149.94	1.34	149.95	132.44	17.51	8.565		
2,600.00	2,600.00	2,600.50	2,600.50	9.11	9.11	179.49	-149.94	1.34	149.95	131.72	18.22	8.229		
2,700.00	2,700.00	2,700.50	2,700.50	9.47	9.47	179.49	-149.94	1.34	149.95	131.01	18.94	7.918		
2,800.00	2,800.00	2,800.50	2,800.50	9.83	9.83	179.49	-149.94	1.34	149.95	130.29	19.65	7.629		
2,900.00	2,900.00	2,900.50	2,900.50	10.18	10.19	179.49	-149.94	1.34	149.95	129.58	20.37	7.361		
3,000.00	3,000.00	3,000.50	3,000.50	10.54	10.54	179.49	-149.94	1.34	149.95	128.86	21.09	7.111		
3,100.00	3,100.00	3,100.50	3,100.50	10.90	10.90	179.49	-149.94	1.34	149.95	128.14	21.80	6.878		
3,200.00	3,200.00	3,200.50	3,200.50	11.26	11.26	179.49	-149.94	1.34	149.95	127.43	22.52	6.659		
3,300.00	3,300.00	3,300.50	3,300.50	11.62	11.62	179.49	-149.94	1.34	149.95	126.71	23.23	6.454		
3,400.00	3,400.00	3,400.50	3,400.50	11.97	11.98	179.49	-149.94	1.34	149.95	126.00	23.95	6.261		
3,500.00	3,500.00	3,500.50	3,500.50	12.33	12.33	179.49	-149.94	1.34	149.95	125.28	24.67	6.079		
3,600.00	3,600.00	3,600.50	3,600.50	12.69	12.69	179.49	-149.94	1.34	149.95	124.56	25.38	5.907		
3,700.00	3,700.00	3,700.50	3,700.50	13.05	13.05	179.49	-149.94	1.34	149.95	123.85	26.10	5.745		
3,800.00	3,800.00	3,800.50	3,800.50	13.41	13.41	179.49	-149.94	1.34	149.95	123.13	26.82	5.592		
3,900.00	3,900.00	3,900.50	3,900.50	13.77	13.77	179.49	-149.94	1.34	149.95	122.41	27.53	5.446		
4,000.00	4,000.00	4,000.50	4,000.50	14.12	14.13	179.49	-149.94	1.34	149.95	121.70	28.25	5.308		
4,100.00	4,100.00	4,100.50	4,100.50	14.48	14.48	179.49	-149.94	1.34	149.95	120.98	28.97	5.177		
4,200.00	4,200.00	4,200.50	4,200.50	14.84	14.84	179.49	-149.94	1.34	149.95	120.26	29.68	5.052		
4,300.00	4,300.00	4,300.50	4,300.50	15.20	15.20	179.49	-149.94	1.34	149.95	119.55	30.40	4.933 Alert		
4,400.00	4,400.00	4,400.50	4,400.50	15.56	15.56	179.49	-149.94	1.34	149.95	118.83	31.12	4.819 Alert		
4,500.00	4,500.00	4,500.50	4,500.50	15.92	15.92	179.49	-149.94	1.34	149.95	118.11	31.83	4.711 Alert		
4,600.00	4,600.00	4,600.50	4,600.50	16.27	16.28	179.49	-149.94	1.34	149.95	117.40	32.55	4.607 Alert		
4,700.00	4,700.00	4,700.50	4,700.50	16.63	16.63	179.49	-149.94	1.34	149.95	116.68	33.27	4.508 Alert		
4,800.00	4,800.00	4,800.50	4,800.50	16.99	16.99	179.49	-149.94	1.34	149.95	115.96	33.98	4.413 Alert		
4,900.00	4,900.00	4,900.50	4,900.50	17.35	17.35	179.49	-149.94	1.34	149.95	115.25	34.70	4.321 Alert		
5,000.00	5,000.00	5,000.52	5,000.52	17.71	17.71	179.49	-149.94	1.34	149.95	114.53	35.42	4.234 Alert		
5,010.68	5,010.68	5,011.52	5,011.52	17.74	17.75	176.35	-149.93	1.33	149.95	114.45	35.49	4.225 Alert, CC		

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

Anticollision Report

**Company:** WCDSC Permian NM  
**Project:** Lea County (NAD83 New Mexico East)  
**Reference Site:** Sec 06-T26S-R34E  
**Site Error:** 5.00 ft  
**Reference Well:** Jayhawk FED FEE COM 1H  
**Well Error:** 0.50 ft  
**Reference Wellbore:** Wellbore #1  
**Reference Design:** Permit Plan 1

**Local Co-ordinate Reference:** Well Jayhawk FED FEE COM 1H  
**TVD Reference:** RKB @ 3357.70ft  
**MD Reference:** RKB @ 3357.70ft  
**North Reference:** Grid  
**Survey Calculation Method:** Minimum Curvature  
**Output errors are at** 2.00 sigma  
**Database:** EDM r5000.141\_Prod US  
**Offset TVD Reference:** Offset Datum

Offset Design Sec 06-T26S-R34E - Jayhawk 6-7 FED FEE COM 5H - Wellbore #1 - Permit Plan 1													Offset Site Error:	5.00 ft
Survey Program: 0-MWD+IGRF													Offset Well Error:	0.50 ft
Reference		Offset		Semi Major Axis			Distance						Warning	
Measured Depth (ft)	Vertical Depth (ft)	Measured Depth (ft)	Vertical Depth (ft)	Reference (ft)	Offset (ft)	Highside Tooface (')	Offset Wellbore Centre +N/-S (ft)	+E/-W (ft)	Between Centres (ft)	Between Ellipses (ft)	Minimum Separation (ft)	Separation Factor		
5,100.00	5,099.99	5,103.63	5,103.62	18.06	18.08	176.54	-148.86	0.88	149.99	113.85	36.14	4.151	Alert	
5,200.00	5,199.94	5,206.73	5,206.66	18.42	18.45	177.13	-145.65	-0.48	150.13	113.29	36.84	4.075	Alert	
5,300.00	5,299.79	5,309.79	5,309.56	18.78	18.81	178.11	-140.30	-2.74	150.42	112.89	37.54	4.007	Alert	
5,400.00	5,399.49	5,412.81	5,412.25	19.14	19.18	179.47	-132.83	-5.89	150.90	112.68	38.22	3.949	Alert	
5,500.00	5,499.01	5,515.75	5,514.66	19.49	19.55	-178.80	-123.24	-9.95	151.64	112.75	38.89	3.899	Alert	
5,600.00	5,598.40	5,616.85	5,615.03	19.85	19.91	-176.80	-112.12	-14.65	152.16	112.57	39.59	3.844	Alert	
5,700.00	5,697.78	5,716.70	5,714.15	20.20	20.27	-174.81	-100.95	-19.37	152.70	112.39	40.31	3.788	Alert, ES	
5,800.00	5,797.17	5,816.56	5,813.27	20.56	20.64	-172.84	-89.79	-24.09	153.43	112.39	41.04	3.739	Alert	
5,900.00	5,896.55	5,916.42	5,912.39	20.92	21.00	-170.88	-78.62	-28.81	154.34	112.57	41.76	3.696	Alert	
6,000.00	5,995.94	6,016.28	6,011.51	21.28	21.37	-168.95	-67.46	-33.53	155.42	112.93	42.49	3.658	Alert	
6,100.00	6,095.32	6,116.13	6,110.63	21.64	21.74	-167.05	-56.30	-38.25	156.68	113.46	43.22	3.625	Alert	
6,200.00	6,194.71	6,215.99	6,209.75	22.00	22.11	-165.18	-45.13	-42.97	158.12	114.16	43.95	3.597	Alert	
6,300.00	6,294.09	6,315.85	6,308.87	22.37	22.48	-163.35	-33.97	-47.69	159.71	115.02	44.69	3.574	Alert	
6,400.00	6,393.48	6,415.71	6,407.99	22.73	22.86	-161.55	-22.80	-52.41	161.47	116.04	45.43	3.555	Alert	
6,500.00	6,492.86	6,515.56	6,507.11	23.09	23.23	-159.80	-11.64	-57.13	163.38	117.22	46.17	3.539	Alert	
6,600.00	6,592.25	6,615.42	6,606.23	23.46	23.61	-158.08	-0.47	-61.85	165.44	118.54	46.91	3.527	Alert	
6,700.00	6,691.63	6,715.28	6,705.35	23.82	23.99	-156.42	10.69	-66.57	167.65	120.00	47.65	3.518	Alert	
6,800.00	6,791.02	6,815.14	6,804.46	24.19	24.37	-154.79	21.86	-71.30	170.00	121.60	48.40	3.513	Alert	
6,900.00	6,890.40	6,914.99	6,903.58	24.56	24.75	-153.21	33.02	-76.02	172.48	123.33	49.14	3.510	Alert	
7,000.00	6,989.79	7,014.85	7,002.70	24.92	25.13	-151.68	44.18	-80.74	175.08	125.19	49.89	3.509	Alert	
7,100.00	7,089.17	7,114.71	7,101.82	25.29	25.52	-150.19	55.35	-85.46	177.81	127.17	50.64	3.511	Alert	
7,200.00	7,188.56	7,214.57	7,200.94	25.66	25.90	-148.75	66.51	-90.18	180.65	129.26	51.40	3.515	Alert	
7,300.00	7,287.94	7,314.43	7,300.06	26.03	26.29	-147.35	77.68	-94.90	183.61	131.46	52.15	3.521	Alert	
7,400.00	7,387.33	7,414.28	7,399.18	26.40	26.68	-146.00	88.84	-99.62	186.67	133.76	52.91	3.528	Alert	
7,500.00	7,486.71	7,514.14	7,498.30	26.77	27.06	-144.69	100.01	-104.34	189.83	136.17	53.67	3.537	Alert	
7,600.00	7,586.10	7,614.00	7,597.42	27.14	27.45	-143.43	111.17	-109.06	193.09	138.67	54.43	3.548	Alert	
7,700.00	7,685.48	7,713.86	7,696.54	27.51	27.84	-142.21	122.33	-113.78	196.44	141.25	55.19	3.560	Alert	
7,800.00	7,784.87	7,813.71	7,795.66	27.88	28.23	-141.03	133.50	-118.50	199.87	143.92	55.95	3.572	Alert	
7,900.00	7,884.25	7,912.32	7,893.59	28.25	28.62	-140.01	144.13	-122.99	203.57	146.85	56.71	3.589	Alert	
8,000.00	7,983.79	8,010.11	7,990.95	28.62	28.99	-139.40	152.56	-126.56	207.12	149.65	57.46	3.604	Alert	
8,100.00	8,083.54	8,107.96	8,088.57	28.98	29.36	-138.96	158.70	-129.15	209.72	151.52	58.20	3.604	Alert	
8,200.00	8,183.45	8,205.86	8,186.37	29.34	29.72	-138.70	162.54	-130.78	211.35	152.44	58.92	3.587	Alert	
8,300.00	8,283.43	8,303.77	8,284.26	29.70	30.07	-138.60	164.07	-131.42	212.01	152.39	59.62	3.556	Alert	
8,400.00	8,383.43	8,403.43	8,383.93	30.06	30.42	-135.45	164.10	-131.43	212.02	151.70	60.32	3.515	Alert	
8,500.00	8,483.43	8,503.43	8,483.93	30.41	30.77	-135.45	164.10	-131.43	212.02	151.00	61.03	3.474	Alert	
8,600.00	8,583.43	8,603.43	8,583.93	30.77	31.12	-135.45	164.10	-131.43	212.02	150.29	61.74	3.434	Alert	
8,700.00	8,683.43	8,703.43	8,683.93	31.12	31.47	-135.45	164.10	-131.43	212.02	149.58	62.44	3.395	Alert	
8,800.00	8,783.43	8,803.43	8,783.93	31.48	31.82	-135.45	164.10	-131.43	212.02	148.87	63.15	3.357	Alert	
8,900.00	8,883.43	8,903.43	8,883.93	31.83	32.17	-135.45	164.10	-131.43	212.02	148.17	63.86	3.320	Alert	
9,000.00	8,983.43	9,003.43	8,983.93	32.19	32.52	-135.45	164.10	-131.43	212.02	147.46	64.57	3.284	Alert	
9,100.00	9,083.43	9,103.43	9,083.93	32.54	32.87	-135.45	164.10	-131.43	212.02	146.75	65.28	3.248	Alert	
9,200.00	9,183.43	9,203.43	9,183.93	32.90	33.22	-135.45	164.10	-131.43	212.02	146.04	65.99	3.213	Alert	
9,300.00	9,283.43	9,303.43	9,283.93	33.25	33.57	-135.45	164.10	-131.43	212.02	145.33	66.69	3.179	Alert	
9,400.00	9,383.43	9,403.43	9,383.93	33.61	33.93	-135.45	164.10	-131.43	212.02	144.62	67.40	3.146	Alert	
9,500.00	9,483.43	9,503.43	9,483.93	33.96	34.28	-135.45	164.10	-131.43	212.02	143.91	68.11	3.113	Alert	
9,600.00	9,583.43	9,603.43	9,583.93	34.32	34.63	-135.45	164.10	-131.43	212.02	143.20	68.82	3.081	Alert	
9,700.00	9,683.43	9,703.43	9,683.93	34.67	34.98	-135.45	164.10	-131.43	212.02	142.49	69.53	3.049	Alert	
9,800.00	9,783.43	9,803.43	9,783.93	35.03	35.34	-135.45	164.10	-131.43	212.02	141.78	70.24	3.019	Alert	
9,900.00	9,883.43	9,903.43	9,883.93	35.38	35.69	-135.45	164.10	-131.43	212.02	141.07	70.95	2.988	Alert	
10,000.00	9,983.43	10,003.43	9,983.93	35.74	36.04	-135.45	164.10	-131.43	212.02	140.36	71.66	2.959	Alert	
10,100.00	10,083.43	10,103.43	10,083.93	36.10	36.39	-135.45	164.10	-131.43	212.02	139.65	72.37	2.930	Alert	
10,200.00	10,183.43	10,203.43	10,183.93	36.45	36.75	-135.45	164.10	-131.43	212.02	138.94	73.08	2.901	Alert	

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

Anticollision Report

Company: WCDSC Permian NM  
 Project: Lea County (NAD83 New Mexico East)  
 Reference Site: Sec 06-T26S-R34E  
 Site Error: 5.00 ft  
 Reference Well: Jayhawk FED FEE COM 1H  
 Well Error: 0.50 ft  
 Reference Wellbore: Wellbore #1  
 Reference Design: Permit Plan 1

Local Co-ordinate Reference: Well Jayhawk FED FEE COM 1H  
 TVD Reference: RKB @ 3357.70ft  
 MD Reference: RKB @ 3357.70ft  
 North Reference: Grid  
 Survey Calculation Method: Minimum Curvature  
 Output errors are at: 2.00 sigma  
 Database: EDM r5000.141\_Prod US  
 Offset TVD Reference: Offset Datum


Offset Design													Offset Site Error:	5.00 ft				
Survey Program: 0-MWD+IGRF													Offset Well Error:	0.50 ft				
Reference													Semi Major Axis		Distance		Separation Factor	Warning
Measured Depth (ft)	Vertical Depth (ft)	Measured Depth (ft)	Vertical Depth (ft)	Reference (ft)	Offset (ft)	Highside Toolface (°)	Offset Wellbore Centre +N/-S (ft)	+E/-W (ft)	Between Centres (ft)	Between Ellipses (ft)	Minimum Separation (ft)							
10,209.73	10,193.16	10,213.16	10,193.66	36.49	36.78	-135.45	164.10	-131.43	212.02	138.87	73.15	2.898 Alert						
10,300.00	10,283.43	10,300.00	10,280.49	36.81	37.08	-135.48	163.94	-131.43	212.16	138.41	73.75	2.877 Alert, SF						
10,400.00	10,383.43	10,378.41	10,358.51	37.16	37.31	-136.82	156.75	-131.37	218.76	144.86	73.90	2.960 Alert						
10,500.00	10,483.43	10,453.57	10,431.71	37.52	37.51	-139.72	139.92	-131.23	235.60	162.22	73.39	3.210 Alert						
10,600.00	10,583.43	10,523.28	10,497.10	37.87	37.66	-143.34	115.88	-131.03	263.19	191.03	72.15	3.648 Alert						
10,700.00	10,683.43	10,586.30	10,553.30	38.23	37.78	-146.96	87.46	-130.79	301.42	231.11	70.31	4.287 Alert						
10,800.00	10,783.43	10,642.24	10,600.32	38.59	37.88	-150.19	57.19	-130.53	349.47	281.36	68.12	5.131						
10,900.00	10,883.43	10,691.35	10,638.99	38.94	37.95	-152.89	26.95	-130.28	406.02	340.19	65.84	6.167						
11,000.00	10,983.43	10,734.20	10,670.52	39.30	38.01	-155.09	-2.05	-130.03	469.66	406.00	63.66	7.378						
11,100.00	11,083.43	10,771.52	10,696.14	39.65	38.06	-156.87	-29.18	-129.80	539.08	477.39	61.69	8.738						
11,200.00	11,183.43	10,800.00	10,714.48	40.01	38.09	-158.14	-50.97	-129.62	613.23	553.47	59.76	10.262						
11,300.00	11,283.43	10,832.50	10,734.05	40.37	38.13	-159.49	-76.91	-129.40	691.11	632.60	58.51	11.812						
11,400.00	11,383.43	10,850.00	10,743.97	40.72	38.16	-160.17	-91.33	-129.28	772.20	715.24	56.97	13.556						
11,500.00	11,483.43	10,879.46	10,759.65	41.08	38.20	-161.26	-116.25	-129.06	855.65	799.39	56.27	15.207						
11,600.00	11,583.43	10,900.00	10,769.83	41.44	38.23	-161.97	-134.10	-128.91	941.28	885.80	55.48	16.967						

# Anticollision Report

<b>Company:</b> WCDSC Permian NM	<b>Local Co-ordinate Reference:</b> Well Jayhawk FED FEE COM 1H
<b>Project:</b> Lea County (NAD83 New Mexico East)	<b>TVD Reference:</b> RKB @ 3357.70ft
<b>Reference Site:</b> Sec 06-T26S-R34E	<b>MD Reference:</b> RKB @ 3357.70ft
<b>Site Error:</b> 5.00 ft	<b>North Reference:</b> Grid
<b>Reference Well:</b> Jayhawk FED FEE COM 1H	<b>Survey Calculation Method:</b> Minimum Curvature
<b>Well Error:</b> 0.50 ft	<b>Output errors are at:</b> 2.00 sigma
<b>Reference Wellbore:</b> Wellbore #1	<b>Database:</b> EDM r5000.141_Prod US
<b>Reference Design:</b> Permit Plan 1	<b>Offset TVD Reference:</b> Offset Datum

Reference Depths are relative to RKB @ 3357.70ft  
 Offset Depths are relative to Offset Datum  
 Central Meridian is -104.333334

Coordinates are relative to: Jayhawk FED FEE COM 1H  
 Coordinate System is US State Plane 1983, New Mexico Eastern Zone  
 Grid Convergence at Surface is: 0.44°




CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

# Anticollision Report

<b>Company:</b> WCDSC Permian NM <b>Project:</b> Lea County (NAD83 New Mexico East) <b>Reference Site:</b> Sec 06-T26S-R34E <b>Site Error:</b> 5.00 ft <b>Reference Well:</b> Jayhawk FED FEE COM 1H <b>Well Error:</b> 0.50 ft <b>Reference Wellbore:</b> Wellbore #1 <b>Reference Design:</b> Permit Plan 1	<b>Local Co-ordinate Reference:</b> Well Jayhawk FED FEE COM 1H <b>TVD Reference:</b> RKB @ 3357.70ft <b>MD Reference:</b> RKB @ 3357.70ft <b>North Reference:</b> Grid <b>Survey Calculation Method:</b> Minimum Curvature <b>Output errors are at:</b> 2.00 sigma <b>Database:</b> EDM r5000.141_Prod US <b>Offset TVD Reference:</b> Offset Datum	
--	---	--

Reference Depths are relative to RKB @ 3357.70ft Offset Depths are relative to Offset Datum Central Meridian is -104.333334	Coordinates are relative to: Jayhawk FED FEE COM 1H Coordinate System is US State Plane 1983, New Mexico Eastern Zone Grid Convergence at Surface is: 0.44°
---	---



CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation