

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**HOBBS OCD**

FORM APPROVED  
OMB NO. 1004-0137  
Expires: January 31, 2018

**SUNDRY NOTICES AND REPORTS ON WELLS** OCT 24 2018  
*Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.*

**SUBMIT IN TRIPLICATE - Other instructions on page 2**

**RECEIVED**

1. Type of Well <input type="checkbox"/> Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other	8. Well Name and No. SALADO DRAW 9 16 W1AP FED COM 2H
2. Name of Operator MEWBOURNE OIL COMPANY Contact: JACKIE LATHAN E-Mail: jlathan@mewbourne.com	9. API Well No. 30-025-44913-00-X1
3a. Address P O BOX 5270 HOBBS, NM 88241	10. Field and Pool or Exploratory Area RED HILLS - WOLFCAMP (GAS)
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Sec 9 T26S R33E NENE 330FNL 210FEL	11. County or Parish, State LEA COUNTY, NM

**12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA**

TYPE OF SUBMISSION	TYPE OF ACTION
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize <input type="checkbox"/> Deepen <input type="checkbox"/> Production (Start/Resume) <input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing <input type="checkbox"/> Hydraulic Fracturing <input type="checkbox"/> Reclamation <input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair <input type="checkbox"/> New Construction <input type="checkbox"/> Recomplete <input checked="" type="checkbox"/> Other Change to Original APD
	<input type="checkbox"/> Change Plans <input type="checkbox"/> Plug and Abandon <input type="checkbox"/> Temporarily Abandon
	<input type="checkbox"/> Convert to Injection <input type="checkbox"/> Plug Back <input type="checkbox"/> Water Disposal

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.

Mewbourne Oil Company requests approval to make the following changes to the approved APD:

- 1) Change well name to ~~Salado Draw 9/16 W1AP Fed Com #2H~~ **OK-0110 - 322769**
- 2) Change BHL to 100' FSL & 330' FEL, Sec 16, T26S, R32E
- 3) Change casing & cement design as detailed in attached drilling program.
- 4) Variance for use of 5M annular BOP on 10M BOPE stack
- 5) Variance for use of multi-bowl wellhead
- 6) Variance to batch drill wells as detailed in attachment

See attachments for C-102, drilling program, directional plan and equipment schematics.

Please contact Andy Taylor with any questions.

14. I hereby certify that the foregoing is true and correct.

**Electronic Submission #437870 verified by the BLM Well Information System  
For MEWBOURNE OIL COMPANY, sent to the Hobbs  
Committed to AFMSS for processing by PRISCILLA PEREZ on 10/03/2018 (19PP0012SE)**

Name (Printed/Typed) <b>ANDY TAYLOR</b>	Title <b>ENGINEER</b>
Signature (Electronic Submission)	Date <b>10/01/2018</b>

**THIS SPACE FOR FEDERAL OR STATE OFFICE USE**

Approved By <u>ZQIA STEVENS</u>	Title <b>PETROLEUM ENGINEER</b>	Date <b>10/18/2018</b>
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.		Office <b>Hobbs</b>

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

**\*\* BLM REVISED \*\* BLM REVISED \*\* BLM REVISED \*\* BLM REVISED \*\* BLM REVISED \*\***

District I  
1625 N. French Dr., Hobbs, NM 88240  
Phone: (575) 393-6161 Fax: (575) 393-0720  
District II  
811 S. First St., Artesia, NM 88210  
Phone: (575) 748-1283 Fax: (575) 748-9720  
District III  
1000 Rio Brazos Road, Aztec, NM 87410  
Phone: (505) 334-6178 Fax: (505) 334-6170  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM 87505  
Phone: (505) 476-3460 Fax: (505) 476-3462

State of New Mexico  
Energy, Minerals & Natural Resources Department  
OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

Form C-102  
Revised August 1, 2011  
Submit one copy to appropriate  
District Office

AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

1 API Number <b>30-024 44913</b>		2 Pool Code		3 Pool Name	
4 Property Code <b>722769</b>		5 Property Name <b>SALADO DRAW 9/16 WIAP FED COM</b>			6 Well Number <b>2H</b>
7 OGRID NO.		8 Operator Name <b>MEWBOURNE OIL COMPANY</b>			9 Elevation <b>3332'</b>

10 Surface Location


UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet From the	East/West line	County
<b>A</b>	<b>9</b>	<b>26S</b>	<b>33E</b>		<b>330</b>	<b>NORTH</b>	<b>210</b>	<b>EAST</b>	<b>LEA</b>

11 Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
<b>P</b>	<b>16</b>	<b>26S</b>	<b>33E</b>		<b>100</b>	<b>SOUTH</b>	<b>330</b>	<b>EAST</b>	<b>LEA</b>

12 Dedicated Acres	13 Joint or Infill	14 Consolidation Code	15 Order No.
--------------------	--------------------	-----------------------	--------------

No allowable will be assigned to this completion until all interest have been consolidated or a non-standard unit has been approved by the division.



Operator Name: Mewbourne Oil Co.	Property Name: Salado Draw 9/16 W1AP Fed Com	Well Number 2H
-------------------------------------	---	-------------------

Kick Off Point (KOP)

UL A	Section 9	Township 26S	Range 32E	Lot	Feet 10	From N/S N	Feet 330	From E/W E	County Lea
Latitude 32.0652329					Longitude -103.5697841				NAD 83

First Take Point (FTP)

UL A	Section 9	Township 26S	Range 32E	Lot	Feet 100	From N/S N	Feet 330	From E/W E	County Lea
Latitude 32.0649882					Longitude -103.5697841				NAD 83

Last Take Point (LTP)

UL P	Section 16	Township 26S	Range 32E	Lot	Feet 100	From N/S S	Feet 330	From E/W E	County Lea
Latitude 32.0365016					Longitude -103.5697806				NAD 83

Is this well the defining well for the Horizontal Spacing Unit?  N


Is this well an infill well?  Y

If infill is yes please provide API if available, Operator Name and well number for Defining well for Horizontal Spacing Unit.

API # 30-025-44648	Operator Name: Mewbourne Oil Co.	Property Name: Salado Draw 9/16 W0AP Fed Com	Well Number 3H
-----------------------	-------------------------------------	---	-------------------

# LOCATION VERIFICATION MAP

NOT TO SCALE



*SECTION 9, TWP. 26 SOUTH, RGE. 33 EAST,  
N. M. P. M., LEA COUNTY, NEW MEXICO*

OPERATOR: Mewbourne Oil Company  
 LEASE: Salado Draw 9/16 W1AP Fed Com  
 WELL NO.: 2H  
 ELEVATION: 3332'

LOCATION: 330' FNL & 210' FEL  
 CONTOUR INTERVAL: 10'  
 USGS TOPO. SOURCE MAP:  
Paduca Breaks East, NM (1973)

*Copyright 2016 - All Rights Reserved*

NO.	REVISION	DATE
JOB NO.: LS1509543D		
DWG. NO.: 1509543LVM		


# RRC

308 W. BROADWAY ST., HOBBS, NM 88240 (575) 964-8200

SCALE: N. T. S.  
 DATE: 11-18-2015  
 SURVEYED BY: BC/HD  
 DRAWN BY: LPS  
 APPROVED BY: RMH  
 SHEET: 1 OF 1

# VICINITY MAP

NOT TO SCALE



*SECTION 9, TWP. 26 SOUTH, RGE. 33 EAST,  
N. M. P. M., LEA COUNTY, NEW MEXICO*

OPERATOR: Mewbourne Oil Company  
 LEASE: Salado Draw 9/16 W1AP Fed Com  
 WELL NO.: 2H

LOCATION: 330' FNL & 210' FEL  
 ELEVATION: 3332'

*Copyright 2016 - All Rights Reserved*

NO.	REVISION	DATE
JOB NO.: LS1509543D		
DWG. NO.: 1509543LVM		

# RRC



308 W. BROADWAY ST., HOBBS, NM 88240 (575) 964-8200

SCALE: N. T. S.
DATE: 11-18-2015
SURVEYED BY: BC/HD
DRAWN BY: LPS
APPROVED BY: RMH
SHEET: 1 OF 1



Mewbourne Oil Company, Salado Draw 9/16 W1AP Fed Com #2H

Sec 9, T26S, R33E

SL: 330' FNL & 210' FEL, Sec 9

BHL: 100' FSL & 330' FEL, Sec 16

1. Geologic Formations

TVD of target	12,310'	Pilot hole depth	NA
MD at TD:	17,014'	Deepest expected fresh water:	250'

**Basin**

Formation	Depth (TVD) from KB	Water/Mineral Bearing/ Target Zone?	Hazards*
Quaternary Fill	Surface		
Rustler	934		
Top of Salt	1292		
Castile	3502		
Base of Salt	4874		
Lamar	5005	Oil	
Bell Canyon	5052		
Cherry Canyon	6108		
Manzanita Marker	6227		
Brushy Canyon	7590		
Bone Spring	9022	Oil/Gas	
1 <sup>st</sup> Bone Spring Sand	10,010		
2 <sup>nd</sup> Bone Spring Sand	10,589		
3 <sup>rd</sup> Bone Spring Sand	11,652		
Abo			
Wolfcamp	12,107	Target Zone	
Devonian			
Fusselman			
Ellenburger			
Granite Wash			

\*H2S, water flows, loss of circulation, abnormal pressures, etc.

Mewbourne Oil Company, Salado Draw 9/16 W1AP Fed Com #2H

Sec 9, T26S, R33E

SL: 330' FNL & 210' FEL, Sec 9

BHL: 100' FSL & 330' FEL, Sec 16

2. Casing Program

Hole Size	Casing Interval		Csg. Size	Weight (lbs/ft)	Grade	Conn.	SF Collapse	SF Burst	SF Jt Tension	SF Body Tension
	From	To								
20"	0'	1010'	16"	65	H40	BTC	1.36	3.55	11.90	11.21
13.5"	0'	4930'	10.75"	45.5	HCL80	BTC	1.23	2.04	5.24	4.64
9.875"	0'	11,900'	7.625"	29.7	HCP110	LTC	1.16	1.53	2.18	2.66
6.5"	0'	22,779'	5.5"	23	P110	UFJ	1.70	1.70	1.67	2.51
BLM Minimum Safety Factor							1.125	1	1.6 Dry 1.8 Wet	1.6 Dry 1.8 Wet

All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.h

Must have table for contingency casing

	Y or N
Is casing new? If used, attach certification as required in Onshore Order #1	Y
Is casing API approved? If no, attach casing specification sheet.	Y
Is premium or uncommon casing planned? If yes attach casing specification sheet.	N
Does the above casing design meet or exceed BLM's minimum standards? If not provide justification (loading assumptions, casing design criteria).	Y
Will the pipe be kept at a minimum 1/3 fluid filled to avoid approaching the collapse pressure rating of the casing?	Y
Is well located within Capitan Reef?	N
If yes, does production casing cement tie back a minimum of 50' above the Reef?	
Is well within the designated 4 string boundary.	
Is well located in SOPA but not in R-111-P?	N
If yes, are the first 2 strings cemented to surface and 3 <sup>rd</sup> string cement tied back 500' into previous casing?	
Is well located in R-111-P and SOPA?	N
If yes, are the first three strings cemented to surface?	
Is 2 <sup>nd</sup> string set 100' to 600' below the base of salt?	
Is well located in high Cave/Karst?	N
If yes, are there two strings cemented to surface?	
(For 2 string wells) If yes, is there a contingency casing if lost circulation occurs?	
Is well located in critical Cave/Karst?	N
If yes, are there three strings cemented to surface?	

Mewbourne Oil Company, Salado Draw 9/16 W1AP Fed Com #2H  
 Sec 9, T26S, R33E  
 SL: 330' FNL & 210' FEL, Sec 9  
 BHL: 100' FSL & 330' FEL, Sec 16

**3. Cementing Program**

A

Casing	# Sks	Wt. lb/gal	Yld ft <sup>3</sup> /sack	H <sub>2</sub> O gal/sk	500# Comp. Strength (hours)	Slurry Description
urf.	625	12.5	2.12	11	10	Lead: Class C + Salt + Gel + Extender + LCM
	200	14.8	1.34	6.3	8	Tail: Class C + Retarder
nter.	1100	12.5	2.12	11	10	Lead: Class C + Salt + Gel + Extender + LCM
	200	14.8	1.34	6.3	8	Tail: Class C + Retarder
rod. tg 1	500	12.5	2.12	11	9	Lead: Class C + Gel + Retarder + Defoamer + Extender
	400	15.6	1.18	5.2	13	Tail: Class H + Retarder + Fluid Loss + Defoamer
ECP/DV Tool @ 6227'						
rod. tg 2	130	12.5	2.12	11	16	Lead: Class C + Gel + Retarder + Defoamer + Extender
	100	14.8	1.34	6.3	8	Tail: Class C + Retarder
iner	425	11.2	2.97	18	16	Class C + Salt + Gel + Fluid Loss + Retarder + Dispersant + Defoamer + Anti-Settling Agent

copy of cement test will be available on location at time of cement job providing pump times & compressive strengths.

Casing String	TOC	% Excess
Surface	0'	100%
Intermediate	0'	25%
Production	4730'	25%
Liner	11,000'	25%

Mewbourne Oil Company, Salado Draw 9/16 W1AP Fed Com #2H

Sec 9, T26S, R33E

SL: 330' FNL & 210' FEL, Sec 9

BHL: 100' FSL & 330' FEL, Sec 16

4. Pressure Control Equipment

Y	Variance: A variance is requested for use of a 5000 psi annular BOP with the 10,000 psi BOP stack. Please see attached description and procedure.
---	---

BOP installed and tested before drilling which hole?	Size?	System Rated WP	Type	✓	Tested to:
13-1/2"	13-5/8"	3M	Annular	X	1500#
			Blind Ram	X	3000#
			Pipe Ram	X	
			Double Ram		
			Other*		
9-7/8"	13-5/8"	10M	Annular	X	5000#
			Blind Ram	X	
			Pipe Ram	X	10,000#
			Double Ram		
			Other*		

\*Specify if additional ram is utilized.

BOP/BOPE will be tested by an independent service company to 250 psi low and the high pressure indicated above per Onshore Order 2 requirements. The System may be upgraded to a higher pressure but still tested to the working pressure listed in the table above. If the system is upgraded all the components installed will be functional and tested.

Pipe rams will be operationally checked each 24 hour period. Blind rams will be operationally checked on each trip out of the hole. These checks will be noted on the daily tour sheets. Other accessories to the BOP equipment will include a Kelly cock and floor safety valve (inside BOP) and choke lines and choke manifold. See attached schematics.

X	Formation integrity test will be performed per Onshore Order #2. On Exploratory wells or on that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.i.
Y	A variance is requested for the use of a flexible choke line from the BOP to Choke Manifold. See attached for specs and hydrostatic test chart.
N	Are anchors required by manufacturer?

**Mewbourne Oil Company, Salado Draw 9/16 W1AP Fed Com #2H**  
**Sec 9, T26S, R33E**  
**SL: 330' FNL & 210' FEL, Sec 9**  
**BHL: 100' FSL & 330' FEL, Sec 16**

Y	<p>A multibowl wellhead is being used. The BOP will be tested per Onshore Order #2 after installation on the surface casing which will cover testing requirements for a maximum of 30 days. If any seal subject to test pressure is broken the system must be tested.</p> <ul style="list-style-type: none"> <li>• Provide description here: See attached schematic.</li> </ul>
---	---

**5. Mud Program**

TVD		Type	Weight (ppg)	Viscosity	Water Loss
From	To				
0	1010	FW Gel	8.6-8.8	28-34	N/C
1010	4930	Saturated Brine	10.0	28-34	N/C
4930	11,900	Cut Brine	8.6-10.0	28-34	N/C
11,900	12,629	OBM	10.0-13.0	30-40	<10cc

Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept on location at all times.

What will be used to monitor the loss or gain of fluid?	Pason/PVT/Visual Monitoring
---	-----------------------------

**6. Logging and Testing Procedures**

Logging, Coring and Testing.	
X	Will run GR/CNL from KOP (12,000') to surface (horizontal well – vertical portion of hole). Stated logs run will be in the Completion Report and submitted to the BLM.
	No Logs are planned based on well control or offset log information.
	Drill stem test? If yes, explain
	Coring? If yes, explain

Additional logs planned	Interval
X	Gamma Ray
	Density
	CBL
	Mud log
	PEX

**7. Drilling Conditions**

Condition	Specify what type and where?
BH Pressure at deepest TVD	8537 psi
Abnormal Temperature	No

Mitigation measure for abnormal conditions. Describe. Lost circulation material/sweeps/mud scavengers in surface hole. Weighted mud for possible over-pressure in Wolfcamp formation.

Hydrogen Sulfide (H2S) monitors will be installed prior to drilling out the surface shoe. If H2S is detected in concentrations greater than 100 ppm, the operator will comply with the provisions of Onshore Oil and Gas Order #6. If Hydrogen Sulfide is encountered, measured values and formations will be provided to the BLM.	
	H2S is present
X	H2S Plan attached

**8. Other facets of operation**

Is this a walking operation? If yes, describe.  
 Will be pre-setting casing? If yes, describe.

- Attachments
- Directional Plan
  - Other, describe

**TUBULAR PARAMETERS**

Nominal OD, (inch)	5.500
Wall Thickness, (inch)	0.562
Pipe Grade	P110 HC
Drift	Standard

**PIPE BODY PROPERTIES**



PE Weight, (lbs/ft)	29.64
Nominal Weight, (lbs/ft)	29.70
Nominal ID, (inch)	4.376
Drift Diameter, (inch)	4.251
Nominal Pipe Body Area, (sq inch)	8.718
Yield Strength in Tension, (klbs)	959
Min. Internal Yield Pressure, (psi)	19 670
Collapse Pressure, (psi)	22 200

**CONNECTION PARAMETERS**

Connection OD (inch)	5.50
Connection ID, (inch)	4.373
Make-Up Loss, (inch)	5.040
Connection Critical Area, (sq inch)	4.886
Yield Strength in Tension, (klbs)	717
Yield Strength in Compression, (klbs)	618
Tension Efficiency	75%
Compression Efficiency	64%
Min. Internal Yield Pressure, (psi)	19 670
Collapse Pressure, (psi)	22 200
Uniaxial Bending (deg/100ft)	69.0



**MAKE-UP TORQUES**

Yield Torque, (ft-lb)	18 800
Minimum Make-Up Torque, (ft-lb)	10 600
Optimum Make-Up Torque, (ft-lb)	11 800
Maximum Make-Up Torque, (ft-lb)	13 000



NOTE: The content of this Technical Data Sheet is for general information only and does not guarantee performance or imply fitness for a particular purpose which only a competent drilling professional can determine considering the specific installation and operation parameters. This information supersedes all prior versions for this connection. Information that is printed or downloaded is no longer controlled by TMK and might not be the latest information. Anyone using the information herein does so at their own risk. To verify that you have the latest technical information, please contact PAO TMK Technical Sales in Russia (Tel: +7 (495) 775-16-00; Email: techsales@tmk-group.com) and TMK IPSCO in North America (Tel: +1 (281)949-1044; Email: techsales@tmk-ipso.com).

# Salado Draw 9/16 W1AP Fed Com #2H



# **Mewbourne Oil Company**

**Lea County, New Mexico NAD 83**

**Salado Draw 9/16 W1AP Fed Com #2H**

**Sec 9, T26S, R33E**

**SL: 330' FNL & 210' FEL, Sec 9**

**BHL: 100' FSL & 330' FEL, Sec 16**

**Plan: Design #1**

## **Standard Planning Report**

**27 September, 2018**

# Planning Report

**Database:** Hobbs  
**Company:** Mewbourne Oil Company  
**Project:** Lea County, New Mexico NAD 83  
**Site:** Salado Draw 9/16 W1AP Fed Com #2H  
**Well:** Sec 9, T26S, R33E  
**Wellbore:** BHL: 100' FSL & 330' FEL, Sec 16  
**Design:** Design #1

**Local Co-ordinate Reference:** Site Salado Draw 9/16 W1AP Fed Com #2H  
**TVD Reference:** WELL @ 3359.0usft (Original Well Elev)  
**MD Reference:** WELL @ 3359.0usft (Original Well Elev)  
**North Reference:** Grid  
**Survey Calculation Method:** Minimum Curvature

<b>Project</b> Lea County, New Mexico NAD 83	
<b>Map System:</b> US State Plane 1983	<b>System Datum:</b> Mean Sea Level
<b>Geo Datum:</b> North American Datum 1983	
<b>Map Zone:</b> New Mexico Eastern Zone	

<b>Site</b> Salado Draw 9/16 W1AP Fed Com #2H	
<b>Site Position:</b>	<b>Northing:</b> 387,987.00 usft <b>Latitude:</b> 32.0643537
<b>From:</b> Map	<b>Easting:</b> 777,986.00 usft <b>Longitude:</b> -103.5693976
<b>Position Uncertainty:</b> 0.0 usft	<b>Slot Radius:</b> 13-3/16 " <b>Grid Convergence:</b> 0.41 °

<b>Well</b> Sec 9, T26S, R33E	
<b>Well Position</b>	<b>+N/-S</b> 0.0 usft <b>Northing:</b> 387,987.00 usft <b>Latitude:</b> 32.0643537
	<b>+E/-W</b> 0.0 usft <b>Easting:</b> 777,986.00 usft <b>Longitude:</b> -103.5693976
<b>Position Uncertainty</b>	0.0 usft <b>Wellhead Elevation:</b> 3,359.0 usft <b>Ground Level:</b> 3,332.0 usft

<b>Wellbore</b> BHL: 100' FSL & 330' FEL, Sec 16					
<b>Magnetics</b>	<b>Model Name</b> IGRF2010	<b>Sample Date</b> 9/27/2018	<b>Declination</b> 6.67	<b>Dip Angle</b> 59.85	<b>Field Strength</b> 47,793
			(°)	(°)	(nT)

<b>Design</b> Design #1	
<b>Audit Notes:</b>	
<b>Version:</b>	<b>Phase:</b> PROTOTYPE <b>Tie On Depth:</b> 0.0
<b>Vertical Section:</b>	<b>Depth From (TVD)</b> 0.0 <b>+N/-S</b> 0.0 <b>+E/-W</b> 0.0 <b>Direction</b> 180.27
	(usft) (usft) (usft) (°)

<b>Plan Sections</b>										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	TFO (°)	Target
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.00	0.00	
5,000.0	0.00	0.00	5,000.0	0.0	0.0	0.00	0.00	0.00	0.00	
5,191.7	2.88	339.07	5,191.6	4.5	-1.7	1.50	1.50	0.00	339.07	
11,807.8	2.88	339.07	11,799.4	314.5	-120.3	0.00	0.00	0.00	0.00	
11,999.5	0.00	0.00	11,991.0	319.0	-122.0	1.50	-1.50	0.00	180.00	KOP: 10' FNL & 330' I
12,895.8	89.62	179.59	12,564.0	-250.2	-117.9	10.00	10.00	0.00	179.59	
22,779.1	89.62	179.59	12,629.0	-10,133.0	-47.0	0.00	0.00	0.00	0.00	BHL: 100' FSL & 330'

Planning Report

Database:	Hobbs	Local Co-ordinate Reference:	Site Salado Draw 9/16 W1AP Fed Com #2H
Company:	Mewbourne Oil Company	TVD Reference:	WELL @ 3359.0usft (Original Well Elev)
Project:	Lea County, New Mexico NAD 83	MD Reference:	WELL @ 3359.0usft (Original Well Elev)
Site:	Salado Draw 9/16 W1AP Fed Com #2H	North Reference:	Grid
Well:	Sec 9, T26S, R33E	Survey Calculation Method:	Minimum Curvature
Wellbore:	BHL: 100' FSL & 330' FEL, Sec 16		
Design:	Design #1		

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N-S (usft)	+E-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
0.0	0.00	0.00	0.0	0.0	0.0	0.0	0.00	0.00	0.00	
<b>SL: 330' FNL &amp; 210' FEL, Sec 9</b>										
100.0	0.00	0.00	100.0	0.0	0.0	0.0	0.00	0.00	0.00	
200.0	0.00	0.00	200.0	0.0	0.0	0.0	0.00	0.00	0.00	
300.0	0.00	0.00	300.0	0.0	0.0	0.0	0.00	0.00	0.00	
400.0	0.00	0.00	400.0	0.0	0.0	0.0	0.00	0.00	0.00	
500.0	0.00	0.00	500.0	0.0	0.0	0.0	0.00	0.00	0.00	
600.0	0.00	0.00	600.0	0.0	0.0	0.0	0.00	0.00	0.00	
700.0	0.00	0.00	700.0	0.0	0.0	0.0	0.00	0.00	0.00	
800.0	0.00	0.00	800.0	0.0	0.0	0.0	0.00	0.00	0.00	
900.0	0.00	0.00	900.0	0.0	0.0	0.0	0.00	0.00	0.00	
1,000.0	0.00	0.00	1,000.0	0.0	0.0	0.0	0.00	0.00	0.00	
1,100.0	0.00	0.00	1,100.0	0.0	0.0	0.0	0.00	0.00	0.00	
1,200.0	0.00	0.00	1,200.0	0.0	0.0	0.0	0.00	0.00	0.00	
1,300.0	0.00	0.00	1,300.0	0.0	0.0	0.0	0.00	0.00	0.00	
1,400.0	0.00	0.00	1,400.0	0.0	0.0	0.0	0.00	0.00	0.00	
1,500.0	0.00	0.00	1,500.0	0.0	0.0	0.0	0.00	0.00	0.00	
1,600.0	0.00	0.00	1,600.0	0.0	0.0	0.0	0.00	0.00	0.00	
1,700.0	0.00	0.00	1,700.0	0.0	0.0	0.0	0.00	0.00	0.00	
1,800.0	0.00	0.00	1,800.0	0.0	0.0	0.0	0.00	0.00	0.00	
1,900.0	0.00	0.00	1,900.0	0.0	0.0	0.0	0.00	0.00	0.00	
2,000.0	0.00	0.00	2,000.0	0.0	0.0	0.0	0.00	0.00	0.00	
2,100.0	0.00	0.00	2,100.0	0.0	0.0	0.0	0.00	0.00	0.00	
2,200.0	0.00	0.00	2,200.0	0.0	0.0	0.0	0.00	0.00	0.00	
2,300.0	0.00	0.00	2,300.0	0.0	0.0	0.0	0.00	0.00	0.00	
2,400.0	0.00	0.00	2,400.0	0.0	0.0	0.0	0.00	0.00	0.00	
2,500.0	0.00	0.00	2,500.0	0.0	0.0	0.0	0.00	0.00	0.00	
2,600.0	0.00	0.00	2,600.0	0.0	0.0	0.0	0.00	0.00	0.00	
2,700.0	0.00	0.00	2,700.0	0.0	0.0	0.0	0.00	0.00	0.00	
2,800.0	0.00	0.00	2,800.0	0.0	0.0	0.0	0.00	0.00	0.00	
2,900.0	0.00	0.00	2,900.0	0.0	0.0	0.0	0.00	0.00	0.00	
3,000.0	0.00	0.00	3,000.0	0.0	0.0	0.0	0.00	0.00	0.00	
3,100.0	0.00	0.00	3,100.0	0.0	0.0	0.0	0.00	0.00	0.00	
3,200.0	0.00	0.00	3,200.0	0.0	0.0	0.0	0.00	0.00	0.00	
3,300.0	0.00	0.00	3,300.0	0.0	0.0	0.0	0.00	0.00	0.00	
3,400.0	0.00	0.00	3,400.0	0.0	0.0	0.0	0.00	0.00	0.00	
3,500.0	0.00	0.00	3,500.0	0.0	0.0	0.0	0.00	0.00	0.00	
3,600.0	0.00	0.00	3,600.0	0.0	0.0	0.0	0.00	0.00	0.00	
3,700.0	0.00	0.00	3,700.0	0.0	0.0	0.0	0.00	0.00	0.00	
3,800.0	0.00	0.00	3,800.0	0.0	0.0	0.0	0.00	0.00	0.00	
3,900.0	0.00	0.00	3,900.0	0.0	0.0	0.0	0.00	0.00	0.00	
4,000.0	0.00	0.00	4,000.0	0.0	0.0	0.0	0.00	0.00	0.00	
4,100.0	0.00	0.00	4,100.0	0.0	0.0	0.0	0.00	0.00	0.00	
4,200.0	0.00	0.00	4,200.0	0.0	0.0	0.0	0.00	0.00	0.00	
4,300.0	0.00	0.00	4,300.0	0.0	0.0	0.0	0.00	0.00	0.00	
4,400.0	0.00	0.00	4,400.0	0.0	0.0	0.0	0.00	0.00	0.00	
4,500.0	0.00	0.00	4,500.0	0.0	0.0	0.0	0.00	0.00	0.00	
4,600.0	0.00	0.00	4,600.0	0.0	0.0	0.0	0.00	0.00	0.00	
4,700.0	0.00	0.00	4,700.0	0.0	0.0	0.0	0.00	0.00	0.00	
4,800.0	0.00	0.00	4,800.0	0.0	0.0	0.0	0.00	0.00	0.00	
4,900.0	0.00	0.00	4,900.0	0.0	0.0	0.0	0.00	0.00	0.00	
5,000.0	0.00	0.00	5,000.0	0.0	0.0	0.0	0.00	0.00	0.00	
5,100.0	1.50	339.07	5,100.0	1.2	-0.5	-1.2	1.50	1.50	0.00	
5,191.7	2.88	339.07	5,191.6	4.5	-1.7	-4.5	1.50	1.50	0.00	

Planning Report

<b>Database:</b>	Hobbs	<b>Local Co-ordinate Reference:</b>	Site Salado Draw 9/16 W1AP Fed Com #2H
<b>Company:</b>	Mewbourne Oil Company	<b>TVD Reference:</b>	WELL @ 3359.0usft (Original Well Elev)
<b>Project:</b>	Lea County, New Mexico NAD 83	<b>MD Reference:</b>	WELL @ 3359.0usft (Original Well Elev)
<b>Site:</b>	Salado Draw 9/16 W1AP Fed Com #2H	<b>North Reference:</b>	Grid
<b>Well:</b>	Sec 9, T26S, R33E	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	BHL: 100' FSL & 330' FEL, Sec 16		
<b>Design:</b>	Design #1		

Planned Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
5,200.0	2.88	339.07	5,199.9	4.9	-1.9	-4.9	0.00	0.00	0.00	
5,300.0	2.88	339.07	5,299.8	9.6	-3.7	-9.5	0.00	0.00	0.00	
5,400.0	2.88	339.07	5,399.7	14.3	-5.5	-14.2	0.00	0.00	0.00	
5,500.0	2.88	339.07	5,499.5	18.9	-7.2	-18.9	0.00	0.00	0.00	
5,600.0	2.88	339.07	5,599.4	23.6	-9.0	-23.6	0.00	0.00	0.00	
5,700.0	2.88	339.07	5,699.3	28.3	-10.8	-28.3	0.00	0.00	0.00	
5,800.0	2.88	339.07	5,799.2	33.0	-12.6	-32.9	0.00	0.00	0.00	
5,900.0	2.88	339.07	5,899.0	37.7	-14.4	-37.6	0.00	0.00	0.00	
6,000.0	2.88	339.07	5,998.9	42.4	-16.2	-42.3	0.00	0.00	0.00	
6,100.0	2.88	339.07	6,098.8	47.1	-18.0	-47.0	0.00	0.00	0.00	
6,200.0	2.88	339.07	6,198.6	51.7	-19.8	-51.6	0.00	0.00	0.00	
6,300.0	2.88	339.07	6,298.5	56.4	-21.6	-56.3	0.00	0.00	0.00	
6,400.0	2.88	339.07	6,398.4	61.1	-23.4	-61.0	0.00	0.00	0.00	
6,500.0	2.88	339.07	6,498.3	65.8	-25.2	-65.7	0.00	0.00	0.00	
6,600.0	2.88	339.07	6,598.1	70.5	-27.0	-70.4	0.00	0.00	0.00	
6,700.0	2.88	339.07	6,698.0	75.2	-28.7	-75.0	0.00	0.00	0.00	
6,800.0	2.88	339.07	6,797.9	79.9	-30.5	-79.7	0.00	0.00	0.00	
6,900.0	2.88	339.07	6,897.8	84.5	-32.3	-84.4	0.00	0.00	0.00	
7,000.0	2.88	339.07	6,997.6	89.2	-34.1	-89.1	0.00	0.00	0.00	
7,100.0	2.88	339.07	7,097.5	93.9	-35.9	-93.7	0.00	0.00	0.00	
7,200.0	2.88	339.07	7,197.4	98.6	-37.7	-98.4	0.00	0.00	0.00	
7,300.0	2.88	339.07	7,297.3	103.3	-39.5	-103.1	0.00	0.00	0.00	
7,400.0	2.88	339.07	7,397.1	108.0	-41.3	-107.8	0.00	0.00	0.00	
7,500.0	2.88	339.07	7,497.0	112.7	-43.1	-112.5	0.00	0.00	0.00	
7,600.0	2.88	339.07	7,596.9	117.3	-44.9	-117.1	0.00	0.00	0.00	
7,700.0	2.88	339.07	7,696.8	122.0	-46.7	-121.8	0.00	0.00	0.00	
7,800.0	2.88	339.07	7,796.6	126.7	-48.5	-126.5	0.00	0.00	0.00	
7,900.0	2.88	339.07	7,896.5	131.4	-50.3	-131.2	0.00	0.00	0.00	
8,000.0	2.88	339.07	7,996.4	136.1	-52.0	-135.8	0.00	0.00	0.00	
8,100.0	2.88	339.07	8,096.3	140.8	-53.8	-140.5	0.00	0.00	0.00	
8,200.0	2.88	339.07	8,196.1	145.5	-55.6	-145.2	0.00	0.00	0.00	
8,300.0	2.88	339.07	8,296.0	150.1	-57.4	-149.9	0.00	0.00	0.00	
8,400.0	2.88	339.07	8,395.9	154.8	-59.2	-154.5	0.00	0.00	0.00	
8,500.0	2.88	339.07	8,495.8	159.5	-61.0	-159.2	0.00	0.00	0.00	
8,600.0	2.88	339.07	8,595.6	164.2	-62.8	-163.9	0.00	0.00	0.00	
8,700.0	2.88	339.07	8,695.5	168.9	-64.6	-168.6	0.00	0.00	0.00	
8,800.0	2.88	339.07	8,795.4	173.6	-66.4	-173.3	0.00	0.00	0.00	
8,900.0	2.88	339.07	8,895.2	178.3	-68.2	-177.9	0.00	0.00	0.00	
9,000.0	2.88	339.07	8,995.1	182.9	-70.0	-182.6	0.00	0.00	0.00	
9,100.0	2.88	339.07	9,095.0	187.6	-71.8	-187.3	0.00	0.00	0.00	
9,200.0	2.88	339.07	9,194.9	192.3	-73.5	-192.0	0.00	0.00	0.00	
9,300.0	2.88	339.07	9,294.7	197.0	-75.3	-196.6	0.00	0.00	0.00	
9,400.0	2.88	339.07	9,394.6	201.7	-77.1	-201.3	0.00	0.00	0.00	
9,500.0	2.88	339.07	9,494.5	206.4	-78.9	-206.0	0.00	0.00	0.00	
9,600.0	2.88	339.07	9,594.4	211.1	-80.7	-210.7	0.00	0.00	0.00	
9,700.0	2.88	339.07	9,694.2	215.7	-82.5	-215.4	0.00	0.00	0.00	
9,800.0	2.88	339.07	9,794.1	220.4	-84.3	-220.0	0.00	0.00	0.00	
9,900.0	2.88	339.07	9,894.0	225.1	-86.1	-224.7	0.00	0.00	0.00	
10,000.0	2.88	339.07	9,993.9	229.8	-87.9	-229.4	0.00	0.00	0.00	
10,100.0	2.88	339.07	10,093.7	234.5	-89.7	-234.1	0.00	0.00	0.00	
10,200.0	2.88	339.07	10,193.6	239.2	-91.5	-238.7	0.00	0.00	0.00	
10,300.0	2.88	339.07	10,293.5	243.9	-93.3	-243.4	0.00	0.00	0.00	
10,400.0	2.88	339.07	10,393.4	248.5	-95.1	-248.1	0.00	0.00	0.00	
10,500.0	2.88	339.07	10,493.2	253.2	-96.8	-252.8	0.00	0.00	0.00	

Planning Report

Database: Hobbs  
 Company: Mewbourne Oil Company  
 Project: Lea County, New Mexico NAD 83  
 Site: Salado Draw 9/16 W1AP Fed Com #2H  
 Well: Sec 9, T26S, R33E  
 Wellbore: BHL: 100' FSL & 330' FEL, Sec 16  
 Design: Design #1

Local Co-ordinate Reference:  
 TVD Reference:  
 MD Reference:  
 North Reference:  
 Survey Calculation Method:

Site Salado Draw 9/16 W1AP Fed Com #2H  
 WELL @ 3359.0usft (Original Well Elev)  
 WELL @ 3359.0usft (Original Well Elev)  
 Grid  
 Minimum Curvature

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
10,600.0	2.88	339.07	10,593.1	257.9	-98.6	-257.5	0.00	0.00	0.00
10,700.0	2.88	339.07	10,693.0	262.6	-100.4	-262.1	0.00	0.00	0.00
10,800.0	2.88	339.07	10,792.9	267.3	-102.2	-266.8	0.00	0.00	0.00
10,900.0	2.88	339.07	10,892.7	272.0	-104.0	-271.5	0.00	0.00	0.00
11,000.0	2.88	339.07	10,992.6	276.7	-105.8	-276.2	0.00	0.00	0.00
11,100.0	2.88	339.07	11,092.5	281.3	-107.6	-280.8	0.00	0.00	0.00
11,200.0	2.88	339.07	11,192.4	286.0	-109.4	-285.5	0.00	0.00	0.00
11,300.0	2.88	339.07	11,292.2	290.7	-111.2	-290.2	0.00	0.00	0.00
11,400.0	2.88	339.07	11,392.1	295.4	-113.0	-294.9	0.00	0.00	0.00
11,500.0	2.88	339.07	11,492.0	300.1	-114.8	-299.5	0.00	0.00	0.00
11,600.0	2.88	339.07	11,591.9	304.8	-116.6	-304.2	0.00	0.00	0.00
11,700.0	2.88	339.07	11,691.7	309.5	-118.3	-308.9	0.00	0.00	0.00
11,800.0	2.88	339.07	11,791.6	314.1	-120.1	-313.6	0.00	0.00	0.00
11,807.8	2.88	339.07	11,799.4	314.5	-120.3	-313.9	0.00	0.00	0.00
11,900.0	1.49	339.07	11,891.5	317.8	-121.5	-317.2	1.50	-1.50	0.00
11,999.5	0.00	0.00	11,991.0	319.0	-122.0	-318.4	1.50	-1.50	0.00
<b>KOP: 10' FNL &amp; 330' FEL, Sec 9</b>									
12,000.0	0.05	179.59	11,991.5	319.0	-122.0	-318.4	10.00	10.00	0.00
12,100.0	10.05	179.59	12,091.0	310.2	-121.9	-309.6	10.00	10.00	0.00
12,200.0	20.05	179.59	12,187.4	284.3	-121.8	-283.7	10.00	10.00	0.00
12,300.0	30.05	179.59	12,277.9	242.0	-121.4	-241.4	10.00	10.00	0.00
12,323.2	32.36	179.59	12,297.7	230.0	-121.4	-229.4	10.00	10.00	0.00
<b>FTP: 100' FNL &amp; 330' FEL, Sec 9</b>									
12,400.0	40.05	179.59	12,359.7	184.7	-121.0	-184.1	10.00	10.00	0.00
12,500.0	50.05	179.59	12,430.3	114.0	-120.5	-113.4	10.00	10.00	0.00
12,600.0	60.05	179.59	12,487.5	32.1	-119.9	-31.6	10.00	10.00	0.00
12,700.0	70.05	179.59	12,529.6	-58.4	-119.3	59.0	10.00	10.00	0.00
12,800.0	80.04	179.59	12,555.4	-154.9	-118.6	155.5	10.00	10.00	0.00
12,895.8	89.62	179.59	12,564.0	-250.2	-117.9	250.7	10.00	10.00	0.00
<b>LP: 580' FNL &amp; 330' FEL, Sec 9</b>									
12,900.0	89.62	179.59	12,564.0	-254.4	-117.9	254.9	0.00	0.00	0.00
13,000.0	89.62	179.59	12,564.7	-354.4	-117.2	354.9	0.00	0.00	0.00
13,100.0	89.62	179.59	12,565.3	-454.4	-116.5	454.9	0.00	0.00	0.00
13,200.0	89.62	179.59	12,566.0	-554.4	-115.7	554.9	0.00	0.00	0.00
13,300.0	89.62	179.59	12,566.7	-654.4	-115.0	654.9	0.00	0.00	0.00
13,400.0	89.62	179.59	12,567.3	-754.4	-114.3	754.9	0.00	0.00	0.00
13,500.0	89.62	179.59	12,568.0	-854.4	-113.6	854.9	0.00	0.00	0.00
13,600.0	89.62	179.59	12,568.6	-954.4	-112.9	954.9	0.00	0.00	0.00
13,700.0	89.62	179.59	12,569.3	-1,054.4	-112.1	1,054.9	0.00	0.00	0.00
13,800.0	89.62	179.59	12,569.9	-1,154.4	-111.4	1,154.9	0.00	0.00	0.00
13,900.0	89.62	179.59	12,570.6	-1,254.4	-110.7	1,254.9	0.00	0.00	0.00
14,000.0	89.62	179.59	12,571.3	-1,354.4	-110.0	1,354.8	0.00	0.00	0.00
14,100.0	89.62	179.59	12,571.9	-1,454.3	-109.3	1,454.8	0.00	0.00	0.00
14,200.0	89.62	179.59	12,572.6	-1,554.3	-108.6	1,554.8	0.00	0.00	0.00
14,300.0	89.62	179.59	12,573.2	-1,654.3	-107.8	1,654.8	0.00	0.00	0.00
14,400.0	89.62	179.59	12,573.9	-1,754.3	-107.1	1,754.8	0.00	0.00	0.00
14,500.0	89.62	179.59	12,574.6	-1,854.3	-106.4	1,854.8	0.00	0.00	0.00
14,600.0	89.62	179.59	12,575.2	-1,954.3	-105.7	1,954.8	0.00	0.00	0.00
14,700.0	89.62	179.59	12,575.9	-2,054.3	-105.0	2,054.8	0.00	0.00	0.00
14,800.0	89.62	179.59	12,576.5	-2,154.3	-104.3	2,154.8	0.00	0.00	0.00
14,900.0	89.62	179.59	12,577.2	-2,254.3	-103.5	2,254.8	0.00	0.00	0.00
14,955.7	89.62	179.59	12,577.5	-2,310.0	-103.1	2,310.5	0.00	0.00	0.00
<b>PPP2: 2641' FSL &amp; 330' FEL, Sec 9</b>									

# Planning Report

<b>Database:</b>	Hobbs	<b>Local Co-ordinate Reference:</b>	Site Salado Draw 9/16 W1AP Fed Com #2H
<b>Company:</b>	Mewbourne Oil Company	<b>TVD Reference:</b>	WELL @ 3359.0usft (Original Well Elev)
<b>Project:</b>	Lea County, New Mexico NAD 83	<b>MD Reference:</b>	WELL @ 3359.0usft (Original Well Elev)
<b>Site:</b>	Salado Draw 9/16 W1AP Fed Com #2H	<b>North Reference:</b>	Grid
<b>Well:</b>	Sec 9, T26S, R33E	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	BHL: 100' FSL & 330' FEL, Sec 16		
<b>Design:</b>	Design #1		

Planned Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
15,000.0	89.62	179.59	12,577.8	-2,354.3	-102.8	2,354.8	0.00	0.00	0.00	
15,100.0	89.62	179.59	12,578.5	-2,454.3	-102.1	2,454.7	0.00	0.00	0.00	
15,200.0	89.62	179.59	12,579.2	-2,554.3	-101.4	2,554.7	0.00	0.00	0.00	
15,300.0	89.62	179.59	12,579.8	-2,654.3	-100.7	2,654.7	0.00	0.00	0.00	
15,400.0	89.62	179.59	12,580.5	-2,754.3	-99.9	2,754.7	0.00	0.00	0.00	
15,500.0	89.62	179.59	12,581.1	-2,854.3	-99.2	2,854.7	0.00	0.00	0.00	
15,600.0	89.62	179.59	12,581.8	-2,954.3	-98.5	2,954.7	0.00	0.00	0.00	
15,700.0	89.62	179.59	12,582.4	-3,054.3	-97.8	3,054.7	0.00	0.00	0.00	
15,800.0	89.62	179.59	12,583.1	-3,154.3	-97.1	3,154.7	0.00	0.00	0.00	
15,900.0	89.62	179.59	12,583.8	-3,254.3	-96.4	3,254.7	0.00	0.00	0.00	
16,000.0	89.62	179.59	12,584.4	-3,354.3	-95.6	3,354.7	0.00	0.00	0.00	
16,100.0	89.62	179.59	12,585.1	-3,454.3	-94.9	3,454.7	0.00	0.00	0.00	
16,200.0	89.62	179.59	12,585.7	-3,554.2	-94.2	3,554.6	0.00	0.00	0.00	
16,300.0	89.62	179.59	12,586.4	-3,654.2	-93.5	3,654.6	0.00	0.00	0.00	
16,400.0	89.62	179.59	12,587.0	-3,754.2	-92.8	3,754.6	0.00	0.00	0.00	
16,500.0	89.62	179.59	12,587.7	-3,854.2	-92.1	3,854.6	0.00	0.00	0.00	
16,600.0	89.62	179.59	12,588.4	-3,954.2	-91.3	3,954.6	0.00	0.00	0.00	
16,700.0	89.62	179.59	12,589.0	-4,054.2	-90.6	4,054.6	0.00	0.00	0.00	
16,800.0	89.62	179.59	12,589.7	-4,154.2	-89.9	4,154.6	0.00	0.00	0.00	
16,900.0	89.62	179.59	12,590.3	-4,254.2	-89.2	4,254.6	0.00	0.00	0.00	
17,000.0	89.62	179.59	12,591.0	-4,354.2	-88.5	4,354.6	0.00	0.00	0.00	
17,100.0	89.62	179.59	12,591.6	-4,454.2	-87.7	4,454.6	0.00	0.00	0.00	
17,200.0	89.62	179.59	12,592.3	-4,554.2	-87.0	4,554.6	0.00	0.00	0.00	
17,300.0	89.62	179.59	12,593.0	-4,654.2	-86.3	4,654.5	0.00	0.00	0.00	
17,400.0	89.62	179.59	12,593.6	-4,754.2	-85.6	4,754.5	0.00	0.00	0.00	
17,500.0	89.62	179.59	12,594.3	-4,854.2	-84.9	4,854.5	0.00	0.00	0.00	
17,600.0	89.62	179.59	12,594.9	-4,954.2	-84.2	4,954.5	0.00	0.00	0.00	
17,700.0	89.62	179.59	12,595.6	-5,054.2	-83.4	5,054.5	0.00	0.00	0.00	
17,800.0	89.62	179.59	12,596.3	-5,154.2	-82.7	5,154.5	0.00	0.00	0.00	
17,900.0	89.62	179.59	12,596.9	-5,254.2	-82.0	5,254.5	0.00	0.00	0.00	
18,000.0	89.62	179.59	12,597.6	-5,354.2	-81.3	5,354.5	0.00	0.00	0.00	
18,100.0	89.62	179.59	12,598.2	-5,454.2	-80.6	5,454.5	0.00	0.00	0.00	
18,200.0	89.62	179.59	12,598.9	-5,554.2	-79.9	5,554.5	0.00	0.00	0.00	
18,300.0	89.62	179.59	12,599.5	-5,654.1	-79.1	5,654.5	0.00	0.00	0.00	
18,400.0	89.62	179.59	12,600.2	-5,754.1	-78.4	5,754.4	0.00	0.00	0.00	
18,500.0	89.62	179.59	12,600.9	-5,854.1	-77.7	5,854.4	0.00	0.00	0.00	
18,600.0	89.62	179.59	12,601.5	-5,954.1	-77.0	5,954.4	0.00	0.00	0.00	
18,700.0	89.62	179.59	12,602.2	-6,054.1	-76.3	6,054.4	0.00	0.00	0.00	
18,800.0	89.62	179.59	12,602.8	-6,154.1	-75.6	6,154.4	0.00	0.00	0.00	
18,900.0	89.62	179.59	12,603.5	-6,254.1	-74.8	6,254.4	0.00	0.00	0.00	
19,000.0	89.62	179.59	12,604.1	-6,354.1	-74.1	6,354.4	0.00	0.00	0.00	
19,100.0	89.62	179.59	12,604.8	-6,454.1	-73.4	6,454.4	0.00	0.00	0.00	
19,200.0	89.62	179.59	12,605.5	-6,554.1	-72.7	6,554.4	0.00	0.00	0.00	
19,300.0	89.62	179.59	12,606.1	-6,654.1	-72.0	6,654.4	0.00	0.00	0.00	
19,400.0	89.62	179.59	12,606.8	-6,754.1	-71.2	6,754.4	0.00	0.00	0.00	
19,500.0	89.62	179.59	12,607.4	-6,854.1	-70.5	6,854.3	0.00	0.00	0.00	
19,600.0	89.62	179.59	12,608.1	-6,954.1	-69.8	6,954.3	0.00	0.00	0.00	
19,700.0	89.62	179.59	12,608.7	-7,054.1	-69.1	7,054.3	0.00	0.00	0.00	
19,800.0	89.62	179.59	12,609.4	-7,154.1	-68.4	7,154.3	0.00	0.00	0.00	
19,900.0	89.62	179.59	12,610.1	-7,254.1	-67.7	7,254.3	0.00	0.00	0.00	
20,000.0	89.62	179.59	12,610.7	-7,354.1	-66.9	7,354.3	0.00	0.00	0.00	
20,100.0	89.62	179.59	12,611.4	-7,454.1	-66.2	7,454.3	0.00	0.00	0.00	
20,200.0	89.62	179.59	12,612.0	-7,554.1	-65.5	7,554.3	0.00	0.00	0.00	
20,300.0	89.62	179.59	12,612.7	-7,654.1	-64.8	7,654.3	0.00	0.00	0.00	

Planning Report

<b>Database:</b>	Hobbs	<b>Local Co-ordinate Reference:</b>	Site Salado Draw 9/16 W1AP Fed Com #2H
<b>Company:</b>	Mewbourne Oil Company	<b>TVD Reference:</b>	WELL @ 3359.0usft (Original Well Elev)
<b>Project:</b>	Lea County, New Mexico NAD 83	<b>MD Reference:</b>	WELL @ 3359.0usft (Original Well Elev)
<b>Site:</b>	Salado Draw 9/16 W1AP Fed Com #2H	<b>North Reference:</b>	Grid
<b>Well:</b>	Sec 9, T26S, R33E	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	BHL: 100' FSL & 330' FEL, Sec 16		
<b>Design:</b>	Design #1		

Planned Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
20,400.0	89.62	179.59	12,613.4	-7,754.0	-64.1	7,754.3	0.00	0.00	0.00	
20,500.0	89.62	179.59	12,614.0	-7,854.0	-63.4	7,854.3	0.00	0.00	0.00	
20,600.0	89.62	179.59	12,614.7	-7,954.0	-62.6	7,954.2	0.00	0.00	0.00	
20,700.0	89.62	179.59	12,615.3	-8,054.0	-61.9	8,054.2	0.00	0.00	0.00	
20,800.0	89.62	179.59	12,616.0	-8,154.0	-61.2	8,154.2	0.00	0.00	0.00	
20,900.0	89.62	179.59	12,616.6	-8,254.0	-60.5	8,254.2	0.00	0.00	0.00	
21,000.0	89.62	179.59	12,617.3	-8,354.0	-59.8	8,354.2	0.00	0.00	0.00	
21,100.0	89.62	179.59	12,618.0	-8,454.0	-59.0	8,454.2	0.00	0.00	0.00	
21,200.0	89.62	179.59	12,618.6	-8,554.0	-58.3	8,554.2	0.00	0.00	0.00	
21,300.0	89.62	179.59	12,619.3	-8,654.0	-57.6	8,654.2	0.00	0.00	0.00	
21,400.0	89.62	179.59	12,619.9	-8,754.0	-56.9	8,754.2	0.00	0.00	0.00	
21,500.0	89.62	179.59	12,620.6	-8,854.0	-56.2	8,854.2	0.00	0.00	0.00	
21,600.0	89.62	179.59	12,621.2	-8,954.0	-55.5	8,954.2	0.00	0.00	0.00	
21,700.0	89.62	179.59	12,621.9	-9,054.0	-54.7	9,054.1	0.00	0.00	0.00	
21,800.0	89.62	179.59	12,622.6	-9,154.0	-54.0	9,154.1	0.00	0.00	0.00	
21,900.0	89.62	179.59	12,623.2	-9,254.0	-53.3	9,254.1	0.00	0.00	0.00	
22,000.0	89.62	179.59	12,623.9	-9,354.0	-52.6	9,354.1	0.00	0.00	0.00	
22,100.0	89.62	179.59	12,624.5	-9,454.0	-51.9	9,454.1	0.00	0.00	0.00	
22,200.0	89.62	179.59	12,625.2	-9,554.0	-51.2	9,554.1	0.00	0.00	0.00	
22,300.0	89.62	179.59	12,625.8	-9,654.0	-50.4	9,654.1	0.00	0.00	0.00	
22,400.0	89.62	179.59	12,626.5	-9,754.0	-49.7	9,754.1	0.00	0.00	0.00	
22,500.0	89.62	179.59	12,627.2	-9,853.9	-49.0	9,854.1	0.00	0.00	0.00	
22,600.0	89.62	179.59	12,627.8	-9,953.9	-48.3	9,954.1	0.00	0.00	0.00	
22,700.0	89.62	179.59	12,628.5	-10,053.9	-47.6	10,054.1	0.00	0.00	0.00	
22,779.1	89.62	179.59	12,629.0	-10,133.0	-47.0	10,133.1	0.00	0.00	0.00	

BHL: 100' FSL & 330' FEL, Sec 16

Design Targets										
Target Name	Dip Angle (°)	Dip Dir. (°)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude	
SL: 330' FNL & 210' FEL - hit/miss target - Shape - plan hits target center - Point	0.00	0.00	0.0	0.0	0.0	387,987.00	777,986.00	32.0643537	-103.5693976	
KOP: 10' FNL & 330' FE - plan hits target center - Point	0.00	0.00	11,991.0	319.0	-122.0	388,306.00	777,864.00	32.0652329	-103.5697841	
FTP: 100' FNL & 330' FE - plan hits target center - Point	0.00	0.00	12,297.7	230.0	-121.4	388,217.00	777,864.64	32.0649882	-103.5697841	
LP: 580' FNL & 330' FEL - plan hits target center - Point	0.00	0.00	12,564.0	-250.2	-117.9	387,736.80	777,868.10	32.0636682	-103.5697838	
PPP2: 2641' FSL & 330' - plan hits target center - Point	0.00	0.00	12,577.5	-2,310.0	-103.1	385,677.00	777,882.86	32.0580061	-103.5697832	
BHL: 100' FSL & 330' FE - plan hits target center - Point	0.00	0.00	12,629.0	-10,133.0	-47.0	377,854.00	777,939.00	32.0365016	-103.5697806	


# Planning Report

<b>Database:</b>	Hobbs	<b>Local Co-ordinate Reference:</b>	Site Salado Draw 9/16 W1AP Fed Com #2H
<b>Company:</b>	Mewbourne Oil Company	<b>TVD Reference:</b>	WELL @ 3359.0usft (Original Well Elev)
<b>Project:</b>	Lea County, New Mexico NAD 83	<b>MD Reference:</b>	WELL @ 3359.0usft (Original Well Elev)
<b>Site:</b>	Salado Draw 9/16 W1AP Fed Com #2H	<b>North Reference:</b>	Grid
<b>Well:</b>	Sec 9, T26S, R33E	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	BHL: 100' FSL & 330' FEL, Sec 16		
<b>Design:</b>	Design #1		

**NOTE** DRAFT Publication is for Review ONLY. NOT approved for System Installation. NOT approved for field usage. NOT approved for distribution. If you obtain a DRAFT copy, it is your responsibility to verify SAP revision level or contact Houston Engineering to ensure document has been approved and released.

# RUNNING PROCEDURE

## Mewbourne Oil Co



**Publication Status Note:**

Draft A sent to John Cortinas for review. RA 04/29/17

Surface Systems Publication



13-5/8" 10K MN-DS System  
13-3/8" x 9-5/8" x 7" Casing Program

RP-003815  
Rev 01 Draft A

## 5,000 PSI Annular BOP Variance Request

Mewbourne Oil Company request a variance to use a 5000 psi annular BOP with a 10,000 psi BOP stack. The component and compatibility tables along with the general well control plans demonstrate how the 5000 psi annular BOP will be protected from pressures that exceed its rated working pressure (RWP). The pressure at which the control of the wellbore is transferred from the annular preventer to another available preventer will not exceed 3500 psi (70% of the RWP of the 5000 psi annular BOP).

### 1. Component and Preventer Compatibility Tables

The tables below outline the tubulars and the compatible preventers in use. This table, combined with the drilling fluid, documents that two barriers to flow will be maintained at all times.

<b>12-1/4" Intermediate Hole Section 10M psi Requirement</b>					
Component	OD	Primary Preventer	RWP	Alternate Preventer(s)	RWP
Drillpipe	5.000" or 4.500"	Annular	5M	Upper 3.5"-5.5" VBR Lower 3.5"-5.5" VBR	10M 10M
HWDP	5.000" or 4.500"	Annular	5M	Upper 3.5"-5.5" VBR Lower 3.5"-5.5" VBR	10M 10M
Jars	6.500"	Annular	5M	-	-
DCs and MWD tools	6.500"- 8.000"	Annular	5M	-	-
Mud Motor	8.000"- 9.625"	Annular	5M	-	-
Intermediate Casing	10.75"	Annular	5M	-	-
Open-Hole	-	Blind Rams	10M	-	-

<b>9-7/8" Production Hole Section 10M psi Requirement</b>					
Component	OD	Primary Preventer	RWP	Alternate Preventer(s)	RWP
Drillpipe	5.000" or 4.500"	Annular	5M	Upper 3.5"-5.5" VBR Lower 3.5"-5.5" VBR	10M 10M
HWDP	5.000" or 4.500"	Annular	5M	Upper 3.5"-5.5" VBR Lower 3.5"-5.5" VBR	10M 10M
Jars	6.500"	Annular	5M	-	-
DCs and MWD tools	6.500"- 8.000"	Annular	5M	-	-
Mud Motor	6.750"- 8.000"	Annular	5M	-	-
Production Casing	7.625"	Annular	5M	-	-

Open-Hole	-	Blind Rams	10M	-	-
-----------	---	------------	-----	---	---

6-1/8" Lateral Hole Section 10M psi Requirement					
Component	OD	Primary Preventer	RWP	Alternate Preventer(s)	RWP
Drillpipe	4.500"	Annular	5M	Upper 3.5"-5.5" VBR Lower 3.5"-5.5" VBR	10M 10M
HWDP	4.500"	Annular	5M	Upper 3.5"-5.5" VBR Lower 3.5"-5.5" VBR	10M 10M
DCs and MWD tools	4.750"- 5.500"	Annular	5M	Upper 3.5"-5.5" VBR Lower 3.5"-5.5" VBR	10M 10M
Mud Motor	4.750"- 5.500"	Annular	5M	Upper 3.5"-5.5" VBR Lower 3.5"-5.5" VBR	10M 10M
Production Casing	5.500"	Annular	5M	Upper 3.5"-5.5" VBR Upper 3.5"-5.5" VBR	10M 10M
Open-Hole	-	Blind Rams	10M	-	-

VBR = Variable Bore Ram

## 2. Well Control Procedures

Below are the minimal high-level tasks prescribed to assure a proper shut-in while drilling, tripping, running casing, pipe out of the hole (open hole), and moving the BHA through the BOPs. At least one well control drill will be performed weekly per crew to demonstrate compliance with the procedure and well control plan. The well control drill will be recorded in the daily drilling log. The type of drill will be determined by the ongoing operations, but reasonable attempts will be made to vary the type of drill conducted (pit, trip, open hole, choke, etc.). This well control plan will be available for review by rig personnel in the Mewbourne Oil Company drilling supervisor's office on location and on the rig floor. All BOP equipment will be tested as per Onshore O&G Order No. 2 with the exception of the 5000 psi annular which will be tested to 70% of its RWP.

### General Procedure While Drilling

1. Sound alarm (alert crew)
2. Space out drill string
3. Shut down pumps (stop pumps and rotary)
4. Shut-in well (uppermost applicable BOP, typically annular preventer, first. HCR & choke will already be in the closed position.)

5. Confirm shut-in
6. Notify toolpusher/company representative
7. Read and record the following:
  - a. SIDPP & SICP
  - b. Pit gain
  - c. Time
8. Regroup and identify forward plan
9. If pressure has built or is anticipated during the kill to reach 70% or greater of the RWP of the annular preventer, confirm spacing and close the upper variable bore rams.

#### General Procedure While Tripping

1. Sound alarm (alert crew)
2. Stab full-opening safety valve & close
3. Space out drill string
4. Shut-in well (uppermost applicable BOP, typically annular preventer, first. HCR & choke will already be in the closed position.)
5. Confirm shut-in
6. Notify toolpusher/company representative
7. Read and record the following:
  - a. SIDPP & SICP
  - b. Pit gain
  - c. Time
8. Regroup and identify forward plan
9. If pressure has built or is anticipated during the kill to reach 70% of the RWP of the annular preventer, confirm spacing and close the upper variable bore rams.

#### General Procedure While Running Production Casing

1. Sound alarm (alert crew)

2. Stab crossover and full-opening safety valve and close
3. Space out string
4. Shut-in well (uppermost applicable BOP, typically annular preventer, first. HCR & choke will already be in the closed position.)
5. Confirm shut-in
6. Notify toolpusher/company representative
7. Read and record the following:
  - a. SIDPP & SICP
  - b. Pit gain
  - c. Time
8. Regroup and identify forward plan
9. If pressure has built or is anticipated during the kill to reach 70% or greater of the RWP of the annular preventer, confirm spacing and close the upper variable bore rams.

#### General Procedure With No Pipe In Hole (Open Hole)

1. Sound alarm (alert crew)
2. Shut-in with blind rams (HCR & choke will already be in the closed position)
3. Confirm shut-in
4. Notify toolpusher/company representative
5. Read and record the following:
  - a. SICP
  - b. Pit gain
  - c. Time
6. Regroup and identify forward plan

#### General Procedures While Pulling BHA Through Stack

1. PRIOR to pulling last joint of drillpipe through stack:
  - a. Perform flow check. If flowing, continue to (b).
  - b. Sound alarm (alert crew)
  - c. Stab full-opening safety valve and close
  - d. Space out drill string with tool joint just beneath the upper variable bore rams
  - e. Shut-in using upper variable bore rams (HCR & choke will already be in the closed position)
  - f. Confirm shut-in
  - g. Notify toolpusher/company representative
  - h. Read and record the following:
    - i. SIDPP & SICP
    - ii. Pit gain
    - iii. Time
  - i. Regroup and identify forward plan
2. With BHA in the stack and compatible ram preventer and pipe combination immediately available:
  - a. Sound alarm (alert crew)
  - b. Stab crossover and full-opening safety valve and close
  - c. Space out drill string with upset just beneath the upper variable bore rams
  - d. Shut-in using upper variable bore rams (HCR & choke will already be in the closed position)
  - e. Confirm shut-in
  - f. Notify toolpusher/company representative
  - g. Read and record the following:
    - i. SIDPP & SICP
    - ii. Pit gain

- iii. Time
  - h. Regroup and identify forward plan
3. With BHA in the stack and NO compatible ram preventer and pipe combination immediately available:
- a. Sound alarm (alert crew)
  - b. If possible, pull string clear of the stack and follow "Open Hole" procedure.
  - c. If impossible to pull string clear of the stack:
  - d. Stab crossover, make up one joint/stand of drillpipe and full-opening safety valve and close
  - e. Space out drill string with tooljoint just beneath the upper variable bore ram
  - f. Shut-in using upper variable bore ram (HCR & choke will already be in the closed position)
  - g. Confirm shut-in
  - h. Notify toolpusher/company representative
  - i. Read and record the following:
    - i. SIDPP & SICP
    - ii. Pit gain
    - iii. Time
  - j. Regroup and identify forward plan


**Mewbourne Oil Company, Salado Draw 9/16 W1AP Fed Com #2H**

**Sec 9, T26S, R32E**

**SL: 330' FNL & 210' FEL, Sec 9**

**BHL: 100' FSL & 330' FEL, Sec 16**

Mewbourne Oil Co. requests approval to batch drill the Salado Draw 9/16 W1AP Fed Com #2H and Salado Draw 9/16 W0AP Fed Com #3H in the sequence depicted below.



- Surface, Production & Intermediate Hole:
  1. Drill 17-1/2" surface hole with fresh water to planned casing set depth.
  2. Run casing as stated by approved APD, land out wellhead, and cement.
  3. N/U and test 13-5/8" BOPE to 250 psi / 5,000 psi.
  4. Test casing to required pressure. Drill out shoe and 10' of new formation. Perform FIT.
  5. Drill 12-1/4" hole to planned casing set depth.
  6. Run casing as stated by approved APD, land out hanger and cement.
  7. Test casing to required pressure. Drill out shoe and 10' of new formation. Perform FIT.
  8. Drill <sup>9 7/8</sup>~~8-3/4~~" vertical section and curve as stated by approved APD.
  9. Run casing as stated by approved APD, land out hanger and cement.
  10. Secure with wellhead cover, walk rig to Salado Draw 9/16 W0AP Fed Com #3H and repeat Steps 1-9.

**Mewbourne Oil Company, Salado Draw 9/16 W1AP Fed Com #2H**

**Sec 9, T26S, R32E**

**SL: 330' FNL & 210' FEL, Sec 9**

**BHL: 100' FSL & 330' FEL, Sec 16**

- Lateral:
  1. Test casing to required pressure. Drill out shoe and 10' of new formation. Perform FIT.
  2. Drill 6-1/8" lateral as stated by approved APD.
  3. Run liner as stated by approved APD, cement, set liner hanger and secure with wellhead cover.
  4. Walk rig to Salado Draw 9/16 W1AP Fed Com #2H.
  5. N/U and test 13-5/8" BOPE to 250 psi / 5000 psi.
  6. Repeat Steps 1-3.

## PECOS DISTRICT DRILLING CONDITIONS OF APPROVAL

<b>OPERATOR'S NAME:</b>	Mewbourne Oil Company
<b>LEASE NO.:</b>	NMNM0000127A
<b>WELL NAME &amp; NO.:</b>	2H-Salado Draw 9/16 W1AP Fed Com
<b>SURFACE HOLE FOOTAGE:</b>	330'/N & 210'/E
<b>BOTTOM HOLE FOOTAGE:</b>	100'/S & 330'/E; Sec. 16
<b>LOCATION:</b>	Section 9, T.26 S., R.33 E., NMPM
<b>COUNTY:</b>	Lea County, New Mexico

COA

**All COA still apply expect the following:**

H2S	<input checked="" type="radio"/> Yes	<input type="radio"/> No	
Potash	<input checked="" type="radio"/> None	<input type="radio"/> Secretary	<input type="radio"/> R-111-P
Cave/Karst Potential	<input type="radio"/> Low	<input checked="" type="radio"/> Medium	<input type="radio"/> High
Variance	<input type="radio"/> None	<input checked="" type="radio"/> Flex Hose	<input type="radio"/> Other
Wellhead	<input type="radio"/> Conventional	<input checked="" type="radio"/> Multibowl	<input type="radio"/> Both
Other	<input type="checkbox"/> 4 String Area	<input type="checkbox"/> Capitan Reef	<input type="checkbox"/> WIPP

### A. Hydrogen Sulfide

A Hydrogen Sulfide (H2S) Drilling Plan shall be activated 500 feet prior to drilling into the **Delaware** formation. As a result, the Hydrogen Sulfide area must meet Onshore Order 6 requirements, which includes equipment and personnel/public protection items. If Hydrogen Sulfide is encountered, please provide measured values and formations to the BLM.

### B. CASING

1. The ~~13-3/8~~<sup>16</sup> inch surface casing shall be set at approximately 1010 feet (a minimum of 25 feet into the Rustler Anhydrite and above the salt) and cemented to the surface.
  - a. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with surface log readout will be used or a cement bond log shall be run to verify the top of the cement. Temperature survey will be run a minimum of six hours after pumping cement and ideally between 8-10 hours after completing the cement job.
  - b. Wait on cement (WOC) time for a primary cement job will be a minimum of **8 hours** or 500 pounds compressive strength, whichever is greater. (This is to include the lead cement)
  - c. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength,

whichever is greater.

- d. If cement falls back, remedial cementing will be done prior to drilling out that string.
2. The minimum required fill of cement behind the 10 3/4 inch 1<sup>st</sup> intermediate is:
    - Cement to surface. If cement does not circulate see B.1.a, c-d above. **Additional cement maybe required. Excess calculates to 24%.**
    - ❖ In Medium/High Cave/Karst Areas if cement does not circulate to surface on the first two casing strings , the cement on the 3rd casing string must come to surface.
- 96
3. The minimum required fill of cement behind the 7-5/8 inch 2<sup>nd</sup> intermediate casing is:

Operator has proposed a DV tool, the depth may be adjusted as long as the cement is changed proportionally. The DV tool may be cancelled if cement circulates to surface on the first stage.

    - a. First stage to DV tool: Cement to circulate. If cement does not circulate off the DV tool, contact the appropriate BLM office before proceeding with second stage cement job.
    - b. Second stage above DV tool: Cement should tie-back at least 200 feet into previous casing string. Operator shall provide method of verification.
  4. The minimum required fill of cement behind the 5-1/2 inch production casing is:
    - Cement should tie-back 200' into the previous casing. Operator shall provide method of verification.

### C. PRESSURE CONTROL

1. Variance approved to use flex line from BOP to choke manifold. Manufacturer's specification to be readily available. No external damage to flex line. Flex line to be installed as straight as possible (no hard bends).
2. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be **3000 (3M) psi.**
3. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the 9-5/8 intermediate casing shoe shall be **5000 (5M) psi.**
4. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the 7 intermediate casing shoe shall be **10,000 (10M) psi.**

**Variance approved to use a 5M annular. The annular must be tested to full working pressure (5000 psi.).**

## SPECIAL REQUIREMENTS

### Communitization Agreement

- The operator will submit a Communitization Agreement to the Carlsbad Field Office, 620 E Greene St. Carlsbad, New Mexico 88220, at least 90 days before the anticipated date of first production from a well subject to a spacing order issued by the New Mexico Oil Conservation Division. The Communitization Agreement will include the signatures of all working interest owners in all Federal and Indian leases subject to the Communitization Agreement (i.e., operating rights owners and lessees of record), or certification that the operator has obtained the written signatures of all such owners and will make those signatures available to the BLM immediately upon request.
- If the operator does not comply with this condition of approval, the BLM may take enforcement actions that include, but are not limited to, those specified in 43 CFR 3163.1.
- In addition, the well sign shall include the surface and bottom hole lease numbers. When the Communitization Agreement number is known, it shall also be on the sign.

## GENERAL REQUIREMENTS

The BLM is to be notified in advance for a representative to witness:

- a. Spudding well (minimum of 24 hours)
- b. Setting and/or Cementing of all casing strings (minimum of 4 hours)
- c. BOPE tests (minimum of 4 hours)

Lea County

Call the Hobbs Field Station, 414 West Taylor, Hobbs NM 88240, (575) 393-3612

1. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval.
  - a. **Operator has proposed to drill multiple wells utilizing a skid/walking rig. Operator shall secure the wellbore on the current well, after installing and testing the wellhead, by installing a blind flange of like pressure rating to the wellhead and a pressure gauge that can be monitored while drilling is performed on the other well(s).**
  - b. When the operator proposes to set surface casing with Spudder Rig
    - Notify the BLM when moving in and removing the Spudder Rig.
    - Notify the BLM when moving in the 2<sup>nd</sup> Rig. Rig to be moved in within 90 days of notification that Spudder Rig has left the location.
    - BOP/BOPE test to be conducted per Onshore Oil and Gas Order No. 2 as soon as 2nd Rig is rigged up on well.

2. Floor controls are required for 3M or Greater systems. These controls will be on the rig floor, unobstructed, readily accessible to the driller and will be operational at all times during drilling and/or completion activities. Rig floor is defined as the area immediately around the rotary table; the area immediately above the substructure on which the draw works are located, this does not include the dog house or stairway area.
3. The record of the drilling rate along with the GR/N well log run from TD to surface (horizontal well – vertical portion of hole) shall be submitted to the BLM office as well as all other logs run on the borehole 30 days from completion. If available, a digital copy of the logs is to be submitted in addition to the paper copies. The Rustler top and top and bottom of Salt are to be recorded on the Completion Report.

#### A. CASING

1. Changes to the approved APD casing program need prior approval if the items substituted are of lesser grade or different casing size or are Non-API. The Operator can exchange the components of the proposal with that of superior strength (i.e. changing from J-55 to N-80, or from 36# to 40#). Changes to the approved cement program need prior approval if the altered cement plan has less volume or strength or if the changes are substantial (i.e. Multistage tool, ECP, etc.). The initial wellhead installed on the well will remain on the well with spools used as needed.
2. Wait on cement (WOC) for Potash Areas: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi for all cement blends, 2) until cement has been in place at least 24 hours. WOC time will be recorded in the driller's log. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
3. Wait on cement (WOC) for Water Basin: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi at the shoe, 2) until cement has been in place at least 8 hours. WOC time will be recorded in the driller's log. See individual casing strings for details regarding lead cement slurry requirements. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
4. Provide compressive strengths including hours to reach required 500 pounds compressive strength prior to cementing each casing string. Have well specific cement details onsite prior to pumping the cement for each casing string.
5. No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.

6. **On that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Formation at the shoe shall be tested to a minimum of the mud weight equivalent anticipated to control the formation pressure to the next casing depth or at total depth of the well. This test shall be performed before drilling more than 20 feet of new hole.**
7. If hardband drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.
8. Whenever a casing string is cemented in the R-111-P potash area, the NMOCD requirements shall be followed.

#### B. PRESSURE CONTROL

1. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in Onshore Oil and Gas Order No. 2 and API RP 53 Sec. 17.
2. If a variance is approved for a flexible hose to be installed from the BOP to the choke manifold, the following requirements apply: The flex line must meet the requirements of API 16C. Check condition of flexible line from BOP to choke manifold, replace if exterior is damaged or if line fails test. Line to be as straight as possible with no hard bends and is to be anchored according to Manufacturer's requirements. The flexible hose can be exchanged with a hose of equal size and equal or greater pressure rating. Anchor requirements, specification sheet and hydrostatic pressure test certification matching the hose in service, to be onsite for review. These documents shall be posted in the company man's trailer and on the rig floor.
3. 5M or higher system requires an HCR valve, remote kill line and annular to match. The remote kill line is to be installed prior to testing the system and tested to stack pressure.
4. **If the operator has proposed a multi-bowl wellhead assembly in the APD. The following requirements must be met:**
  - a. **Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.**
  - b. **If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.**
  - c. **Manufacturer representative shall install the test plug for the initial BOP test.**



feet of the top of the Wolfcamp formation if the time between the setting of the intermediate casing and reaching this depth exceeds 20 days. This test does not exclude the test prior to drilling out the casing shoe as per Onshore Order No. 2.

#### C. DRILLING MUD

Mud system monitoring equipment, with derrick floor indicators and visual and audio alarms, shall be operating before drilling into the Wolfcamp formation, and shall be used until production casing is run and cemented.

#### D. WASTE MATERIAL AND FLUIDS

All waste (i.e. drilling fluids, trash, salts, chemicals, sewage, gray water, etc.) created as a result of drilling operations and completion operations shall be safely contained and disposed of properly at a waste disposal facility. No waste material or fluid shall be disposed of on the well location or surrounding area.

Porto-johns and trash containers will be on-location during fracturing operations or any other crew-intensive operations.

#### **Waste Minimization Plan (WMP)**

In the interest of resource development, submission of additional well gas capture development plan information is deferred but may be required by the BLM Authorized Officer at a later date.

**ZS 101818**

16	surface csg in a	20	inch hole.	Design Factors				SURFACE	
Segment	#/ft	Grade	Coupling	Body	Collapse	Burst	Length	Weight	
"A"	65.00	H 40	BUTT	11.22	1.36	0.64	1,010	65,650	
"B"							0	0	
w/8.4#/g mud, 30min Sfc Csg Test psig: 707				Tail Cmt	does not	circ to sfc.	Totals:	1,010	65,650
<b>Comparison of Proposed to Minimum Required Cement Volumes</b>									
Hole	Annular	1 Stage	1 Stage	Min	1 Stage	Drilling	Calc	Req'd	Min Dist
Size	Volume	Cmt Sx	CuFt Cmt	Cu Ft	% Excess	Mud Wt	MASP	BOPE	Hole-Cplg
20	0.7854	825	1593	988	61	8.80	1476	2M	1.50

Burst Frac Gradient(s) for Segment(s) A, B = , b All > 0.70, OK.

10 3/4	casing inside the	16		Design Factors				INTERMEDIATE	
Segment	#/ft	Grade	Coupling	Body	Collapse	Burst	Length	Weight	
"A"	45.50	HCL 80	BUTT	4.64	1.22	0.84	4,930	224,315	
"B"							0	0	
w/8.4#/g mud, 30min Sfc Csg Test psig:							Totals:	4,930	224,315
The cement volume(s) are intended to achieve a top of				0	ft from surface or a			1010	overlap.
Hole	Annular	1 Stage	1 Stage	Min	1 Stage	Drilling	Calc	Req'd	Min Dist
Size	Volume	Cmt Sx	CuFt Cmt	Cu Ft	% Excess	Mud Wt	MASP	BOPE	Hole-Cplg
13 1/2	0.3637	1300	2600	2094	24	10.00	3561	5M	0.88

Burst Frac Gradient(s) for Segment(s): A, B, C, D = 1.06, b, c, d All

7 5/8	casing inside the	10 3/4		Design Factors				INTERMEDIATE	
Segment	#/ft	Grade	Coupling	Joint	Collapse	Burst	Length	Weight	
"A"	29.70	HCP 110	LT&C	2.18	1.16	1.11	11,900	353,430	
"B"							0	0	
w/8.4#/g mud, 30min Sfc Csg Test psig: 1,440							Totals:	11,900	353,430
The cement volume(s) are intended to achieve a top of				4730	ft from surface or a			200	overlap.
Hole	Annular	1 Stage	1 Stage	Min	1 Stage	Drilling	Calc	Req'd	Min Dist
Size	Volume	Cmt Sx	CuFt Cmt	Cu Ft	% Excess	Mud Wt	MASP	BOPE	Hole-Cplg
9 7/8	0.2148	look	0	1553		10.00	5750	10M	0.69
Setting Depths for D V Tool(s):				6227			sum of sx	Σ CuFt	Σ%excess
% excess cmt by stage:				25	27		1130	1942	25

MASP is within 10% of 5000psig, need exrta equip?

Tail cmt										
5 1/2	casing inside the	7 5/8		Design Factors				PRODUCTION		
Segment	#/ft	Grade	Coupling	Joint	Collapse	Burst	Length	Weight		
"A"	23.00	P 110	#N/A	2.47	2.74	2.31	12,000	276,000		
"B"	23.00	P 110	#N/A	7.61	2.36	2.31	10,779	247,917		
w/8.4#/g mud, 30min Sfc Csg Test psig: 2,640							Totals:	22,779	523,917	
B Segment Design Factors would be:				49.56	2.6	if it were a vertical wellbore.				
No Pilot Hole Planned				MTD	Max VTD	Csg VD	Curve KOP	Dogleg°	Severity°	MEOC
				22779	12629	12629	12000	90	10	12896
The cement volume(s) are intended to achieve a top of				11700	ft from surface or a			200	overlap.	
Hole	Annular	1 Stage	1 Stage	Min	1 Stage	Drilling	Calc	Req'd	Min Dist	
Size	Volume	Cmt Sx	CuFt Cmt	Cu Ft	% Excess	Mud Wt	MASP	BOPE	Hole-Cplg	
6 1/2	0.0654	425	1262	735	72	13.00			0.50	

Class 'H' tail cmt yld > 1.20      Capitan Reef est top XXXX.      MASP is within 10% of 5000psig, need exrta equip?